

FCC Test Report

(Class II Permissive Change)

Product Name	Intel® Wi-Fi 6E AX211
Model No.	AX211NGW
FCC ID.	PD9AX211NG

Applicant	Intel Corporation
Address	100 Center Point Circle Suite 200 Columbia, South Carolina 29210, United States

Date of Receipt	Aug. 22, 2021
Issued Date	Oct. 08, 2021
Report No.	2180902R-RFUSBT2V01
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test Report

Issued Date: Oct. 08, 2021

Report No.: 2180902R-RFUSBT2V01




Product Name	Intel® Wi-Fi 6E AX211
Applicant	Intel Corporation
Address	100 Center Point Circle Suite 200 Columbia, South Carolina 29210, United States
Manufacturer	INTEL MOBILE COMMUNICATIONS
Model No.	AX211NGW
FCC ID.	PD9AX211NG
EUT Rated Voltage	DC 3.3V
EUT Test Voltage	DC 3.3V (Power By Test Fixture)
Trade Name	Intel
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C ANSI C63.4: 2014, ANSI C63.10: 2013
Test Result	Complied

Documented By :



(Senior Project Specialist / Genie Chang)

Tested By :



(Senior Engineer / Ivan Chuang)

Approved By :



(Senior Engineer / Alan Chen)

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	5
1.1. EUT Description.....	5
1.2. Tested System Details.....	7
1.3. Configuration of Tested System	7
1.4. EUT Exercise Software	7
1.5. Test Facility	8
1.6. List of Test Equipment.....	9
1.7. Uncertainty	10
2. PEAK POWER OUTPUT	11
2.1. Test Setup	11
2.2. Limit	11
2.3. Test Procedure	11
2.4. Test Result of Peak Power Output	12
3. RADIATED EMISSION	15
3.1. Test Setup	15
3.2. Limits.....	16
3.3. Test Procedure	17
3.4. Test Result of Radiated Emission	18
4. BAND EDGE	22
4.1. Test Setup	22
4.2. Limit	23
4.3. Test Procedure	23
4.4. Test Result of Band Edge	24
5. DUTY CYCLE	30
5.1. Test Setup	30
5.2. Test Procedure	30
5.3. Test Result of Duty Cycle.....	31
6. EMI REDUCTION METHOD DURING COMPLIANCE TESTING	34
Appendix 1: EUT Test Photographs	
Appendix 2: Product Photos: Please refer to the file: 2180902R-Product Photos	

Revision History

Report No.	Version	Description	Issued Date
2180902R-RFUSBT2V01	V1.0	Initial issue of report.	2021-10-08

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	Intel® Wi-Fi 6E AX211
Trade Name	Intel
Model No.	AX211NGW
FCC ID.	PD9AX211NG
Frequency Range	2402 – 2480MHz
Channel Number	79
Type of Modulation	FHSS: GFSK(1Mbps) / π /4DQPSK(2Mbps) / 8DPSK(3Mbps)
Antenna Type	PIFA Antenna
Channel Control	Auto
Antenna Gain	Refer to the table “Antenna List”
Power Adapter	MFR: FSP , M/N: FSP065-A1BR3 Input: AC 100-240V, 50-60Hz, 1.7A Output: DC 5V,3A 15W,9V,3A 27W, 12V,3A 36W,15V,3A 45W,20V,3.25A 65W Cable Out: Non-shielded, 1.8m Power Cord: Non-shielded, 0.9m
Contain Module	Intel / AX211NGW

Antenna List

No.	Manufacturer	Part No. (Vendor)	Antenna Type	Peak Gain
1	Auden	ANTRP5C119-1801 (Main) ANTRP5C119-1802 (Aux)	PIFA	3.36dBi in 2.4 GHz

Note: The antenna of EUT is conforming to FCC 15.203.

Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 00:	2402 MHz	Channel 20:	2422 MHz	Channel 40:	2442 MHz	Channel 60:	2462 MHz
Channel 01:	2403 MHz	Channel 21:	2423 MHz	Channel 41:	2443 MHz	Channel 61:	2463 MHz
Channel 02:	2404 MHz	Channel 22:	2424 MHz	Channel 42:	2444 MHz	Channel 62:	2464 MHz
Channel 03:	2405 MHz	Channel 23:	2425 MHz	Channel 43:	2445 MHz	Channel 63:	2465 MHz
Channel 04:	2406 MHz	Channel 24:	2426 MHz	Channel 44:	2446 MHz	Channel 64:	2466 MHz
Channel 05:	2407 MHz	Channel 25:	2427 MHz	Channel 45:	2447 MHz	Channel 65:	2467 MHz
Channel 06:	2408 MHz	Channel 26:	2428 MHz	Channel 46:	2448 MHz	Channel 66:	2468 MHz
Channel 07:	2409 MHz	Channel 27:	2429 MHz	Channel 47:	2449 MHz	Channel 67:	2469 MHz
Channel 08:	2410 MHz	Channel 28:	2430 MHz	Channel 48:	2450 MHz	Channel 68:	2470 MHz
Channel 09:	2411 MHz	Channel 29:	2431 MHz	Channel 49:	2451 MHz	Channel 69:	2471 MHz
Channel 10:	2412 MHz	Channel 30:	2432 MHz	Channel 50:	2452 MHz	Channel 70:	2472 MHz
Channel 11:	2413 MHz	Channel 31:	2433 MHz	Channel 51:	2453 MHz	Channel 71:	2473 MHz
Channel 12:	2414 MHz	Channel 32:	2434 MHz	Channel 52:	2454 MHz	Channel 72:	2474 MHz
Channel 13:	2415 MHz	Channel 33:	2435 MHz	Channel 53:	2455 MHz	Channel 73:	2475 MHz
Channel 14:	2416 MHz	Channel 34:	2436 MHz	Channel 54:	2456 MHz	Channel 74:	2476 MHz
Channel 15:	2417 MHz	Channel 35:	2437 MHz	Channel 55:	2457 MHz	Channel 75:	2477 MHz
Channel 16:	2418 MHz	Channel 36:	2438 MHz	Channel 56:	2458 MHz	Channel 76:	2478 MHz
Channel 17:	2419 MHz	Channel 37:	2439 MHz	Channel 57:	2459 MHz	Channel 77:	2479 MHz
Channel 18:	2420 MHz	Channel 38:	2440 MHz	Channel 58:	2460 MHz	Channel 78:	2480 MHz
Channel 19:	2421 MHz	Channel 39:	2441 MHz	Channel 59:	2461 MHz		

Note:

1. The EUT is an Intel® Wi-Fi 6E AX211 with built-in WLAN and Bluetooth transceiver, this report for Bluetooth.
2. These tests were conducted on a sample for the purpose of demonstrating compliance of Bluetooth transmitter with Part 15 Subpart C Paragraph 15.247 for spread spectrum devices.
3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
4. This is to request a Class II permissive change for FCC ID: PD9AX211NG, originally granted on 02/17/2021.

The major change filed under this application is:

Change #1: Additional Chassis added, Product name: Laptop ,Model number: RC57

Change #2: Reduce the Output Power through firmware, and SAR measurement were evaluated.
(Only reduce Wi-Fi Output Power, Bluetooth Output Power haven't changes).

Change #3: Addition one antennas, the antenna type is same, the antenna gain is higher than the original application.

Test Mode	Mode 1: Transmit - 1Mbps Mode 1: Transmit - 2Mbps Mode 3: Transmit - 3Mbps
-----------	--


1.2. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	Monitor	ASUS	VS229HA	F4LMQS135395	Non-shielded, 1.8m
2	External HDD	Transcend	TS1TSJ25H3B	F21786-0005	N/A
3	External HDD	Transcend	TS1TSJ25H3B	F21786-0125	N/A
4	Microphone & Earphone	Verbatim	C09024VB	N/A	N/A
5	External HDD	Transcend	TS1TSJ25MC	F30467-0011	N/A

Signal Cable Type	Signal cable Description
A HDMI Cable	Shielded, 1.8m
B USB Cable	Shielded, 0.5m
C Microphone & Earphone Cable	Non-shielded, 1.2m

1.3. Configuration of Tested System



1.4. EUT Exercise Software

1. Setup the EUT as shown in Section 1.3.
2. Execute software "DRTU Ver 22.21060.0-12219" on the EUT.
3. Configure the test mode, the test channel, and the data rate.
4. Press "OK" to start the continuous Transmit.
5. Verify that the EUT works properly.

1.5. Test Facility

Ambient conditions in the laboratory:

Performed Item	Items	Required	Actual
Radiated Emission	Temperature (°C)	10~40 °C	22.0°C
	Humidity (%RH)	10~90 %	63.0 %
Conductive	Temperature (°C)	10~40 °C	22.0 °C
	Humidity (%RH)	10~90 %	55.0%

USA : FCC Registration Number: TW0033

Canada : IC Registration Number: 26930

Site Description : Accredited by TAF
Accredited Number: 3023

Test Laboratory : DEKRA Testing and Certification Co., Ltd
Address : No. 26, Huaya 1st Rd., Guishan Dist.,
Taoyuan City 333411, Taiwan, R.O.C.
Phone number : 886-3-275-7255
Fax number : 866-3-327-5505
Email address : info.tw@dekra.com
Website : <http://www.dekra.com.tw>

1.6. List of Test Equipment

For Conduction measurements /SH1

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due. Date
	EMI Test Receiver	R&S	ESR7	102260	2020.12.28	2021.12.27
	Two-Line V-Network	R&S	ENV216	101306	2021.04.08	2022.04.07
	Two-Line V-Network	R&S	ENV216	101307	2021.05.04	2022.05.03
	Coaxial Cable	DEKRA	RG400_BNC	RF001	2021.05.24	2022.05.23

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with "X" are used to measure the final test results.
3. Test Software version : AUDIX e3 V9.

For Conducted measurements /SH2

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due. Date
X	Spectrum Analyzer	R&S	FSV30	103464	2021.03.25	2022.03.24
X	Power Meter	Anritsu	ML2496A	1548002	2021.02.24	2022.02.23
X	Power Sensor	Anritsu	MA2411B	1531023	2021.02.24	2022.02.23
X	Power Sensor	Anritsu	MA2411B	1531022	2021.02.24	2022.02.23

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with "X" are used to measure the final test results.
3. Test Software version : DEKRA Conduction Test System V9.0.5

For Radiated measurements / 966-1

	Equipment	Manufacturer	Model No.	Serial No.	Cali. Data	Due. Data
	Loop Antenna	AMETEK	HLA6121	56736	2021.04.14	2022.04.13
X	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-953	2021.01.29	2022.01.28
X	Horn Antenna	ETS-Lindgren	3117	00203799	2020.12.22	2021.12.21
	Horn Antenna	Com-Power	AH-840	101087	2021.06.16	2022.06.15
X	Pre-Amplifier	EMCI	EMC001330	980302	2021.07.06	2022.07.05
X	Pre-Amplifier	EMCI	EMC051835SE	980312	2021.02.24	2022.02.23
	Pre-Amplifier	EMCI	EMC05820SE	980361	2020.12.21	2021.12.20
X	Pre-Amplifier	EMCI	EMC184045SE	980314	2021.06.24	2022.06.23
	Filter	MICRO TRONICS	BRM50702	G251	2021.09.16	2022.09.15
X	Filter	MICRO TRONICS	BRM50716	G188	2021.09.16	2022.09.15
X	EMI Test Receiver	R&S	ESR	102793	2020.12.17	2021.12.16
X	Spectrum Analyzer	R&S	FSV3044	101114	2021.02.04	2022.02.03
X	Coaxial Cable	SGH	HA800 , SGH18	HY2105-002C	2021.03.03	2022.03.02
X	Mircoflex Cable	HUBER SUHNER	SUCOFLEX 102	MY3381/2	2021.06.25	2022.06.24

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with "X" are used to measure the final test results.
Test Software version : AUDIX e3 V9.

1.7. Uncertainty

Uncertainties have been calculated according to the DEKRA internal document, and is described in each test chapter of this report.


The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test item	Uncertainty	
Peak Power Output	± 0.91 dB	
Radiated Emission	Under 1GHz ± 4.06 dB	Above 1GHz ± 3.73 dB
Band Edge	± 2.53 dB	
Duty Cycle	± 2.31 ms	

2. Peak Power Output

2.1. Test Setup



2.2. Limit

The maximum peak power shall be less 1Watt.

2.3. Test Procedure

Tested according to FHSS test procedure of KDB 558074 section 9 (b for compliance to FCC 47CFR 15.247 requirements.

2.4. Test Result of Peak Power Output

Product : Intel® Wi-Fi 6E AX211
Test Item : Peak Power Output
Test Mode : Mode 1: Transmit - 1Mbps
Test Date : 2021/09/15

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
Channel 00	2402.00	8.99	1 Watt= 30 dBm	Pass
Channel 39	2441.00	9.26	1 Watt= 30 dBm	Pass
Channel 78	2480.00	9.66	1 Watt= 30 dBm	Pass

Product : Intel® Wi-Fi 6E AX211
Test Item : Peak Power Output
Test Mode : Mode 1: Transmit - 2Mbps
Test Date : 2021/09/15

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
Channel 00	2402.00	8.64	1 Watt= 30 dBm	Pass
Channel 39	2441.00	8.89	1 Watt= 30 dBm	Pass
Channel 78	2480.00	9.16	1 Watt= 30 dBm	Pass


Product : Intel® Wi-Fi 6E AX211
Test Item : Peak Power Output
Test Mode : Mode 3: Transmit - 3Mbps
Test Date : 2021/09/15

Channel No.	Frequency (MHz)	Measurement (dBm)	Required Limit	Result
Channel 00	2402.00	8.61	1 Watt= 30 dBm	Pass
Channel 39	2441.00	8.91	1 Watt= 30 dBm	Pass
Channel 78	2480.00	9.25	1 Watt= 30 dBm	Pass


3. Radiated Emission

3.1. Test Setup


Radiated Emission Under 30MHz



Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



3.2. Limits

➤ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

- Remarks:
1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
 2. In the Above Table, the tighter limit applies at the band edges.
 3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

3.3. Test Procedure

The EUT was setup according to ANSI C63.10, 2013 and tested compliance to FCC 47CFR 15.247 requirements.

Measuring the frequency range below 1GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1GHz, the EUT is placed on a turn table which is 1.5 meter above ground.

The turn table is rotated 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2013 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.





Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.


The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The measurement frequency range from 9kHz - 10th Harmonic of fundamental was investigated.

3.4. Test Result of Radiated Emission




Site :966-1
Condition :3m ,HORIZONTAL
Mode :TX_bt1M_2480MHz
TEST BY :Ashton Chiu



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4960.000	42.48	74.00	-31.52	45.66	-3.18	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line


Site :966-1
Condition :3m ,VERTICAL
Mode :TX_bt1M_2480MHz
TEST BY :Ashton Chiu



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4960.000	44.08	74.00	-29.92	47.26	-3.18	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line


Site :966-1
Condition :3m ,HORIZONTAL
Mode :TX_bt3M_2482MHz
TEST BY :Ashton Chiu



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4804.000	39.68	74.00	-34.32	43.15	-3.47	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line


Site :966-1
Condition :3m ,VERTICAL
Mode :TX_bt3M_2482MHz
TEST BY :Ashton Chiu



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4804.000	40.18	74.00	-33.82	43.65	-3.47	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line


Site :966-1
Condition :3m ,HORIZONTAL
Mode :TX_bt3M_2441MHz
TEST BY :Ashton Chiu



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4882.000	41.81	74.00	-32.19	45.19	-3.38	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line


Site :966-1
Condition :3m ,VERTICAL
Mode :TX_bt3M_2441MHz
TEST BY :Ashton Chiu



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4882.000	39.85	74.00	-34.15	43.23	-3.38	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line


Site :966-1
Condition :3m ,HORIZONTAL
Mode :TX_bt3M_2480MHz
TEST BY :Ashton Chiu



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4960.000	41.38	74.00	-32.62	44.56	-3.18	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line


Site :966-1
Condition :3m ,VERTICAL
Mode :TX_bt3M_2480MHz
TEST BY :Ashton Chiu



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level	dB	
1	4960.000	44.25	74.00	-29.75	47.43	-3.18	Peak

Note:
1. Level = Read Level + Factor
2. Factor = Antenna- Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line

Site :966-1
Condition :3m ,HORIZONTAL
Mode :TX_bt3M_2441MHz
TEST BY :Caster




No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level		
1	109.540	18.09	43.50	-25.41	33.07	-14.98	QP
2	249.220	22.31	46.00	-23.69	35.14	-12.83	QP
3	336.520	34.39	46.00	-11.61	44.53	-10.14	QP
4	534.400	23.87	46.00	-22.13	29.87	-6.00	QP
5	706.090	30.67	46.00	-15.33	33.62	-2.95	QP
6	910.760	29.01	46.00	-16.99	29.46	-8.45	QP

Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission under 30MHz was not included since the emission levels are very low against the limit.

Site :966-1
Condition :3m ,VERTICAL
Mode :TX_bt3M_2441MHz
TEST BY :Caster



No.	Frequency	Level	Limit	Over	Read	Factor	Remark
	MHz	dBuV/m	Line	Limit	Level		
1	45.520	30.79	40.00	-9.21	42.52	-11.73	QP
2	192.960	19.19	43.50	-24.31	33.60	-14.41	QP
3	336.520	34.32	46.00	-11.68	44.46	-10.14	QP
4	519.850	24.25	46.00	-21.75	38.37	-6.12	QP
5	653.710	36.99	46.00	-9.01	40.58	-3.59	QP
6	903.000	29.46	46.00	-16.54	30.11	-8.65	QP


Note:

1. Level = Read Level + Factor
2. Factor = Antenna Factor + Cable Loss - Preamp Factor
3. Over Limit = Level - Limit Line
4. The emission under 30MHz was not included since the emission levels are very low against the limit.


4. Band Edge

4.1. Test Setup

RF Conducted Measurement



RF Radiated Measurement:



4.2. Limit

According to FCC Section 15.247(d). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

4.3. Test Procedure

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.


Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.10: 2013 on radiated measurement.

The bandwidth setting below 1GHz and above 1GHz on the field strength meter is 120 kHz and 1MHz, respectively.

4.4. Test Result of Band Edge

Product : Intel® Wi-Fi 6E AX211
 Test Item : Band Edge
 Test Mode : Mode 1: Transmit - 1Mbps (2402MHz)
 Test Date : 2021/09/07

Peak:




Date: 7.SEP.2021 05:06:28

Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Measurement (dBm)	Margin (dB)	Limit (dBm)
00 (Average)	2342.240	-41.070	-24.731	-65.801	-24.571	-41.230
00 (Average)	2390.000	-46.330	-24.731	-71.061	-29.831	-41.230
00 (Average)	2400.000	-15.680	-24.731	-40.411	--	--
00 (Average)	2402.010	12.150	-24.731	-12.581	--	--

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor.
2. The Duty Cycle is refer to section 11.

Product : Intel® Wi-Fi 6E AX211
 Test Item : Band Edge
 Test Mode : Mode 1: Transmit - 1Mbps (2480MHz)
 Test Date : 2021/09/07

Peak:


Date: 7.SEP.2021 05:08:28

Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Measurement (dBm))	Margin (dB)	Limit (dBm)
78 (Average)	2480.030	12.620	-24.731	-12.111	--	--
78 (Average)	2483.500	-42.020	-24.731	-66.751	-25.521	-41.230
78 (Average)	2487.550	-39.000	-24.731	-63.731	-22.501	-41.230

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor.
2. The Duty Cycle is refer to section 11.

Product : Intel® Wi-Fi 6E AX211
 Test Item : Band Edge
 Test Mode : Mode 1: Transmit - 2Mbps (2402MHz)
 Test Date : 2021/09/07

Peak:


Date: 7.SEP.2021 05:09:45

Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Measurement (dBm)	Margin (dB)	Limit (dBm)
00 (Average)	2341.950	-42.010	-24.731	-66.741	-25.511	-41.230
00 (Average)	2390.000	-47.690	-24.731	-72.421	-31.191	-41.230
00 (Average)	2400.000	-9.500	-24.731	-34.231	--	--
00 (Average)	2401.870	11.330	-24.731	-13.401	--	--

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor.
2. The Duty Cycle is refer to section 11.

Product : Intel® Wi-Fi 6E AX211
 Test Item : Band Edge
 Test Mode : Mode 1: Transmit - 2Mbps (2480MHz)
 Test Date : 2021/09/07

Peak:


Date: 7.SEP.2021 05:11:03

Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Measurement (dBm))	Margin (dB)	Limit (dBm)
78 (Average)	2480.030	11.670	-24.731	-13.061	--	--
78 (Average)	2483.500	-29.140	-24.731	-53.871	-12.641	-41.230

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor.
2. The Duty Cycle is refer to section 11.

Product : Intel® Wi-Fi 6E AX211
 Test Item : Band Edge
 Test Mode : Mode 3: Transmit - 3Mbps (2402MHz)
 Test Date : 2021/09/07

Peak:


Date: 7.SEP.2021 05:13:08

Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Measurement (dBm)	Margin (dB)	Limit (dBm)
00 (Average)	2388.990	-38.300	-24.731	-63.031	-21.801	-41.230
00 (Average)	2390.000	-42.940	-24.731	-67.671	-26.441	-41.230
00 (Average)	2400.000	-9.240	-24.731	-33.971	--	--
00 (Average)	2402.010	11.420	-24.731	-13.311	--	--

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor.
2. The Duty Cycle is refer to section 11.

Product : Intel® Wi-Fi 6E AX211
 Test Item : Band Edge
 Test Mode : Mode 3: Transmit - 3Mbps (2480MHz)
 Test Date : 2021/09/07

Peak:

Date: 7.SEP.2021 05:14:12


Channel No.	Frequency (MHz)	Peak Measurement (dBm)	Duty Cycle Factor (dB)	Measurement (dBm))	Margin (dB)	Limit (dBm)
78 (Average)	2480.030	11.810	-24.731	-12.921	--	--
78 (Average)	2483.500	-29.290	-24.731	-54.021	-12.791	-41.230

Note:

1. Average Measurement=Peak Measurement + Duty Cycle Factor.
2. The Duty Cycle is refer to section 11.

5. Duty Cycle

5.1. Test Setup



5.2. Test Procedure

The EUT was setup according to ANSI C63.10 2013; tested according to ANSI C63.10 2013 for compliance to FCC 47CFR 15.247 requirements.


Product	:	Intel® Wi-Fi 6E AX211
Test Item	:	Duty Cycle
Test Mode	:	Mode 1: Transmit - 1Mbps

Date: 1.SEP.2021 08:03:12

Duty Cycle correction factor= $20 \text{ LOG } 0.058 = -24.731 \text{ dB}$

Duty Cycle correction factor	-24.731	dB
-------------------------------------	----------------	-----------

Product : Intel® Wi-Fi 6E AX211
 Test Item : Duty Cycle
 Test Mode : Mode 1: Transmit - 2Mbps



Date: 1.SEP.2021 08:04:35


Time on of 100ms=2.9ms*2=5.8ms

Duty Cycle=5.8ms / 100ms= 0.058

Duty Cycle correction factor= 20 LOG 0.058= -24.731 dB

Duty Cycle correction factor	-24.731	dB
------------------------------	---------	----

Product : Intel® Wi-Fi 6E AX211
 Test Item : Duty Cycle
 Test Mode : Mode 3: Transmit - 3Mbps



Date: 1.SEP.2021 08:05:50

Time on of 100ms=2.9ms*2=5.8ms

Duty Cycle=5.8ms / 100ms= 0.058

Duty Cycle correction factor= 20 LOG 0.058= -24.731 dB

Duty Cycle correction factor	-24.731	dB
------------------------------	---------	----

6. EMI Reduction Method During Compliance Testing

No modification was made during testing.