

**SK TECH CO., LTD.**

Page 1 of 10

## Certificate of Compliance

|                    |  |                  |               |
|--------------------|--|------------------|---------------|
| Test Report No.:   | SKTOS-01019  |                  |               |
| NVLAP CODE :       | 200220-0   |                  |               |
| Applicant:         | OJU CTN CO., LTD.  |                  |               |
| Applicant Address: | OJU CTN B/D, Sungnae-Dong, Kangdong-Gu, Seoul, Korea   |                  |               |
| Product:           | PLUS FM  |                  |               |
| FCC ID:            | PH4OMS-001   | Model No.:       | OMS-001       |
| Receipt No.:       | SKE20001221-943  | Date of receipt: | Dec. 21, 2000 |
| Date of Issue:     | Feb. 13, 2001  |                  |               |
| Testing location:  | SK TECH CO., LTD.<br>820-2, Wolmoon-Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea                     |                  |               |
| Test Standards:    | ANSI C63.4 / 1992  |                  |               |
| Rule Parts:        | FCC part 15 Subpart C  |                  |               |
| Equipment Class :  | Class B Digital Device Peripheral<br>/This Class B digital apparatus complies with Canadian ICES-003 |                  |               |
| Test Result:       | The above mentioned product has been tested and passed.  |                  |               |

Prepared by: Y.H. Kang

Tested by: K.H. Nam/Engineer

Approved by: J.Y. Hyun  
/Lab. Manager

Signature

Date

Signature

Date

Signature

Date

Other Aspects :

Abbreviations :

· OK, Pass = passed · Fail = failed · N/A = not applicable

- This test report is not permitted to copy partly without our permission.
- This test result is dependent on only equipment to be used.
- This test result is based on a single evaluation of one sample of the above mentioned.
- This test report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S Government.
- We certify that this test report has been based on the measurement standards that is traceable to the national or International standards.

NVLAP Lab. Code: 200220-0



## » » Contents « «

|  |    |
|--|----|
| Contents                                     | 2  |
| List of Tables                               | 2  |
| List of Figures                              | 2  |
| List of Photographs                          | 2  |
| 1. General                                   | 3  |
| 2. Test Site                                 | 3  |
| 2.1 Location                                 | 3  |
| 2.2 List of Test and Measurement Instruments | 4  |
| 2.3 Test Data                                | 4  |
| 2.4 Test Environment                         | 4  |
| 3. Description of the tested samples         | 5  |
| 3.1 Rating and Physical characteristics      | 5  |
| 3.2 Submitted documents                      | 5  |
| 4. Measurement conditions                    | 6  |
| 4.1 Modes of operation                       | 6  |
| 4.2 List of Peripherals                      | 6  |
| 4.3 Type of Used cables                      | 6  |
| 4.4 Test Setup                               | 6  |
| 4.5 Uncertainty                              | 6  |
| 5. Emission Test                             | 7  |
| 5.1 Conducted Emissions                      | 7  |
| 5.2 Radiated Emissions                       | 11 |

## » List of Tables

|         |  |    |
|---------|--|----|
| Table 1 | List of test and measurement equipment | 4  |
| Table 2 | Test Data, Conducted Emissions         | 10 |
| Table 3 | Test Data, Radiated Emissions          | 12 |

## » List of Figures

|          |                              |   |
|----------|------------------------------|---|
| Figure 1 | Spectral Diagram, LINE-PE    | 8 |
| Figure 2 | Spectral Diagram, Neutral-PE | 9 |



## **1. General**

This equipment has been shown to be capable of compliance with the applicable technical standards and was tested in accordance with the measurement procedures as indicated in this report.

We attest to the accuracy of data. All measurements reported herein were performed by SK Tech Co., Ltd. and were made under Chief Engineer's supervision.

We assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

## **2. Test Site**

SK TECH Co., Ltd.

### **2.1 Location**

820-2, Wolmoon Ri, Wabu-Up, Namyangju-Si, Kyunggi-Do, Korea

The test site is in compliance with ANSI C63.4/1992 for measurement of radio interference.



## 2.2 List of Test and Measurement Instruments

**Table 1 : List of Test and Measurement Equipment**

- **Radiated Emissions**

| Kind of Equipment               | Type      | S/N        | Calibrated until |
|---------------------------------|-----------|------------|------------------|
| Field Strength Meter            | ESVS 10   | 825120/013 | 04.2001          |
| Spectrum Analyzer               | R3361A    | 11730187   | 07.2001          |
| Amplifier                       | 8447F     | 3113A05153 | 05.2001          |
| Log Periodic Antenna            | UHALP9107 | 91071238   | 04.2001          |
| Biconical Antenna               | BBA9106   | N/A        | 04.2001          |
| Open Site Cable                 | N/A       | N/A        | 07.2001          |
| Antenna Mast                    | 5907      | N/A        | N/A              |
| Antenna & Turntable controller  | 5906      | 91X519     | N/A              |
| Amp & Receiver connection cable | N/A       | N/A        | 07.2001          |
| Amp & Spectrum connection cable | N/A       | N/A        | 07.2001          |
| 50Ω Switcher                    | MP59B     | M93083     | 07.2001          |

## 2.3 Test Date

Date of Application : Dec. 21, 2000

Date of Test : Feb. 06, 2001

## 2.4 Test Environment

See each test item's description.



### **3. Description of the tested samples**

The EUT is PLUS FM.

#### **3.1 Rating and Physical Characteristics**

- Input Voltage : DC 9V Battery
- Transmission Frequency : 88.2MHz, 88.4MHz, 88.6MHz, 88.8MHz
- Transmission range : less than 3m
- Dimension : 66.00 X 66.00 X 24.50mm
- Output Power : Below 250μV
- Antenna Impedance : 50 OHM

#### **3.2 Submitted Documents**

N/A



## 4. Measurement Conditions

Testing Input Voltage : DC 9V Battery

### 4.1 Modes of Operation

The EUT was in the following operation mode during all testing;

EUT is connected with MP3 CD Player by audio cable to receive audio signal from MP3 CD Player. EUT is transmitting the audio signal with four channel frequency, such as 88.2MHz, 88.4MHz, 88.6MHz, 88.8MHz.

EUT is supplied power by using DC 9V New Battery.

### 4.2 List of Peripherals

| Description   | Manufacturer                | Model Name    | Serial No. | FCC ID |
|---------------|-----------------------------|---------------|------------|--------|
| MP3 CD Player | Multichannel Labs Co., Ltd. | MJ-2000       | N/A        | N/A    |
| AC/DC Adapter | N/A                         | FE4116045D070 | N/A        | N/A    |

### 4.3 Type of Used Cables

| Description                 | Length | Type of shield | Manufacturer | Remark |
|-----------------------------|--------|----------------|--------------|--------|
| Audio cable (EUT)           | 0.3m   | Non-shield     | N/A          |        |
| Audio cable (MP3 CD Player) | 0.3m   | Non-shield     | N/A          |        |
| Adapter cable               | 1.0m   | Non-shield     | N/A          |        |



## 4.4 Test Setup

The test setup photographs showed the external supply connections and interfaces.

## 4.5 Uncertainty

### 1) Radiated disturbance

$U_c$  (Combined standard Uncertainty) =  $\pm 1.9\text{dB}$

Expanded uncertainty  $U = KU_c$

$K = 2$

$\therefore U = \pm 3.8\text{dB}$

### 2) Conducted disturbance

$U_c = \pm 0.88\text{dB}$

$U = KU_c = 2 \times U_c = \pm 1.8\text{dB}$



## 5. EMISSION Test

### 5.1 Conducted Emissions

**Result:**

**N/A**

***Measurements to demonstrate compliance with the Conducted limits are not required for devices which employ battery power for operation and which do not operate from the AC power lines.***

The line-conducted facility is located inside a 2.0M x 3.6M x 7.2M shielded enclosure.

The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 604-05.

A 1m x 1.5m wooden table 40cm. high is placed 40cm. away from the vertical wall and 1.5m away from the side wall of the shielded room. Kyoritsu Model KNW-407 (10kHz-30MHz)

50ohm/50 uH Line-Impedance Stabilization Networks(LISNs) are bonded to the shielded room.

The EUT is powered from the Kyoritsu LISN and the support equipment is powered from the Kyoritsu LISN. Power to the LISNs are filtered by a high-current high-insertion loss Lindgren enclosures power line filters (100dB 14kHz-10GHz).

The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure.

All electrical cables are shielded by braided tinned copper zipper tubing with inner diameter of 1/2".

If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the Kyoritsu LISN.

All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1-meter length.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.

The spectrum was scanned from 450kHz to 30MHz with 100msec. sweep time.

The frequency producing the maximum level was reexamined using EMI/field Intensity Meter (ESHS 10) and Quasi-Peak adapter. The detector function was set to CISPR quasi-peak mode.

The bandwidth of the receiver was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.

Each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; if applicable; whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of conducted test.

Each EME reported was calibrated using self-calibrating mode.





## 5.2 Radiated Emissions

**Result:****Pass**

Preliminary measurements were made indoors at 1 meter using broadband antennas, broadband amplifier, and spectrum analyzer to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, turntable azimuth with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 to 300 MHz using biconical antenna and from 300 to 1000 MHz using log-periodic antenna. Above 1GHz, linearly polarized double ridge horn antennas were used.

Final measurements were made outdoors at 3-meter test range using SCHWARZBECK dipole antennas. The test equipment was placed on a wooden table situated on a 4x4 meter area adjacent to the measurement area. Turntable was to protect from weather in the dome that made with FRP. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined and investigated using EMI/Field Intensity Meter(ESVS 10) and Quasi-Peak Adapter. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100kHz or 1MHz depending on the frequency or type of signal.

The half-wave dipole antenna was tuned to the frequency found during preliminary radiated measurements. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8-meter high non-metallic 1 x 1.5 meter table.

The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each EME emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation or resolution; clock or data exchange speed, and/or support equipment, if applicable; and changing the polarity of the antenna, whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of radiated emission test. Each EME reported was calibrated using self-calibrating mode.

**Table 2 : Test Data, Radiated Emissions**

| Channel | Frequency (MHz) | Pol. | Height [m] | Angle [° ] | (1) Reading (dBμV) | (2) AFCL (dB/m) | (3) Actual (dBμV/m) | (4) Limit (dBμV/m) | (5) Margin (dB) |
|---------|-----------------|------|------------|------------|--------------------|-----------------|---------------------|--------------------|-----------------|
| ※1      | 88.22           | H    | 1.0        | 132        | 23.1               | 9.6             | 32.7                | 48.0               | 15.3            |
| ※2      | 88.42           | H    | 1.0        | 130        | 24.8               | 9.6             | 34.4                | 48.0               | 13.6            |
| ※3      | 88.62           | H    | 1.1        | 41         | 26.0               | 9.9             | 35.9                | 48.0               | 12.1            |
| ※4      | 88.82           | H    | 4.0        | 49         | 26.8               | 9.9             | 36.7                | 48.0               | 11.3            |
| #4      | 177.86          | H    | 1.0        | 47         | 16.3               | 17.4            | 33.7                | 43.5               | 9.8             |

Table. Radiated Measurements at 3-meters

**※ Operating Frequency****# Harmonic Frequency**

- (a) Emissions from the intentional radiator shall be confined within a band 200kHz wide centered on the operating frequency. The 200kHz band shall lie wholly within the frequency range of 88-108MHz.
- (b) The field strength of any emissions within the permitted 200kHz band shall not exceed 250 microvolts/meter at 3 meters.

**NOTES:**

1. All modes of operation were investigated and the worst-case emission are reported.
2. All other emission are non-significant.
3. All readings are calibrated by self-mode in receiver.
4. AFCL = Antenna factor and cable loss
5. H = Horizontal, V = Vertical Polarization

**◆ Margin Calculation**

$$(5)\text{Margin} = (4)\text{Limit} - (3)\text{Actual}$$

$$[(3)\text{Actual} = (1)\text{Reading} + (2)\text{AFCL}]$$