



## TEST REPORT

Report No. : AK004503-001 Date : 2008 February 26

Application No. : LK200148(4)

Client : Mattel Asia Pacific Sourcing Limited  
13/F., South Tower, World Finance Centre,  
Harbour City, Tsim Sha Tsui,  
Kowloon, Hong Kong

Sample Description : One(1) submitted sample(s) stated to be RC 1:16 Mach 6  
of Model No. M0664  
Radio Frequency : 49.860MHz Transmitter  
Rating : 2 x 1.5V AA size batteries  
No. of submitted sample : Three (3) piece(s) \*\*\*

Date Received : 2008 January 09

Test Period : 2008 January 09 – 2008 January 21

Test Requested : FCC Part 15 Certification.


Test Method : 47 CFR Part 15 (10-1-07 Edition)  
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15  
Subpart C.

*For and on behalf of*  
CMA Industrial Development Foundation Limited

Authorized Signature : \_\_\_\_\_



Andrew Wong  
Senior Technical Officer - EL Division

FCC ID: PIYM0664-08A4T

Page 1 of 11



## **TEST REPORT**

Report No. : AK004503-001

Date : 2008 February 26

### **Table of Contents**

1	General Information .....	3
1.1	General Description .....	3
1.2	Location of the test site .....	4
1.3	List of measuring equipment.....	5
2	Description of the radiated emission test.....	6
2.1	Test Procedure.....	6
2.2	Test Result.....	6
2.3	Radiated Emission Measurement Data .....	7
3	Description of the Line-conducted Test.....	8
3.1	Test Procedure.....	8
3.2	Test Result.....	8
4	Photograph .....	9
4.1	Photographs of the Test Setup for Radiated Emission and Conducted Emission.....	9
4.2	Photographs of the External and Internal Configurations of the EUT.....	9
5	Supplementary document.....	10
5.1	Bandwidth .....	10
5.2	Duty cycle .....	10
5.3	Transmission time .....	10
5.4	Power Spectrum Density .....	10
6	Appendices.....	11



## **TEST REPORT**

Report No. : AK004503-001

Date : 2008 February 26

### **1 General Information**

#### **1.1 General Description**

The equipment under test (EUT) is a transmitter for RC 1:16 Mach 6. It operates at 49.860MHz and the oscillation of radio control is generated by a crystal. The EUT is powered by 2 x 1.5V AA size batteries. There are two control sticks in the center of EUT. If the sticks are pushed once, it will transmit a radio control signal to receiver. The antenna terminal is permanently attached in EUT and the radio output power is unable to adjust.

The brief circuit description is listed as follows:

- X1 and associated circuit act as oscillator.
- SPRC205A and associated circuit act as encoder.



## **TEST REPORT**

Report No. : AK004503-001

Date : 2008 February 26

### **1.2 Location of the test site**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.



## **TEST REPORT**

Report No. : AK004503-001

Date : 2008 February 26

### **1.3 List of measuring equipment**

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date
EMI Test Receiver	R&S	ESCI	100152	2008 October 14
Broadband Antenna	Schaffner	CBL6112B	2718	2008 May 23



## **TEST REPORT**

Report No. : AK004503-001

Date : 2008 February 26

### **2 Description of the radiated emission test**

#### **2.1 Test Procedure**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

#### **2.2 Test Result**

Peak Detector data was measured unless otherwise stated.

“#” means emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



## TEST REPORT

Report No. : AK004503-001

Date : 2008 February 26

### 2.3 Radiated Emission Measurement Data

#### Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB $\mu$ V/m)	Antenna and Cable factor (dB)	Average Factor (dB)	Field Strength (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
49.860	V	65.1	10.6	-5.8	69.8	80.0	-10.2
99.720	H	15.4	9.5	-	24.9	43.5	-18.6
149.580	H	20.3	12.0	-	32.3	43.5	-11.2
199.441	H	14.2	9.5	-	23.7	43.5	-19.8
#249.301	H	26.5	9.8	-	36.3	46.0	-9.7
299.161	H	21.4	13.9	-	35.3	46.0	-10.7
349.029	H	16.9	14.9	-	31.8	46.0	-14.2
398.881	H	18.7	14.9	-	33.6	46.0	-12.4
448.742	H	5.9	17.9	-	23.8	46.0	-22.2
498.602	H	10.7	17.9	-	28.6	46.0	-17.4



## **TEST REPORT**

Report No. : AK004503-001

Date : 2008 February 26

### **3 Description of the Line-conducted Test**

#### **3.1 Test Procedure**

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

#### **3.2 Test Result**

No measurement is required as the EUT is a battery-operated product.



## **TEST REPORT**

Report No. : AK004503-001

Date : 2008 February 26

### **4 Photograph**

#### **4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission**

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg.

#### **4.2 Photographs of the External and Internal Configurations of the EUT**

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



## TEST REPORT

Report No. : AK004503-001

Date : 2008 February 26

### 5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

#### 5.1 Bandwidth

The plot saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10kHz above and below the band edges (49.81 and 49.91MHz) is at least 26dB below the carrier level. It meets the requirement of Section 15.235(b).

#### 5.2 Duty cycle

The duty cycle is simply the on-time divided by the period:

$$\begin{aligned} \text{The duration of one cycle} &= 31.8\text{ms} \\ \text{Effective period of the cycle} &= (0.952 \times 8)\text{ms} + (0.472 \times 18)\text{ms} \\ &= 16.112\text{ms} \\ \text{Duty Cycle} &= 16.112 / 31.8 \\ &= 0.506 \end{aligned}$$

Therefore, the average factor is found by  $20 \log_{10} 0.506 = -5.9\text{dB}$

#### 5.3 Transmission time

Not Applicable

#### 5.4 Power Spectrum Density

Not Applicable



## TEST REPORT

Report No. : AK004503-001

Date : 2008 February 26

### 6 Appendices

A1.	Photos of the set-up of Radiated Emissions	2	pages
A2.	Photos of External Configurations	2	pages
A3.	Photos of Internal Configurations	2	pages
A4.	ID Label/Location	2	pages
A5.	Bandwidth Plot	1	page
A6.	Average Factor	2	pages
A7.	Block Diagram	1	page
A8.	Schematics Diagram	1	page
A9.	User Manual	4	pages
A10.	Operation Description	1	page

\*\*\*\*\* End of Report \*\*\*\*\*