



Flom Test Labs
EMI, EMC, RF Testing Experts Since 1963

toll-free: (866)311-3268
fax: (480)926-3598
<http://www.flomlabs.com>
info@flomlabs.com

Date: July 27, 2007

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Novatel Wireless Inc.
Equipment: PKRNVWE725 Collocated with QDS-BRCM1022 802.11.a,b,g
FCC ID: PKRNVWE725
FCC Rules: Radio Frequency Radiation Exposure Limits
47 CFR 1.1310
MPE - Mobiles Fixed Based Station

Gentlemen:

On behalf of the Applicant, enclosed please find the Supplemental Test Data Report, the whole for Environmental Assessment (MPE) of the referenced equipment as shown.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

Hoosamuddin S. Bandukwala, Lab Director

enclosure(s)
cc: Applicant
HSB/jhe

Flom Test Labs
3356 N. San Marcos Place, Suite 107
Chandler, Arizona 85225-7176
(866) 311-3268 phone, (480) 926-3598 fax

p0770006, d0770022

Environmental Assessment

for

Mobiles

for

FCC ID: FCC ID: PKRNVWE725

Model:PKRNVWE725

to

Federal Communications Commission

47 CFR 1.1310 (MPE)

Radio Frequency Radiation Exposure Limits


Date Of Report: July 27, 2007

On the Behalf of the Applicant: Novatel Wireless Inc.

At the Request of: Novatel Wireless Inc.
9645 Scranton Rd, Suite 205
San Diego, CA 92121

Attention of: John Spall, Project Manager
Ph: 858-812-0697 Fax: 858-450-7183
Email: jspall@nvtl.com

Supervised By:



Hoosamuddin S. Bandukwala, Lab Director

Table of Contents

| Rule | Description | Page |
|--------|--|------|
| | Test Report | 1 |
| | Identification of the Equipment Under Test | 2 |
| | Standard Test Conditions and Engineering Practices | 3 |
| 1.1310 | Environmental Assessment | 4 |

Required information per ISO 17025-2005, paragraph 5.0:

a)

Test Report (Supplemental)

b) Laboratory:
(FCC: 31040/SIT)
(Canada: IC 2044)

Flom Test Labs
3356 N. San Marcos Place, Suite 107
Chandler, AZ 85225

c) Report Number:

d0770022

d) Client:

Novatel Wireless Inc.
9645 Scranton Rd, Suite 205
San Diego, CA 92121

e) Identification:

PKRNVWE725
FCC ID: PKRNVWE725

Description:

Dell laptop models Inspiron 1526, Inspiron 1525, and XPS M1530

f) EUT Condition:

Not required unless specified in individual tests.

g) Report Date:

July 27, 2007

h, j, k):

As indicated in individual tests.


i) Sampling method:

No sampling procedure used.

l) Uncertainty:

In accordance with MFA internal quality manual.

m) Supervised by:



Hoosamuddin S. Bandukwala, Lab Director

n) Results:

The results presented in this report relate only to the item tested.

o) Reproduction:

This report must not be reproduced, except in full, without written permission from this laboratory.

Identification of the Equipment Under Test (EUT)

| | |
|---------------------------------------|---|
| Name and Address of Applicant: | Novatel Wireless Inc. 9645 Scranton Rd, Suite 205 San Diego, CA 92121 |
| Manufacturer: | Novatel Wireless Inc. 9645 Scranton Rd, Suite 205 San Diego, CA 92121 |
| FCC ID: | PKRNVWE725 |
| Model Number: | PKRNVWE725 |
| Description: | Dell laptop models Inspiron 1526, Inspiron 1525, and XPS M1530 |
| Type of Emission: | CDMA collocated with 802.11. a,b,g |
| Frequency Range, MHz: | CDMA 824 - 848 and 1851 - 1908 802.11.a,b,g 2412 – 2462 and 5745 - 5825 |
| Power Rating, Watts: | 0.296 <input type="checkbox"/> Switchable <input type="checkbox"/> Variable <input checked="" type="checkbox"/> N/A |
| Modulation: | <input type="checkbox"/> AMPS <input type="checkbox"/> TDMA <input checked="" type="checkbox"/> CDMA <input checked="" type="checkbox"/> OTHER |
| Antenna: | <input type="checkbox"/> Helical <input type="checkbox"/> Monopole <input type="checkbox"/> Whip <input checked="" type="checkbox"/> Other |

Note: For RF Safety test antenna gain taken at the upper range of expected gain (i.e. 0 dBd) and RF Power set to highest nominal power across all channels.

Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-2004, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.

A2LA

"A2LA has accredited Flom Test Labs, Inc. Chandler, AZ for technical competence in the field of Electrical testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO 17025:2005 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing."

Please refer to www.a2la.org for current scope of accreditation.

Certificate number: 2152.01



| | | |
|---|---|---|
| Name of Test: | Environmental Assessment | |
| Specification: | FCC: 47 CFR 1.1310 | |
| Measurement Guide: | ANSI/IEEE C95.1 1992 | |
| Name of Test: | R.F. Radiation Exposure | |
| FCC Rules: | 1.1307, 1.1310, 1.1311, 2.1091 | |
| Description, EUT: | See page 2 of Test Report | |
| Limits: Uncontrolled Exposure 47 CFR 1.1310 Table 1, (B) | 0.3-1.234 MHz: 1.34-30 MHz: 30-300 MHz: 300-1500 MHz: 1500-100,000 MHz: | Limit [mW/cm^2] = 100 Limit [mW/cm^2] = $(180/f^2)$ Limit [mW/cm^2] = 0.2 Limit [mW/cm^2] = $f/1500$ Limit [mW/cm^2] = 1.0 |
| Test Frequencies, MHz Power, Conducted, mW Antenna Gain Antenna Model Distance cm | 824 – 848 = 291 = 3 dBi Planer Inverted F Antenna 20 | |
| Limit Calculations | Limit _[mW/cm²] = 0.549 | |
| Test Frequencies, MHz Power, Conducted, mW Antenna Gain Antenna Model Distance cm | 1851 - 1908 = 296 = 3 dBi Planer Inverted F Antenna 20 | |
| Limit Calculations | Limit _[mW/cm²] = 1.0 | |

PKRNVWE725 CDMA

| CDMA Frequency MHz | TX Power (m)W | Power Density (mW/cm ²) | Limit (mW/cm ²) | Result |
|-----------------------|------------------|--|--------------------------------|--------|
| 824 – 848 | 291 | 0.116 | 0.549 | Pass |
| 1851 - 1908 | 296 | 0.117 | 1.0 | Pass |


QDS-BRCM1022 802.11.a,b,g

| 802.11 a,b,g Frequency MHz | TX Power (mW) | Power Density (mW/cm ²) | Limit (mW/cm ²) | Result |
|-------------------------------|------------------|--|--------------------------------|--------|
| 2412 – 2462 | 489 | 0.195 | 1.0 | Pass |
| 5745 - 5825 | 406 | 0.162 | 1.0 | Pass |

PKRNVWE725 CDMA Collocated with QDS-BRCM1022 802.11.a,b,g

| CDMA Frequency MHz | 802.11.a,b,g Frequency MHz | CDMA Power Density (mW/cm ²) | 802.11.a,b,g Power Density (mW/cm ²) | Total Power Density (mW/cm ²) | Limit (mW/cm ²) | Result |
|-----------------------|----------------------------------|---|---|--|--------------------------------|--------|
| 824 – 848 | 2412 – 2462 | 0.116 | 0.195 | 0.311 | 0.549 | Pass |
| 824 – 848 | 5745 - 5825 | 0.116 | 0.162 | 0.278 | 0.549 | Pass |
| 1851 - 1908 | 2412 – 2462 | 0.117 | 0.195 | 0.312 | 1.0 | Pass |
| 1851 - 1908 | 5745 - 5825 | 0.117 | 0.162 | 0.279 | 1.0 | Pass |

End of Test Report



Supervised By:


Hoosamuddin S. Bandukwala, Lab Director

**Testimonial
and
Statement of Certification**

This is to certify that:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Certifying Engineer:



Hoosamuddin S. Bandukwala, Lab Director