

**MPE CALCULATION**  
**FCC ID: POJDMLWAN915**

RF Exposure Requirements: 47 CFR §1.1307(b)  
 RF Radiation Exposure Limits: 47 CFR §1.1310  
 RF Radiation Exposure Guidelines: FCC OST/OET Bulletin Number 65  
 EUT Frequency Band: 900MHz 902.3-914.9 MHz  
 Limits for General Population/Uncontrolled Exposure in the band of: 300 -1,500 MHz  
 Power Density Limit: f/1500 mW / cm<sup>2</sup>

Equation:  $S = PG / 4\pi R^2$  or  $R = \sqrt{PG / 4\pi S}$   
 Where, S = Power Density  
 P = Power Input to Antenna  
 G = Antenna Gain  
 R = distance to the center of radiated antenna

**EUT: DM-LWAN-915**

**Host: Guppy LWAN 915**

(900MHz Radio): Power = 18.73 dBm, Power density = 0.014 mW/ cm<sup>2</sup>

Type	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Tune-Up Tolerance	Tolerance Max Power (dBm)	Measurement Distance (cm)	Calculated MPE (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Pass/Fail
900MHz	902.3	18.73	-1	±1dB	19.73	20	0.014	0.60	Pass

The Above Result had shown that the Device complied with MPE requirement.

*Gary Chou*

Completed By: Gary Chou

SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: 02/21/2019