

Report No.: SHEM200200116802

Page: 1 of 7

## 1 Cover Page

RF Exposure REPORT

Application No.: SHEM2002001168CR

**FCC ID:** POTGIV100 **IC:** 4773A-GIV100

**Applicant:** Inventec Appliances Corp.

Address of Applicant:

No.37, Wugong 5thRoad, New Taipei industrial Park, Wugu District, New

Taipei City, Taiwan, R.O.C.

**Factory:** Inventec Appliances(Pudong)Corporation Address of Factory: No.789 Pu Xing Road,Shanghai,PRC

**Equipment Under Test (EUT):** 

**EUT Name:** Smart Audio Bar

Model No.: GIV10L Trade mark: Lenovo

FCC Rules 47 CFR §2.1091

Standard(s): KDB447498 D01 General RF Exposure Guidance v06

RSS-102 Issue 5 (March 2015)

**Date of Receipt:** 2020-07-11

**Date of Test:** 2020-07-31 to 2020-08-17

**Date of Issue:** 2020-08-19

Test Result: Pass\*

rarlan Zhan

Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@egs.com

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM200200116802

Page: 2 of 7

Revision Record				
Version	Description	Date	Remark	
00	Original	2020-08-19	1	

Authorized for issue by:		
	Michael Mil	
	Micheal Niu / Project Engineer	
	Parlam zhan	
	Parlam Zhan / Reviewer	



Report No.: SHEM200200116802

Page: 3 of 7

### 2 Contents

		F	Page
1	COV	/ER PAGE	1
2	CON	NTENTS	3
3	GEN	NERAL INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T.	4
	3.2	DETAILS OF E.U.T.	4
	3.3	TEST LOCATION	5
	3.4	TEST FACILITY	5
4	TES	T STANDARDS AND LIMITS	6
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
	4.2	IC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
5	MEA	ASUREMENT AND CALCULATION	7
	5.1	MAXIMUM TRANSMIT POWER	7
	5.2	MPE CALCULATION	7



Report No.: SHEM200200116802

Page: 4 of 7

## 3 General Information

## 3.1 General Description of E.U.T.

Power supply:	DC 54V/1.76A by Adapter or IEEE802.3bt POE Adapter
Serial Number:	GVKIAC2070018
Firmware Version:	FW V0.3.5

### 3.2 Details of E.U.T.

Antenna Gain:	1.56dBi
Antenna Type:	Chip Antenna
Bluetooth Version:	V4.2 LE
Channel Spacing:	2MHz
Modulation Type:	GFSK
Data rate:	1Mbps
Number of Channels:	40
Operation Frequency:	2402MHz to 2480MHz



Report No.: SHEM200200116802

Page: 5 of 7

#### 3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weive Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

### 3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • CNAS (No. CNAS L4354)

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

#### A2LA (Certificate No. 2541.01)

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

#### FCC (Designation Number: CN1172)

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

#### • ISED (CAB identifier: CN0072)

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

CAB Identifier: CN0072.
• VCCI (Member No.: 1938)

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-10216 respectively.



Report No.: SHEM200200116802

Page: 6 of 7

### 4 Test Standards and Limits

### 4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm²)	Averaging time(minutes)	
300MHz~1.5GHz	f/1500	30	
1.5GHz~100GHz	1.0	30	

## 4.2 IC Radiofrequency radiation exposure limits:

According to RSS-102 section 2.5.2, RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);

- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

For 2.4G device, the limit of worse case is 2.68 W



Report No.: SHEM200200116802

Page: 7 of 7

### 5 Measurement and Calculation

### 5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM200200116801

#### **Test Data:**

Test Mode	Test Channel	Power[dBm]	Peak Power (mW)
BLE	2402	0.67	1.17
BLE	2440	0.08	1.02
BLE	2480	0.54	1.13

#### 5.2 MPE Calculation

For FCC:

According to the formula  $S=P/4\pi R^2$ , we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in meter) = 20cm
- 3) MPE limit = 1mW/cm<sup>2</sup>

The max. antenna gain is

1.56 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm²)	Limit (mW/cm <sup>2</sup> )	Result
1.17	1.432	20	0.00033	1	Pass

For IC:

E.I.R.P.=P\*G=0.00117x 1.432=0.0017W<2.68W

So the device is exclusion from SAR test.

-- End of the Report--