

Section 8. Host PC labeling

<E-label screen>

To access the E-label screen, do one of the following:

- Restart the computer. When the logo screen is displayed, press F9. The E-label screen is displayed.
- Restart the computer. When the logo screen is displayed, press Enter or tap the prompt to enter the Startup Interrupt menu. Then press F9 or tap the Regulatory Information option. The E-label screen is displayed.

Lenovo Regulatory Information

     

CAN ICES-3(B)/NMB-3(B)

ご使用のコンピュータにIEEE802.11a準拠の無線機が搭載されている場合は、電波法の規定により5.15-5.35GHz周波数帯での使用は屋内に限られます。

This product contains a lithium-ion battery and a lithium battery; dispose of according to local, state, or federal laws.

Copyrighted code and parts contained herein.
© Copyright Lenovo 2005, 2018.

M/N: TP00107A
FCC ID: PU5-TP00107A, IC: 4182A-TP00107A
Contains FCC ID: PD99560D2, IC: 1000M-9560D2
Contains FCC ID: MCLT77H747, IC: 2878D-T77T747

R-R-LVK-TP00107A
MSIP-CRM-FOB-L850-GL
MSIP-CRM-INT-9560D2W
MSIP-CRM-FOX-T77H747

TA-2016/3502
TA-2016/2773
TA-2016/2877
APPROVED

XXX-XXXXXX
XXXXXXXXXX

003-170244
D170150003

MIC/KS 総務省指定
第AC-1607号

Press **Enter** to exit and restart your computer