

LOW CHANNEL

FCC RADIATED EMISSIONS DATA

CLIENT: IKUSI
EUT: TM60 TX
CPU:
CLOCK: 430.10 MHz
MODE: TRANSMIT

3 METER TEST Peak Level

DATE: 10/10/2001

FREQUENCY MHz	POLARITY		SPEC A dBuV	AF/C dB/m	AMP Gain dB	Average Factor dB	PEAK E-Field dbuV/m	AVERAGE Limit dBuV/m	MARGIN dB	CONDITION
	Ant.	EUT								
430.10	V	Y	59.00	17.00	0.00	0.00	76.00	81.00	5.00	PASS
860.20	H	Z	60.00	24.00	30.00	0.00	54.00	61.00	7.00	PASS
1,290.30	V	Y	52.00	26.00	30.00	0.00	48.00	54.00	6.00	PASS
1,720.40	V	Y	54.00	29.00	30.00	0.00	53.00	61.00	8.00	PASS
2,150.50	H	X	48.00	32.00	30.00	0.00	50.00	61.00	11.00	PASS
2,580.60	H	Z	42.00	33.00	30.00	0.00	45.00	61.00	16.00	PASS
3,010.70	H	X	40.00	36.00	30.00	0.00	46.00	61.00	15.00	PASS
3,440.80	V	Y	40.00	36.00	30.00	0.00	46.00	61.00	15.00	PASS
3,870.90	H	X	36.00	37.00	30.00	0.00	43.00	54.00	11.00	PASS
4,301.00	V	Z	32.00	38.00	30.00	0.00	40.00	54.00	14.00	PASS

HIGH CHANNEL

FCC RADIATED EMISSIONS DATA

CLIENT: IKUSI
EUT: TM60 TX
CPU:
CLOCK 439.90 MHz
MODE: TRANSMIT

3 METER TEST Peak Level

DATE: 10/10/2001

FREQUENCY MHz	POLARITY		SPEC A dBuV	AF/C dB/m	AMP Gain dB	Average Factor dB	PEAK E-Field dbuV/m	AVERAGE Limit dBuV/m	MARGIN dB	CONDITION
	Ant.	EUT								
439.90	V	Y	60.00	17.00	0.00	0.00	77.00	81.00	4.00	PASS
879.80	H	Z	58.00	24.00	30.00	0.00	52.00	61.00	9.00	PASS
1,319.70	V	Y	53.00	26.00	30.00	0.00	49.00	54.00	5.00	PASS
1,759.60	V	Y	52.00	29.00	30.00	0.00	51.00	61.00	10.00	PASS
2,199.50	H	X	47.00	32.00	30.00	0.00	49.00	61.00	12.00	PASS
2,639.40	H	Z	40.00	33.00	30.00	0.00	43.00	61.00	18.00	PASS
3,079.30	H	X	39.00	36.00	30.00	0.00	45.00	61.00	16.00	PASS
3,519.20	V	Y	39.00	36.00	30.00	0.00	45.00	61.00	16.00	PASS
3,959.10	H	X	35.00	37.00	30.00	0.00	42.00	54.00	12.00	PASS
4,399.00	V	Z	31.00	38.00	30.00	0.00	39.00	54.00	15.00	PASS