



FCC RADIO TEST REPORT

FCC ID : PY7-04606A
Equipment : GSM/WCDMA/LTE Phone+Bluetooth,
DTS/UNII a/b/g/n/ac and NFC
Brand Name : Sony
Applicant : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Manufacturer : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Standard : FCC Part 15 Subpart C §15.247

The product was received on Mar. 25, 2018 and testing was started from Apr. 03, 2018 and completed on Apr. 26, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report	3
Summary of Test Result	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards	6
2 Test Configuration of Equipment Under Test.....	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System	8
2.4 Support Unit used in test configuration and system.....	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example	9
3 Test Result.....	10
3.1 6dB and 99% Bandwidth Measurement.....	10
3.2 Output Power Measurement	12
3.3 Power Spectral Density Measurement.....	13
3.4 Conducted Band Edges and Spurious Emission Measurement	15
3.5 Radiated Band Edges and Spurious Emission Measurement	25
3.6 AC Conducted Emission Measurement	29
3.7 Antenna Requirements.....	31
4 List of Measuring Equipment	32
5 Uncertainty of Evaluation.....	34
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	



History of this test report

Report No.	Version	Description	Issued Date
FR832501-01C	01	Initial issue of report	May 29, 2018
FR832501-01C	02	Revising the test procedures description of output power in section 3.2.3.	Jun. 29, 2018

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Bandwidth	Pass	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 8.80 dB at 68.340 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 19.09 dB at 0.643 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Reviewed by: Joseph Lin

Report Producer: Maggie Chiang

1 General Description

1.1 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII a/b/g/n/ac, FM Receiver, NFC, and GNSS

Standards-related Product Specification	
Antenna Type / Gain	C-feed Antenna type with gain -4.60 dBi

EUT Information List			
HW Version	SW Version	S/N	Performed Test Item
A	9.29	CQ3000NYWW	RF conducted measurement
		CQ3000NYWV	Radiated Spurious Emission
		CQ3000PSRK	Conducted Emission

Accessory List	
AC Adapter	Model No. : UCH20
	S/N :
	3515W45302499 (for radiated spurious emission) 3515W45302520 (for conducted emission)
Earphone	Model No. : MH410c
	S/N: N/A
USB Cable	Model No. : UCB20
	S/N : N/A

Note:

1. Above EUT list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test, and the serial number of each type of accessories is listed in each section of this report. .
3. For other wireless features of this EUT, test report will be issued separately.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH12-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Test Mode


Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0


Test Cases	
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN (2.4GHz) Link + Earphone + Battery + USB Cable (Charging from Adapter)

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emissions Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony	SBH20	PY7-RD0010	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Notebook	Lenovo	E335	N/A	N/A	N/A
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

For RF test items, an engineering test program was provided and enabled to make EUT transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Peak Power, the testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.3 PKPM1 Peak power meter method.
2. For Average Power, the testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.2.3.1 Method AVGPM.
3. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures


1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Engineer :	Shiang Wang and Tommy Lee	Temperature :	21~25°C
		Relative Humidity :	51~54%


Test Mode :	802.11b	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11b	Test Channel :	06
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 18.APR.2018 10:58:09

Channel Plot




Spurious Emission 30MHz~3GHz



Date: 18.APR.2018 10:59:44

Spurious Emission 2GHz~25GHz




Date: 18.APR.2018 11:00:16



Test Mode : 802.11b


Test Channel : 11

100kHz PSD reference Level




Date: 18.APR.2018 11:10:31

Channel Plot




Date: 18.APR.2018 11:11:52

Spurious Emission 30MHz~3GHz



Date: 18.APR.2018 11:13:16


Spurious Emission 2GHz~25GHz



Date: 18.APR.2018 11:14:08




Test Mode :	802.11g	Test Channel :	01
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	06
-------------	---------	----------------	----






Test Mode :	802.11g	Test Channel :	11
-------------	---------	----------------	----

100kHz PSD reference Level




Date: 18.APR.2018 11:41:22

Channel Plot




Date: 18.APR.2018 11:43:45

Spurious Emission 30MHz~3GHz



Date: 18.APR.2018 11:45:59

Spurious Emission 2GHz~25GHz




Date: 18.APR.2018 11:46:55



Test Mode : 802.11n HT20


Test Channel : 01

100kHz PSD reference Level




Date: 18.APR.2018 11:56:00

Channel Plot




Date: 18.APR.2018 11:57:23

Spurious Emission 30MHz~3GHz



Date: 18.APR.2018 11:57:58


Spurious Emission 2GHz~25GHz



Date: 18.APR.2018 11:58:45




Test Mode :	802.11n HT20	Test Channel :	06
-------------	--------------	----------------	----






Test Mode :	802.11n HT20	Test Channel :	11
-------------	--------------	----------------	----

100kHz PSD reference Level




Date: 18.APR.2018 14:11:45

Channel Plot




Date: 18.APR.2018 14:14:25

Spurious Emission 30MHz~3GHz



Date: 18.APR.2018 14:15:53

Spurious Emission 2GHz~25GHz



Date: 18.APR.2018 14:16:19

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1218006	N/A	Oct. 06, 2017	Apr. 03, 2018~ Apr. 18, 2018	Oct. 05, 2018	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1207363	300MHz~40GHz	Oct. 06, 2017	Apr. 03, 2018~ Apr. 18, 2018	Oct. 05, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2017	Apr. 03, 2018~ Apr. 18, 2018	Nov. 20, 2018	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1300484	N/A	Mar. 01, 2018	Apr. 03, 2018~ Apr. 18, 2018	Feb. 28, 2019	Conducted (TH05-HY)
Hygrometer	TECPEL	HTC-1	2	N/A	Mar. 06, 2018	Apr. 03, 2018~ Apr. 18, 2018	Mar. 05, 2019	Conducted (TH05-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY84209521	1GHz~26GHz	Dec. 01, 2017	Apr. 03, 2018~ Apr. 18, 2018	Nov. 30, 2018	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Apr. 17, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	3.6GHz	Dec. 08, 2017	Apr. 17, 2018	Dec. 07, 2018	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	May 02, 2017	Apr. 17, 2018	May 01, 2018	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Apr. 17, 2018	Nov. 29, 2018	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Apr. 17, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Test Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Apr. 17, 2018	N/A	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Apr. 17, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Apr. 23, 2018~ Apr. 26, 2018	Nov. 22, 2018	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-06	35414&AT-N0 602	30MHz~1GHz	Oct. 14, 2017	Apr. 23, 2018~ Apr. 26, 2018	Oct. 13, 2018	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Oct. 20, 2017	Apr. 23, 2018~ Apr. 26, 2018	Oct. 19, 2018	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz ~ 40GHz	Nov. 27, 2017	Apr. 23, 2018~ Apr. 26, 2018	Nov. 26, 2018	Radiation (03CH12-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200485	10Hz ~ 44GHz	Oct. 31, 2017	Apr. 23, 2018~ Apr. 26, 2018	Oct. 30, 2018	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100390	20Hz~26.5GHz	Dec. 25, 2017	Apr. 23, 2018~ Apr. 26, 2018	Dec. 24, 2018	Radiation (03CH12-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 26, 2018	Apr. 23, 2018~ Apr. 26, 2018	Mar. 25, 2019	Radiation (03CH12-HY)
Preamplifier	Jet-Power	JPA0118-55-30 3K	171000180005 4002	1GHz~18GHz	Apr. 17, 2018	Apr. 23, 2018~ Apr. 26, 2018	Apr. 16, 2019	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY53270148	1GHz~26.5GHz	Jan. 15, 2018	Apr. 23, 2018~ Apr. 26, 2018	Jan. 14, 2019	Radiation (03CH12-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Apr. 23, 2018~ Apr. 26, 2018	Jul. 17, 2018	Radiation (03CH12-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTM-303B	TP140320	N/A	Nov. 13, 2017	Apr. 23, 2018~ Apr. 26, 2018	Nov. 12, 2018	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0058/126E	30M-18G	Mar. 14, 2018	Apr. 23, 2018~ Apr. 26, 2018	Mar. 13, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY15539/4	30M-18G	Mar. 14, 2018	Apr. 23, 2018~ Apr. 26, 2018	Mar. 13, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY36979/4	30M-18G	Mar. 14, 2018	Apr. 23, 2018~ Apr. 26, 2018	Mar. 13, 2019	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	505134/2	30M-40GHz	Oct. 17, 2017	Apr. 23, 2018~ Apr. 26, 2018	Oct. 16, 2018	Radiation (03CH12-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	800740/2	30M-40GHz	Oct. 17, 2017	Apr. 23, 2018~ Apr. 26, 2018	Oct. 16, 2018	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-2700 -3000-18000-6 0ST	SN2	3 GHz Highpass	Jul. 17, 2017	Apr. 23, 2018~ Apr. 26, 2018	Jul. 16, 2018	Radiation (03CH12-HY)
Filter	Wainwright	WLKS1200-12 SS	SN2	1.2G Low Pass	Jul. 17, 2017	Apr. 23, 2018~ Apr. 26, 2018	Jul. 16, 2018	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Apr. 23, 2018~ Apr. 26, 2018	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Apr. 23, 2018~ Apr. 26, 2018	N/A	Radiation (03CH12-HY)
Test Software	Audix	E3 6.2009-8-24	RK-000989	N/A	N/A	Apr. 23, 2018~ Apr. 26, 2018	N/A	Radiation (03CH12-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.70
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.10
---	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20
---	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.70
---	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Shiang Wang / Tommy Lee	Temperature:	21~25	°C
Test Date:	2018/4/3~2018/4/18	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	1	1	2412	12.85	-	7.08	-	0.50	Pass
11b	1Mbps	1	6	2437	13.80	-	7.08	-	0.50	Pass
11b	1Mbps	1	11	2462	13.45	-	7.56	-	0.50	Pass
11g	6Mbps	1	1	2412	17.80	-	15.92	-	0.50	Pass
11g	6Mbps	1	6	2437	17.85	-	15.80	-	0.50	Pass
11g	6Mbps	1	11	2462	17.70	-	15.48	-	0.50	Pass
HT20	MCS0	1	1	2412	18.75	-	16.44	-	0.50	Pass
HT20	MCS0	1	6	2437	18.60	-	15.72	-	0.50	Pass
HT20	MCS0	1	11	2462	18.75	-	15.96	-	0.50	Pass

TEST RESULTS DATA
Peak Output Power

2.4GHz Band																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	22.01	-	-	30.00	-	-4.60	-	17.41	-	36.00	-	Pass
11b	1Mbps	1	6	2437	21.48	-	-	30.00	-	-4.60	-	16.88	-	36.00	-	Pass
11b	1Mbps	1	11	2462	21.83	-	-	30.00	-	-4.60	-	17.23	-	36.00	-	Pass
11g	6Mbps	1	1	2412	21.65	-	-	30.00	-	-4.60	-	17.05	-	36.00	-	Pass
11g	6Mbps	1	6	2437	21.00	-	-	30.00	-	-4.60	-	16.40	-	36.00	-	Pass
11g	6Mbps	1	11	2462	21.45	-	-	30.00	-	-4.60	-	16.85	-	36.00	-	Pass
HT20	MCS0	1	1	2412	18.35	-	-	30.00	-	-4.60	-	13.75	-	36.00	-	Pass
HT20	MCS0	1	6	2437	18.42	-	-	30.00	-	-4.60	-	13.82	-	36.00	-	Pass
HT20	MCS0	1	11	2462	18.53	-	-	30.00	-	-4.60	-	13.93	-	36.00	-	Pass
VHT20	MCS0	1	1	2412	18.32	-	-	30.00	-	-4.60	-	13.72	-	36.00	-	Pass
VHT20	MCS0	1	6	2437	18.41	-	-	30.00	-	-4.60	-	13.81	-	36.00	-	Pass
VHT20	MCS0	1	11	2462	18.52	-	-	30.00	-	-4.60	-	13.92	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Average Output Power

2.4GHz Band									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)		
					Ant 1	Ant 2	Ant 1	Ant 2	SUM
11b	1Mbps	1	1	2412	0.00	-	19.30	-	-
11b	1Mbps	1	6	2437	0.00	-	19.10	-	
11b	1Mbps	1	11	2462	0.00	-	19.26	-	
11g	6Mbps	1	1	2412	0.25	-	16.99	-	
11g	6Mbps	1	6	2437	0.25	-	16.75	-	
11g	6Mbps	1	11	2462	0.25	-	16.93	-	
HT20	MCS0	1	1	2412	0.31	-	13.70	-	
HT20	MCS0	1	6	2437	0.31	-	13.91	-	
HT20	MCS0	1	11	2462	0.31	-	13.83	-	
VHT20	MCS0	1	1	2412	0.27	-	13.58	-	
VHT20	MCS0	1	6	2437	0.27	-	13.84	-	
VHT20	MCS0	1	11	2462	0.27	-	13.78	-	

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	-2.01	-	-	-4.60	-	8.00	-	Pass
11b	1Mbps	1	6	2437	-3.69	-	-	-4.60	-	8.00	-	Pass
11b	1Mbps	1	11	2462	-2.66	-	-	-4.60	-	8.00	-	Pass
11g	6Mbps	1	1	2412	-7.65	-	-	-4.60	-	8.00	-	Pass
11g	6Mbps	1	6	2437	-8.43	-	-	-4.60	-	8.00	-	Pass
11g	6Mbps	1	11	2462	-7.77	-	-	-4.60	-	8.00	-	Pass
HT20	MCS0	1	1	2412	-12.09	-	-	-4.60	-	8.00	-	Pass
HT20	MCS0	1	6	2437	-12.07	-	-	-4.60	-	8.00	-	Pass
HT20	MCS0	1	11	2462	-11.78	-	-	-4.60	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Blue Lan	Temperature :	25~26℃
		Relative Humidity :	55~58%

EUT Information

Report NO : 832501-01
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	28.45	56.00	27.55	L1	OFF	19.5
0.150000	44.07	---	66.00	21.93	L1	OFF	19.5
0.192750	---	31.95	53.92	21.97	L1	OFF	19.5
0.192750	41.32	---	63.92	22.60	L1	OFF	19.5
0.255750	---	26.95	51.57	24.62	L1	OFF	19.5
0.255750	35.22	---	61.57	26.35	L1	OFF	19.5
0.318750	---	24.17	49.74	25.57	L1	OFF	19.5
0.318750	29.06	---	59.74	30.68	L1	OFF	19.5
0.642750	---	26.91	46.00	19.09	L1	OFF	19.5
0.642750	30.09	---	56.00	25.91	L1	OFF	19.5
0.708000	---	24.14	46.00	21.86	L1	OFF	19.5
0.708000	27.45	---	56.00	28.55	L1	OFF	19.5
10.524750	---	26.12	50.00	23.88	L1	OFF	19.7
10.524750	29.09	---	60.00	30.91	L1	OFF	19.7

EUT Information

Report NO : 832501-01
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	27.86	55.88	28.02	N	OFF	19.5
0.152250	44.06	---	65.88	21.82	N	OFF	19.5
0.192750	---	29.43	53.92	24.49	N	OFF	19.5
0.192750	37.35	---	63.92	26.57	N	OFF	19.5
0.255750	---	25.14	51.57	26.43	N	OFF	19.5
0.255750	31.24	---	61.57	30.33	N	OFF	19.5
0.516750	---	24.60	46.00	21.40	N	OFF	19.5
0.516750	28.34	---	56.00	27.66	N	OFF	19.5
0.631500	---	24.14	46.00	21.86	N	OFF	19.5
0.631500	28.02	---	56.00	27.98	N	OFF	19.5
10.054500	---	26.37	50.00	23.63	N	OFF	19.7
10.054500	29.64	---	60.00	30.36	N	OFF	19.7



Appendix C. Radiated Spurious Emission

Test Engineer :	Watt Tseng, Karl Hou, and Nick Yu	Temperature :	21~23°C
		Relative Humidity :	59~62%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2370.48	53.86	-20.14	74	44.29	27.11	14.04	31.58	393	48	P	H
		2390	41.69	-12.31	54	32.05	27.15	14.06	31.57	393	48	A	H
	*	2412	105.69	-	-	95.99	27.19	14.08	31.57	393	48	P	H
	*	2412	101.34	-	-	91.64	27.19	14.08	31.57	393	48	A	H
													H
		2387.28	53.66	-20.34	74	44.03	27.15	14.06	31.58	131	278	P	V
		2388.855	41.75	-12.25	54	32.12	27.15	14.06	31.58	131	278	A	V
	*	2412	107.31	-	-	97.61	27.19	14.08	31.57	131	278	P	V
	*	2412	103.05	-	-	93.35	27.19	14.08	31.57	131	278	A	V
													V
802.11b CH 06 2437MHz		2328.06	53.1	-20.9	74	43.69	26.99	14.01	31.59	381	52	P	H
		2389.24	41.22	-12.78	54	31.59	27.15	14.06	31.58	381	52	A	H
	*	2437	105.14	-	-	95.33	27.28	14.1	31.57	381	52	P	H
	*	2437	101.08	-	-	91.27	27.28	14.1	31.57	381	52	A	H
		2484.53	53.06	-20.94	74	43.12	27.36	14.14	31.56	381	52	P	H
		2484.53	41.48	-12.52	54	31.54	27.36	14.14	31.56	381	52	A	H
		2348.22	53.53	-20.47	74	44.05	27.03	14.03	31.58	153	264	P	V
		2389.8	41.32	-12.68	54	31.68	27.15	14.06	31.57	153	264	A	V
	*	2437	105.22	-	-	95.41	27.28	14.1	31.57	153	264	P	V
	*	2437	101.11	-	-	91.3	27.28	14.1	31.57	153	264	A	V
		2494.89	54.61	-19.39	74	44.62	27.4	14.14	31.55	153	264	P	V
		2488.52	41.44	-12.56	54	31.46	27.4	14.14	31.56	153	264	A	V



802.11b CH 11 2462MHz	*	2462	104.18	-	-	94.31	27.32	14.11	31.56	377	51	P	H
	*	2462	100.09	-	-	90.22	27.32	14.11	31.56	377	51	A	H
		2486.84	54.56	-19.44	74	44.62	27.36	14.14	31.56	377	51	P	H
		2483.52	44.54	-9.46	54	34.6	27.36	14.14	31.56	377	51	A	H
													H
													H
	*	2462	103.7	-	-	93.83	27.32	14.11	31.56	117	265	P	V
	*	2462	99.49	-	-	89.62	27.32	14.11	31.56	117	265	A	V
		2485.08	54.18	-19.82	74	44.24	27.36	14.14	31.56	117	265	P	V
		2486	43.65	-10.35	54	33.71	27.36	14.14	31.56	117	265	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		4824	48.89	-25.11	74	67.4	31.36	6.7	56.57	100	0	P	H
													H
													H
													H
		4824	47.4	-26.6	74	65.91	31.36	6.7	56.57	100	0	P	V
													V
													V
													V
802.11b CH 06 2437MHz		4874	45.05	-28.95	74	63.41	31.46	6.73	56.55	100	0	P	H
		7311	44.11	-29.89	74	56.16	36.11	8.07	56.23	100	0	P	H
													H
													H
		4874	43.46	-30.54	74	61.82	31.46	6.73	56.55	100	0	P	V
		7311	43.21	-30.79	74	55.26	36.11	8.07	56.23	100	0	P	V
													V
													V
802.11b CH 11 2462MHz		4924	47.4	-26.6	74	65.64	31.56	6.73	56.53	100	0	P	H
		7386	45.89	-28.11	74	57.69	36.33	8.01	56.14	100	0	P	H
													H
													H
		4924	46.05	-27.95	74	64.29	31.56	6.73	56.53	100	0	P	V
		7386	43.51	-30.49	74	55.31	36.33	8.01	56.14	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2388.015	55.95	-18.05	74	46.32	27.15	14.06	31.58	395	49	P	H
		2390	45.17	-8.83	54	35.53	27.15	14.06	31.57	395	49	A	H
	*	2412	104.69	-	-	94.99	27.19	14.08	31.57	395	49	P	H
	*	2412	95.02	-	-	85.32	27.19	14.08	31.57	395	49	A	H
													H
													H
		2389.59	55.73	-18.27	74	46.1	27.15	14.06	31.58	128	267	P	V
		2389.905	45.1	-8.9	54	35.46	27.15	14.06	31.57	128	267	A	V
	*	2412	105.81	-	-	96.11	27.19	14.08	31.57	128	267	P	V
	*	2412	95.83	-	-	86.13	27.19	14.08	31.57	128	267	A	V
													V
													V
802.11g CH 06 2437MHz		2318.82	53.03	-20.97	74	43.63	26.99	14	31.59	384	51	P	H
		2389.8	42.01	-11.99	54	32.37	27.15	14.06	31.57	384	51	A	H
	*	2437	104.63	-	-	94.82	27.28	14.1	31.57	384	51	P	H
	*	2437	94.25	-	-	84.44	27.28	14.1	31.57	384	51	A	H
		2488.03	53.96	-20.04	74	43.98	27.4	14.14	31.56	384	51	P	H
		2485.86	42.5	-11.5	54	32.56	27.36	14.14	31.56	384	51	A	H
		2387.42	53.13	-20.87	74	43.5	27.15	14.06	31.58	151	264	P	V
		2389.38	42.08	-11.92	54	32.45	27.15	14.06	31.58	151	264	A	V
	*	2437	104.83	-	-	95.02	27.28	14.1	31.57	151	264	P	V
	*	2437	94.04	-	-	84.23	27.28	14.1	31.57	151	264	A	V
		2496.22	53.44	-20.56	74	43.45	27.4	14.14	31.55	151	264	P	V
		2484.18	42.47	-11.53	54	32.53	27.36	14.14	31.56	151	264	A	V



802.11g CH 11 2462MHz	*	2462	102.86	-	-	92.99	27.32	14.11	31.56	301	46	P	H
	*	2462	92.36	-	-	82.49	27.32	14.11	31.56	301	46	A	H
		2483.52	56.07	-17.93	74	46.13	27.36	14.14	31.56	301	46	P	H
		2483.64	44.93	-9.07	54	34.99	27.36	14.14	31.56	301	46	A	H
													H
													H
	*	2462	103.58	-	-	93.71	27.32	14.11	31.56	121	266	P	V
	*	2462	92.86	-	-	82.99	27.32	14.11	31.56	121	266	A	V
		2483.72	56.13	-17.87	74	46.19	27.36	14.14	31.56	121	266	P	V
		2483.52	44.58	-9.42	54	34.64	27.36	14.14	31.56	121	266	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		4824	43.85	-30.15	74	62.36	31.36	6.7	56.57	100	0	P	H
													H
													H
													H
		4824	41.45	-32.55	74	59.96	31.36	6.7	56.57	100	0	P	V
													V
													V
													V
802.11g CH 06 2437MHz		4874	42.49	-31.51	74	60.85	31.46	6.73	56.55	100	0	P	H
		7311	43.36	-30.64	74	55.41	36.11	8.07	56.23	100	0	P	H
													H
													H
		4874	41.73	-32.27	74	60.09	31.46	6.73	56.55	100	0	P	V
		7311	42.25	-31.75	74	54.3	36.11	8.07	56.23	100	0	P	V
													V
													V
802.11g CH 11 2462MHz		4924	43.22	-30.78	74	61.46	31.56	6.73	56.53	100	0	P	H
		7386	43.9	-30.1	74	55.7	36.33	8.01	56.14	100	0	P	H
													H
													H
		4924	42.08	-31.92	74	60.32	31.56	6.73	56.53	100	0	P	V
		7386	44	-30	74	55.8	36.33	8.01	56.14	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2390	53.92	-20.08	74	44.28	27.15	14.06	31.57	395	50	P	H
		2389.59	43.28	-10.72	54	33.65	27.15	14.06	31.58	395	50	A	H
	*	2412	100.14	-	-	90.44	27.19	14.08	31.57	395	50	P	H
	*	2412	91.03	-	-	81.33	27.19	14.08	31.57	395	50	A	H
													H
													H
		2389.485	54.33	-19.67	74	44.7	27.15	14.06	31.58	131	280	P	V
		2390	43.58	-10.42	54	33.94	27.15	14.06	31.57	131	280	A	V
	*	2412	102.08	-	-	92.38	27.19	14.08	31.57	131	280	P	V
	*	2412	92.13	-	-	82.43	27.19	14.08	31.57	131	280	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		2384.76	53.44	-20.56	74	43.85	27.11	14.06	31.58	382	48	P	H
		2389.94	42.08	-11.92	54	32.44	27.15	14.06	31.57	382	48	A	H
	*	2437	101.28	-	-	91.47	27.28	14.1	31.57	382	48	P	H
	*	2437	90.78	-	-	80.97	27.28	14.1	31.57	382	48	A	H
		2494.33	54.05	-19.95	74	44.06	27.4	14.14	31.55	382	48	P	H
		2493.77	42.53	-11.47	54	32.54	27.4	14.14	31.55	382	48	A	H
		2324.14	53.16	-20.84	74	43.75	26.99	14.01	31.59	157	266	P	V
		2369.5	42.08	-11.92	54	32.51	27.11	14.04	31.58	157	266	A	V
	*	2437	100.88	-	-	91.07	27.28	14.1	31.57	157	266	P	V
	*	2437	90.16	-	-	80.35	27.28	14.1	31.57	157	266	A	V
		2494.33	53.44	-20.56	74	43.45	27.4	14.14	31.55	157	266	P	V
		2483.55	42.28	-11.72	54	32.34	27.36	14.14	31.56	157	266	A	V



802.11n HT20 CH 11 2462MHz	*	2462	99.43	-	-	89.56	27.32	14.11	31.56	376	51	P	H
	*	2462	89.84	-	-	79.97	27.32	14.11	31.56	376	51	A	H
		2496.24	53.43	-20.57	74	43.44	27.4	14.14	31.55	376	51	P	H
		2483.6	43.11	-10.89	54	33.17	27.36	14.14	31.56	376	51	A	H
													H
													H
	*	2462	99.25	-	-	89.38	27.32	14.11	31.56	116	263	P	V
	*	2462	89.25	-	-	79.38	27.32	14.11	31.56	116	263	A	V
		2499.04	54.19	-19.81	74	44.2	27.4	14.14	31.55	116	263	P	V
		2483.52	42.8	-11.2	54	32.86	27.36	14.14	31.56	116	263	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	39.67	-34.33	74	58.18	31.36	6.7	56.57	100	0	P	H
													H
													H
													H
		4824	39.11	-34.89	74	57.62	31.36	6.7	56.57	100	0	P	V
													V
													V
													V
802.11n HT20 CH 06 2437MHz		4874	39.15	-34.85	74	57.51	31.46	6.73	56.55	100	0	P	H
		7311	42.31	-31.69	74	54.36	36.11	8.07	56.23	100	0	P	H
													H
													H
		4874	40.57	-33.43	74	58.93	31.46	6.73	56.55	100	0	P	V
		7311	42.09	-31.91	74	54.14	36.11	8.07	56.23	100	0	P	V
													V
													V
802.11n HT20 CH 11 2462MHz		4924	41.02	-32.98	74	59.26	31.56	6.73	56.53	100	0	P	H
		7386	43.45	-30.55	74	55.25	36.33	8.01	56.14	100	0	P	H
													H
													H
		4924	39.69	-34.31	74	57.93	31.56	6.73	56.53	100	0	P	V
		7386	43.31	-30.69	74	55.11	36.33	8.01	56.14	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11b (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11b LF		98.58	22.41	-21.09	43.5	36.31	15.68	0.85	30.43	-	-	P	H
		142.59	21.47	-22.03	43.5	33.76	17.06	1.03	30.38	-	-	P	H
		207.66	19.9	-23.6	43.5	33.94	14.95	1.32	30.31	-	-	P	H
		568.8	27.6	-18.4	46	29.45	25.8	2.03	29.68	-	-	P	H
		778.1	30.23	-15.77	46	29.2	27.99	2.38	29.34	-	-	P	H
		957.3	33.4	-12.6	46	28.65	30.97	2.75	28.97	100	0	P	H
													H
													H
													H
													H
													H
													H
													H
		34.59	27.14	-12.86	40	35.11	21.84	0.45	30.26	-	-	P	V
		63.75	25.12	-14.88	40	43.13	11.73	0.72	30.46	-	-	P	V
		123.69	22.94	-20.56	43.5	35.18	17.23	0.93	30.4	-	-	P	V
		561.1	27.98	-18.02	46	29.63	26.01	2.03	29.69	-	-	P	V
		784.4	31.51	-14.49	46	30.43	28.03	2.38	29.33	-	-	P	V
		956.6	34.04	-11.96	46	29.35	30.92	2.75	28.98	100	0	P	V
													V
												V	
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		60.51	16.91	-23.09	40	35.15	11.5	0.72	30.46	-	-	P	H
		103.98	21.4	-22.1	43.5	34.83	16.15	0.85	30.43	-	-	P	H
		143.4	21.46	-22.04	43.5	33.8	17	1.04	30.38	-	-	P	H
		575.8	26.99	-19.01	46	29.07	25.57	2.02	29.67	-	-	P	H
		772.5	30.76	-15.24	46	29.8	27.96	2.35	29.35	-	-	P	H
		952.4	33.57	-12.43	46	29.12	30.71	2.73	28.99	100	0	P	H
													H
													H
													H
													H
													H
													H
													H
		34.59	27.46	-12.54	40	35.43	21.84	0.45	30.26	-	-	P	V
		63.48	30.01	-9.99	40	48.02	11.73	0.72	30.46	100	0	P	V
		126.93	24.92	-18.58	43.5	37.12	17.27	0.93	30.4	-	-	P	V
		496.7	26.23	-19.77	46	30.51	23.65	1.86	29.79	-	-	P	V
		561.8	28.09	-17.91	46	29.74	26.01	2.03	29.69	-	-	P	V
		871.9	32.25	-13.75	46	29.82	29.08	2.53	29.18	-	-	P	V
													V
												V	
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		99.93	25.36	-18.14	43.5	39.13	15.81	0.85	30.43	-	-	P	H
		142.05	20.66	-22.84	43.5	32.95	17.06	1.03	30.38	-	-	P	H
		260.58	20.82	-25.18	46	29.82	19.74	1.47	30.21	-	-	P	H
		569.5	27.2	-18.8	46	29.09	25.77	2.02	29.68	-	-	P	H
		715.8	28.5	-17.5	46	28.95	26.77	2.26	29.48	-	-	P	H
		933.5	32.44	-13.56	46	28.99	29.8	2.69	29.04	100	0	P	H
													H
													H
													H
													H
													H
													H
		38.1	31.03	-8.97	40	40.61	20.26	0.46	30.3	-	-	P	V
		68.34	31.2	-8.8	40	49	11.93	0.73	30.46	100	0	P	V
		116.4	25.79	-17.71	43.5	38.2	17.08	0.92	30.41	-	-	P	V
		519.8	25.23	-20.77	46	29.3	23.77	1.91	29.75	-	-	P	V
		558.3	27.46	-18.54	46	29.17	25.97	2.01	29.69	-	-	P	V
		953.8	33.17	-12.83	46	28.66	30.76	2.73	28.98	-	-	P	V
													V
													V
												V	
												V	
												V	
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.







Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Watt Tseng, Karl Hou, and Nick Yu	Temperature :	21~23°C
		Relative Humidity :	59~62%





Note symbol

-L	Low channel location
-R	High channel location





2.4GHz 2400~2483.5MHz
WIFI 802.11b (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Project : 832501-01 Mode : 18	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Project : 832501-01 Mode : 18
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:0.0100Hz SWT:Auto Project : 832501-01 Mode : 18	 Site : 03CH12-HY Condition : AVG_54 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:0.0100Hz SWT:Auto Project : 832501-01 Mode : 18





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH12-HV Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 18	 Site : 03CH12-HV Condition : PEAK_74 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 18
Avg.	 Site : 03CH12-HV Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 18	 Site : 03CH12-HV Condition : AVG_54 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 18







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-1H Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL Detector : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto Project : 832501-01 Mode : 19	 Site : 03CH12-1H Condition : PEAK_F4 3m HORN_91200_1328 HORIZONTAL Detector : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto Project : 832501-01 Mode : 19
Avg.	 Site : 03CH12-1H Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL Detector : RBW:3000.000KHz VBW:0.010KHz SWT:Auto Project : 832501-01 Mode : 19	 Site : 03CH12-1H Condition : AVG_F4 3m HORN_91200_1328 HORIZONTAL Detector : RBW:3000.000KHz VBW:0.010KHz SWT:Auto Project : 832501-01 Mode : 19





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 19	Left blank
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL RBW:1000.000kHz VBW:10100kHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 19	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH12-1H Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 19	 Site : 03CH12-1H Condition : PEAK_74 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 19
Avg.	 Site : 03CH12-1H Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 19	 Site : 03CH12-1H Condition : AVG_54 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 19







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 19	Left blank
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:1000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 19	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-14Y Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VSW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 20	 Site : 03CH12-14Y Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VSW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 20
Avg.	 Site : 03CH12-14Y Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VSW:0.010KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 20	 Site : 03CH12-14Y Condition : AVG_54 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VSW:0.010KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 20











WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH12-14Y Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VSW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 20	 Site : 03CH12-14Y Condition : PEAK_74 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VSW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 20
Avg.	 Site : 03CH12-14Y Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VSW:0.010KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 20	 Site : 03CH12-14Y Condition : AVG_54 3m HORN_91200_1328 VERTICAL RBW:3000.000KHz VSW:0.010KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 20

2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Detector : Peak Project : 832501-01 Mode : 22	 Site : 03CH12-HY Condition : PEAK_F4 3m HORN_91200_1328 HORIZONTAL RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Detector : Peak Project : 832501-01 Mode : 22
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL RBW:1000.0000Hz VBW:1.0000Hz SWT:Auto Detector : Peak Project : 832501-01 Mode : 22	 Site : 03CH12-HY Condition : AVG_F4 3m HORN_91200_1328 HORIZONTAL RBW:1000.0000Hz VBW:1.0000Hz SWT:Auto Detector : Peak Project : 832501-01 Mode : 22







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH12-1H Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 832501-01 Mode : 22	 Site : 03CH12-1H Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 832501-01 Mode : 22
Avg.	 Site : 03CH12-1H Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : 832501-01 Mode : 22	 Site : 03CH12-1H Condition : AVG_54 3m HORN_91200_1328 VERTICAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : 832501-01 Mode : 22

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-1H Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL Detector : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto Project : 832501-01 Mode : 23	 Site : 03CH12-1H Condition : PEAK_T4 3m HORN_91200_1328 HORIZONTAL Detector : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto Project : 832501-01 Mode : 23
Avg.	 Site : 03CH12-1H Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL Detector : RBW:3000.000KHz VBW:1000KHz SWT:Auto Project : 832501-01 Mode : 23	 Site : 03CH12-1H Condition : AVG_54 3m HORN_91200_1328 HORIZONTAL Detector : RBW:3000.000KHz VBW:1000KHz SWT:Auto Project : 832501-01 Mode : 23









WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 23	Left blank
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL RBW:1000.000kHz VBW:1000kHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 23	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH12-HV Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 23	 Site : 03CH12-HV Condition : PEAK_F4 3m HORN_91200_1328 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 23
Avg.	 Site : 03CH12-HV Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL RBW:1000.000kHz VBW:1.000kHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 23	 Site : 03CH12-HV Condition : AVG_F4 3m HORN_91200_1328 VERTICAL RBW:1000.000kHz VBW:1.000kHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 23



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Detector : Peak Project : 832501-01 Mode : 23	Left Blank
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL RBW:1000.0000Hz VBW:10000Hz SWT:Auto Detector : Peak Project : 832501-01 Mode : 23	Left Blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-14Y Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VSW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 24	 Site : 03CH12-14Y Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VSW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 24
Avg.	 Site : 03CH12-14Y Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VSW:1000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 24	 Site : 03CH12-14Y Condition : AVG_54 3m HORN_91200_1328 HORIZONTAL RBW:3000.000KHz VSW:1000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 24











WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH12-14Y Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 24	 Site : 03CH12-14Y Condition : PEAK_F4 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 24
Avg.	 Site : 03CH12-14Y Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 24	 Site : 03CH12-14Y Condition : AVG_F4 3m HORN_91200_1328 VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 24







2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Project : 832501-01 Mode : 25	 Site : 03CH12-HY Condition : PEAK_F4 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:3000.0000Hz SWT:Auto Project : 832501-01 Mode : 25
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:1.0000Hz SWT:Auto Project : 832501-01 Mode : 25	 Site : 03CH12-HY Condition : AVG_F4 3m HORN_91200_1328 HORIZONTAL Detector : RBW:1000.0000Hz VBW:1.0000Hz SWT:Auto Project : 832501-01 Mode : 25





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH12-1H Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto Project : 832501-01 Mode : 25	 Site : 03CH12-1H Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000KHz VBW:3000.000KHz SWT:Auto Project : 832501-01 Mode : 25
Avg.	 Site : 03CH12-1H Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000KHz VBW:1000KHz SWT:Auto Project : 832501-01 Mode : 25	 Site : 03CH12-1H Condition : AVG_54 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000KHz VBW:1000KHz SWT:Auto Project : 832501-01 Mode : 25





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-HV Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 26	 Site : 03CH12-HV Condition : PEAK_F4 3m HORN_91200_1328 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 26
Avg.	 Site : 03CH12-HV Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 26	 Site : 03CH12-HV Condition : AVG_F4 3m HORN_91200_1328 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 26







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 26	Left blank
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL RBW:1000.000kHz VBW:1000kHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 26	Left blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH12-1H Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000kHz VBW:3000.000kHz SWT:Auto Project : 832501-01 Mode : 26	 Site : 03CH12-1H Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000kHz VBW:3000.000kHz SWT:Auto Project : 832501-01 Mode : 26
Avg.	 Site : 03CH12-1H Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000kHz VBW:10000Hz SWT:Auto Project : 832501-01 Mode : 26	 Site : 03CH12-1H Condition : AVG_54 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000kHz VBW:10000Hz SWT:Auto Project : 832501-01 Mode : 26







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 26	Left Blank
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL RBW:1000.000kHz VBW:10000Hz SWT:Auto Detector : Peak Project : 832501-01 Mode : 26	Left Blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-14Y Condition : PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 27	 Site : 03CH12-14Y Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 27
Avg.	 Site : 03CH12-14Y Condition : AVG_BE_54 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 27	 Site : 03CH12-14Y Condition : AVG_54 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 27



WIFI	2.4GHz 2400~2483.5MHz Fundamental @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH12-14Y Condition : PEAK_BE_74 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000KHz VSW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 27	 Site : 03CH12-14Y Condition : PEAK_F4 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000KHz VSW:3000.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 27
Avg.	 Site : 03CH12-14Y Condition : AVG_BE_54 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000KHz VSW:1.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 27	 Site : 03CH12-14Y Condition : AVG_F4 3m HORN_91200_1328 VERTICAL Detector : RBW:3000.000KHz VSW:1.000KHz SWT:Auto Detector : Peak Project : 832501-01 Mode : 27





2.4GHz 2400~2483.5MHz



WIFI 802.11b (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak	Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 1B	Site : 03CH12-HY Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 832501-01 Mode : 1B



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH06 2437MHz	
1	Horizontal	Vertical
Peak	Level (dBm/Vm) Date: 2018.04.24  Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 19	Level (dBm/Vm) Date: 2018.04.24  Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 832501-01 Mode : 19





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 20	 Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 832501-01 Mode : 20



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH12-4Y Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 22	 Site : 03CH12-4Y Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 832501-01 Mode : 22





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1	Horizontal	Vertical
Peak	Level (dBuV/m) Date: 2018.04.24 Frequency (MHz) Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 23	Level (dBuV/m) Date: 2018.04.24 Frequency (MHz) Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 832501-01 Mode : 23



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak	Level (dBm/Vm) Date: 2018.04.24 Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 24	Level (dBm/Vm) Date: 2018.04.24 Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 832501-01 Mode : 24





2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH12-4Y Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 25	 Site : 03CH12-4Y Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 832501-01 Mode : 25





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH06 2437MHz	
1	Horizontal	Vertical
Peak	Level (dBm/Vm) Date: 2018.04.24 Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 26	Level (dBm/Vm) Date: 2018.04.24 Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 832501-01 Mode : 26





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
Peak	Level (dBm/Vm) Date: 2018.04.24  Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 27	Level (dBm/Vm) Date: 2018.04.24  Site : 03CH12-11Y Condition : PEAK_74 3m HORN_91200_1328 VERTICAL Detector : Peak Project : 832501-01 Mode : 27



Emission below 1GHz
2.4GHz WIFI 802.11b (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11b LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH12-HY Condition : QP 3m 802.11b_6111b_35414 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 21	 Site : 03CH12-HY Condition : QP 3m 802.11b_6111b_35414 VERTICAL Detector : Peak Project : 832501-01 Mode : 21

Emission below 1GHz
2.4GHz WIFI 802.11g (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11g LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH12-HY Condition : QP 3m 802.11g_6111D_35414 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 28	 Site : 03CH12-HY Condition : QP 3m 802.11g_6111D_35414 VERTICAL Detector : Peak Project : 832501-01 Mode : 28

Emission below 1GHz
2.4GHz WIFI 802.11n HT20 (LF)


WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11n HT20 LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH12-HY Condition : QP 3m 81LO6_6111D_35414 HORIZONTAL Detector : Peak Project : 832501-01 Mode : 29	 Site : 03CH12-HY Condition : QP 3m 81LO6_6111D_35414 VERTICAL Detector : Peak Project : 832501-01 Mode : 29



Appendix E. Duty Cycle Plots


Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
802.11b	100	1000	1.00	10Hz	0.00
802.11g	94.39	2020	0.50	1kHz	0.25
2.4GHz 802.11n HT20	93.07	1880	0.53	1kHz	0.31
2.4GHz 802.11ac VHT20	94.06	1900	0.53	1kHz	0.27

802.11b



Date: 3.APR.2018 01:09:56


802.11g



Date: 3.APR.2018 01:17:08




802.11n HT20



Date: 3.APR.2018 01:21:41

802.11ac VHT20



Date: 3.APR.2018 01:27:11

THE END