

## FCC Test Report

### (PART 22)

**Report No.:** RF160621C21-5

**FCC ID:** PY7-14784Z

**Received Date:** Jun. 21, 2016

**Test Date:** Jul. 05, 2016 ~ Jul. 07, 2016

**Issued Date:** Jul. 15, 2016

**Applicant:** Sony Mobile Communications Inc.

**Address:** 4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan ( R.O.C )

**Test Location (1):** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

**Test Location (2):** No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan, R.O.C



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 Summary of Test Results</b> .....	<b>5</b>
2.1 Measurement Uncertainty .....	5
2.2 Test Site and Instruments .....	6
<b>3 General Information</b> .....	<b>7</b>
3.1 General Description of EUT .....	7
3.2 Configuration of System under Test .....	9
3.2.1 Description of Support Units .....	9
3.3 Test Mode Applicability and Tested Channel Detail .....	10
3.4 EUT Operating Conditions .....	13
3.5 General Description of Applied Standards .....	13
<b>4 Test Types and Results</b> .....	<b>14</b>
4.1 Output Power Measurement .....	14
4.1.1 Limits of Output Power Measurement .....	14
4.1.2 Test Procedures .....	14
4.1.3 Test Setup .....	15
4.1.4 Test Results .....	16
4.2 Frequency Stability Measurement .....	26
4.2.1 Limits of Frequency Stability Measurement .....	26
4.2.2 Test Procedure .....	26
4.2.3 Test Setup .....	26
4.2.4 Test Results .....	27
4.3 Occupied Bandwidth Measurement .....	29
4.3.1 Test Procedure .....	29
4.3.2 Test Setup .....	29
4.3.3 Test Result .....	30
4.4 Band Edge Measurement .....	36
4.4.1 Limits of Band Edge Measurement .....	36
4.4.2 Test Setup .....	36
4.4.3 Test Procedures .....	36
4.4.4 Test Results .....	37
4.5 Peak to Average Ratio .....	47
4.5.1 Limits of Peak to Average Ratio Measurement .....	47
4.5.2 Test Setup .....	47
4.5.3 Test Procedures .....	47
4.5.4 Test Results .....	48
4.6 Conducted Spurious Emissions .....	54
4.6.1 Limits of Conducted Spurious Emissions Measurement .....	54
4.6.2 Test Setup .....	54
4.6.3 Test Procedure .....	54
4.6.4 Test Results .....	55
4.7 Radiated Emission Measurement .....	58
4.7.1 Limits of Radiated Emission Measurement .....	58
4.7.2 Test Procedure .....	58
4.7.3 Deviation from Test Standard .....	58
4.7.4 Test Setup .....	58
4.7.5 Test Results .....	59
<b>5 Pictures of Test Arrangements</b> .....	<b>69</b>
<b>Appendix – Information on the Testing Laboratories</b> .....	<b>70</b>

### Release Control Record

Issue No.	Description	Date Issued
RF160621C21-5	Original Release	Jul. 15, 2016



## 1 Certificate of Conformity

**Product:** Mobile Phone

**Brand:** Sony

**Sample Status:** Identical Prototype

**Applicant:** Sony Mobile Communications Inc.

**Test Date:** Jul. 05, 2016 ~ Jul. 07, 2016

**Standards:** FCC Part 22, Subpart H

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Evonne Liu , **Date:** Jul. 15, 2016  
Evonne Liu / Specialist

**Approved by :** Stanley Wu , **Date:** Jul. 15, 2016  
Stanley Wu / Assistant Manager

## 2 Summary of Test Results

Applied Standard: FCC Part 22 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 22.913 (a)	Effective Radiated Power	Pass	Meet the requirement of limit.
---	Peak to Average Ratio	Pass	Meet the requirement of limit.
2.1055 22.355	Frequency Stability	Pass	Meet the requirement of limit.
2.1049	Occupied Bandwidth	Pass	Meet the requirement of limit.
22.917	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 22.917	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 22.917	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -33.82 dB at 61.32 MHz.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

## 2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY50010135	Jul. 18, 2015	Jul. 17, 2016
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 17, 2015	Dec. 16, 2016
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Jan. 07, 2016	Jan. 06, 2017
HORN Antenna ETS-Lindgren	3117	00143293	Jan. 04, 2016	Jan. 03, 2017
Double Ridge Guide Horn Antenna EMCO	3115	5619	Jan. 04, 2016	Jan. 03, 2017
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Jan. 07, 2016	Jan. 06, 2017
Agilent Communications Tester-Wireless	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Preamplifier Agilent	310N	187226	Jun. 24, 2016	Jun. 23, 2017
Preamplifier Agilent	83017A	MY39501357	Jun. 24, 2016	Jun. 23, 2017
Power Meter Anritsu	ML2495A	1232002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor Anritsu	MA2411B	1207325	Sep. 21, 2015	Sep. 20, 2016
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 24, 2016	Jun. 23, 2017
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 24, 2016	Jun. 23, 2017
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless Agilent	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Radio Communication Analyzer Anritsu	MT8820C	6201240432	Jul. 06, 2015	Jul. 05, 2017

Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HsinTien Chamber 1.

3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.

4. The FCC Site Registration No. is 149147.

5. The IC Site Registration No. is IC7450I-1.

### 3 General Information

#### 3.1 General Description of EUT

<b>Product</b>	Mobile Phone	
<b>Brand</b>	Sony	
<b>Status of EUT</b>	Identical Prototype	
<b>Power Supply Rating</b>	3.8Vdc (Embedded Battery) 5Vdc or 9Vdc or 12Vdc (Adapter)	
<b>Modulation Type</b>	GSM/GPRS	GMSK
	EDGE	GMSK, 8PSK
	WCDMA	BPSK
	LTE	QPSK, 16QAM
<b>Frequency Range</b>	GSM/GPRS/EDGE	824.2 ~ 848.8 MHz
	WCDMA	826.4 ~ 846.6 MHz
	LTE 5 (Channel Bandwidth: 1.4 MHz)	824.7 ~ 848.3 MHz
	LTE 5 (Channel Bandwidth: 3 MHz)	825.5 ~ 847.5 MHz
	LTE 5 (Channel Bandwidth: 5 MHz)	826.5 ~ 846.5 MHz
	LTE 5 (Channel Bandwidth: 10 MHz)	829 ~ 844 MHz
	LTE 26 (Channel Bandwidth: 1.4 MHz)	824.7 ~ 848.3 MHz
	LTE 26 (Channel Bandwidth: 3 MHz)	825.5 ~ 847.5 MHz
	LTE 26 (Channel Bandwidth: 5 MHz)	826.5 ~ 846.5 MHz
	LTE 26 (Channel Bandwidth: 10 MHz)	829 ~ 844 MHz
LTE 26 (Channel Bandwidth: 15 MHz)	831.5 ~ 841.5 MHz	
<b>Max. ERP Power</b>	GSM/GPRS	468.60 mW
	EDGE	149.28 mW
	WCDMA	74.13 mW
	LTE 5 (Channel Bandwidth: 1.4 MHz)	QPSK : 61.97 mW 16QAM : 43.73 mW
	LTE 5 (Channel Bandwidth: 3 MHz)	QPSK : 60.23 mW 16QAM : 45.48 mW
	LTE 5 (Channel Bandwidth: 5 MHz)	QPSK : 54.95 mW 16QAM : 46.75 mW
	LTE 5 (Channel Bandwidth: 10 MHz)	QPSK : 60.12 mW 16QAM : 45.39 mW
	LTE 26 (Channel Bandwidth: 1.4 MHz)	QPSK : 57.44 mW 16QAM : 45.29 mW
	LTE 26 (Channel Bandwidth: 3 MHz)	QPSK : 56.13 mW 16QAM : 44.69 mW
	LTE 26 (Channel Bandwidth: 5 MHz)	QPSK : 57.02 mW 16QAM : 44.59 mW
	LTE 26 (Channel Bandwidth: 10 MHz)	QPSK : 55.23 mW 16QAM : 46.11 mW
	LTE 26 (Channel Bandwidth: 15 MHz)	QPSK : 56.23 mW 16QAM : 44.59 mW

<b>Emission Designator</b>	GSM/GPRS	247KGXW
	EDGE	247KG7W
	WCDMA	4M13F9W
	LTE 5 (Channel Bandwidth: 1.4 MHz)	QPSK : 1M09G7D 16QAM : 1M09W7D
	LTE 5 (Channel Bandwidth: 3 MHz)	QPSK : 2M70G7D 16QAM : 2M69W7D
	LTE 5 (Channel Bandwidth: 5 MHz)	QPSK : 4M49G7D 16QAM : 4M48W7D
	LTE 5 (Channel Bandwidth: 10 MHz)	QPSK : 8M95G7D 16QAM : 8M96W7D
	LTE 26 (Channel Bandwidth: 1.4 MHz)	QPSK : 1M09G7D 16QAM : 1M09W7D
	LTE 26 (Channel Bandwidth: 3 MHz)	QPSK : 2M70G7D 16QAM : 2M69W7D
	LTE 26 (Channel Bandwidth: 5 MHz)	QPSK : 4M49G7D 16QAM : 4M48W7D
	LTE 26 (Channel Bandwidth: 10 MHz)	QPSK : 8M95G7D 16QAM : 8M96W7D
	LTE 26 (Channel Bandwidth: 15 MHz)	QPSK : 13M4G7D 16QAM : 13M4W7D
	<b>Antenna Type</b>	Fixed Internal Antenna
<b>Accessory Device</b>	Refer to Note as below	
<b>Data Cable Supplied</b>	Refer to Note as below	

Note:



1. The EUT contains following accessory devices.

Product	Brand	Model	Type	Description
Adapter	Sony	UCH12	AC-0051	I/P: 100- 240Vac, 400mA, 50~60 Hz, O/P: 5.0Vdc, 2700 mA / O/P: 9.0Vdc, 1800 mA / O/P: 12.0Vdc, 1350 mA
Battery	Sony	1303-8269	N/A	3.8Vdc, 2700mAh
Earphone	Sony	MH410c	AG-1100	1.5m non-shielded cable w/o core
USB Cable	Sony	UCB20	AI-0160	0.95m shielded cable w/o core



2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 Configuration of System under Test

#### <Radiated Emission Test>



#### <E.R.P. Test>



#### 3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

### 3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports.

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	ERP	Radiated Emission
GSM	X-plane	X-axis
EDGE	X-plane	X-axis
WCDMA	X-plane	X-axis
LTE Band 5	X-plane	X-axis
LTE Band 26	X-plane	X-axis

#### GSM

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	ERP	128 to 251	128, 189, 251	GSM, EDGE
-	Frequency Stability	128 to 251	189	GSM, EDGE
-	Occupied Bandwidth	128 to 251	128, 189, 251	GSM, EDGE
-	Band Edge	128 to 251	128, 251	GSM, EDGE
-	Peak to Average Ratio	128 to 251	128, 189, 251	GSM, EDGE
-	Conducuted Emission	128 to 251	189	GSM, EDGE
-	Radiated Emission	128 to 251	189	GSM, EDGE

#### WCDMA

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	ERP	4132 to 4233	4132, 4182, 4233	WCDMA
-	Frequency Stability	4132 to 4233	4182	WCDMA
-	Occupied Bandwidth	4132 to 4233	4132, 4182, 4233	WCDMA
-	Band Edge	4132 to 4233	4132, 4233	WCDMA
-	Peak to Average Ratio	4132 to 4233	4132, 4182, 4233	WCDMA
-	Conducuted Emission	4132 to 4233	4182	WCDMA
-	Radiated Emission	4132 to 4233	4182	WCDMA

### LTE Band 5

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode		
-	ERP	20407 to 20643	20407, 20525, 20643	1.4 MHz	QPSK, 16QAM	1 RB / 2 RB Offset		
		20415 to 20635	20415, 20525, 20635	3 MHz	QPSK, 16QAM	1 RB / 7 RB Offset		
		20425 to 20625	20425, 20525, 20625	5 MHz	QPSK, 16QAM	1 RB / 12 RB Offset		
		20450 to 20600	20450, 20525, 20600	10 MHz	QPSK, 16QAM	1 RB / 24 RB Offset		
-	Frequency Stability	20407 to 20643	20525	1.4 MHz	QPSK	1 RB / 2 RB Offset		
		20415 to 20635	20525	3 MHz	QPSK	1 RB / 7 RB Offset		
		20425 to 20625	20525	5 MHz	QPSK	1 RB / 12 RB Offset		
		20450 to 20600	20525	10 MHz	QPSK	1 RB / 24 RB Offset		
-	Occupied Bandwidth	20407 to 20643	20407, 20525, 20643	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset		
		20415 to 20635	20415, 20525, 20635	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset		
		20425 to 20625	20425, 20525, 20625	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset		
		20450 to 20600	20450, 20525, 20600	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset		
-	Band Edge	20407 to 20643	20407	1.4MHz	QPSK	1 RB / 0 RB Offset 6 RB / 0 RB Offset		
			20643	1.4MHz	QPSK	1 RB / 5 RB Offset 6 RB / 0 RB Offset		
		20415 to 20635	20415	3 MHz	QPSK	1 RB / 0 RB Offset 15 RB / 0 RB Offset		
			20635	3 MHz	QPSK	1 RB / 14 RB Offset 15 RB / 0 RB Offset		
		20425 to 20625	20425	5 MHz	QPSK	1 RB / 0 RB Offset 25 RB / 0 RB Offset		
			20625	5 MHz	QPSK	1 RB / 24 RB Offset 25 RB / 0 RB Offset		
		20450 to 20600	20450	10 MHz	QPSK	1 RB / 0 RB Offset 50 RB / 0 RB Offset		
			20600	10 MHz	QPSK	1 RB / 49 RB Offset 50 RB / 0 RB Offset		
		-	Peak to Average Ratio	20407 to 20643	20407, 20525, 20643	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
				20415 to 20635	20415, 20525, 20635	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
				20425 to 20625	20425, 20525, 20625	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
				20450 to 20600	20450, 20525, 20600	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
-	Conducted Emission	20407 to 20643	20525	1.4 MHz	QPSK	1 RB / 2 RB Offset		
		20415 to 20635	20525	3 MHz	QPSK	1 RB / 7 RB Offset		
		20425 to 20625	20525	5 MHz	QPSK	1 RB / 12 RB Offset		
		20450 to 20600	20525	10 MHz	QPSK	1 RB / 24 RB Offset		
-	Radiated Emission	20450 to 20600	20525	10 MHz	QPSK	1 RB / 24 RB Offset		

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

**LTE Band 26**

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode		
-	ERP	26797 to 27033	26797, 26915, 27033	1.4 MHz	QPSK, 16QAM	1 RB / 5 RB Offset		
		26805 to 27025	26805, 26915, 27025	3 MHz	QPSK, 16QAM	1 RB / 14 RB Offset		
		26815 to 27015	26815, 26915, 27015	5 MHz	QPSK, 16QAM	1 RB / 24 RB Offset		
		26840 to 26990	26840, 26915, 26990	10 MHz	QPSK, 16QAM	1 RB / 49 RB Offset		
		26865 to 26965	26865, 26915, 26965	15 MHz	QPSK, 16QAM	1 RB / 49 RB Offset		
-	Frequency Stability	26797 to 27033	26915	1.4 MHz	QPSK	1 RB / 5 RB Offset		
		26805 to 27025	26915	3 MHz	QPSK	1 RB / 14 RB Offset		
		26815 to 27015	26915	5 MHz	QPSK	1 RB / 24 RB Offset		
		26840 to 26990	26915	10 MHz	QPSK	1 RB / 49 RB Offset		
		26865 to 26965	26915	15 MHz	QPSK	1 RB / 49 RB Offset		
-	Occupied Bandwidth	26797 to 27033	26797, 26915, 27033	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset		
		26805 to 27025	26805, 26915, 27025	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset		
		26815 to 27015	26815, 26915, 27015	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset		
		26840 to 26990	26840, 26915, 26990	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset		
		26865 to 26965	26865, 26915, 26965	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset		
-	Band Edge	26797 to 27033	26797	1.4 MHz	QPSK	1 RB / 0 RB Offset 6 RB / 0 RB Offset		
			27033	1.4 MHz	QPSK	1 RB / 5 RB Offset 6 RB / 0 RB Offset		
		26805 to 27025	26805	3 MHz	QPSK	1 RB / 0 RB Offset 15 RB / 0 RB Offset		
			27025	3 MHz	QPSK	1 RB / 14 RB Offset 15 RB / 0 RB Offset		
		26815 to 27015	26815	5 MHz	QPSK	1 RB / 0 RB Offset 25 RB / 0 RB Offset		
			27015	5 MHz	QPSK	1 RB / 24 RB Offset 25 RB / 0 RB Offset		
		26840 to 26990	26840	10 MHz	QPSK	1 RB / 0 RB Offset 50 RB / 0 RB Offset		
			26990	10 MHz	QPSK	1 RB / 49 RB Offset 50 RB / 0 RB Offset		
		26865 to 26965	26865	15 MHz	QPSK	1 RB / 0 RB Offset 75 RB / 0 RB Offset		
			26965	15 MHz	QPSK	1 RB / 74 RB Offset 75 RB / 0 RB Offset		
		-	Peak to Average Ratio	26797 to 27033	26797, 26915, 27033	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
				26805 to 27025	26805, 26915, 27025	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
				26815 to 27015	26815, 26915, 27015	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
				26840 to 26990	26840, 26915, 26990	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
26865 to 26965	26865, 26915, 26965			15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset		
-	Conducted Emission	26797 to 27033	26915	1.4 MHz	QPSK	1 RB / 0 RB Offset		
		26805 to 27025	26915	3 MHz	QPSK	15 RB / 0 RB Offset		
		26815 to 27015	26915	5 MHz	QPSK	25 RB / 0 RB Offset		
		26840 to 26990	26915	10 MHz	QPSK	1 RB / 0 RB Offset		
		26865 to 26965	26915	15 MHz	QPSK	25 RB / 0 RB Offset		
-	Radiated Emission	26865 to 26965	26915	15 MHz	QPSK	1 RB / 0 RB Offset		

**Note:** This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

**Test Condition:**

Test Item	Environmental Conditions	Input Power	Tested By
ERP	25 deg. C, 65 % RH	3.8 Vdc	Charles Hsiao
Frequency Stability	25 deg. C, 65 % RH	3.8 Vdc	Carlos Chen
Occupied Bandwidth	25 deg. C, 65 % RH	3.8 Vdc	Carlos Chen
Band Edge	25 deg. C, 65 % RH	3.8 Vdc	Carlos Chen
Peak to Average Ratio	25 deg. C, 65 % RH	3.8 Vdc	Carlos Chen
Condcudeted Emission	25 deg. C, 65 % RH	3.8 Vdc	Carlos Chen
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao

**3.4 EUT Operating Conditions**

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

**3.5 General Description of Applied Standards**

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC 47 CFR Part 2**

**FCC 47 CFR Part 22**

**KDB 971168 D01 Power Meas License Digital Systems v02r02**

**ANSI/TIA/EIA-603-D 2010**

**Note:** All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Output Power Measurement

#### 4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 7 watts e.r.p.

#### 4.1.2 Test Procedures

##### **EIRP / ERP Measurement:**


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1 MHz for GSM, GPRS & EDGE, and 5 MHz for WCDMA and CDMA, and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G.
- d.  $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$ . E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole,  $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}$ .

##### **Conducted Power Measurement:**

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA, CDMA, and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


### 4.1.3 Test Setup

#### EIRP / ERP Measurement:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### Conducted Power Measurement:



#### 4.1.4 Test Results

##### Conducted Output Power (dBm)

Band	GSM850		
	128	189	251
Channel	824.2	836.4	848.8
Frequency (MHz)	824.2	836.4	848.8
GSM (GMSK, 1Tx-slot)	32.61	32.51	32.31
GPRS 8 (GMSK, 1Tx-slot)	32.59	32.58	32.32
GPRS 10 (GMSK, 2Tx-slot)	31.51	31.34	31.21
GPRS 11 (GMSK, 3Tx-slot)	29.67	29.51	29.15
GPRS 12 (GMSK, 4Tx-slot)	28.52	28.35	28.12
GPRS 30 (GMSK, 1Tx-slot)	32.59	32.59	32.27
GPRS 31 (GMSK, 2Tx-slot)	31.56	31.40	31.16
GPRS 32 (GMSK, 3Tx-slot)	29.74	29.48	29.25
GPRS 33 (GMSK, 4Tx-slot)	28.51	28.34	28.11
EDGE 8 (8PSK, 1Tx-slot)	26.89	26.73	26.46
EDGE 10 (8PSK, 2Tx-slot)	25.76	25.53	25.28
EDGE 11 (8PSK, 3Tx-slot)	23.78	23.60	23.32
EDGE 12 (8PSK, 4Tx-slot)	22.85	22.64	22.40
EDGE 30 (8PSK, 1Tx-slot)	27.00	26.85	26.59
EDGE 31 (8PSK, 2Tx-slot)	25.62	25.45	25.17
EDGE 32 (8PSK, 3Tx-slot)	23.74	23.60	23.31
EDGE 33 (8PSK, 4Tx-slot)	22.83	22.66	22.37
DTM (GMSK, 2Tx-slot)	31.45	31.28	31.12
DTM (GMSK, 3Tx-slot)	29.68	29.50	29.16
DTM (8PSK, 2Tx-slot)	25.64	25.47	25.19
DTM (8PSK, 3Tx-slot)	23.78	23.61	23.34

Band	WCDMA V		
	4132	4182	4233
Channel	826.4	836.4	846.6
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	24.25	24.10	24.24
HSDPA Subtest-1	23.09	23.03	23.15
HSDPA Subtest-2	23.09	23.06	23.26
HSDPA Subtest-3	22.70	22.56	22.67
HSDPA Subtest-4	22.70	22.57	22.78
HSUPA Subtest-1	23.12	22.98	23.26
HSUPA Subtest-2	21.14	21.14	21.26
HSUPA Subtest-3	22.15	22.05	22.23
HSUPA Subtest-4	21.13	21.12	21.26
HSUPA Subtest-5	23.19	23.06	23.15

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20407	Mid Ch 20525	High Ch 20643		Low Ch 20407	Mid Ch 20525	High Ch 20643	
			824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz	
5 / 1.4M	1	0	23.33	23.12	23.17	0	22.69	22.87	22.94	1
	1	2	23.25	23.26	22.98	0	22.53	22.80	22.38	1
	1	5	23.30	23.35	23.12	0	22.65	22.43	22.73	1
	3	0	23.30	23.34	23.25	0	22.66	22.58	22.35	1
	3	1	23.28	23.22	23.14	0	22.37	22.41	22.47	2
	3	3	23.14	23.11	23.08	0	22.25	22.45	22.35	1
	6	0	22.11	22.18	21.95	1	20.79	21.12	20.70	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20415	Mid Ch 20525	High Ch 20635		Low Ch 20415	Mid Ch 20525	High Ch 20635	
			825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz	
5 / 3M	1	0	23.39	23.20	23.23	0	22.78	22.93	23.00	1
	1	7	23.28	23.32	23.06	0	22.63	22.85	22.47	1
	1	14	23.34	23.34	23.20	0	22.75	22.52	22.80	1
	8	0	22.30	22.20	22.05	1	21.30	21.02	20.90	2
	8	3	22.27	22.18	21.99	1	21.22	21.28	21.00	2
	8	7	22.13	22.17	22.08	1	20.88	21.07	21.14	2
	15	0	22.17	22.23	22.06	1	20.93	21.24	20.85	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20425	Mid Ch 20525	High Ch 20625		Low Ch 20425	Mid Ch 20525	High Ch 20625	
			826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz	
5 / 5M	1	0	23.44	23.27	23.29	0	22.83	22.96	23.05	1
	1	12	23.35	23.37	23.15	0	22.68	22.91	22.54	1
	1	24	23.40	23.40	23.27	0	22.80	22.58	22.86	1
	12	0	22.40	22.35	22.18	1	21.38	21.14	21.05	2
	12	6	22.38	22.33	22.14	1	21.30	21.36	21.12	2
	12	13	22.28	22.32	22.23	1	21.02	21.17	21.22	2
	25	0	22.32	22.37	22.21	1	21.07	21.32	21.00	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 20450	Mid Ch 20525	High Ch 20600		Low Ch 20450	Mid Ch 20525	High Ch 20600	
			829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz	
5 / 10M	1	0	23.49	23.36	23.38	0	22.91	23.03	23.10	1
	1	24	23.43	23.44	23.25	0	22.78	22.98	22.65	1
	1	49	23.46	23.46	23.36	0	22.89	22.69	22.93	1
	25	0	22.50	22.45	22.33	1	21.49	21.27	21.19	2
	25	12	22.48	22.44	22.29	1	21.43	21.47	21.25	2
	25	25	22.40	22.43	22.36	1	21.17	21.30	21.35	2
	50	0	22.43	22.47	22.34	1	21.20	21.45	21.15	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 26797	Mid Ch 26915	High Ch 27033		Low Ch 26797	Mid Ch 26915	High Ch 27033	
			824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz	
26 / 1.4M	1	0	23.23	23.21	23.11	0	22.63	22.20	22.44	1
	1	2	23.65	23.59	23.43	0	22.32	22.89	22.56	1
	1	5	23.27	22.91	23.29	0	22.51	22.14	22.53	1
	3	0	23.22	23.20	23.11	0	22.41	22.45	22.42	1
	3	1	23.15	23.17	23.16	0	22.35	22.25	22.31	1
	3	3	23.06	23.02	23.01	0	22.11	22.21	22.25	1
	6	0	22.28	22.24	21.89	1	21.17	21.19	21.13	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 26805	Mid Ch 26915	High Ch 27025		Low Ch 26805	Mid Ch 26915	High Ch 27025	
			825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz	
26 / 3M	1	0	23.28	23.25	23.18	0	22.66	22.26	22.44	1
	1	7	23.68	23.63	23.49	0	22.35	22.92	22.62	1
	1	14	23.31	22.99	23.34	0	22.52	22.20	22.58	1
	8	0	22.26	22.37	22.02	1	21.11	21.07	20.86	2
	8	3	22.41	22.23	22.10	1	21.11	21.35	20.94	2
	8	7	22.18	22.11	22.13	1	20.94	21.03	20.98	2
	15	0	22.37	22.32	22.05	1	21.23	21.26	21.17	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 26815	Mid Ch 26915	High Ch 27015		Low Ch 26815	Mid Ch 26915	High Ch 27015	
			826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz	
26 / 5M	1	0	23.33	23.31	23.24	0	22.72	22.39	22.56	1
	1	12	23.75	23.69	23.54	0	22.47	22.99	22.68	1
	1	24	23.37	23.08	23.40	0	22.63	22.32	22.65	1
	12	0	22.38	22.45	22.15	1	21.26	21.24	21.01	2
	12	6	22.50	22.35	22.22	1	21.26	21.47	21.10	2
	12	13	22.30	22.24	22.26	1	21.10	21.21	21.14	2
	25	0	22.45	22.43	22.18	1	21.37	21.38	21.31	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 26840	Mid Ch 26915	High Ch 26990		Low Ch 26840	Mid Ch 26915	High Ch 26990	
			829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz	
26 / 10M	1	0	23.41	23.39	23.32	0	22.79	22.48	22.67	1
	1	24	23.80	23.76	23.62	0	22.56	23.04	22.75	1
	1	49	23.45	23.14	23.48	0	22.72	22.43	22.73	1
	25	0	22.47	22.55	22.30	1	21.38	21.36	21.16	2
	25	12	22.58	22.45	22.35	1	21.38	21.57	21.24	2
	25	25	22.42	22.37	22.38	1	21.24	21.34	21.29	2
	50	0	22.55	22.52	22.33	1	21.48	21.49	21.44	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 26865	Mid Ch 26915	High Ch 26965		Low Ch 26865	Mid Ch 26915	High Ch 26965	
			831.5 MHz	836.5 MHz	841.5 MHz		831.5 MHz	836.5 MHz	841.5 MHz	
26 / 15M	1	0	23.49	23.48	23.41	0	22.84	22.57	22.72	1
	1	37	23.85	23.81	23.67	0	22.64	23.09	22.80	1
	1	74	23.52	23.25	23.53	0	22.77	22.52	22.78	1
	36	0	22.60	22.66	22.45	1	21.50	21.49	21.31	2
	36	19	22.69	22.59	22.50	1	21.50	21.68	21.38	2
	36	39	22.56	22.51	22.52	1	21.38	21.47	21.42	2
	75	0	22.66	22.65	22.48	1	21.59	21.60	21.55	2

**ERP Power (dBm)**

GSM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	128	824.2	-2.35	31.208	26.71	468.60	H
	189	836.4	-2.55	31.3	26.60	457.09	
	251	848.8	-2.68	31.222	26.39	435.71	
	128	824.2	-9.65	31.504	19.70	93.41	V
	189	836.4	-9.56	31.117	19.41	87.24	
	251	848.8	-9.90	31.922	19.87	97.10	

EDGE							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	128	824.2	-7.56	31.208	21.50	141.19	H
	189	836.4	-7.41	31.3	21.74	149.28	
	251	848.8	-7.49	31.222	21.58	143.95	
	128	824.2	-15.33	31.504	14.02	25.26	V
	189	836.4	-14.58	31.117	14.39	27.46	
	251	848.8	-14.91	31.922	14.86	30.63	

WCDMA							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	4132	826.4	-10.65	31.208	18.41	69.31	H
	4182	836.4	-10.45	31.3	18.70	74.13	
	4233	846.6	-10.84	31.222	18.23	66.56	
	4132	826.4	-17.51	31.504	11.84	15.29	V
	4182	836.4	-17.36	31.117	11.61	14.48	
	4233	846.6	-17.80	31.922	11.97	15.75	

LTE Band 5							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	20407	824.7	-11.14	31.208	17.92	61.92	H
	20525	836.5	-11.36	31.3	17.79	60.12	
	20643	848.3	-11.15	31.222	17.92	61.97	
	20407	824.7	-18.56	31.504	10.79	12.01	V
	20525	836.5	-18.26	31.117	10.71	11.77	
	20643	848.3	-18.82	31.922	10.95	12.45	
Channel Bandwidth: 1.4 MHz / 16QAM							
X	20407	824.7	-12.65	31.208	16.41	43.73	H
	20525	836.5	-12.94	31.3	16.21	41.78	
	20643	848.3	-12.72	31.222	16.35	43.17	
	20407	824.7	-19.50	31.504	9.85	9.67	V
	20525	836.5	-19.72	31.117	9.25	8.41	
	20643	848.3	-19.88	31.922	9.89	9.75	

LTE Band 5							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	20415	825.5	-11.26	31.208	17.80	60.23	H
	20525	836.5	-11.55	31.3	17.60	57.54	
	20635	847.5	-11.61	31.222	17.46	55.74	
	20415	825.5	-18.37	31.504	10.98	12.54	V
	20525	836.5	-18.64	31.117	10.33	10.78	
	20635	847.5	-18.85	31.922	10.92	12.37	
Channel Bandwidth: 3 MHz / 16QAM							
X	20415	825.5	-12.48	31.208	16.58	45.48	H
	20525	836.5	-12.72	31.3	16.43	43.95	
	20635	847.5	-12.59	31.222	16.48	44.48	
	20415	825.5	-19.43	31.504	9.92	9.83	V
	20525	836.5	-19.26	31.117	9.71	9.35	
	20635	847.5	-19.86	31.922	9.91	9.80	

LTE Band 5							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	20425	826.5	-11.66	31.208	17.40	54.93	H
	20525	836.5	-11.75	31.3	17.40	54.95	
	20625	846.5	-11.84	31.222	17.23	52.87	
	20425	826.5	-18.54	31.504	10.81	12.06	V
	20525	836.5	-18.62	31.117	10.35	10.83	
	20625	846.5	-18.79	31.922	10.98	12.54	
Channel Bandwidth: 5 MHz / 16QAM							
X	20425	826.5	-12.36	31.208	16.70	46.75	H
	20525	836.5	-12.56	31.3	16.59	45.60	
	20625	846.5	-12.78	31.222	16.29	42.58	
	20425	826.5	-19.59	31.504	9.76	9.47	V
	20525	836.5	-19.43	31.117	9.54	8.99	
	20625	846.5	-19.89	31.922	9.88	9.73	

LTE Band 5							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	20450	829.0	-11.54	31.208	17.52	56.47	H
	20525	836.5	-11.36	31.3	17.79	60.12	
	20600	844.0	-11.42	31.222	17.65	58.24	
	20450	829.0	-18.71	31.504	10.64	11.60	V
	20525	836.5	-18.55	31.117	10.42	11.01	
	20600	844.0	-18.95	31.922	10.82	12.08	
Channel Bandwidth: 10 MHz / 16QAM							
X	20450	829.0	-12.69	31.208	16.37	43.33	H
	20525	836.5	-12.58	31.3	16.57	45.39	
	20600	844.0	-12.69	31.222	16.38	43.47	
	20450	829.0	-19.75	31.504	9.60	9.13	V
	20525	836.5	-19.89	31.117	9.08	8.09	
	20600	844.0	-20.21	31.922	9.56	9.04	

LTE Band 26							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	26797	824.7	-12.01	31.208	17.05	50.68	H
	26915	836.5	-11.86	31.3	17.29	53.58	
	27033	848.3	-11.48	31.222	17.59	57.44	
	26797	824.7	-19.25	31.504	10.10	10.24	V
	26915	836.5	-18.85	31.117	10.12	10.27	
	27033	848.3	-18.79	31.922	10.98	12.54	
Channel Bandwidth: 1.4 MHz / 16QAM							
X	26797	824.7	-12.64	31.208	16.42	43.83	H
	26915	836.5	-12.59	31.3	16.56	45.29	
	27033	848.3	-12.78	31.222	16.29	42.58	
	26797	824.7	-19.58	31.504	9.77	9.49	V
	26915	836.5	-19.47	31.117	9.50	8.91	
	27033	848.3	-19.82	31.922	9.95	9.89	

LTE Band 26							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	26805	825.5	-11.84	31.208	17.22	52.70	H
	26915	836.5	-11.96	31.3	17.19	52.36	
	27025	847.5	-11.58	31.222	17.49	56.13	
	26805	825.5	-18.75	31.504	10.60	11.49	V
	26915	836.5	-18.53	31.117	10.44	11.06	
	27025	847.5	-19.36	31.922	10.41	11.00	
Channel Bandwidth: 3 MHz / 16QAM							
X	26805	825.5	-12.84	31.208	16.22	41.86	H
	26915	836.5	-12.69	31.3	16.46	44.26	
	27025	847.5	-12.57	31.222	16.50	44.69	
	26805	825.5	-19.63	31.504	9.72	9.38	V
	26915	836.5	-19.72	31.117	9.25	8.41	
	27025	847.5	-19.95	31.922	9.82	9.60	

LTE Band 26							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	26815	826.5	-11.76	31.208	17.30	53.68	H
	26915	836.5	-11.59	31.3	17.56	57.02	
	27015	846.5	-11.81	31.222	17.26	53.24	
	26815	826.5	-18.69	31.504	10.66	11.65	V
	26919	836.5	-18.81	31.117	10.16	10.37	
	27015	846.5	-19.67	31.922	10.10	10.24	
Channel Bandwidth: 5 MHz / 16QAM							
X	26815	826.5	-12.64	31.208	16.42	43.83	H
	26915	836.5	-12.71	31.3	16.44	44.06	
	27015	846.5	-12.58	31.222	16.49	44.59	
	26815	826.5	-19.74	31.504	9.61	9.15	V
	26919	836.5	-19.69	31.117	9.28	8.47	
	27015	846.5	-19.84	31.922	9.93	9.84	

LTE Band 26							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	26840	829.0	-11.81	31.208	17.25	53.06	H
	26915	836.5	-11.76	31.3	17.39	54.83	
	26990	844.0	-11.65	31.222	17.42	55.23	
	26840	829.0	-18.57	31.504	10.78	11.98	V
	26919	836.5	-18.79	31.117	10.18	10.42	
	26990	844.0	-19.69	31.922	10.08	10.19	
Channel Bandwidth: 10 MHz / 16QAM							
X	26840	829.0	-12.42	31.208	16.64	46.11	H
	26915	836.5	-12.76	31.3	16.39	43.55	
	26990	844.0	-12.69	31.222	16.38	43.47	
	26840	829.0	-19.57	31.504	9.78	9.51	V
	26919	836.5	-19.14	31.117	9.83	9.61	
	26990	844.0	-19.92	31.922	9.85	9.66	

LTE Band 26							
Channel Bandwidth: 15 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	ERP (dBm)	ERP (mW)	Polarization (H/V)
X	26865	831.5	-11.94	31.208	17.12	51.50	H
	26915	836.5	-11.65	31.3	17.50	56.23	
	26965	841.5	-11.73	31.222	17.34	54.23	
	26865	831.5	-18.84	31.504	10.51	11.26	V
	26915	836.5	-18.65	31.117	10.32	10.76	
	26965	841.5	-19.42	31.922	10.35	10.84	
Channel Bandwidth: 15 MHz / 16QAM							
X	26865	831.5	-12.96	31.208	16.10	40.72	H
	26915	836.5	-12.75	31.3	16.40	43.65	
	26965	841.5	-12.58	31.222	16.49	44.59	
	26865	831.5	-19.36	31.504	9.99	9.99	V
	26915	836.5	-19.75	31.117	9.22	8.35	
	26965	841.5	-19.92	31.922	9.85	9.66	

## 4.2 Frequency Stability Measurement

### 4.2.1 Limits of Frequency Stability Measurement


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

### 4.2.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the  $\pm 0.5$  °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

**NOTE:** The frequency error was recorded frequency error from the communication simulator.

### 4.2.3 Test Setup



#### 4.2.4 Test Results

##### Frequency Error vs. Voltage

Voltage (Volts)	Frequency Error (ppm)							Limit (ppm)
	GSM	EDGE	WCDMA	LTE Band 5				
				1.4 MHz	3 MHz	5 MHz	10 MHz	
3.8	0.002	0.004	0.001	0.003	0.004	0.003	0.002	2.5
3.6	0.005	0.004	0.005	0.003	0.002	0.002	0.001	2.5
4.2	0.003	0.002	0.004	0.004	0.002	0.003	0.005	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 3.6 Vdc to 4.2 Vdc.

##### Frequency Error vs. Temperature

Temp. (°C)	Frequency Error (ppm)							Limit (ppm)
	GSM	EDGE	WCDMA	LTE Band 5				
				1.4 MHz	3 MHz	5 MHz	10 MHz	
-30	0.003	0.005	0.004	0.004	0.003	0.004	0.001	2.5
-20	0.002	0.002	-0.004	0.005	0.002	0.002	-0.002	2.5
-10	0.005	-0.002	-0.003	0.003	0.003	-0.003	-0.003	2.5
0	-0.005	-0.002	-0.004	0.004	-0.003	-0.002	-0.001	2.5
10	-0.002	-0.004	-0.004	0.004	-0.003	-0.004	-0.005	2.5
20	-0.002	-0.002	-0.002	-0.005	-0.001	-0.003	-0.002	2.5
30	-0.002	-0.001	0.003	-0.004	-0.004	-0.003	0.003	2.5
40	-0.003	0.001	0.004	-0.002	-0.005	0.005	0.002	2.5
50	0.001	0.004	0.001	-0.002	0.003	0.002	0.004	2.5
55	0.001	0.004	0.003	-0.002	0.002	0.003	0.003	2.5

## Frequency Error vs. Voltage

Voltage (Volts)	Frequency Error (ppm)					Limit (ppm)
	LTE Band 26					
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	
3.8	0.003	0.003	0.002	0.002	0.002	2.5
3.6	0.004	0.004	0.004	0.004	0.005	2.5
4.2	0.004	0.003	0.001	0.003	0.002	2.5

**Note:** The applicant defined the normal working voltage of the battery is from 3.6 Vdc to 4.2 Vdc.

## Frequency Error vs. Temperature


Temp. (°C)	Frequency Error (ppm)					Limit (ppm)
	LTE Band 26					
	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	
-30	0.003	0.002	0.002	0.003	0.003	2.5
-20	0.003	0.005	0.002	-0.001	0.004	2.5
-10	0.004	0.005	-0.005	-0.004	0.003	2.5
0	0.003	-0.003	-0.004	-0.004	-0.005	2.5
10	0.004	-0.002	-0.003	-0.003	-0.002	2.5
20	-0.002	-0.002	-0.002	-0.004	-0.003	2.5
30	-0.003	-0.004	-0.003	0.004	-0.003	2.5
40	-0.004	-0.002	0.001	0.003	-0.003	2.5
50	-0.001	0.005	0.003	0.004	0.002	2.5
55	-0.004	0.002	0.004	0.005	0.002	2.5

### 4.3 Occupied Bandwidth Measurement

#### 4.3.1 Test Procedure


The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

#### 4.3.2 Test Setup




### 4.3.3 Test Result

Channel	Frequency (MHz)	99 % Occupied Bandwidth (kHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)
		GSM	EDGE			WCDMA
128	824.2	243.53	246.63	4132	826.4	4.1306
189	836.4	243.20	244.14	4182	836.4	4.1258
251	848.8	247.06	244.75	4233	846.6	4.1326




LTE Band 5							
Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	1.0939	1.0903	20415	825.5	2.6957	2.6935
20525	836.5	1.0911	1.0897	20525	836.5	2.6942	2.6946
20643	848.3	1.0929	1.0908	20635	847.5	2.6936	2.6941



### LTE Band 5

Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	4.4847	4.4836	20450	829.0	8.9538	8.9590
20525	836.5	4.4860	4.4816	20525	836.5	8.9511	8.9485
20625	846.5	4.4831	4.4816	20600	844.0	8.9511	8.9537


### Spectrum Plot of Worst Value



### LTE Band 26

Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
26797	824.7	1.0897	1.0904	26805	825.5	2.6939	2.6921
26915	836.5	1.0917	1.0896	26915	836.5	2.6971	2.6931
27033	848.3	1.0927	1.0893	27025	847.5	2.6935	2.6924


### Spectrum Plot of Worst Value



### LTE Band 26

Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
26815	826.5	4.4876	4.4838	26840	829.0	8.9507	8.9582
26915	836.5	4.4821	4.4793	26915	836.5	8.9470	8.9498
27015	846.5	4.4835	4.4795	26990	844.0	8.9527	8.9539

### Spectrum Plot of Worst Value




**LTE Band 26**

**Channel Bandwidth: 15 MHz**

Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM
26865	831.5	13.433	13.414
26915	836.5	13.412	13.407
26965	841.5	13.424	13.411

**Spectrum Plot of Worst Value**




## 4.4 Band Edge Measurement

### 4.4.1 Limits of Band Edge Measurement

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.


### 4.4.2 Test Setup





### 4.4.3 Test Procedures

- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 10 kHz and VB of the spectrum is 30 kHz (GSM/GPRS/EDGE).
- c. The center frequency of spectrum is the band edge frequency and span is 5 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (WCDMA).
- d. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 13 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 1.4 MHz).
- e. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 30 kHz and VB of the spectrum is 100 kHz (LTE Bandwidth 3 MHz).
- f. The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (LTE Bandwidth 5 MHz/10 MHz).
- g. The center frequency of spectrum is the band edge frequency and span is 1MHz. RB of the spectrum is 150 kHz and VB of the spectrum is 470 kHz (LTE Bandwidth 15 MHz).
- h. Record the max trace plot into the test report.


### 4.4.4 Test Results




**LTE Band 5**  
**Channel Bandwidth: 1.4 MHz**




**LTE Band 5**  
**Channel Bandwidth: 3 MHz**





**LTE Band 5**  
**Channel Bandwidth: 5 MHz**




**LTE Band 5**  
**Channel Bandwidth: 10 MHz**




**LTE Band 26**  
**Channel Bandwidth: 1.4 MHz**





**LTE Band 26**  
**Channel Bandwidth: 3 MHz**



**LTE Band 26**  
**Channel Bandwidth: 5 MHz**








## 4.5 Peak to Average Ratio

### 4.5.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 4.5.2 Test Setup




### 4.5.3 Test Procedures

1. Set resolution/measurement bandwidth  $\geq$  signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

#### 4.5.4 Test Results


Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)
		GSM	EDGE			
128	824.2	0.23	3.19	4132	826.4	3.00
189	836.4	0.23	3.26	4182	836.4	3.07
251	848.8	0.24	3.25	4233	846.6	2.94



### LTE Band 5

Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20407	824.7	3.89	4.44	20415	825.5	3.86	4.54
20525	836.5	3.99	4.66	20525	836.5	3.94	4.71
20643	848.3	3.61	4.15	20635	847.5	3.73	4.37


### Spectrum Plot of Worst Value



### LTE Band 5

Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
20425	826.5	3.81	4.55	20450	829.0	3.81	4.50
20525	836.5	3.87	4.65	20525	836.5	3.83	4.58
20625	846.5	3.79	4.42	20600	844.0	3.75	4.46


### Spectrum Plot of Worst Value



### LTE Band 26

Channel Bandwidth: 1.4 MHz				Channel Bandwidth: 3 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
26797	824.7	3.80	4.66	26805	825.5	3.80	4.68
26915	836.5	3.93	4.84	26915	836.5	3.91	4.75
27033	848.3	3.45	4.33	27025	847.5	3.63	4.53


### Spectrum Plot of Worst Value



### LTE Band 26

Channel Bandwidth: 5 MHz				Channel Bandwidth: 10 MHz			
Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
26815	826.5	3.79	4.65	26840	829.0	3.75	4.63
26915	836.5	3.86	4.70	26915	836.5	3.79	4.70
27015	846.5	3.69	4.55	26990	844.0	3.79	4.61

### Spectrum Plot of Worst Value




**LTE Band 26**

**Channel Bandwidth: 15 MHz**

Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM
26865	831.5	3.72	4.54
26915	836.5	3.82	4.67
26965	841.5	3.82	4.68

**Spectrum Plot of Worst Value**




## 4.6 Conducted Spurious Emissions

### 4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit equal to  $-13$  dBm.


### 4.6.2 Test Setup



### 4.6.3 Test Procedure


- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9 kHz to 9 GHz. 20 dB attenuation pad is connected with spectrum. RBW=1 MHz and VBW=3 MHz is used for conducted emission measurement.

### 4.6.4 Test Results




**LTE Band 5  
Channel 20525**

**Channel Bandwidth: 1.4 MHz**



**Channel Bandwidth: 3 MHz**



**Channel Bandwidth: 5 MHz**




**Channel Bandwidth: 10 MHz**




## LTE Band 26 Channel 26915


### Channel Bandwidth: 1.4 MHz




### Channel Bandwidth: 3 MHz



### Channel Bandwidth: 5 MHz



### Channel Bandwidth: 10 MHz



### Channel Bandwidth: 15 MHz



## 4.7 Radiated Emission Measurement

### 4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB. The emission limit is equal to -13 dBm.

### 4.7.2 Test Procedure


- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15 dBi.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz.

### 4.7.3 Deviation from Test Standard

No deviation.

### 4.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results

GSM:




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2016-07-06



Site : 966 chamber 1  
 Condition: PART 22/24 Horizontal  
 Remark : GSM 850\_Link\_CH189  
 Tested by: Charles Hsiao

	Read	Limit	Over				
Freq	Level	Level	Line	Limit	Factor	Remark	
MHz	dBm	dBm	dBm	dB	dB		
1	92.91	-55.58	-45.07	-13.00	-42.58	-10.51	Peak
2	141.51	-56.68	-48.94	-13.00	-43.68	-7.74	Peak
3	190.65	-61.25	-55.47	-13.00	-48.25	-5.78	Peak
4	394.50	-69.91	-66.91	-13.00	-56.91	-3.00	Peak
5	538.00	-70.49	-67.98	-13.00	-57.49	-2.51	Peak
6	679.40	-68.30	-68.03	-13.00	-55.30	-0.27	Peak
7 pp	1672.80	-52.10	-60.01	-13.00	-39.10	7.91	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2016-07-06



Site : 966 chamber 1  
 Condition: PART 22/24 Vertical  
 Remark : GSM 850\_Link\_CH189  
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1 pp	61.32	-46.82	-32.89	-13.00	-33.82	-13.93	Peak
2	92.91	-57.33	-46.82	-13.00	-44.33	-10.51	Peak
3	145.56	-56.76	-48.93	-13.00	-43.76	-7.83	Peak
4	335.70	-70.71	-65.16	-13.00	-57.71	-5.55	Peak
5	395.20	-69.54	-66.54	-13.00	-56.54	-3.00	Peak
6	612.20	-67.87	-68.16	-13.00	-54.87	0.29	Peak
7	1672.80	-51.46	-59.37	-13.00	-38.46	7.91	Peak

EDGE:




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2016-07-06



Site : 966 chamber 1  
 Condition: PART 22/24 Horizontal  
 Remark : EDGE 850\_Link\_CH189  
 Tested by: Charles Hsiao


Freq	Level	Read Level	Limit	Over	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 1672.80	-57.32	-65.23	-13.00	-44.32	7.91	Peak



A D T

Data: 6

Date: 2016-07-06



Site : 966 chamber 1  
 Condition: PART 22/24 Vertical  
 Remark : EDGE 850\_Link\_CH189  
 Tested by: Charles Hsiao

	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 1672.80	-56.61	-64.52	-13.00	-43.61	7.91	Peak

WCDMA:




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 5

Date: 2016-07-06



Site : 966 chamber 1  
 Condition: PART 22/24 Horizontal  
 Remark : Band V\_Link\_CH4182  
 Tested by: Charles Hsiao


Freq	Level	Read Level	Limit	Over	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 1672.80	-58.60	-66.51	-13.00	-45.60	7.91	Peak



A D T

Data: 6

Date: 2016-07-06



Site : 966 chamber 1  
 Condition: PART 22/24 Vertical  
 Remark : Band V\_Link\_CH4182  
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	pp 1672.80	-58.12	-66.03	-13.00	-45.12	7.91	Peak

**LTE Band 5**  
**Channel Bandwidth: 10 MHz / QPSK**




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2016-07-06



Site : 966 chamber 1  
 Condition: PART 22/24 Horizontal  
 Remark : LTE\_Band 5\_Link\_CH20525  
 Tested by: Karl Lee


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	94.53	-57.48	-47.08	-13.00	-44.48	-10.40	Peak
2	pp 123.96	-56.66	-48.65	-13.00	-43.66	-8.01	Peak
3	141.51	-57.23	-49.49	-13.00	-44.23	-7.74	Peak
4	315.40	-67.79	-62.01	-13.00	-54.79	-5.78	Peak
5	552.00	-70.23	-68.65	-13.00	-57.23	-1.58	Peak
6	669.60	-68.24	-68.01	-13.00	-55.24	-0.23	Peak
7	1673.00	-57.42	-65.33	-13.00	-44.42	7.91	Peak



A D T

Data: 10

Date: 2016-07-06



Site : 966 chamber 1  
 Condition: PART 22/24 Vertical  
 Remark : LTE\_Band 5\_Link\_CH20525  
 Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	54.30	-57.00	-42.94	-13.00	-44.00	-14.06	Peak
2	92.37	-56.79	-46.23	-13.00	-43.79	-10.56	Peak
3	140.43	-60.79	-53.07	-13.00	-47.79	-7.72	Peak
4	395.20	-69.47	-66.47	-13.00	-56.47	-3.00	Peak
5	542.20	-72.42	-70.19	-13.00	-59.42	-2.23	Peak
6	626.90	-68.97	-69.10	-13.00	-55.97	0.13	Peak
7 pp	1673.00	-56.49	-64.40	-13.00	-43.49	7.91	Peak

LTE Band 26  
Channel Bandwidth: 15 MHz / QPSK




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2016-07-07



Site : 966 chamber 1  
Condition: PART 22/24 Horizontal  
Remark : LTE\_Band 26\_Link\_CH26915  
Tested by: Charles Hsiao

	Read	Limit	Over				
Freq	Level	Level	Line	Limit	Factor	Remark	
MHz	dBm	dBm	dBm	dB	dB		
1	118.29	-59.04	-50.66	-13.00	-46.04	-8.38	Peak
2	142.32	-56.82	-49.06	-13.00	-43.82	-7.76	Peak
3	177.42	-60.32	-54.44	-13.00	-47.32	-5.88	Peak
4	305.60	-63.25	-57.36	-13.00	-50.25	-5.89	Peak
5	401.50	-69.90	-67.12	-13.00	-56.90	-2.78	Peak
6	689.20	-68.65	-68.32	-13.00	-55.65	-0.33	Peak
7 pp	1673.00	-55.18	-63.09	-13.00	-42.18	7.91	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2016-07-07



Site : 966 chamber 1  
 Condition: PART 22/24 Vertical  
 Remark : LTE\_Band 26\_Link\_CH26915  
 Tested by: Charles Hsiao

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	94.80	-53.33	-42.93	-13.00	-40.33	-10.40	Peak
2	144.48	-60.97	-53.16	-13.00	-47.97	-7.81	Peak
3	pp 176.61	-50.90	-44.91	-13.00	-37.90	-5.99	Peak
4	358.80	-74.00	-69.09	-13.00	-61.00	-4.91	Peak
5	397.30	-70.10	-67.26	-13.00	-57.10	-2.84	Peak
6	619.20	-67.87	-68.09	-13.00	-54.87	0.22	Peak
7	1673.00	-55.70	-63.61	-13.00	-42.70	7.91	Peak

## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---