

**MEASUREMENT REPORT  
FCC Part 15B****Applicant Name:**Sony Corporation  
1-7-1 Konan Minato-ku  
Tokyo, 108-0075  
Japan**Date of Testing:**

02/08/2023 - 04/18/2023

**Test Report Issue Date:**

04/19/2023

**Test Site/Location:**

Element lab, Columbia, MD, USA

**Test Report Serial No.:**

1M2302230018-08-R1.PY7

**FCC ID:****PY7-25682R****APPLICANT:****Sony Corporation****Application Type:**

Certification

**EUT Type:**

Portable Handset

**FCC Classification:**

Part 15 Class B Computing Device Peripheral (JBP)

**FCC Rule Part(s):**

FCC Part 15 Subpart B

**Test Procedure(s):**

ANSI C63.4-2014

Note: This revised Test Report (S/N: 1M2302230018-08-R1.PY7) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in ANSI C63.4-2014 (See Test Report). These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**RJ Ortanez Executive Vice  
President**

<b>FCC ID:</b> PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2302230018-08-R1.PY7	<b>Test Dates:</b> 02/08/2023 - 04/18/2023	<b>EUT Type:</b> Portable Handset	Page 1 of 20

# TABLE OF CONTENTS

1.0	INTRODUCTION.....	3
1.1	Scope.....	3
1.2	Element Test Location .....	3
1.3	Test Facility / Accreditations .....	3
2.0	PRODUCT INFORMATION .....	4
2.1	Equipment Description.....	4
2.2	Device Capabilities .....	4
2.3	Test Configuration .....	4
2.4	Software and Firmware.....	4
2.5	EMI Suppression Device(s)/Modifications.....	4
3.0	DESCRIPTION OF TESTS .....	5
3.1	Evaluation Procedure.....	5
3.2	AC Line Conducted Emissions .....	5
3.3	Radiated Emissions .....	6
3.4	Environmental Conditions .....	6
4.0	SAMPLE CALCULATIONS .....	7
4.1	Conducted Emission Measurement Sample Calculation .....	7
4.2	Radiated Emission Measurement Sample Calculation .....	7
5.0	MEASUREMENT UNCERTAINTY .....	8
6.0	TEST EQUIPMENT CALIBRATION DATA.....	9
7.0	TEST DATA .....	10
7.1	Summary .....	10
7.2	Test Support Equipment .....	10
7.3	Radiated Measurement Data .....	11
7.4	Line Conducted Measurement Data .....	16
8.0	CONCLUSION .....	20

<b>FCC ID:</b> PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2302230018-08-R1.PY7	<b>Test Dates:</b> 02/08/2023 - 04/18/2023	<b>EUT Type:</b> Portable Handset	Page 2 of 20

## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and Innovation, Science and Economic Development Canada.

### 1.2 Element Test Location

These measurement tests were conducted at the Element laboratory located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

### 1.3 Test Facility / Accreditations

**Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.**

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (2451B) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 3 of 20

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Sony Portable Handset FCC ID: PY7-25682R**. The test data contained in this report pertains only to the emissions due to the digital circuitry of the EUT.

**Test Device Serial No.:** 85463

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5GHZ), Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer

### 2.3 Test Configuration

The EUT was evaluated with two cases.

**Case#1:** The EUT was tested with a laptop PC connected via USB interface port. The EUT was exercised during testing by means of software installed on the PC. Since the EUT is a peripheral device, the host PC was populated with another USB device and an additional peripheral device with a non-USB interface, as shown in Table 7-2, thus satisfying the minimum system requirement of two different I/O interfaces. All equipment is placed on the test tabletop and arranged in a typical configuration in accordance with ANSI C63.4-2014 and manipulated to obtain worst case emissions.

**Case #2:** The EUT was tested with an AC charger and USB cable connected to the EUT. Also, on the audio port the headset was inserted into the EUT. Therefore, the EUT was tested with all ports populated and exercised.

For more information, please see Section 7.0 for test data and the test setup photos document for the test setup photographs.

### 2.4 Software and Firmware

The test was conducted with software/firmware version 0.621 installed on the EUT.

### 2.5 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added, and no modifications were made during testing.

FCC ID: PY7-25682R	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 4 of 20

## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2014) was used in the measurement of the EUT.

**Deviation from measurement procedure.....None**

### 3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1-meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground plane. Power cables for support equipment were routed down to the second LISN while ensuring that those cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst-case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.4. The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

FCC ID: PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2302230018-08-R1.PY7	<b>Test Dates:</b> 02/08/2023 - 04/18/2023	<b>EUT Type:</b> Portable Handset	Page 5 of 20

### 3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3-meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2014. A raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. . An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst-case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014. Additionally, radiated emissions below 30MHz are also validated on an Open Area Test Site to assert correlation with the chamber measurements per the requirements of KDB 414788 D01 v01r01.

### 3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 6 of 20

## 4.0 SAMPLE CALCULATIONS

### 4.1 Conducted Emission Measurement Sample Calculation

@ 20.3 MHz

<b>Class B limit</b>	= 60.0 dB $\mu$ V (Quasi-peak limit)
Reading	= - 57.8 dBm (calibrated quasi-peak level)
Convert to dB $\mu$ V	= - 57.8 + 107 = 49.2 dB $\mu$ V
Margin	= 49.2 - 60.0 = - 10.8 dB
	= <b>10.8 dB below limit</b>

### 4.2 Radiated Emission Measurement Sample Calculation

@ 66.7 MHz

<b>Class B limit</b>	= 100 $\mu$ V/m = 40.0 dB $\mu$ V/m
Reading	= - 76.0 dBm (calibrated level)
Convert to dB $\mu$ V	= - 76.0 + 107 = 31.0 dB $\mu$ V
Antenna Factor + Cable Loss	= 5.8 dB/m
Total	= 36.8 dB $\mu$ V/m
Margin	= 36.8 - 40.0 = - 3.2 dB
	= <b>3.2 dB below limit</b>

#### Note:

$$\text{Level [dB}\mu\text{V]} = 20 \log_{10} (\text{Level } [\mu\text{V/m}])$$

$$\text{Level [dB}\mu\text{V]} = \text{Level [dBm]} + 107$$

FCC ID: PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 7 of 20

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ( $\pm$ dB)
Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07

FCC ID: PY7-25682R	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 8 of 20

## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance with the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	ETS-001	EMC Cable and Switch System	1/11/2023	Annual	1/11/2024	ETS-001
-	ETS-002	EMC Cable and Switch System	1/11/2023	Annual	1/11/2024	ETS-002
Agilent	N9038A	MXE EMI Receiver	1/21/2022	Annual	7/21/2023	MY51210133
ETS-Lindgren	3816/2NM	LISN	8/11/2022	Biennial	8/11/2024	114451
Pasternack	NMLC-2	Line Conducted Emissions Cable (NM)	1/11/2023	Annual	1/11/2024	NMLC-2
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	8/25/2022	Annual	8/25/2023	100348
Sunol Sciences	JB5	Bi-Log Antenna (30M-5GHz)	8/30/2022	Biennial	8/30/2024	A051107

**Table 6-1. Annual Test Equipment Calibration Schedule**

**Note:**

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 9 of 20

## 7.0 TEST DATA

### 7.1 Summary

Test Date(s): 02/08/2023 - 04/18/2023

Test Engineer: Jon Snyder

FCC Part 15 Section	Description	Result
15.107	Conducted Emissions	PASS
15.109	Radiated Emissions	PASS

**Table 7-1. Summary of Test Results**

### 7.2 Test Support Equipment

Case #1	Lenovo Laptop	Model:	Thinkpad T15p	S/N:	PF-19CPWG	Length:	N/A
	Lenovo AC Adapter	Model:	ADL135SCC2A	S/N:	N/A	Length:	N/A
	Cisco Router	Model:	Linksys E900	S/N:	12310C65201062	Length:	N/A
	Lenovo Monitor	Model:	ThinkVision S24e-10	S/N:	V5WR4107	Length:	N/A
	Keyboard	Model:	KU-0833	S/N:	9H09801365B	Length:	N/A
	USB Cable	Model:	XQZ-UB1	S/N:	N/A	Length:	N/A
	Sony Headset	Model:	MDR-EX015AP	S/N:	N/A	Length:	N/A

Case #2	Sony AC Charger	Model:	XQZ-UC1	S/N:	0020W51300113	Length:	N/A
	USB Cable	Model:	XQZ-UB1	S/N:	N/A	Length:	N/A
	Sony Headset	Model:	MDR-EX015AP	S/N:	N/A	Length:	N/A

**Table 7-2. Test Support Equipment Used**

**Note:** See test setup photographs for actual system test setup.

FCC ID: PY7-25682R	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 10 of 20

### 7.3 Radiated Measurement Data

#### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

**All out of band emissions must not exceed the limits shown in FCC Part 15.109.**

Frequency [MHz]	Field Strength Limit [ $\mu\text{V/m}$ ]
30 – 88	100
88 – 216	150
216 – 960	200
> 960	500

**Table 7-3. 3-Meter Radiated Limits (Section 15.109)**

#### Test Procedures Used

ANSI C63.4-2014

#### Test Settings


##### Quasi-Peak Field Strength Measurements

1. Analyzer frequency set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 11 of 20

**Test Setup**

The EUT and measurement equipment were set up as shown test setup photos provided.




**Figure 7-1. Radiated Test Setup < 1GHz**

<b>FCC ID:</b> PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2302230018-08-R1.PY7	<b>Test Dates:</b> 02/08/2023 - 04/18/2023	<b>EUT Type:</b> Portable Handset	Page 12 of 20

**Test Notes**

1. All modes of operation were investigated, and the worst-case emissions are reported.
2. Radiated emissions were measured from 30MHz – 30GHz to ensure that the provisions of 15.33(b)(1) are satisfied with respect to the upper frequency scanning range.
3. The radiated limits for unintentional radiators at 3 meters are used in the table above, as specified in 15.109(a).
4. All readings are calibrated by a signal generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
5.  $AFCL (dB/m) = Antenna\ Factor (dB/m) + Cable\ Loss (dB)$
6.  $Level (dB\mu V/m) = Analyzer\ Reading (dBm) + AFCL (dB/m) + 107$
7.  $Margin (dB) = Field\ strength (dB\mu V/m) - Limit (dB\mu V/m)$
8. Measurements are made using a CISPR quasi-peak detector with a 120kHz resolution bandwidth. Above 1GHz, peak measurements are made using a peak detector with a resolution bandwidth of 1MHz and a video bandwidth of 3MHz and average measurements are made with a RMS detector using a resolution bandwidth of 1MHz and a video bandwidth of 3MHz.
9. Calibrated linearly polarized broadband and horn antennas were used for measurements below and above 1GHz, respectively. For measurements made below 1GHz, the results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antennas was found to be less than 2:1.
10. Calibrated low-loss microwaves cables and broadband amplifiers are used.

FCC ID: PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 13 of 20




**Plot 7-1. Radiated Spurious Plot Below 1GHz Case #1**

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
50.00	Quasi-Peak	H	-	-	-99.26	14.71	22.45	40.00	-17.55
125.00	Quasi-Peak	H	-	-	-100.20	20.41	27.21	43.52	-16.31
250.00	Quasi-Peak	H	-	-	-98.87	18.69	26.82	46.02	-19.20
350.00	Quasi-Peak	H	-	-	-100.12	22.02	28.90	46.02	-17.12
500.00	Quasi-Peak	H	-	-	-97.99	25.84	34.85	46.02	-11.17
700.00	Quasi-Peak	H	-	-	-98.54	28.46	36.92	46.02	-9.10

**Table 7-4. Radiated Measurements at 3-meters Case #1 [PC as host]**

FCC ID: PY7-25682R	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 14 of 20



**Plot 7-2. Radiated Spurious Plot Below 1GHz Case #2**

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBµV/m]	Limit [dBµV/m]	Margin [dB]
43.00	Quasi-Peak	H	-	-	-100.31	18.27	24.96	40.00	-15.04
100.00	Quasi-Peak	H	-	-	-99.45	17.25	24.80	43.52	-18.72
200.00	Quasi-Peak	H	-	-	-99.62	20.36	27.74	43.52	-15.79
300.00	Quasi-Peak	H	-	-	-98.62	21.05	29.43	46.02	-16.59
500.00	Quasi-Peak	H	-	-	-99.22	25.84	33.62	46.02	-12.40
700.00	Quasi-Peak	H	-	-	-98.77	28.46	36.69	46.02	-9.33

**Table 7-5. Radiated Measurements at 3-meters Case #2 [Audio Port/Charger Port Occupied]**

FCC ID: PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 15 of 20

## 7.4 Line Conducted Measurement Data

### Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst-case emissions are reported in this section.

**All conducted emissions must not exceed the limits shown in the table below per FCC Part 15.107.**

Frequency of emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

**Table 7-6. Conducted Limits**

\*Decreases with the logarithm of the frequency.

### Test Procedures Used

ANSI C63.4-2014

### Test Settings

#### Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

#### Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: PY7-25682R	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset	Page 16 of 20




**Test Setup**

The EUT and measurement equipment were set up as shown in the test setup photos provided.


**Test Notes**

1. All Modes of operation were investigated, and the worst-case emissions are reported.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.107.
3. L1 = Phase; N = Neutral
4.  $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
5.  $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Reading (dB}\mu\text{V)} + \text{Factor (dB)}$
6.  $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
7. Traces shown in plot are made using a peak detector.
8. Deviations to the Specifications: None.

<b>FCC ID:</b> PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2302230018-08-R1.PY7	<b>Test Dates:</b> 02/08/2023 - 04/18/2023	<b>EUT Type:</b> Portable Handset	Page 17 of 20




Plot 7-3. Line Conducted Plot (L1) \_ Case #1




Plot 7-4. Line Conducted Plot (N) \_ Case #1

FCC ID: PY7-25682R		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset		Page 18 of 20



Plot 7-5. Line Conducted Plot (L1) \_ Case #2



Plot 7-6. Line Conducted Plot (N) \_ Case #2

FCC ID: PY7-25682R		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1M2302230018-08-R1.PY7	Test Dates: 02/08/2023 - 04/18/2023	EUT Type: Portable Handset		Page 19 of 20

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Sony Portable Handset FCC ID: PY7-25682R** has been tested to comply with the requirements specified in §15.107 and §15.109 of the FCC rules.

<b>FCC ID:</b> PY7-25682R	<b>MEASUREMENT REPORT (CERTIFICATION)</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2302230018-08-R1.PY7	<b>Test Dates:</b> 02/08/2023 - 04/18/2023	<b>EUT Type:</b> Portable Handset	Page 20 of 20