

### #01\_HAC\_E\_GSM850\_GSM Voice\_Ch128

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 824.2 MHz; Duty Cycle: 1:8.3  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.5 °C

#### DASY5 Configuration

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2016/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1399; Calibrated: 2016/11/17
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

#### Ch128/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm  
 Reference Value = 51.99 V/m; Power Drift = -0.05 dB  
 Applied MIF = 3.63 dB  
 RF audio interference level = 36.38 dBV/m


#### Emission category: M4

MIF scaled E-field

Grid 1 M4 <b>34.67 dBV/m</b>	Grid 2 M4 <b>35.58 dBV/m</b>	Grid 3 M4 <b>35.4 dBV/m</b>
Grid 4 M4 <b>35.26 dBV/m</b>	Grid 5 M4 <b>36.02 dBV/m</b>	Grid 6 M4 <b>35.75 dBV/m</b>
Grid 7 M4 <b>35.89 dBV/m</b>	Grid 8 M4 <b>36.38 dBV/m</b>	Grid 9 M4 <b>35.93 dBV/m</b>

#### Cursor:

Total = 36.38 dBV/m  
 E Category: M4  
 Location: 0, 25, 8.7 mm



0 dB = 65.89 V/m = 36.38 dBV/m

## #02\_HAC\_E\_GSM850\_GSM Voice\_Ch189

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 836.4 MHz; Duty Cycle: 1:8.3  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.5 °C

### DASY5 Configuration

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2016/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1399; Calibrated: 2016/11/17
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

### Ch189/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm  
 Reference Value = 49.31 V/m; Power Drift = -0.07 dB  
 Applied MIF = 3.63 dB  
 RF audio interference level = 36.00 dBV/m


### Emission category: M4

MIF scaled E-field

Grid 1 <b>M4</b> <b>34.23 dBV/m</b>	Grid 2 <b>M4</b> <b>35.22 dBV/m</b>	Grid 3 <b>M4</b> <b>35.03 dBV/m</b>
Grid 4 <b>M4</b> <b>34.84 dBV/m</b>	Grid 5 <b>M4</b> <b>35.64 dBV/m</b>	Grid 6 <b>M4</b> <b>35.38 dBV/m</b>
Grid 7 <b>M4</b> <b>35.46 dBV/m</b>	Grid 8 <b>M4</b> <b>36 dBV/m</b>	Grid 9 <b>M4</b> <b>35.56 dBV/m</b>

#### Cursor:

Total = 36.00 dBV/m  
 E Category: M4  
 Location: -0.5, 25, 8.7 mm



0 dB = 63.07 V/m = 36.00 dBV/m

### #03\_HAC\_E\_GSM850\_GSM Voice\_Ch251

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 848.8 MHz; Duty Cycle: 1:8.3  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.5 °C

#### DASY5 Configuration

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2016/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1399; Calibrated: 2016/11/17
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

#### Ch251/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid

**Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 47.69 V/m; Power Drift = -0.05 dB

Applied MIF = 3.63 dB

RF audio interference level = 35.60 dBV/m

**Emission category: M4**

MIF scaled E-field


Grid 1 <b>M4</b> <b>33.6 dBV/m</b>	Grid 2 <b>M4</b> <b>34.92 dBV/m</b>	Grid 3 <b>M4</b> <b>34.83 dBV/m</b>
Grid 4 <b>M4</b> <b>34.26 dBV/m</b>	Grid 5 <b>M4</b> <b>35.34 dBV/m</b>	Grid 6 <b>M4</b> <b>35.13 dBV/m</b>
Grid 7 <b>M4</b> <b>34.85 dBV/m</b>	Grid 8 <b>M4</b> <b>35.6 dBV/m</b>	Grid 9 <b>M4</b> <b>35.32 dBV/m</b>

**Cursor:**

Total = 35.60 dBV/m

E Category: M4

Location: -3, 23, 8.7 mm



0 dB = 60.27 V/m = 35.60 dBV/m

### #04\_HAC\_E\_GSM850\_GSM Voice\_Ch128

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 824.2 MHz; Duty Cycle: 1:8.3

Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C

#### DASY5 Configuration

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2016/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1399; Calibrated: 2016/11/17
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

#### Ch128/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid

**Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 56.87 V/m; Power Drift = -0.01 dB

Applied MIF = 3.63 dB

RF audio interference level = 36.70 dBV/m

**Emission category: M4**

MIF scaled E-field


Grid 1 <b>M4</b> <b>34.19 dBV/m</b>	Grid 2 <b>M4</b> <b>36.19 dBV/m</b>	Grid 3 <b>M4</b> <b>36.27 dBV/m</b>
Grid 4 <b>M4</b> <b>35.15 dBV/m</b>	Grid 5 <b>M4</b> <b>36.67 dBV/m</b>	Grid 6 <b>M4</b> <b>36.69 dBV/m</b>
Grid 7 <b>M4</b> <b>35.52 dBV/m</b>	Grid 8 <b>M4</b> <b>36.7 dBV/m</b>	Grid 9 <b>M4</b> <b>36.7 dBV/m</b>

**Cursor:**

Total = 36.70 dBV/m

E Category: M4

Location: 1, 27.5, 8.7 mm



0 dB = 68.42 V/m = 36.70 dBV/m

### #05\_HAC\_E\_GSM1900\_GSM Voice\_Ch512

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.5 °C

#### DASY5 Configuration

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2016/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1399; Calibrated: 2016/11/17
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

#### Ch512/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid

**Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 6.655 V/m; Power Drift = 0.12 dB

Applied MIF = 3.63 dB

RF audio interference level = 28.33 dBV/m

**Emission category: M4**

MIF scaled E-field


Grid 1 <b>M4</b> <b>26.9 dBV/m</b>	Grid 2 <b>M4</b> <b>28.33 dBV/m</b>	Grid 3 <b>M4</b> <b>28.02 dBV/m</b>
Grid 4 <b>M4</b> <b>21.29 dBV/m</b>	Grid 5 <b>M4</b> <b>23.26 dBV/m</b>	Grid 6 <b>M4</b> <b>23.23 dBV/m</b>
Grid 7 <b>M4</b> <b>25.16 dBV/m</b>	Grid 8 <b>M4</b> <b>25.78 dBV/m</b>	Grid 9 <b>M4</b> <b>24.92 dBV/m</b>

**Cursor:**

Total = 28.33 dBV/m

E Category: M4

Location: -3, -25, 8.7 mm



0 dB = 26.08 V/m = 28.33 dBV/m

## #06\_HAC\_E\_GSM1900\_GSM Voice\_Ch661

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 23.5 °C

### DASY5 Configuration

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2016/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1399; Calibrated: 2016/11/17
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

### Ch661/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid

**Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 6.451 V/m; Power Drift = -0.17 dB

Applied MIF = 3.63 dB

RF audio interference level = 27.17 dBV/m

**Emission category: M4**

MIF scaled E-field


Grid 1 <b>M4</b> <b>25.68 dBV/m</b>	Grid 2 <b>M4</b> <b>27.17 dBV/m</b>	Grid 3 <b>M4</b> <b>26.85 dBV/m</b>
Grid 4 <b>M4</b> <b>20.55 dBV/m</b>	Grid 5 <b>M4</b> <b>21.9 dBV/m</b>	Grid 6 <b>M4</b> <b>21.88 dBV/m</b>
Grid 7 <b>M4</b> <b>24.44 dBV/m</b>	Grid 8 <b>M4</b> <b>25.21 dBV/m</b>	Grid 9 <b>M4</b> <b>24.7 dBV/m</b>

**Cursor:**

Total = 27.17 dBV/m

E Category: M4

Location: -2.5, -25, 8.7 mm



0 dB = 22.83 V/m = 27.17 dBV/m

### #07\_HAC\_E\_GSM1900\_GSM Voice\_Ch810

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1909.8 MHz; Duty Cycle: 1:8.3  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.5 °C

#### DASY5 Configuration

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2016/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1399; Calibrated: 2016/11/17
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

#### Ch810/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid

**Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 7.181 V/m; Power Drift = 0.11 dB

Applied MIF = 3.63 dB

RF audio interference level = 27.52 dBV/m

**Emission category: M4**

MIF scaled E-field


Grid 1 <b>M4</b> <b>25.89 dBV/m</b>	Grid 2 <b>M4</b> <b>27.52 dBV/m</b>	Grid 3 <b>M4</b> <b>27.42 dBV/m</b>
Grid 4 <b>M4</b> <b>20.92 dBV/m</b>	Grid 5 <b>M4</b> <b>23.77 dBV/m</b>	Grid 6 <b>M4</b> <b>23.82 dBV/m</b>
Grid 7 <b>M4</b> <b>24.48 dBV/m</b>	Grid 8 <b>M4</b> <b>24.88 dBV/m</b>	Grid 9 <b>M4</b> <b>24.2 dBV/m</b>

**Cursor:**

Total = 27.52 dBV/m

E Category: M4

Location: -4.5, -25, 8.7 mm



0 dB = 23.76 V/m = 27.52 dBV/m

## #08\_HAC\_E\_GSM1900\_GSM Voice\_Ch512

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1850.2 MHz; Duty Cycle: 1:8.3  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.5 °C

### DASY5 Configuration

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2016/1/19;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1399; Calibrated: 2016/11/17
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

### Ch512/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid

**Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 6.147 V/m; Power Drift = 0.16 dB

Applied MIF = 3.63 dB

RF audio interference level = 26.07 dBV/m

**Emission category: M4**

MIF scaled E-field


Grid 1 <b>M4</b> <b>18.17 dBV/m</b>	Grid 2 <b>M4</b> <b>22.85 dBV/m</b>	Grid 3 <b>M4</b> <b>23.48 dBV/m</b>
Grid 4 <b>M4</b> <b>21.73 dBV/m</b>	Grid 5 <b>M4</b> <b>24.13 dBV/m</b>	Grid 6 <b>M4</b> <b>24.14 dBV/m</b>
Grid 7 <b>M4</b> <b>24.37 dBV/m</b>	Grid 8 <b>M4</b> <b>26.07 dBV/m</b>	Grid 9 <b>M4</b> <b>26.03 dBV/m</b>

**Cursor:**

Total = 26.07 dBV/m

E Category: M4

Location: 4, 38.5, 8.7 mm



0 dB = 20.11 V/m = 26.07 dBV/m