

FCC RADIO TEST REPORT

FCC ID : PY7-35228T
Equipment : GSM/WCDMA/LTE Phone+Bluetooth,
DTS/UNII a/b/g/n/ac and NFC
Brand Name : Sony
Applicant : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Manufacturer : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa, Shinagawa-ku,
Tokyo, 140-0002, Japan
Standard : FCC Part 15 Subpart C §15.247

The product was received on Aug. 31, 2018 and testing was started from Sep. 14, 2018 and completed on Nov. 24, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Reviewed by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result	4
1 General Description.....	5
1.1 Product Feature of Equipment Under Test	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency Channel.....	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system.....	10
2.5 EUT Operation Test Setup.....	10
2.6 Measurement Results Explanation Example	10
3 Test Result	11
3.1 Number of Channel Measurement	11
3.2 Hopping Channel Separation Measurement.....	13
3.3 Dwell Time Measurement	19
3.4 20dB and 99% Bandwidth Measurement	21
3.5 Output Power Measurement	32
3.6 Conducted Band Edges Measurement.....	33
3.7 Conducted Spurious Emission Measurement.....	40
3.8 Radiated Band Edges and Spurious Emission Measurement.....	50
3.9 AC Conducted Emission Measurement.....	54
3.10 Antenna Requirements	56
4 List of Measuring Equipment.....	57
5 Uncertainty of Evaluation.....	59
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	



History of this test report

Report No.	Version	Description	Issued Date
FR882923-01A	01	Initial issue of report	Dec. 10, 2018

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Reporting only	-
3.5	15.247(b)(1)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 3.30 dB at 41.070 MHz
3.9	15.207	AC Conducted Emission	Pass	Under limit 11.56 dB at 1.066 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Reviewed by: Wii Chang

Report Producer: Natasha Hsieh



1 General Description

1.1 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII a/b/g/n/ac, FM Receiver, NFC, and GNSS.

Standards-related Product Specification	
Antenna Type / Gain	PIFA Antenna with gain -3.2 dBi

EUT Information List			
HW Version	SW Version	S/N	Performed Test Item
A	1.129	CQ3001BTLD	RF conducted measurement
		CQ3001BN5M	Radiated Spurious Emission
		CQ3001BMVB	AC Conducted Emission

Accessory List	
AC Adapter	Model Name: UCH32
	S/N: 6218W30200215 (for radiated emission) 6218W30200140 (for conducted emission)
Earphone	Model Name: MH410c
	S/N: N/A
USB Cable	Model Name: UCB24
	S/N: N/A

Note:

1. Above EUT list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test, and the serial number of each type of accessories is listed in each section of this report. .
3. For other wireless features of this EUT, test report will be issued separately.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH11-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth 1Mbps GFSK / EDR 2Mbps $\pi/4$ -DQPSK / EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz for 1Mbps Mode 2: CH39_2441 MHz for 1Mbps Mode 3: CH78_2480 MHz for 1Mbps Mode 4: CH00_2402 MHz for 2Mbps Mode 5: CH39_2441 MHz for 2Mbps Mode 6: CH78_2480 MHz for 2Mbps Mode 7: CH00_2402 MHz for 3Mbps Mode 8: CH39_2441 MHz for 3Mbps Mode 9: CH78_2480 MHz for 3Mbps		
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN (2.4GHz) Link + Earphone + Battery + USB Cable (Charging from Adapter)		

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Sony	SBH20	PY7-RD0010	N/A	N/A
4.	Notebook	DELL	P20G	FCC DoC/ Contains FCC ID: QDS-BRCM1051	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to contact with base station to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup







3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

Number of Hopping Channel Plot on Channel 00 - 78



Date: 21.SEP.2018 17:26:32



Date: 21.SEP.2018 17:27:56

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup




3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.




<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 21.SEP.2018 16:09:05

Channel Separation Plot on Channel 39 - 40



Date: 21.SEP.2018 16:22:20




Channel Separation Plot on Channel 00 - 01






Channel Separation Plot on Channel 39 - 40



Date: 21.SEP.2018 17:49:14

Channel Separation Plot on Channel 77 - 78




Date: 21.SEP.2018 17:51:08




<3Mbps>

Channel Separation Plot on Channel 00 - 01




Date: 21.SEP.2018 18:09:36

Channel Separation Plot on Channel 39 - 40



Date: 21.SEP.2018 18:13:42



3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.


3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

Package Transfer Time Plot



Date: 14.SEP.2018 07:40:41

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW $\geq$ 1-5% of the 99% bandwidth; VBW $\geq$ 3 * RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup




3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.


<1Mbps>

20 dB Bandwidth Plot on Channel 00




Date: 21.SEP.2018 18:26:14


20 dB Bandwidth Plot on Channel 39




Date: 21.SEP.2018 16:17:49

**20 dB Bandwidth Plot on Channel 78**


Date: 21.SEP.2018 16:24:49

<2Mbps>**20 dB Bandwidth Plot on Channel 00**

Date: 21.SEP.2018 17:34:36

**20 dB Bandwidth Plot on Channel 39**


Date: 21.SEP.2018 17:42:44

20 dB Bandwidth Plot on Channel 78

Date: 21.SEP.2018 17:52:08


<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 21.SEP.2018 18:00:51


20 dB Bandwidth Plot on Channel 39



Date: 21.SEP.2018 18:10:58



20 dB Bandwidth Plot on Channel 78




Date: 21.SEP.2018 18:16:55

3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<1Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 21.SEP.2018 16:06:16




99% Occupied Bandwidth Plot on Channel 39



Date: 21.SEP.2018 16:19:17


99% Occupied Bandwidth Plot on Channel 78



Date: 21.SEP.2018 16:26:11


<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 21.SEP.2018 17:35:42


99% Occupied Bandwidth Plot on Channel 39



Date: 21.SEP.2018 17:43:33




99% Occupied Bandwidth Plot on Channel 78



Date: 21.SEP.2018 17:53:38

<3Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 21.SEP.2018 18:02:42




99% Occupied Bandwidth Plot on Channel 39



Date: 21.SEP.2018 18:11:44

99% Occupied Bandwidth Plot on Channel 78



Date: 21.SEP.2018 18:17:54

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.


3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges


<1Mbps>

Low Band Edge Plot on Channel 00



Date: 21.SEP.2018 16:05:39


High Band Edge Plot on Channel 78



Date: 21.SEP.2018 16:25:19


<2Mbps>

Low Band Edge Plot on Channel 00



Date: 21.SEP.2018 17:35:08


High Band Edge Plot on Channel 78



Date: 21.SEP.2018 17:52:29


<3Mbps>

Low Band Edge Plot on Channel 00



Date: 21.SEP.2018 18:01:56

High Band Edge Plot on Channel 78




Date: 21.SEP.2018 18:17:19

3.6.6 Test Result of Conducted Hopping Mode Band Edges


<1Mbps>

Hopping Mode Low Band Edge Plot



Date: 21.SEP.2018 17:23:29

Hopping Mode High Band Edge Plot




Date: 21.SEP.2018 17:25:05




<2Mbps>

Hopping Mode Low Band Edge Plot



Date: 21.SEP.2018 17:29:32

Hopping Mode High Band Edge Plot




Date: 21.SEP.2018 17:30:53




<3Mbps>

Hopping Mode Low Band Edge Plot



Date: 21.SEP.2018 17:32:18

Hopping Mode High Band Edge Plot



Date: 21.SEP.2018 17:33:10

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

See list of measuring equipment of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission


<1Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz




Date: 17.SEP.2018 15:30:53


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 21.SEP.2018 16:10:59

**CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 21.SEP.2018 16:20:50

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz

Date: 21.SEP.2018 16:21:18

**CSE Plot on Ch 78 between 30MHz ~ 3 GHz**


Date: 21.SEP.2018 16:34:31

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz

Date: 21.SEP.2018 17:09:48


<2Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz




Date: 21.SEP.2018 17:37:35


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 21.SEP.2018 17:38:03

**CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 21.SEP.2018 17:47:55

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz

Date: 21.SEP.2018 17:48:22




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 21.SEP.2018 17:54:27


CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 21.SEP.2018 17:54:58


<3Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz




Date: 21.SEP.2018 18:07:16


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 21.SEP.2018 18:07:43

**CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 21.SEP.2018 18:12:18

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz

Date: 21.SEP.2018 18:12:51

**CSE Plot on Ch 78 between 30MHz ~ 3 GHz**

Date: 21.SEP.2018 18:18:25

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz

Date: 21.SEP.2018 18:18:53

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

See list of measuring equipment of this test report.


3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.8.7 Duty Cycle

Please refer to Appendix E.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

See list of measuring equipment of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	DTM-303A	TP157075	N/A	Mar. 06, 2018	Sep. 14, 2018~ Sep. 21, 2018	Mar. 05, 2019	Conducted (TH05-HY)
Power Meter	Agilent	E4416A	GB412923 44	N/A	Dec. 20, 2017	Sep. 14, 2018~ Sep. 21, 2018	Dec. 19, 2018	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US404415 48	50MHz~18GHz	Dec. 20, 2017	Sep. 14, 2018~ Sep. 21, 2018	Dec. 19, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2017	Sep. 14, 2018~ Sep. 21, 2018	Nov. 20, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV30	103738-kt	9kHz-30GHz	May. 22, 2018	Sep. 14, 2018~ Sep. 21, 2018	May. 21, 2019	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC130048 4	N/A	Mar. 01, 2018	Sep. 14, 2018~ Sep. 21, 2018	Feb. 28, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Nov. 20, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Dec. 08, 2017	Nov. 20, 2018	Dec. 07, 2018	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Mar. 06, 2018	Nov. 20, 2018	Mar. 05, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Nov. 20, 2018	Nov. 29, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Nov. 20, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Nov. 20, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Nov. 20, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Amplifier	MITEQ	TTA1840-35- HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 16, 2018	Nov. 22, 2018~ Nov. 24, 2018	Jul. 15, 2019	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Jan. 16, 2018	Nov. 22, 2018~ Nov. 24, 2018	Jan. 15, 2019	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6- 06	35414&AT- N0602	30MHz~1GHz	Oct. 13, 2018	Nov. 22, 2018~ Nov. 24, 2018	Oct. 12, 2019	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-132 6	1GHz ~ 18GHz	Oct. 30, 2018	Nov. 22, 2018~ Nov. 24, 2018	Oct. 29, 2019	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTN-303B	TP140325	N/A	Nov. 05, 2018	Nov. 22, 2018~ Nov. 24, 2018	Nov 04, 2019	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 22, 2018	Nov. 22, 2018~ Nov. 24, 2018	Nov. 21, 2019	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY532700 80	1GHz~26.5GHz	Nov. 14, 2018	Nov. 22, 2018~ Nov. 24, 2018	Nov. 13, 2020	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 86	10Hz ~ 44GHz	Oct. 19, 2018	Nov. 22, 2018~ Nov. 24, 2018	Oct. 18, 2019	Radiation (03CH11-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Nov. 22, 2018~ Nov. 24, 2018	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500 -B	N/A	1~4m	N/A	Nov. 22, 2018~ Nov. 24, 2018	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Nov. 22, 2018~ Nov. 24, 2018	N/A	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55- 303K	17100018 00054001	1GHz~18GHz	Apr. 16, 2018	Nov. 22, 2018~ Nov. 24, 2018	Apr. 15, 2019	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Nov. 27, 2017	Nov. 22, 2018~ Nov. 24, 2018	Nov. 26, 2018	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-00104 2	N/A	N/A	Nov. 22, 2018~ Nov. 24, 2018	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	9kHz-30MHz	Mar. 14, 2018	Nov. 22, 2018~ Nov. 24, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 14, 2018	Nov. 22, 2018~ Nov. 24, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	30M-18G	Mar. 14, 2018	Nov. 22, 2018~ Nov. 24, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 14, 2018	Nov. 22, 2018~ Nov. 24, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000- 1530-8000-4 0SS	SN11	1G Low Pass	Sep. 16, 2018	Nov. 22, 2018~ Nov. 24, 2018	Sep. 15, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-27 00-3000-180 00-60SS	SN3	2.7G High Pass	Sep. 16, 2018	Nov. 22, 2018~ Nov. 24, 2018	Sep. 15, 2019	Radiation (03CH11-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.20
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.20
---	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.50
---	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.20
---	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Allen Lin	Temperature:	21~25	°C
Test Date:	2018/9/14~2018/9/21	Relative Humidity:	51~54	%

TEST RESULTS DATA**20dB and 99% Occupied Bandwidth and Hopping Channel Separation**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.872	0.812	1.008	0.5813	Pass
DH	1Mbps	1	39	2441	0.892	0.844	1.002	0.5947	Pass
DH	1Mbps	1	78	2480	0.896	0.844	1.008	0.5973	Pass
2DH	2Mbps	1	0	2402	1.266	1.168	0.996	0.8440	Pass
2DH	2Mbps	1	39	2441	1.266	1.168	1.314	0.8440	Pass
2DH	2Mbps	1	78	2480	1.290	1.168	1.002	0.8600	Pass
3DH	3Mbps	1	0	2402	1.236	1.152	1.002	0.8240	Pass
3DH	3Mbps	1	39	2441	1.236	1.148	1.002	0.8240	Pass
3DH	3Mbps	1	78	2480	1.236	1.152	1.008	0.8240	Pass

TEST RESULTS DATA**Dwell Time**

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

TEST RESULTS DATA**Peak Power Table**

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	11.38	20.97	Pass
	39	1	10.08	20.97	Pass
	78	1	11.42	20.97	Pass
2DH1	0	1	10.87	20.97	Pass
	39	1	10.04	20.97	Pass
	78	1	10.85	20.97	Pass
3DH1	0	1	11.11	20.97	Pass
	39	1	9.71	20.97	Pass
	78	1	11.16	20.97	Pass

TEST RESULTS DATA**Average Power Table****(Reporting Only)**

DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	11.30	5.15
	39	1	9.96	5.15
	78	1	11.29	5.15
2DH1	0	1	8.82	5.08
	39	1	7.04	5.08
	78	1	8.76	5.08
3DH1	0	1	8.85	5.08
	39	1	7.05	5.08
	78	1	8.81	5.08

TEST RESULTS DATA**Number of Hopping Frequency**

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Jimmy Chang	Temperature :	24~25℃
		Relative Humidity :	61~62%

EUT Information

Report NO : 882923-01
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.156750	---	29.33	55.63	26.30	L1	OFF	19.5
0.156750	45.14	---	65.63	20.49	L1	OFF	19.5
0.469500	---	23.78	46.52	22.74	L1	OFF	19.5
0.469500	27.50	---	56.52	29.02	L1	OFF	19.5
0.552750	---	32.94	46.00	13.06	L1	OFF	19.5
0.552750	43.31	---	56.00	12.69	L1	OFF	19.5
0.622500	---	32.18	46.00	13.82	L1	OFF	19.6
0.622500	42.24	---	56.00	13.76	L1	OFF	19.6
1.065750	---	34.44	46.00	11.56	L1	OFF	19.6
1.065750	38.21	---	56.00	17.79	L1	OFF	19.6
4.814250	---	25.48	46.00	20.52	L1	OFF	19.7
4.814250	29.13	---	56.00	26.87	L1	OFF	19.7
14.624250	---	27.94	50.00	22.06	L1	OFF	20.1
14.624250	34.87	---	60.00	25.13	L1	OFF	20.1

EUT Information

Report NO : 882923-01
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	31.68	55.88	24.20	N	OFF	19.5
0.152250	52.81	---	65.88	13.07	N	OFF	19.5
0.159000	---	29.87	55.52	25.65	N	OFF	19.5
0.159000	51.15	---	65.52	14.37	N	OFF	19.5
0.163500	---	29.09	55.28	26.19	N	OFF	19.5
0.163500	49.73	---	65.28	15.55	N	OFF	19.5
0.174750	---	27.39	54.73	27.34	N	OFF	19.5
0.174750	45.40	---	64.73	19.33	N	OFF	19.5
0.483000	---	31.46	46.29	14.83	N	OFF	19.5
0.483000	41.10	---	56.29	15.19	N	OFF	19.5
0.564000	---	33.39	46.00	12.61	N	OFF	19.5
0.564000	41.61	---	56.00	14.39	N	OFF	19.5
0.620250	---	28.38	46.00	17.62	N	OFF	19.6
0.620250	39.86	---	56.00	16.14	N	OFF	19.6
1.068000	---	32.65	46.00	13.35	N	OFF	19.6
1.068000	35.89	---	56.00	20.11	N	OFF	19.6
4.920000	---	25.52	46.00	20.48	N	OFF	19.7
4.920000	27.97	---	56.00	28.03	N	OFF	19.7
14.381250	---	27.75	50.00	22.25	N	OFF	20.1
14.381250	33.10	---	60.00	26.90	N	OFF	20.1



Appendix C. Radiated Spurious Emission

Test Engineer :	Hao Hsu, Ken Wu, and Chuan Zhu	Temperature :	21~26°C
		Relative Humidity :	51~56%

2.4GHz 2400~2483.5MHz

BT 1Mbps (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2368.905	43.39	-30.61	74	42.97	27.52	6.54	33.64	117	288	P	H
		2368.905	18.6	-35.4	54	-	-	-	-	-	-	A	H
	*	2402	104.31	-	-	103.95	27.4	6.59	33.63	117	288	P	H
	*	2402	79.52	-	-	-	-	-	-	-	-	A	H
													H
													H
		2321.445	43.33	-30.67	74	42.8	27.71	6.47	33.65	400	287	P	V
		2321.445	18.54	-35.46	54	-	-	-	-	-	-	A	V
	*	2402	101	-	-	100.64	27.4	6.59	33.63	400	287	P	V
	*	2402	76.21	-	-	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		2352.28	44.49	-29.51	74	44.02	27.59	6.52	33.64	100	288	P	H
		2352.28	19.7	-34.3	54	-	-	-	-	-	-	A	H
	*	2441	104.39	-	-	104.06	27.32	6.62	33.61	100	288	P	H
	*	2441	79.6	-	-	-	-	-	-	-	-	A	H
		2490.97	43.52	-30.48	74	43.15	27.3	6.66	33.59	100	288	P	H
		2490.97	18.73	-35.27	54	-	-	-	-	-	-	A	H
		2323.3	43.6	-30.4	74	43.07	27.71	6.47	33.65	385	286	P	V
		2323.3	18.81	-35.19	54	-	-	-	-	-	-	A	V
	*	2441	100.62	-	-	100.29	27.32	6.62	33.61	385	286	P	V
	*	2441	75.83	-	-	-	-	-	-	-	-	A	V
		2491.32	43.1	-30.9	74	42.73	27.3	6.66	33.59	385	286	P	V
		2491.32	18.31	-35.69	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	106.67	-	-	106.32	27.3	6.65	33.6	100	289	P	H
	*	2480	81.88	-	-	-	-	-	-	-	-	A	H
		2483.52	55.14	-18.86	74	54.78	27.3	6.66	33.6	100	289	P	H
		2483.52	30.35	-23.65	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	101.64	-	-	101.29	27.3	6.65	33.6	370	290	P	V
	*	2480	76.85	-	-	-	-	-	-	-	-	A	V
		2483.56	50.12	-23.88	74	49.76	27.3	6.66	33.6	370	290	P	V
		2483.56	25.33	-28.67	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BT 1Mbps (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	43.95	-30.05	74	61.36	31.1	10.07	58.58	100	0	P	H
		4804	19.16	-34.84	54	-	-	-	-	-	-	A	H
													H
													H
		4804	41.75	-32.25	74	59.16	31.1	10.07	58.58	100	0	P	V
		4804	16.96	-37.04	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	48.15	-25.85	74	65.51	31.04	10.15	58.55	100	0	P	H
		4882	23.36	-30.64	54	-	-	-	-	-	-	A	H
		7323	42.01	-31.99	74	51.79	36.55	12.48	58.81	100	0	P	H
		7323	17.22	-36.78	54	-	-	-	-	-	-	A	H
		4882	45.95	-28.05	74	63.31	31.04	10.15	58.55	100	0	P	V
		4882	21.16	-32.84	54	-	-	-	-	-	-	A	V
		7323	41.98	-32.02	74	51.76	36.55	12.48	58.81	100	0	P	V
		7323	17.19	-36.81	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	45.83	-28.17	74	62.8	31.32	10.22	58.51	100	0	P	H
		4960	21.04	-32.96	54	-	-	-	-	-	-	A	H
		7440	42.45	-31.55	74	52.16	36.48	12.47	58.66	100	0	P	H
		7440	17.66	-36.34	54	-	-	-	-	-	-	A	H
		4960	42.31	-31.69	74	59.28	31.32	10.22	58.51	100	0	P	V
		4960	17.52	-36.48	54	-	-	-	-	-	-	A	V
		7440	42.24	-31.76	74	51.95	36.48	12.47	58.66	100	0	P	V
		7440	17.45	-36.55	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
2.4GHz BT LF		38.91	26.28	-13.72	40	38.28	19.64	0.85	32.49	-	-	P	H
		81.57	25.51	-14.49	40	43.45	13.27	1.27	32.48	-	-	P	H
		148.26	31.83	-11.67	43.5	45.65	16.96	1.66	32.44	100	0	P	H
		533.8	28.4	-17.6	46	33.93	23.84	3.04	32.41	-	-	P	H
		878.9	32.12	-13.88	46	30.75	29.15	3.99	31.77	-	-	P	H
		958	33.16	-12.84	46	29.19	30.92	4.18	31.13	-	-	P	H
													H
													H
													H
													H
													H
													H
		41.07	36.7	-3.3	40	49.81	18.51	0.87	32.49	100	0	P	V
		62.13	32.23	-7.77	40	52.01	11.62	1.09	32.49	-	-	P	V
		81.84	30.17	-9.83	40	48.06	13.31	1.28	32.48	-	-	P	V
		673.1	28.18	-17.82	46	30.76	26.47	3.42	32.47	-	-	P	V
		929.3	31.95	-14.05	46	29.79	29.45	4.1	31.39	-	-	P	V
		958	33.33	-12.67	46	29.36	30.92	4.18	31.13	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



2.4GHz 2400~2483.5MHz
BT 2Mbps (Band Edge @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH00 2402MHz		2323.335	43.62	-30.38	74	43.08	27.71	6.48	33.65	100	265	P	H
		2323.335	18.86	-35.14	54	-	-	-	-	-	-	A	H
	*	2402	102.18	-	-	101.82	27.4	6.59	33.63	100	265	P	H
	*	2402	77.42	-	-	-	-	-	-	-	-	A	H
													H
													H
		2338.245	43.5	-30.5	74	43	27.65	6.5	33.65	305	18	P	V
		2338.245	18.74	-35.26	54	-	-	-	-	-	-	A	V
	*	2402	98.17	-	-	97.81	27.4	6.59	33.63	305	18	P	V
	*	2402	73.41	-	-	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		2376.36	43.94	-30.06	74	43.53	27.49	6.55	33.63	100	289	P	H
		2376.36	19.18	-34.82	54	-	-	-	-	-	-	A	H
	*	2441	103.16	-	-	102.83	27.32	6.62	33.61	100	289	P	H
	*	2441	78.4	-	-	-	-	-	-	-	-	A	H
		2484.32	43.4	-30.6	74	43.04	27.3	6.66	33.6	100	289	P	H
		2484.32	18.64	-35.36	54	-	-	-	-	-	-	A	H
		2381.68	43.67	-30.33	74	43.27	27.47	6.56	33.63	296	300	P	V
		2381.68	18.91	-35.09	54	-	-	-	-	-	-	A	V
	*	2441	98.31	-	-	97.98	27.32	6.62	33.61	296	300	P	V
	*	2441	73.55	-	-	-	-	-	-	-	-	A	V
		2494.68	43.57	-30.43	74	43.19	27.3	6.67	33.59	296	300	P	V
		2494.68	18.81	-35.19	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	105.91	-	-	105.56	27.3	6.65	33.6	141	289	P	H
	*	2480	81.15	-	-	-	-	-	-	-	-	A	H
		2483.52	53.07	-20.93	74	52.71	27.3	6.66	33.6	141	289	P	H
		2483.52	28.31	-25.69	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	101.25	-	-	100.9	27.3	6.65	33.6	291	300	P	V
	*	2480	76.49	-	-	-	-	-	-	-	-	A	V
		2483.6	49.22	-24.78	74	48.86	27.3	6.66	33.6	291	300	P	V
		2483.6	24.46	-29.54	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BT 2Mbps (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	44.47	-29.53	74	61.88	31.1	10.07	58.58	100	0	P	H
		4804	19.71	-34.29	54	-	-	-	-	-	-	A	H
													H
													H
		4804	41.52	-32.48	74	58.93	31.1	10.07	58.58	100	0	P	V
		4804	16.76	-37.24	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	46.51	-27.49	74	63.87	31.04	10.15	58.55	100	0	P	H
		4882	21.75	-32.25	54	-	-	-	-	-	-	A	H
		7323	41.12	-32.88	74	50.9	36.55	12.48	58.81	100	0	P	H
		7323	16.36	-37.64	54	-	-	-	-	-	-	A	H
		4882	42.78	-31.22	74	60.14	31.04	10.15	58.55	100	0	P	V
		4882	18.02	-35.98	54	-	-	-	-	-	-	A	V
		7323	41.92	-32.08	74	51.7	36.55	12.48	58.81	100	0	P	V
		7323	17.16	-36.84	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	45.74	-28.26	74	62.71	31.32	10.22	58.51	100	0	P	H
		4960	20.98	-33.02	54	-	-	-	-	-	-	A	H
		7440	41.9	-32.1	74	51.61	36.48	12.47	58.66	100	0	P	H
		7440	17.14	-36.86	54	-	-	-	-	-	-	A	H
		4960	42.39	-31.61	74	59.36	31.32	10.22	58.51	100	0	P	V
		4960	17.63	-36.37	54	-	-	-	-	-	-	A	V
		7440	42.34	-31.66	74	52.05	36.48	12.47	58.66	100	0	P	V
		7440	17.58	-36.42	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BT 3Mbps (Band Edge @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH00 2402MHz		2376.675	43.37	-30.63	74	42.95	27.49	6.56	33.63	299	265	P	H
		2376.675	18.58	-35.42	54	-	-	-	-	-	-	A	H
	*	2402	102.26	-	-	101.9	27.4	6.59	33.63	299	265	P	H
	*	2402	77.47	-	-	-	-	-	-	-	-	A	H
													H
													H
		2372.265	42.82	-31.18	74	42.4	27.51	6.55	33.64	305	17	P	V
		2372.265	18.03	-35.97	54	-	-	-	-	-	-	A	V
	*	2402	98.25	-	-	97.89	27.4	6.59	33.63	305	17	P	V
	*	2402	73.46	-	-	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		2337.16	42.91	-31.09	74	42.41	27.65	6.5	33.65	116	306	P	H
		2337.16	18.12	-35.88	54	-	-	-	-	-	-	A	H
	*	2441	103.08	-	-	102.75	27.32	6.62	33.61	116	306	P	H
	*	2441	78.29	-	-	-	-	-	-	-	-	A	H
		2486.21	42.51	-31.49	74	42.14	27.3	6.66	33.59	116	306	P	H
		2486.21	17.72	-36.28	54	-	-	-	-	-	-	A	H
		2355.92	43.01	-30.99	74	42.55	27.58	6.52	33.64	336	14	P	V
		2355.92	18.22	-35.78	54	-	-	-	-	-	-	A	V
	*	2441	98.89	-	-	98.56	27.32	6.62	33.61	336	14	P	V
	*	2441	74.1	-	-	-	-	-	-	-	-	A	V
		2493.49	42.69	-31.31	74	42.32	27.3	6.66	33.59	336	14	P	V
		2493.49	17.9	-36.1	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	105.21	-	-	104.86	27.3	6.65	33.6	141	306	P	H
	*	2480	80.42	-	-	-	-	-	-	-	-	A	H
		2483.64	50.77	-23.23	74	50.41	27.3	6.66	33.6	141	306	P	H
		2483.64	25.98	-28.02	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	98.58	-	-	98.23	27.3	6.65	33.6	290	17	P	V
	*	2480	73.79	-	-	-	-	-	-	-	-	A	V
		2483.56	45.9	-28.1	74	45.54	27.3	6.66	33.6	290	17	P	V
		2483.56	21.11	-32.89	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BT 3Mbps (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	45.39	-28.61	74	62.8	31.1	10.07	58.58	100	0	P	H
		4804	20.6	-33.4	54	-	-	-	-	-	-	A	H
													H
													H
		4804	41.28	-32.72	74	58.69	31.1	10.07	58.58	100	0	P	V
		4804	16.49	-37.51	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	45.82	-28.18	74	63.18	31.04	10.15	58.55	100	0	P	H
		4882	21.03	-32.97	54	-	-	-	-	-	-	A	H
		7323	41.61	-32.39	74	51.39	36.55	12.48	58.81	100	0	P	H
		7323	16.82	-37.18	54	-	-	-	-	-	-	A	H
		4882	43.15	-30.85	74	60.51	31.04	10.15	58.55	100	0	P	V
		4882	18.36	-35.64	54	-	-	-	-	-	-	A	V
		7323	41.36	-32.64	74	51.14	36.55	12.48	58.81	100	0	P	V
		7323	16.57	-37.43	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	46.37	-27.63	74	63.34	31.32	10.22	58.51	100	0	P	H
		4960	21.58	-32.42	54	-	-	-	-	-	-	A	H
		7440	43.35	-30.65	74	53.06	36.48	12.47	58.66	100	0	P	H
		7440	18.56	-35.44	54	-	-	-	-	-	-	A	H
		4960	42.23	-31.77	74	59.2	31.32	10.22	58.51	100	0	P	V
		4960	17.44	-36.56	54	-	-	-	-	-	-	A	V
		7440	42.57	-31.43	74	52.28	36.48	12.47	58.66	100	0	P	V
		7440	17.78	-36.22	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Hao Hsu, Ken Wu, and Chuan Zhu	Temperature :	21~26°C
		Relative Humidity :	51~56%



Note symbol

-L	Low channel location
-R	High channel location








2.4GHz 2400~2483.5MHz




BT 1Mbps (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH11-HV Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 882923-01	 Site : 03CH11-HV Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 882923-01





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH11-1FY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01	 Site : 03CH11-1FY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01	Left blank

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Horizontal	Fundamental
Peak	Level (dBm/Vm) Date: 2018-11-21  Site : 03CH11-14Y Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01	Level (dBm/Vm) Date: 2018-11-21  Site : 03CH11-14Y Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Vertical	Fundamental
Peak	Level (dBuV/m) Date: 2018-11-21 2460 2463.2465.2467.2469.2471.2473.2475.2477.2479.2481.2483.2485.2487.2489.2491.2493.2495.2497. 2500 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01	Level (dBuV/m) Date: 2018-11-21 1000 1300. 1500. 1700. 1900. 2100. 2300. 2500. 2700. 3000 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01



2.4GHz 2400~2483.5MHz

BT 1Mbps (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH39 2441MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-1F Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 882923-01	Level (dBuV/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-1F Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 882923-01





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH78 2480MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBu/V/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 882923-01	Level (dBu/V/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 882923-01



Emission below 1GHz



2.4GHz BT 1Mbps (LF)

BT	2.4GHz 2400~2483.5MHz	
	BT LF	
	Horizontal	Vertical
QP / Peak	 Site : 03CH11-HY Condition : QP 3m BT-LOG 6111D-LF_ETC HORIZONTAL Detector : Peak Project : 882923-01	 Site : 03CH11-HY Condition : QP 3m BT-LOG 6111D-LF_ETC VERTICAL Detector : Peak Project : 882923-01






2.4GHz 2400~2483.5MHz




BT 2Mbps (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH11-HV Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 882923-01	 Site : 03CH11-HV Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 882923-01



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Vertical	Fundamental
Peak	Level (dBu/Vm) Date: 2018-11-22 Frequency (MHz) Site : 03CH11-1FY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01	Level (dBu/Vm) Date: 2018-11-22 Frequency (MHz) Site : 03CH11-1FY Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01	Left blank

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Horizontal	Fundamental
Peak	Level (dBm/Vm) Date: 2018-11-22 2480 2483.2485 2487 2489 2471 2473 2475 2477 2479 2481 2483 2485 2487 2489 2491 2493 2495 2497 2500 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01	Level (dBm/Vm) Date: 2018-11-22 1000 1300 1500 1700 1900 2100 2300 2500 2700 3000 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Vertical	Fundamental
Peak	Level (dBm/Vm) Date: 2018-11-22 2480 2483.2485 2487 2489 2471 2473 2475 2477 2479 2481 2483 2485 2487 2489 2491 2493 2495 2497 2500 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01	Level (dBm/Vm) Date: 2018-11-22 1000 1300 1500 1700 1900 2100 2300 2500 2700 3000 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01



2.4GHz 2400~2483.5MHz

BT 2Mbps (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH39 2441MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-1F Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 882923-01	Level (dBuV/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-1F Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 882923-01





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH78 2480MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBu/V/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 882923-01	Level (dBu/V/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 882923-01





2.4GHz 2400~2483.5MHz




BT 3Mbps (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH11-HV Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 882923-01	 Site : 03CH11-HV Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : 882923-01






BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Vertical	Fundamental
Peak	 Site : 03CH11-1FY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01	 Site : 03CH11-1FY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Horizontal	Fundamental
Peak	Level (dBm/Vm) Date: 2018-11-22 2480 2483.2485 2487 2489 2471 2473 2475 2477 2479 2481 2483 2485 2487 2489 2491 2493 2495 2497 2500 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01	Level (dBm/Vm) Date: 2018-11-22 1000 1300 1600 1900 2100 2300 2500 2700 3000 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Vertical	Fundamental
Peak	Level (dBuV/m) Date: 2018-11-22 2460 2463.2465.2467.2469.2471.2473.2475.2477.2479.2481.2483.2485.2487.2489.2491.2493.2495.2497. 2500 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01	Level (dBuV/m) Date: 2018-11-22 1000 1300. 1500. 1700. 1900. 2100. 2300. 2500. 2700. 3000 Frequency (MHz) Site : 03CH11-14Y Condition : PEAK_74 3m HORN 91200-HF VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 882923-01



2.4GHz 2400~2483.5MHz

BT 3Mbps (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL Detector : Peak Project : 882923-01	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL Detector : Peak Project : 882923-01



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH39 2441MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-1F Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 882923-01	Level (dBuV/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-1F Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 882923-01




BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH78 2480MHz	
	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-1F Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 882923-01	Level (dBuV/m) Date: 2018-11-23 Frequency (MHz) Site : 03CH11-1F Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 882923-01


Appendix E. Duty Cycle Plots

<1Mbps>

DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39




Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.766 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. **DH5** has the highest duty cycle worst case and is reported.




<2Mbps>

2DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39




Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.89 / 100 = 5.78\%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.76 \text{ dB}$
3. 2DH5 has the highest duty cycle worst case and is reported.




<3Mbps>

3DH5 on time (One Pulse) Plot on Channel 39



on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76\%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.

**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100\text{ms}) = -24.79 \text{ dB}$$

—————THE END—————