




FCC SAR TEST REPORT

FCC ID : PY7-35228T
Brand Name : Sony
Applicant : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa,
Shinagawa-ku, Tokyo, 140-0002, Japan
Manufacturer : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa,
Shinagawa-ku, Tokyo, 140-0002, Japan
Standard : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

The product was received on Sep. 19, 2018 and testing was started from Nov. 23, 2018 and completed on Nov. 29 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	5
3. Equipment Under Test (EUT) Information	5
3.1 General Information	5
3.2 Device Serial Number	6
3.3 General LTE SAR Test and Reporting Considerations	7
4. RF Exposure Limits.....	9
4.1 Uncontrolled Environment.....	9
4.2 Controlled Environment.....	9
5. Specific Absorption Rate (SAR).....	10
5.1 Introduction	10
5.2 SAR Definition.....	10
6. System Description and Setup	11
6.1 E-Field Probe	12
6.2 Data Acquisition Electronics (DAE)	12
6.3 Phantom.....	13
6.4 Device Holder.....	14
7. Measurement Procedures	15
7.1 Spatial Peak SAR Evaluation.....	15
7.2 Power Reference Measurement.....	16
7.3 Area Scan	16
7.4 Zoom Scan.....	17
7.5 Volume Scan Procedures.....	17
7.6 Power Drift Monitoring.....	17
8. Test Equipment List.....	18
9. System Verification	19
9.1 Tissue Simulating Liquids.....	19
9.2 Tissue Verification	20
9.3 System Performance Check Results.....	22
10. RF Exposure Positions	24
10.1 Ear and handset reference point.....	24
10.2 Definition of the cheek position	25
10.3 Definition of the tilt position	26
10.4 Body Worn Accessory	26
10.5 Product Specific Exposure	27
10.6 Wireless Router.....	27
11. Conducted RF Output Power (Unit: dBm).....	28
12. RF Exposure Conditions	88
13. SAR Test Results	89
13.1 Head SAR	91
13.2 Hotspot SAR	94
13.3 Body Worn Accessory SAR.....	97
13.4 Product Specific SAR.....	99
13.5 Repeated SAR Measurement	100
14. Simultaneous Transmission Analysis.....	101
14.1 Head Exposure Conditions	102
14.2 Hotspot Exposure Conditions.....	104
14.3 Body-Worn Accessory Exposure Conditions	108
14.4 Product Specific Exposure Conditions	109
15. Uncertainty Assessment	110
16. References.....	110
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

History of this test report

Report No.	Version	Description	Issued Date
FA882923-01	01	Initial issue of report	Dec. 14, 2018
FA882923-01	02	Updated section 3.3 note.	Dec. 21, 2018
FA882923-01	03	Added BT Duty cycle plot on page 87.	Dec. 24, 2018

1. Statement of Compliance

Applicant Name	Sony Mobile Communications Inc.			
EUT Description	GSM/WCDMA/LTE Phone+Bluetooth, DTS/UNII a/b/g/n/ac and NFC			
Brand Name	Sony			
FCC ID	PY7-35228T			
HW Version	A			
SW Version	1.129			
RF Exposure Conditions	Equipment Class			
	Licensed	DTS	NII	DSS
Head (1g SAR W/kg)	0.23	0.61	0.92	0.10
Body-Worn (1g SAR W/kg)	0.63	0.06	0.07	0.01
Wireless Router (1g SAR W/kg)	1.12	0.16		0.03
Product Specific (10g SAR W/kg)	2.95		0.36	
Highest Simultaneous Transmission (1g SAR W/kg)	Head: 1.06 Body-worn: 0.68 Hotspot: 1.24	Head: 0.78 Body-worn: 0.68 Hotspot: 1.24	Head: 1.06 Body-worn: 0.64 Hotspot: NA	Head: 0.27 Body-worn: 0.64 Hotspot: 1.12
Date Tested	2018/11/23 ~ 2018/11/29			
Test Result	Pass			
Remark:				
1. This device 2.4GHz WLAN support Hotspot operation and Bluetooth support tethering applications.				
2. When hotspot mode is active which the power will be reduced of GSM1900, WCDMA B2/B4, and LTE B2/B4/B25/B66, detail descriptions of the power reduction mechanism are included in the operational description.				
3. The device employs sensors to detect different usage conditions, when operating in near-body or handheld condition by end user, the device will reduced maximum output powers on the WCDMA B2 / B4 and LTE B2 / B4 / B25 / B66 and detail descriptions of the power reduction mechanism are included in the operational description.				

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body, 4.0 W/kg for Product Specific) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

Reviewed by: Jason Wang

Report Producer: Wan Liu



2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D05A Rel.10 LTE SAR Test Guidance v01r02
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01

3. Equipment Under Test (EUT) Information

3.1 General Information

Wireless Technologies	Frequency	Operating Mode	
GSM	850 1900	• GSM Voice • GPRS (GMSK) • EDGE (8PSK)	Multi-Slot Class: Class 33
	Does device support dual transfer mode? (Yes)		
W-CDMA (UMTS)	Band 5 Band 4 Band 2	• AMR / RMC 12.2Kbps • HSDPA • HSUPA • DC-HSDPA	
LTE (FDD)	Band 2 Band 4 Band 5 Band 7 Band 12 Band 13 Band 17 Band 25 Band 66	• QPSK • 16QAM • 64QAM • Rel 12 Carrier Aggregation Downlink only (the detail refer to section 11)	
WiFi	2.4GHz: 2412 MHz ~ 2472 MHz	• 11b • 11g • 11n (HT20)	
	5GHz: 5.2GHz: 5180 MHz ~ 5240 MHz 5.3GHz: 5260 MHz ~ 5320 MHz 5.5GHz: 5500 MHz ~ 5720 MHz 5.8GHz: 5745 MHz ~ 5825 MHz	• 11a • 11n (HT20) • 11n (HT40) • 11ac (VHT20) • 11ac (VHT40) • 11ac (VHT80)	
Bluetooth	2.4GHz	• BR / EDR / LE	
NFC	13.56MHz	• ASK	



Accessories Information		
Earphone 1	Model Name	MH410c
	Type Name	AG-1100

3.2 Device Serial Number

Band	SN
WWAN	CQ3001BMX2
WLAN	CQ3001BTG9

Note: Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device tested gave the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

3.3 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05												
FCC ID			PY7-35228T									
Operating Frequency Range of each LTE transmission band			LTE Band 2: 1850.7 MHz ~ 1909.3 MHz									
			LTE Band 4: 1710.7 MHz ~ 1754.3 MHz									
			LTE Band 5: 824.7 MHz ~ 848.3 MHz									
			LTE Band 7: 2502.5 MHz ~ 2567.5 MHz									
			LTE Band 12: 699.7 MHz ~ 715.3 MHz									
			LTE Band 13: 779.5 MHz ~ 784.5 MHz									
			LTE Band 17: 706.5 MHz ~ 713.5 MHz									
			LTE Band 25: 1850.7 MHz ~ 1914.3 MHz									
			LTE Band 66: 1710.7 MHz ~ 1779.3 MHz									
Channel Bandwidth			LTE Band 02:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 04:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 05:1.4MHz, 3MHz, 5MHz, 10MHz									
			LTE Band 07: 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 12:1.4MHz, 3MHz, 5MHz, 10MHz									
			LTE Band 13: 5MHz, 10MHz									
			LTE Band 17: 5MHz, 10MHz									
			LTE Band 25:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
			LTE Band 66:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz									
uplink modulations used			QPSK / 16QAM / 64QAM									
LTE Voice / Data requirements			Voice and Data									
LTE MPR permanently built-in by design			Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3									
			Modulation		Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)	
					1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz		
			QPSK		> 5	> 4	> 8	> 12	> 16	> 18	≤ 1	
			16 QAM		≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1	
			16 QAM		> 5	> 4	> 8	> 12	> 16	> 18	≤ 2	
			64 QAM		≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2	
			64 QAM		> 5	> 4	> 8	> 12	> 16	> 18	≤ 3	
			256 QAM		≥ 1						≤ 5	
			LTE A-MPR			In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)						
Spectrum plots for RB configuration			A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.									
Power reduction applied to satisfy SAR compliance			1. Yes, when operating in hotspot mode that LTE B2/B4/B25/B66 power reduction applied to satisfy SAR compliance. 2. The device employs sensors to detect different usage conditions, when operating in near-body or handheld condition by end user, the device will reduced maximum output powers on the WCDMA B2 / B4, LTE B2 / B4 / B25 / B66 and detail descriptions of the power reduction mechanism are included in the operational description.									
LTE Carrier Aggregation Combinations			Inter-Band and Intra-Band possible combinations and the detail power measurement please referred to section 11.									
LTE Carrier Aggregation Additional Information			This device supports maximum of 3 carriers in the downlink, uplink CA is not supported. Additional following LTE Release features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.									
Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900

LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829				
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5				
H	20643	848.3	20635	847.5	20625	846.5	20600	844				
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510				
M	21100	2535	21100	2535	21100	2535	21100	2535				
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560				
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	23017	699.7	23025	700.5	23035	701.5	23060	704				
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5				
H	23173	715.3	23165	714.5	23155	713.5	23130	711				
LTE Band 13												
	Bandwidth 5 MHz					Bandwidth 10 MHz						
	Channel #		Freq.(MHz)			Channel #		Freq.(MHz)				
L	23205		779.5			23230		782				
M	23230		782									
H	23255		784.5									
LTE Band 17												
	Bandwidth 5 MHz					Bandwidth 10 MHz						
	Channel #		Freq.(MHz)			Channel #		Freq. (MHz)				
L	23755		706.5			23780		709				
M	23790		710			23790		710				
H	23825		713.5			23800		711				
LTE Band 25												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26047	1850.7	26055	1851.5	26065	1852.5	26090	1855	26115	1857.5	26140	1860
M	26340	1880	26340	1880	26340	1880	26340	1880	26340	1880	26340	1880
H	26683	1914.3	26675	1913.5	26665	1912.5	26640	1910	26615	1907.5	26590	1905
LTE Band 66												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	131979	1710.7	131987	1711.5	131997	1712.5	132022	1715	132047	1717.5	132072	1720
M	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745	132322	1745
H	132665	1779.3	132657	1778.5	132647	1777.5	132622	1775	132597	1772.5	132572	1770

4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

6.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1012	Sep. 05, 2018	Sep. 04, 2019
SPEAG	835MHz System Validation Kit	D835V2	4d167	Feb. 27, 2018	Feb. 26, 2019
SPEAG	1750MHz System Validation Kit	D1750V2	1112	Feb. 28, 2018	Feb. 27, 2019
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Sep. 11, 2018	Sep. 10, 2019
SPEAG	2450MHz System Validation Kit	D2450V2	736	Aug. 31, 2018	Aug. 30, 2019
SPEAG	2600MHz System Validation Kit	D2600V2	1008	Aug. 31, 2018	Aug. 30, 2019
SPEAG	5GHz System Validation Kit	D5GHzV2	1006	Sep. 27, 2018	Sep. 26, 2019
SPEAG	Data Acquisition Electronics	DAE3	495	May. 24, 2018	May. 23, 2019
SPEAG	Data Acquisition Electronics	DAE3	577	Sep. 19, 2018	Sep. 18, 2019
SPEAG	Data Acquisition Electronics	DAE4	853	Jul. 24, 2018	Jul. 23, 2019
SPEAG	Data Acquisition Electronics	DAE4	918	Jun. 20, 2018	Jun. 19, 2019
SPEAG	Dosimetric E-Field Probe	ES3DV3	3270	Sep. 24, 2018	Sep. 23, 2019
SPEAG	Dosimetric E-Field Probe	EX3DV4	7306	Jul. 26, 2018	Jul. 25, 2019
SPEAG	Dosimetric E-Field Probe	EX3DV4	7515	Oct. 03, 2018	Oct. 02, 2019
RCPTWN	Thermometer	HTC-1	TM281-1	Mar. 16, 2018	Mar. 15, 2019
RCPTWN	Thermometer	HTC-1	TM560-1	Mar. 16, 2018	Mar. 15, 2019
Gencom	Thermometer	TE1	TM225-1	Mar. 16, 2018	Mar. 15, 2019
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Apr. 17, 2018	Apr. 16, 2019
Agilent	Wireless Communication Test Set	E5515C	MY48360820	Jan. 15, 2018	Jan. 14, 2019
R&S	BT Base Station	CBT	100815	Feb. 05, 2018	Feb. 04, 2019
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Dec. 07, 2017	Dec. 06, 2018
Agilent	ENA Network Analyzer	E5071C	MY46316648	Jan. 17, 2018	Jan. 16, 2019
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 19, 2018	Sep. 18, 2019
LINE SEIKI	Digital Thermometer	DTM3000-spezial	2942	Dec. 08, 2017	Dec. 07, 2018
Anritsu	Power Meter	ML2495A	1419002	May. 18, 2018	May. 17, 2019
Anritsu	Power Sensor	MA2411B	1339124	May. 18, 2018	May. 17, 2019
Anritsu	Power Meter	ML2495A	1240001	Sep. 13, 2018	Sep. 12, 2019
Anritsu	Power Sensor	MA2411B	1207349	Sep. 13, 2018	Sep. 12, 2019
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 28, 2018	Aug. 27, 2019
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 23, 2018	Jun. 22, 2019
Mini-Circuits	Power Amplifier	ZVE-8G+	6382	Aug. 09, 2018	Aug. 08, 2019
Mini-Circuits	Power Amplifier	ZHL-42W+	15542	Aug. 09, 2018	Aug. 08, 2019
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

9. System Verification

9.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.



Fig 10.1Photo of Liquid Height for Head SAR



Fig 10.2 Photo of Liquid Height for Body SAR

9.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	HSL	22.4	0.885	42.910	0.89	41.90	-0.56	2.41	±5	2018/11/29
750	MSL	22.5	0.973	53.678	0.96	55.50	1.35	-3.28	±5	2018/11/27
835	HSL	22.7	0.897	42.957	0.90	41.50	-0.33	3.51	±5	2018/11/28
835	MSL	22.7	0.947	54.503	0.97	55.20	-2.37	-1.26	±5	2018/11/27
835	MSL	22.1	0.966	57.377	0.97	55.20	-0.41	3.94	±5	2018/11/29
1750	HSL	22.7	1.384	41.352	1.37	40.10	1.02	3.12	±5	2018/11/28
1750	MSL	22.5	1.449	55.060	1.49	53.40	-2.75	3.11	±5	2018/11/25
1900	HSL	22.7	1.433	38.773	1.40	40.00	2.36	-3.07	±5	2018/11/28
1900	MSL	22.6	1.530	52.500	1.52	53.30	0.66	-1.50	±5	2018/11/23
1900	MSL	22.5	1.552	52.396	1.52	53.30	2.11	-1.70	±5	2018/11/25
1900	MSL	22.5	1.550	52.469	1.52	53.30	1.97	-1.56	±5	2018/11/26
2450	HSL	22.5	1.775	39.455	1.80	39.20	-1.39	0.65	±5	2018/11/23
2450	HSL	22.4	1.789	38.732	1.80	39.20	-0.61	-1.19	±5	2018/11/26
2450	MSL	22.5	1.960	52.489	1.95	52.70	0.51	-0.40	±5	2018/11/24
2450	MSL	22.1	2.016	54.225	1.95	52.70	3.38	2.89	±5	2018/11/29
2600	HSL	22.1	1.986	37.575	1.96	39.00	1.33	-3.65	±5	2018/11/28
2600	MSL	22.5	2.238	50.598	2.16	52.50	3.61	-3.62	±5	2018/11/25
5250	HSL	22.6	4.677	37.464	4.71	35.95	-0.70	4.21	±5	2018/11/23
5250	MSL	22.4	5.432	48.993	5.36	48.95	1.34	0.09	±5	2018/11/26
5600	HSL	22.6	5.041	36.979	5.07	35.50	-0.57	4.17	±5	2018/11/23
5600	HSL	22.3	5.079	37.102	5.07	35.50	0.18	4.51	±5	2018/11/25
5600	MSL	22.4	5.817	48.505	5.77	48.50	0.81	0.01	±5	2018/11/26
5750	HSL	22.3	5.236	36.841	5.22	35.35	0.31	4.22	±5	2018/11/25
5750	MSL	22.4	5.978	48.301	5.94	48.28	0.64	0.04	±5	2018/11/26

9.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2018/11/29	750	HSL	250	D750V3-1012	ES3DV3 - SN3270	DAE4 Sn853	2.17	8.47	8.68	2.48
2018/11/27	750	MSL	250	D750V3-1012	EX3DV4 - SN7306	DAE3 Sn577	2.30	8.76	9.2	5.02
2018/11/28	835	HSL	250	D835V2-4d167	ES3DV3 - SN3270	DAE3 Sn495	2.23	9.26	8.92	-3.67
2018/11/27	835	MSL	250	D835V2-4d167	EX3DV4 - SN7306	DAE3 Sn577	2.34	9.62	9.36	-2.70
2018/11/29	835	MSL	250	D835V2-4d167	ES3DV3 - SN3270	DAE3 Sn495	2.60	9.62	10.4	8.11
2018/11/28	1750	HSL	250	D1750V2-1112	ES3DV3 - SN3270	DAE3 Sn495	9.73	37.90	38.92	2.69
2018/11/25	1750	MSL	250	D1750V2-1112	EX3DV4 - SN7306	DAE3 Sn577	9.21	38.10	36.84	-3.31
2018/11/28	1900	HSL	250	D1900V2-5d041	ES3DV3 - SN3270	DAE3 Sn495	10.20	40.20	40.8	1.49
2018/11/23	1900	MSL	250	D1900V2-5d041	ES3DV3 - SN3270	DAE3 Sn495	10.50	40.20	42	4.48
2018/11/25	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN7306	DAE3 Sn577	10.70	40.20	42.8	6.47
2018/11/26	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN7306	DAE3 Sn577	10.70	40.20	42.8	6.47
2018/11/23	2450	HSL	250	D2450V2-736	EX3DV4 - SN7515	DAE4 Sn918	13.50	52.70	54	2.47
2018/11/26	2450	HSL	250	D2450V2-736	EX3DV4 - SN7515	DAE4 Sn918	13.30	52.70	53.2	0.95
2018/11/24	2450	MSL	250	D2450V2-736	EX3DV4 - SN7515	DAE4 Sn918	12.20	51.50	48.8	-5.24
2018/11/29	2450	MSL	250	D2450V2-736	ES3DV3 - SN3270	DAE3 Sn495	13.80	51.50	55.2	7.18
2018/11/28	2600	HSL	250	D2600V2-1008	ES3DV3 - SN3270	DAE3 Sn495	13.90	56.40	55.6	-1.42
2018/11/25	2600	MSL	250	D2600V2-1008	EX3DV4 - SN7306	DAE3 Sn577	13.70	55.30	54.8	-0.90
2018/11/23	5250	HSL	100	D5GHzV2-1006	EX3DV4 - SN7515	DAE4 Sn918	8.40	80.70	84	4.09
2018/11/26	5250	MSL	100	D5GHzV2-1006	EX3DV4 - SN7515	DAE4 Sn918	7.43	78.30	74.3	-5.11
2018/11/23	5600	HSL	100	D5GHzV2-1006	EX3DV4 - SN7515	DAE4 Sn918	9.07	83.30	90.7	8.88
2018/11/25	5600	HSL	100	D5GHzV2-1006	EX3DV4 - SN7515	DAE4 Sn918	8.53	83.30	85.3	2.40
2018/11/26	5600	MSL	100	D5GHzV2-1006	EX3DV4 - SN7515	DAE4 Sn918	7.57	81.00	75.7	-6.54
2018/11/25	5750	HSL	100	D5GHzV2-1006	EX3DV4 - SN7515	DAE4 Sn918	8.25	80.40	82.5	2.61
2018/11/26	5750	MSL	100	D5GHzV2-1006	EX3DV4 - SN7515	DAE4 Sn918	7.25	77.40	72.5	-6.33

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2018/11/29	750	HSL	250	D750V3-1012	ES3DV3 - SN3270	DAE4 Sn853	1.46	5.64	5.84	3.55
2018/11/27	750	MSL	250	D750V3-1012	EX3DV4 - SN7306	DAE3 Sn577	1.53	5.97	6.12	2.51
2018/11/28	835	HSL	250	D835V2-4d167	ES3DV3 - SN3270	DAE3 Sn495	1.48	6.03	5.92	-1.82
2018/11/27	835	MSL	250	D835V2-4d167	EX3DV4 - SN7306	DAE3 Sn577	1.54	6.27	6.16	-1.75
2018/11/29	835	MSL	250	D835V2-4d167	ES3DV3 - SN3270	DAE3 Sn495	1.69	6.27	6.76	7.81
2018/11/28	1750	HSL	250	D1750V2-1112	ES3DV3 - SN3270	DAE3 Sn495	5.21	20.00	20.84	4.20
2018/11/25	1750	MSL	250	D1750V2-1112	EX3DV4 - SN7306	DAE3 Sn577	4.98	20.20	19.92	-1.39
2018/11/28	1900	HSL	250	D1900V2-5d041	ES3DV3 - SN3270	DAE3 Sn495	5.08	21.20	20.32	-4.15
2018/11/23	1900	MSL	250	D1900V2-5d041	ES3DV3 - SN3270	DAE3 Sn495	5.39	21.50	21.56	0.28
2018/11/25	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN7306	DAE3 Sn577	5.54	21.50	22.16	3.07
2018/11/26	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN7306	DAE3 Sn577	5.53	21.50	22.12	2.88
2018/11/23	2450	HSL	250	D2450V2-736	EX3DV4 - SN7515	DAE4 Sn918	6.21	24.60	24.84	0.98
2018/11/26	2450	HSL	250	D2450V2-736	EX3DV4 - SN7515	DAE4 Sn918	6.26	24.60	25.04	1.79
2018/11/24	2450	MSL	250	D2450V2-736	EX3DV4 - SN7515	DAE4 Sn918	5.69	24.40	22.76	-6.72
2018/11/29	2450	MSL	250	D2450V2-736	ES3DV3 - SN3270	DAE3 Sn495	6.39	24.40	25.56	4.75
2018/11/28	2600	HSL	250	D2600V2-1008	ES3DV3 - SN3270	DAE3 Sn495	6.09	25.30	24.36	-3.72
2018/11/25	2600	MSL	250	D2600V2-1008	EX3DV4 - SN7306	DAE3 Sn577	6.06	24.70	24.24	-1.86
2018/11/23	5250	HSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	2.41	23.20	24.1	3.88
2018/11/26	5250	MSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	2.09	21.70	20.9	-3.69
2018/11/23	5600	HSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	2.58	23.80	25.8	8.40
2018/11/25	5600	HSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	2.37	23.80	23.7	-0.42
2018/11/26	5600	MSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	2.11	22.50	21.1	-6.22
2018/11/25	5750	HSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	2.35	22.90	23.5	2.62
2018/11/26	5750	MSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	2.04	21.30	20.4	-4.23



Fig 8.3.1 System Performance Check Setup

Fig 8.3.2 Setup Photo

10. RF Exposure Positions

10.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

10.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 9.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

10.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

10.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position



10.5 Product Specific Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.⁶ The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

10.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9$ cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

11. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

- For DTM multi-slot class mode, the device was linked with base station simulator (Agilent E5515C) and transmit maximum power on maximum number of TX slots, i.e. one CS timeslot, and additional PS timeslots (1 for DTM class 5 and 9, 2 for DTM class 11) in one TDMA frame.
- Agilent E5515C was used to setup the device operated under DTM mode for power measurement and SAR testing. For conducted power, the power of the burst for voice and the power of the bursts for data was reported separately in the table above, and the frame-average power is derived below to determine SAR testing.

$$DTM \text{ frame average power (dBm)} = 10 * \log [\sum (\text{power of each slot, in mW}) / 8]$$

- Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
- Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE / DTM modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
- Other configurations of GSM / GPRS / EDGE / DTM are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode
- Power reduction which is triggered by hotspot mode is implemented in GSM1900 band, for hotspot mode SAR testing EUT was set in reduced power mode and GPRS 4Tx slot due to its highest frame-average power.

<Default Power Mode>

GSM850		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		128	189	251		128	189	251	
Frequency (MHz)		824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot		32.75	32.91	32.97	33.50	23.75	23.91	23.97	24.50
GPRS 1 Tx slot		32.96	32.93	32.99	33.50	23.96	23.93	23.99	24.50
GPRS 2 Tx slots		30.69	30.82	30.58	31.00	24.69	24.82	24.58	25.00
GPRS 3 Tx slots		28.37	28.47	28.34	29.20	24.11	24.21	24.08	24.94
GPRS 4 Tx slots		27.47	27.42	27.44	28.00	24.47	24.42	24.44	25.00
EDGE 1 Tx slot		26.86	26.89	26.72	27.50	17.86	17.89	17.72	18.50
EDGE 2 Tx slots		26.69	26.67	26.58	27.30	20.69	20.67	20.58	21.30
EDGE 3 Tx slots		26.14	26.16	26.32	27.10	21.88	21.90	22.06	22.84
EDGE 4 Tx slots		25.88	26.04	26.08	26.90	22.88	23.04	23.08	23.90
DTM Multi-slot class 5	GSM 1 Tx slot	30.60	30.63	30.54	31.00	24.34	24.37	24.26	24.98
	GPRS 1 Tx slot	30.10	30.14	30.00	31.00				
DTM Multi-slot class 9	GSM 1 Tx slot	30.50	30.54	30.48	31.00	24.25	24.26	24.23	24.98
	GPRS 1 Tx slot	30.02	30.01	30.01	31.00				
DTM Multi-slot class 11	GSM 1 Tx slot	28.33	28.35	28.20	29.20	23.76	23.78	23.62	24.94
	GPRS 2 Tx slots	27.85	27.87	27.71	29.20				
DTM Multi-slot class 5	GSM 1 Tx slot	30.71	30.80	30.48	31.00	23.09	23.23	22.96	23.51
	EDGE 1 Tx slot	26.54	26.82	26.68	27.30				
DTM Multi-slot class 9	GSM 1 Tx slot	30.70	30.38	30.50	31.00	23.08	22.73	22.95	23.51
	EDGE 1 Tx slot	26.53	26.10	26.60	27.30				
DTM Multi-slot class 11	GSM 1 Tx slot	28.72	28.91	28.87	29.20	22.94	22.99	22.96	23.66
	EDGE 2 Tx slots	26.17	26.09	26.07	27.10				

GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot		29.69	29.62	29.78	30.50	20.69	20.62	20.78	21.50
GPRS 1 Tx slot		29.51	29.64	29.63	30.50	20.51	20.64	20.63	21.50
GPRS 2 Tx slots		27.04	27.11	27.08	27.50	21.04	21.11	21.08	21.50
GPRS 3 Tx slots		25.72	25.36	25.86	26.00	21.46	21.10	21.60	21.74
GPRS 4 Tx slots		24.87	24.85	24.94	25.00	21.87	21.85	21.94	22.00
EDGE 1 Tx slot		25.83	25.93	25.73	26.00	16.83	16.93	16.73	17.00
EDGE 2 Tx slots		25.67	25.81	25.96	26.00	19.67	19.81	19.96	20.00
EDGE 3 Tx slots		25.49	25.49	25.50	25.50	21.23	21.23	21.24	21.24
EDGE 4 Tx slots		24.53	24.99	24.90	25.00	21.53	21.99	21.90	22.00
DTM Multi-slot class 5	GSM 1 Tx slot	26.96	27.12	27.08	27.50	20.67	20.81	20.76	21.48
	GPRS 1 Tx slot	26.40	26.51	26.45	27.50				
DTM Multi-slot class 9	GSM 1 Tx slot	26.95	27.14	27.09	27.50	20.66	20.81	20.76	21.48
	GPRS 1 Tx slot	26.39	26.50	26.45	27.50				
DTM Multi-slot class 11	GSM 1 Tx slot	25.21	25.59	25.48	26.00	20.58	20.96	20.84	21.74
	GPRS 2 Tx slots	24.64	25.02	24.89	26.00				
DTM Multi-slot class 5	GSM 1 Tx slot	26.37	26.74	26.46	27.50	20.00	20.12	20.05	20.79
	EDGE 1 Tx slot	25.64	25.44	25.65	26.00				
DTM Multi-slot class 9	GSM 1 Tx slot	26.96	27.19	27.15	27.50	20.12	20.25	20.26	20.79
	EDGE 1 Tx slot	25.12	25.09	25.18	26.00				
DTM Multi-slot class 11	GSM 1 Tx slot	25.35	25.29	25.32	26.00	20.63	20.88	20.86	21.41
	EDGE 2 Tx slots	24.64	25.07	25.01	25.50				

<Hotspot Power Mode>

GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot		29.39	29.35	29.37	29.50	20.39	20.35	20.37	20.50
GPRS 1 Tx slot		29.37	29.32	29.33	29.50	20.37	20.32	20.33	20.50
GPRS 2 Tx slots		26.19	26.23	26.12	26.50	20.19	20.23	20.12	20.50
GPRS 3 Tx slots		24.33	24.47	24.49	24.50	20.07	20.21	20.23	20.24
GPRS 4 Tx slots		23.16	23.33	23.49	23.50	20.16	20.33	20.49	20.50
EDGE 1 Tx slot		24.10	24.35	24.34	24.50	15.10	15.35	15.34	15.50
EDGE 2 Tx slots		24.18	24.30	24.22	24.50	18.18	18.30	18.22	18.50
EDGE 3 Tx slots		23.61	23.71	23.54	24.00	19.35	19.45	19.28	19.74
EDGE 4 Tx slots		22.89	22.90	22.98	23.50	19.89	19.90	19.98	20.50
DTM Multi-slot class 5	GSM 1 Tx slot	25.73	25.67	25.61	26.50	19.66	19.66	19.58	20.48
	GPRS 1 Tx slot	25.64	25.69	25.59	26.50				
DTM Multi-slot class 9	GSM 1 Tx slot	25.60	25.65	25.61	26.50	19.50	19.58	19.45	20.48
	GPRS 1 Tx slot	25.43	25.56	25.33	26.50				
DTM Multi-slot class 11	GSM 1 Tx slot	23.75	24.06	24.08	24.50	19.48	19.58	19.66	20.24
	GPRS 2 Tx slots	23.73	23.73	23.84	24.50				
DTM Multi-slot class 5	GSM 1 Tx slot	25.76	25.80	25.66	26.50	18.80	18.91	18.77	19.59
	EDGE 1 Tx slot	23.61	23.83	23.69	24.50				
DTM Multi-slot class 9	GSM 1 Tx slot	25.69	25.55	25.58	26.50	18.76	18.74	18.67	19.59
	EDGE 1 Tx slot	23.63	23.79	23.57	24.50				
DTM Multi-slot class 11	GSM 1 Tx slot	23.83	23.94	24.05	24.50	19.17	19.19	19.19	19.91
	EDGE 2 Tx slots	23.21	23.18	23.12	24.00				

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5
Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$. Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPCCH, DPDCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases. Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.							

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_d/\beta_c = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration


DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Cycle to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12
Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		


Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)
Setup Configuration

<WCDMA Conducted Power>
General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

<Default Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	AMR 12.2Kbps	24.40	24.34	24.44	25.00	24.35	24.41	24.34	24.50	24.53	24.40	24.50	25.00
3GPP Rel 99	RMC 12.2Kbps	24.43	24.37	24.47	25.00	24.36	24.43	24.36	24.50	24.55	24.42	24.51	25.00
3GPP Rel 6	HSDPA Subtest-1	23.57	23.54	23.49	24.00	23.40	23.47	23.34	23.50	23.54	23.46	23.52	24.00
3GPP Rel 6	HSDPA Subtest-2	23.58	23.57	23.51	24.00	23.41	23.47	23.33	23.50	23.59	23.41	23.50	24.00
3GPP Rel 6	HSDPA Subtest-3	23.11	23.07	23.04	23.50	22.92	22.95	22.89	23.00	23.07	23.00	23.06	23.50
3GPP Rel 6	HSDPA Subtest-4	23.11	23.06	23.03	23.50	22.91	22.93	22.90	23.00	23.07	23.00	23.08	23.50
3GPP Rel 8	DC-HSDPA Subtest-1	23.47	23.48	23.49	24.00	23.41	23.48	23.36	23.50	23.44	23.36	23.42	24.00
3GPP Rel 8	DC-HSDPA Subtest-2	23.48	23.45	23.51	24.00	23.42	23.46	23.33	23.50	23.48	23.31	23.40	24.00
3GPP Rel 8	DC-HSDPA Subtest-3	23.00	22.96	23.04	23.50	22.91	22.96	22.90	23.00	22.97	22.90	22.96	23.50
3GPP Rel 8	DC-HSDPA Subtest-4	22.98	22.93	23.02	23.50	22.92	22.94	22.89	23.00	22.98	22.91	22.99	23.50
3GPP Rel 6	HSUPA Subtest-1	23.50	23.48	23.40	23.50	22.45	22.43	22.43	22.50	23.47	23.31	23.38	23.50
3GPP Rel 6	HSUPA Subtest-2	21.48	21.50	21.48	21.50	20.50	20.43	20.42	20.50	21.45	21.35	21.37	21.50
3GPP Rel 6	HSUPA Subtest-3	22.46	22.40	22.40	22.50	21.45	21.41	21.41	21.50	22.47	22.35	22.35	22.50
3GPP Rel 6	HSUPA Subtest-4	21.48	21.43	21.39	21.50	20.46	20.41	20.40	20.50	21.43	21.27	21.40	21.50
3GPP Rel 6	HSUPA Subtest-5	23.45	23.40	23.45	23.50	22.45	22.50	22.48	22.50	23.45	23.35	23.35	23.50

<Hotspot Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513	
Rx Channel		9662	9800	9938		1537	1638	1738	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6	
3GPP Rel 99	AMR 12.2Kbps	19.72	19.90	19.84	20.00	20.30	20.40	20.28	20.50
3GPP Rel 99	RMC 12.2Kbps	19.90	19.91	19.87	20.00	20.39	20.43	20.40	20.50
3GPP Rel 6	HSDPA Subtest-1	18.83	18.77	18.87	19.00	19.44	19.49	19.45	19.50
3GPP Rel 6	HSDPA Subtest-2	18.78	18.75	19.00	19.00	19.49	19.41	19.44	19.50
3GPP Rel 6	HSDPA Subtest-3	18.43	18.43	18.50	18.50	18.96	18.97	18.97	19.00
3GPP Rel 6	HSDPA Subtest-4	18.30	18.35	18.44	18.50	18.96	18.95	18.95	19.00
3GPP Rel 8	DC-HSDPA Subtest-1	18.84	18.81	18.87	19.00	19.45	19.44	19.31	19.50
3GPP Rel 8	DC-HSDPA Subtest-2	18.92	18.78	18.84	19.00	19.45	19.49	19.23	19.50
3GPP Rel 8	DC-HSDPA Subtest-3	18.21	18.23	18.48	18.50	18.94	18.87	18.80	19.00
3GPP Rel 8	DC-HSDPA Subtest-4	18.20	18.27	18.40	18.50	18.97	18.95	18.83	19.00
3GPP Rel 6	HSUPA Subtest-1	18.76	18.83	18.97	19.00	18.40	18.50	18.43	19.50
3GPP Rel 6	HSUPA Subtest-2	16.74	16.78	16.97	17.00	16.40	16.50	16.49	17.50
3GPP Rel 6	HSUPA Subtest-3	17.73	17.90	18.00	18.00	17.41	17.41	17.35	18.50
3GPP Rel 6	HSUPA Subtest-4	16.84	16.81	16.99	17.00	16.44	16.43	16.42	17.50
3GPP Rel 6	HSUPA Subtest-5	18.73	18.94	18.90	19.00	18.45	18.41	18.53	19.50


<Near-Body and Product Specific Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513	
Rx Channel		9662	9800	9938		1537	1638	1738	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6	
3GPP Rel 99	AMR 12.2Kbps	22.27	22.27	22.37	22.50	22.36	22.33	22.30	22.50
3GPP Rel 99	RMC 12.2Kbps	22.23	22.43	22.49	22.50	22.36	22.43	22.37	22.50
3GPP Rel 6	HSDPA Subtest-1	21.37	21.37	21.31	21.50	21.46	21.35	21.39	21.50
3GPP Rel 6	HSDPA Subtest-2	21.33	21.34	21.39	21.50	21.27	21.50	21.33	21.50
3GPP Rel 6	HSDPA Subtest-3	20.77	20.70	20.86	21.00	20.84	20.96	20.88	21.00
3GPP Rel 6	HSDPA Subtest-4	20.93	20.87	20.85	21.00	20.93	20.98	20.77	21.00
3GPP Rel 8	DC-HSDPA Subtest-1	21.06	21.30	21.24	21.50	21.34	21.46	21.38	21.50
3GPP Rel 8	DC-HSDPA Subtest-2	21.24	21.34	21.49	21.50	21.47	21.38	21.31	21.50
3GPP Rel 8	DC-HSDPA Subtest-3	20.94	20.61	20.84	21.00	20.99	20.87	20.89	21.00
3GPP Rel 8	DC-HSDPA Subtest-4	20.87	20.85	20.80	21.00	20.92	20.89	20.91	21.00
3GPP Rel 6	HSUPA Subtest-1	21.43	21.31	21.24	21.50	20.50	20.45	20.47	21.50
3GPP Rel 6	HSUPA Subtest-2	19.32	19.13	19.48	19.50	18.51	18.48	18.49	19.50
3GPP Rel 6	HSUPA Subtest-3	20.37	20.23	20.28	20.50	19.38	19.50	19.39	20.50
3GPP Rel 6	HSUPA Subtest-4	19.25	19.49	19.28	19.50	18.56	18.43	18.43	19.50
3GPP Rel 6	HSUPA Subtest-5	21.41	21.33	21.34	21.50	20.48	20.47	20.44	21.50


<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B5/B12 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 2/4/17 SAR test was covered by Band 25/66/12; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM

<Default Power Mode>
<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	23.94	23.91	23.88	24.5	0
20	QPSK	1	49	23.88	23.87	23.82		
20	QPSK	1	99	23.84	23.81	23.78		
20	QPSK	50	0	22.91	22.95	22.91	23.5	1
20	QPSK	50	24	22.89	22.92	22.81		
20	QPSK	50	50	22.89	22.86	22.86		
20	QPSK	100	0	22.96	22.87	22.79	23.5	1
20	16QAM	1	0	23.26	23.08	23.19		
20	16QAM	1	49	23.21	23.15	23.19		
20	16QAM	1	99	23.09	23.21	23.07	22.5	2
20	16QAM	50	0	22.02	22.00	21.94		
20	16QAM	50	24	22.03	22.04	22.04		
20	16QAM	50	50	22.05	21.98	21.99	22.5	2
20	16QAM	100	0	22.07	21.99	21.91		
20	64QAM	1	0	22.25	22.09	22.13		
20	64QAM	1	49	22.18	22.14	22.12	22.5	2
20	64QAM	1	99	22.05	22.13	22.04		
20	64QAM	50	0	21.05	21.05	20.99	21.5	3
20	64QAM	50	24	21.05	21.08	21.08		
20	64QAM	50	50	21.06	21.04	21.03		
20	64QAM	100	0	21.13	21.02	20.94		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	23.78	23.84	23.78	24.5	0
15	QPSK	1	37	23.76	23.86	23.74		
15	QPSK	1	74	23.65	23.78	23.69		
15	QPSK	36	0	22.79	22.93	22.80	23.5	1
15	QPSK	36	20	22.85	22.95	22.81		
15	QPSK	36	39	22.74	22.90	22.77		
15	QPSK	75	0	22.81	22.89	22.81	23.5	1
15	16QAM	1	0	23.12	23.05	23.16		
15	16QAM	1	37	23.12	23.14	23.04		
15	16QAM	1	74	22.91	23.12	22.99	22.5	2
15	16QAM	36	0	21.97	21.99	21.92		
15	16QAM	36	20	21.98	22.06	21.90		
15	16QAM	36	39	21.90	22.02	21.89	22.5	2
15	16QAM	75	0	21.90	21.99	21.90		
15	64QAM	1	0	22.10	22.04	22.11		
15	64QAM	1	37	22.06	22.11	22.01	22.5	2
15	64QAM	1	74	21.87	22.10	21.94		
15	64QAM	36	0	21.03	21.06	20.98	21.5	3
15	64QAM	36	20	21.03	21.11	21.01		
15	64QAM	36	39	20.92	21.09	20.95		
15	64QAM	75	0	20.96	21.03	20.96		

Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	23.88	23.86	23.78	24.5	0
10	QPSK	1	25	23.77	23.85	23.74		
10	QPSK	1	49	23.76	23.85	23.69		
10	QPSK	25	0	22.81	22.93	22.83	23.5	1
10	QPSK	25	12	22.81	22.92	22.85		
10	QPSK	25	25	22.76	22.89	22.75		
10	QPSK	50	0	22.79	22.91	22.80	23.5	1
10	16QAM	1	0	23.23	23.20	23.08		
10	16QAM	1	25	23.15	23.16	23.05		
10	16QAM	1	49	23.11	23.23	22.98	22.5	2
10	16QAM	25	0	21.97	22.03	21.88		
10	16QAM	25	12	21.96	22.01	21.88		
10	16QAM	25	25	21.91	21.98	21.87	22.5	2
10	16QAM	50	0	21.93	22.00	21.92		
10	64QAM	1	0	22.17	22.17	22.03		
10	64QAM	1	25	22.10	22.11	21.99	22.5	2
10	64QAM	1	49	22.05	22.15	21.95		
10	64QAM	25	0	20.98	21.06	20.92		
10	64QAM	25	12	21.00	21.09	20.95	21.5	3
10	64QAM	25	25	20.92	21.02	20.91		
10	64QAM	50	0	20.96	21.04	20.92		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	23.74	23.84	23.71	24.5	0
5	QPSK	1	12	23.76	23.85	23.73		
5	QPSK	1	24	23.70	23.81	23.68		
5	QPSK	12	0	22.82	22.90	22.79	23.5	1
5	QPSK	12	7	22.80	22.91	22.79		
5	QPSK	12	13	22.79	22.87	22.77		
5	QPSK	25	0	22.78	22.88	22.78	23.5	1
5	16QAM	1	0	23.11	23.05	22.97		
5	16QAM	1	12	23.15	23.14	22.97		
5	16QAM	1	24	23.06	23.08	22.91	22.5	2
5	16QAM	12	0	21.96	22.00	21.88		
5	16QAM	12	7	21.97	22.01	21.87		
5	16QAM	12	13	21.92	22.01	21.87	22.5	2
5	16QAM	25	0	21.90	21.97	21.85		
5	64QAM	1	0	22.03	22.06	21.95		
5	64QAM	1	12	22.09	22.12	21.96	22.5	2
5	64QAM	1	24	22.00	22.07	21.94		
5	64QAM	12	0	21.03	21.07	20.94		
5	64QAM	12	7	21.03	21.13	20.99	21.5	3
5	64QAM	12	13	21.01	21.09	20.94		
5	64QAM	25	0	20.93	21.00	20.89		

Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	23.72	23.84	23.82	24.5	0
3	QPSK	1	8	23.74	23.85	23.81		
3	QPSK	1	14	23.71	23.83	23.77		
3	QPSK	8	0	22.79	22.89	22.83	23.5	1
3	QPSK	8	4	22.83	22.92	22.89		
3	QPSK	8	7	22.75	22.88	22.86		
3	QPSK	15	0	22.74	22.91	22.88		
3	16QAM	1	0	23.07	23.10	23.06	23.5	1
3	16QAM	1	8	23.13	23.14	23.09		
3	16QAM	1	14	23.06	23.08	23.04		
3	16QAM	8	0	21.96	22.03	21.88	22.5	2
3	16QAM	8	4	22.00	22.05	21.91		
3	16QAM	8	7	21.96	22.01	21.88		
3	16QAM	15	0	21.90	22.00	21.86		
3	64QAM	1	0	22.04	22.07	21.95	22.5	2
3	64QAM	1	8	22.07	22.11	21.97		
3	64QAM	1	14	22.04	22.06	21.96		
3	64QAM	8	0	21.01	21.06	20.94	21.5	3
3	64QAM	8	4	21.04	21.11	20.98		
3	64QAM	8	7	20.99	21.09	20.93		
3	64QAM	15	0	20.94	21.01	20.90		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	23.69	23.80	23.63	24.5	0
1.4	QPSK	1	3	23.74	23.86	23.72		
1.4	QPSK	1	5	23.69	23.78	23.63		
1.4	QPSK	3	0	23.71	23.83	23.69		
1.4	QPSK	3	1	23.78	23.91	23.72		
1.4	QPSK	3	3	23.74	23.83	23.68		
1.4	QPSK	6	0	22.71	22.85	22.71	23.5	1
1.4	16QAM	1	0	23.05	23.05	22.89	23.5	1
1.4	16QAM	1	3	23.08	23.10	22.98		
1.4	16QAM	1	5	23.01	23.05	22.88		
1.4	16QAM	3	0	22.82	22.89	22.73		
1.4	16QAM	3	1	22.87	22.92	22.75		
1.4	16QAM	3	3	22.83	22.86	22.75		
1.4	16QAM	6	0	21.93	21.98	21.87	22.5	2
1.4	64QAM	1	0	21.99	22.03	21.92	22.5	2
1.4	64QAM	1	3	22.09	22.09	21.93		
1.4	64QAM	1	5	21.99	22.04	21.87		
1.4	64QAM	3	0	21.97	22.03	21.89		
1.4	64QAM	3	1	22.01	22.08	21.91		
1.4	64QAM	3	3	21.97	22.03	21.90		
1.4	64QAM	6	0	20.88	20.97	20.83	21.5	3

<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	24.43	24.45	24.39	24.5	0
20	QPSK	1	49	24.41	24.40	24.32		
20	QPSK	1	99	24.33	24.24	24.27		
20	QPSK	50	0	23.46	23.47	23.48	23.5	1
20	QPSK	50	24	23.48	23.50	23.49		
20	QPSK	50	50	23.43	23.43	23.42		
20	QPSK	100	0	23.46	23.47	23.43		
20	16QAM	1	0	23.34	23.50	23.40	23.5	1
20	16QAM	1	49	23.45	23.44	23.27		
20	16QAM	1	99	23.42	23.20	23.24		
20	16QAM	50	0	22.36	22.35	22.32	22.5	2
20	16QAM	50	24	22.37	22.38	22.29		
20	16QAM	50	50	22.33	22.29	22.26		
20	16QAM	100	0	22.34	22.32	22.27		
20	64QAM	1	0	22.35	22.47	22.39	22.5	2
20	64QAM	1	49	22.44	22.41	22.26		
20	64QAM	1	99	22.39	22.20	22.26		
20	64QAM	50	0	21.37	21.42	21.34	21.5	3
20	64QAM	50	24	21.41	21.40	21.34		
20	64QAM	50	50	21.38	21.33	21.27		
20	64QAM	100	0	21.37	21.36	21.28		
Channel				20025	20175	20325		
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	24.41	24.44	24.37	24.5	0
15	QPSK	1	37	24.39	24.31	24.33		
15	QPSK	1	74	24.35	24.29	24.25		
15	QPSK	36	0	23.49	23.50	23.44	23.5	1
15	QPSK	36	20	23.50	23.49	23.46		
15	QPSK	36	39	23.47	23.42	23.38		
15	QPSK	75	0	23.48	23.45	23.40		
15	16QAM	1	0	23.35	23.50	23.28	23.5	1
15	16QAM	1	37	23.39	23.40	23.24		
15	16QAM	1	74	23.42	23.21	23.27		
15	16QAM	36	0	22.31	22.38	22.22	22.5	2
15	16QAM	36	20	22.36	22.37	22.25		
15	16QAM	36	39	22.31	22.30	22.20		
15	16QAM	75	0	22.30	22.32	22.20		
15	64QAM	1	0	22.35	22.49	22.31	22.5	2
15	64QAM	1	37	22.41	22.41	22.28		
15	64QAM	1	74	22.39	22.22	22.27		
15	64QAM	36	0	21.37	21.42	21.32	21.5	3
15	64QAM	36	20	21.43	21.42	21.31		
15	64QAM	36	39	21.36	21.34	21.29		
15	64QAM	75	0	21.37	21.35	21.28		

Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	24.38	24.43	24.31	24.5	0
10	QPSK	1	25	24.44	24.40	24.26		
10	QPSK	1	49	24.38	24.35	24.21		
10	QPSK	25	0	23.50	23.48	23.39	23.5	1
10	QPSK	25	12	23.50	23.50	23.38		
10	QPSK	25	25	23.49	23.46	23.33		
10	QPSK	50	0	23.34	23.28	23.18	23.5	1
10	16QAM	1	0	23.40	23.50	23.26		
10	16QAM	1	25	23.41	23.49	23.24		
10	16QAM	1	49	23.43	23.33	23.24	22.5	2
10	16QAM	25	0	22.37	22.39	22.18		
10	16QAM	25	12	22.36	22.35	22.19		
10	16QAM	25	25	22.32	22.32	22.15	22.5	2
10	16QAM	50	0	22.36	22.34	22.17		
10	64QAM	1	0	22.39	22.49	22.20	22.5	2
10	64QAM	1	25	22.39	22.45	22.19		
10	64QAM	1	49	22.40	22.33	22.18		
10	64QAM	25	0	21.40	21.40	21.20	21.5	3
10	64QAM	25	12	21.37	21.39	21.22		
10	64QAM	25	25	21.33	21.32	21.17		
10	64QAM	50	0	21.38	21.36	21.22		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	24.43	24.39	24.25	24.5	0
5	QPSK	1	12	24.43	24.38	24.26		
5	QPSK	1	24	24.38	24.32	24.22		
5	QPSK	12	0	23.47	23.48	23.33	23.5	1
5	QPSK	12	7	23.50	23.50	23.34		
5	QPSK	12	13	23.46	23.42	23.28		
5	QPSK	25	0	23.32	23.25	23.15	23.5	1
5	16QAM	1	0	23.33	23.44	23.20		
5	16QAM	1	12	23.34	23.41	23.23		
5	16QAM	1	24	23.32	23.36	23.22	22.5	2
5	16QAM	12	0	22.31	22.36	22.13		
5	16QAM	12	7	22.35	22.36	22.21		
5	16QAM	12	13	22.31	22.32	22.14	22.5	2
5	16QAM	25	0	22.33	22.34	22.16		
5	64QAM	1	0	22.35	22.44	22.20		
5	64QAM	1	12	22.34	22.41	22.23	22.5	2
5	64QAM	1	24	22.32	22.33	22.21		
5	64QAM	12	0	21.38	21.43	21.22	21.5	3
5	64QAM	12	7	21.40	21.44	21.24		
5	64QAM	12	13	21.34	21.37	21.23		
5	64QAM	25	0	21.36	21.36	21.16		

Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	24.40	24.40	24.24	24.5	0
3	QPSK	1	8	24.43	24.39	24.24		
3	QPSK	1	14	24.41	24.36	24.20		
3	QPSK	8	0	23.48	23.43	23.28	23.5	1
3	QPSK	8	4	23.34	23.47	23.33		
3	QPSK	8	7	23.48	23.42	23.29		
3	QPSK	15	0	23.32	23.26	23.11	23.5	1
3	16QAM	1	0	23.34	23.45	23.23		
3	16QAM	1	8	23.36	23.46	23.27		
3	16QAM	1	14	23.30	23.37	23.23	22.5	2
3	16QAM	8	0	22.33	22.35	22.17		
3	16QAM	8	4	22.35	22.40	22.19		
3	16QAM	8	7	22.31	22.33	22.17	22.5	2
3	16QAM	15	0	22.36	22.34	22.18		
3	64QAM	1	0	22.32	22.40	22.18		
3	64QAM	1	8	22.34	22.42	22.24	22.5	2
3	64QAM	1	14	22.34	22.38	22.21		
3	64QAM	8	0	21.39	21.38	21.21		
3	64QAM	8	4	21.36	21.44	21.25	21.5	3
3	64QAM	8	7	21.37	21.37	21.19		
3	64QAM	15	0	21.38	21.36	21.20		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	24.39	24.33	24.20	24.5	0
1.4	QPSK	1	3	24.44	24.38	24.26		
1.4	QPSK	1	5	24.38	24.32	24.16		
1.4	QPSK	3	0	24.41	24.36	24.23		
1.4	QPSK	3	1	24.38	24.41	24.28		
1.4	QPSK	3	3	24.39	24.37	24.22		
1.4	QPSK	6	0	23.41	23.40	23.27	23.5	1
1.4	16QAM	1	0	23.29	23.36	23.20	23.5	1
1.4	16QAM	1	3	23.34	23.43	23.25		
1.4	16QAM	1	5	23.27	23.32	23.19		
1.4	16QAM	3	0	23.14	23.19	23.04		
1.4	16QAM	3	1	23.19	23.24	23.09		
1.4	16QAM	3	3	23.13	23.19	23.01		
1.4	16QAM	6	0	22.38	22.33	22.17	22.5	2
1.4	64QAM	1	0	22.30	22.38	22.18	22.5	2
1.4	64QAM	1	3	22.35	22.44	22.22		
1.4	64QAM	1	5	22.30	22.32	22.16		
1.4	64QAM	3	0	22.31	22.35	22.16		
1.4	64QAM	3	1	22.35	22.39	22.19		
1.4	64QAM	3	3	22.28	22.33	22.13		
1.4	64QAM	6	0	21.28	21.27	21.12	21.5	3

<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	24.12	24.15	23.98	25	0
10	QPSK	1	25	24.07	24.09	23.97		
10	QPSK	1	49	24.08	24.03	23.94		
10	QPSK	25	0	23.19	23.19	23.03	24	1
10	QPSK	25	12	23.28	23.15	23.10		
10	QPSK	25	25	23.17	23.13	23.04		
10	QPSK	50	0	23.15	23.16	23.01		
10	16QAM	1	0	23.32	23.48	23.11	24	1
10	16QAM	1	25	23.43	23.33	23.19		
10	16QAM	1	49	23.44	23.15	23.05		
10	16QAM	25	0	22.29	22.27	22.04	23	2
10	16QAM	25	12	22.38	22.25	22.14		
10	16QAM	25	25	22.34	22.17	22.08		
10	16QAM	50	0	22.35	22.23	22.05		
10	64QAM	1	0	22.24	22.40	22.03	23	2
10	64QAM	1	25	22.34	22.28	22.13		
10	64QAM	1	49	22.36	22.11	22.00		
10	64QAM	25	0	21.28	21.31	21.10	22	3
10	64QAM	25	12	21.38	21.28	21.16		
10	64QAM	25	25	21.34	21.16	21.12		
10	64QAM	50	0	21.38	21.26	21.06		
Channel				20425	20525	20625	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	24.12	24.07	23.98	25	0
5	QPSK	1	12	24.13	24.09	24.01		
5	QPSK	1	24	24.07	24.05	23.93		
5	QPSK	12	0	23.17	23.15	23.03	24	1
5	QPSK	12	7	23.19	23.16	23.06		
5	QPSK	12	13	23.16	23.13	23.01		
5	QPSK	25	0	23.18	23.13	23.04		
5	16QAM	1	0	23.25	23.38	23.12	24	1
5	16QAM	1	12	23.32	23.30	23.14		
5	16QAM	1	24	23.32	23.19	23.02		
5	16QAM	12	0	22.24	22.25	22.10	23	2
5	16QAM	12	7	22.28	22.24	22.11		
5	16QAM	12	13	22.23	22.16	22.04		
5	16QAM	25	0	22.22	22.20	22.07		
5	64QAM	1	0	22.29	22.36	22.17	23	2
5	64QAM	1	12	22.31	22.30	22.13		
5	64QAM	1	24	22.34	22.16	22.05		
5	64QAM	12	0	21.30	21.30	21.14	22	3
5	64QAM	12	7	21.36	21.32	21.18		
5	64QAM	12	13	21.30	21.26	21.14		
5	64QAM	25	0	21.29	21.24	21.10		

Channel				20415	20525	20635	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	24.12	24.09	23.94	25	0
3	QPSK	1	8	24.09	24.06	23.93		
3	QPSK	1	14	24.06	24.04	23.92		
3	QPSK	8	0	23.16	23.11	23.01	24	1
3	QPSK	8	4	23.17	23.14	23.03		
3	QPSK	8	7	23.15	23.09	22.98		
3	QPSK	15	0	23.19	23.12	23.04		
3	16QAM	1	0	23.28	23.37	23.13	24	1
3	16QAM	1	8	23.33	23.32	23.08		
3	16QAM	1	14	23.32	23.08	23.01		
3	16QAM	8	0	22.26	22.25	22.06	23	2
3	16QAM	8	4	22.27	22.23	22.07		
3	16QAM	8	7	22.26	22.18	22.02		
3	16QAM	15	0	22.26	22.23	22.08		
3	64QAM	1	0	22.27	22.31	22.11	23	2
3	64QAM	1	8	22.11	22.26	22.09		
3	64QAM	1	14	22.31	22.20	22.01		
3	64QAM	8	0	21.27	21.28	21.11	22	3
3	64QAM	8	4	21.33	21.27	21.14		
3	64QAM	8	7	21.29	21.23	21.09		
3	64QAM	15	0	21.26	21.25	20.92		
Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	24.05	23.99	23.92	25	0
1.4	QPSK	1	3	24.11	24.08	23.97		
1.4	QPSK	1	5	24.05	23.98	23.89		
1.4	QPSK	3	0	24.11	24.06	23.90		
1.4	QPSK	3	1	24.14	24.12	23.98		
1.4	QPSK	3	3	24.10	24.07	23.91		
1.4	QPSK	6	0	23.14	23.06	22.98	24	1
1.4	16QAM	1	0	23.21	23.22	23.04	24	1
1.4	16QAM	1	3	23.31	23.30	23.05		
1.4	16QAM	1	5	23.23	23.19	22.95		
1.4	16QAM	3	0	23.08	23.05	22.85		
1.4	16QAM	3	1	23.12	23.11	22.91		
1.4	16QAM	3	3	23.09	23.03	22.82		
1.4	16QAM	6	0	22.25	22.22	22.02	23	2
1.4	64QAM	1	0	22.20	22.24	22.03	23	2
1.4	64QAM	1	3	22.29	22.26	22.07		
1.4	64QAM	1	5	22.21	22.20	21.96		
1.4	64QAM	3	0	22.22	22.26	22.03		
1.4	64QAM	3	1	22.27	22.28	22.08		
1.4	64QAM	3	3	22.23	22.21	22.01		
1.4	64QAM	6	0	21.20	21.17	20.98	22	3

<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	24.25	24.28	24.22	24.5	0
20	QPSK	1	49	24.31	24.28	24.27		
20	QPSK	1	99	24.39	24.37	24.34		
20	QPSK	50	0	23.32	23.29	23.29	23.5	1
20	QPSK	50	24	23.36	23.34	23.34		
20	QPSK	50	50	23.38	23.35	23.35		
20	QPSK	100	0	23.36	23.35	23.32		
20	16QAM	1	0	23.38	23.39	23.39	23.5	1
20	16QAM	1	49	23.45	23.46	23.45		
20	16QAM	1	99	23.50	23.50	23.46		
20	16QAM	50	0	22.43	22.38	22.41	22.5	2
20	16QAM	50	24	22.48	22.45	22.46		
20	16QAM	50	50	22.49	22.47	22.48		
20	16QAM	100	0	22.47	22.44	22.47		
20	64QAM	1	0	22.33	22.29	22.32	22.5	2
20	64QAM	1	49	22.38	22.34	22.36		
20	64QAM	1	99	22.43	22.50	22.45		
20	64QAM	50	0	21.44	21.40	21.43	21.5	3
20	64QAM	50	24	21.49	21.44	21.48		
20	64QAM	50	50	21.49	21.48	21.46		
20	64QAM	100	0	21.47	21.45	21.47		
Channel				20825	21100	21375		
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	24.33	24.31	24.27	24.5	0
15	QPSK	1	37	24.32	24.30	24.27		
15	QPSK	1	74	24.35	24.32	24.29		
15	QPSK	36	0	23.39	23.36	23.34	23.5	1
15	QPSK	36	20	23.42	23.41	23.39		
15	QPSK	36	39	23.42	23.43	23.40		
15	QPSK	75	0	23.39	23.39	23.35		
15	16QAM	1	0	23.46	23.43	23.41	23.5	1
15	16QAM	1	37	23.49	23.43	23.46		
15	16QAM	1	74	23.50	23.50	23.50		
15	16QAM	36	0	22.28	22.24	22.25	22.5	2
15	16QAM	36	20	22.34	22.28	22.28		
15	16QAM	36	39	22.33	22.30	22.30		
15	16QAM	75	0	22.30	22.25	22.26		
15	64QAM	1	0	22.42	22.36	22.37	22.5	2
15	64QAM	1	37	22.42	22.39	22.38		
15	64QAM	1	74	22.50	22.49	22.46		
15	64QAM	36	0	21.31	21.27	21.28	21.5	3
15	64QAM	36	20	21.34	21.33	21.34		
15	64QAM	36	39	21.36	21.35	21.33		
15	64QAM	75	0	21.29	21.26	21.26		

Channel				20800	21100	21400	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565		
10	QPSK	1	0	24.27	24.27	24.22	24.5	0
10	QPSK	1	25	24.30	24.31	24.26		
10	QPSK	1	49	24.36	24.33	24.30		
10	QPSK	25	0	23.31	23.31	23.27	23.5	1
10	QPSK	25	12	23.35	23.35	23.30		
10	QPSK	25	25	23.35	23.34	23.32		
10	QPSK	50	0	23.32	23.31	23.29	23.5	1
10	16QAM	1	0	23.45	23.40	23.42		
10	16QAM	1	25	23.47	23.46	23.42		
10	16QAM	1	49	23.50	23.47	23.43	22.5	2
10	16QAM	25	0	22.41	22.37	22.40		
10	16QAM	25	12	22.44	22.45	22.41		
10	16QAM	25	25	22.47	22.45	22.42	22.5	2
10	16QAM	50	0	22.45	22.42	22.40		
10	64QAM	1	0	22.38	22.34	22.35		
10	64QAM	1	25	22.41	22.39	22.37	22.5	2
10	64QAM	1	49	22.46	22.43	22.42		
10	64QAM	25	0	21.45	21.40	21.41		
10	64QAM	25	12	21.47	21.46	21.44	21.5	3
10	64QAM	25	25	21.45	21.47	21.44		
10	64QAM	50	0	21.47	21.43	21.44		
Channel				20775	21100	21425	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	24.38	24.28	24.22	24.5	0
5	QPSK	1	12	24.30	24.31	24.21		
5	QPSK	1	24	24.34	24.34	24.26		
5	QPSK	12	0	23.46	23.31	23.26	23.5	1
5	QPSK	12	7	23.48	23.35	23.30		
5	QPSK	12	13	23.48	23.39	23.31		
5	QPSK	25	0	23.46	23.32	23.26	23.5	1
5	16QAM	1	0	23.42	23.38	23.36		
5	16QAM	1	12	23.43	23.44	23.37		
5	16QAM	1	24	23.50	23.46	23.36	22.5	2
5	16QAM	12	0	22.34	22.23	22.17		
5	16QAM	12	7	22.37	22.26	22.21		
5	16QAM	12	13	22.37	22.26	22.25	22.5	2
5	16QAM	25	0	22.35	22.22	22.19		
5	64QAM	1	0	22.47	22.37	22.33		
5	64QAM	1	12	22.47	22.40	22.36	22.5	2
5	64QAM	1	24	22.46	22.38	22.31		
5	64QAM	12	0	21.28	21.22	21.23		
5	64QAM	12	7	21.42	21.31	21.30	21.5	3
5	64QAM	12	13	21.42	21.32	21.27		
5	64QAM	25	0	21.31	21.20	21.20		

<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130		
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	23.55	23.59	23.58	24.5	0
10	QPSK	1	25	23.53	23.56	23.46		
10	QPSK	1	49	23.52	23.53	23.54		
10	QPSK	25	0	22.56	22.62	22.52	23.5	1
10	QPSK	25	12	22.58	22.61	22.53		
10	QPSK	25	25	22.52	22.58	22.47		
10	QPSK	50	0	22.57	22.61	22.50		
10	16QAM	1	0	22.75	22.83	22.75	23.5	1
10	16QAM	1	25	22.81	22.91	22.90		
10	16QAM	1	49	22.90	22.84	22.87		
10	16QAM	25	0	21.63	21.70	21.58	22.5	2
10	16QAM	25	12	21.66	21.70	21.62		
10	16QAM	25	25	21.66	21.63	21.62		
10	16QAM	50	0	21.63	21.64	21.56		
10	64QAM	1	0	21.62	21.71	21.64	22.5	2
10	64QAM	1	25	21.69	21.76	21.76		
10	64QAM	1	49	21.79	21.75	21.76		
10	64QAM	25	0	20.62	20.67	20.60	21.5	3
10	64QAM	25	12	20.69	20.74	20.67		
10	64QAM	25	25	20.66	20.69	20.58		
10	64QAM	50	0	20.63	20.70	20.62		
Channel				23035	23095	23155	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	23.56	23.50	23.52	24.5	0
5	QPSK	1	12	23.56	23.53	23.52		
5	QPSK	1	24	23.58	23.50	23.58		
5	QPSK	12	0	22.62	22.54	22.58	23.5	1
5	QPSK	12	7	22.63	22.56	22.74		
5	QPSK	12	13	22.71	22.52	22.67		
5	QPSK	25	0	22.69	22.54	22.55		
5	16QAM	1	0	22.92	22.71	22.91	23.5	1
5	16QAM	1	12	22.89	22.79	23.00		
5	16QAM	1	24	22.93	22.78	22.85		
5	16QAM	12	0	21.74	21.57	21.69	22.5	2
5	16QAM	12	7	21.76	21.62	21.82		
5	16QAM	12	13	21.81	21.59	21.77		
5	16QAM	25	0	21.82	21.60	21.66		
5	64QAM	1	0	21.89	21.75	21.86	22.5	2
5	64QAM	1	12	21.88	21.75	21.96		
5	64QAM	1	24	21.92	21.77	21.86		
5	64QAM	12	0	20.78	20.64	20.74	21.5	3
5	64QAM	12	7	20.82	20.69	20.87		
5	64QAM	12	13	20.87	20.68	20.81		
5	64QAM	25	0	20.82	20.59	20.66		

Channel				23025	23095	23165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	23.56	23.58	23.58	24.5	0
3	QPSK	1	8	23.58	23.58	23.58		
3	QPSK	1	14	23.54	23.58	23.58		
3	QPSK	8	0	22.61	22.61	22.67	23.5	1
3	QPSK	8	4	22.65	22.66	22.69		
3	QPSK	8	7	22.60	22.62	22.65		
3	QPSK	15	0	22.59	22.64	22.63		
3	16QAM	1	0	22.91	22.84	22.99	23.5	1
3	16QAM	1	8	22.96	22.87	22.95		
3	16QAM	1	14	22.91	22.88	22.87		
3	16QAM	8	0	21.78	21.69	21.83	22.5	2
3	16QAM	8	4	21.76	21.74	21.84		
3	16QAM	8	7	21.76	21.74	21.76		
3	16QAM	15	0	21.70	21.71	21.76		
3	64QAM	1	0	21.83	21.76	21.91	22.5	2
3	64QAM	1	8	21.86	21.78	21.86		
3	64QAM	1	14	21.66	21.87	21.82		
3	64QAM	8	0	20.77	20.68	20.82	21.5	3
3	64QAM	8	4	20.76	20.74	20.82		
3	64QAM	8	7	20.75	20.76	20.79		
3	64QAM	15	0	20.72	20.71	20.77		
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	23.42	23.43	23.50	24.5	0
1.4	QPSK	1	3	23.48	23.49	23.50		
1.4	QPSK	1	5	23.42	23.42	23.50		
1.4	QPSK	3	0	23.55	23.47	23.55		
1.4	QPSK	3	1	23.51	23.52	23.58		
1.4	QPSK	3	3	23.56	23.48	23.58		
1.4	QPSK	6	0	22.55	22.47	22.61	23.5	1
1.4	16QAM	1	0	22.89	22.69	22.86	23.5	1
1.4	16QAM	1	3	22.95	22.77	22.89		
1.4	16QAM	1	5	22.90	22.70	22.81		
1.4	16QAM	3	0	22.64	22.51	22.62		
1.4	16QAM	3	1	22.71	22.56	22.67		
1.4	16QAM	3	3	22.65	22.52	22.60		
1.4	16QAM	6	0	21.74	21.58	21.72	22.5	2
1.4	64QAM	1	0	21.81	21.59	21.81	22.5	2
1.4	64QAM	1	3	21.87	21.70	21.84		
1.4	64QAM	1	5	21.77	21.64	21.76		
1.4	64QAM	3	0	21.79	21.65	21.77		
1.4	64QAM	3	1	21.86	21.68	21.82		
1.4	64QAM	3	3	21.80	21.66	21.77		
1.4	64QAM	6	0	20.64	20.54	20.68	21.5	3

<LTE Band 13>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23230				
Frequency (MHz)				782				
10	QPSK	1	0	24.33			25	0
10	QPSK	1	25	24.29				
10	QPSK	1	49	24.26				
10	QPSK	25	0	23.46			24	1
10	QPSK	25	12	23.41				
10	QPSK	25	25	23.39				
10	QPSK	50	0	23.40			24	1
10	16QAM	1	0	23.28				
10	16QAM	1	25	23.47				
10	16QAM	1	49	23.54			23	2
10	16QAM	25	0	22.49				
10	16QAM	25	12	22.43				
10	16QAM	25	25	22.41			23	2
10	16QAM	50	0	22.47				
10	64QAM	1	0	22.24				
10	64QAM	1	25	22.42			22	3
10	64QAM	1	49	22.46				
10	64QAM	25	0	21.51				
10	64QAM	25	12	21.45			22	3
10	64QAM	25	25	21.43				
10	64QAM	50	0	21.48				
Channel				23205	23230	23255	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				779.5	782	784.5		
5	QPSK	1	0	24.24	24.18	24.27	25	0
5	QPSK	1	12	24.23	24.31	24.26		
5	QPSK	1	24	24.30	24.29	24.22		
5	QPSK	12	0	23.30	23.39	23.33	24	1
5	QPSK	12	7	23.43	23.40	23.35		
5	QPSK	12	13	23.40	23.34	23.30		
5	QPSK	25	0	23.43	23.39	23.27	24	1
5	16QAM	1	0	23.23	23.41	23.31		
5	16QAM	1	12	23.43	23.42	23.31		
5	16QAM	1	24	23.44	23.37	23.38	23	2
5	16QAM	12	0	22.26	22.41	22.22		
5	16QAM	12	7	22.45	22.42	22.26		
5	16QAM	12	13	22.43	22.33	22.34	23	2
5	16QAM	25	0	22.45	22.41	22.39		
5	64QAM	1	0	22.23	22.40	22.41		
5	64QAM	1	12	22.42	22.42	22.34	22	3
5	64QAM	1	24	22.46	22.34	22.45		
5	64QAM	12	0	21.37	21.49	21.43		
5	64QAM	12	7	21.53	21.49	21.40	22	3
5	64QAM	12	13	21.50	21.43	21.42		
5	64QAM	25	0	21.47	21.43	21.41		

<LTE Band 17>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23780	23790	23800	24.5	0
Frequency (MHz)				709	710	711		
10	QPSK	1	0	23.58	23.67	23.53		
10	QPSK	1	25	23.58	23.54	23.63	23.5	1
10	QPSK	1	49	23.66	23.61	23.61		
10	QPSK	25	0	22.65	22.72	22.56		
10	QPSK	25	12	22.64	22.60	22.58	23.5	1
10	QPSK	25	25	22.62	22.64	22.70		
10	QPSK	50	0	22.64	22.59	22.61		
10	16QAM	1	0	22.86	22.85	22.79	23.5	1
10	16QAM	1	25	22.96	23.04	23.03		
10	16QAM	1	49	23.04	22.98	22.91		
10	16QAM	25	0	21.72	21.70	21.69	22.5	2
10	16QAM	25	12	21.72	21.73	21.72		
10	16QAM	25	25	21.73	21.80	21.76		
10	16QAM	50	0	21.72	21.67	21.67	22.5	2
10	64QAM	1	0	21.78	21.75	21.75		
10	64QAM	1	25	21.83	21.94	21.96		
10	64QAM	1	49	21.91	21.87	21.86	21.5	3
10	64QAM	25	0	20.73	20.70	20.66		
10	64QAM	25	12	20.73	20.74	20.72		
10	64QAM	25	25	20.71	20.82	20.79	21.5	3
10	64QAM	50	0	20.70	20.73	20.70		
Channel				23755	23790	23825	24.5	0
Frequency (MHz)				706.5	710	713.5		
5	QPSK	1	0	23.58	23.51	23.59		
5	QPSK	1	12	23.60	23.64	23.62	23.5	1
5	QPSK	1	24	23.58	23.64	23.58		
5	QPSK	12	0	22.63	22.60	22.66		
5	QPSK	12	7	22.69	22.64	22.73	23.5	1
5	QPSK	12	13	22.62	22.74	22.69		
5	QPSK	25	0	22.63	22.58	22.63		
5	16QAM	1	0	22.89	22.83	23.02	23.5	1
5	16QAM	1	12	22.84	23.01	23.00		
5	16QAM	1	24	22.86	23.03	22.87		
5	16QAM	12	0	21.72	21.68	21.78	22.5	2
5	16QAM	12	7	21.72	21.73	21.83		
5	16QAM	12	13	21.68	21.83	21.74		
5	16QAM	25	0	21.73	21.71	21.75	22.5	2
5	64QAM	1	0	21.80	21.74	21.92		
5	64QAM	1	12	21.81	21.94	21.91		
5	64QAM	1	24	21.82	21.96	21.82	21.5	3
5	64QAM	12	0	20.75	20.70	20.83		
5	64QAM	12	7	20.80	20.76	20.86		
5	64QAM	12	13	20.75	20.84	20.80	21.5	3
5	64QAM	25	0	20.70	20.67	20.78		


<LTE Band 25>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				26140	26340	26590		
Frequency (MHz)				1860	1880	1905		
20	QPSK	1	0	24.25	24.25	24.28	24.5	0
20	QPSK	1	49	24.19	24.20	24.27		
20	QPSK	1	99	24.16	24.21	24.18		
20	QPSK	50	0	23.28	23.28	23.25	23.5	1
20	QPSK	50	24	23.34	23.29	23.35		
20	QPSK	50	50	23.30	23.23	23.31		
20	QPSK	100	0	23.30	23.23	23.31		
20	16QAM	1	0	23.43	23.35	23.46	23.5	1
20	16QAM	1	49	23.42	23.38	23.44		
20	16QAM	1	99	23.33	23.43	23.41		
20	16QAM	50	0	22.33	22.32	22.35	22.5	2
20	16QAM	50	24	22.43	22.35	22.42		
20	16QAM	50	50	22.34	22.32	22.40		
20	16QAM	100	0	22.37	22.28	22.28		
20	64QAM	1	0	22.49	22.36	22.48	22.5	2
20	64QAM	1	49	22.41	22.42	22.48		
20	64QAM	1	99	22.31	22.44	22.44		
20	64QAM	50	0	21.39	21.34	21.35	21.5	3
20	64QAM	50	24	21.48	21.36	21.42		
20	64QAM	50	50	21.36	21.32	21.38		
20	64QAM	100	0	21.41	21.31	21.33		
Channel				26115	26340	26615	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1907.5		
15	QPSK	1	0	24.19	24.17	24.20	24.5	0
15	QPSK	1	37	24.18	24.19	24.26		
15	QPSK	1	74	24.17	24.23	24.27		
15	QPSK	36	0	23.22	23.25	23.32	23.5	1
15	QPSK	36	20	23.29	23.27	23.31		
15	QPSK	36	39	23.29	23.21	23.30		
15	QPSK	75	0	23.31	23.22	23.30		
15	16QAM	1	0	23.49	23.32	23.50	23.5	1
15	16QAM	1	37	23.50	23.43	23.45		
15	16QAM	1	74	23.41	23.44	23.41		
15	16QAM	36	0	22.34	22.27	22.37	22.5	2
15	16QAM	36	20	22.34	22.33	22.41		
15	16QAM	36	39	22.37	22.28	22.37		
15	16QAM	75	0	22.38	22.28	22.36		
15	64QAM	1	0	22.43	22.30	22.46	22.5	2
15	64QAM	1	37	22.42	22.38	22.43		
15	64QAM	1	74	22.35	22.49	22.41		
15	64QAM	36	0	21.40	21.34	21.40	21.5	3
15	64QAM	36	20	21.40	21.38	21.45		
15	64QAM	36	39	21.42	21.33	21.42		
15	64QAM	75	0	21.43	21.31	21.42		

Channel				26090	26340	26640	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1910		
10	QPSK	1	0	24.18	24.21	24.19	24.5	0
10	QPSK	1	25	24.07	24.20	24.24		
10	QPSK	1	49	24.09	24.19	24.21		
10	QPSK	25	0	23.14	23.26	23.34	23.5	1
10	QPSK	25	12	23.14	23.25	23.34		
10	QPSK	25	25	23.09	23.21	23.42		
10	QPSK	50	0	23.09	23.23	23.34	23.5	1
10	16QAM	1	0	23.47	23.44	23.48		
10	16QAM	1	25	23.42	23.42	23.45		
10	16QAM	1	49	23.36	23.45	23.43	22.5	2
10	16QAM	25	0	22.23	22.30	22.39		
10	16QAM	25	12	22.23	22.32	22.41		
10	16QAM	25	25	22.16	22.28	22.43	22.5	2
10	16QAM	50	0	22.19	22.31	22.38		
10	64QAM	1	0	22.42	22.43	22.47		
10	64QAM	1	25	22.38	22.42	22.46	22.5	2
10	64QAM	1	49	22.33	22.44	22.44		
10	64QAM	25	0	21.25	21.31	21.41	21.5	3
10	64QAM	25	12	21.26	21.35	21.44		
10	64QAM	25	25	21.20	21.32	21.45		
10	64QAM	50	0	21.23	21.33	21.39	21.5	3
10	64QAM	50	0	21.23	21.33	21.39		
Channel				26065	26340	26665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1912.5		
5	QPSK	1	0	24.08	24.18	24.24	24.5	0
5	QPSK	1	12	24.10	24.20	24.28		
5	QPSK	1	24	24.04	24.23	24.25		
5	QPSK	12	0	23.12	23.21	23.39	23.5	1
5	QPSK	12	7	23.14	23.24	23.42		
5	QPSK	12	13	23.08	23.20	23.36		
5	QPSK	25	0	23.11	23.22	23.40	23.5	1
5	16QAM	1	0	23.39	23.36	23.50		
5	16QAM	1	12	23.41	23.40	23.50		
5	16QAM	1	24	23.33	23.48	23.40	22.5	2
5	16QAM	12	0	22.19	22.27	22.42		
5	16QAM	12	7	22.22	22.29	22.41		
5	16QAM	12	13	22.19	22.24	22.38	22.5	2
5	16QAM	25	0	22.18	22.25	22.42		
5	64QAM	1	0	22.32	22.35	22.50		
5	64QAM	1	12	22.32	22.37	22.50	22.5	2
5	64QAM	1	24	22.26	22.43	22.42		
5	64QAM	12	0	21.27	21.32	21.50		
5	64QAM	12	7	21.27	21.36	21.50	21.5	3
5	64QAM	12	13	21.26	21.34	21.45		
5	64QAM	25	0	21.19	21.28	21.48		

Channel				26055	26340	26675	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1913.5		
3	QPSK	1	0	24.07	24.17	24.27	24.5	0
3	QPSK	1	8	24.09	24.18	24.26		
3	QPSK	1	14	24.04	24.28	24.24		
3	QPSK	8	0	23.11	23.23	23.38	23.5	1
3	QPSK	8	4	23.16	23.25	23.41		
3	QPSK	8	7	23.10	23.21	23.37		
3	QPSK	15	0	23.08	23.21	23.42	23.5	1
3	16QAM	1	0	23.20	23.37	23.50		
3	16QAM	1	8	23.42	23.43	23.47		
3	16QAM	1	14	23.36	23.46	23.38	22.5	2
3	16QAM	8	0	22.03	22.29	22.41		
3	16QAM	8	4	22.28	22.31	22.46		
3	16QAM	8	7	22.22	22.28	22.42	22.5	2
3	16QAM	15	0	22.20	22.29	22.45		
3	64QAM	1	0	22.29	22.32	22.46	22.5	2
3	64QAM	1	8	22.30	22.38	22.47		
3	64QAM	1	14	22.29	22.43	22.42		
3	64QAM	8	0	21.24	21.31	21.46	21.5	3
3	64QAM	8	4	21.28	21.37	21.50		
3	64QAM	8	7	21.25	21.33	21.44		
3	64QAM	15	0	21.23	21.30	21.49		
Channel				26047	26340	26683	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1914.3		
1.4	QPSK	1	0	24.04	24.16	24.20	24.5	0
1.4	QPSK	1	3	24.07	24.20	24.27		
1.4	QPSK	1	5	24.04	24.13	24.22		
1.4	QPSK	3	0	24.07	24.19	24.22		
1.4	QPSK	3	1	24.15	24.25	24.23		
1.4	QPSK	3	3	24.09	24.18	24.27		
1.4	QPSK	6	0	23.07	23.19	23.38	23.5	1
1.4	16QAM	1	0	23.30	23.32	23.39	23.5	1
1.4	16QAM	1	3	23.42	23.42	23.44		
1.4	16QAM	1	5	23.34	23.32	23.37		
1.4	16QAM	3	0	23.11	23.16	23.25		
1.4	16QAM	3	1	23.17	23.23	23.29		
1.4	16QAM	3	3	23.11	23.15	23.24		
1.4	16QAM	6	0	22.23	22.32	22.44	22.5	2
1.4	64QAM	1	0	22.27	22.30	22.41	22.5	2
1.4	64QAM	1	3	22.32	22.36	22.45		
1.4	64QAM	1	5	22.26	22.35	22.37		
1.4	64QAM	3	0	22.26	22.33	22.43		
1.4	64QAM	3	1	22.33	22.37	22.47		
1.4	64QAM	3	3	22.25	22.32	22.42		
1.4	64QAM	6	0	21.14	21.23	21.40	21.5	3



<LTE Band 66>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				132072	132322	132572		
Frequency (MHz)				1720	1745	1770		
20	QPSK	1	0	24.38	24.50	24.48	24.5	0
20	QPSK	1	49	24.35	24.44	24.47		
20	QPSK	1	99	24.22	24.41	24.33		
20	QPSK	50	0	23.36	23.45	23.44	23.5	1
20	QPSK	50	24	23.31	23.42	23.42		
20	QPSK	50	50	23.26	23.48	23.41		
20	QPSK	100	0	23.33	23.50	23.46		
20	16QAM	1	0	23.22	23.46	23.43	23.5	1
20	16QAM	1	49	23.37	23.42	23.31		
20	16QAM	1	99	23.28	23.43	23.29		
20	16QAM	50	0	22.21	22.41	22.36	22.5	2
20	16QAM	50	24	22.19	22.39	22.28		
20	16QAM	50	50	22.17	22.35	22.25		
20	16QAM	100	0	22.16	22.35	22.29		
20	64QAM	1	0	22.26	22.48	22.43	22.5	2
20	64QAM	1	49	22.41	22.41	22.40		
20	64QAM	1	99	22.32	22.45	22.32		
20	64QAM	50	0	21.24	21.47	21.39	21.5	3
20	64QAM	50	24	21.19	21.39	21.32		
20	64QAM	50	50	21.21	21.40	21.29		
20	64QAM	100	0	21.19	21.41	21.33		
Channel				132047	132322	132597		
Frequency (MHz)				1717.5	1745	1772.5		
15	QPSK	1	0	24.26	24.43	24.46	24.5	0
15	QPSK	1	37	24.34	24.49	24.49		
15	QPSK	1	74	24.24	24.41	24.35		
15	QPSK	36	0	23.26	23.48	23.42	23.5	1
15	QPSK	36	20	23.35	23.49	23.41		
15	QPSK	36	39	23.22	23.46	23.36		
15	QPSK	75	0	23.26	23.49	23.43		
15	16QAM	1	0	23.24	23.48	23.37	23.5	1
15	16QAM	1	37	23.33	23.45	23.32		
15	16QAM	1	74	23.31	23.41	23.30		
15	16QAM	36	0	22.10	22.30	22.20	22.5	2
15	16QAM	36	20	22.23	22.39	22.30		
15	16QAM	36	39	22.15	22.26	22.20		
15	16QAM	75	0	22.13	22.32	22.21		
15	64QAM	1	0	22.24	22.50	22.40	22.5	2
15	64QAM	1	37	22.33	22.47	22.36		
15	64QAM	1	74	22.29	22.40	22.33		
15	64QAM	36	0	21.15	21.38	21.27	21.5	3
15	64QAM	36	20	21.27	21.43	21.33		
15	64QAM	36	39	21.15	21.33	21.23		
15	64QAM	75	0	21.13	21.35	21.26		

Channel				132022	132322	132622	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1745	1775		
10	QPSK	1	0	24.27	24.43	24.41	24.5	0
10	QPSK	1	25	24.27	24.42	24.42		
10	QPSK	1	49	24.19	24.42	24.30		
10	QPSK	25	0	23.34	23.50	23.50	23.5	1
10	QPSK	25	12	23.35	23.47	23.48		
10	QPSK	25	25	23.28	23.42	23.46		
10	QPSK	50	0	23.35	23.49	23.49	23.5	1
10	16QAM	1	0	23.21	23.42	23.29		
10	16QAM	1	25	23.26	23.41	23.31		
10	16QAM	1	49	23.25	23.33	23.29	22.5	2
10	16QAM	25	0	22.19	22.38	22.31		
10	16QAM	25	12	22.17	22.36	22.28		
10	16QAM	25	25	22.13	22.34	22.27	22.5	2
10	16QAM	50	0	22.19	22.40	22.29		
10	64QAM	1	0	22.23	22.42	22.29	22.5	2
10	64QAM	1	25	22.27	22.44	22.33		
10	64QAM	1	49	22.22	22.34	22.32		
10	64QAM	25	0	21.20	21.42	21.30	21.5	3
10	64QAM	25	12	21.17	21.37	21.31		
10	64QAM	25	25	21.18	21.34	21.27		
10	64QAM	50	0	21.19	21.41	21.28		
Channel				131997	132322	132647	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1745	1777.5		
5	QPSK	1	0	24.10	24.37	24.27	24.5	0
5	QPSK	1	12	24.29	24.43	24.42		
5	QPSK	1	24	24.09	24.31	24.22		
5	QPSK	12	0	23.29	23.47	23.42	23.5	1
5	QPSK	12	7	23.37	23.48	23.41		
5	QPSK	12	13	23.25	23.46	23.40		
5	QPSK	25	0	23.30	23.50	23.42	23.5	1
5	16QAM	1	0	23.05	23.28	23.17		
5	16QAM	1	12	23.22	23.38	23.38		
5	16QAM	1	24	23.06	23.24	23.22	22.5	2
5	16QAM	12	0	22.11	22.27	22.20		
5	16QAM	12	7	22.19	22.37	22.30		
5	16QAM	12	13	22.07	22.26	22.22	22.5	2
5	16QAM	25	0	22.10	22.31	22.25		
5	64QAM	1	0	22.08	22.27	22.17		
5	64QAM	1	12	22.21	22.39	22.38	22.5	2
5	64QAM	1	24	22.03	22.18	22.19		
5	64QAM	12	0	21.14	21.36	21.29		
5	64QAM	12	7	21.24	21.46	21.39	21.5	3
5	64QAM	12	13	21.18	21.36	21.30		
5	64QAM	25	0	21.14	21.35	21.26		

Channel				131987	132322	132657	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1745	1778.5		
3	QPSK	1	0	24.18	24.39	24.32	24.5	0
3	QPSK	1	8	24.27	24.43	24.44		
3	QPSK	1	14	23.96	24.36	24.28		
3	QPSK	8	0	23.34	23.44	23.44	23.5	1
3	QPSK	8	4	23.37	23.50	23.41		
3	QPSK	8	7	23.31	23.43	23.45		
3	QPSK	15	0	23.37	23.46	23.47		
3	16QAM	1	0	23.11	23.30	23.26	23.5	1
3	16QAM	1	8	23.23	23.40	23.43		
3	16QAM	1	14	23.07	23.29	23.26		
3	16QAM	8	0	22.14	22.33	22.29	22.5	2
3	16QAM	8	4	22.22	22.43	22.38		
3	16QAM	8	7	22.16	22.34	22.33		
3	16QAM	15	0	22.17	22.42	22.33		
3	64QAM	1	0	22.11	22.27	22.23	22.5	2
3	64QAM	1	8	22.18	22.39	22.35		
3	64QAM	1	14	22.07	22.29	22.23		
3	64QAM	8	0	21.19	21.36	21.30	21.5	3
3	64QAM	8	4	21.23	21.43	21.38		
3	64QAM	8	7	21.18	21.40	21.32		
3	64QAM	15	0	21.21	21.45	21.35		
Channel				131979	132322	132665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1745	1779.3		
1.4	QPSK	1	0	24.19	24.47	24.36	24.5	0
1.4	QPSK	1	3	24.30	24.45	24.43		
1.4	QPSK	1	5	24.21	24.45	24.33		
1.4	QPSK	3	0	24.23	24.49	24.39		
1.4	QPSK	3	1	24.36	24.47	24.47		
1.4	QPSK	3	3	24.25	24.47	24.40		
1.4	QPSK	6	0	23.35	23.42	23.47	23.5	1
1.4	16QAM	1	0	23.14	23.32	23.32	23.5	1
1.4	16QAM	1	3	23.21	23.41	23.38		
1.4	16QAM	1	5	23.12	23.33	23.28		
1.4	16QAM	3	0	22.99	23.15	23.13		
1.4	16QAM	3	1	23.04	23.27	23.22		
1.4	16QAM	3	3	23.00	23.16	23.16		
1.4	16QAM	6	0	22.21	22.42	22.38	22.5	2
1.4	64QAM	1	0	22.14	22.33	22.30	22.5	2
1.4	64QAM	1	3	22.21	22.41	22.39		
1.4	64QAM	1	5	22.14	22.32	22.30		
1.4	64QAM	3	0	22.19	22.35	22.31		
1.4	64QAM	3	1	22.22	22.40	22.37		
1.4	64QAM	3	3	22.17	22.34	22.31		
1.4	64QAM	6	0	21.17	21.36	21.30	21.5	3

<Hotspot Power Mode>
<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	19.37	19.40	19.20	20	0
20	QPSK	1	49	19.33	19.37	19.28		
20	QPSK	1	99	19.33	19.33	19.22		
20	QPSK	50	0	19.38	19.40	19.19	20	0
20	QPSK	50	24	19.38	19.41	19.32		
20	QPSK	50	50	19.42	19.32	19.25		
20	QPSK	100	0	19.46	19.36	19.20		
20	16QAM	1	0	19.90	19.83	19.73	20	0
20	16QAM	1	49	19.81	19.86	19.74		
20	16QAM	1	99	19.76	19.81	19.72		
20	16QAM	50	0	19.58	19.56	19.39	20	0
20	16QAM	50	24	19.54	19.60	19.47		
20	16QAM	50	50	19.57	19.50	19.42		
20	16QAM	100	0	19.64	19.53	19.35		
20	64QAM	1	0	19.77	19.78	19.65	20	0
20	64QAM	1	49	19.73	19.81	19.69		
20	64QAM	1	99	19.66	19.77	19.64		
20	64QAM	50	0	19.59	19.56	19.42	20	0
20	64QAM	50	24	19.56	19.62	19.50		
20	64QAM	50	50	19.59	19.52	19.44		
20	64QAM	100	0	19.66	19.56	19.39		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	19.13	19.11	19.05	20	0
15	QPSK	1	37	19.17	19.11	19.18		
15	QPSK	1	74	19.04	19.09	18.98		
15	QPSK	36	0	19.10	19.25	18.99	20	0
15	QPSK	36	20	19.15	19.27	19.18		
15	QPSK	36	39	19.31	19.18	19.11		
15	QPSK	75	0	19.22	19.20	18.99		
15	16QAM	1	0	19.79	19.56	19.60	20	0
15	16QAM	1	37	19.56	19.63	19.57		
15	16QAM	1	74	19.60	19.54	19.56		
15	16QAM	36	0	19.40	19.27	19.16	20	0
15	16QAM	36	20	19.28	19.35	19.28		
15	16QAM	36	39	19.47	19.22	19.27		
15	16QAM	75	0	19.40	19.42	19.09		
15	64QAM	1	0	19.60	19.57	19.40	20	0
15	64QAM	1	37	19.56	19.57	19.39		
15	64QAM	1	74	19.36	19.52	19.53		
15	64QAM	36	0	19.35	19.36	19.14	20	0
15	64QAM	36	20	19.30	19.45	19.40		
15	64QAM	36	39	19.29	19.33	19.25		
15	64QAM	75	0	19.52	19.37	19.21		

Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	18.98	19.11	18.96	20	0
10	QPSK	1	25	18.98	18.98	18.84		
10	QPSK	1	49	19.06	18.91	18.89		
10	QPSK	25	0	18.98	19.09	18.77	20	0
10	QPSK	25	12	18.90	19.00	18.83		
10	QPSK	25	25	19.03	18.86	18.81		
10	QPSK	50	0	19.01	18.96	18.66	20	0
10	16QAM	1	0	19.37	19.52	19.39		
10	16QAM	1	25	19.52	19.51	19.34		
10	16QAM	1	49	19.42	19.35	19.27	20	0
10	16QAM	25	0	19.34	19.23	19.09		
10	16QAM	25	12	19.22	19.19	19.03		
10	16QAM	25	25	19.23	19.11	19.02	20	0
10	16QAM	50	0	19.22	19.28	18.99		
10	64QAM	1	0	19.29	19.20	19.25		
10	64QAM	1	25	19.31	19.48	19.36	20	0
10	64QAM	1	49	19.19	19.41	19.28		
10	64QAM	25	0	19.22	19.16	19.07		
10	64QAM	25	12	19.22	19.13	18.95	20	0
10	64QAM	25	25	19.33	19.06	19.00		
10	64QAM	50	0	19.19	19.12	19.09		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	18.72	18.90	18.63	20	0
5	QPSK	1	12	18.83	18.70	18.68		
5	QPSK	1	24	18.86	18.82	18.54		
5	QPSK	12	0	18.86	18.78	18.65	20	0
5	QPSK	12	7	18.72	18.90	18.86		
5	QPSK	12	13	18.96	18.65	18.54		
5	QPSK	25	0	18.72	18.77	18.47	20	0
5	16QAM	1	0	19.23	19.22	19.17		
5	16QAM	1	12	19.45	19.25	19.06		
5	16QAM	1	24	18.99	19.19	19.06	20	0
5	16QAM	12	0	18.96	19.10	18.91		
5	16QAM	12	7	18.92	19.03	18.76		
5	16QAM	12	13	19.10	18.99	18.89	20	0
5	16QAM	25	0	18.99	18.88	18.77		
5	64QAM	1	0	19.14	19.12	18.95		
5	64QAM	1	12	19.13	19.34	19.09	20	0
5	64QAM	1	24	19.12	19.25	19.05		
5	64QAM	12	0	19.11	18.92	19.00		
5	64QAM	12	7	18.87	19.20	18.77	20	0
5	64QAM	12	13	19.09	18.94	18.63		
5	64QAM	25	0	19.05	18.91	18.77		



FCC SAR TEST REPORT

Report No. : FA882923-01

Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	18.53	18.67	18.51	20	0
3	QPSK	1	8	18.48	18.63	18.41		
3	QPSK	1	14	18.62	18.58	18.34		
3	QPSK	8	0	18.50	18.53	18.49	20	0
3	QPSK	8	4	18.77	18.68	18.63		
3	QPSK	8	7	18.65	18.47	18.20		
3	QPSK	15	0	18.73	18.56	18.19		
3	16QAM	1	0	19.15	19.05	18.88	20	0
3	16QAM	1	8	19.24	18.82	18.93		
3	16QAM	1	14	18.90	18.85	18.85		
3	16QAM	8	0	18.79	18.95	18.58	20	0
3	16QAM	8	4	18.87	18.76	18.50		
3	16QAM	8	7	18.92	18.64	18.78		
3	16QAM	15	0	18.88	18.72	18.53		
3	64QAM	1	0	19.00	18.82	18.76	20	0
3	64QAM	1	8	18.91	19.10	19.01		
3	64QAM	1	14	19.06	19.02	18.88		
3	64QAM	8	0	18.82	18.93	18.83	20	0
3	64QAM	8	4	18.85	18.89	18.74		
3	64QAM	8	7	18.92	18.78	18.63		
3	64QAM	15	0	18.89	18.68	18.36		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	18.34	18.36	18.32	20	0
1.4	QPSK	1	3	18.33	18.41	18.26		
1.4	QPSK	1	5	18.36	18.52	18.13		
1.4	QPSK	3	0	18.38	18.37	18.19		
1.4	QPSK	3	1	18.36	18.56	18.41		
1.4	QPSK	3	3	18.38	18.30	18.21		
1.4	QPSK	6	0	18.42	18.47	18.11	20	0
1.4	16QAM	1	0	18.91	19.03	18.68	20	0
1.4	16QAM	1	3	19.03	18.71	18.83		
1.4	16QAM	1	5	18.71	18.62	18.56		
1.4	16QAM	3	0	18.55	18.58	18.35		
1.4	16QAM	3	1	18.50	18.55	18.54		
1.4	16QAM	3	3	18.53	18.41	18.37		
1.4	16QAM	6	0	18.62	18.52	18.10	20	0
1.4	64QAM	1	0	18.77	18.72	18.76	20	0
1.4	64QAM	1	3	18.62	18.97	18.57		
1.4	64QAM	1	5	18.61	18.72	18.52		
1.4	64QAM	3	0	18.75	18.81	18.64		
1.4	64QAM	3	1	18.58	18.70	18.43		
1.4	64QAM	3	3	18.48	18.31	18.28		
1.4	64QAM	6	0	18.94	18.29	18.33	20	0



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	19.26	19.28	19.27	20	0
20	QPSK	1	49	19.22	19.23	19.22		
20	QPSK	1	99	19.16	19.11	19.10		
20	QPSK	50	0	19.31	19.27	19.28	20	0
20	QPSK	50	24	19.31	19.25	19.27		
20	QPSK	50	50	19.26	19.23	19.17		
20	QPSK	100	0	19.27	19.25	19.22	20	0
20	16QAM	1	0	19.67	19.71	19.63		
20	16QAM	1	49	19.68	19.63	19.56		
20	16QAM	1	99	19.59	19.49	19.53	20	0
20	16QAM	50	0	19.44	19.42	19.38		
20	16QAM	50	24	19.43	19.41	19.37		
20	16QAM	50	50	19.40	19.34	19.30	20	0
20	16QAM	100	0	19.41	19.38	19.33		
20	64QAM	1	0	19.60	19.61	19.56		
20	64QAM	1	49	19.60	19.59	19.48	20	0
20	64QAM	1	99	19.54	19.43	19.42		
20	64QAM	50	0	19.45	19.43	19.40		
20	64QAM	50	24	19.46	19.43	19.36	20	0
20	64QAM	50	50	19.40	19.37	19.34		
20	64QAM	100	0	19.46	19.46	19.38		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	19.08	19.07	19.14	20	0
15	QPSK	1	37	18.94	19.13	18.94		
15	QPSK	1	74	19.05	18.86	18.99		
15	QPSK	36	0	19.13	19.09	19.07	20	0
15	QPSK	36	20	19.08	18.98	19.10		
15	QPSK	36	39	19.10	19.08	18.93		
15	QPSK	75	0	19.14	18.98	19.09	20	0
15	16QAM	1	0	19.50	19.41	19.37		
15	16QAM	1	37	19.43	19.46	19.43		
15	16QAM	1	74	19.31	19.35	19.35	20	0
15	16QAM	36	0	19.27	19.27	19.26		
15	16QAM	36	20	19.30	19.31	19.08		
15	16QAM	36	39	19.20	19.20	19.13	20	0
15	16QAM	75	0	19.15	19.28	19.17		
15	64QAM	1	0	19.39	19.45	19.27		
15	64QAM	1	37	19.43	19.47	19.36	20	0
15	64QAM	1	74	19.37	19.23	19.32		
15	64QAM	36	0	19.28	19.13	19.26		
15	64QAM	36	20	19.26	19.27	19.07	20	0
15	64QAM	36	39	19.30	19.22	19.16		
15	64QAM	75	0	19.36	19.17	19.23		

Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	18.85	19.02	18.98	20	0
10	QPSK	1	25	18.77	18.84	18.67		
10	QPSK	1	49	18.76	18.74	18.68		
10	QPSK	25	0	18.88	18.98	18.95	20	0
10	QPSK	25	12	18.95	18.73	18.74		
10	QPSK	25	25	18.83	18.84	18.77		
10	QPSK	50	0	18.84	18.85	18.85	20	0
10	16QAM	1	0	19.33	19.18	19.25		
10	16QAM	1	25	19.36	19.14	19.19		
10	16QAM	1	49	19.22	19.20	19.23	20	0
10	16QAM	25	0	19.10	18.99	19.04		
10	16QAM	25	12	19.11	19.07	18.80		
10	16QAM	25	25	18.99	18.97	18.91	20	0
10	16QAM	50	0	19.03	19.04	18.84		
10	64QAM	1	0	19.28	19.12	19.11		
10	64QAM	1	25	19.39	19.19	19.07	20	0
10	64QAM	1	49	19.08	18.99	19.04		
10	64QAM	25	0	19.00	19.06	18.94		
10	64QAM	25	12	19.12	19.04	18.91	20	0
10	64QAM	25	25	19.02	18.96	18.96		
10	64QAM	50	0	19.13	19.13	19.13		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	18.50	18.70	18.77	20	0
5	QPSK	1	12	18.48	18.60	18.66		
5	QPSK	1	24	18.47	18.50	18.45		
5	QPSK	12	0	18.67	18.77	18.70	20	0
5	QPSK	12	7	18.85	18.63	18.43		
5	QPSK	12	13	18.56	18.61	18.53		
5	QPSK	25	0	18.60	18.59	18.70	20	0
5	16QAM	1	0	19.12	19.13	19.11		
5	16QAM	1	12	19.08	18.91	19.00		
5	16QAM	1	24	18.87	18.90	19.08	20	0
5	16QAM	12	0	18.78	18.70	18.87		
5	16QAM	12	7	18.88	18.86	18.62		
5	16QAM	12	13	18.70	18.75	18.55	20	0
5	16QAM	25	0	18.86	18.99	18.62		
5	64QAM	1	0	18.98	18.91	18.98		
5	64QAM	1	12	19.26	19.05	18.83	20	0
5	64QAM	1	24	18.86	18.82	18.87		
5	64QAM	12	0	18.74	18.82	18.73		
5	64QAM	12	7	18.92	18.72	18.67	20	0
5	64QAM	12	13	18.77	18.93	18.71		
5	64QAM	25	0	18.95	18.81	18.79		

Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	18.29	18.40	18.49	20	0
3	QPSK	1	8	18.38	18.47	18.35		
3	QPSK	1	14	18.20	18.32	18.21		
3	QPSK	8	0	18.64	18.74	18.36	20	0
3	QPSK	8	4	18.48	18.46	18.30		
3	QPSK	8	7	18.45	18.57	18.55		
3	QPSK	15	0	18.38	18.50	18.63		
3	16QAM	1	0	18.74	19.12	18.81	20	0
3	16QAM	1	8	18.76	18.78	18.89		
3	16QAM	1	14	18.65	18.61	18.79		
3	16QAM	8	0	18.67	18.47	18.68	20	0
3	16QAM	8	4	18.67	18.58	18.43		
3	16QAM	8	7	18.38	18.60	18.57		
3	16QAM	15	0	18.46	18.78	18.45		
3	64QAM	1	0	18.79	18.66	18.62	20	0
3	64QAM	1	8	19.05	18.89	18.69		
3	64QAM	1	14	18.69	18.76	18.77		
3	64QAM	8	0	18.53	18.75	18.54	20	0
3	64QAM	8	4	18.71	18.66	18.52		
3	64QAM	8	7	18.68	18.50	18.54		
3	64QAM	15	0	18.62	18.66	18.49		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	18.24	18.40	18.28	20	0
1.4	QPSK	1	3	18.19	18.14	18.19		
1.4	QPSK	1	5	18.02	18.19	18.12		
1.4	QPSK	3	0	18.54	18.41	18.09		
1.4	QPSK	3	1	18.30	18.05	18.12		
1.4	QPSK	3	3	18.24	18.46	18.24		
1.4	QPSK	6	0	18.29	18.21	18.35	20	0
1.4	16QAM	1	0	18.55	18.91	18.57	20	0
1.4	16QAM	1	3	18.60	18.50	18.76		
1.4	16QAM	1	5	18.57	18.44	18.52		
1.4	16QAM	3	0	18.46	18.19	18.58		
1.4	16QAM	3	1	18.47	18.32	18.25		
1.4	16QAM	3	3	18.31	18.25	18.21		
1.4	16QAM	6	0	18.22	18.54	18.12	20	0
1.4	64QAM	1	0	18.60	18.55	18.61	20	0
1.4	64QAM	1	3	18.76	18.83	18.49		
1.4	64QAM	1	5	18.57	18.44	18.51		
1.4	64QAM	3	0	18.31	18.31	18.33		
1.4	64QAM	3	1	18.43	18.56	18.50		
1.4	64QAM	3	3	18.46	18.27	18.19		
1.4	64QAM	6	0	18.40	18.47	18.32	20	0



<LTE Band 25>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				26140	26340	26590		
Frequency (MHz)				1860	1880	1905		
20	QPSK	1	0	19.45	19.51	19.50	20	0
20	QPSK	1	49	19.38	19.38	19.47		
20	QPSK	1	99	19.37	19.44	19.43		
20	QPSK	50	0	19.46	19.61	19.60	20	0
20	QPSK	50	24	19.45	19.42	19.58		
20	QPSK	50	50	19.43	19.39	19.50		
20	QPSK	100	0	19.40	19.45	19.43		
20	16QAM	1	0	19.85	19.99	19.81	20	0
20	16QAM	1	49	19.74	19.76	19.87		
20	16QAM	1	99	19.71	19.85	19.95		
20	16QAM	50	0	19.52	19.54	19.54	20	0
20	16QAM	50	24	19.61	19.58	19.64		
20	16QAM	50	50	19.56	19.54	19.62		
20	16QAM	100	0	19.60	19.51	19.55		
20	64QAM	1	0	19.73	19.66	19.77	20	0
20	64QAM	1	49	19.69	19.66	19.73		
20	64QAM	1	99	19.60	19.77	19.77		
20	64QAM	50	0	19.57	19.56	19.56	20	0
20	64QAM	50	24	19.66	19.60	19.67		
20	64QAM	50	50	19.58	19.53	19.65		
20	64QAM	100	0	19.63	19.55	19.58		
Channel				26115	26340	26615	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1907.5		
15	QPSK	1	0	19.34	19.15	19.12	20	0
15	QPSK	1	37	19.22	19.16	19.25		
15	QPSK	1	74	19.07	19.30	19.42		
15	QPSK	36	0	19.27	19.14	19.25	20	0
15	QPSK	36	20	19.37	19.22	19.41		
15	QPSK	36	39	19.24	19.29	19.34		
15	QPSK	75	0	19.20	19.28	19.25		
15	16QAM	1	0	19.68	19.47	19.52	20	0
15	16QAM	1	37	19.51	19.63	19.71		
15	16QAM	1	74	19.50	19.58	19.76		
15	16QAM	36	0	19.41	19.29	19.42	20	0
15	16QAM	36	20	19.44	19.32	19.39		
15	16QAM	36	39	19.42	19.37	19.48		
15	16QAM	75	0	19.30	19.25	19.28		
15	64QAM	1	0	19.51	19.55	19.47	20	0
15	64QAM	1	37	19.55	19.47	19.50		
15	64QAM	1	74	19.50	19.47	19.57		
15	64QAM	36	0	19.44	19.36	19.42	20	0
15	64QAM	36	20	19.50	19.45	19.40		
15	64QAM	36	39	19.36	19.38	19.53		
15	64QAM	75	0	19.47	19.25	19.43		

Channel				26090	26340	26640	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1910		
10	QPSK	1	0	19.15	19.10	18.92	20	0
10	QPSK	1	25	19.14	18.88	19.02		
10	QPSK	1	49	19.09	19.07	19.03		
10	QPSK	25	0	19.15	19.11	19.12	20	0
10	QPSK	25	12	19.13	19.01	19.28		
10	QPSK	25	25	18.89	19.01	19.18		
10	QPSK	50	0	18.92	19.06	19.06	20	0
10	16QAM	1	0	19.55	19.38	19.49		
10	16QAM	1	25	19.24	19.43	19.33		
10	16QAM	1	49	19.39	19.51	19.66	20	0
10	16QAM	25	0	19.09	19.22	19.22		
10	16QAM	25	12	19.07	19.32	19.18		
10	16QAM	25	25	19.13	19.22	19.14	20	0
10	16QAM	50	0	19.22	19.27	19.01		
10	64QAM	1	0	19.29	19.24	19.44		
10	64QAM	1	25	19.33	19.33	19.32	20	0
10	64QAM	1	49	19.07	19.48	19.32		
10	64QAM	25	0	19.23	19.20	19.16		
10	64QAM	25	12	19.38	19.14	19.24	20	0
10	64QAM	25	25	19.34	19.19	19.30		
10	64QAM	50	0	19.21	19.26	19.20		
Channel				26065	26340	26665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1912.5		
5	QPSK	1	0	18.91	18.88	18.85	20	0
5	QPSK	1	12	19.01	18.68	18.89		
5	QPSK	1	24	18.88	19.06	18.75		
5	QPSK	12	0	18.80	18.95	18.75	20	0
5	QPSK	12	7	19.04	18.98	18.99		
5	QPSK	12	13	18.74	18.70	18.90		
5	QPSK	25	0	18.72	18.71	18.79	20	0
5	16QAM	1	0	19.26	19.31	19.30		
5	16QAM	1	12	19.13	19.28	19.11		
5	16QAM	1	24	19.27	19.25	19.41	20	0
5	16QAM	12	0	18.96	18.93	19.01		
5	16QAM	12	7	18.95	19.18	18.99		
5	16QAM	12	13	18.92	18.86	19.02	20	0
5	16QAM	25	0	19.13	18.88	18.76		
5	64QAM	1	0	19.27	19.02	19.28		
5	64QAM	1	12	19.00	19.20	19.06	20	0
5	64QAM	1	24	18.87	19.23	19.08		
5	64QAM	12	0	19.05	18.79	18.87		
5	64QAM	12	7	19.13	18.98	19.10	20	0
5	64QAM	12	13	19.21	18.85	19.03		
5	64QAM	25	0	19.20	18.98	18.85		



FCC SAR TEST REPORT

Report No. : FA882923-01

Channel				26055	26340	26675	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1913.5		
3	QPSK	1	0	18.76	18.43	18.60	20	0
3	QPSK	1	8	18.69	18.49	18.67		
3	QPSK	1	14	18.71	18.62	18.77		
3	QPSK	8	0	18.65	18.62	18.58	20	0
3	QPSK	8	4	18.83	18.82	18.78		
3	QPSK	8	7	18.66	18.54	18.81		
3	QPSK	15	0	18.65	18.45	18.63		
3	16QAM	1	0	18.99	19.02	19.00	20	0
3	16QAM	1	8	18.92	19.12	19.03		
3	16QAM	1	14	19.04	18.85	19.11		
3	16QAM	8	0	18.74	18.60	18.83	20	0
3	16QAM	8	4	18.87	18.94	18.66		
3	16QAM	8	7	18.77	18.75	18.69		
3	16QAM	15	0	18.75	18.61	18.60		
3	64QAM	1	0	19.07	18.99	18.94	20	0
3	64QAM	1	8	18.87	19.06	18.95		
3	64QAM	1	14	18.63	19.05	18.75		
3	64QAM	8	0	18.76	18.57	18.76	20	0
3	64QAM	8	4	18.78	18.64	18.98		
3	64QAM	8	7	18.79	18.62	18.76		
3	64QAM	15	0	19.05	18.72	18.63		
Channel				26047	26340	26683	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1914.3		
1.4	QPSK	1	0	18.58	18.36	18.40	20	0
1.4	QPSK	1	3	18.36	18.29	18.54		
1.4	QPSK	1	5	18.51	18.53	18.46		
1.4	QPSK	3	0	18.39	18.51	18.32		
1.4	QPSK	3	1	18.76	18.53	18.33		
1.4	QPSK	3	3	18.27	18.35	18.71		
1.4	QPSK	6	0	18.56	18.30	18.50	20	0
1.4	16QAM	1	0	18.83	18.79	18.91	20	0
1.4	16QAM	1	3	18.72	18.87	18.84		
1.4	16QAM	1	5	19.01	18.90	18.94		
1.4	16QAM	3	0	18.66	18.54	18.58		
1.4	16QAM	3	1	18.54	18.68	18.58		
1.4	16QAM	3	3	18.49	18.50	18.50		
1.4	16QAM	6	0	18.76	18.43	18.35	20	0
1.4	64QAM	1	0	18.90	18.53	18.67	20	0
1.4	64QAM	1	3	18.63	18.86	18.78		
1.4	64QAM	1	5	18.32	18.92	18.57		
1.4	64QAM	3	0	18.56	18.36	18.62		
1.4	64QAM	3	1	18.68	18.46	18.71		
1.4	64QAM	3	3	18.82	18.35	18.60		
1.4	64QAM	6	0	18.73	18.71	18.40	20	0



<LTE Band 66>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				132072	132322	132572	20	0
Frequency (MHz)				1720	1745	1770		
20	QPSK	1	0	19.35	19.66	19.56		
20	QPSK	1	49	19.40	19.63	19.55	20	0
20	QPSK	1	99	19.24	19.47	19.40		
20	QPSK	50	0	19.31	19.58	19.46		
20	QPSK	50	24	19.28	19.54	19.42	20	0
20	QPSK	50	50	19.26	19.47	19.44		
20	QPSK	100	0	19.28	19.55	19.44		
20	16QAM	1	0	19.79	20.00	19.98	20	0
20	16QAM	1	49	19.83	19.96	19.88		
20	16QAM	1	99	19.68	19.87	19.80		
20	16QAM	50	0	19.42	19.68	19.61	20	0
20	16QAM	50	24	19.39	19.65	19.52		
20	16QAM	50	50	19.39	19.60	19.53		
20	16QAM	100	0	19.43	19.63	19.57	20	0
20	64QAM	1	0	19.69	19.96	19.93		
20	64QAM	1	49	19.73	19.91	19.85		
20	64QAM	1	99	19.59	19.79	19.74	20	0
20	64QAM	50	0	19.45	19.72	19.62		
20	64QAM	50	24	19.42	19.65	19.55		
20	64QAM	50	50	19.40	19.62	19.55	20	0
20	64QAM	100	0	19.42	19.68	19.59		
Channel				132047	132322	132597	20	0
Frequency (MHz)				1717.5	1745	1772.5		
15	QPSK	1	0	19.24	19.49	19.42		
15	QPSK	1	37	19.12	19.44	19.29	20	0
15	QPSK	1	74	18.97	19.18	19.22		
15	QPSK	36	0	19.13	19.28	19.18	20	0
15	QPSK	36	20	19.00	19.32	19.17		
15	QPSK	36	39	19.15	19.31	19.20		
15	QPSK	75	0	19.14	19.36	19.26	20	0
15	16QAM	1	0	19.67	19.76	19.72		
15	16QAM	1	37	19.61	19.70	19.61		
15	16QAM	1	74	19.48	19.71	19.59	20	0
15	16QAM	36	0	19.23	19.46	19.49		
15	16QAM	36	20	19.22	19.45	19.35		
15	16QAM	36	39	19.11	19.36	19.32	20	0
15	16QAM	75	0	19.19	19.44	19.36		
15	64QAM	1	0	19.49	19.70	19.77		
15	64QAM	1	37	19.49	19.63	19.60	20	0
15	64QAM	1	74	19.32	19.51	19.50		
15	64QAM	36	0	19.35	19.61	19.48		
15	64QAM	36	20	19.14	19.37	19.34	20	0
15	64QAM	36	39	19.25	19.44	19.41		
15	64QAM	75	0	19.17	19.46	19.47		

Channel				132022	132322	132622	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1745	1775		
10	QPSK	1	0	18.87	19.14	19.17	20	0
10	QPSK	1	25	18.84	19.32	19.01		
10	QPSK	1	49	18.84	19.01	19.02		
10	QPSK	25	0	19.03	19.35	19.21	20	0
10	QPSK	25	12	18.98	19.13	19.21		
10	QPSK	25	25	18.73	19.10	18.94		
10	QPSK	50	0	18.90	19.17	19.04		
10	16QAM	1	0	19.48	19.50	19.41	20	0
10	16QAM	1	25	19.44	19.54	19.42		
10	16QAM	1	49	19.40	19.35	19.22		
10	16QAM	25	0	19.07	19.10	19.10	20	0
10	16QAM	25	12	19.01	19.39	19.09		
10	16QAM	25	25	18.97	19.17	19.13		
10	16QAM	50	0	19.09	19.18	19.17		
10	64QAM	1	0	19.39	19.58	19.52	20	0
10	64QAM	1	25	19.35	19.60	19.39		
10	64QAM	1	49	19.05	19.38	19.15		
10	64QAM	25	0	18.96	19.34	19.12	20	0
10	64QAM	25	12	19.02	19.20	19.15		
10	64QAM	25	25	19.07	19.21	18.97		
10	64QAM	50	0	19.17	19.27	19.23		
Channel				131997	132322	132647	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1745	1777.5		
5	QPSK	1	0	18.50	19.05	19.06	20	0
5	QPSK	1	12	18.64	19.06	18.80		
5	QPSK	1	24	18.68	18.81	18.76		
5	QPSK	12	0	18.63	19.08	18.79	20	0
5	QPSK	12	7	18.78	18.93	18.80		
5	QPSK	12	13	18.59	19.04	18.79		
5	QPSK	25	0	18.68	18.86	18.78		
5	16QAM	1	0	19.26	19.40	19.19	20	0
5	16QAM	1	12	19.34	19.48	19.31		
5	16QAM	1	24	19.10	19.21	19.01		
5	16QAM	12	0	18.78	19.09	18.96	20	0
5	16QAM	12	7	19.01	19.08	18.80		
5	16QAM	12	13	18.70	19.08	18.93		
5	16QAM	25	0	18.93	19.13	19.02		
5	64QAM	1	0	19.09	19.29	19.33	20	0
5	64QAM	1	12	19.11	19.36	19.25		
5	64QAM	1	24	18.86	19.33	19.03		
5	64QAM	12	0	18.95	19.07	18.96	20	0
5	64QAM	12	7	18.90	18.91	18.90		
5	64QAM	12	13	18.87	18.84	18.93		
5	64QAM	25	0	18.93	19.23	19.00		



FCC SAR TEST REPORT

Report No. : FA882923-01

Channel				131987	132322	132657	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1745	1778.5		
3	QPSK	1	0	18.26	18.82	19.00	20	0
3	QPSK	1	8	18.31	18.94	18.57		
3	QPSK	1	14	18.33	18.68	18.73		
3	QPSK	8	0	18.52	18.83	18.70	20	0
3	QPSK	8	4	18.42	18.62	18.65		
3	QPSK	8	7	18.56	18.88	18.60		
3	QPSK	15	0	18.53	18.68	18.54		
3	16QAM	1	0	19.20	19.17	18.97	20	0
3	16QAM	1	8	18.99	19.29	19.31		
3	16QAM	1	14	18.90	19.01	18.90		
3	16QAM	8	0	18.59	18.79	18.62	20	0
3	16QAM	8	4	18.90	19.14	18.53		
3	16QAM	8	7	18.63	18.78	18.88		
3	16QAM	15	0	18.72	18.73	18.76		
3	64QAM	1	0	19.00	19.19	18.86	20	0
3	64QAM	1	8	18.94	19.28	19.06		
3	64QAM	1	14	18.71	19.02	18.98		
3	64QAM	8	0	18.50	18.85	18.78	20	0
3	64QAM	8	4	18.84	18.64	18.75		
3	64QAM	8	7	18.80	18.69	18.65		
3	64QAM	15	0	18.65	19.01	19.03		
Channel				131979	132322	132665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1745	1779.3		
1.4	QPSK	1	0	18.11	18.61	18.66	20	0
1.4	QPSK	1	3	18.08	18.65	18.22		
1.4	QPSK	1	5	18.17	18.45	18.52		
1.4	QPSK	3	0	18.27	18.62	18.60		
1.4	QPSK	3	1	18.21	18.62	18.54		
1.4	QPSK	3	3	18.36	18.67	18.31		
1.4	QPSK	6	0	18.35	18.68	18.34	20	0
1.4	16QAM	1	0	18.85	18.81	18.94	20	0
1.4	16QAM	1	3	18.72	19.03	19.20		
1.4	16QAM	1	5	18.66	18.86	18.87		
1.4	16QAM	3	0	18.55	18.65	18.37		
1.4	16QAM	3	1	18.52	18.79	18.31		
1.4	16QAM	3	3	18.28	18.50	18.65		
1.4	16QAM	6	0	18.51	18.59	18.38	20	0
1.4	64QAM	1	0	18.86	18.96	18.87	20	0
1.4	64QAM	1	3	18.67	18.90	18.87		
1.4	64QAM	1	5	18.62	18.89	18.70		
1.4	64QAM	3	0	18.40	18.59	18.62		
1.4	64QAM	3	1	18.43	18.57	18.67		
1.4	64QAM	3	3	18.62	18.40	18.64		
1.4	64QAM	6	0	18.42	18.86	18.86	20	0

<Near-Body and Product Specific Mode>
<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	21.92	21.90	21.73	22.5	0
20	QPSK	1	49	21.89	21.86	21.76		
20	QPSK	1	99	21.86	21.82	21.73		
20	QPSK	50	0	21.89	21.91	21.68	22.5	0
20	QPSK	50	24	21.92	21.90	21.81		
20	QPSK	50	50	21.94	21.86	21.76		
20	QPSK	100	0	21.94	21.89	21.69		
20	16QAM	1	0	22.38	22.20	22.21	22.5	0
20	16QAM	1	49	22.28	22.24	22.15		
20	16QAM	1	99	22.17	22.27	22.04		
20	16QAM	50	0	22.06	22.00	21.85	22.5	0
20	16QAM	50	24	22.02	22.05	21.94		
20	16QAM	50	50	22.03	21.99	21.88		
20	16QAM	100	0	22.09	22.02	21.80		
20	64QAM	1	0	22.21	22.07	22.07	22.5	0
20	64QAM	1	49	22.14	22.12	22.01		
20	64QAM	1	99	21.99	22.14	21.97		
20	64QAM	50	0	21.07	21.04	20.88	22.5	0
20	64QAM	50	24	21.08	21.10	20.98		
20	64QAM	50	50	21.08	21.03	20.93		
20	64QAM	100	0	21.13	21.01	20.89		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	21.81	21.79	21.67	22.5	0
15	QPSK	1	37	21.69	21.70	21.61		
15	QPSK	1	74	21.73	21.71	21.70		
15	QPSK	36	0	21.83	21.84	21.56	22.5	0
15	QPSK	36	20	21.78	21.81	21.61		
15	QPSK	36	39	21.91	21.83	21.71		
15	QPSK	75	0	21.94	21.74	21.55	22.5	0
15	16QAM	1	0	22.20	22.15	22.17		
15	16QAM	1	37	22.13	22.11	22.01		
15	16QAM	1	74	22.04	22.20	21.91	22.5	0
15	16QAM	36	0	22.02	21.97	21.79		
15	16QAM	36	20	21.96	21.91	21.87		
15	16QAM	36	39	21.87	21.91	21.74	22.5	0
15	16QAM	75	0	22.05	21.92	21.66		
15	64QAM	1	0	22.16	21.99	21.98		
15	64QAM	1	37	22.00	22.11	21.98	22.5	0
15	64QAM	1	74	21.87	22.00	21.91		
15	64QAM	36	0	20.97	20.90	20.72		
15	64QAM	36	20	20.93	21.02	20.87	22.5	0
15	64QAM	36	39	20.89	20.91	20.74		
15	64QAM	75	0	21.09	20.95	20.77		

Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	21.84	21.79	21.48	22.5	0
10	QPSK	1	25	21.70	21.73	21.68		
10	QPSK	1	49	21.60	21.70	21.59		
10	QPSK	25	0	21.69	21.76	21.41	22.5	0
10	QPSK	25	12	21.64	21.64	21.62		
10	QPSK	25	25	21.67	21.68	21.65		
10	QPSK	50	0	21.71	21.66	21.48		
10	16QAM	1	0	22.32	21.98	22.21	22.5	0
10	16QAM	1	25	22.06	22.00	21.91		
10	16QAM	1	49	22.05	22.10	21.91		
10	16QAM	25	0	21.99	22.00	21.82	22.5	0
10	16QAM	25	12	21.97	21.89	21.70		
10	16QAM	25	25	21.81	21.83	21.88		
10	16QAM	50	0	22.06	21.92	21.70		
10	64QAM	1	0	22.15	21.89	22.00	22.5	0
10	64QAM	1	25	21.94	21.93	21.71		
10	64QAM	1	49	21.94	21.97	21.86		
10	64QAM	25	0	21.00	20.72	20.54	22.5	0
10	64QAM	25	12	20.87	20.96	20.77		
10	64QAM	25	25	21.00	20.76	20.81		
10	64QAM	50	0	20.93	20.82	20.80		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	21.57	21.83	21.53	22.5	0
5	QPSK	1	12	21.69	21.66	21.59		
5	QPSK	1	24	21.53	21.55	21.71		
5	QPSK	12	0	21.46	21.74	21.46	22.5	0
5	QPSK	12	7	21.79	21.66	21.60		
5	QPSK	12	13	21.84	21.66	21.58		
5	QPSK	25	0	21.72	21.62	21.50		
5	16QAM	1	0	22.16	21.88	22.23	22.5	0
5	16QAM	1	12	22.16	21.98	21.94		
5	16QAM	1	24	22.12	22.30	21.88		
5	16QAM	12	0	21.80	21.94	21.73	22.5	0
5	16QAM	12	7	21.88	21.72	21.64		
5	16QAM	12	13	21.95	21.61	21.68		
5	16QAM	25	0	22.09	21.75	21.68		
5	64QAM	1	0	21.93	21.92	21.82	22.5	0
5	64QAM	1	12	21.98	22.14	21.92		
5	64QAM	1	24	21.92	21.92	21.67		
5	64QAM	12	0	20.97	20.60	20.50	22.5	0
5	64QAM	12	7	20.66	20.98	20.66		
5	64QAM	12	13	20.78	20.69	20.76		
5	64QAM	25	0	20.91	20.72	20.72		

Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	21.75	21.83	21.36	22.5	0
3	QPSK	1	8	21.73	21.66	21.57		
3	QPSK	1	14	21.51	21.33	21.57		
3	QPSK	8	0	21.55	21.75	21.44	22.5	0
3	QPSK	8	4	21.80	21.56	21.50		
3	QPSK	8	7	21.87	21.61	21.37		
3	QPSK	15	0	21.55	21.61	21.29		
3	16QAM	1	0	22.10	21.83	22.19	22.5	0
3	16QAM	1	8	22.01	22.02	21.78		
3	16QAM	1	14	22.07	22.21	21.67		
3	16QAM	8	0	21.78	21.68	21.67	22.5	0
3	16QAM	8	4	22.04	21.79	21.57		
3	16QAM	8	7	21.78	21.60	21.74		
3	16QAM	15	0	22.01	21.71	21.54		
3	64QAM	1	0	21.95	21.86	21.85	22.5	0
3	64QAM	1	8	21.92	22.02	21.86		
3	64QAM	1	14	21.90	21.75	21.76		
3	64QAM	8	0	20.93	20.65	20.65	22.5	0
3	64QAM	8	4	20.76	20.68	20.69		
3	64QAM	8	7	20.80	20.90	20.75		
3	64QAM	15	0	20.87	20.69	20.70		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	21.78	21.71	21.35	22.5	0
1.4	QPSK	1	3	21.62	21.57	21.63		
1.4	QPSK	1	5	21.34	21.26	21.54		
1.4	QPSK	3	0	21.58	21.78	21.38		
1.4	QPSK	3	1	21.70	21.47	21.45		
1.4	QPSK	3	3	21.79	21.44	21.26		
1.4	QPSK	6	0	21.38	21.59	21.40	22.5	0
1.4	16QAM	1	0	21.93	21.89	22.00	22.5	0
1.4	16QAM	1	3	21.96	22.04	21.79		
1.4	16QAM	1	5	22.05	22.17	21.76		
1.4	16QAM	3	0	21.57	21.53	21.71		
1.4	16QAM	3	1	21.87	21.60	21.60		
1.4	16QAM	3	3	21.69	21.60	21.58		
1.4	16QAM	6	0	22.05	21.70	21.41	22.5	0
1.4	64QAM	1	0	21.97	21.72	21.68	22.5	0
1.4	64QAM	1	3	21.81	21.92	21.86		
1.4	64QAM	1	5	21.88	21.71	21.75		
1.4	64QAM	3	0	20.95	20.58	20.53		
1.4	64QAM	3	1	20.51	20.78	20.86		
1.4	64QAM	3	3	20.86	20.76	20.76		
1.4	64QAM	6	0	20.69	20.74	20.55	22.5	0



<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	21.73	21.71	21.67	22.5	0
20	QPSK	1	49	21.73	21.66	21.61		
20	QPSK	1	99	21.69	21.52	21.50		
20	QPSK	50	0	21.86	21.69	21.70	22.5	0
20	QPSK	50	24	21.85	21.72	21.67		
20	QPSK	50	50	21.75	21.64	21.63		
20	QPSK	100	0	21.74	21.67	21.70	22.5	0
20	16QAM	1	0	21.96	22.05	22.05		
20	16QAM	1	49	22.08	22.02	21.85		
20	16QAM	1	99	21.99	21.80	21.92	22.5	0
20	16QAM	50	0	21.83	21.84	21.77		
20	16QAM	50	24	21.82	21.82	21.77		
20	16QAM	50	50	21.79	21.73	21.77	22.5	0
20	16QAM	100	0	21.79	21.74	21.79		
20	64QAM	1	0	21.83	21.94	21.94		
20	64QAM	1	49	21.86	21.87	21.73	22.5	0
20	64QAM	1	99	21.81	21.68	21.70		
20	64QAM	50	0	21.49	21.50	21.42		
20	64QAM	50	24	21.52	21.49	21.52	22.5	0
20	64QAM	50	50	21.49	21.43	21.46		
20	64QAM	100	0	21.49	21.49	21.49		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	21.70	21.51	21.64	22.5	0
15	QPSK	1	37	21.55	21.66	21.48		
15	QPSK	1	74	21.62	21.37	21.44		
15	QPSK	36	0	21.76	21.51	21.66	22.5	0
15	QPSK	36	20	21.71	21.52	21.53		
15	QPSK	36	39	21.59	21.54	21.47		
15	QPSK	75	0	21.73	21.53	21.63	22.5	0
15	16QAM	1	0	21.95	22.03	21.98		
15	16QAM	1	37	22.08	21.83	21.81		
15	16QAM	1	74	21.99	21.78	21.79	22.5	0
15	16QAM	36	0	21.65	21.73	21.72		
15	16QAM	36	20	21.82	21.71	21.65		
15	16QAM	36	39	21.65	21.62	21.65	22.5	0
15	16QAM	75	0	21.68	21.69	21.59		
15	64QAM	1	0	21.82	21.79	21.93		
15	64QAM	1	37	21.84	21.80	21.58	22.5	0
15	64QAM	1	74	21.69	21.57	21.63		
15	64QAM	36	0	21.46	21.36	21.32		
15	64QAM	36	20	21.34	21.34	21.47	22.5	0
15	64QAM	36	39	21.44	21.29	21.31		
15	64QAM	75	0	21.37	21.32	21.35		

Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	21.59	21.52	21.38	22.5	0
10	QPSK	1	25	21.58	21.36	21.28		
10	QPSK	1	49	21.52	21.43	21.31		
10	QPSK	25	0	21.80	21.61	21.56	22.5	0
10	QPSK	25	12	21.64	21.45	21.50		
10	QPSK	25	25	21.70	21.51	21.40		
10	QPSK	50	0	21.57	21.34	21.51	22.5	0
10	16QAM	1	0	21.83	21.89	21.86		
10	16QAM	1	25	21.80	21.81	21.65		
10	16QAM	1	49	21.88	21.72	21.83	22.5	0
10	16QAM	25	0	21.66	21.71	21.59		
10	16QAM	25	12	21.66	21.65	21.53		
10	16QAM	25	25	21.46	21.57	21.63	22.5	0
10	16QAM	50	0	21.64	21.57	21.73		
10	64QAM	1	0	21.57	21.70	21.69		
10	64QAM	1	25	21.66	21.66	21.57	22.5	0
10	64QAM	1	49	21.63	21.64	21.34		
10	64QAM	25	0	21.30	21.32	21.23		
10	64QAM	25	12	21.34	21.43	21.30	22.5	0
10	64QAM	25	25	21.30	21.19	21.08		
10	64QAM	50	0	21.16	21.33	21.27		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	21.58	21.38	21.33	22.5	0
5	QPSK	1	12	21.40	21.15	21.24		
5	QPSK	1	24	21.31	21.47	21.31		
5	QPSK	12	0	21.53	21.42	21.52	22.5	0
5	QPSK	12	7	21.60	21.46	21.30		
5	QPSK	12	13	21.40	21.17	21.42		
5	QPSK	25	0	21.39	21.27	21.30	22.5	0
5	16QAM	1	0	21.87	21.88	21.72		
5	16QAM	1	12	21.74	21.56	21.50		
5	16QAM	1	24	21.81	21.72	21.75	22.5	0
5	16QAM	12	0	21.66	21.62	21.41		
5	16QAM	12	7	21.61	21.48	21.30		
5	16QAM	12	13	21.54	21.57	21.62	22.5	0
5	16QAM	25	0	21.53	21.47	21.64		
5	64QAM	1	0	21.69	21.66	21.62		
5	64QAM	1	12	21.49	21.63	21.42	22.5	0
5	64QAM	1	24	21.62	21.60	21.30		
5	64QAM	12	0	21.15	21.07	20.98		
5	64QAM	12	7	21.25	21.28	21.33	22.5	0
5	64QAM	12	13	21.12	21.08	21.04		
5	64QAM	25	0	21.14	21.35	21.17		

Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	21.48	21.38	21.29	22.5	0
3	QPSK	1	8	21.18	21.00	21.29		
3	QPSK	1	14	21.27	21.27	21.21		
3	QPSK	8	0	21.46	21.19	21.41	22.5	0
3	QPSK	8	4	21.40	21.35	21.02		
3	QPSK	8	7	21.42	21.15	21.25		
3	QPSK	15	0	21.12	21.19	21.16		
3	16QAM	1	0	21.68	21.72	21.53	22.5	0
3	16QAM	1	8	21.62	21.59	21.30		
3	16QAM	1	14	21.75	21.68	21.57		
3	16QAM	8	0	21.65	21.56	21.32	22.5	0
3	16QAM	8	4	21.43	21.34	21.32		
3	16QAM	8	7	21.38	21.36	21.54		
3	16QAM	15	0	21.45	21.26	21.57		
3	64QAM	1	0	21.36	21.56	21.40	22.5	0
3	64QAM	1	8	21.58	21.55	21.33		
3	64QAM	1	14	21.63	21.49	21.16		
3	64QAM	8	0	21.04	21.06	20.72	22.5	0
3	64QAM	8	4	21.18	21.16	21.37		
3	64QAM	8	7	21.10	20.85	20.89		
3	64QAM	15	0	21.02	21.27	21.09		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	21.44	21.17	21.22	22.5	0
1.4	QPSK	1	3	21.08	20.89	21.10		
1.4	QPSK	1	5	21.00	21.15	21.16		
1.4	QPSK	3	0	21.35	21.22	21.25		
1.4	QPSK	3	1	21.52	21.10	21.18		
1.4	QPSK	3	3	21.42	21.12	21.20		
1.4	QPSK	6	0	20.99	20.96	21.01	22.5	0
1.4	16QAM	1	0	21.59	21.48	21.51	22.5	0
1.4	16QAM	1	3	21.59	21.28	21.18		
1.4	16QAM	1	5	21.71	21.59	21.53		
1.4	16QAM	3	0	21.40	21.36	21.27		
1.4	16QAM	3	1	21.34	21.20	21.29		
1.4	16QAM	3	3	21.29	21.48	21.39		
1.4	16QAM	6	0	21.31	21.19	21.31	22.5	0
1.4	64QAM	1	0	21.24	21.41	21.26	22.5	0
1.4	64QAM	1	3	21.41	21.31	21.27		
1.4	64QAM	1	5	21.49	21.35	20.95		
1.4	64QAM	3	0	21.07	20.87	20.62		
1.4	64QAM	3	1	20.99	21.04	21.36		
1.4	64QAM	3	3	20.87	20.82	21.00		
1.4	64QAM	6	0	20.89	21.13	20.85	22.5	0



<LTE Band 25>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				26140	26340	26590		
Frequency (MHz)				1860	1880	1905		
20	QPSK	1	0	22.03	21.95	21.94	22.5	0
20	QPSK	1	49	21.89	21.91	21.92		
20	QPSK	1	99	21.85	21.95	21.93		
20	QPSK	50	0	22.07	21.99	22.01	22.5	0
20	QPSK	50	24	22.06	21.96	21.96		
20	QPSK	50	50	21.97	21.88	21.93		
20	QPSK	100	0	22.04	21.92	21.96	22.5	0
20	16QAM	1	0	22.27	22.13	22.27		
20	16QAM	1	49	22.19	22.18	22.17		
20	16QAM	1	99	22.11	22.29	22.24	22.5	0
20	16QAM	50	0	22.06	22.02	21.95		
20	16QAM	50	24	22.12	22.04	22.02		
20	16QAM	50	50	22.02	22.00	22.01	22.5	0
20	16QAM	100	0	22.09	21.99	21.90		
20	64QAM	1	0	22.21	22.06	22.08		
20	64QAM	1	49	22.11	22.10	22.06	22.5	0
20	64QAM	1	99	22.01	22.21	22.05		
20	64QAM	50	0	21.39	21.35	21.24		
20	64QAM	50	24	21.45	21.37	21.38	22.5	0
20	64QAM	50	50	21.39	21.36	21.31		
20	64QAM	100	0	21.43	21.32	21.25		
Channel				26115	26340	26615	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1907.5		
15	QPSK	1	0	21.79	21.88	21.90	22.5	0
15	QPSK	1	37	21.74	21.76	21.83		
15	QPSK	1	74	21.72	21.81	21.82		
15	QPSK	36	0	21.78	21.76	21.88	22.5	0
15	QPSK	36	20	21.87	21.79	21.95		
15	QPSK	36	39	21.77	21.88	21.98		
15	QPSK	75	0	21.95	21.72	21.81	22.5	0
15	16QAM	1	0	22.21	22.05	22.12		
15	16QAM	1	37	22.08	22.09	22.13		
15	16QAM	1	74	21.97	22.29	22.13	22.5	0
15	16QAM	36	0	21.99	21.95	21.89		
15	16QAM	36	20	21.99	21.96	21.87		
15	16QAM	36	39	22.00	21.97	21.94	22.5	0
15	16QAM	75	0	21.93	21.82	21.90		
15	64QAM	1	0	22.13	22.02	21.97		
15	64QAM	1	37	22.08	21.91	21.98	22.5	0
15	64QAM	1	74	21.98	22.04	21.98		
15	64QAM	36	0	21.28	21.21	21.10		
15	64QAM	36	20	21.43	21.34	21.35	22.5	0
15	64QAM	36	39	21.25	21.23	21.27		
15	64QAM	75	0	21.31	21.14	21.18		

Channel				26090	26340	26640	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1910		
10	QPSK	1	0	21.86	21.82	21.69	22.5	0
10	QPSK	1	25	21.85	21.85	21.72		
10	QPSK	1	49	21.71	21.61	21.77		
10	QPSK	25	0	21.74	21.63	21.83	22.5	0
10	QPSK	25	12	21.87	21.95	21.85		
10	QPSK	25	25	21.74	21.56	21.83		
10	QPSK	50	0	21.86	21.78	21.57	22.5	0
10	16QAM	1	0	22.20	22.00	22.15		
10	16QAM	1	25	21.92	22.12	21.99		
10	16QAM	1	49	21.85	22.10	22.03	22.5	0
10	16QAM	25	0	21.85	21.84	21.71		
10	16QAM	25	12	21.92	21.82	21.89		
10	16QAM	25	25	21.75	21.71	21.80	22.5	0
10	16QAM	50	0	21.80	21.88	21.70		
10	64QAM	1	0	22.01	21.86	21.90		
10	64QAM	1	25	22.05	22.00	22.01	22.5	0
10	64QAM	1	49	21.77	22.06	21.92		
10	64QAM	25	0	21.19	21.27	21.01		
10	64QAM	25	12	21.27	21.12	21.29	22.5	0
10	64QAM	25	25	21.27	21.22	21.18		
10	64QAM	50	0	21.27	21.12	21.14		
Channel				26065	26340	26665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1912.5		
5	QPSK	1	0	21.82	21.77	21.48	22.5	0
5	QPSK	1	12	21.87	21.67	21.73		
5	QPSK	1	24	21.64	21.74	21.76		
5	QPSK	12	0	21.72	21.38	21.66	22.5	0
5	QPSK	12	7	21.64	21.75	21.86		
5	QPSK	12	13	21.64	21.51	21.79		
5	QPSK	25	0	21.74	21.67	21.70	22.5	0
5	16QAM	1	0	22.03	21.92	21.94		
5	16QAM	1	12	21.80	21.95	21.94		
5	16QAM	1	24	21.74	21.93	21.87	22.5	0
5	16QAM	12	0	21.70	21.78	21.52		
5	16QAM	12	7	21.74	21.62	21.65		
5	16QAM	12	13	21.67	21.64	21.75	22.5	0
5	16QAM	25	0	21.82	21.76	21.71		
5	64QAM	1	0	21.73	21.94	21.83		
5	64QAM	1	12	21.86	21.79	21.83	22.5	0
5	64QAM	1	24	21.82	22.05	21.91		
5	64QAM	12	0	21.16	21.15	20.83		
5	64QAM	12	7	21.23	20.96	21.05	22.5	0
5	64QAM	12	13	21.19	20.93	21.19		
5	64QAM	25	0	21.19	21.10	20.97		

Channel				26055	26340	26675	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1913.5		
3	QPSK	1	0	21.74	21.61	21.40	22.5	0
3	QPSK	1	8	21.74	21.56	21.41		
3	QPSK	1	14	21.47	21.68	21.76		
3	QPSK	8	0	21.69	21.23	21.54	22.5	0
3	QPSK	8	4	21.44	21.73	21.75		
3	QPSK	8	7	21.33	21.34	21.78		
3	QPSK	15	0	21.65	21.58	21.57		
3	16QAM	1	0	21.92	21.77	21.66	22.5	0
3	16QAM	1	8	21.75	21.84	21.77		
3	16QAM	1	14	21.56	21.81	21.95		
3	16QAM	8	0	21.61	21.71	21.50	22.5	0
3	16QAM	8	4	21.50	21.60	21.57		
3	16QAM	8	7	21.71	21.67	21.78		
3	16QAM	15	0	21.59	21.50	21.76		
3	64QAM	1	0	21.65	21.74	21.63	22.5	0
3	64QAM	1	8	21.81	21.56	21.69		
3	64QAM	1	14	21.55	21.86	21.68		
3	64QAM	8	0	21.10	20.87	20.74	22.5	0
3	64QAM	8	4	21.28	20.84	21.02		
3	64QAM	8	7	21.09	20.84	20.98		
3	64QAM	15	0	21.12	21.02	20.72		
Channel				26047	26340	26683	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1914.3		
1.4	QPSK	1	0	21.80	21.66	21.31	22.5	0
1.4	QPSK	1	3	21.67	21.42	21.24		
1.4	QPSK	1	5	21.25	21.60	21.66		
1.4	QPSK	3	0	21.54	21.09	21.32		
1.4	QPSK	3	1	21.30	21.73	21.60		
1.4	QPSK	3	3	21.23	21.15	21.68		
1.4	QPSK	6	0	21.69	21.32	21.30	22.5	0
1.4	16QAM	1	0	21.81	21.94	21.72	22.5	0
1.4	16QAM	1	3	21.62	21.76	21.83		
1.4	16QAM	1	5	21.54	21.79	22.00		
1.4	16QAM	3	0	21.56	21.62	21.41		
1.4	16QAM	3	1	21.60	21.50	21.35		
1.4	16QAM	3	3	21.53	21.64	21.58		
1.4	16QAM	6	0	21.56	21.45	21.74	22.5	0
1.4	64QAM	1	0	21.58	21.56	21.52	22.5	0
1.4	64QAM	1	3	21.85	21.42	21.53		
1.4	64QAM	1	5	21.49	21.66	21.75		
1.4	64QAM	3	0	20.88	20.90	20.53		
1.4	64QAM	3	1	21.14	20.82	20.96		
1.4	64QAM	3	3	21.04	20.71	20.96		
1.4	64QAM	6	0	20.86	21.02	20.62	22.5	0



<LTE Band 66>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				132072	132322	132572		
Frequency (MHz)				1720	1745	1770		
20	QPSK	1	0	21.95	22.12	22.10	22.5	0
20	QPSK	1	49	21.94	22.10	22.07		
20	QPSK	1	99	21.77	21.89	21.92		
20	QPSK	50	0	21.86	22.05	22.01	22.5	0
20	QPSK	50	24	21.77	21.96	22.01		
20	QPSK	50	50	21.76	21.94	21.97		
20	QPSK	100	0	21.80	21.97	21.99	22.5	0
20	16QAM	1	0	22.14	22.35	22.38		
20	16QAM	1	49	22.23	22.25	22.22		
20	16QAM	1	99	22.09	22.18	22.15	22.5	0
20	16QAM	50	0	21.91	22.04	22.06		
20	16QAM	50	24	21.89	22.00	21.98		
20	16QAM	50	50	21.89	21.95	21.94	22.5	0
20	16QAM	100	0	21.85	22.00	21.99		
20	64QAM	1	0	22.02	22.23	22.29		
20	64QAM	1	49	22.12	22.14	22.12	22.5	0
20	64QAM	1	99	22.00	22.09	22.05		
20	64QAM	50	0	21.45	21.56	21.59		
20	64QAM	50	24	21.42	21.52	21.53	22.5	0
20	64QAM	50	50	21.40	21.51	21.49		
20	64QAM	100	0	21.41	21.52	21.54		
Channel				132047	132322	132597	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1745	1772.5		
15	QPSK	1	0	21.84	22.01	21.91	22.5	0
15	QPSK	1	37	21.75	22.02	22.06		
15	QPSK	1	74	21.70	21.81	21.88		
15	QPSK	36	0	21.80	21.99	21.89	22.5	0
15	QPSK	36	20	21.64	21.88	21.90		
15	QPSK	36	39	21.67	21.93	21.86		
15	QPSK	75	0	21.78	21.81	21.96	22.5	0
15	16QAM	1	0	22.06	22.31	22.22		
15	16QAM	1	37	22.07	22.24	22.06		
15	16QAM	1	74	21.90	22.03	22.11	22.5	0
15	16QAM	36	0	21.90	21.84	22.03		
15	16QAM	36	20	21.80	21.80	21.98		
15	16QAM	36	39	21.77	21.89	21.84	22.5	0
15	16QAM	75	0	21.82	21.87	21.93		
15	64QAM	1	0	21.90	22.12	22.24		
15	64QAM	1	37	22.01	22.14	22.01	22.5	0
15	64QAM	1	74	21.87	21.89	21.95		
15	64QAM	36	0	21.26	21.54	21.59		
15	64QAM	36	20	21.26	21.44	21.35	22.5	0
15	64QAM	36	39	21.21	21.41	21.44		
15	64QAM	75	0	21.24	21.34	21.39		

Channel				132022	132322	132622	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1745	1775		
10	QPSK	1	0	21.80	21.94	21.93	22.5	0
10	QPSK	1	25	21.72	21.91	21.98		
10	QPSK	1	49	21.65	21.68	21.69		
10	QPSK	25	0	21.71	21.64	21.92	22.5	0
10	QPSK	25	12	21.37	21.91	21.77		
10	QPSK	25	25	21.60	21.78	21.82		
10	QPSK	50	0	21.64	21.70	21.62		
10	16QAM	1	0	21.92	22.00	22.35	22.5	0
10	16QAM	1	25	22.04	21.94	22.07		
10	16QAM	1	49	21.87	22.09	21.77		
10	16QAM	25	0	21.60	21.80	21.86	22.5	0
10	16QAM	25	12	21.63	21.62	21.66		
10	16QAM	25	25	21.64	21.78	21.74		
10	16QAM	50	0	21.75	21.77	21.82		
10	64QAM	1	0	21.81	22.18	22.06	22.5	0
10	64QAM	1	25	21.94	21.84	21.92		
10	64QAM	1	49	21.76	21.97	21.85		
10	64QAM	25	0	21.41	21.38	21.30	22.5	0
10	64QAM	25	12	21.22	21.21	21.18		
10	64QAM	25	25	21.35	21.27	21.36		
10	64QAM	50	0	21.20	21.41	21.35		
Channel				131997	132322	132647	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1745	1777.5		
5	QPSK	1	0	21.66	21.74	21.86	22.5	0
5	QPSK	1	12	21.66	21.70	21.69		
5	QPSK	1	24	21.46	21.51	21.41		
5	QPSK	12	0	21.42	21.55	21.87	22.5	0
5	QPSK	12	7	21.34	21.71	21.63		
5	QPSK	12	13	21.52	21.75	21.66		
5	QPSK	25	0	21.48	21.51	21.63		
5	16QAM	1	0	22.01	21.99	22.24	22.5	0
5	16QAM	1	12	22.04	21.92	21.92		
5	16QAM	1	24	21.79	22.05	21.74		
5	16QAM	12	0	21.65	21.70	21.90	22.5	0
5	16QAM	12	7	21.78	21.53	21.71		
5	16QAM	12	13	21.56	21.69	21.79		
5	16QAM	25	0	21.69	21.62	21.68		
5	64QAM	1	0	21.90	21.90	21.98	22.5	0
5	64QAM	1	12	21.78	21.79	22.00		
5	64QAM	1	24	21.81	21.86	21.95		
5	64QAM	12	0	21.19	21.16	21.21	22.5	0
5	64QAM	12	7	21.29	21.08	21.22		
5	64QAM	12	13	21.30	21.18	21.24		
5	64QAM	25	0	20.93	21.25	21.19		

Channel				131987	132322	132657	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1745	1778.5		
3	QPSK	1	0	21.54	21.74	21.75	22.5	0
3	QPSK	1	8	21.56	21.57	21.60		
3	QPSK	1	14	21.33	21.59	21.43		
3	QPSK	8	0	21.34	21.34	21.94	22.5	0
3	QPSK	8	4	21.12	21.63	21.65		
3	QPSK	8	7	21.39	21.55	21.46		
3	QPSK	15	0	21.29	21.34	21.39		
3	16QAM	1	0	21.99	21.98	22.20	22.5	0
3	16QAM	1	8	21.96	21.69	21.69		
3	16QAM	1	14	21.73	21.99	21.47		
3	16QAM	8	0	21.58	21.68	21.71	22.5	0
3	16QAM	8	4	21.73	21.30	21.56		
3	16QAM	8	7	21.53	21.48	21.54		
3	16QAM	15	0	21.56	21.60	21.55		
3	64QAM	1	0	21.90	21.83	21.86	22.5	0
3	64QAM	1	8	21.64	21.43	21.91		
3	64QAM	1	14	21.44	21.82	21.65		
3	64QAM	8	0	21.01	21.01	20.96	22.5	0
3	64QAM	8	4	21.07	20.92	21.04		
3	64QAM	8	7	21.19	21.05	21.13		
3	64QAM	15	0	20.88	21.34	21.06		
Channel				131979	132322	132665	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1745	1779.3		
1.4	QPSK	1	0	21.47	21.66	21.60	22.5	0
1.4	QPSK	1	3	21.28	21.57	21.54		
1.4	QPSK	1	5	21.28	21.36	21.15		
1.4	QPSK	3	0	21.23	21.26	21.87		
1.4	QPSK	3	1	21.01	21.58	21.48		
1.4	QPSK	3	3	21.46	21.58	21.32		
1.4	QPSK	6	0	21.28	21.14	21.33	22.5	0
1.4	16QAM	1	0	21.77	21.76	22.04	22.5	0
1.4	16QAM	1	3	21.96	21.54	21.49		
1.4	16QAM	1	5	21.50	22.05	21.36		
1.4	16QAM	3	0	21.44	21.67	21.70		
1.4	16QAM	3	1	21.52	21.34	21.44		
1.4	16QAM	3	3	21.38	21.63	21.47		
1.4	16QAM	6	0	21.27	21.34	21.44	22.5	0
1.4	64QAM	1	0	21.63	21.59	21.56	22.5	0
1.4	64QAM	1	3	21.65	21.43	21.70		
1.4	64QAM	1	5	21.24	21.89	21.49		
1.4	64QAM	3	0	21.13	21.04	20.80		
1.4	64QAM	3	1	20.90	20.92	20.72		
1.4	64QAM	3	3	21.18	20.91	21.12		
1.4	64QAM	6	0	20.86	21.22	21.00	22.5	0

<LTE Carrier Aggregation combinations>
General Note:

1. This device supports Carrier Aggregation on downlink only for inter and intra band, Uplink CA is not supported. For the device supports combination bands and configurations are according to 3GPP.
2. In applying the existing power measurement procedure of KDB 941225 D05A for DL CA SAR test exclusion, only the subset with the largest number of combinations of the frequency band and CCs in each row need consideration, and that configurations require power measurement should be highlighted in the below table.

2CC Downlink Carrier Aggregation				3CC Downlink Carrier Aggregation			
Number	Combination	Restriction	Covered by Measurement Superset	Number	Combination	Restriction	Covered by Measurement Superset
1	CA_2A-2A			30	CA_2A-4A-5A		
2	CA_2A-4A		3CC-31	31	CA_2A-4A-7A		
3	CA_2A-66A			32	CA_2A-4A-12A		
4	CA_2A-5A		3CC-30	33	CA_2A-4A-29A	B29 SCC only	
5	CA_2A-7A		3CC-35	34	CA_2A-7C		
6	CA_2A-12A		3CC-32	35	CA_2A-7A-7A		
7	CA_2A-13A			36	CA_2A-7A-12A		
8	CA_2A-17A			37	CA_2A-12B		
9	CA_2A-29A	B29 SCC only	3CC-33	38	CA_4A-4A-12A		
10	CA_4A-4A			39	CA_4A-4A-29A	B29 SCC only	
11	CA_4A-5A		3CC-30	40	CA_4A-7A-7A		
12	CA_4A-7A		3CC-40	41	CA_4A-7A-12A		
13	CA_4A-12A		3CC-38	42	CA_4A-12B		
14	CA_4A-13A			43	CA_5A-7C		
15	CA_4A-17A			44	CA_12A-66A-66A		
16	CA_4A-29A	B29 SCC only	3CC-39	45	CA_12A-66C		
17	CA_5A-7A						
18	CA_5A-25A						
19	CA_7A-7A						
20	CA_7A-12A		3CC-36				
21	CA_12A-66A		3CC-44				
22	CA_12B						
23	CA_12A-25A						
24	CA_7C						
25	CA_7B						
26	CA_25A-25A						
27	CA_66C						
28	CA_66B						
29	CA_66A-66A						

<Power verification when LTE Carrier Aggregation Active>
General Note:

- i. According to KDB941225 D05A v01r02, Uplink maximum output power measurement with downlink carrier aggregation active should be measured, using the highest output channel measured without downlink carrier aggregation, to confirm that uplink maximum output power with downlink carrier aggregation active remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output measured without downlink carrier aggregation active.
- ii. Uplink maximum output power with downlink carrier aggregation active does not show more than ¼ dB higher than the maximum output power without downlink carrier aggregation active, therefore SAR evaluation with downlink carrier aggregation active can be excluded.
- iii. The device supports downlink two carrier aggregation. For power measurement were control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
- iv. Selected highest measured power when downlink carrier aggregation is inactive for conducted power comparison with downlink carrier aggregation is active, to confirm that when downlink carrier aggregation is active uplink maximum output power remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output power measured when downlink carrier aggregation inactive.
- v. For non-contiguous intra-band CA, the SCC selected to provide maximum separation from the PCC and must remain fully within the downlink transmission band.
- vi. For Intra-band, contiguous CA, the downlink channels selected to perform the uplink power measurement must satisfy 3GPP channel spacing (5.4.1A of 3GPP TS 36.521 or equivalent) and channel bandwidth (5.4.2A) requirements.

$$\text{Nominal channel spacing} = \left\lceil \frac{BW_{\text{Channel}(1)} + BW_{\text{Channel}(2)} - 0.1 |BW_{\text{Channel}(1)} - BW_{\text{Channel}(2)}|}{0.6} \right\rceil 0.3 \text{ [MHz]}$$

<Two Carrier power verification>

Configure		PCC						SCC				Power		
		LTE Band	BW (MHz)	UL Freq. (MHz)	UL Channel	Mod.	UL# RB	UL RB Offset	LTE Band	BW (MHz)	DL Freq. (MHz)	DL Channel	With CA Tx.Power (dBm)	W/O CA Tx.Power (dBm)
Inter-Band		2	20	1860	18700	QPSK	1	0	13	10	751	5230	23.80	23.83
		2	10	1880	18900	QPSK	1	0	17	10	740	5790	23.72	23.82
		2	20	1860	18700	QPSK	1	0	66	20	2155	66886	23.72	23.83
		4	20	1732.5	20175	QPSK	1	0	13	10	751	5230	24.42	24.45
		4	10	1715	20000	QPSK	1	0	17	10	740	5790	24.34	24.44
		5	10	829	20450	QPSK	1	0	7	20	2655	3100	24.41	24.50
		5	10	829	20450	QPSK	1	0	25	20	1960	8340	24.40	24.50
		12	10	707.5	23095	QPSK	1	0	25	20	1960	8340	24.40	24.49
Intra-Band	Non-Contiguous	2	20	1860	18700	QPSK	1	0	2	5	1987.5	1175	23.75	23.83
		4	20	1732.5	20175	QPSK	1	0	4	5	2152.5	2375	24.43	24.45
		7	20	2535	21100	QPSK	1	99	7	5	2687.5	3425	23.98	24.03
		25	20	1880	26340	QPSK	1	0	25	5	1992.5	8665	23.91	23.99
		66	20	1745	132322	QPSK	1	0	66	5	2197.5	67311	23.82	23.84
	Contiguous	12	10	710	23120	QPSK	1	0	12	5	732.80	5048	24.39	24.40
		7	20	2535	21100	QPSK	1	99	7	20	2674.80	3298	23.93	24.03
		7	15	2562.5	21375	QPSK	1	74	7	5	2673.20	3282	23.97	24.02
		66	15	1745	132322	QPSK	1	0	66	5	2154.30	66879	23.82	23.83
		66	20	1745	132322	QPSK	1	0	66	20	2164.80	67084	23.78	23.84



<Three Carrier power verification>

Configure	PCC							SCC1				SCC2				Power	
	LTE Band	BW (MHz)	UL Freq. (MHz)	UL Channel	Mod.	UL# RB	UL RB Offset	LTE Band	BW (MHz)	DL Freq. (MHz)	DL Channel	LTE Band	BW (MHz)	DL Freq. (MHz)	DL Channel	With CA Tx.Power (dBm)	W/O CA Tx.Power (dBm)
Inter-Band	2	20	1860	18700	QPSK	1	0	4	20	2132.5	2175	5	10	881.5	2525	23.76	23.83
	2	20	1860	18700	QPSK	1	0	4	20	2132.5	2175	7	20	2655	3100	23.74	23.83
	2	20	1860	18700	QPSK	1	0	4	20	2132.5	2175	12	10	737.5	5095	23.83	23.83
	2	20	1860	18700	QPSK	1	0	4	20	2132.5	2175	29	10	722.5	9715	23.81	23.83
	2	20	1860	18700	QPSK	1	0	7	20	2655	3100	7	20	2674.8	3298	23.78	23.83
	2	20	1860	18700	QPSK	1	0	7	20	2655	3100	7	5	2687.5	3425	23.76	23.83
	2	20	1860	18700	QPSK	1	0	7	20	2655	3100	12	10	737.5	5095	23.83	23.83
	2	20	1860	18700	QPSK	1	0	12	10	740	5120	12	5	732.8	5048	23.73	23.83
	4	20	1732.5	20175	QPSK	1	0	4	5	2152.5	2375	12	10	737.5	5095	24.40	24.45
	4	20	1732.5	20175	QPSK	1	0	4	20	2132.5	2175	29	10	722.5	9715	24.44	24.45
	4	20	1732.5	20175	QPSK	1	0	7	20	2655	3100	7	5	2687.5	3425	24.45	24.45
	4	20	1732.5	20175	QPSK	1	0	7	20	2655	3100	12	10	737.5	5095	24.39	24.45
	4	20	1732.5	20175	QPSK	1	0	12	10	740	5120	12	5	732.8	5048	24.37	24.45
	5	10	829	20450	QPSK	1	0	7	20	2655	3100	7	20	2674.8	3298	24.47	24.50
	12	10	707.5	23095	QPSK	1	0	66	20	2155	66886	66	5	2197.5	67311	24.44	24.49
	12	10	707.5	23095	QPSK	1	0	66	20	2155	66886	66	20	2174.8	67084	24.41	24.49

<WLAN Conducted Power>**General Note:**

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.¹⁸ The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

<2.4GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	16.77	17.00	99.05
		6	2437	16.72	17.00	
		11	2462	16.79	17.00	
		12	2467	16.67	17.00	
		13	2472	16.78	17.00	
	802.11g 6Mbps	1	2412	15.79	16.00	94.95
		6	2437	15.91	16.00	
		11	2462	15.97	16.00	
		12	2467	11.79	12.00	
		13	2472	-3.12	-3.00	
	802.11n-HT20 MCS0	1	2412	15.69	16.00	94.55
		6	2437	15.78	16.00	
		11	2462	15.80	16.00	
		12	2467	11.65	12.00	
		13	2472	-4.78	-4.50	

<5GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	15.44	15.50	94.95
		40	5200	15.21	15.50	
		44	5220	15.26	15.50	
		48	5240	15.22	15.50	
	802.11n-HT20 MCS0	36	5180	14.79	15.00	94.12
		40	5200	14.83	15.00	
		44	5220	14.98	15.00	
		48	5240	14.94	15.00	
	802.11n-HT40 MCS0	38	5190	14.37	14.50	90.87
		46	5230	14.47	14.50	
	802.11ac-VHT20 MCS0	36	5180	14.74	15.00	94.61
		40	5200	14.72	15.00	
		44	5220	14.96	15.00	
		48	5240	14.92	15.00	
	802.11ac-VHT40 MCS0	38	5190	14.36	14.50	88.32
		46	5230	14.40	14.50	
	802.11ac-VHT80 MCS0	42	5210	12.84	13.00	86.71

5.3GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	52	5260	15.12	15.50	94.95
		56	5280	15.16	15.50	
		60	5300	15.19	15.50	
		64	5320	15.41	15.50	
	802.11n-HT20 MCS0	52	5260	14.89	15.00	94.12
		56	5280	14.88	15.00	
		60	5300	14.92	15.00	
		64	5320	14.99	15.00	
	802.11n-HT40 MCS0	54	5270	14.28	14.50	90.87
		62	5310	14.47	14.50	
	802.11ac-VHT20 MCS0	52	5260	14.87	15.00	94.61
		56	5280	14.86	15.00	
		60	5300	14.88	15.00	
		64	5320	14.95	15.00	
	802.11ac-VHT40 MCS0	54	5270	14.25	14.50	88.32
		62	5310	14.45	14.50	
	802.11ac-VHT80 MCS0	58	5290	11.63	12.00	86.71

5.5GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	100	5500	15.49	15.50	94.95
		116	5580	15.41	15.50	
		124	5620	15.40	15.50	
		132	5660	15.42	15.50	
		144	5720	15.38	15.50	
	802.11n-HT20 MCS0	100	5500	14.91	15.00	94.12
		116	5580	14.98	15.00	
		124	5620	14.92	15.00	
		132	5660	14.88	15.00	
		144	5720	14.84	15.00	
	802.11n-HT40 MCS0	102	5510	14.49	14.50	90.87
		110	5550	14.47	14.50	
		126	5630	14.41	14.50	
		134	5670	14.46	14.50	
		142	5710	14.43	14.50	
	802.11ac-VHT20 MCS0	100	5500	14.89	15.00	94.61
		116	5580	14.96	15.00	
		124	5620	14.91	15.00	
		132	5660	14.86	15.00	
		144	5720	14.81	15.00	
	802.11ac-VHT40 MCS0	102	5510	14.48	14.50	88.32
		110	5550	14.44	14.50	
		126	5630	14.42	14.50	
		134	5670	14.45	14.50	
		142	5710	14.41	14.50	
	802.11ac-VHT80 MCS0	106	5530	13.65	14.00	86.71
		122	5610	13.69	14.00	
		138	5690	13.77	14.00	

5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a MCS0	149	5745	15.46	15.50	94.95
		157	5785	15.36	15.50	
		165	5825	15.39	15.50	
	802.11n-HT20 MCS0	149	5745	14.97	15.00	94.12
		157	5785	14.88	15.00	
		165	5825	14.61	15.00	
	802.11n-HT40 MCS0	151	5755	14.47	14.50	90.87
		159	5795	14.49	14.50	
	802.11ac-VHT20 MCS0	149	5745	14.95	15.00	94.61
		157	5785	14.82	15.00	
		165	5825	14.63	15.00	
	802.11ac-VHT40 MCS0	151	5755	14.45	14.50	88.32
		159	5795	14.47	14.50	
	802.11ac-VHT80 MCS0	155	5775	13.66	14.00	86.71




<2.4GHz Bluetooth>

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	11.30	8.82	8.85
	CH 39	2441	9.96	7.04	7.05
	CH 78	2480	11.29	8.76	8.81
Tune-up Limit			11.50	9.50	9.50

Mode	Channel	Frequency (MHz)	Average power (dBm)	
			1Mbps	2Mbps
LE	CH 00	2402	0.58	0.66
	CH 19	2440	-0.61	-0.57
	CH 39	2480	1.61	1.65
Tune-up Limit			2.00	2.00

General Note:

- For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 77.07% is refer part15C report and also considered in SAR testing, and the duty cycle would be scaled to theoretical 83.3% in reported SAR calculation.



12. RF Exposure Conditions

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	Yes	No

General Note:

- Referring to KDB 941225 D06 v02r01, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge, The detail antenna location please refers to Appendix D.

13. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. Per KDB 648474 D04v01r03, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.
5. Per KDB648474 D04v01r03, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, when hotspot mode applies, 10-g product specific SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg, however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold, for this device only GSM1900, WCDMA B2/B4 and LTE B25/B66 scaled to maximum output power is higher than 1.2W/kg, therefore product specific SAR is necessary.
6. For 5GHz WLAN product specific SAR is necessary too, due to an overall diagonal dimension is > 16 cm.
7. When hotspot mode is active which the power will be reduced of GSM1900, WCDMA B2/B4, and LTE B2/B4/B25/B66, detail descriptions of the power reduction mechanism are included in the operational description.
8. The device employs sensors to detect different usage conditions, when operating in near-body or handheld condition by end user, the device will reduced maximum output powers on the WCDMA B2 / B4, LTE B2 / B4 / B25 / B66 and detail descriptions of the power reduction mechanism are included in the operational description.
9. In this report, the 10g SAR results which is submitted voluntarily.

GSM Note:

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE / DTM modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE / DTM are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode, SAR measurement is not required for the secondary mode.
3. Power reduction which is triggered by hotspot mode is implemented in GSM1900 band, for hotspot mode SAR testing EUT was set in reduced power mode and GPRS 4Tx slot due to its highest frame-average power.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B5/B12 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE Band 2/4/17 SAR test was covered by Band 25/66/12; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

13.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
01	GSM850	GPRS (4 Tx slots)	Right Cheek	0mm	128	824.2	27.47	28.00	1.130	0.04	0.199	0.225	0.160	0.181
	GSM850	GPRS (4 Tx slots)	Right Tilted	0mm	128	824.2	27.47	28.00	1.130	0.028	0.099	0.112	0.040	0.045
	GSM850	GPRS (4 Tx slots)	Left Cheek	0mm	128	824.2	27.47	28.00	1.130	-0.077	0.156	0.176	0.120	0.136
	GSM850	GPRS (4 Tx slots)	Left Tilted	0mm	128	824.2	27.47	28.00	1.130	-0.061	0.102	0.115	0.077	0.087
02	GSM1900	GPRS (4 Tx slots)	Right Cheek	0mm	810	1909.8	24.94	25.00	1.014	0.12	0.021	0.021	0.013	0.013
	GSM1900	GPRS (4 Tx slots)	Right Tilted	0mm	810	1909.8	24.94	25.00	1.014	0.12	0.007	0.007	0.002	0.002
	GSM1900	GPRS (4 Tx slots)	Left Cheek	0mm	810	1909.8	24.94	25.00	1.014	0.194	0.017	0.017	0.010	0.010
	GSM1900	GPRS (4 Tx slots)	Left Tilted	0mm	810	1909.8	24.94	25.00	1.014	0.13	0.015	0.015	0.008	0.009

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
03	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	9538	1907.6	24.47	25.00	1.130	0.1	0.054	0.061	0.035	0.040
	WCDMA II	RMC 12.2Kbps	Right Tilted	0mm	9538	1907.6	24.47	25.00	1.130	0.15	0.025	0.028	0.014	0.016
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9538	1907.6	24.47	25.00	1.130	0.141	0.037	0.042	0.023	0.026
	WCDMA II	RMC 12.2Kbps	Left Tilted	0mm	9538	1907.6	24.47	25.00	1.130	0.137	0.028	0.032	0.016	0.018
04	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	1413	1732.6	24.43	24.50	1.016	0.13	0.069	0.070	0.044	0.045
	WCDMA IV	RMC 12.2Kbps	Right Tilted	0mm	1413	1732.6	24.43	24.50	1.016	0.01	0.015	0.015	0.009	0.010
	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1413	1732.6	24.43	24.50	1.016	0.114	0.050	0.051	0.031	0.032
	WCDMA IV	RMC 12.2Kbps	Left Tilted	0mm	1413	1732.6	24.43	24.50	1.016	0.171	0.020	0.020	0.011	0.011
05	WCDMA V	RMC 12.2Kbps	Right Cheek	0mm	4132	826.4	24.55	25.00	1.109	-0.03	0.137	0.152	0.106	0.118
	WCDMA V	RMC 12.2Kbps	Right Tilted	0mm	4132	826.4	24.55	25.00	1.109	-0.137	0.064	0.071	0.050	0.055
	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4132	826.4	24.55	25.00	1.109	-0.029	0.117	0.130	0.089	0.099
	WCDMA V	RMC 12.2Kbps	Left Tilted	0mm	4132	826.4	24.55	25.00	1.109	-0.043	0.076	0.084	0.057	0.063



<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 5	10M	QPSK	1	0	Right Cheek	0mm	20525	836.5	24.15	25.00	1.216	0.06	0.121	0.147	0.092	0.112
	LTE Band 5	10M	QPSK	25	0	Right Cheek	0mm	20525	836.5	23.19	24.00	1.205	0.071	0.110	0.133	0.083	0.100
	LTE Band 5	10M	QPSK	1	0	Right Tilted	0mm	20525	836.5	24.15	25.00	1.216	-0.087	0.072	0.088	0.055	0.067
	LTE Band 5	10M	QPSK	25	0	Right Tilted	0mm	20525	836.5	23.19	24.00	1.205	-0.095	0.060	0.072	0.045	0.054
06	LTE Band 5	10M	QPSK	1	0	Left Cheek	0mm	20525	836.5	24.15	25.00	1.216	0.14	0.137	0.167	0.105	0.128
	LTE Band 5	10M	QPSK	25	0	Left Cheek	0mm	20525	836.5	23.19	24.00	1.205	0.06	0.101	0.122	0.079	0.095
	LTE Band 5	10M	QPSK	1	0	Left Tilted	0mm	20525	836.5	24.15	25.00	1.216	0.057	0.086	0.105	0.064	0.078
	LTE Band 5	10M	QPSK	25	0	Left Tilted	0mm	20525	836.5	23.19	24.00	1.205	-0.061	0.067	0.081	0.050	0.060
	LTE Band 7	20M	QPSK	1	99	Right Cheek	0mm	20850	2510	24.39	24.50	1.026	0.11	0.107	0.110	0.063	0.065
	LTE Band 7	20M	QPSK	50	50	Right Cheek	0mm	20850	2510	23.38	23.50	1.028	-0.106	0.075	0.077	0.043	0.044
07	LTE Band 7	20M	QPSK	1	99	Right Tilted	0mm	20850	2510	24.39	24.50	1.026	0.16	0.119	0.122	0.066	0.068
	LTE Band 7	20M	QPSK	50	50	Right Tilted	0mm	20850	2510	23.38	23.50	1.028	0.125	0.099	0.102	0.053	0.054
	LTE Band 7	20M	QPSK	1	99	Left Cheek	0mm	20850	2510	24.39	24.50	1.026	0.114	0.112	0.115	0.062	0.064
	LTE Band 7	20M	QPSK	50	50	Left Cheek	0mm	20850	2510	23.38	23.50	1.028	0.159	0.044	0.045	0.027	0.028
	LTE Band 7	20M	QPSK	1	99	Left Tilted	0mm	20850	2510	24.39	24.50	1.026	0.19	0.045	0.046	0.024	0.025
	LTE Band 7	20M	QPSK	50	50	Left Tilted	0mm	20850	2510	23.38	23.50	1.028	0.127	0.035	0.036	0.018	0.019
08	LTE Band 12	10M	QPSK	1	0	Right Cheek	0mm	23095	707.5	23.59	24.50	1.233	0.01	0.151	0.186	0.120	0.148
	LTE Band 12	10M	QPSK	25	0	Right Cheek	0mm	23095	707.5	22.62	23.50	1.225	0.138	0.124	0.152	0.098	0.120
	LTE Band 12	10M	QPSK	1	0	Right Tilted	0mm	23095	707.5	23.59	24.50	1.233	0.146	0.077	0.095	0.063	0.078
	LTE Band 12	10M	QPSK	25	0	Right Tilted	0mm	23095	707.5	22.62	23.50	1.225	0.042	0.075	0.092	0.062	0.076
	LTE Band 12	10M	QPSK	1	0	Left Cheek	0mm	23095	707.5	23.59	24.50	1.233	0.123	0.121	0.149	0.099	0.122
	LTE Band 12	10M	QPSK	25	0	Left Cheek	0mm	23095	707.5	22.62	23.50	1.225	0.18	0.107	0.131	0.090	0.110
	LTE Band 12	10M	QPSK	1	0	Left Tilted	0mm	23095	707.5	23.59	24.50	1.233	0.1	0.097	0.120	0.082	0.101
	LTE Band 12	10M	QPSK	25	0	Left Tilted	0mm	23095	707.5	22.62	23.50	1.225	0.162	0.087	0.107	0.072	0.088
09	LTE Band 13	10M	QPSK	1	0	Right Cheek	0mm	23230	782	24.33	25.00	1.167	-0.07	0.170	0.198	0.134	0.156
	LTE Band 13	10M	QPSK	25	0	Right Cheek	0mm	23230	782	23.46	24.00	1.132	-0.052	0.144	0.163	0.114	0.129
	LTE Band 13	10M	QPSK	1	0	Right Tilted	0mm	23230	782	24.33	25.00	1.167	-0.013	0.092	0.107	0.074	0.086
	LTE Band 13	10M	QPSK	25	0	Right Tilted	0mm	23230	782	23.46	24.00	1.132	-0.022	0.078	0.088	0.063	0.071
	LTE Band 13	10M	QPSK	1	0	Left Cheek	0mm	23230	782	24.33	25.00	1.167	0.102	0.149	0.174	0.119	0.139
	LTE Band 13	10M	QPSK	25	0	Left Cheek	0mm	23230	782	23.46	24.00	1.132	0.07	0.120	0.136	0.095	0.108
	LTE Band 13	10M	QPSK	1	0	Left Tilted	0mm	23230	782	24.33	25.00	1.167	-0.008	0.104	0.121	0.080	0.093
	LTE Band 13	10M	QPSK	25	0	Left Tilted	0mm	23230	782	23.46	24.00	1.132	-0.02	0.084	0.095	0.065	0.074
10	LTE Band 25	20M	QPSK	1	0	Right Cheek	0mm	26590	1905	24.28	24.50	1.052	0.14	0.056	0.059	0.035	0.037
	LTE Band 25	20M	QPSK	50	24	Right Cheek	0mm	26590	1905	23.35	23.50	1.035	0.014	0.044	0.046	0.027	0.028
	LTE Band 25	20M	QPSK	1	0	Right Tilted	0mm	26590	1905	24.28	24.50	1.052	0.017	0.039	0.041	0.022	0.023
	LTE Band 25	20M	QPSK	50	24	Right Tilted	0mm	26590	1905	23.35	23.50	1.035	0.176	0.030	0.031	0.016	0.017
	LTE Band 25	20M	QPSK	1	0	Left Cheek	0mm	26590	1905	24.28	24.50	1.052	0.029	0.039	0.041	0.023	0.024
	LTE Band 25	20M	QPSK	50	24	Left Cheek	0mm	26590	1905	23.35	23.50	1.035	0.021	0.034	0.035	0.020	0.021
	LTE Band 25	20M	QPSK	1	0	Left Tilted	0mm	26590	1905	24.28	24.50	1.052	-0.033	0.023	0.024	0.013	0.014
	LTE Band 25	20M	QPSK	50	24	Left Tilted	0mm	26590	1905	23.35	23.50	1.035	0.129	0.018	0.019	0.010	0.010
11	LTE Band 66	20M	QPSK	1	0	Right Cheek	0mm	132322	1745	24.50	24.50	1.000	0.19	0.114	0.114	0.072	0.072
	LTE Band 66	20M	QPSK	50	50	Right Cheek	0mm	132322	1745	23.48	23.50	1.005	0.088	0.090	0.090	0.058	0.058
	LTE Band 66	20M	QPSK	1	0	Right Tilted	0mm	132322	1745	24.50	24.50	1.000	-0.07	0.049	0.049	0.029	0.029
	LTE Band 66	20M	QPSK	50	50	Right Tilted	0mm	132322	1745	23.48	23.50	1.005	0.002	0.048	0.048	0.028	0.028
	LTE Band 66	20M	QPSK	1	0	Left Cheek	0mm	132322	1745	24.50	24.50	1.000	0.08	0.052	0.052	0.036	0.036
	LTE Band 66	20M	QPSK	50	50	Left Cheek	0mm	132322	1745	23.48	23.50	1.005	-0.046	0.038	0.038	0.026	0.026
	LTE Band 66	20M	QPSK	1	0	Left Tilted	0mm	132322	1745	24.50	24.50	1.000	0.127	0.037	0.037	0.022	0.022
	LTE Band 66	20M	QPSK	50	50	Left Tilted	0mm	132322	1745	23.48	23.50	1.005	0.025	0.031	0.031	0.018	0.018

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	11	2462	16.79	17.00	1.050	99.05	1.010	0.11	0.194	0.206	0.094	0.100
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	11	2462	16.79	17.00	1.050	99.05	1.010	0.06	0.146	0.155	0.072	0.076
12	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	11	2462	16.79	17.00	1.050	99.05	1.010	-0.1	0.573	0.607	0.259	0.275
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	11	2462	16.79	17.00	1.050	99.05	1.010	-0.05	0.378	0.401	0.191	0.202
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	64	5320	15.41	15.50	1.022	94.95	1.053	-0.11	0.545	0.587	0.180	0.194
	WLAN5GHz	802.11a 6Mbps	Right Tilted	0mm	64	5320	15.41	15.50	1.022	94.95	1.053	-0.09	0.546	0.588	0.172	0.185
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	64	5320	15.41	15.50	1.022	94.95	1.053	-0.02	0.664	0.715	0.214	0.230
13	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	64	5320	15.41	15.50	1.022	94.95	1.053	-0.09	0.696	0.749	0.216	0.232
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	100	5500	15.49	15.50	1.003	94.95	1.053	0.19	0.336	0.355	0.109	0.115
	WLAN5GHz	802.11a 6Mbps	Right Tilted	0mm	100	5500	15.49	15.50	1.003	94.95	1.053	0.15	0.382	0.404	0.123	0.130
14	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	100	5500	15.49	15.50	1.003	94.95	1.053	0	0.499	0.527	0.159	0.168
	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	100	5500	15.49	15.50	1.003	94.95	1.053	0.07	0.476	0.503	0.150	0.158
	WLAN5GHz	802.11a 6Mbps	Right Cheek	0mm	149	5745	15.46	15.50	1.010	94.95	1.053	0.11	0.587	0.625	0.195	0.207
	WLAN5GHz	802.11a 6Mbps	Right Tilted	0mm	149	5745	15.46	15.50	1.010	94.95	1.053	0.15	0.635	0.676	0.211	0.224
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	149	5745	15.46	15.50	1.010	94.95	1.053	0.01	0.768	0.817	0.227	0.242
	WLAN5GHz	802.11a 6Mbps	Left Cheek	0mm	165	5825	15.39	15.50	1.027	94.95	1.053	0.11	0.818	0.884	0.246	0.266
	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	149	5745	15.46	15.50	1.010	94.95	1.053	0	0.762	0.811	0.232	0.247
15	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	165	5825	15.39	15.50	1.027	94.95	1.053	0	0.853	0.922	0.257	0.278

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	Bluetooth	1Mbps	Right Cheek	0mm	0	2402	11.30	11.50	1.047	77.07	1.081	0.09	0.036	0.041	0.015	0.017
	Bluetooth	1Mbps	Right Tilted	0mm	0	2402	11.30	11.50	1.047	77.07	1.081	0.06	0.031	0.035	0.014	0.016
16	Bluetooth	1Mbps	Left Cheek	0mm	0	2402	11.30	11.50	1.047	77.07	1.081	0.01	0.084	0.095	0.035	0.040
	Bluetooth	1Mbps	Left Tilted	0mm	0	2402	11.30	11.50	1.047	77.07	1.081	0.16	0.064	0.072	0.029	0.033

13.2 Hotspot SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Front	10mm	OFF	128	824.2	27.47	28.00	1.130	-0.154	0.231	0.261	0.136	0.154
17	GSM850	GPRS (4 Tx slots)	Back	10mm	OFF	128	824.2	27.47	28.00	1.130	-0.11	0.516	0.583	0.298	0.337
	GSM850	GPRS (4 Tx slots)	Left Side	10mm	OFF	128	824.2	27.47	28.00	1.130	0.028	0.085	0.096	0.059	0.067
	GSM850	GPRS (4 Tx slots)	Right Side	10mm	OFF	128	824.2	27.47	28.00	1.130	0.068	0.242	0.273	0.165	0.186
	GSM850	GPRS (4 Tx slots)	Bottom Side	10mm	OFF	128	824.2	27.47	28.00	1.130	-0.014	0.279	0.315	0.140	0.158
	GSM1900	GPRS (4 Tx slots)	Front	10mm	ON	810	1909.8	23.49	23.50	1.002	-0.03	0.516	0.517	0.259	0.260
	GSM1900	GPRS (4 Tx slots)	Back	10mm	ON	810	1909.8	23.49	23.50	1.002	0.04	0.969	0.971	0.490	0.491
18	GSM1900	GPRS (4 Tx slots)	Back	10mm	ON	512	1850.2	23.16	23.50	1.081	0.05	0.999	1.080	0.521	0.563
	GSM1900	GPRS (4 Tx slots)	Back	10mm	ON	661	1880	23.33	23.50	1.040	0.04	0.979	1.018	0.507	0.527
	GSM1900	GPRS (4 Tx slots)	Left Side	10mm	ON	810	1909.8	23.49	23.50	1.002	-0.17	0.019	0.019	0.010	0.010
	GSM1900	GPRS (4 Tx slots)	Right Side	10mm	ON	810	1909.8	23.49	23.50	1.002	-0.12	0.022	0.022	0.013	0.013
	GSM1900	GPRS (4 Tx slots)	Bottom Side	10mm	ON	810	1909.8	23.49	23.50	1.002	-0.01	0.744	0.746	0.355	0.356

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	10mm	ON	9400	1880	19.91	20.00	1.021	-0.09	0.353	0.360	0.176	0.180
	WCDMA II	RMC 12.2Kbps	Back	10mm	ON	9400	1880	19.91	20.00	1.021	-0.01	0.651	0.665	0.335	0.342
	WCDMA II	RMC 12.2Kbps	Left Side	10mm	ON	9400	1880	19.91	20.00	1.021	0.12	0.018	0.018	0.012	0.012
	WCDMA II	RMC 12.2Kbps	Right Side	10mm	ON	9400	1880	19.91	20.00	1.021	0.04	0.022	0.022	0.013	0.013
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	ON	9400	1880	19.91	20.00	1.021	-0.16	0.832	0.849	0.415	0.424
	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	ON	9262	1852.4	19.90	20.00	1.023	-0.11	0.777	0.795	0.392	0.401
19	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	ON	9538	1907.6	19.87	20.00	1.030	-0.07	0.911	0.939	0.451	0.465
	WCDMA IV	RMC 12.2Kbps	Front	10mm	ON	1413	1732.6	20.43	20.50	1.016	0.04	0.411	0.418	0.216	0.220
	WCDMA IV	RMC 12.2Kbps	Back	10mm	ON	1413	1732.6	20.43	20.50	1.016	0.09	0.648	0.659	0.347	0.353
	WCDMA IV	RMC 12.2Kbps	Left Side	10mm	ON	1413	1732.6	20.43	20.50	1.016	0.04	0.031	0.032	0.019	0.019
	WCDMA IV	RMC 12.2Kbps	Right Side	10mm	ON	1413	1732.6	20.43	20.50	1.016	-0.11	0.027	0.027	0.016	0.016
	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	ON	1413	1732.6	20.43	20.50	1.016	-0.11	0.855	0.869	0.439	0.446
	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	ON	1312	1712.4	20.39	20.50	1.026	-0.06	0.552	0.566	0.286	0.293
20	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	ON	1513	1752.6	20.40	20.50	1.023	-0.03	1.030	1.054	0.525	0.537
	WCDMA V	RMC 12.2Kbps	Front	10mm	OFF	4132	826.4	24.55	25.00	1.109	0.02	0.149	0.165	0.083	0.092
21	WCDMA V	RMC 12.2Kbps	Back	10mm	OFF	4132	826.4	24.55	25.00	1.109	0.01	0.317	0.352	0.183	0.203
	WCDMA V	RMC 12.2Kbps	Left Side	10mm	OFF	4132	826.4	24.55	25.00	1.109	0.01	0.064	0.071	0.044	0.049
	WCDMA V	RMC 12.2Kbps	Right Side	10mm	OFF	4132	826.4	24.55	25.00	1.109	-0.04	0.169	0.187	0.118	0.131
	WCDMA V	RMC 12.2Kbps	Bottom Side	10mm	OFF	4132	826.4	24.55	25.00	1.109	-0.07	0.180	0.200	0.090	0.100

**<LTE SAR>**

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
22	LTE Band 5	10M	QPSK	1	0	Front	10mm	OFF	20525	836.5	24.15	25.00	1.216	0.11	0.170	0.207	0.099	0.120
	LTE Band 5	10M	QPSK	25	0	Front	10mm	OFF	20525	836.5	23.19	24.00	1.205	-0.05	0.138	0.166	0.081	0.098
	LTE Band 5	10M	QPSK	1	0	Back	10mm	OFF	20525	836.5	24.15	25.00	1.216	0.01	0.374	0.455	0.220	0.268
	LTE Band 5	10M	QPSK	25	0	Back	10mm	OFF	20525	836.5	23.19	24.00	1.205	-0.02	0.316	0.381	0.184	0.222
	LTE Band 5	10M	QPSK	1	0	Left Side	10mm	OFF	20525	836.5	24.15	25.00	1.216	-0.04	0.092	0.112	0.064	0.078
	LTE Band 5	10M	QPSK	25	0	Left Side	10mm	OFF	20525	836.5	23.19	24.00	1.205	-0.05	0.075	0.090	0.052	0.063
	LTE Band 5	10M	QPSK	1	0	Right Side	10mm	OFF	20525	836.5	24.15	25.00	1.216	0.02	0.213	0.259	0.148	0.180
	LTE Band 5	10M	QPSK	25	0	Right Side	10mm	OFF	20525	836.5	23.19	24.00	1.205	-0.08	0.173	0.208	0.120	0.145
23	LTE Band 5	10M	QPSK	1	0	Bottom Side	10mm	OFF	20525	836.5	24.15	25.00	1.216	0.04	0.179	0.218	0.090	0.109
	LTE Band 5	10M	QPSK	25	0	Bottom Side	10mm	OFF	20525	836.5	23.19	24.00	1.205	-0.14	0.144	0.174	0.073	0.088
	LTE Band 7	20M	QPSK	1	99	Front	10mm	OFF	20850	2510	24.39	24.50	1.026	-0.04	0.223	0.229	0.116	0.119
	LTE Band 7	20M	QPSK	50	50	Front	10mm	OFF	20850	2510	23.38	23.50	1.028	0.04	0.182	0.187	0.094	0.097
	LTE Band 7	20M	QPSK	1	99	Back	10mm	OFF	20850	2510	24.39	24.50	1.026	0.05	0.340	0.349	0.153	0.157
	LTE Band 7	20M	QPSK	50	50	Back	10mm	OFF	20850	2510	23.38	23.50	1.028	-0.03	0.277	0.285	0.124	0.127
	LTE Band 7	20M	QPSK	1	99	Left Side	10mm	OFF	20850	2510	24.39	24.50	1.026	0.01	0.288	0.295	0.147	0.151
	LTE Band 7	20M	QPSK	50	50	Left Side	10mm	OFF	20850	2510	23.38	23.50	1.028	-0.01	0.239	0.246	0.122	0.125
24	LTE Band 7	20M	QPSK	1	99	Right Side	10mm	OFF	20850	2510	24.39	24.50	1.026	-0.06	0.074	0.076	0.043	0.044
	LTE Band 7	20M	QPSK	50	50	Right Side	10mm	OFF	20850	2510	23.38	23.50	1.028	-0.01	0.056	0.058	0.032	0.033
	LTE Band 7	20M	QPSK	1	99	Bottom Side	10mm	OFF	20850	2510	24.39	24.50	1.026	0.07	0.317	0.325	0.147	0.151
	LTE Band 7	20M	QPSK	50	50	Bottom Side	10mm	OFF	20850	2510	23.38	23.50	1.028	0	0.268	0.276	0.140	0.144
	LTE Band 12	10M	QPSK	1	0	Front	10mm	OFF	23095	707.5	23.59	24.50	1.233	-0.12	0.179	0.221	0.144	0.178
	LTE Band 12	10M	QPSK	25	0	Front	10mm	OFF	23095	707.5	22.62	23.50	1.225	0	0.147	0.180	0.119	0.146
	LTE Band 12	10M	QPSK	1	0	Back	10mm	OFF	23095	707.5	23.59	24.50	1.233	-0.07	0.275	0.339	0.211	0.260
	LTE Band 12	10M	QPSK	25	0	Back	10mm	OFF	23095	707.5	22.62	23.50	1.225	0.09	0.226	0.277	0.174	0.213
25	LTE Band 12	10M	QPSK	1	0	Left Side	10mm	OFF	23095	707.5	23.59	24.50	1.233	-0.01	0.202	0.249	0.145	0.179
	LTE Band 12	10M	QPSK	25	0	Left Side	10mm	OFF	23095	707.5	22.62	23.50	1.225	-0.08	0.163	0.200	0.117	0.143
	LTE Band 12	10M	QPSK	1	0	Right Side	10mm	OFF	23095	707.5	23.59	24.50	1.233	0	0.267	0.329	0.192	0.237
	LTE Band 12	10M	QPSK	25	0	Right Side	10mm	OFF	23095	707.5	22.62	23.50	1.225	-0.07	0.215	0.263	0.155	0.190
	LTE Band 12	10M	QPSK	1	0	Bottom Side	10mm	OFF	23095	707.5	23.59	24.50	1.233	0.09	0.076	0.094	0.040	0.049
	LTE Band 12	10M	QPSK	25	0	Bottom Side	10mm	OFF	23095	707.5	22.62	23.50	1.225	-0.13	0.061	0.075	0.032	0.039
	LTE Band 13	10M	QPSK	1	0	Front	10mm	OFF	23230	782	24.33	25.00	1.167	0.05	0.227	0.265	0.175	0.204
	LTE Band 13	10M	QPSK	25	0	Front	10mm	OFF	23230	782	23.46	24.00	1.132	0	0.187	0.212	0.145	0.164
26	LTE Band 13	10M	QPSK	1	0	Back	10mm	OFF	23230	782	24.33	25.00	1.167	0	0.302	0.352	0.186	0.217
	LTE Band 13	10M	QPSK	25	0	Back	10mm	OFF	23230	782	23.46	24.00	1.132	-0.07	0.251	0.284	0.153	0.173
	LTE Band 13	10M	QPSK	1	0	Left Side	10mm	OFF	23230	782	24.33	25.00	1.167	0	0.227	0.265	0.160	0.187
	LTE Band 13	10M	QPSK	25	0	Left Side	10mm	OFF	23230	782	23.46	24.00	1.132	-0.07	0.185	0.209	0.130	0.147
	LTE Band 13	10M	QPSK	1	0	Right Side	10mm	OFF	23230	782	24.33	25.00	1.167	-0.01	0.329	0.384	0.232	0.271
	LTE Band 13	10M	QPSK	25	0	Right Side	10mm	OFF	23230	782	23.46	24.00	1.132	-0.1	0.270	0.306	0.191	0.216
	LTE Band 13	10M	QPSK	1	0	Bottom Side	10mm	OFF	23230	782	24.33	25.00	1.167	0	0.100	0.117	0.052	0.061
	LTE Band 13	10M	QPSK	25	0	Bottom Side	10mm	OFF	23230	782	23.46	24.00	1.132	-0.02	0.084	0.095	0.044	0.050

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 25	20M	QPSK	1	0	Front	10mm	ON	26340	1880	19.51	20.00	1.119	-0.023	0.334	0.374	0.166	0.186
	LTE Band 25	20M	QPSK	50	0	Front	10mm	ON	26340	1880	19.61	20.00	1.094	0.072	0.287	0.314	0.147	0.161
	LTE Band 25	20M	QPSK	1	0	Back	10mm	ON	26340	1880	19.51	20.00	1.119	0.031	0.513	0.574	0.266	0.298
	LTE Band 25	20M	QPSK	50	0	Back	10mm	ON	26340	1880	19.61	20.00	1.094	0.05	0.513	0.561	0.265	0.290
	LTE Band 25	20M	QPSK	1	0	Left Side	10mm	ON	26340	1880	19.51	20.00	1.119	-0.137	0.018	0.020	0.011	0.012
	LTE Band 25	20M	QPSK	50	0	Left Side	10mm	ON	26340	1880	19.61	20.00	1.094	-0.007	0.018	0.020	0.011	0.012
	LTE Band 25	20M	QPSK	1	0	Right Side	10mm	ON	26340	1880	19.51	20.00	1.119	0.116	0.018	0.020	0.011	0.012
	LTE Band 25	20M	QPSK	50	0	Right Side	10mm	ON	26340	1880	19.61	20.00	1.094	0.049	0.018	0.020	0.012	0.013
	LTE Band 25	20M	QPSK	1	0	Bottom Side	10mm	ON	26340	1880	19.51	20.00	1.119	0.072	0.855	0.957	0.427	0.478
	LTE Band 25	20M	QPSK	1	0	Bottom Side	10mm	ON	26140	1860	19.45	20.00	1.135	0.092	0.711	0.807	0.359	0.407
26	LTE Band 25	20M	QPSK	1	0	Bottom Side	10mm	ON	26590	1905	19.50	20.00	1.122	0.13	1.000	1.122	0.501	0.562
	LTE Band 25	20M	QPSK	50	0	Bottom Side	10mm	ON	26340	1880	19.61	20.00	1.094	-0.057	0.734	0.803	0.368	0.403
	LTE Band 25	20M	QPSK	50	0	Bottom Side	10mm	ON	26140	1860	19.46	20.00	1.132	0.047	0.722	0.818	0.364	0.412
	LTE Band 25	20M	QPSK	50	0	Bottom Side	10mm	ON	26590	1905	19.60	20.00	1.096	0.035	0.777	0.852	0.388	0.425
	LTE Band 25	20M	QPSK	100	0	Bottom Side	10mm	ON	26340	1880	19.45	20.00	1.135	0.021	0.743	0.843	0.374	0.424
	LTE Band 66	20M	QPSK	1	0	Front	10mm	ON	132322	1745	19.66	20.00	1.081	0.01	0.386	0.417	0.204	0.221
	LTE Band 66	20M	QPSK	50	0	Front	10mm	ON	132322	1745	19.58	20.00	1.102	0.01	0.379	0.417	0.199	0.219
	LTE Band 66	20M	QPSK	1	0	Back	10mm	ON	132322	1745	19.66	20.00	1.081	-0.09	0.593	0.641	0.318	0.344
	LTE Band 66	20M	QPSK	50	0	Back	10mm	ON	132322	1745	19.58	20.00	1.102	-0.06	0.594	0.654	0.317	0.349
	LTE Band 66	20M	QPSK	1	0	Left Side	10mm	ON	132322	1745	19.66	20.00	1.081	-0.14	0.024	0.026	0.014	0.015
	LTE Band 66	20M	QPSK	50	0	Left Side	10mm	ON	132322	1745	19.58	20.00	1.102	0.08	0.023	0.025	0.013	0.014
	LTE Band 66	20M	QPSK	1	0	Right Side	10mm	ON	132322	1745	19.66	20.00	1.081	-0.01	0.030	0.032	0.018	0.019
	LTE Band 66	20M	QPSK	50	0	Right Side	10mm	ON	132322	1745	19.58	20.00	1.102	0.07	0.030	0.033	0.018	0.020
27	LTE Band 66	20M	QPSK	1	0	Bottom Side	10mm	ON	132322	1745	19.66	20.00	1.081	-0.02	0.722	0.781	0.373	0.403
	LTE Band 66	20M	QPSK	50	0	Bottom Side	10mm	ON	132322	1745	19.58	20.00	1.102	-0.06	0.700	0.771	0.362	0.399

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	11	2462	16.79	17.00	1.050	99.05	1.010	-0.16	0.067	0.071	0.032	0.034
28	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	11	2462	16.79	17.00	1.050	99.05	1.010	-0.07	0.150	0.159	0.063	0.067
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	11	2462	16.79	17.00	1.050	99.05	1.010	-0.14	0.053	0.056	0.026	0.028
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	11	2462	16.79	17.00	1.050	99.05	1.010	0.05	0.101	0.107	0.052	0.055

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	Bluetooth	1Mbps	Front	10mm	0	2402	11.30	11.50	1.047	77.07	1.081	0.185	0.012	0.014	0.006	0.007
29	Bluetooth	1Mbps	Back	10mm	0	2402	11.30	11.50	1.047	77.07	1.081	0.19	0.023	0.026	0.010	0.011
	Bluetooth	1Mbps	Right Side	10mm	0	2402	11.30	11.50	1.047	77.07	1.081	-0.1	0.008	0.009	0.004	0.004
	Bluetooth	1Mbps	Top Side	10mm	0	2402	11.30	11.50	1.047	77.07	1.081	0.124	0.016	0.018	0.008	0.009

13.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Front	15mm	OFF	128	824.2	27.47	28.00	1.130	0.175	0.181	0.204	0.139	0.157
30	GSM850	GPRS (4 Tx slots)	Back	15mm	OFF	128	824.2	27.47	28.00	1.130	0.06	0.288	0.325	0.218	0.246
	GSM1900	GPRS (4 Tx slots)	Front	15mm	OFF	810	1909.8	24.94	25.00	1.014	-0.02	0.223	0.226	0.122	0.124
31	GSM1900	GPRS (4 Tx slots)	Back	15mm	OFF	810	1909.8	24.94	25.00	1.014	0.04	0.446	0.452	0.242	0.245

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	15mm	ON	9538	1907.6	22.49	22.50	1.002	0.07	0.312	0.313	0.168	0.168
32	WCDMA II	RMC 12.2Kbps	Back	15mm	ON	9538	1907.6	22.49	22.50	1.002	0.09	0.596	0.597	0.325	0.326
	WCDMA IV	RMC 12.2Kbps	Front	15mm	ON	1413	1732.6	22.43	22.50	1.016	0.06	0.313	0.318	0.182	0.185
33	WCDMA IV	RMC 12.2Kbps	Back	15mm	ON	1413	1732.6	22.43	22.50	1.016	0.01	0.586	0.596	0.337	0.342
	WCDMA V	RMC 12.2Kbps	Front	15mm	OFF	4132	826.4	24.55	25.00	1.109	0.01	0.120	0.133	0.093	0.103
34	WCDMA V	RMC 12.2Kbps	Back	15mm	OFF	4132	826.4	24.55	25.00	1.109	-0.01	0.191	0.212	0.145	0.161

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 5	10M	QPSK	1	0	Front	15mm	OFF	20525	836.5	24.15	25.00	1.216	-0.05	0.149	0.181	0.115	0.140
	LTE Band 5	10M	QPSK	25	0	Front	15mm	OFF	20525	836.5	23.19	24.00	1.205	0	0.118	0.142	0.091	0.110
35	LTE Band 5	10M	QPSK	1	0	Back	15mm	OFF	20525	836.5	24.15	25.00	1.216	0.01	0.236	0.287	0.179	0.218
	LTE Band 5	10M	QPSK	25	0	Back	15mm	OFF	20525	836.5	23.19	24.00	1.205	-0.03	0.190	0.229	0.144	0.174
36	LTE Band 7	20M	QPSK	1	99	Front	15mm	OFF	20850	2510	24.39	24.50	1.026	0.02	0.128	0.131	0.074	0.076
	LTE Band 7	20M	QPSK	50	50	Front	15mm	OFF	20850	2510	23.38	23.50	1.028	0.01	0.105	0.108	0.061	0.063
	LTE Band 7	20M	QPSK	1	99	Back	15mm	OFF	20850	2510	24.39	24.50	1.026	0.05	0.121	0.124	0.058	0.059
	LTE Band 7	20M	QPSK	50	50	Back	15mm	OFF	20850	2510	23.38	23.50	1.028	0.02	0.097	0.100	0.046	0.047
	LTE Band 12	10M	QPSK	1	0	Front	15mm	OFF	23095	707.5	23.59	24.50	1.233	-0.08	0.206	0.254	0.165	0.203
	LTE Band 12	10M	QPSK	25	0	Front	15mm	OFF	23095	707.5	22.62	23.50	1.225	0.02	0.171	0.209	0.137	0.168
37	LTE Band 12	10M	QPSK	1	0	Back	15mm	OFF	23095	707.5	23.59	24.50	1.233	0.01	0.276	0.340	0.218	0.269
	LTE Band 12	10M	QPSK	25	0	Back	15mm	OFF	23095	707.5	22.62	23.50	1.225	0.13	0.229	0.280	0.180	0.220
	LTE Band 13	10M	QPSK	1	0	Front	15mm	OFF	23230	782	24.33	25.00	1.167	0.04	0.247	0.288	0.195	0.228
	LTE Band 13	10M	QPSK	25	0	Front	15mm	OFF	23230	782	23.46	24.00	1.132	-0.01	0.204	0.231	0.160	0.181
38	LTE Band 13	10M	QPSK	1	0	Back	15mm	OFF	23230	782	24.33	25.00	1.167	0.01	0.351	0.410	0.271	0.316
	LTE Band 13	10M	QPSK	25	0	Back	15mm	OFF	23230	782	23.46	24.00	1.132	-0.04	0.289	0.327	0.224	0.254
	LTE Band 25	20M	QPSK	1	0	Front	15mm	ON	26140	1860	22.03	22.50	1.114	0.009	0.270	0.301	0.148	0.165
	LTE Band 25	20M	QPSK	50	0	Front	15mm	ON	26140	1860	22.07	22.50	1.104	0	0.273	0.301	0.149	0.165
	LTE Band 25	20M	QPSK	1	0	Back	15mm	ON	26140	1860	22.03	22.50	1.114	0.033	0.504	0.562	0.275	0.306
39	LTE Band 25	20M	QPSK	50	0	Back	15mm	ON	26140	1860	22.07	22.50	1.104	-0.02	0.510	0.563	0.279	0.308
	LTE Band 66	20M	QPSK	1	0	Front	15mm	ON	132322	1745	22.12	22.50	1.091	0.03	0.336	0.367	0.192	0.210
	LTE Band 66	20M	QPSK	50	0	Front	15mm	ON	132322	1745	22.05	22.50	1.109	0.01	0.386	0.428	0.182	0.202
	LTE Band 66	20M	QPSK	1	0	Back	15mm	ON	132322	1745	22.12	22.50	1.091	-0.07	0.563	0.614	0.324	0.354
40	LTE Band 66	20M	QPSK	50	0	Back	15mm	ON	132322	1745	22.05	22.50	1.109	-0.03	0.565	0.627	0.323	0.358

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	15mm	11	2462	16.79	17.00	1.050	99.05	1.010	0.18	0.030	0.032	0.013	0.014
41	WLAN2.4GHz	802.11b 1Mbps	Back	15mm	11	2462	16.79	17.00	1.050	99.05	1.010	0.01	0.054	0.057	0.022	0.023
42	WLAN5GHz	802.11a 6Mbps	Front	15mm	64	5320	15.41	15.50	1.022	94.95	1.053	-0.03	0.027	0.029	0.006	0.007
	WLAN5GHz	802.11a 6Mbps	Back	15mm	64	5320	15.41	15.50	1.022	94.95	1.053	0.08	0.015	0.016	0.005	0.005
43	WLAN5GHz	802.11a 6Mbps	Front	15mm	100	5500	15.49	15.50	1.003	94.95	1.053	0.16	0.025	0.026	0.009	0.009
	WLAN5GHz	802.11a 6Mbps	Back	15mm	100	5500	15.49	15.50	1.003	94.95	1.053	0.13	0.011	0.012	0.004	0.004
44	WLAN5GHz	802.11a 6Mbps	Front	15mm	149	5745	15.46	15.50	1.010	94.95	1.053	-0.11	0.068	0.072	0.022	0.023
	WLAN5GHz	802.11a 6Mbps	Back	15mm	149	5745	15.46	15.50	1.010	94.95	1.053	-0.16	0.010	0.011	0.003	0.004

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	Bluetooth	1Mbps	Front	15mm	0	2402	11.30	11.50	1.047	77.07	1.081	0.108	0.006	0.006	0.003	0.004
45	Bluetooth	1Mbps	Back	15mm	0	2402	11.30	11.50	1.047	77.07	1.081	-0.17	0.009	0.010	0.005	0.006

13.4 Product Specific SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	GSM1900	GPRS (4 Tx slots)	Front	0mm	OFF	810	1909.8	24.94	25.00	1.014	0.18	1.500	1.521
	GSM1900	GPRS (4 Tx slots)	Back	0mm	OFF	810	1909.8	24.94	25.00	1.014	0.03	2.110	2.139
46	GSM1900	GPRS (4 Tx slots)	Back	0mm	OFF	512	1850.2	24.87	25.00	1.030	0.08	2.130	2.195
	GSM1900	GPRS (4 Tx slots)	Back	0mm	OFF	661	1880	24.85	25.00	1.035	0.02	2.100	2.174
	GSM1900	GPRS (4 Tx slots)	Bottom Side	0mm	OFF	810	1909.8	24.94	25.00	1.014	0.18	0.485	0.492

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	0mm	ON	9538	1907.6	22.49	22.50	1.002	-0.17	2.390	2.396
	WCDMA II	RMC 12.2Kbps	Front	0mm	ON	9262	1852.4	22.23	22.50	1.064	-0.12	2.280	2.426
	WCDMA II	RMC 12.2Kbps	Front	0mm	ON	9400	1880	22.43	22.50	1.016	-0.06	2.340	2.378
	WCDMA II	RMC 12.2Kbps	Back	0mm	ON	9538	1907.6	22.49	22.50	1.002	-0.01	2.660	2.666
47	WCDMA II	RMC 12.2Kbps	Back	0mm	ON	9262	1852.4	22.23	22.50	1.064	-0.05	2.770	2.948
	WCDMA II	RMC 12.2Kbps	Back	0mm	ON	9400	1880	22.43	22.50	1.016	-0.04	2.750	2.795
	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	ON	9538	1907.6	22.49	22.50	1.002	0.16	0.774	0.776
	WCDMA IV	RMC 12.2Kbps	Front	0mm	ON	1513	1752.6	22.37	22.50	1.030	-0.08	2.400	2.473
	WCDMA IV	RMC 12.2Kbps	Front	0mm	ON	1312	1712.4	22.36	22.50	1.033	0.03	2.460	2.541
	WCDMA IV	RMC 12.2Kbps	Front	0mm	ON	1413	1732.6	22.43	22.50	1.016	0.04	2.520	2.561
	WCDMA IV	RMC 12.2Kbps	Back	0mm	ON	1513	1752.6	22.37	22.50	1.030	-0.08	2.500	2.576
48	WCDMA IV	RMC 12.2Kbps	Back	0mm	ON	1312	1712.4	22.36	22.50	1.033	-0.16	2.590	2.675
	WCDMA IV	RMC 12.2Kbps	Back	0mm	ON	1413	1732.6	22.43	22.50	1.016	-0.17	2.550	2.591
	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	ON	1413	1732.6	22.43	22.50	1.016	0.04	0.920	0.935

<LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 25	20M	QPSK	1	0	Front	0mm	ON	26140	1860	22.03	22.50	1.114	0.009	1.980	2.206
49	LTE Band 25	20M	QPSK	1	0	Front	0mm	ON	26340	1880	21.95	22.50	1.135	-0.04	2.530	2.872
	LTE Band 25	20M	QPSK	1	0	Front	0mm	ON	26590	1905	21.94	22.50	1.138	0.017	2.090	2.378
	LTE Band 25	20M	QPSK	1	0	Back	0mm	ON	26140	1860	22.03	22.50	1.114	-0.015	2.230	2.485
	LTE Band 25	20M	QPSK	1	0	Back	0mm	ON	26340	1880	21.95	22.50	1.135	0	2.200	2.497
	LTE Band 25	20M	QPSK	1	0	Back	0mm	ON	26590	1905	21.94	22.50	1.138	0.023	2.160	2.457
	LTE Band 25	20M	QPSK	1	0	Bottom side	0mm	ON	26140	1860	22.03	22.50	1.114	0.049	1.260	1.404
	LTE Band 66	20M	QPSK	1	0	Front	0mm	ON	132322	1745	22.12	22.50	1.091	0.18	2.300	2.510
	LTE Band 66	20M	QPSK	1	0	Front	0mm	ON	132072	1720	21.95	22.50	1.135	0.09	2.150	2.440
	LTE Band 66	20M	QPSK	1	0	Front	0mm	ON	132572	1770	22.10	22.50	1.096	0.02	2.190	2.401
	LTE Band 66	20M	QPSK	1	0	Back	0mm	ON	132322	1745	22.12	22.50	1.091	0.03	2.360	2.576
50	LTE Band 66	20M	QPSK	1	0	Back	0mm	ON	132072	1720	21.95	22.50	1.135	0.03	2.380	2.701
	LTE Band 66	20M	QPSK	1	0	Back	0mm	ON	132572	1770	22.10	22.50	1.096	0.08	2.320	2.544
	LTE Band 66	20M	QPSK	1	0	Bottom Side	0mm	ON	132322	1745	22.12	22.50	1.091	-0.14	0.872	0.952

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
51	WLAN5GHz	802.11a 6Mbps	Front	0mm	64	5320	15.41	15.50	1.022	94.95	1.053	-0.03	0.335	0.361
	WLAN5GHz	802.11a 6Mbps	Back	0mm	64	5320	15.41	15.50	1.022	94.95	1.053	0.16	0.149	0.160
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	64	5320	15.41	15.50	1.022	94.95	1.053	-0.02	0.006	0.007
	WLAN5GHz	802.11a 6Mbps	Top Side	0mm	64	5320	15.41	15.50	1.022	94.95	1.053	0.08	0.197	0.212
52	WLAN5GHz	802.11a 6Mbps	Front	0mm	100	5500	15.49	15.50	1.003	94.95	1.053	-0.18	0.215	0.227
	WLAN5GHz	802.11a 6Mbps	Back	0mm	100	5500	15.49	15.50	1.003	94.95	1.053	0.13	0.080	0.085
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	100	5500	15.49	15.50	1.003	94.95	1.053	-0.19	0.001	0.001
	WLAN5GHz	802.11a 6Mbps	Top Side	0mm	100	5500	15.49	15.50	1.003	94.95	1.053	0.11	0.142	0.150
	WLAN5GHz	802.11a 6Mbps	Front	0mm	149	5745	15.46	15.50	1.010	94.95	1.053	-0.01	0.258	0.275
	WLAN5GHz	802.11a 6Mbps	Back	0mm	149	5745	15.46	15.50	1.010	94.95	1.053	-0.11	0.135	0.144
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	149	5745	15.46	15.50	1.010	94.95	1.053	0.08	0.007	0.007
53	WLAN5GHz	802.11a 6Mbps	Top Side	0mm	149	5745	15.46	15.50	1.010	94.95	1.053	-0.18	0.265	0.282

13.5 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	-	165	5825	15.39	15.50	1.027	94.95	1.053	0	0.853	-	0.922
2nd	WLAN5GHz	802.11a 6Mbps	Left Tilted	0mm	-	165	5825	15.39	15.50	1.027	94.95	1.053	-0.1	0.851	1.00	0.920
1st	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	ON	1513	1752.6	20.40	20.50	1.023	-	1.000	-0.03	1.030	-	1.054
2nd	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	ON	1513	1752.6	20.40	20.50	1.023	-	1.000	-0.02	1.010	1.02	1.034
1st	LTE Band 25	20M_QPSK_1_0	Bottom Side	10mm	ON	26590	1905	19.50	20.00	1.122	-	1.000	0.13	1.000	-	1.122
2nd	LTE Band 25	20M_QPSK_1_0	Bottom side	10mm	ON	26590	1905	19.50	20.00	1.122	-	1.000	0.07	0.877	1.14	0.984

No.	Band	Mode	Test Position	Gap (mm)	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Ratio	Reported 10g SAR (W/kg)
1st	WCDMA II	RMC 12.2Kbps	Back	0mm	ON	9262	1852.4	22.23	22.50	1.064	-0.05	2.770	-	2.948
2nd	WCDMA II	RMC 12.2Kbps	Back	0mm	ON	9262	1852.4	22.23	22.50	1.064	0	2.720	1.02	2.894
1st	WCDMA IV	RMC 12.2Kbps	Back	0mm	ON	1312	1712.4	22.36	22.50	1.033	-0.16	2.590	-	2.675
2nd	WCDMA IV	RMC 12.2Kbps	Back	0mm	ON	1312	1712.4	22.36	22.50	1.033	0.01	2.530	1.02	2.613

General Note:

- Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
- Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.
- Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
- The ratio is the difference in percentage between original and repeated *measured SAR*.
- All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

14. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset			
		Head	Body-worn	Hotspot	Product Specific
1.	GSM Voice + 2.4GHz WLAN	Yes	Yes		Yes
2.	GPRS/EDGE + 2.4GHz WLAN	Yes	Yes	Yes	Yes
3.	WCDMA + 2.4GHz WLAN	Yes	Yes	Yes	Yes
4.	LTE + 2.4GHz WLAN	Yes	Yes	Yes	Yes
5.	GSM Voice + Bluetooth	Yes	Yes		Yes
6.	GPRS/EDGE + Bluetooth	Yes	Yes	Yes	Yes
7.	WCDMA + Bluetooth	Yes	Yes	Yes	Yes
8.	LTE + Bluetooth	Yes	Yes	Yes	Yes
9.	GSM Voice + 5GHz WLAN	Yes	Yes		Yes
10.	GPRS/EDGE + 5GHz WLAN	Yes	Yes		Yes
11.	WCDMA + 5GHz WLAN	Yes	Yes		Yes
12.	LTE + 5GHz WLAN	Yes	Yes		Yes

General Note:

1. In this report, the 10g SAR results which is submitted voluntarily.
2. This device WLAN 2.4GHz supports Hotspot operation and Bluetooth support tethering applications.
3. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
4. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
5. The Scaled SAR summation is calculated based on the same configuration and test position.
6. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation $< 1.6\text{W/kg}$.
 - ii) $\text{SPLSR} = (\text{SAR1} + \text{SAR2})^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where $(x1, y1, z1)$ and $(x2, y2, z2)$ are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR $< 1.6\text{W/kg}$.

14.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
GSM	GSM850	Right Cheek	0.225	0.206	0.625	0.041	0.43	0.85	0.27
		Right Tilted	0.112	0.155	0.676	0.035	0.27	0.79	0.15
		Left Cheek	0.176	0.607	0.884	0.095	0.78	1.06	0.27
		Left Tilted	0.115	0.401	0.922	0.072	0.52	1.04	0.19
	GSM1900	Right Cheek	0.021	0.206	0.625	0.041	0.23	0.65	0.06
		Right Tilted	0.007	0.155	0.676	0.035	0.16	0.68	0.04
		Left Cheek	0.017	0.607	0.884	0.095	0.62	0.90	0.11
		Left Tilted	0.015	0.401	0.922	0.072	0.42	0.94	0.09
WCDMA	WCDMA II	Right Cheek	0.061	0.206	0.625	0.041	0.27	0.69	0.10
		Right Tilted	0.028	0.155	0.676	0.035	0.18	0.70	0.06
		Left Cheek	0.042	0.607	0.884	0.095	0.65	0.93	0.14
		Left Tilted	0.032	0.401	0.922	0.072	0.43	0.95	0.10
	WCDMA IV	Right Cheek	0.070	0.206	0.625	0.041	0.28	0.70	0.11
		Right Tilted	0.015	0.155	0.676	0.035	0.17	0.69	0.05
		Left Cheek	0.051	0.607	0.884	0.095	0.66	0.94	0.15
		Left Tilted	0.020	0.401	0.922	0.072	0.42	0.94	0.09
	WCDMA V	Right Cheek	0.152	0.206	0.625	0.041	0.36	0.78	0.19
		Right Tilted	0.071	0.155	0.676	0.035	0.23	0.75	0.11
		Left Cheek	0.130	0.607	0.884	0.095	0.74	1.01	0.23
		Left Tilted	0.084	0.401	0.922	0.072	0.49	1.01	0.16
LTE	LTE Band 5	Right Cheek	0.147	0.206	0.625	0.041	0.35	0.77	0.19
		Right Tilted	0.088	0.155	0.676	0.035	0.24	0.76	0.12
		Left Cheek	0.167	0.607	0.884	0.095	0.77	1.05	0.26
		Left Tilted	0.105	0.401	0.922	0.072	0.51	1.03	0.18
	LTE Band 7	Right Cheek	0.110	0.206	0.625	0.041	0.32	0.74	0.15
		Right Tilted	0.122	0.155	0.676	0.035	0.28	0.80	0.16
		Left Cheek	0.115	0.607	0.884	0.095	0.72	1.00	0.21
		Left Tilted	0.046	0.401	0.922	0.072	0.45	0.97	0.12
	LTE Band 12	Right Cheek	0.186	0.206	0.625	0.041	0.39	0.81	0.23
		Right Tilted	0.095	0.155	0.676	0.035	0.25	0.77	0.13
		Left Cheek	0.149	0.607	0.884	0.095	0.76	1.03	0.24
		Left Tilted	0.120	0.401	0.922	0.072	0.52	1.04	0.19
	LTE Band 13	Right Cheek	0.198	0.206	0.625	0.041	0.40	0.82	0.24
		Right Tilted	0.107	0.155	0.676	0.035	0.26	0.78	0.14
		Left Cheek	0.174	0.607	0.884	0.095	0.78	1.06	0.27
		Left Tilted	0.121	0.401	0.922	0.072	0.52	1.04	0.19
	LTE Band 25	Right Cheek	0.059	0.206	0.625	0.041	0.27	0.68	0.10
		Right Tilted	0.041	0.155	0.676	0.035	0.20	0.72	0.08
		Left Cheek	0.041	0.607	0.884	0.095	0.65	0.93	0.14
		Left Tilted	0.024	0.401	0.922	0.072	0.43	0.95	0.10
	LTE Band 66	Right Cheek	0.114	0.206	0.625	0.041	0.32	0.74	0.16
		Right Tilted	0.049	0.155	0.676	0.035	0.20	0.73	0.08
		Left Cheek	0.052	0.607	0.884	0.095	0.66	0.94	0.15
		Left Tilted	0.037	0.401	0.922	0.072	0.44	0.96	0.11

WWAN Band		Exposure Position	1	2	3	4	1+2	1+3	1+4
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth	Summed 10g SAR (W/kg)	Summed 10g SAR (W/kg)	Summed 10g SAR (W/kg)
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)			
GSM	GSM850	Right Cheek	0.181	0.100	0.207	0.017	0.281	0.388	0.198
		Right Tilted	0.045	0.076	0.224	0.016	0.121	0.269	0.061
		Left Cheek	0.136	0.275	0.266	0.040	0.411	0.402	0.176
		Left Tilted	0.087	0.202	0.278	0.033	0.289	0.365	0.120
	GSM1900	Right Cheek	0.013	0.100	0.207	0.017	0.113	0.220	0.030
		Right Tilted	0.002	0.076	0.224	0.016	0.078	0.226	0.018
		Left Cheek	0.010	0.275	0.266	0.040	0.285	0.276	0.050
		Left Tilted	0.009	0.202	0.278	0.033	0.211	0.287	0.042
WCDMA	WCDMA II	Right Cheek	0.040	0.100	0.207	0.017	0.140	0.247	0.057
		Right Tilted	0.016	0.076	0.224	0.016	0.092	0.240	0.032
		Left Cheek	0.026	0.275	0.266	0.040	0.301	0.292	0.066
		Left Tilted	0.018	0.202	0.278	0.033	0.220	0.296	0.051
	WCDMA IV	Right Cheek	0.045	0.100	0.207	0.017	0.145	0.252	0.062
		Right Tilted	0.010	0.076	0.224	0.016	0.086	0.234	0.026
		Left Cheek	0.032	0.275	0.266	0.040	0.307	0.298	0.072
		Left Tilted	0.011	0.202	0.278	0.033	0.213	0.289	0.044
	WCDMA V	Right Cheek	0.118	0.100	0.207	0.017	0.218	0.325	0.135
		Right Tilted	0.055	0.076	0.224	0.016	0.131	0.279	0.071
		Left Cheek	0.099	0.275	0.266	0.040	0.374	0.365	0.139
		Left Tilted	0.063	0.202	0.278	0.033	0.265	0.341	0.096
LTE	LTE Band 5	Right Cheek	0.112	0.100	0.207	0.017	0.212	0.319	0.129
		Right Tilted	0.067	0.076	0.224	0.016	0.143	0.291	0.083
		Left Cheek	0.128	0.275	0.266	0.040	0.403	0.394	0.168
		Left Tilted	0.078	0.202	0.278	0.033	0.280	0.356	0.111
	LTE Band 7	Right Cheek	0.065	0.100	0.207	0.017	0.165	0.272	0.082
		Right Tilted	0.068	0.076	0.224	0.016	0.144	0.292	0.084
		Left Cheek	0.064	0.275	0.266	0.040	0.339	0.330	0.104
		Left Tilted	0.025	0.202	0.278	0.033	0.227	0.303	0.058
	LTE Band 12	Right Cheek	0.148	0.100	0.207	0.017	0.248	0.355	0.165
		Right Tilted	0.078	0.076	0.224	0.016	0.154	0.302	0.094
		Left Cheek	0.122	0.275	0.266	0.040	0.397	0.388	0.162
		Left Tilted	0.101	0.202	0.278	0.033	0.303	0.379	0.134
	LTE Band 13	Right Cheek	0.156	0.100	0.207	0.017	0.256	0.363	0.173
		Right Tilted	0.086	0.076	0.224	0.016	0.162	0.310	0.102
		Left Cheek	0.139	0.275	0.266	0.040	0.414	0.405	0.179
		Left Tilted	0.093	0.202	0.278	0.033	0.295	0.371	0.126
	LTE Band 25	Right Cheek	0.037	0.100	0.207	0.017	0.137	0.244	0.054
		Right Tilted	0.023	0.076	0.224	0.016	0.099	0.247	0.039
		Left Cheek	0.024	0.275	0.266	0.040	0.299	0.290	0.064
		Left Tilted	0.014	0.202	0.278	0.033	0.216	0.292	0.047
	LTE Band 66	Right Cheek	0.072	0.100	0.207	0.017	0.172	0.279	0.089
		Right Tilted	0.029	0.076	0.224	0.016	0.105	0.253	0.045
		Left Cheek	0.036	0.275	0.266	0.040	0.311	0.302	0.076
		Left Tilted	0.022	0.202	0.278	0.033	0.224	0.300	0.055

14.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	4	1+2 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	Bluetooth		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM	GSM850	Front	0.261	0.071	0.014	0.33	0.28
		Back	0.583	0.159	0.026	0.74	0.61
		Left side	0.096			0.10	0.10
		Right side	0.273	0.056	0.009	0.33	0.28
		Top side		0.107	0.018	0.11	0.02
		Bottom side	0.315			0.32	0.32
	GSM1900	Front	0.517	0.071	0.014	0.59	0.53
		Back	1.080	0.159	0.026	1.24	1.11
		Left side	0.019			0.02	0.02
		Right side	0.022	0.056	0.009	0.08	0.03
		Top side		0.107	0.018	0.11	0.02
		Bottom side	0.746			0.75	0.75
WCDMA	WCDMA II	Front	0.360	0.071	0.014	0.43	0.37
		Back	0.665	0.159	0.026	0.82	0.69
		Left side	0.018			0.02	0.02
		Right side	0.022	0.056	0.009	0.08	0.03
		Top side		0.107	0.018	0.11	0.02
		Bottom side	0.939			0.94	0.94
	WCDMA IV	Front	0.418	0.071	0.014	0.49	0.43
		Back	0.659	0.159	0.026	0.82	0.69
		Left side	0.032			0.03	0.03
		Right side	0.027	0.056	0.009	0.08	0.04
		Top side		0.107	0.018	0.11	0.02
		Bottom side	1.054			1.05	1.05
	WCDMA V	Front	0.165	0.071	0.014	0.24	0.18
		Back	0.352	0.159	0.026	0.51	0.38
		Left side	0.071			0.07	0.07
		Right side	0.187	0.056	0.009	0.24	0.20
		Top side		0.107	0.018	0.11	0.02
		Bottom side	0.200			0.20	0.20

WWAN Band		Exposure Position	1	2	4	1+2 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	Bluetooth		
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
LTE	LTE Band 5	Front	0.207	0.071	0.014	0.28	0.22
		Back	0.455	0.159	0.026	0.61	0.48
		Left side	0.112			0.11	0.11
		Right side	0.259	0.056	0.009	0.32	0.27
		Top side		0.107	0.018	0.11	0.02
		Bottom side	0.218			0.22	0.22
	LTE Band 7	Front	0.229	0.071	0.014	0.30	0.24
		Back	0.349	0.159	0.026	0.51	0.38
		Left side	0.295			0.30	0.30
		Right side	0.076	0.056	0.009	0.13	0.09
		Top side		0.107	0.018	0.11	0.02
		Bottom side	0.325			0.33	0.33
	LTE Band 12	Front	0.221	0.071	0.014	0.29	0.24
		Back	0.339	0.159	0.026	0.50	0.37
		Left side	0.249			0.25	0.25
		Right side	0.329	0.056	0.009	0.39	0.34
		Top side		0.107	0.018	0.11	0.02
		Bottom side	0.094			0.09	0.09
	LTE Band 13	Front	0.265	0.071	0.014	0.34	0.28
		Back	0.352	0.159	0.026	0.51	0.38
		Left side	0.265			0.27	0.27
		Right side	0.384	0.056	0.009	0.44	0.39
		Top side		0.107	0.018	0.11	0.02
		Bottom side	0.117			0.12	0.12
	LTE Band 25	Front	0.374	0.071	0.014	0.45	0.39
		Back	0.574	0.159	0.026	0.73	0.60
		Left side	0.020			0.02	0.02
		Right side	0.020	0.056	0.009	0.08	0.03
		Top side		0.107	0.018	0.11	0.02
		Bottom side	1.122			1.12	1.12
	LTE Band 66	Front	0.417	0.071	0.014	0.49	0.43
		Back	0.654	0.159	0.026	0.81	0.68
		Left side	0.026			0.03	0.03
		Right side	0.033	0.056	0.009	0.09	0.04
		Top side		0.107	0.018	0.11	0.02
		Bottom side	0.781			0.78	0.78

WWAN Band		Exposure Position	1	2	4	1+2 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WLAN	Bluetooth		
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)		
GSM	GSM850	Front	0.154	0.034	0.007	0.188	0.161
		Back	0.337	0.067	0.011	0.404	0.348
		Left side	0.067			0.067	0.067
		Right side	0.186	0.028	0.004	0.214	0.190
		Top side		0.055	0.009	0.055	0.009
		Bottom side	0.158			0.158	0.158
	GSM1900	Front	0.260	0.034	0.007	0.294	0.267
		Back	0.563	0.067	0.011	0.630	0.574
		Left side	0.010			0.010	0.010
		Right side	0.013	0.028	0.004	0.041	0.017
		Top side		0.055	0.009	0.055	0.009
		Bottom side	0.356			0.356	0.356
WCDMA	WCDMA II	Front	0.180	0.034	0.007	0.214	0.187
		Back	0.342	0.067	0.011	0.409	0.353
		Left side	0.012			0.012	0.012
		Right side	0.013	0.028	0.004	0.041	0.017
		Top side		0.055	0.009	0.055	0.009
		Bottom side	0.465			0.465	0.465
	WCDMA IV	Front	0.220	0.034	0.007	0.254	0.227
		Back	0.353	0.067	0.011	0.420	0.364
		Left side	0.019			0.019	0.019
		Right side	0.016	0.028	0.004	0.044	0.020
		Top side		0.055	0.009	0.055	0.009
		Bottom side	0.537			0.537	0.537
	WCDMA V	Front	0.092	0.034	0.007	0.126	0.099
		Back	0.203	0.067	0.011	0.270	0.214
		Left side	0.049			0.049	0.049
		Right side	0.131	0.028	0.004	0.159	0.135
		Top side		0.055	0.009	0.055	0.009
		Bottom side	0.100			0.100	0.100

WWAN Band		Exposure Position	1	2	4	1+2 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WLAN	Bluetooth		
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)		
LTE	LTE Band 5	Front	0.120	0.034	0.007	0.154	0.127
		Back	0.268	0.067	0.011	0.335	0.279
		Left side	0.078			0.078	0.078
		Right side	0.180	0.028	0.004	0.208	0.184
		Top side		0.055	0.009	0.055	0.009
		Bottom side	0.109			0.109	0.109
	LTE Band 7	Front	0.119	0.034	0.007	0.153	0.126
		Back	0.157	0.067	0.011	0.224	0.168
		Left side	0.151			0.151	0.151
		Right side	0.044	0.028	0.004	0.072	0.048
		Top side		0.055	0.009	0.055	0.009
		Bottom side	0.151			0.151	0.151
	LTE Band 12	Front	0.178	0.034	0.007	0.212	0.185
		Back	0.260	0.067	0.011	0.327	0.271
		Left side	0.179			0.179	0.179
		Right side	0.237	0.028	0.004	0.265	0.241
		Top side		0.055	0.009	0.055	0.009
		Bottom side	0.049			0.049	0.049
	LTE Band 13	Front	0.204	0.034	0.007	0.238	0.211
		Back	0.217	0.067	0.011	0.284	0.228
		Left side	0.187			0.187	0.187
		Right side	0.271	0.028	0.004	0.299	0.275
		Top side		0.055	0.009	0.055	0.009
		Bottom side	0.061			0.061	0.061
	LTE Band 25	Front	0.186	0.034	0.007	0.220	0.193
		Back	0.298	0.067	0.011	0.365	0.309
		Left side	0.012			0.012	0.012
		Right side	0.013	0.028	0.004	0.041	0.017
		Top side		0.055	0.009	0.055	0.009
		Bottom side	0.562			0.562	0.562
	LTE Band 66	Front	0.221	0.034	0.007	0.255	0.228
		Back	0.349	0.067	0.011	0.416	0.360
		Left side	0.015			0.015	0.015
		Right side	0.020	0.028	0.004	0.048	0.024
		Top side		0.055	0.009	0.055	0.009
		Bottom side	0.403			0.403	0.403

14.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
GSM	GSM850	Front	0.204	0.032	0.072	0.006	0.24	0.28	0.21
		Back	0.325	0.057	0.016	0.010	0.38	0.34	0.34
	GSM1900	Front	0.226	0.032	0.072	0.006	0.26	0.30	0.23
		Back	0.452	0.057	0.016	0.010	0.51	0.47	0.46
WCDMA	WCDMA II	Front	0.313	0.032	0.072	0.006	0.35	0.39	0.32
		Back	0.597	0.057	0.016	0.010	0.65	0.61	0.61
	WCDMA IV	Front	0.318	0.032	0.072	0.006	0.35	0.39	0.32
		Back	0.596	0.057	0.016	0.010	0.65	0.61	0.61
	WCDMA V	Front	0.133	0.032	0.072	0.006	0.17	0.21	0.14
		Back	0.212	0.057	0.016	0.010	0.27	0.23	0.22
LTE	LTE Band 5	Front	0.181	0.032	0.072	0.006	0.21	0.25	0.19
		Back	0.287	0.057	0.016	0.010	0.34	0.30	0.30
	LTE Band 7	Front	0.131	0.032	0.072	0.006	0.16	0.20	0.14
		Back	0.124	0.057	0.016	0.010	0.18	0.14	0.13
	LTE Band 12	Front	0.254	0.032	0.072	0.006	0.29	0.33	0.26
		Back	0.340	0.057	0.016	0.010	0.40	0.36	0.35
	LTE Band 13	Front	0.288	0.032	0.072	0.006	0.32	0.36	0.29
		Back	0.410	0.057	0.016	0.010	0.47	0.43	0.42
	LTE Band 25	Front	0.301	0.032	0.072	0.006	0.33	0.37	0.31
		Back	0.563	0.057	0.016	0.010	0.62	0.58	0.57
	LTE Band 66	Front	0.428	0.032	0.072	0.006	0.46	0.50	0.43
		Back	0.627	0.057	0.016	0.010	0.68	0.64	0.64

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)			
GSM	GSM850	Front	0.157	0.014	0.023	0.004	0.171	0.180	0.161
		Back	0.246	0.023	0.005	0.006	0.269	0.251	0.252
	GSM1900	Front	0.124	0.014	0.023	0.004	0.138	0.147	0.128
		Back	0.245	0.023	0.005	0.006	0.268	0.250	0.251
WCDMA	WCDMA II	Front	0.168	0.014	0.023	0.004	0.182	0.191	0.172
		Back	0.326	0.023	0.005	0.006	0.349	0.331	0.332
	WCDMA IV	Front	0.185	0.014	0.023	0.004	0.199	0.208	0.189
		Back	0.342	0.023	0.005	0.006	0.365	0.347	0.348
	WCDMA V	Front	0.103	0.014	0.023	0.004	0.117	0.126	0.107
		Back	0.161	0.023	0.005	0.006	0.184	0.166	0.167
LTE	LTE Band 5	Front	0.140	0.014	0.023	0.004	0.154	0.163	0.144
		Back	0.218	0.023	0.005	0.006	0.241	0.223	0.224
	LTE Band 7	Front	0.076	0.014	0.023	0.004	0.090	0.099	0.080
		Back	0.059	0.023	0.005	0.006	0.082	0.064	0.065
	LTE Band 12	Front	0.203	0.014	0.023	0.004	0.217	0.226	0.207
		Back	0.269	0.023	0.005	0.006	0.292	0.274	0.275
	LTE Band 13	Front	0.228	0.014	0.023	0.004	0.242	0.251	0.232
		Back	0.316	0.023	0.005	0.006	0.339	0.321	0.322
	LTE Band 25	Front	0.165	0.014	0.023	0.004	0.179	0.188	0.169
		Back	0.308	0.023	0.005	0.006	0.331	0.313	0.314
	LTE Band 66	Front	0.210	0.014	0.023	0.004	0.224	0.233	0.214
		Back	0.358	0.023	0.005	0.006	0.381	0.363	0.364

14.4 Product Specific Exposure Conditions

Remark:

1. According to KDB 648474 D04v01r03, for WWAN / 2.4GHz WLAN / Bluetooth SAR ("") was excluded, due to Hotspot SAR was < 1.2W/kg.
2. According to KDB 941225 D06 v02r01, for 5GHz WLAN SAR ("") was excluded, due to transmitting antenna located larger 25mm from that surface or edge

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)			
GSM	GSM1900	Front	1.521	-	0.361	-	1.52	1.88	1.52
		Back	2.195	-	0.160	-	2.20	2.36	2.20
		Left side	-	-	-	-	-	-	-
		Right side	-	-	0.007	-	-	0.01	-
		Top side	-	-	0.282	-	-	0.28	-
		Bottom side	0.492	-	-	-	0.49	0.49	0.49
WCDMA	WCDMA II	Front	2.426	-	0.361	-	2.43	2.79	2.43
		Back	2.948	-	0.160	-	2.95	3.11	2.95
		Left side	-	-	-	-	-	-	-
		Right side	-	-	0.007	-	-	0.01	-
		Top side	-	-	0.282	-	-	0.28	-
		Bottom side	0.776	-	-	-	0.78	0.78	0.78
	WCDMA IV	Front	2.561	-	0.361	-	2.56	2.92	2.56
		Back	2.675	-	0.160	-	2.68	2.84	2.68
		Left side	-	-	-	-	-	-	-
		Right side	-	-	0.007	-	-	0.01	-
		Top side	-	-	0.282	-	-	0.28	-
		Bottom side	0.935	-	-	-	0.94	0.94	0.94
LTE	LTE Band 25	Front	2.872	-	0.361	-	2.87	3.23	2.87
		Back	2.497	-	0.160	-	2.50	2.66	2.50
		Left side	-	-	-	-	-	-	-
		Right side	-	-	0.007	-	-	0.01	-
		Top side	-	-	0.282	-	-	0.28	-
		Bottom side	1.404	-	-	-	1.40	1.40	1.40
	LTE Band 66	Front	2.510	-	0.361	-	2.51	2.87	2.51
		Back	2.701	-	0.160	-	2.70	2.86	2.70
		Left side	-	-	-	-	-	-	-
		Right side	-	-	0.007	-	-	0.01	-
		Top side	-	-	0.282	-	-	0.28	-
		Bottom side	0.952	-	-	-	0.95	0.95	0.95

Test Engineer : Neil Hsiang Randy Lin Andy Jiang Willy Yu Ted Hsieh Jay Jian Thomas Wang White
Huang Wilson Lin and Carter Chuang

15. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

16. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D05A v01r02, "Rel. 10 LTE SAR Test Guidance and KDB Inquiries", Oct 2015
- [11] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [12] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [13] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.