



# FCC RF Test Report

APPLICANT : Sony Mobile Communications Inc.  
EQUIPMENT : GSM/WCDMA/LTE Phone+Bluetooth,  
DTS/UNII a/b/g/n and NFC  
BRAND NAME : Sony  
FCC ID : PY7-02885J  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Apr. 28, 2017 and testing was completed on May 31, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



## SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : PY7-02885J

Page Number : 1 of 71

Report Issued Date : Jul. 10, 2017

Report Version : Rev. 02

Report Template No.: BU5-FR15CBT Version 1.1



## TABLE OF CONTENTS

|                                                                 |           |
|-----------------------------------------------------------------|-----------|
| <b>REVISION HISTORY .....</b>                                   | <b>3</b>  |
| <b>SUMMARY OF TEST RESULT .....</b>                             | <b>4</b>  |
| <b>1 GENERAL DESCRIPTION .....</b>                              | <b>5</b>  |
| 1.1 Applicant .....                                             | 5         |
| 1.2 Manufacturer .....                                          | 5         |
| 1.3 Product Feature of Equipment Under Test .....               | 5         |
| 1.4 Modification of EUT .....                                   | 6         |
| 1.5 Testing Location .....                                      | 7         |
| 1.6 Applicable Standards .....                                  | 7         |
| <b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>       | <b>8</b>  |
| 2.1 Carrier Frequency Channel .....                             | 8         |
| 2.2 Descriptions of Test Mode .....                             | 9         |
| 2.3 Test Mode .....                                             | 10        |
| 2.4 Connection Diagram of Test System .....                     | 11        |
| 2.5 Support Unit used in test configuration and system .....    | 12        |
| 2.6 EUT Operation Test Setup .....                              | 12        |
| 2.7 Measurement Results Explanation Example .....               | 12        |
| <b>3 TEST RESULT .....</b>                                      | <b>13</b> |
| 3.1 Number of Channel Measurement .....                         | 13        |
| 3.2 Hopping Channel Separation Measurement .....                | 15        |
| 3.3 Dwell Time Measurement .....                                | 22        |
| 3.4 20dB and 99% Bandwidth Measurement .....                    | 24        |
| 3.5 Peak Output Power Measurement .....                         | 37        |
| 3.6 Conducted Band Edges Measurement .....                      | 39        |
| 3.7 Conducted Spurious Emission Measurement .....               | 46        |
| 3.8 Radiated Band Edges and Spurious Emission Measurement ..... | 56        |
| 3.9 AC Conducted Emission Measurement .....                     | 64        |
| 3.10 Antenna Requirements .....                                 | 68        |
| <b>4 LIST OF MEASURING EQUIPMENT .....</b>                      | <b>69</b> |
| <b>5 UNCERTAINTY OF EVALUATION .....</b>                        | <b>71</b> |
| <b>APPENDIX A. RADIATED SPURIOUS EMISSION</b>                   |           |
| <b>APPENDIX B. RADIATED SPURIOUS EMISSION PLOTS</b>             |           |



## REVISION HISTORY

| REPORT NO.   | VERSION | DESCRIPTION                                        | ISSUED DATE   |
|--------------|---------|----------------------------------------------------|---------------|
| FR742206-01A | Rev. 01 | Initial issue of report.                           | Jun. 27, 2017 |
| FR742206-01A | Rev. 02 | Revising hygrometer calibration date in section 4. | Jul. 10, 2017 |
|              |         |                                                    |               |
|              |         |                                                    |               |
|              |         |                                                    |               |
|              |         |                                                    |               |
|              |         |                                                    |               |
|              |         |                                                    |               |
|              |         |                                                    |               |
|              |         |                                                    |               |
|              |         |                                                    |               |
|              |         |                                                    |               |
|              |         |                                                    |               |
|              |         |                                                    |               |
|              |         |                                                    |               |

## SUMMARY OF TEST RESULT

| Report Section | FCC Rule           | Description                                        | Limit                                  | Result | Remark                                   |
|----------------|--------------------|----------------------------------------------------|----------------------------------------|--------|------------------------------------------|
| 3.1            | 15.247(a)(1)       | Number of Channels                                 | $\geq 15\text{Chs}$                    | Pass   | -                                        |
| 3.2            | 15.247(a)(1)       | Hopping Channel Separation                         | $\geq 2/3$ of 20dB BW                  | Pass   | -                                        |
| 3.3            | 15.247(a)(1)       | Dwell Time of Each Channel                         | $\leq 0.4\text{sec}$ in 31.6sec period | Pass   | -                                        |
| 3.4            | 15.247(a)(1)       | 20dB Bandwidth                                     | NA                                     | Pass   | -                                        |
| 3.4            | -                  | 99% Bandwidth                                      | -                                      | Pass   | -                                        |
| 3.5            | 15.247(b)(1)       | Peak Output Power                                  | $\leq 125\text{ mW}$                   | Pass   | -                                        |
| 3.6            | 15.247(d)          | Conducted Band Edges                               | $\leq 20\text{dBc}$                    | Pass   | -                                        |
| 3.7            | 15.247(d)          | Conducted Spurious Emission                        | $\leq 20\text{dBc}$                    | Pass   | -                                        |
| 3.8            | 15.247(d)          | Radiated Band Edges and Radiated Spurious Emission | 15.209(a) & 15.247(d)                  | Pass   | Under limit<br>6.90 dB at<br>139.080 MHz |
| 3.9            | 15.207             | AC Conducted Emission                              | 15.207(a)                              | Pass   | Under limit<br>15.20 dB at<br>0.454 MHz  |
| 3.10           | 15.203 & 15.247(b) | Antenna Requirement                                | N/A                                    | Pass   | -                                        |



# 1 General Description

## 1.1 Applicant

**Sony Mobile Communications Inc.**

4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

## 1.2 Manufacturer

**Sony Mobile Communications Inc.**

4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

## 1.3 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII a/b/g/n, NFC, and GPS

| Standards-related Product Specification |            |                                      |                            |
|-----------------------------------------|------------|--------------------------------------|----------------------------|
| Antenna Type / Gain                     |            | PIFA Antenna type with gain -2.2 dBi |                            |
| EUT Information List                    |            |                                      |                            |
| HW Version                              | SW Version | S/N                                  | Performed Test Item        |
| A                                       | 0.32       | RQ3004QXCU                           | RF conducted measurement   |
|                                         |            | RQ3004QXE8                           | Radiated Spurious Emission |
|                                         |            | RQ3004R9RH                           | Conducted Emission         |

| Accessory List |                                                                                                       |
|----------------|-------------------------------------------------------------------------------------------------------|
| AC Adapter 1   | Model No. : UCH20                                                                                     |
|                | S/N :<br>1215W48600059 (for radiated spurious emission)<br>1215W48600011 (for conducted emission)     |
|                |                                                                                                       |
| Earphone 1     | Model No. : MH410c                                                                                    |
|                | S/N: 1632A86600000E0                                                                                  |
| USB Cable      | Model No. : UCB20                                                                                     |
|                | S/N :<br>1625A9110003BFA (for radiated spurious emission)<br>1625A9100003A98 (for conducted emission) |
|                |                                                                                                       |

**Note:**

1. Above EUT list and accessory list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test.
3. For other wireless features of this EUT, test report will be issued separately.

## 1.4 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

|                           |                                                                                                                                                                  |         |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
| <b>Test Site</b>          | SPORTON INTERNATIONAL INC.                                                                                                                                       |         |
| <b>Test Site Location</b> | No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park,<br>Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.<br>TEL: +886-3-327-3456<br>FAX: +886-3-328-4978 |         |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                                                                          |         |
|                           | TH05-HY                                                                                                                                                          | CO05-HY |

**Note:** The test site complies with ANSI C63.4 2014 requirement.

|                           |                                                                                                                                        |  |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------|--|
| <b>Test Site</b>          | SPORTON INTERNATIONAL INC.                                                                                                             |  |
| <b>Test Site Location</b> | No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist,<br>Taoyuan City, Taiwan (R.O.C.)<br>TEL: +886-3-327-0868<br>FAX: +886-3-327-0855 |  |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                                                |  |
|                           | 03CH13-HY                                                                                                                              |  |

**Note:** The test site complies with ANSI C63.4 2014 requirement.

## 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

| Frequency Band  | Channel | Freq.<br>(MHz) | Channel | Freq.<br>(MHz) | Channel | Freq.<br>(MHz) |
|-----------------|---------|----------------|---------|----------------|---------|----------------|
| 2400-2483.5 MHz | 0       | 2402           | 27      | 2429           | 54      | 2456           |
|                 | 1       | 2403           | 28      | 2430           | 55      | 2457           |
|                 | 2       | 2404           | 29      | 2431           | 56      | 2458           |
|                 | 3       | 2405           | 30      | 2432           | 57      | 2459           |
|                 | 4       | 2406           | 31      | 2433           | 58      | 2460           |
|                 | 5       | 2407           | 32      | 2434           | 59      | 2461           |
|                 | 6       | 2408           | 33      | 2435           | 60      | 2462           |
|                 | 7       | 2409           | 34      | 2436           | 61      | 2463           |
|                 | 8       | 2410           | 35      | 2437           | 62      | 2464           |
|                 | 9       | 2411           | 36      | 2438           | 63      | 2465           |
|                 | 10      | 2412           | 37      | 2439           | 64      | 2466           |
|                 | 11      | 2413           | 38      | 2440           | 65      | 2467           |
|                 | 12      | 2414           | 39      | 2441           | 66      | 2468           |
|                 | 13      | 2415           | 40      | 2442           | 67      | 2469           |
|                 | 14      | 2416           | 41      | 2443           | 68      | 2470           |
|                 | 15      | 2417           | 42      | 2444           | 69      | 2471           |
|                 | 16      | 2418           | 43      | 2445           | 70      | 2472           |
|                 | 17      | 2419           | 44      | 2446           | 71      | 2473           |
|                 | 18      | 2420           | 45      | 2447           | 72      | 2474           |
|                 | 19      | 2421           | 46      | 2448           | 73      | 2475           |
|                 | 20      | 2422           | 47      | 2449           | 74      | 2476           |
|                 | 21      | 2423           | 48      | 2450           | 75      | 2477           |
|                 | 22      | 2424           | 49      | 2451           | 76      | 2478           |
|                 | 23      | 2425           | 50      | 2452           | 77      | 2479           |
|                 | 24      | 2426           | 51      | 2453           | 78      | 2480           |
|                 | 25      | 2427           | 52      | 2454           | -       | -              |
|                 | 26      | 2428           | 53      | 2455           | -       | -              |

## 2.2 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

| Channel | Frequency | Bluetooth RF Output Power |                |          |
|---------|-----------|---------------------------|----------------|----------|
|         |           | Data Rate / Modulation    |                |          |
|         |           | GFSK                      | $\pi/4$ -DQPSK | 8-DPSK   |
|         |           | 1Mbps                     | 2Mbps          | 3Mbps    |
| Ch00    | 2402MHz   | 6.17 dBm                  | 5.29 dBm       | 5.56 dBm |
| Ch39    | 2441MHz   | <b>7.46 dBm</b>           | 6.72 dBm       | 6.94 dBm |
| Ch78    | 2480MHz   | 4.58 dBm                  | 3.88 dBm       | 4.07 dBm |

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (X plane as worst plane) from all possible combinations.
- b. AC power line Conducted Emission was tested under maximum output power.


## 2.3 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


| Summary table of Test Cases          |                                                                                                                                                                                                                                                                                                                         |                                       |                               |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|-------------------------------|
| Test Item                            | Data Rate / Modulation                                                                                                                                                                                                                                                                                                  |                                       |                               |
|                                      | Bluetooth BR 1Mbps<br>GFSK                                                                                                                                                                                                                                                                                              | Bluetooth EDR 2Mbps<br>$\pi/4$ -DQPSK | Bluetooth EDR 3Mbps<br>8-DPSK |
| <b>Conducted<br/>Test Cases</b>      | Mode 1: CH00_2402 MHz                                                                                                                                                                                                                                                                                                   | Mode 4: CH00_2402 MHz                 | Mode 7: CH00_2402 MHz         |
|                                      | Mode 2: CH39_2441 MHz                                                                                                                                                                                                                                                                                                   | Mode 5: CH39_2441 MHz                 | Mode 8: CH39_2441 MHz         |
|                                      | Mode 3: CH78_2480 MHz                                                                                                                                                                                                                                                                                                   | Mode 6: CH78_2480 MHz                 | Mode 9: CH78_2480 MHz         |
| <b>Radiated<br/>Test Cases</b>       | <b>Bluetooth 1Mbps GFSK / EDR 2Mbps <math>\pi/4</math>-DQPSK / EDR 3Mbps 8-DPSK</b>                                                                                                                                                                                                                                     |                                       |                               |
|                                      | Mode 1: CH00_2402 MHz for 1Mbps<br>Mode 2: CH39_2441 MHz for 1Mbps<br>Mode 3: CH78_2480 MHz for 1Mbps<br>Mode 4: CH00_2402 MHz for 2Mbps<br>Mode 5: CH39_2441 MHz for 2Mbps<br>Mode 6: CH78_2480 MHz for 2Mbps<br>Mode 7: CH00_2402 MHz for 3Mbps<br>Mode 8: CH39_2441 MHz for 3Mbps<br>Mode 9: CH78_2480 MHz for 3Mbps |                                       |                               |
| <b>AC<br/>Conducted<br/>Emission</b> | Mode 1 :GSM1900 Idle + Bluetooth Link + WLAN (2.4GHz) Link + MP3 + Earphone 1<br>+ Battery + USB Cable (Charging from Adapter 1)                                                                                                                                                                                        |                                       |                               |

## 2.4 Connection Diagram of Test System

### <Bluetooth Tx Mode>



### <AC Conducted Emission Mode>



## 2.5 Support Unit used in test configuration and system

| Item | Equipment              | Trade Name | Model Name     | FCC ID                                       | Data Cable | Power Cord                                                 |
|------|------------------------|------------|----------------|----------------------------------------------|------------|------------------------------------------------------------|
| 1.   | Bluetooth Base Station | R&S        | CBT32          | N/A                                          | N/A        | Unshielded, 1.8 m                                          |
| 2.   | System Simulator       | Anritsu    | MT8820C        | N/A                                          | N/A        | Unshielded, 1.8 m                                          |
| 3.   | WLAN AP                | ASUS       | RT-AC66U       | MSQ-RTAC66U                                  | N/A        | Unshielded, 1.8 m                                          |
| 4.   | Notebook               | DELL       | Latitude E6320 | FCC DoC/<br>Contains FCC ID:<br>QDS-BRCM1054 | N/A        | AC I/P:<br>Unshielded, 1.2 m<br>DC O/P:<br>Shielded, 1.8 m |
| 5.   | Bluetooth Earphone     | Sony       | SBH20          | PY7-RD0010                                   | N/A        | N/A                                                        |
| 6.   | SD Card                | SanDisk    | MicroSD HC     | FCC DoC                                      | N/A        | N/A                                                        |

## 2.6 EUT Operation Test Setup

For RF test items, an engineering test program was provided and enabled to make EUT transmitting signals.

## 2.7 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure


1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup




##### 3.1.5 Test Result of Number of Hopping Frequency

| <b>Test Mode :</b>                     | 1Mbps                                           | <b>Temperature :</b>        | 24~26°C          |
|----------------------------------------|-------------------------------------------------|-----------------------------|------------------|
| <b>Test Engineer :</b>                 | Kai Liao                                        | <b>Relative Humidity :</b>  | 48~51%           |
| <b>Number of Hopping<br/>(Channel)</b> | <b>Adaptive Frequency<br/>Hopping (Channel)</b> | <b>Limits<br/>(Channel)</b> | <b>Pass/Fail</b> |
| 79                                     | 20                                              | > 15                        | Pass             |

**Number of Hopping Channel Plot on Channel 00 - 78**


Date: 27.MAY.2017 18:35:58



Date: 27.MAY.2017 18:37:03

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup






## 3.2.5 Test Result of Hopping Channel Separation

|                 |          |                     |         |
|-----------------|----------|---------------------|---------|
| Test Mode :     | 1Mbps    | Temperature :       | 24~26°C |
| Test Engineer : | Kai Liao | Relative Humidity : | 48~51%  |

| Channel | Frequency (MHz) | Frequency Separation (MHz) | (2/3 of 20dB BW) Limits (MHz) | Pass/Fail |
|---------|-----------------|----------------------------|-------------------------------|-----------|
| 00      | 2402            | 1.014                      | 0.6240                        | Pass      |
| 39      | 2441            | 1.008                      | 0.6187                        | Pass      |
| 78      | 2480            | 0.996                      | 0.6160                        | Pass      |


Channel Separation Plot on Channel 00 - 01



Date: 27.MAY.2017 18:55:00




### Channel Separation Plot on Channel 39 - 40



Date: 27.MAY.2017 19:04:56

### Channel Separation Plot on Channel 77 - 78




Date: 27.MAY.2017 19:13:00



|                 |          |                     |        |
|-----------------|----------|---------------------|--------|
| Test Mode :     | 2Mbps    | Temperature :       | 24~26℃ |
| Test Engineer : | Kai Liao | Relative Humidity : | 48~51% |


| Channel | Frequency (MHz) | Frequency Separation (MHz) | (2/3 of 20dB BW) Limits (MHz) | Pass/Fail |
|---------|-----------------|----------------------------|-------------------------------|-----------|
| 00      | 2402            | 0.996                      | 0.8400                        | Pass      |
| 39      | 2441            | 0.990                      | 0.8440                        | Pass      |
| 78      | 2480            | 1.002                      | 0.8400                        | Pass      |

**Channel Separation Plot on Channel 00 - 01**

Date: 27.MAY.2017 19:23:06




### Channel Separation Plot on Channel 39 - 40



Date: 27.MAY.2017 19:32:20

### Channel Separation Plot on Channel 77 - 78




Date: 27.MAY.2017 19:37:47




|                 |          |                     |         |
|-----------------|----------|---------------------|---------|
| Test Mode :     | 3Mbps    | Temperature :       | 24~26°C |
| Test Engineer : | Kai Liao | Relative Humidity : | 48~51%  |

| Channel | Frequency (MHz) | Frequency Separation (MHz) | (2/3 of 20dB BW) Limits (MHz) | Pass/Fail |
|---------|-----------------|----------------------------|-------------------------------|-----------|
| 00      | 2402            | 0.990                      | 0.8240                        | Pass      |
| 39      | 2441            | 1.008                      | 0.8280                        | Pass      |
| 78      | 2480            | 0.990                      | 0.8320                        | Pass      |

**Channel Separation Plot on Channel 00 - 01**


Date: 27.MAY.2017 20:10:48

### Channel Separation Plot on Channel 39 - 40



Date: 27.MAY.2017 20:19:58

### Channel Separation Plot on Channel 77 - 78



Date: 27.MAY.2017 20:24:39

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup




### 3.3.5 Test Result of Dwell Time

|                 |          |                     |         |
|-----------------|----------|---------------------|---------|
| Test Mode :     | DH5      | Temperature :       | 24~26°C |
| Test Engineer : | Kai Liao | Relative Humidity : | 48~51%  |

| Mode   | Hopping Channel Number | Hops Over Occupancy Time(hops) | Package Transfer Time (msec) | Dwell Time (sec) | Limits (sec) | Pass/Fail |
|--------|------------------------|--------------------------------|------------------------------|------------------|--------------|-----------|
| Normal | 79                     | 106.67                         | 2.88                         | 0.31             | 0.4          | Pass      |
| AFH    | 20                     | 53.33                          | 2.88                         | 0.15             | 0.4          | Pass      |

**Remark:**

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.  
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),  
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.  
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),  
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

**Package Transfer Time Plot**


Date: 17.MAY.2017 01:54:34

### 3.4 20dB and 99% Bandwidth Measurement

#### 3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.  
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 99% bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
6. Measure and record the results in the test report.

#### 3.4.4 Test Setup




### 3.4.5 Test Result of 20dB Bandwidth

|                 |          |                     |        |
|-----------------|----------|---------------------|--------|
| Test Mode :     | 1Mbps    | Temperature :       | 24~26℃ |
| Test Engineer : | Kai Liao | Relative Humidity : | 48~51% |

| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) |
|---------|-----------------|----------------------|
| 00      | 2402            | 0.936                |
| 39      | 2441            | 0.928                |
| 78      | 2480            | 0.924                |


**20 dB Bandwidth Plot on Channel 00**



Date: 27.MAY.2017 18:57:40




### 20 dB Bandwidth Plot on Channel 39



Date: 27.MAY.2017 19:18:40

### 20 dB Bandwidth Plot on Channel 78




Date: 27.MAY.2017 19:16:20




|                 |          |                     |        |
|-----------------|----------|---------------------|--------|
| Test Mode :     | 2Mbps    | Temperature :       | 24~26℃ |
| Test Engineer : | Kai Liao | Relative Humidity : | 48~51% |

| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) |
|---------|-----------------|----------------------|
| 00      | 2402            | 1.260                |
| 39      | 2441            | 1.266                |
| 78      | 2480            | 1.260                |

**20 dB Bandwidth Plot on Channel 00**


Date: 27.MAY.2017 19:41:26

### 20 dB Bandwidth Plot on Channel 39



Date: 27.MAY.2017 19:35:13

### 20 dB Bandwidth Plot on Channel 78




Date: 27.MAY.2017 19:38:57

|                        |          |                            |        |
|------------------------|----------|----------------------------|--------|
| <b>Test Mode :</b>     | 3Mbps    | <b>Temperature :</b>       | 24~26℃ |
| <b>Test Engineer :</b> | Kai Liao | <b>Relative Humidity :</b> | 48~51% |

| Channel | Frequency (MHz) | 20dB Bandwidth (MHz) |
|---------|-----------------|----------------------|
| 00      | 2402            | 1.236                |
| 39      | 2441            | 1.242                |
| 78      | 2480            | 1.248                |


### 20 dB Bandwidth Plot on Channel 00



Date: 27.MAY.2017 20:12:26




### 20 dB Bandwidth Plot on Channel 39



Date: 27.MAY.2017 20:21:14

### 20 dB Bandwidth Plot on Channel 78



Date: 27.MAY.2017 20:26:31




## 3.4.6 Test Result of 99% Occupied Bandwidth

|                 |          |                     |        |
|-----------------|----------|---------------------|--------|
| Test Mode :     | 1Mbps    | Temperature :       | 24~26℃ |
| Test Engineer : | Kai Liao | Relative Humidity : | 48~51% |


| Channel | Frequency (MHz) | 99% Occupied Bandwidth (MHz) |
|---------|-----------------|------------------------------|
| 00      | 2402            | 0.860                        |
| 39      | 2441            | 0.860                        |
| 78      | 2480            | 0.860                        |

99% Occupied Bandwidth Plot on Channel 00




Date: 27.MAY.2017 19:00:28

### 99% Occupied Bandwidth Plot on Channel 39



Date: 27.MAY.2017 19:08:45

### 99% Occupied Bandwidth Plot on Channel 78




Date: 27.MAY.2017 19:19:59



|                 |          |                     |        |
|-----------------|----------|---------------------|--------|
| Test Mode :     | 2Mbps    | Temperature :       | 24~26℃ |
| Test Engineer : | Kai Liao | Relative Humidity : | 48~51% |


| Channel | Frequency (MHz) | 99% Occupied Bandwidth (MHz) |
|---------|-----------------|------------------------------|
| 00      | 2402            | 1.164                        |
| 39      | 2441            | 1.164                        |
| 78      | 2480            | 1.168                        |

**99% Occupied Bandwidth Plot on Channel 00**

Date: 27.MAY.2017 19:26:19




### 99% Occupied Bandwidth Plot on Channel 39



Date: 27.MAY.2017 19:34:13

### 99% Occupied Bandwidth Plot on Channel 78




Date: 27.MAY.2017 19:40:02



|                 |          |                     |        |
|-----------------|----------|---------------------|--------|
| Test Mode :     | 3Mbps    | Temperature :       | 24~26℃ |
| Test Engineer : | Kai Liao | Relative Humidity : | 48~51% |

| Channel | Frequency (MHz) | 99% Occupied Bandwidth (MHz) |
|---------|-----------------|------------------------------|
| 00      | 2402            | 1.164                        |
| 39      | 2441            | 1.148                        |
| 78      | 2480            | 1.152                        |


99% Occupied Bandwidth Plot on Channel 00



Date: 27.MAY.2017 20:13:01




### 99% Occupied Bandwidth Plot on Channel 39



Date: 27.MAY.2017 20:22:14

### 99% Occupied Bandwidth Plot on Channel 78



Date: 27.MAY.2017 20:27:19

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

### 3.5 Peak Output Power Measurement

#### 3.5.1 Limit of Peak Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

#### 3.5.4 Test Setup



### 3.5.5 Test Result of Peak Output Power

|                        |          |                            |         |
|------------------------|----------|----------------------------|---------|
| <b>Test Mode :</b>     | 1Mbps    | <b>Temperature :</b>       | 24~26°C |
| <b>Test Engineer :</b> | Kai Liao | <b>Relative Humidity :</b> | 48~51%  |

| Channel | Frequency<br>(MHz) | RF Power (dBm) |                      |           |
|---------|--------------------|----------------|----------------------|-----------|
|         |                    | GFSK           | Max. Limits<br>(dBm) | Pass/Fail |
|         |                    | 1 Mbps         |                      |           |
| 00      | 2402               | 6.17           | 20.97                | Pass      |
| 39      | 2441               | 7.46           | 20.97                | Pass      |
| 78      | 2480               | 4.58           | 20.97                | Pass      |

**Note:** For AFH mode using 20 hopping channels, the maximum output power limit is 20.97dBm.

|                        |          |                            |         |
|------------------------|----------|----------------------------|---------|
| <b>Test Mode :</b>     | 2Mbps    | <b>Temperature :</b>       | 24~26°C |
| <b>Test Engineer :</b> | Kai Liao | <b>Relative Humidity :</b> | 48~51%  |

| Channel | Frequency<br>(MHz) | RF Power (dBm) |                      |           |
|---------|--------------------|----------------|----------------------|-----------|
|         |                    | $\pi/4$ -DQPSK | Max. Limits<br>(dBm) | Pass/Fail |
|         |                    | 2 Mbps         |                      |           |
| 00      | 2402               | 5.29           | 20.97                | Pass      |
| 39      | 2441               | 6.72           | 20.97                | Pass      |
| 78      | 2480               | 3.88           | 20.97                | Pass      |

|                        |          |                            |         |
|------------------------|----------|----------------------------|---------|
| <b>Test Mode :</b>     | 3Mbps    | <b>Temperature :</b>       | 24~26°C |
| <b>Test Engineer :</b> | Kai Liao | <b>Relative Humidity :</b> | 48~51%  |

| Channel | Frequency<br>(MHz) | RF Power (dBm) |                      |           |
|---------|--------------------|----------------|----------------------|-----------|
|         |                    | 8-DPSK         | Max. Limits<br>(dBm) | Pass/Fail |
|         |                    | 3 Mbps         |                      |           |
| 00      | 2402               | 5.56           | 20.97                | Pass      |
| 39      | 2441               | 6.94           | 20.97                | Pass      |
| 78      | 2480               | 4.07           | 20.97                | Pass      |

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup






### 3.6.5 Test Result of Conducted Band Edges


|                |           |                     |          |
|----------------|-----------|---------------------|----------|
| Test Mode :    | 1Mbps     | Temperature :       | 24~26℃   |
| Test Channel : | 00 and 78 | Relative Humidity : | 48~51%   |
|                |           | Test Engineer :     | Kai Liao |

Low Band Edge Plot on Channel 00



Date: 27.MAY.2017 19:03:31


High Band Edge Plot on Channel 78




Date: 27.MAY.2017 19:21:52



|                |           |                     |          |
|----------------|-----------|---------------------|----------|
| Test Mode :    | 2Mbps     | Temperature :       | 24~26°C  |
| Test Channel : | 00 and 78 | Relative Humidity : | 48~51%   |
|                |           | Test Engineer :     | Kai Liao |

**Low Band Edge Plot on Channel 00**


Date: 27.MAY.2017 19:31:09

**High Band Edge Plot on Channel 78**


Date: 27.MAY.2017 20:09:30



|                |           |                     |          |
|----------------|-----------|---------------------|----------|
| Test Mode :    | 3Mbps     | Temperature :       | 24~26℃   |
| Test Channel : | 00 and 78 | Relative Humidity : | 48~51%   |
|                |           | Test Engineer :     | Kai Liao |

**Low Band Edge Plot on Channel 00**

Date: 27.MAY.2017 20:18:38


**High Band Edge Plot on Channel 78**

Date: 27.MAY.2017 20:30:18

### 3.6.6 Test Result of Conducted Hopping Mode Band Edges


|                        |          |                            |        |
|------------------------|----------|----------------------------|--------|
| <b>Test Mode :</b>     | 1Mbps    | <b>Temperature :</b>       | 24~26℃ |
| <b>Test Engineer :</b> | Kai Liao | <b>Relative Humidity :</b> | 48~51% |

### 1Mbps Hopping Mode Low Band Edge Plot



Date: 27.MAY.2017 18:48:42


### 1Mbps Hopping Mode High Band Edge Plot




Date: 27.MAY.2017 18:47:10



|                 |          |                     |         |
|-----------------|----------|---------------------|---------|
| Test Mode :     | 2Mbps    | Temperature :       | 24~26°C |
| Test Engineer : | Kai Liao | Relative Humidity : | 48~51%  |

**2Mbps Hopping Mode Low Band Edge Plot**

Date: 27.MAY.2017 18:50:18


**2Mbps Hopping Mode High Band Edge Plot**

Date: 27.MAY.2017 18:50:54




|                 |          |                     |         |
|-----------------|----------|---------------------|---------|
| Test Mode :     | 3Mbps    | Temperature :       | 24~26°C |
| Test Engineer : | Kai Liao | Relative Humidity : | 48~51%  |

### 3Mbps Hopping Mode Low Band Edge Plot



Date: 27.MAY.2017 18:52:16

### 3Mbps Hopping Mode High Band Edge Plot



Date: 27.MAY.2017 18:53:03

## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### 3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.7.4 Test Setup






## 3.7.5 Test Result of Conducted Spurious Emission


|                |       |                     |          |
|----------------|-------|---------------------|----------|
| Test Mode :    | 1Mbps | Temperature :       | 24~26°C  |
| Test Channel : | 00    | Relative Humidity : | 48~51%   |
|                |       | Test Engineer :     | Kai Liao |

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 27.MAY.2017 19:01:34


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 27.MAY.2017 19:01:55



|                |       |                     |          |
|----------------|-------|---------------------|----------|
| Test Mode :    | 1Mbps | Temperature :       | 24~26°C  |
| Test Channel : | 39    | Relative Humidity : | 48~51%   |
|                |       | Test Engineer :     | Kai Liao |

**1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 27.MAY.2017 19:11:00

**1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**


Date: 27.MAY.2017 19:11:22



|                |       |                     |          |
|----------------|-------|---------------------|----------|
| Test Mode :    | 1Mbps | Temperature :       | 24~26°C  |
| Test Channel : | 78    | Relative Humidity : | 48~51%   |
|                |       | Test Engineer :     | Kai Liao |

**1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz**


Date: 27.MAY.2017 19:20:37

**1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**


Date: 27.MAY.2017 19:20:59



|                |       |                     |          |
|----------------|-------|---------------------|----------|
| Test Mode :    | 2Mbps | Temperature :       | 24~26°C  |
| Test Channel : | 00    | Relative Humidity : | 48~51%   |
|                |       | Test Engineer :     | Kai Liao |

**2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 27.MAY.2017 19:29:58

**2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**


Date: 27.MAY.2017 19:30:20



|                |       |                     |          |
|----------------|-------|---------------------|----------|
| Test Mode :    | 2Mbps | Temperature :       | 24~26°C  |
| Test Channel : | 39    | Relative Humidity : | 48~51%   |
|                |       | Test Engineer :     | Kai Liao |

**2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 27.MAY.2017 19:36:06

**2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**


Date: 27.MAY.2017 19:36:27



|                |       |                     |          |
|----------------|-------|---------------------|----------|
| Test Mode :    | 2Mbps | Temperature :       | 24~26°C  |
| Test Channel : | 78    | Relative Humidity : | 48~51%   |
|                |       | Test Engineer :     | Kai Liao |

**2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz**


Date: 27.MAY.2017 20:08:10

**2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**


Date: 27.MAY.2017 20:08:31



|                |       |                     |          |
|----------------|-------|---------------------|----------|
| Test Mode :    | 3Mbps | Temperature :       | 24~26°C  |
| Test Channel : | 00    | Relative Humidity : | 48~51%   |
|                |       | Test Engineer :     | Kai Liao |

**3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz**


Date: 27.MAY.2017 20:17:45

**3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz**


Date: 27.MAY.2017 20:18:07



|                |       |                     |          |
|----------------|-------|---------------------|----------|
| Test Mode :    | 3Mbps | Temperature :       | 24~26°C  |
| Test Channel : | 39    | Relative Humidity : | 48~51%   |
|                |       | Test Engineer :     | Kai Liao |

**3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz**


Date: 27.MAY.2017 20:22:50

**3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz**


Date: 27.MAY.2017 20:23:12



|                |       |                     |          |
|----------------|-------|---------------------|----------|
| Test Mode :    | 3Mbps | Temperature :       | 24~26°C  |
| Test Channel : | 78    | Relative Humidity : | 48~51%   |
|                |       | Test Engineer :     | Kai Liao |

**3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz**

Date: 27.MAY.2017 20:29:23

**3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz**

Date: 27.MAY.2017 20:29:45

### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

| Frequency<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|--------------------|--------------------------------------|----------------------------------|
| 0.009 – 0.490      | 2400/F(kHz)                          | 300                              |
| 0.490 – 1.705      | 24000/F(kHz)                         | 30                               |
| 1.705 – 30.0       | 30                                   | 30                               |
| 30 – 88            | 100                                  | 3                                |
| 88 – 216           | 150                                  | 3                                |
| 216 - 960          | 200                                  | 3                                |
| Above 960          | 500                                  | 3                                |

#### 3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


### 3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (24.82dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.


### 3.8.6 Duty cycle correction factor for average measurement

<1Mbps>

**DH5 on time (One Pulse) Plot on Channel 39**



**DH5 on time (Count Pulses) Plot on Channel 39**




**Note:**

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.87 / 100 = 5.74 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.82 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported




&lt;2Mbps&gt;

## 2DH5 on time (One Pulse) Plot on Channel 39




## DH5 on time (Count Pulses) Plot on Channel 39






&lt;3Mbps&gt;

## 3DH5 on time (One Pulse) Plot on Channel 39



## DH5 on time (Count Pulses) Plot on Channel 39



**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100\text{ms}) = -24.79 \text{ dB}$$

**3.8.7 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix A and B.

**3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix A and B.

## 3.9 AC Conducted Emission Measurement

### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

| Frequency of emission (MHz) | Conducted limit (dB $\mu$ V) |           |
|-----------------------------|------------------------------|-----------|
|                             | Quasi-peak                   | Average   |
| 0.15-0.5                    | 66 to 56*                    | 56 to 46* |
| 0.5-5                       | 56                           | 46        |
| 5-30                        | 60                           | 50        |

\*Decreases with the logarithm of the frequency.


### 3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.9.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

|                 |                                                                                                                       |                     |         |
|-----------------|-----------------------------------------------------------------------------------------------------------------------|---------------------|---------|
| Test Mode :     | Mode 1                                                                                                                | Temperature :       | 22~25°C |
| Test Engineer : | Arthur Hsieh                                                                                                          | Relative Humidity : | 51~55%  |
| Test Voltage :  | 120Vac / 60Hz                                                                                                         | Phase :             | Line    |
| Function Type : | GSM1900 Idle + Bluetooth Link + WLAN (2.4GHz) Link + MP3 + Earphone 1 + Battery + USB Cable (Charging from Adapter 1) |                     |         |




#### Final Result : Quasi-Peak

| Frequency (MHz) | Quasi-Peak (dBµV) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|-------------------|--------|------|------------|-------------|--------------|
| 0.166000        | 41.9              | Off    | L1   | 19.6       | 23.3        | 65.2         |
| 0.190000        | 39.2              | Off    | L1   | 19.6       | 24.8        | 64.0         |
| 0.238000        | 34.7              | Off    | L1   | 19.6       | 27.5        | 62.2         |
| 0.278000        | 34.9              | Off    | L1   | 19.6       | 26.0        | 60.9         |
| 0.454000        | 41.6              | Off    | L1   | 19.6       | 15.2        | 56.8         |
| 0.502000        | 36.1              | Off    | L1   | 19.6       | 19.9        | 56.0         |
| 1.814000        | 31.9              | Off    | L1   | 19.6       | 24.1        | 56.0         |

#### Final Result : Average

| Frequency (MHz) | Average (dBµV) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|----------------|--------|------|------------|-------------|--------------|
| 0.166000        | 29.2           | Off    | L1   | 19.6       | 26.0        | 55.2         |
| 0.190000        | 25.0           | Off    | L1   | 19.6       | 29.0        | 54.0         |
| 0.238000        | 25.5           | Off    | L1   | 19.6       | 26.7        | 52.2         |
| 0.278000        | 26.0           | Off    | L1   | 19.6       | 24.9        | 50.9         |
| 0.454000        | 30.7           | Off    | L1   | 19.6       | 16.1        | 46.8         |
| 0.502000        | 26.7           | Off    | L1   | 19.6       | 19.3        | 46.0         |
| 1.814000        | 21.3           | Off    | L1   | 19.6       | 24.7        | 46.0         |

|                        |                                                                                                                       |                            |         |
|------------------------|-----------------------------------------------------------------------------------------------------------------------|----------------------------|---------|
| <b>Test Mode :</b>     | Mode 1                                                                                                                | <b>Temperature :</b>       | 22~25°C |
| <b>Test Engineer :</b> | Arthur Hsieh                                                                                                          | <b>Relative Humidity :</b> | 51~55%  |
| <b>Test Voltage :</b>  | 120Vac / 60Hz                                                                                                         | <b>Phase :</b>             | Neutral |
| <b>Function Type :</b> | GSM1900 Idle + Bluetooth Link + WLAN (2.4GHz) Link + MP3 + Earphone 1 + Battery + USB Cable (Charging from Adapter 1) |                            |         |


**Final Result : Quasi-Peak**

| Frequency (MHz) | Quasi-Peak (dBµV) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|-------------------|--------|------|------------|-------------|--------------|
| 0.150000        | 42.9              | Off    | N    | 19.5       | 23.1        | 66.0         |
| 0.182000        | 37.0              | Off    | N    | 19.5       | 27.4        | 64.4         |
| 0.238000        | 32.2              | Off    | N    | 19.5       | 30.0        | 62.2         |
| 0.422000        | 32.2              | Off    | N    | 19.5       | 25.2        | 57.4         |
| 0.462000        | 32.7              | Off    | N    | 19.5       | 24.0        | 56.7         |
| 0.502000        | 31.3              | Off    | N    | 19.5       | 24.7        | 56.0         |
| 1.814000        | 27.9              | Off    | N    | 19.6       | 28.1        | 56.0         |

**Final Result : Average**

| Frequency (MHz) | Average (dBµV) | Filter | Line | Corr. (dB) | Margin (dB) | Limit (dBµV) |
|-----------------|----------------|--------|------|------------|-------------|--------------|
| 0.150000        | 25.8           | Off    | N    | 19.5       | 30.2        | 56.0         |
| 0.182000        | 24.6           | Off    | N    | 19.5       | 29.8        | 54.4         |
| 0.238000        | 25.0           | Off    | N    | 19.5       | 27.2        | 52.2         |
| 0.422000        | 21.6           | Off    | N    | 19.5       | 25.8        | 47.4         |
| 0.462000        | 24.1           | Off    | N    | 19.5       | 22.6        | 46.7         |
| 0.502000        | 26.5           | Off    | N    | 19.5       | 19.5        | 46.0         |
| 1.814000        | 20.4           | Off    | N    | 19.6       | 25.6        | 46.0         |



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

| Instrument           | Manufacturer          | Model No.                           | Serial No.      | Characteristics | Calibration Date | Test Date                     | Due Date      | Remark                |
|----------------------|-----------------------|-------------------------------------|-----------------|-----------------|------------------|-------------------------------|---------------|-----------------------|
| Spectrum Analyzer    | Rohde & Schwarz       | FSP40                               | 100055          | 9kHz-40GHz      | Jul. 17, 2016    | May 17, 2017~<br>May 27, 2017 | Jul. 16, 2017 | Conducted (TH05-HY)   |
| Power Meter          | Agilent               | E4416A                              | GB4129234<br>4  | 300MHz~40GHz    | Dec. 26, 2016    | May 17, 2017~<br>May 27, 2017 | Dec. 25, 2017 | Conducted (TH05-HY)   |
| Power Sensor         | Agilent               | E9327A                              | US40441548      | 300MHz~40GHz    | Dec. 26, 2016    | May 17, 2017~<br>May 27, 2017 | Dec. 25, 2017 | Conducted (TH05-HY)   |
| Hygrometer           | Testo                 | 608-H2                              | 41410069        | N/A             | Aug. 28, 2016    | May 17, 2017~<br>May 27, 2017 | Aug. 27, 2017 | Conducted (TH05-HY)   |
| RF Cable             | HUBER +<br>SUHNER     | SUCOFLEX<br>104                     | MY8420952<br>1  | 1GHz~26GHz      | Dec. 02, 2016    | May 17, 2017~<br>May 27, 2017 | Dec. 01, 2017 | Conducted (TH05-HY)   |
| AC Power Source      | ChainTek              | APC-1000W                           | N/A             | N/A             | N/A              | May 14, 2017                  | N/A           | Conduction (CO05-HY)  |
| EMI Test Receiver    | Rohde & Schwarz       | ESCI 7                              | 100724          | 9kHz~7GHz       | Aug. 30, 2016    | May 14, 2017                  | Aug. 29, 2017 | Conduction (CO05-HY)  |
| Hygrometer           | Testo                 | 608-H1                              | 34913912        | N/A             | May 02, 2017     | May 14, 2017                  | May 01, 2018  | Conduction (CO05-HY)  |
| LISN                 | Rohde & Schwarz       | ENV216                              | 100080          | 9kHz~30MHz      | Nov. 29, 2016    | May 14, 2017                  | Nov. 28, 2017 | Conduction (CO05-HY)  |
| LF Cable             | HUBER +<br>SUHNER     | RG-214/U                            | LF01            | N/A             | Jan. 05, 2017    | May 14, 2017                  | Jan. 04, 2018 | Conduction (CO05-HY)  |
| Test Software        | N/A                   | EMC32                               | 8.40.0          | N/A             | N/A              | May 14, 2017                  | N/A           | Conduction (CO05-HY)  |
| Loop Antenna         | Rohde & Schwarz       | HFH2-Z2                             | 100315          | 9 kHz~30 MHz    | May 15, 2017     | May 19, 2017~<br>May 31, 2017 | May 14, 2019  | Radiation (03CH13-HY) |
| Bilog Antenna        | TESEQ                 | CBL<br>6111D&008<br>00N1D01N-<br>06 | 40103&04        | 30MHz to 1GHz   | Jan. 07, 2017    | May 19, 2017~<br>May 31, 2017 | Jan. 06, 2018 | Radiation (03CH13-HY) |
| Horn Antenna         | SCHWARZBE<br>CK       | BBHA 9120<br>D                      | 9120D-1522      | 1GHz ~ 18GHz    | May 17, 2017     | May 19, 2017~<br>May 31, 2017 | May 16, 2018  | Radiation (03CH13-HY) |
| SHF-EHF Horn Antenna | SCHWARZBE<br>CK       | BBHA 9170                           | BBHA91705<br>84 | 18GHz- 40GHz    | Nov. 08, 2016    | May 19, 2017~<br>May 31, 2017 | Nov. 07, 2017 | Radiation (03CH13-HY) |
| Spectrum Analyzer    | Keysight              | N9010A                              | MY5537052<br>6  | N/A             | Mar. 15, 2017    | May 19, 2017~<br>May 31, 2017 | Mar. 14, 2018 | Radiation (03CH13-HY) |
| Amplifier            | Sonoma-Instru<br>ment | 310 N                               | 187282          | 9KHz~1GHz       | Dec. 21, 2016    | May 19, 2017~<br>May 31, 2017 | Dec. 20, 2017 | Radiation (03CH13-HY) |
| Preamplifier         | MITEQ                 | JS44-18004<br>000-33-8P             | 1840917         | 18GHz ~ 40GHz   | Jun. 14, 2016    | May 19, 2017~<br>May 31, 2017 | Jun. 13, 2017 | Radiation (03CH13-HY) |
| Preamplifier         | MITEQ                 | AMF-7D-00<br>101800-30-<br>10P      | 1590074         | 1GHz~18GHz      | Jun. 27, 2016    | May 19, 2017~<br>May 31, 2017 | Jun. 26, 2017 | Radiation (03CH13-HY) |
| Preamplifier         | Keysight              | 83017A                              | MY5327014<br>7  | 1GHz~26.5GHz    | Jan. 09, 2017    | May 19, 2017~<br>May 31, 2017 | Jan. 08, 2018 | Radiation (03CH13-HY) |



| Instrument    | Manufacturer      | Model No.                           | Serial No.                                 | Characteristics                  | Calibration Date | Test Date                     | Due Date      | Remark                   |
|---------------|-------------------|-------------------------------------|--------------------------------------------|----------------------------------|------------------|-------------------------------|---------------|--------------------------|
| Hygrometer    | TECEPIL           | DTM-303B                            | TP140349                                   | N/A                              | Nov. 14, 2016    | May 19, 2017~<br>May 31, 2017 | Nov. 13, 2017 | Radiation<br>(03CH13-HY) |
| RF Cable      | HUBER +<br>SUHNER | SUCOFLEX<br>104                     | MY335041/4<br>MY9840/4<br>MY9838/4         | 26G~40GHz                        | Mar. 27, 2017    | May 19, 2017~<br>May 31, 2017 | Mar. 26, 2018 | Radiation<br>(03CH13-HY) |
| RF Cable      | HUBER +<br>SUHNER | SUCOFLEX<br>104                     | MY335041/4<br>MY9840/4<br>MY9838/4         | 1G~26GHz                         | Jan. 27, 2017    | May 19, 2017~<br>May 31, 2017 | Jan. 26, 2017 | Radiation<br>(03CH13-HY) |
| RF Cable      | HUBER +<br>SUHNER | SUCOFLEX<br>104                     | MY335041/4<br>MY9840/4<br>MY9838/4         | 30M~1GHz                         | Jan. 27, 2017    | May 19, 2017~<br>May 31, 2017 | Jan. 26, 2018 | Radiation<br>(03CH13-HY) |
| RF Cable      | HUBER +<br>SUHNER | SUCOFLEX<br>104                     | MY24958/4,<br>MY28653/4,<br>MY9839/4P<br>E | 9K~30MHz                         | Jan. 10, 2017    | May 19, 2017~<br>May 31, 2017 | Jan. 09, 2018 | Radiation<br>(03CH13-HY) |
| Controller    | EMEC              | EM1000                              | N/A                                        | Control Turn<br>table & Ant Mast | N/A              | May 19, 2017~<br>May 31, 2017 | N/A           | Radiation<br>(03CH13-HY) |
| Antenna Mast  | EMEC              | AM-BS-450<br>0-B                    | N/A                                        | 1m~4m                            | N/A              | May 19, 2017~<br>May 31, 2017 | N/A           | Radiation<br>(03CH13-HY) |
| Turn Table    | EMEC              | TT2000                              | N/A                                        | 0~360 Degree                     | N/A              | May 19, 2017~<br>May 31, 2017 | N/A           | Radiation<br>(03CH13-HY) |
| Test Software | Audix             | E3                                  | 6.2009-8-24<br>c                           | N/A                              | N/A              | May 19, 2017~<br>May 31, 2017 | N/A           | Radiation<br>(03CH13-HY) |
| Filter        | Wainwright        | WLKS1200-<br>12SS                   | SN2                                        | 1.2G Low Pass                    | Sep. 19, 2016    | May 19, 2017~<br>May 31, 2017 | Sep. 18, 2017 | Radiation<br>(03CH13-HY) |
| Filter        | Wainwright        | WHKX12-27<br>00-3000-18<br>000-60SS | SN2                                        | 3G High Pass                     | Sep. 20, 2016    | May 19, 2017~<br>May 31, 2017 | Sep. 19, 2017 | Radiation<br>(03CH13-HY) |

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

|                                                                            |      |
|----------------------------------------------------------------------------|------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 2.70 |
|----------------------------------------------------------------------------|------|

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|                                                                            |      |
|----------------------------------------------------------------------------|------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 4.90 |
|----------------------------------------------------------------------------|------|

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

|                                                                            |      |
|----------------------------------------------------------------------------|------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 5.40 |
|----------------------------------------------------------------------------|------|

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

|                                                                            |      |
|----------------------------------------------------------------------------|------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 4.30 |
|----------------------------------------------------------------------------|------|



## Appendix A. Radiated Spurious Emission

|                 |                                       |                     |             |
|-----------------|---------------------------------------|---------------------|-------------|
| Test Engineer : | Alex Jheng, Bill Chang, and Wilson Wu | Temperature :       | 24.5~24.6°C |
|                 |                                       | Relative Humidity : | 55~57%      |

### 2.4GHz 2400~2483.5MHz

#### BT (1M) (Band Edge @ 3m)

| BT                     | Note | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|------------------------|------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| BT<br>CH00<br>2402MHz  |      | 2375.73              | 42.41               | -31.59                  | 74                          | 41.26                     | 27.31                         | 4.83                    | 30.99                      | 377                  | 78                      | P                       | H               |
|                        |      | 2375.73              | 17.59               | -36.41                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        | *    | 2402                 | 97.29               | -                       | -                           | 96.06                     | 27.37                         | 4.85                    | 30.99                      | 377                  | 78                      | P                       | H               |
|                        | *    | 2402                 | 72.47               | -                       | -                           | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |      |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | H               |
|                        |      |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | H               |
|                        |      | 2358.405             | 42.52               | -31.48                  | 74                          | 41.46                     | 27.26                         | 4.8                     | 31                         | 390                  | 341                     | P                       | V               |
|                        |      | 2358.405             | 17.7                | -36.3                   | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        | *    | 2402                 | 94.23               | -                       | -                           | 93                        | 27.37                         | 4.85                    | 30.99                      | 390                  | 341                     | P                       | V               |
|                        | *    | 2402                 | 69.41               | -                       | -                           | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        |      |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | V               |
|                        |      |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | V               |
| BT<br>CH 39<br>2441MHz |      | 2388.12              | 41.59               | -32.41                  | 74                          | 40.38                     | 27.37                         | 4.83                    | 30.99                      | 400                  | 85                      | P                       | H               |
|                        |      | 2388.12              | 16.77               | -37.23                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        | *    | 2441                 | 100.12              | -                       | -                           | 98.68                     | 27.53                         | 4.88                    | 30.97                      | 400                  | 85                      | P                       | H               |
|                        | *    | 2441                 | 75.3                | -                       | -                           | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |      | 2492.65              | 42.34               | -31.66                  | 74                          | 40.67                     | 27.7                          | 4.93                    | 30.96                      | 400                  | 85                      | P                       | H               |
|                        |      | 2492.65              | 17.52               | -36.48                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |      | 2389.66              | 41.86               | -32.14                  | 74                          | 40.65                     | 27.37                         | 4.83                    | 30.99                      | 374                  | 338                     | P                       | V               |
|                        |      | 2389.66              | 17.04               | -36.96                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        | *    | 2441                 | 96.4                | -                       | -                           | 94.96                     | 27.53                         | 4.88                    | 30.97                      | 374                  | 338                     | P                       | V               |
|                        | *    | 2441                 | 71.58               | -                       | -                           | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        |      | 2485.58              | 42.98               | -31.02                  | 74                          | 41.38                     | 27.64                         | 4.93                    | 30.97                      | 374                  | 338                     | P                       | V               |
|                        |      | 2485.58              | 18.16               | -35.84                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |



|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   |   |
|---------------------------------|---------------------------------------------------------------------------------------------|---------|-------|--------|----|-------|-------|------|-------|-----|-----|---|---|
| <b>BT<br/>CH 78<br/>2480MHz</b> | *                                                                                           | 2480    | 97.67 | -      | -  | 96.08 | 27.64 | 4.92 | 30.97 | 392 | 74  | P | H |
|                                 | *                                                                                           | 2480    | 72.85 | -      | -  | -     | -     | -    | -     | -   | -   | A | H |
|                                 |                                                                                             | 2490.72 | 42.59 | -31.41 | 74 | 40.92 | 27.7  | 4.93 | 30.96 | 392 | 74  | P | H |
|                                 |                                                                                             | 2490.72 | 17.77 | -36.23 | 54 | -     | -     | -    | -     | -   | -   | A | H |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | H |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | H |
|                                 | *                                                                                           | 2480    | 93.97 | -      | -  | 92.38 | 27.64 | 4.92 | 30.97 | 400 | 360 | P | V |
|                                 | *                                                                                           | 2480    | 69.15 | -      | -  | -     | -     | -    | -     | -   | -   | A | V |
|                                 |                                                                                             | 2497.2  | 42.89 | -31.11 | 74 | 41.22 | 27.7  | 4.93 | 30.96 | 400 | 360 | P | V |
|                                 |                                                                                             | 2497.2  | 18.07 | -35.93 | 54 | -     | -     | -    | -     | -   | -   | A | V |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | V |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | V |
| <b>Remark</b>                   | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |         |       |        |    |       |       |      |       |     |     |   |   |



## 2.4GHz 2400~2483.5MHz

## BT (1M) (Harmonic @ 3m)

| BT                     | Note                                                                                        | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|------------------------|---------------------------------------------------------------------------------------------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| BT<br>CH 00<br>2402MHz |                                                                                             | 4804                 | 40.22               | -33.78                  | 74                          | 65.04                     | 31.76                         | 7.65                    | 64.75                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 4804                 | 15.4                | -38.6                   | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | H               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | H               |
|                        |                                                                                             | 4804                 | 39.98               | -34.02                  | 74                          | 64.8                      | 31.76                         | 7.65                    | 64.75                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 4804                 | 15.16               | -38.84                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | V               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | V               |
| BT<br>CH 39<br>2441MHz |                                                                                             | 4882                 | 42.55               | -31.45                  | 74                          | 67.05                     | 31.88                         | 7.82                    | 64.7                       | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 4882                 | 17.73               | -36.27                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 7323                 | 45.63               | -28.37                  | 74                          | 63.1                      | 37.22                         | 9.68                    | 64.83                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 7323                 | 20.81               | -33.19                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 4882                 | 41.02               | -32.98                  | 74                          | 65.52                     | 31.88                         | 7.82                    | 64.7                       | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 4882                 | 16.2                | -37.8                   | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        |                                                                                             | 7323                 | 45.85               | -28.15                  | 74                          | 63.32                     | 37.22                         | 9.68                    | 64.83                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 7323                 | 21.03               | -32.97                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
| BT<br>CH 78<br>2480MHz |                                                                                             | 4960                 | 41.05               | -32.95                  | 74                          | 65.17                     | 32.04                         | 7.98                    | 64.63                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 4960                 | 16.23               | -37.77                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 7440                 | 46.56               | -27.44                  | 74                          | 63.65                     | 37.56                         | 9.77                    | 64.88                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 7440                 | 21.74               | -32.26                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 4960                 | 39.71               | -34.29                  | 74                          | 63.83                     | 32.04                         | 7.98                    | 64.63                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 4960                 | 14.89               | -39.11                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        |                                                                                             | 7440                 | 45.07               | -28.93                  | 74                          | 62.16                     | 37.56                         | 9.77                    | 64.88                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 7440                 | 20.25               | -33.75                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
| Remark                 | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         |                 |



## 2.4GHz 2400~2483.5MHz

## BT (2M) (Band Edge @ 3m)

| BT                     | Note | Frequency | Level      | Over   | Limit      | Read     | Antenna  | Cable  | Preamp | Ant    | Table   | Peak    | Pol.    |
|------------------------|------|-----------|------------|--------|------------|----------|----------|--------|--------|--------|---------|---------|---------|
|                        |      |           |            | Limit  | Line       | Level    | Factor   | Loss   | Factor | Pos    | Pos     | Avg.    |         |
|                        |      | ( MHz )   | ( dBμV/m ) | ( dB ) | ( dBμV/m ) | ( dBμV ) | ( dB/m ) | ( dB ) | ( dB ) | ( cm ) | ( deg ) | ( P/A ) | ( H/V ) |
| BT<br>CH00<br>2402MHz  |      | 2380.455  | 43         | -31    | 74         | 41.85    | 27.31    | 4.83   | 30.99  | 378    | 71      | P       | H       |
|                        |      | 2380.455  | 18.21      | -35.79 | 54         | -        | -        | -      | -      | -      | -       | A       | H       |
|                        | *    | 2402      | 96.51      | -      | -          | 95.28    | 27.37    | 4.85   | 30.99  | 378    | 71      | P       | H       |
|                        | *    | 2402      | 71.72      | -      | -          | -        | -        | -      | -      | -      | -       | A       | H       |
|                        |      |           |            |        |            |          |          |        |        |        |         |         | H       |
|                        |      |           |            |        |            |          |          |        |        |        |         |         | H       |
|                        |      | 2358.51   | 42.52      | -31.48 | 74         | 41.46    | 27.26    | 4.8    | 31     | 380    | 338     | P       | V       |
|                        |      | 2358.51   | 17.73      | -36.27 | 54         | -        | -        | -      | -      | -      | -       | A       | V       |
|                        | *    | 2402      | 92.8       | -      | -          | 91.57    | 27.37    | 4.85   | 30.99  | 380    | 338     | P       | V       |
|                        | *    | 2402      | 68.01      | -      | -          | -        | -        | -      | -      | -      | -       | A       | V       |
|                        |      |           |            |        |            |          |          |        |        |        |         |         | V       |
|                        |      |           |            |        |            |          |          |        |        |        |         |         | V       |
| BT<br>CH 39<br>2441MHz |      | 2388.54   | 42.6       | -31.4  | 74         | 41.39    | 27.37    | 4.83   | 30.99  | 400    | 85      | P       | H       |
|                        |      | 2388.54   | 17.81      | -36.19 | 54         | -        | -        | -      | -      | -      | -       | A       | H       |
|                        | *    | 2441      | 99.35      | -      | -          | 97.91    | 27.53    | 4.88   | 30.97  | 400    | 85      | P       | H       |
|                        | *    | 2441      | 74.56      | -      | -          | -        | -        | -      | -      | -      | -       | A       | H       |
|                        |      | 2495.87   | 42.52      | -31.48 | 74         | 40.85    | 27.7     | 4.93   | 30.96  | 400    | 85      | P       | H       |
|                        |      | 2495.87   | 17.73      | -36.27 | 54         | -        | -        | -      | -      | -      | -       | A       | H       |
|                        |      | 2375.8    | 42.08      | -31.92 | 74         | 40.93    | 27.31    | 4.83   | 30.99  | 376    | 337     | P       | V       |
|                        |      | 2375.8    | 17.29      | -36.71 | 54         | -        | -        | -      | -      | -      | -       | A       | V       |
|                        | *    | 2441      | 95.78      | -      | -          | 94.34    | 27.53    | 4.88   | 30.97  | 376    | 337     | P       | V       |
|                        | *    | 2441      | 70.99      | -      | -          | -        | -        | -      | -      | -      | -       | A       | V       |
|                        |      | 2483.76   | 42.44      | -31.56 | 74         | 40.84    | 27.64    | 4.93   | 30.97  | 376    | 337     | P       | V       |
|                        |      | 2483.76   | 17.65      | -36.35 | 54         | -        | -        | -      | -      | -      | -       | A       | V       |



|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   |   |
|---------------------------------|---------------------------------------------------------------------------------------------|---------|-------|--------|----|-------|-------|------|-------|-----|-----|---|---|
| <b>BT<br/>CH 78<br/>2480MHz</b> | *                                                                                           | 2480    | 96.65 | -      | -  | 95.06 | 27.64 | 4.92 | 30.97 | 394 | 76  | P | H |
|                                 | *                                                                                           | 2480    | 71.86 | -      | -  | -     | -     | -    | -     | -   | -   | A | H |
|                                 |                                                                                             | 2484.24 | 43.33 | -30.67 | 74 | 41.73 | 27.64 | 4.93 | 30.97 | 394 | 76  | P | H |
|                                 |                                                                                             | 2484.24 | 18.54 | -35.46 | 54 | -     | -     | -    | -     | -   | -   | A | H |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | H |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | H |
|                                 | *                                                                                           | 2480    | 92.91 | -      | -  | 91.32 | 27.64 | 4.92 | 30.97 | 400 | 360 | P | V |
|                                 | *                                                                                           | 2480    | 68.12 | -      | -  | -     | -     | -    | -     | -   | -   | A | V |
|                                 |                                                                                             | 2499.32 | 42.57 | -31.43 | 74 | 40.9  | 27.7  | 4.93 | 30.96 | 400 | 360 | P | V |
|                                 |                                                                                             | 2499.32 | 17.78 | -36.22 | 54 | -     | -     | -    | -     | -   | -   | A | V |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | V |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | V |
| <b>Remark</b>                   | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |         |       |        |    |       |       |      |       |     |     |   |   |



## 2.4GHz 2400~2483.5MHz

## BT (2M) (Harmonic @ 3m)

| BT                     | Note                                                                                        | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|------------------------|---------------------------------------------------------------------------------------------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| BT<br>CH 00<br>2402MHz |                                                                                             | 4804                 | 38.2                | -35.8                   | 74                          | 63.02                     | 31.76                         | 7.65                    | 64.75                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 4804                 | 13.41               | -40.59                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | H               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | H               |
|                        |                                                                                             | 4804                 | 38.2                | -35.8                   | 74                          | 63.02                     | 31.76                         | 7.65                    | 64.75                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 4804                 | 13.41               | -40.59                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | V               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | V               |
| BT<br>CH 39<br>2441MHz |                                                                                             | 4882                 | 39.81               | -34.19                  | 74                          | 64.31                     | 31.88                         | 7.82                    | 64.7                       | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 4882                 | 15.02               | -38.98                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 7323                 | 45.93               | -28.07                  | 74                          | 63.4                      | 37.22                         | 9.68                    | 64.83                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 7323                 | 21.14               | -32.86                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 4882                 | 39.28               | -34.72                  | 74                          | 63.78                     | 31.88                         | 7.82                    | 64.7                       | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 4882                 | 14.49               | -39.51                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        |                                                                                             | 7323                 | 44.5                | -29.5                   | 74                          | 61.97                     | 37.22                         | 9.68                    | 64.83                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 7323                 | 19.71               | -34.29                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
| BT<br>CH 78<br>2480MHz |                                                                                             | 4960                 | 40.76               | -33.24                  | 74                          | 64.88                     | 32.04                         | 7.98                    | 64.63                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 4960                 | 15.97               | -38.03                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 7440                 | 44.43               | -29.57                  | 74                          | 61.52                     | 37.56                         | 9.77                    | 64.88                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 7440                 | 19.64               | -34.36                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 4960                 | 39.92               | -34.08                  | 74                          | 64.04                     | 32.04                         | 7.98                    | 64.63                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 4960                 | 15.13               | -38.87                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        |                                                                                             | 7440                 | 45.48               | -28.52                  | 74                          | 62.57                     | 37.56                         | 9.77                    | 64.88                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 7440                 | 20.69               | -33.31                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
| Remark                 | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         |                 |



## 2.4GHz 2400~2483.5MHz

## BT (3M) (Band Edge @ 3m)

| BT                     | Note | Frequency | Level      | Over   | Limit      | Read     | Antenna  | Cable  | Preamp | Ant    | Table   | Peak    | Pol.    |
|------------------------|------|-----------|------------|--------|------------|----------|----------|--------|--------|--------|---------|---------|---------|
|                        |      |           |            | Limit  | Line       | Level    | Factor   | Loss   | Factor | Pos    | Pos     | Avg.    |         |
|                        |      | ( MHz )   | ( dBμV/m ) | ( dB ) | ( dBμV/m ) | ( dBμV ) | ( dB/m ) | ( dB ) | ( dB ) | ( cm ) | ( deg ) | ( P/A ) | ( H/V ) |
| BT<br>CH00<br>2402MHz  |      | 2311.785  | 42.09      | -31.91 | 74         | 41.27    | 27.09    | 4.74   | 31.01  | 371    | 76      | P       | H       |
|                        |      | 2311.785  | 17.3       | -36.7  | 54         | -        | -        | -      | -      | -      | -       | A       | H       |
|                        | *    | 2402      | 97.67      | -      | -          | 96.44    | 27.37    | 4.85   | 30.99  | 371    | 76      | P       | H       |
|                        | *    | 2402      | 72.88      | -      | -          | -        | -        | -      | -      | -      | -       | A       | H       |
|                        |      |           |            |        |            |          |          |        |        |        |         |         | H       |
|                        |      |           |            |        |            |          |          |        |        |        |         |         | H       |
|                        |      | 2388.015  | 42.38      | -31.62 | 74         | 41.17    | 27.37    | 4.83   | 30.99  | 382    | 349     | P       | V       |
|                        |      | 2388.015  | 17.59      | -36.41 | 54         | -        | -        | -      | -      | -      | -       | A       | V       |
|                        | *    | 2402      | 94.41      | -      | -          | 93.18    | 27.37    | 4.85   | 30.99  | 382    | 349     | P       | V       |
|                        | *    | 2402      | 69.62      | -      | -          | -        | -        | -      | -      | -      | -       | A       | V       |
|                        |      |           |            |        |            |          |          |        |        |        |         |         | V       |
|                        |      |           |            |        |            |          |          |        |        |        |         |         | V       |
| BT<br>CH 39<br>2441MHz |      | 2315.6    | 42.12      | -31.88 | 74         | 41.3     | 27.09    | 4.74   | 31.01  | 400    | 80      | P       | H       |
|                        |      | 2315.6    | 17.33      | -36.67 | 54         | -        | -        | -      | -      | -      | -       | A       | H       |
|                        | *    | 2441      | 98.89      | -      | -          | 97.45    | 27.53    | 4.88   | 30.97  | 400    | 80      | P       | H       |
|                        | *    | 2441      | 74.1       | -      | -          | -        | -        | -      | -      | -      | -       | A       | H       |
|                        |      | 2485.65   | 41.72      | -32.28 | 74         | 40.12    | 27.64    | 4.93   | 30.97  | 400    | 80      | P       | H       |
|                        |      | 2485.65   | 16.93      | -37.07 | 54         | -        | -        | -      | -      | -      | -       | A       | H       |
|                        |      | 2386.72   | 41.52      | -32.48 | 74         | 40.31    | 27.37    | 4.83   | 30.99  | 400    | 270     | P       | V       |
|                        |      | 2386.72   | 16.73      | -37.27 | 54         | -        | -        | -      | -      | -      | -       | A       | V       |
|                        | *    | 2441      | 92.23      | -      | -          | 90.79    | 27.53    | 4.88   | 30.97  | 400    | 270     | P       | V       |
|                        | *    | 2441      | 67.44      | -      | -          | -        | -        | -      | -      | -      | -       | A       | V       |
|                        |      | 2498.81   | 41.95      | -32.05 | 74         | 40.28    | 27.7     | 4.93   | 30.96  | 400    | 270     | P       | V       |
|                        |      | 2498.81   | 17.16      | -36.84 | 54         | -        | -        | -      | -      | -      | -       | A       | V       |



|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   |   |
|---------------------------------|---------------------------------------------------------------------------------------------|---------|-------|--------|----|-------|-------|------|-------|-----|-----|---|---|
| <b>BT<br/>CH 78<br/>2480MHz</b> | *                                                                                           | 2480    | 97    | -      | -  | 95.41 | 27.64 | 4.92 | 30.97 | 389 | 76  | P | H |
|                                 | *                                                                                           | 2480    | 72.21 | -      | -  | -     | -     | -    | -     | -   | -   | A | H |
|                                 |                                                                                             | 2483.76 | 42.72 | -31.28 | 74 | 41.12 | 27.64 | 4.93 | 30.97 | 389 | 76  | P | H |
|                                 |                                                                                             | 2483.76 | 17.93 | -36.07 | 54 | -     | -     | -    | -     | -   | -   | A | H |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | H |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | H |
|                                 | *                                                                                           | 2480    | 93.46 | -      | -  | 91.87 | 27.64 | 4.92 | 30.97 | 400 | 351 | P | V |
|                                 | *                                                                                           | 2480    | 68.67 | -      | -  | -     | -     | -    | -     | -   | -   | A | V |
|                                 |                                                                                             | 2485.12 | 43.23 | -30.77 | 74 | 41.63 | 27.64 | 4.93 | 30.97 | 400 | 351 | P | V |
|                                 |                                                                                             | 2485.12 | 18.44 | -35.56 | 54 | -     | -     | -    | -     | -   | -   | A | V |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | V |
|                                 |                                                                                             |         |       |        |    |       |       |      |       |     |     |   | V |
| <b>Remark</b>                   | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |         |       |        |    |       |       |      |       |     |     |   |   |



## 2.4GHz 2400~2483.5MHz

## BT (3M) (Harmonic @ 3m)

| BT                     | Note                                                                                        | Frequency<br>( MHz ) | Level<br>( dBμV/m ) | Over<br>Limit<br>( dB ) | Limit<br>Line<br>( dBμV/m ) | Read<br>Level<br>( dBμV ) | Antenna<br>Factor<br>( dB/m ) | Cable<br>Loss<br>( dB ) | Preamp<br>Factor<br>( dB ) | Ant<br>Pos<br>( cm ) | Table<br>Pos<br>( deg ) | Peak<br>Avg.<br>( P/A ) | Pol.<br>( H/V ) |
|------------------------|---------------------------------------------------------------------------------------------|----------------------|---------------------|-------------------------|-----------------------------|---------------------------|-------------------------------|-------------------------|----------------------------|----------------------|-------------------------|-------------------------|-----------------|
| BT<br>CH 00<br>2402MHz |                                                                                             | 4804                 | 38.75               | -35.25                  | 74                          | 63.57                     | 31.76                         | 7.65                    | 64.75                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 4804                 | 13.96               | -40.04                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | H               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | H               |
|                        |                                                                                             | 4804                 | 39.49               | -34.51                  | 74                          | 64.31                     | 31.76                         | 7.65                    | 64.75                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 4804                 | 14.7                | -39.3                   | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | V               |
|                        |                                                                                             |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         | V               |
| BT<br>CH 39<br>2441MHz |                                                                                             | 4882                 | 40.67               | -33.33                  | 74                          | 65.17                     | 31.88                         | 7.82                    | 64.7                       | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 4882                 | 15.88               | -38.12                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 7323                 | 46.13               | -27.87                  | 74                          | 63.6                      | 37.22                         | 9.68                    | 64.83                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 7323                 | 21.34               | -32.66                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 4882                 | 39.33               | -34.67                  | 74                          | 63.83                     | 31.88                         | 7.82                    | 64.7                       | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 4882                 | 14.54               | -39.46                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        |                                                                                             | 7323                 | 44.88               | -29.12                  | 74                          | 62.35                     | 37.22                         | 9.68                    | 64.83                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 7323                 | 20.09               | -33.91                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
| BT<br>CH 78<br>2480MHz |                                                                                             | 4960                 | 39.65               | -34.35                  | 74                          | 63.77                     | 32.04                         | 7.98                    | 64.63                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 4960                 | 14.86               | -39.14                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 7440                 | 44.04               | -29.96                  | 74                          | 61.13                     | 37.56                         | 9.77                    | 64.88                      | 100                  | 0                       | P                       | H               |
|                        |                                                                                             | 7440                 | 19.25               | -34.75                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | H               |
|                        |                                                                                             | 4960                 | 38.95               | -35.05                  | 74                          | 63.07                     | 32.04                         | 7.98                    | 64.63                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 4960                 | 14.16               | -39.84                  | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
|                        |                                                                                             | 7440                 | 44.09               | -29.91                  | 74                          | 61.18                     | 37.56                         | 9.77                    | 64.88                      | 100                  | 0                       | P                       | V               |
|                        |                                                                                             | 7440                 | 19.3                | -34.7                   | 54                          | -                         | -                             | -                       | -                          | -                    | -                       | A                       | V               |
| Remark                 | 1. No other spurious found.<br>2. All results are PASS against Peak and Average limit line. |                      |                     |                         |                             |                           |                               |                         |                            |                      |                         |                         |                 |

## Emission below 1GHz

## 2.4GHz BT (LF)

| BT                     | Note                                                                       | Frequency | Level      | Over   | Limit      | Read   | Antenna  | Cable  | Preamp | Ant    | Table   | Peak  | Pol.  |
|------------------------|----------------------------------------------------------------------------|-----------|------------|--------|------------|--------|----------|--------|--------|--------|---------|-------|-------|
|                        |                                                                            |           |            | Limit  | Line       | Level  | Factor   | Loss   | Factor | Pos    | Pos     | Avg.  |       |
|                        |                                                                            | ( MHz )   | ( dBμV/m ) | ( dB ) | ( dBμV/m ) | (dBμV) | ( dB/m ) | ( dB ) | ( dB ) | ( cm ) | ( deg ) | (P/A) | (H/V) |
| 2.4GHz<br><br>BT<br>LF |                                                                            | 30        | 20.73      | -19.27 | 40         | 29.87  | 22.63    | 0.59   | 32.34  |        |         | P     | H     |
|                        |                                                                            | 139.08    | 36.6       | -6.9   | 43.5       | 53.22  | 14.43    | 1.19   | 32.28  | 100    | 0       | P     | H     |
|                        |                                                                            | 221.97    | 30.89      | -15.11 | 46         | 49.39  | 12.14    | 1.53   | 32.24  |        |         | P     | H     |
|                        |                                                                            | 472.9     | 21.07      | -24.93 | 46         | 30.75  | 20.26    | 2.17   | 32.19  |        |         | P     | H     |
|                        |                                                                            | 727       | 26.28      | -19.72 | 46         | 31.08  | 24.56    | 2.66   | 32.12  |        |         | P     | H     |
|                        |                                                                            | 958       | 30.96      | -15.04 | 46         | 30.27  | 28.46    | 3.07   | 30.98  |        |         | P     | H     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | H     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | H     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | H     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | H     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | H     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | H     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | H     |
|                        |                                                                            | 44.31     | 30.77      | -9.23  | 40         | 50.91  | 11.42    | 0.74   | 32.33  | 100    | 0       | P     | V     |
|                        |                                                                            | 134.76    | 32.39      | -11.11 | 43.5       | 49.52  | 13.91    | 1.19   | 32.28  |        |         | P     | V     |
|                        |                                                                            | 221.97    | 25.46      | -20.54 | 46         | 43.96  | 12.14    | 1.53   | 32.24  |        |         | P     | V     |
|                        |                                                                            | 451.2     | 20.79      | -25.21 | 46         | 30.87  | 19.92    | 2.1    | 32.18  |        |         | P     | V     |
|                        |                                                                            | 843.9     | 32.46      | -13.54 | 46         | 34.96  | 26.31    | 2.84   | 31.78  |        |         | P     | V     |
|                        |                                                                            | 946.1     | 31.34      | -14.66 | 46         | 31.59  | 27.64    | 3.06   | 31.09  |        |         | P     | V     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | V     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | V     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | V     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | V     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         |       | V     |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         | V     |       |
|                        |                                                                            |           |            |        |            |        |          |        |        |        |         | V     |       |
| Remark                 | 1. No other spurious found.<br>2. All results are PASS against limit line. |           |            |        |            |        |          |        |        |        |         |       |       |



**Note symbol**

|     |                                                                                                                                                          |
|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| *   | <b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency. |
| !   | Test result is <b>over limit</b> line.                                                                                                                   |
| P/A | <b>P</b> eak or <b>A</b> verage                                                                                                                          |
| H/V | <b>H</b> orizontal or <b>V</b> ertical                                                                                                                   |



A calculation example for radiated spurious emission is shown as below:

| WIFI    | Note | Frequency | Level      | Over   | Limit      | Read     | Antenna  | Cable  | Preamp | Ant    | Table   | Peak    | Pol.    |
|---------|------|-----------|------------|--------|------------|----------|----------|--------|--------|--------|---------|---------|---------|
| Ant.    |      |           |            | Limit  | Line       | Level    | Factor   | Loss   | Factor | Pos    | Pos     | Avg.    |         |
| 1+2     |      | ( MHz )   | ( dBμV/m ) | ( dB ) | ( dBμV/m ) | ( dBμV ) | ( dB/m ) | ( dB ) | ( dB ) | ( cm ) | ( deg ) | ( P/A ) | ( H/V ) |
| 802.11b |      | 2390      | 55.45      | -18.55 | 74         | 54.51    | 32.22    | 4.58   | 35.86  | 103    | 308     | P       | H       |
| CH 01   |      |           |            |        |            |          |          |        |        |        |         |         |         |
| 2412MHz |      | 2390      | 43.54      | -10.46 | 54         | 42.6     | 32.22    | 4.58   | 35.86  | 103    | 308     | A       | H       |

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## Appendix B. Radiated Spurious Emission Plots



|                 |                                       |                     |             |
|-----------------|---------------------------------------|---------------------|-------------|
| Test Engineer : | Alex Jheng, Bill Chang, and Wilson Wu | Temperature :       | 24.5~24.6°C |
|                 |                                       | Relative Humidity : | 55~57%      |

2.4GHz 2400~2483.5MHz




BT (1M) (Band Edge @ 3m)

| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                             |                                                                               |
|------|----------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| ANT  | BT CH00 2402MHz                                                                  |                                                                               |
| 1    | Horizontal                                                                       | Fundamental                                                                   |
| Peak | <p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_91200_1522 HORIZONTAL</p> | <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_91200_1522 HORIZONTAL</p> |






| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                       |                                                                                                                                                                          |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH00 2402MHz                                                                                                                                                            |                                                                                                                                                                          |
| 1    | Vertical                                                                                                                                                                   | Fundamental                                                                                                                                                              |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_91200_1522 VERTICAL</p></div> | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_91200_1522 VERTICAL</p></div> |





| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                           |                                                                                                                                                                            |
|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH39 2441MHz                                                                                                                                                                |                                                                                                                                                                            |
| 1    | Horizontal                                                                                                                                                                     | Fundamental                                                                                                                                                                |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 HORIZONTAL</p></div>   | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_9120D_1522 HORIZONTAL</p></div> |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 HORIZONTAL</p></div> | Left blank                                                                                                                                                                 |





| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                         |                                                                                                                                                                          |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH39 2441MHz                                                                                                                                                              |                                                                                                                                                                          |
| 1    | Vertical                                                                                                                                                                     | Fundamental                                                                                                                                                              |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 VERTICAL</p></div>   | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_9120D_1522 VERTICAL</p></div> |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 VERTICAL</p></div> | Left blank                                                                                                                                                               |



| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                         |                                                                                                                                                                            |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH78 2480MHz                                                                                                                                                              |                                                                                                                                                                            |
| 1    | Horizontal                                                                                                                                                                   | Fundamental                                                                                                                                                                |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_91200_1522 HORIZONTAL</p></div> | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_91200_1522 HORIZONTAL</p></div> |



| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                       |                                                                                                                                                                          |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH78 2480MHz                                                                                                                                                            |                                                                                                                                                                          |
| 1    | Vertical                                                                                                                                                                   | Fundamental                                                                                                                                                              |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 VERTICAL</p></div> | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_9120D_1522 VERTICAL</p></div> |





2.4GHz 2400~2483.5MHz

BT (1M) (Harmonic @ 3m)

| BT           | 2.4GHz 2400~2483.5MHz Harmonic @ 3m                                        |                                                                          |
|--------------|----------------------------------------------------------------------------|--------------------------------------------------------------------------|
| ANT          | BT CH00 2402MHz                                                            |                                                                          |
| 1            | Horizontal                                                                 | Vertical                                                                 |
| Peak<br>Avg. | <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL</p> | <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 VERTICAL</p> |



| BT           | 2.4GHz 2400~2483.5MHz Harmonic @ 3m                                                                                                                          |                                                                                                                                                             |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT          | BT CH39 2441MHz                                                                                                                                              |                                                                                                                                                             |
| 1            | Horizontal                                                                                                                                                   | Vertical                                                                                                                                                    |
| Peak<br>Avg. |  <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL</p> |  <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 VERTICAL</p> |





| BT           | 2.4GHz 2400~2483.5MHz Harmonic @ 3m                                                                                                                     |                                                                                                                                                       |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT          | BT CH78 2480MHz                                                                                                                                         |                                                                                                                                                       |
| 1            | Horizontal                                                                                                                                              | Vertical                                                                                                                                              |
| Peak<br>Avg. | <div><p>Level (dBuV/m)</p><p>Date: 2017-05-22</p><p>Frequency (MHz)</p><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL</p></div> | <div><p>Level (dBuV/m)</p><p>Date: 2017-05-22</p><p>Frequency (MHz)</p><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 VERTICAL</p></div> |





2.4GHz 2400~2483.5MHz




BT (2M) (Band Edge @ 3m)

| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                         |                                                                                                                                                                            |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH00 2402MHz                                                                                                                                                              |                                                                                                                                                                            |
| 1    | Horizontal                                                                                                                                                                   | Fundamental                                                                                                                                                                |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 HORIZONTAL</p></div> | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_9120D_1522 HORIZONTAL</p></div> |






| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                       |                                                                                                                                                                          |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH00 2402MHz                                                                                                                                                            |                                                                                                                                                                          |
| 1    | Vertical                                                                                                                                                                   | Fundamental                                                                                                                                                              |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_91200_1522 VERTICAL</p></div> | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_91200_1522 VERTICAL</p></div> |





| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                 |                                                                                                                                                                  |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH39 2441MHz                                                                                                                                                      |                                                                                                                                                                  |
| 1    | Horizontal                                                                                                                                                           | Fundamental                                                                                                                                                      |
| Peak |  <p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 HORIZONTAL</p>   |  <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_9120D_1522 HORIZONTAL</p> |
| Peak |  <p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 HORIZONTAL</p> | Left blank                                                                                                                                                       |





| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                         |                                                                                                                                                                          |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH39 2441MHz                                                                                                                                                              |                                                                                                                                                                          |
| 1    | Vertical                                                                                                                                                                     | Fundamental                                                                                                                                                              |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 VERTICAL</p></div>   | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_9120D_1522 VERTICAL</p></div> |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 VERTICAL</p></div> | Left blank                                                                                                                                                               |



| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                         |                                                                                                                                                                            |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH78 2480MHz                                                                                                                                                              |                                                                                                                                                                            |
| 1    | Horizontal                                                                                                                                                                   | Fundamental                                                                                                                                                                |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_91200_1522 HORIZONTAL</p></div> | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_91200_1522 HORIZONTAL</p></div> |



| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                       |                                                                                                                                                                          |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH78 2480MHz                                                                                                                                                            |                                                                                                                                                                          |
| 1    | Vertical                                                                                                                                                                   | Fundamental                                                                                                                                                              |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 VERTICAL</p></div> | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_9120D_1522 VERTICAL</p></div> |



2.4GHz 2400~2483.5MHz



BT (2M) (Harmonic @ 3m)

| BT           | 2.4GHz 2400~2483.5MHz Harmonic @ 3m                                        |                                                                          |
|--------------|----------------------------------------------------------------------------|--------------------------------------------------------------------------|
| ANT          | BT CH00 2402MHz                                                            |                                                                          |
| 1            | Horizontal                                                                 | Vertical                                                                 |
| Peak<br>Avg. | <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL</p> | <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 VERTICAL</p> |





| BT           | 2.4GHz 2400~2483.5MHz Harmonic @ 3m                                                                                                                     |                                                                                                                                                       |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT          | BT CH39 2441MHz                                                                                                                                         |                                                                                                                                                       |
| 1            | Horizontal                                                                                                                                              | Vertical                                                                                                                                              |
| Peak<br>Avg. | <div><p>Level (dBuV/m)</p><p>Date: 2017-05-22</p><p>Frequency (MHz)</p><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL</p></div> | <div><p>Level (dBuV/m)</p><p>Date: 2017-05-22</p><p>Frequency (MHz)</p><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 VERTICAL</p></div> |





| BT           | 2.4GHz 2400~2483.5MHz Harmonic @ 3m                                                                                                                          |                                                                                                                                                             |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT          | BT CH78 2480MHz                                                                                                                                              |                                                                                                                                                             |
| 1            | Horizontal                                                                                                                                                   | Vertical                                                                                                                                                    |
| Peak<br>Avg. |  <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL</p> |  <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 VERTICAL</p> |




**2.4GHz 2400~2483.5MHz**
**BT (3M) (Band Edge @ 3m)**

| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                               |                                                                                                                                                                  |
|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH00 2402MHz                                                                                                                                                    |                                                                                                                                                                  |
| 1    | Horizontal                                                                                                                                                         | Fundamental                                                                                                                                                      |
| Peak |  <p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 HORIZONTAL</p> |  <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_9120D_1522 HORIZONTAL</p> |






| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                       |                                                                                                                                                                          |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH00 2402MHz                                                                                                                                                            |                                                                                                                                                                          |
| 1    | Vertical                                                                                                                                                                   | Fundamental                                                                                                                                                              |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_91200_1522 VERTICAL</p></div> | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_91200_1522 VERTICAL</p></div> |





| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                           |                                                                                                                                                                            |
|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH39 2441MHz                                                                                                                                                                |                                                                                                                                                                            |
| 1    | Horizontal                                                                                                                                                                     | Fundamental                                                                                                                                                                |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 HORIZONTAL</p></div>   | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_9120D_1522 HORIZONTAL</p></div> |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 HORIZONTAL</p></div> | Left blank                                                                                                                                                                 |





| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                         |                                                                                                                                                                          |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH39 2441MHz                                                                                                                                                              |                                                                                                                                                                          |
| 1    | Vertical                                                                                                                                                                     | Fundamental                                                                                                                                                              |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 VERTICAL</p></div>   | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_9120D_1522 VERTICAL</p></div> |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 VERTICAL</p></div> | Left blank                                                                                                                                                               |



| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                         |                                                                                                                                                                            |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH78 2480MHz                                                                                                                                                              |                                                                                                                                                                            |
| 1    | Horizontal                                                                                                                                                                   | Fundamental                                                                                                                                                                |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_91200_1522 HORIZONTAL</p></div> | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_91200_1522 HORIZONTAL</p></div> |





| BT   | 2.4GHz 2400~2483.5MHz Band Edge @ 3m                                                                                                                                       |                                                                                                                                                                          |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT  | BT CH78 2480MHz                                                                                                                                                            |                                                                                                                                                                          |
| 1    | Vertical                                                                                                                                                                   | Fundamental                                                                                                                                                              |
| Peak | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_BE_74 3m HORN_9120D_1522 VERTICAL</p></div> | <div><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m HORN_9120D_1522 VERTICAL</p></div> |



## 2.4GHz 2400~2483.5MHz

## BT (3M) (Harmonic @ 3m)

| BT           | 2.4GHz 2400~2483.5MHz Harmonic @ 3m                                                                                                                          |                                                                                                                                                             |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT          | BT CH00 2402MHz                                                                                                                                              |                                                                                                                                                             |
| 1            | Horizontal                                                                                                                                                   | Vertical                                                                                                                                                    |
| Peak<br>Avg. |  <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL</p> |  <p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 VERTICAL</p> |



| BT           | 2.4GHz 2400~2483.5MHz Harmonic @ 3m                                                                                                                     |                                                                                                                                                       |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT          | BT CH39 2441MHz                                                                                                                                         |                                                                                                                                                       |
| 1            | Horizontal                                                                                                                                              | Vertical                                                                                                                                              |
| Peak<br>Avg. | <div><p>Level (dBuV/m)</p><p>Date: 2017-05-22</p><p>Frequency (MHz)</p><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL</p></div> | <div><p>Level (dBuV/m)</p><p>Date: 2017-05-22</p><p>Frequency (MHz)</p><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 VERTICAL</p></div> |





| BT           | 2.4GHz 2400~2483.5MHz Harmonic @ 3m                                                                                                                     |                                                                                                                                                       |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT          | BT CH78 2480MHz                                                                                                                                         |                                                                                                                                                       |
| 1            | Horizontal                                                                                                                                              | Vertical                                                                                                                                              |
| Peak<br>Avg. | <div><p>Level (dBuV/m)</p><p>Date: 2017-05-22</p><p>Frequency (MHz)</p><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 HORIZONTAL</p></div> | <div><p>Level (dBuV/m)</p><p>Date: 2017-05-22</p><p>Frequency (MHz)</p><p>Site : 03CH13-HY<br/>Condition : PEAK_74 3m SHF_HORN_584 VERTICAL</p></div> |



Emission below 1GHz

2.4GHz BT (LF)

| BT           | 2.4GHz 2400~2483.5MHz                                                                                                                                   |                                                                                                                                                        |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| ANT          | BT LF                                                                                                                                                   |                                                                                                                                                        |
| 1            | Horizontal                                                                                                                                              | Vertical                                                                                                                                               |
| QP /<br>Peak |  <p>Site : 03CH13-1FY<br/>Condition : QP 3m BILOG_40103 HORIZONTAL</p> |  <p>Site : 03CH13-1FY<br/>Condition : QP 3m BILOG_40103 VERTICAL</p> |
|              |                                                                                                                                                         |                                                                                                                                                        |