




FCC SAR TEST REPORT

FCC ID : PY7-80422D
Brand Name : Sony
Applicant : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa,
Shinagawa-ku, Tokyo, 140-0002, Japan
Manufacturer : Sony Mobile Communications Inc.
4-12-3 Higashi-Shinagawa,
Shinagawa-ku, Tokyo, 140-0002, Japan
Standard : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

The product was received on Feb. 12, 2019 and testing was started from Mar. 06, 2019 and completed on Mar. 27, 2019. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	4
3. Equipment Under Test (EUT) Information.....	5
3.1 General Information	5
3.2 Device Serial Number	5
3.3 General LTE SAR Test and Reporting Considerations	6
4. RF Exposure Limits.....	8
4.1 Uncontrolled Environment.....	8
4.2 Controlled Environment.....	8
5. Specific Absorption Rate (SAR).....	9
5.1 Introduction	9
5.2 SAR Definition.....	9
6. System Description and Setup	10
6.1 E-Field Probe	11
6.2 Data Acquisition Electronics (DAE)	11
6.3 Phantom.....	12
6.4 Device Holder.....	13
7. Measurement Procedures	14
7.1 Spatial Peak SAR Evaluation.....	14
7.2 Power Reference Measurement.....	15
7.3 Area Scan	15
7.4 Zoom Scan.....	16
7.5 Volume Scan Procedures.....	16
7.6 Power Drift Monitoring.....	16
8. Test Equipment List.....	17
9. System Verification	18
9.1 Tissue Simulating Liquids.....	18
9.2 Tissue Verification	19
9.3 System Performance Check Results.....	20
10. RF Exposure Positions	22
10.1 Ear and handset reference point.....	22
10.2 Definition of the cheek position	23
10.3 Definition of the tilt position	24
10.4 Body Worn Accessory	24
10.5 Product Specific Exposure	25
10.6 Wireless Router.....	25
11. Conducted RF Output Power (Unit: dBm).....	26
12. RF Exposure Conditions	52
13. SAR Test Results	53
13.1 Head SAR	55
13.2 Hotspot SAR	57
13.3 Body Worn Accessory SAR.....	60
13.4 Product Specific SAR.....	62
14. Simultaneous Transmission Analysis.....	63
14.1 Head Exposure Conditions	64
14.2 Hotspot Exposure Conditions.....	65
14.3 Body-Worn Accessory Exposure Conditions	66
14.4 Product Specific Exposure Conditions	66
15. Uncertainty Assessment	67
16. References.....	67
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	



History of this test report

Report No.	Version	Description	Issued Date
FA8O2425-03	01	Initial issue of report	Apr. 3, 2019



1. Statement of Compliance

Applicant Name	Sony Mobile Communications Inc.			
EUT Description	GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac, GPS and NFC			
Brand Name	Sony			
FCC ID	PY7-80422D			
HW Version	AP			
SW Version	0.203			
RF Exposure Conditions	Equipment Class			
	Licensed	DTS	NII	DSS
Head (1g SAR W/kg)	0.38	0.36	0.25	0.20
Body-Worn (1g SAR W/kg)	0.29	0.06	0.14	0.01
Wireless Router (1g SAR W/kg)	0.74	0.17		0.05
Product Specific (10g SAR W/kg)			0.53	
Highest Simultaneous Transmission (1g SAR W/kg)	Head: 0.92 Body-worn: 0.47 Hotspot: 0.74	Head: 0.92 Body-worn: 0.47 Hotspot: 0.74	Head: 0.92 Body-worn: 0.47 Hotspot: N/A	Head: 0.88 Body-worn: 0.46 Hotspot: 0.74
Highest Simultaneous Transmission (10g SAR W/kg)			Product Specific: 0.96	
Date Tested	2019/3/6 ~ 2019/3/27			
Test Result	Pass			
Remark:				
1. This device 2.4GHz WLAN support Hotspot operation and Bluetooth support tethering applications.				

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body, 4.0 W/kg for Product Specific) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

Reviewed by: Jason Wang
Report Producer: Wan Liu

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D05A Rel.10 LTE SAR Test Guidance v01r02
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01
- FCC KDB 941 225 D07 UMPC Mini Tablet v01r02

3. Equipment Under Test (EUT) Information

3.1 General Information

Wireless Technologies	Frequency	Operating Mode	
GSM	850 1900	· GSM Voice · GPRS (GMSK) · EDGE (8PSK)	Multi-Slot Class: Class 33
	Does device support dual transfer mode? (Yes)		
W-CDMA (UMTS)	Band 2 Band 4	· UMTS Rel.99(Voice & Data) · HSDPA Rel.5 · HSUPA Rel.6 · HSPA+ Rel.7 (downlink only)	
LTE (FDD)	Band 2 Band 4 Band 12 Band 17	· QPSK · 16QAM · 64QAM · Rel 14 Carrier Aggregation Downlink Only (the detail refer to section 11)	
LTE (TDD)	Band 41		
WiFi	2.4GHz: 2412 MHz ~ 2472 MHz	· 11b · 11g · 11n (HT20)	
	5GHz: 5.2GHz: 5180 MHz ~ 5240 MHz 5.3GHz: 5260 MHz ~ 5320 MHz 5.5GHz: 5500 MHz ~ 5720 MHz 5.8GHz: 5745 MHz ~ 5825 MHz	· 11a · 11n (HT20) · 11n (HT40) · 11ac (VHT20) · 11ac (VHT40) · 11ac (VHT80)	
Bluetooth	2.4GHz	· BR / EDR / LE	
NFC	13.56MHz	· ASK	

3.2 Device Serial Number

Band	SN
WWAN	BH9700C1FY BH970025FY BH98009Nfy
WLAN	BH9700C9FY BH97003LFY BH9700C6FY

Note: Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device tested gave the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

3.3 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05								
FCC ID	PY7-80422D							
Operating Frequency Range of each LTE transmission band	LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 41: 2498.5 MHz ~ 2687.5 MHz							
Channel Bandwidth	LTE Band 02:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 04:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 12:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 17: 5MHz, 10MHz LTE Band 41: 5MHz, 10MHz, 15MHz, 20MHz							
uplink modulations used	QPSK / 16QAM / 64QAM							
LTE Voice / Data requirements	Voice and Data							
LTE MPR permanently built-in by design	Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3							
	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})					MPR (dB)	
		1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz		20 MHz
	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
	256 QAM	≥ 1					≤ 5	
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)							
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.							
LTE Carrier Aggregation Combinations	Intra-Band possible combinations and the detail power measurement please referred to section 11.							
LTE Carrier Aggregation Additional Information	This device supports maximum of 2 carriers in the downlink only. Additional following LTE Release features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.							

Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 12												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	23017	699.7	23025	700.5	23035	701.5	23060	704				
M	23095	707.5	23095	707.5	23095	707.5	23095	707.5				
H	23173	715.3	23165	714.5	23155	713.5	23130	711				
LTE Band 17												
	Bandwidth 5 MHz				Bandwidth 10 MHz							
	Channel #		Freq.(MHz)		Channel #		Freq. (MHz)					
L	23755		706.5		23780		709					
M	23790		710		23790		710					
H	23825		713.5		23800		711					
LTE Band 41												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz					
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	39675	2498.5	39700	2501	39725	2503.5	39750	2506				
L	40148	2545.8	40160	2547	40173	2548.3	40185	2549.5				
M	40620	2593	40620	2593	40620	2593	40620	2593				
H	41093	2640.3	41080	2639	41068	2637.8	41055	2636.5				
H	41565	2687.5	41540	2685	41515	2682.5	41490	2680				



4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

6.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	750MHz System Validation Kit	D750V3	1012	Sep. 05, 2018	Sep. 04, 2019
SPEAG	835MHz System Validation Kit	D835V2	499	Sep. 06, 2018	Sep. 05, 2019
SPEAG	1750MHz System Validation Kit	D1750V2	1068	Nov. 19, 2018	Nov. 18, 2019
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Sep. 11, 2018	Sep. 10, 2019
SPEAG	2450MHz System Validation Kit	D2450V2	736	Aug. 31, 2018	Aug. 30, 2019
SPEAG	2600MHz System Validation Kit	D2600V2	1008	Aug. 31, 2018	Aug. 30, 2019
SPEAG	5GHz System Validation Kit	D5GHzV2	1006	Sep. 27, 2018	Sep. 26, 2019
SPEAG	Data Acquisition Electronics	DAE4	316	Jan. 03, 2019	Jan. 02, 2020
SPEAG	Data Acquisition Electronics	DAE4	699	Jan. 03, 2019	Jan. 02, 2020
SPEAG	Data Acquisition Electronics	DAE4	918	Jun. 20, 2018	Jun. 19, 2019
SPEAG	Data Acquisition Electronics	DAE4	1326	Sep. 18, 2018	Sep. 17, 2019
SPEAG	Dosimetric E-Field Probe	ES3DV3	3124	Jan. 15, 2019	Jan. 14, 2020
SPEAG	Dosimetric E-Field Probe	ES3DV3	3169	May. 28, 2018	May. 27, 2019
SPEAG	Dosimetric E-Field Probe	EX3DV4	3728	Jan. 15, 2019	Jan. 14, 2020
SPEAG	Dosimetric E-Field Probe	EX3DV4	7515	Oct. 03, 2018	Oct. 02, 2019
RCPTWN	Thermometer	HTC-1	TM685-1	Nov. 12, 2018	Nov. 11, 2019
RCPTWN	Thermometer	HTC-1	TM560-2	Nov. 12, 2018	Nov. 11, 2019
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Apr. 17, 2018	Apr. 16, 2019
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 21, 2018	May. 20, 2019
R&S	BT Base Station(Measure)	CBT32	100519	May. 30, 2018	May. 29, 2019
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Dec. 11, 2018	Dec. 10, 2019
Agilent	ENA Network Analyzer	E5071C	MY46104758	Sep. 19, 2018	Sep. 18, 2019
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 19, 2018	Sep. 18, 2019
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3169	Sep. 11, 2018	Sep. 10, 2019
Anritsu	Power Meter	ML2495A	1419002	May. 18, 2018	May. 17, 2019
Anritsu	Power Sensor	MA2411B	1339124	May. 18, 2018	May. 17, 2019
Anritsu	Power Meter	ML2495A	1240001	Sep. 13, 2018	Sep. 12, 2019
Anritsu	Power Sensor	MA2411B	1207349	Sep. 13, 2018	Sep. 12, 2019
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 28, 2018	Aug. 27, 2019
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 23, 2018	Jun. 22, 2019
Mini-Circuits	Power Amplifier	ZVE-8G+	6382	Aug. 09, 2018	Aug. 08, 2019
Mini-Circuits	Power Amplifier	ZHL-42W+	15542	Aug. 09, 2018	Aug. 08, 2019
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

9. System Verification

9.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.




Fig 10.1 Photo of Liquid Height for Head SAR




Fig 10.2 Photo of Liquid Height for Body SAR

9.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
750	HSL	22.8	0.891	43.513	0.89	41.90	0.11	3.85	±5	2019/3/11
750	MSL	22.8	0.969	54.123	0.96	55.50	0.94	-2.48	±5	2019/3/9
835	HSL	22.8	0.900	42.398	0.90	41.50	0.00	2.16	±5	2019/3/11
835	MSL	22.8	0.981	57.574	0.97	55.20	1.13	4.30	±5	2019/3/9
1750	HSL	22.6	1.409	40.982	1.37	40.10	2.85	2.20	±5	2019/3/6
1750	MSL	22.6	1.484	55.128	1.49	53.40	-0.40	3.24	±5	2019/3/8
1900	HSL	22.6	1.458	41.063	1.40	40.00	4.14	2.66	±5	2019/3/6
1900	MSL	22.6	1.567	53.492	1.52	53.30	3.09	0.36	±5	2019/3/8
2450	HSL	22.5	1.746	38.118	1.80	39.20	-3.00	-2.76	±5	2019/3/13
2450	MSL	22.5	2.007	52.975	1.95	52.70	2.92	0.52	±5	2019/3/13
2600	HSL	22.7	1.967	39.225	1.96	39.00	0.36	0.58	±5	2019/3/7
2600	MSL	22.6	2.149	51.589	2.16	52.50	-0.51	-1.74	±5	2019/3/27
5250	HSL	22.1	4.517	36.791	4.71	35.95	-4.10	2.34	±5	2019/3/9
5250	MSL	22.7	5.450	47.192	5.36	48.95	1.68	-3.59	±5	2019/3/11
5600	HSL	22.1	4.853	36.279	5.07	35.50	-4.28	2.19	±5	2019/3/9
5600	MSL	22.7	5.905	46.550	5.77	48.50	2.34	-4.02	±5	2019/3/11
5750	HSL	22.1	5.015	36.059	5.22	35.35	-3.93	2.01	±5	2019/3/9
5750	MSL	22.7	6.105	46.281	5.94	48.28	2.78	-4.14	±5	2019/3/11

9.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2019/3/11	750	HSL	250	D750V3-1012	ES3DV3 - SN3124	DAE4 Sn699	2.27	8.47	9.08	7.20
2019/3/9	750	MSL	250	D750V3-1012	ES3DV3 - SN3124	DAE4 Sn699	2.10	8.76	8.4	-4.11
2019/3/11	835	HSL	250	D835V2-499	ES3DV3 - SN3124	DAE4 Sn699	2.53	9.59	10.12	5.53
2019/3/9	835	MSL	250	D835V2-499	ES3DV3 - SN3124	DAE4 Sn699	2.44	9.82	9.76	-0.61
2019/3/6	1750	HSL	250	D1750V2-1068	ES3DV3 - SN3169	DAE4 Sn1326	9.38	37.10	37.52	1.13
2019/3/8	1750	MSL	250	D1750V2-1068	EX3DV4 - SN3728	DAE4 Sn316	8.75	37.00	35	-5.41
2019/3/6	1900	HSL	250	D1900V2-5d041	ES3DV3 - SN3169	DAE4 Sn1326	10.70	40.20	42.8	6.47
2019/3/8	1900	MSL	250	D1900V2-5d041	EX3DV4 - SN3728	DAE4 Sn316	10.20	40.20	40.8	1.49
2019/3/13	2450	HSL	250	D2450V2-736	EX3DV4 - SN7515	DAE4 Sn918	13.20	52.70	52.8	0.19
2019/3/13	2450	MSL	250	D2450V2-736	EX3DV4 - SN7515	DAE4 Sn918	12.40	51.50	49.6	-3.69
2019/3/7	2600	HSL	250	D2600V2-1008	ES3DV3 - SN3169	DAE4 Sn1326	13.30	56.40	53.2	-5.67
2019/3/27	2600	MSL	250	D2600V2-1008	ES3DV3 - SN3169	DAE4 Sn1326	13.80	55.30	55.2	-0.18
2019/3/9	5250	HSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	7.48	80.70	74.8	-7.31
2019/3/11	5250	MSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	7.98	78.30	79.8	1.92
2019/3/9	5600	HSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	8.37	83.30	83.7	0.48
2019/3/11	5600	MSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	8.01	81.00	80.1	-1.11
2019/3/9	5750	HSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	8.58	80.40	85.8	6.72
2019/3/11	5750	MSL	100	D5GHZV2-1006	EX3DV4 - SN7515	DAE4 Sn918	7.39	77.40	73.9	-4.52

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2019/3/11	5250	MSL	100	D5GHzV2-1006	EX3DV4 - SN7515	DAE4 Sn918	2.28	21.70	22.8	5.07
2019/3/11	5600	MSL	100	D5GHzV2-1006	EX3DV4 - SN7515	DAE4 Sn918	2.21	22.50	22.1	-1.78
2019/3/11	5750	MSL	100	D5GHzV2-1006	EX3DV4 - SN7515	DAE4 Sn918	2.00	21.30	20	-6.10



Fig 8.3.1 System Performance Check Setup

Fig 8.3.2 Setup Photo

10. RF Exposure Positions

10.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

10.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 9.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

10.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

10.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position



10.5 Product Specific Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.⁶ The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

10.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9$ cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

11. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

- For DTM multi-slot class mode, the device was linked with base station simulator (Agilent E5515C) and transmit maximum power on maximum number of TX slots, i.e. one CS timeslot, and additional PS timeslots (1 for DTM class 5 and 9, 2 for DTM class 11) in one TDMA frame.
- Agilent E5515C was used to setup the device operated under DTM mode for power measurement and SAR testing. For conducted power, the power of the burst for voice and the power of the bursts for data was reported separately in the table above, and the frame-average power is derived below to determine SAR testing.

$$DTM \text{ frame average power (dBm)} = 10 * \log [\sum (\text{power of each slot, in mW}) / 8]$$

- Per KDB 447498 D01v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.
- Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE / DTM modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
- Other configurations of GSM / GPRS / EDGE / DTM are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode

GSM850		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		128	189	251		128	189	251	
Frequency (MHz)		824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot		31.71	31.56	31.55	32.20	22.71	22.56	22.55	23.20
GPRS 1 Tx slot		31.77	31.64	31.61	32.20	22.77	22.64	22.61	23.20
GPRS 2 Tx slots		29.58	29.01	29.09	30.20	23.58	23.01	23.09	24.20
GPRS 3 Tx slots		27.62	27.27	27.31	28.20	23.36	23.01	23.05	23.94
GPRS 4 Tx slots		26.81	26.50	26.48	27.20	23.81	23.50	23.48	24.20
EDGE 1 Tx slot		27.13	27.23	27.05	28.00	18.13	18.23	18.05	19.00
EDGE 2 Tx slots		25.59	25.45	25.54	26.50	19.59	19.45	19.54	20.50
EDGE 3 Tx slots		23.42	23.58	23.33	24.50	19.16	19.32	19.07	20.24
EDGE 4 Tx slots		22.56	22.56	22.22	23.50	19.56	19.56	19.22	20.50
DTM Multi-slot class 5	GSM 1 Tx slot	29.49	29.14	29.18	30.20	23.39	23.08	23.05	24.18
	GPRS 1 Tx slot	29.33	29.06	28.96	30.20				
DTM Multi-slot class 9	GSM 1 Tx slot	29.42	29.21	29.08	30.20	23.34	23.12	23.04	24.18
	GPRS 1 Tx slot	29.31	29.07	29.04	30.20				
DTM Multi-slot class 11	GSM 1 Tx slot	27.30	27.31	27.24	28.20	23.12	22.95	22.98	23.94
	GPRS 2 Tx slots	27.42	27.16	27.24	28.20				
DTM Multi-slot class 5	GSM 1 Tx slot	29.33	29.11	29.04	30.20	21.79	21.62	21.52	22.71
	EDGE 1 Tx slot	25.45	25.40	25.23	26.50				
DTM Multi-slot class 9	GSM 1 Tx slot	29.39	29.27	29.17	30.20	21.81	21.73	21.58	22.71
	EDGE 1 Tx slot	25.39	25.40	25.13	26.50				
DTM Multi-slot class 11	GSM 1 Tx slot	27.44	27.22	27.30	28.20	20.92	20.75	20.75	21.85
	EDGE 2 Tx slots	23.37	23.26	23.15	24.50				

GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot		26.62	26.96	26.96	27.70	17.62	17.96	17.96	18.70
GPRS 1 Tx slot		26.53	26.96	26.98	27.70	17.53	17.96	17.98	18.70
GPRS 2 Tx slots		24.64	24.97	24.93	25.70	18.64	18.97	18.93	19.70
GPRS 3 Tx slots		22.58	22.97	22.90	23.70	18.32	18.71	18.64	19.44
GPRS 4 Tx slots		21.53	21.99	21.88	22.70	18.53	18.99	18.88	19.70
EDGE 1 Tx slot		25.43	25.86	25.79	27.00	16.43	16.86	16.79	18.00
EDGE 2 Tx slots		24.03	24.07	24.11	25.50	18.03	18.07	18.11	19.50
EDGE 3 Tx slots		22.16	22.25	22.11	23.50	17.90	17.99	17.85	19.24
EDGE 4 Tx slots		21.06	21.33	21.25	22.50	18.06	18.33	18.25	19.50
DTM Multi-slot class 5	GSM 1 Tx slot	24.63	25.10	24.95	25.70	18.53	19.00	18.87	19.68
	GPRS 1 Tx slot	24.46	24.93	24.83	25.70				
DTM Multi-slot class 9	GSM 1 Tx slot	24.74	25.19	25.09	25.70	18.60	19.07	18.96	19.68
	GPRS 1 Tx slot	24.50	24.98	24.87	25.70				
DTM Multi-slot class 11	GSM 1 Tx slot	22.71	23.21	23.25	23.70	18.38	18.80	18.83	19.44
	GPRS 2 Tx slots	22.60	22.99	23.01	23.70				
DTM Multi-slot class 5	GSM 1 Tx slot	24.40	24.98	24.78	25.70	18.21	18.76	18.63	19.58
	EDGE 1 Tx slot	24.06	24.57	24.52	25.50				
DTM Multi-slot class 9	GSM 1 Tx slot	24.65	25.12	25.07	25.70	18.27	18.71	18.70	19.58
	EDGE 1 Tx slot	23.89	24.30	24.34	25.50				
DTM Multi-slot class 11	GSM 1 Tx slot	22.51	23.04	22.88	23.70	17.96	18.47	18.31	19.31
	EDGE 2 Tx slots	22.06	22.56	22.40	23.50				

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_d/\beta_c = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration

<WCDMA Conducted Power>
General Note:


1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA.

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513	
Rx Channel		9662	9800	9938		1537	1638	1738	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6	
3GPP Rel 99	AMR 12.2Kbps	18.38	18.51	18.41	18.70	18.68	18.62	18.57	18.70
3GPP Rel 99	RMC 12.2Kbps	18.41	18.53	18.42	18.70	18.69	18.65	18.60	18.70
3GPP Rel 6	HSDPA Subtest-1	17.43	17.67	17.53	18.00	17.72	17.62	17.60	18.00
3GPP Rel 6	HSDPA Subtest-2	17.40	17.68	17.52	18.00	17.70	17.64	17.59	18.00
3GPP Rel 6	HSDPA Subtest-3	16.91	17.15	17.01	17.50	17.17	17.16	17.13	17.50
3GPP Rel 6	HSDPA Subtest-4	16.88	17.17	17.02	17.50	17.19	17.14	17.12	17.50
3GPP Rel 6	HSUPA Subtest-1	17.48	17.62	17.41	18.00	17.72	17.61	17.56	18.00
3GPP Rel 6	HSUPA Subtest-2	15.32	15.58	15.42	16.00	15.66	15.63	15.52	16.00
3GPP Rel 6	HSUPA Subtest-3	16.22	16.57	16.42	17.00	16.63	16.55	16.54	17.00
3GPP Rel 6	HSUPA Subtest-4	15.33	15.60	15.46	16.00	15.70	15.68	15.57	16.00
3GPP Rel 6	HSUPA Subtest-5	17.40	17.60	17.40	18.00	17.70	17.60	17.48	18.00


<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4/B12 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 17 SAR test was covered by Band 12; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM



<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	18.72	18.78	18.72	19	0
20	QPSK	1	49	18.57	18.67	18.59		
20	QPSK	1	99	18.63	18.68	18.61		
20	QPSK	50	0	18.78	18.90	18.82	19	0
20	QPSK	50	24	18.80	18.89	18.80		
20	QPSK	50	50	18.79	18.86	18.86		
20	QPSK	100	0	18.81	18.86	18.82	19	0
20	16QAM	1	0	18.43	18.50	18.48		
20	16QAM	1	49	18.32	18.44	18.34		
20	16QAM	1	99	18.37	18.48	18.40	19	0
20	16QAM	50	0	18.31	18.38	18.31		
20	16QAM	50	24	18.30	18.40	18.32		
20	16QAM	50	50	18.31	18.39	18.34	19	0
20	16QAM	100	0	18.31	18.37	18.29		
20	64QAM	1	0	18.43	18.49	18.46		
20	64QAM	1	49	18.36	18.44	18.34	19	0
20	64QAM	1	99	18.34	18.47	18.40		
20	64QAM	50	0	18.33	18.40	18.33		
20	64QAM	50	24	18.34	18.40	18.34	19	0
20	64QAM	50	50	18.33	18.44	18.36		
20	64QAM	100	0	18.32	18.40	18.35		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	18.69	18.74	18.73	19	0
15	QPSK	1	37	18.65	18.74	18.69		
15	QPSK	1	74	18.69	18.71	18.66		
15	QPSK	36	0	18.79	18.86	18.80	19	0
15	QPSK	36	20	18.80	18.89	18.84		
15	QPSK	36	39	18.79	18.89	18.82		
15	QPSK	75	0	18.81	18.87	18.82	19	0
15	16QAM	1	0	18.50	18.49	18.49		
15	16QAM	1	37	18.42	18.52	18.43		
15	16QAM	1	74	18.49	18.49	18.47	19	0
15	16QAM	36	0	18.29	18.35	18.30		
15	16QAM	36	20	18.32	18.40	18.31		
15	16QAM	36	39	18.29	18.39	18.35	19	0
15	16QAM	75	0	18.32	18.37	18.33		
15	64QAM	1	0	18.50	18.48	18.46		
15	64QAM	1	37	18.39	18.50	18.40	19	0
15	64QAM	1	74	18.41	18.46	18.47		
15	64QAM	36	0	18.33	18.41	18.35		
15	64QAM	36	20	18.36	18.45	18.36	19	0
15	64QAM	36	39	18.34	18.45	18.37		
15	64QAM	75	0	18.33	18.40	18.33		

Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	18.58	18.63	18.71	19	0
10	QPSK	1	25	18.62	18.70	18.57		
10	QPSK	1	49	18.55	18.61	18.52		
10	QPSK	25	0	18.75	18.79	18.74	19	0
10	QPSK	25	12	18.77	18.80	18.77		
10	QPSK	25	25	18.68	18.75	18.71		
10	QPSK	50	0	18.74	18.79	18.73		
10	16QAM	1	0	18.37	18.37	18.48	19	0
10	16QAM	1	25	18.43	18.45	18.33		
10	16QAM	1	49	18.31	18.44	18.32		
10	16QAM	25	0	18.25	18.31	18.24	19	0
10	16QAM	25	12	18.27	18.32	18.26		
10	16QAM	25	25	18.18	18.24	18.54		
10	16QAM	50	0	18.22	18.28	18.24		
10	64QAM	1	0	18.34	18.37	18.47	19	0
10	64QAM	1	25	18.40	18.44	18.33		
10	64QAM	1	49	18.35	18.38	18.35		
10	64QAM	25	0	18.28	18.32	18.26	19	0
10	64QAM	25	12	18.28	18.36	18.30		
10	64QAM	25	25	18.23	18.24	18.23		
10	64QAM	50	0	18.26	18.29	18.26		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	18.51	18.56	18.53	19	0
5	QPSK	1	12	18.60	18.70	18.64		
5	QPSK	1	24	18.60	18.64	18.63		
5	QPSK	12	0	18.64	18.70	18.66	19	0
5	QPSK	12	7	18.76	18.84	18.81		
5	QPSK	12	13	18.75	18.83	18.74		
5	QPSK	25	0	18.72	18.78	18.67		
5	16QAM	1	0	18.29	18.37	18.31	19	0
5	16QAM	1	12	18.38	18.48	18.43		
5	16QAM	1	24	18.40	18.46	18.38		
5	16QAM	12	0	18.16	18.23	18.19	19	0
5	16QAM	12	7	18.31	18.37	18.33		
5	16QAM	12	13	18.26	18.37	18.26		
5	16QAM	25	0	18.24	18.32	18.18		
5	64QAM	1	0	18.23	18.30	18.31	19	0
5	64QAM	1	12	18.36	18.42	18.38		
5	64QAM	1	24	18.39	18.40	18.35		
5	64QAM	12	0	18.20	18.28	18.23	19	0
5	64QAM	12	7	18.34	18.41	18.33		
5	64QAM	12	13	18.31	18.42	18.35		
5	64QAM	25	0	18.27	18.31	18.24		



FCC SAR TEST REPORT

Report No. : FA8O2425-03

Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	18.49	18.57	18.61	19	0
3	QPSK	1	8	18.69	18.76	18.69		
3	QPSK	1	14	18.63	18.69	18.60		
3	QPSK	8	0	18.67	18.66	18.67	19	0
3	QPSK	8	4	18.73	18.81	18.75		
3	QPSK	8	7	18.72	18.80	18.70		
3	QPSK	15	0	18.72	18.79	18.72		
3	16QAM	1	0	18.27	18.33	18.32	19	0
3	16QAM	1	8	18.43	18.55	18.49		
3	16QAM	1	14	18.36	18.48	18.41		
3	16QAM	8	0	18.21	18.26	18.24	19	0
3	16QAM	8	4	18.28	18.34	18.31		
3	16QAM	8	7	18.30	18.32	18.30		
3	16QAM	15	0	18.24	18.31	18.25		
3	64QAM	1	0	18.23	18.29	18.29	19	0
3	64QAM	1	8	18.42	18.54	18.46		
3	64QAM	1	14	18.36	18.48	18.38		
3	64QAM	8	0	18.23	18.22	18.29	19	0
3	64QAM	8	4	18.31	18.38	18.33		
3	64QAM	8	7	18.30	18.38	18.29		
3	64QAM	15	0	18.24	18.32	18.28		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	18.43	18.53	18.46	19	0
1.4	QPSK	1	3	18.60	18.69	18.59		
1.4	QPSK	1	5	18.53	18.61	18.56		
1.4	QPSK	3	0	18.53	18.60	18.55		
1.4	QPSK	3	1	18.58	18.65	18.56		
1.4	QPSK	3	3	18.55	18.64	18.55		
1.4	QPSK	6	0	18.64	18.71	18.63	19	0
1.4	16QAM	1	0	18.19	18.30	18.31	19	0
1.4	16QAM	1	3	18.37	18.46	18.41		
1.4	16QAM	1	5	18.29	18.50	18.31		
1.4	16QAM	3	0	18.13	18.13	18.08		
1.4	16QAM	3	1	18.16	18.18	18.14		
1.4	16QAM	3	3	18.11	18.20	18.08		
1.4	16QAM	6	0	18.21	18.27	18.23	19	0
1.4	64QAM	1	0	18.17	18.28	18.24	19	0
1.4	64QAM	1	3	18.37	18.39	18.33		
1.4	64QAM	1	5	18.29	18.33	18.29		
1.4	64QAM	3	0	18.28	18.31	18.23		
1.4	64QAM	3	1	18.33	18.37	18.29		
1.4	64QAM	3	3	18.27	18.32	18.29		
1.4	64QAM	6	0	18.15	18.22	18.18	19	0

<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	18.67	18.73	18.83		
20	QPSK	1	49	18.67	18.73	18.72	19	0
20	QPSK	1	99	18.63	18.66	18.74		
20	QPSK	50	0	18.87	18.93	18.91		
20	QPSK	50	24	18.84	18.92	18.90	19	0
20	QPSK	50	50	18.83	18.89	18.84		
20	QPSK	100	0	18.83	18.90	18.87		
20	16QAM	1	0	18.34	18.46	18.57	19	0
20	16QAM	1	49	18.36	18.47	18.49		
20	16QAM	1	99	18.34	18.44	18.54		
20	16QAM	50	0	18.36	18.40	18.40	19	0
20	16QAM	50	24	18.36	18.40	18.40		
20	16QAM	50	50	18.31	18.37	18.34		
20	16QAM	100	0	18.31	18.38	18.33	19	0
20	64QAM	1	0	18.38	18.42	18.57		
20	64QAM	1	49	18.33	18.46	18.45		
20	64QAM	1	99	18.35	18.44	18.53	19	0
20	64QAM	50	0	18.38	18.41	18.41		
20	64QAM	50	24	18.37	18.38	18.41		
20	64QAM	50	50	18.33	18.36	18.37	19	0
20	64QAM	100	0	18.34	18.39	18.36		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	18.74	18.72	18.79		
15	QPSK	1	37	18.66	18.80	18.76	19	0
15	QPSK	1	74	18.67	18.74	18.82		
15	QPSK	36	0	18.86	18.92	18.90	19	0
15	QPSK	36	20	18.86	18.92	18.92		
15	QPSK	36	39	18.83	18.90	18.85		
15	QPSK	75	0	18.84	18.89	18.88	19	0
15	16QAM	1	0	18.48	18.49	18.62		
15	16QAM	1	37	18.42	18.53	18.56		
15	16QAM	1	74	18.41	18.51	18.64	19	0
15	16QAM	36	0	18.33	18.37	18.37		
15	16QAM	36	20	18.34	18.41	18.38		
15	16QAM	36	39	18.29	18.35	18.34	19	0
15	16QAM	75	0	18.34	18.37	18.37		
15	64QAM	1	0	18.47	18.49	18.64		
15	64QAM	1	37	18.38	18.48	18.57	19	0
15	64QAM	1	74	18.38	18.55	18.60		
15	64QAM	36	0	18.35	18.44	18.41		
15	64QAM	36	20	18.41	18.42	18.43	19	0
15	64QAM	36	39	18.38	18.39	18.38		
15	64QAM	75	0	18.36	18.38	18.37		



FCC SAR TEST REPORT

Report No. : FA8O2425-03

Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	18.58	18.65	18.66	19	0
10	QPSK	1	25	18.60	18.69	18.70		
10	QPSK	1	49	18.49	18.54	18.57		
10	QPSK	25	0	18.74	18.82	18.81	19	0
10	QPSK	25	12	18.72	18.80	18.81		
10	QPSK	25	25	18.64	18.73	18.73		
10	QPSK	50	0	18.71	18.80	18.79	19	0
10	16QAM	1	0	18.32	18.39	18.45		
10	16QAM	1	25	18.32	18.45	18.50		
10	16QAM	1	49	18.21	18.36	18.45	19	0
10	16QAM	25	0	18.23	18.30	18.29		
10	16QAM	25	12	18.22	18.28	18.30		
10	16QAM	25	25	18.14	18.20	18.22	19	0
10	16QAM	50	0	18.20	18.25	18.28		
10	64QAM	1	0	18.32	18.37	18.52		
10	64QAM	1	25	18.32	18.41	18.47	19	0
10	64QAM	1	49	18.27	18.30	18.33		
10	64QAM	25	0	18.22	18.31	18.31		
10	64QAM	25	12	18.26	18.31	18.31	19	0
10	64QAM	25	25	18.16	18.23	18.22		
10	64QAM	50	0	18.20	18.26	18.29		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	18.52	18.61	18.63	19	0
5	QPSK	1	12	18.63	18.71	18.73		
5	QPSK	1	24	18.53	18.59	18.65		
5	QPSK	12	0	18.70	18.73	18.76	19	0
5	QPSK	12	7	18.74	18.76	18.78		
5	QPSK	12	13	18.68	18.77	18.79		
5	QPSK	25	0	18.70	18.72	18.71	19	0
5	16QAM	1	0	18.26	18.30	18.44		
5	16QAM	1	12	18.35	18.43	18.49		
5	16QAM	1	24	18.24	18.30	18.41	19	0
5	16QAM	12	0	18.21	18.19	18.22		
5	16QAM	12	7	18.27	18.23	18.27		
5	16QAM	12	13	18.22	18.22	18.26	19	0
5	16QAM	25	0	18.18	18.19	18.20		
5	64QAM	1	0	18.24	18.35	18.44		
5	64QAM	1	12	18.30	18.40	18.50	19	0
5	64QAM	1	24	18.23	18.31	18.40		
5	64QAM	12	0	18.25	18.25	18.27		
5	64QAM	12	7	18.30	18.31	18.30	19	0
5	64QAM	12	13	18.26	18.29	18.34		
5	64QAM	25	0	18.23	18.23	18.24		

Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	18.52	18.57	18.63	19	0
3	QPSK	1	8	18.70	18.75	18.79		
3	QPSK	1	14	18.57	18.62	18.68		
3	QPSK	8	0	18.70	18.70	18.72	19	0
3	QPSK	8	4	18.75	18.77	18.82		
3	QPSK	8	7	18.71	18.76	18.82		
3	QPSK	15	0	18.74	18.76	18.81		
3	16QAM	1	0	18.23	18.27	18.38	19	0
3	16QAM	1	8	18.45	18.46	18.56		
3	16QAM	1	14	18.28	18.30	18.46		
3	16QAM	8	0	18.24	18.22	18.28	19	0
3	16QAM	8	4	18.31	18.27	18.37		
3	16QAM	8	7	18.24	18.31	18.36		
3	16QAM	15	0	18.24	18.23	18.33		
3	64QAM	1	0	18.20	18.27	18.33	19	0
3	64QAM	1	8	18.40	18.43	18.57		
3	64QAM	1	14	18.24	18.29	18.40		
3	64QAM	8	0	18.23	18.24	18.25	19	0
3	64QAM	8	4	18.31	18.27	18.37		
3	64QAM	8	7	18.25	18.32	18.38		
3	64QAM	15	0	18.23	18.21	18.30		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	18.44	18.54	18.60	19	0
1.4	QPSK	1	3	18.60	18.71	18.71		
1.4	QPSK	1	5	18.53	18.65	18.65		
1.4	QPSK	3	0	18.57	18.55	18.62		
1.4	QPSK	3	1	18.61	18.61	18.68		
1.4	QPSK	3	3	18.59	18.66	18.66		
1.4	QPSK	6	0	18.65	18.67	18.76	19	0
1.4	16QAM	1	0	18.15	18.28	18.41	19	0
1.4	16QAM	1	3	18.35	18.42	18.50		
1.4	16QAM	1	5	18.27	18.40	18.45		
1.4	16QAM	3	0	18.06	18.06	18.18		
1.4	16QAM	3	1	18.09	18.15	18.25		
1.4	16QAM	3	3	18.08	18.16	18.23		
1.4	16QAM	6	0	18.18	18.23	18.31	19	0
1.4	64QAM	1	0	18.18	18.26	18.39	19	0
1.4	64QAM	1	3	18.35	18.40	18.51		
1.4	64QAM	1	5	18.26	18.38	18.42		
1.4	64QAM	3	0	18.20	18.24	18.40		
1.4	64QAM	3	1	18.26	18.33	18.41		
1.4	64QAM	3	3	18.23	18.32	18.42		
1.4	64QAM	6	0	18.13	18.15	18.19	19	0



<LTE Band 12>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23060	23095	23130		
Frequency (MHz)				704	707.5	711		
10	QPSK	1	0	23.89	24.03	23.99	25	0
10	QPSK	1	25	23.85	23.85	23.79		
10	QPSK	1	49	23.82	23.85	23.80		
10	QPSK	25	0	23.06	23.05	22.98	24	1
10	QPSK	25	12	23.07	23.08	23.04		
10	QPSK	25	25	23.07	23.05	22.96		
10	QPSK	50	0	23.07	23.05	23.01		
10	16QAM	1	0	22.74	22.68	22.66	24	1
10	16QAM	1	25	22.63	22.62	22.56		
10	16QAM	1	49	22.66	22.65	22.58		
10	16QAM	25	0	21.52	21.51	21.47	23	2
10	16QAM	25	12	21.52	21.52	21.52		
10	16QAM	25	25	21.56	21.55	21.48		
10	16QAM	50	0	21.55	21.54	21.49		
10	64QAM	1	0	21.67	21.60	21.61	23	2
10	64QAM	1	25	21.60	21.60	21.51		
10	64QAM	1	49	21.64	21.62	21.54		
10	64QAM	25	0	20.54	20.53	20.46	22	3
10	64QAM	25	12	20.57	20.54	20.54		
10	64QAM	25	25	20.57	20.58	20.47		
10	64QAM	50	0	20.57	20.56	20.49		
Channel				23035	23095	23155	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				701.5	707.5	713.5		
5	QPSK	1	0	23.87	23.81	23.74	25	0
5	QPSK	1	12	23.96	23.96	23.86		
5	QPSK	1	24	23.95	23.93	23.80		
5	QPSK	12	0	23.04	23.02	22.92	24	1
5	QPSK	12	7	23.08	23.03	23.01		
5	QPSK	12	13	23.02	23.06	22.97		
5	QPSK	25	0	23.05	23.00	23.07		
5	16QAM	1	0	22.59	22.54	22.48	24	1
5	16QAM	1	12	22.70	22.73	22.62		
5	16QAM	1	24	22.69	22.66	22.56		
5	16QAM	12	0	21.58	21.48	21.40	23	2
5	16QAM	12	7	21.60	21.52	21.49		
5	16QAM	12	13	21.57	21.54	21.44		
5	16QAM	25	0	21.59	21.46	21.46		
5	64QAM	1	0	21.62	21.52	21.45	23	2
5	64QAM	1	12	21.72	21.70	21.60		
5	64QAM	1	24	21.63	21.64	21.53		
5	64QAM	12	0	20.63	20.52	20.46	22	3
5	64QAM	12	7	20.65	20.56	20.54		
5	64QAM	12	13	20.62	20.60	20.51		
5	64QAM	25	0	20.61	20.47	20.47		

Channel				23025	23095	23165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				700.5	707.5	714.5		
3	QPSK	1	0	23.94	23.83	23.74	25	0
3	QPSK	1	8	24.00	24.02	23.94		
3	QPSK	1	14	23.91	23.92	23.80		
3	QPSK	8	0	23.03	22.97	22.88	24	1
3	QPSK	8	4	23.09	23.02	23.01		
3	QPSK	8	7	23.05	23.05	22.97		
3	QPSK	15	0	23.07	23.06	22.95		
3	16QAM	1	0	22.70	22.57	22.52	24	1
3	16QAM	1	8	22.83	22.81	22.74		
3	16QAM	1	14	22.68	22.69	22.58		
3	16QAM	8	0	21.64	21.52	21.42	23	2
3	16QAM	8	4	21.65	21.58	21.53		
3	16QAM	8	7	21.63	21.55	21.51		
3	16QAM	15	0	21.60	21.52	21.42		
3	64QAM	1	0	21.69	21.54	21.47	23	2
3	64QAM	1	8	21.77	21.77	21.64		
3	64QAM	1	14	21.68	21.65	21.55		
3	64QAM	8	0	20.58	20.53	20.43	22	3
3	64QAM	8	4	20.68	20.56	20.52		
3	64QAM	8	7	20.63	20.60	20.45		
3	64QAM	15	0	20.61	20.53	20.45		
Channel				23017	23095	23173	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				699.7	707.5	715.3		
1.4	QPSK	1	0	23.91	23.82	23.76	25	0
1.4	QPSK	1	3	24.03	23.95	23.85		
1.4	QPSK	1	5	23.91	23.88	23.75		
1.4	QPSK	3	0	23.92	23.82	23.80		
1.4	QPSK	3	1	24.01	23.92	23.83		
1.4	QPSK	3	3	23.91	23.89	23.76		
1.4	QPSK	6	0	23.02	22.94	22.91	24	1
1.4	16QAM	1	0	22.25	22.61	22.58	24	1
1.4	16QAM	1	3	22.41	22.73	22.63		
1.4	16QAM	1	5	22.67	22.67	22.55		
1.4	16QAM	3	0	22.52	22.38	22.37		
1.4	16QAM	3	1	22.56	22.51	22.41		
1.4	16QAM	3	3	22.49	22.47	22.33		
1.4	16QAM	6	0	21.41	21.48	21.46	23	2
1.4	64QAM	1	0	21.66	21.59	21.51	23	2
1.4	64QAM	1	3	21.72	21.70	21.59		
1.4	64QAM	1	5	21.65	21.64	21.51		
1.4	64QAM	3	0	21.68	21.57	21.55		
1.4	64QAM	3	1	21.72	21.68	21.60		
1.4	64QAM	3	3	21.66	21.65	21.53		
1.4	64QAM	6	0	20.55	20.43	20.38	22	3



<LTE Band 17>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				23780	23790	23800		
Frequency (MHz)				709	710	711		
10	QPSK	1	0	23.90	23.81	23.93	25	0
10	QPSK	1	25	23.86	23.87	23.82		
10	QPSK	1	49	23.81	23.86	23.80		
10	QPSK	25	0	22.74	22.76	22.75	24	1
10	QPSK	25	12	22.93	22.95	22.95		
10	QPSK	25	25	22.66	22.72	22.71		
10	QPSK	50	0	22.71	22.76	22.73		
10	16QAM	1	0	22.69	22.60	22.67	24	1
10	16QAM	1	25	22.60	22.64	22.61		
10	16QAM	1	49	22.64	22.63	22.54		
10	16QAM	25	0	21.24	21.25	21.21	23	2
10	16QAM	25	12	21.43	21.43	21.41		
10	16QAM	25	25	21.18	21.19	21.18		
10	16QAM	50	0	21.23	21.23	21.21		
10	64QAM	1	0	21.63	21.55	21.61	23	2
10	64QAM	1	25	21.60	21.60	21.59		
10	64QAM	1	49	21.61	21.57	21.57		
10	64QAM	25	0	20.26	20.27	20.24	22	3
10	64QAM	25	12	20.45	20.45	20.43		
10	64QAM	25	25	20.21	20.22	20.19		
10	64QAM	50	0	20.25	20.24	20.22		
Channel				23755	23790	23825	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				706.5	710	713.5		
5	QPSK	1	0	23.62	23.61	23.61	25	0
5	QPSK	1	12	23.90	23.90	23.86		
5	QPSK	1	24	23.70	23.70	23.63		
5	QPSK	12	0	22.87	22.93	22.90	24	1
5	QPSK	12	7	23.00	23.01	23.02		
5	QPSK	12	13	22.95	22.96	22.94		
5	QPSK	25	0	22.94	22.93	22.94		
5	16QAM	1	0	22.36	22.35	22.36	24	1
5	16QAM	1	12	22.67	22.72	22.64		
5	16QAM	1	24	22.43	22.46	22.38		
5	16QAM	12	0	21.41	21.43	21.37	23	2
5	16QAM	12	7	21.55	21.51	21.50		
5	16QAM	12	13	21.45	21.48	21.42		
5	16QAM	25	0	21.46	21.42	21.41		
5	64QAM	1	0	21.37	21.31	21.34	23	2
5	64QAM	1	12	21.63	21.68	21.63		
5	64QAM	1	24	21.43	21.41	21.38		
5	64QAM	12	0	20.47	20.47	20.42	22	3
5	64QAM	12	7	20.62	20.56	20.56		
5	64QAM	12	13	20.52	20.50	20.47		
5	64QAM	25	0	20.48	20.44	20.42		

<TDD LTE SAR Measurement>

TDD LTE configuration setup for SAR measurement

SAR was tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- “special subframe S” contains both uplink and downlink transmissions, it has been taken into consideration to determine the transmission duty factor according to the worst case uplink and downlink cyclic prefix requirements for UpPTS
- Establishing connections with base station simulators ensure a consistent means for testing SAR and recommended for evaluating SAR. The Anritsu MT8820C (firmware: #22.52#004) was used for LTE output power measurements and SAR testing.




Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity).

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Special subframe (30720 $\square$ T _s): Normal cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~4	7.13%	8.33%
	5~9	14.3%	16.7%

Special subframe(30720 $\square$ T _s): Extended cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~3	7.13%	8.33%
	4~7	14.3%	16.7%

The highest duty factor is resulted from:

- Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is:
 $(3+0.167)/5 = 63.3\%$
- for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is:
 $(3+0.143)/5 = 62.9\%$
- For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.

<LTE Band 41>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Low Middle Ch. / Freq.	Power Middle Ch. / Freq.	Power High Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				39750	40185	40620	41055	41490		
Frequency (MHz)				2506	2549.5	2593	2636.5	2680		
20	QPSK	1	0	17.41	16.84	17.17	16.65	16.79	18	0
20	QPSK	1	49	17.14	16.56	17.07	16.70	16.95		
20	QPSK	1	99	17.10	16.71	16.93	16.52	16.91		
20	QPSK	50	0	17.53	17.08	17.27	16.79	17.02	18	0
20	QPSK	50	24	17.56	17.05	17.22	16.77	16.98		
20	QPSK	50	50	17.36	17.13	17.16	16.78	16.84		
20	QPSK	100	0	17.44	17.00	17.11	16.65	16.87	18	0
20	16QAM	1	0	17.26	17.29	17.47	16.69	16.75		
20	16QAM	1	49	17.74	16.77	17.26	16.91	17.07		
20	16QAM	1	99	17.57	17.15	17.10	16.73	17.06	18	0
20	16QAM	50	0	17.65	17.09	17.40	16.25	16.63		
20	16QAM	50	24	17.61	17.08	17.34	16.44	16.77		
20	16QAM	50	50	17.48	17.20	17.28	16.45	16.75	18	0
20	16QAM	100	0	17.49	17.09	17.23	16.31	16.79		
20	64QAM	1	0	17.44	17.12	17.07	16.01	16.28		
20	64QAM	1	49	17.35	16.83	17.14	16.17	16.47	18	0
20	64QAM	1	99	17.30	16.99	16.97	16.02	16.92		
20	64QAM	50	0	16.95	17.05	16.88	16.23	16.70		
20	64QAM	50	24	17.40	17.08	16.83	16.44	16.82	18	0
20	64QAM	50	50	17.45	17.09	16.75	16.43	16.81		
20	64QAM	100	0	17.03	17.01	16.69	16.32	16.76		
Channel				39725	40173	40620	41068	41515	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2503.5	2548.3	2593	2637.8	2682.5		
15	QPSK	1	0	17.24	16.40	17.03	16.71	16.81	18	0
15	QPSK	1	37	17.03	16.54	16.99	16.83	17.11		
15	QPSK	1	74	17.19	16.54	17.04	16.77	17.00		
15	QPSK	36	0	17.39	16.89	17.27	16.73	17.03	18	0
15	QPSK	36	20	17.48	16.96	17.27	16.85	16.95		
15	QPSK	36	39	17.41	17.07	17.13	16.81	16.71		
15	QPSK	75	0	17.38	17.03	17.18	16.80	16.84	18	0
15	16QAM	1	0	17.13	16.78	17.41	16.73	16.75		
15	16QAM	1	37	17.35	16.98	17.35	16.96	17.21		
15	16QAM	1	74	17.73	17.00	17.29	16.89	17.18	18	0
15	16QAM	36	0	17.47	16.82	17.33	16.14	16.70		
15	16QAM	36	20	17.50	16.95	17.29	16.45	16.83		
15	16QAM	36	39	17.44	17.05	17.14	16.39	16.90	18	0
15	16QAM	75	0	17.43	17.06	17.17	16.47	16.51		
15	64QAM	1	0	17.21	16.60	17.09	16.00	16.12		
15	64QAM	1	37	17.25	16.79	17.11	16.20	16.46	18	0
15	64QAM	1	74	17.47	16.73	17.03	16.04	16.85		
15	64QAM	36	0	17.46	16.81	16.69	16.16	16.54		
15	64QAM	36	20	16.95	16.89	16.63	16.47	16.69	18	0
15	64QAM	36	39	17.18	16.98	16.37	16.40	16.66		
15	64QAM	75	0	16.91	16.95	16.44	16.46	16.57		

Channel				39700	40160	40620	41080	41540	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2501	2547	2593	2639	2685		
10	QPSK	1	0	17.16	16.45	16.72	16.57	16.75	18	0
10	QPSK	1	25	17.02	16.75	16.95	16.80	17.06		
10	QPSK	1	49	17.12	16.69	17.01	16.76	17.00		
10	QPSK	25	0	17.32	17.04	17.21	16.72	17.08	18	0
10	QPSK	25	12	17.40	17.09	17.26	16.81	17.01		
10	QPSK	25	25	17.39	17.06	17.15	16.78	16.76		
10	QPSK	50	0	17.32	17.02	17.18	16.72	16.83	18	0
10	16QAM	1	0	17.33	17.01	17.24	16.73	16.90		
10	16QAM	1	25	17.65	17.28	17.50	17.01	17.35		
10	16QAM	1	49	17.72	17.25	17.42	17.06	17.29	18	0
10	16QAM	25	0	17.56	17.19	17.44	16.67	16.93		
10	16QAM	25	12	17.58	17.30	17.41	16.83	17.13		
10	16QAM	25	25	17.49	17.26	17.28	16.82	17.01	18	0
10	16QAM	50	0	17.39	17.14	17.24	16.71	16.99		
10	64QAM	1	0	17.37	17.05	17.16	16.46	16.70		
10	64QAM	1	25	17.55	17.26	17.32	16.72	17.04	18	0
10	64QAM	1	49	17.69	17.16	17.25	16.55	16.82		
10	64QAM	25	0	17.53	17.10	16.93	16.72	16.94		
10	64QAM	25	12	17.56	17.18	17.00	16.86	17.14	18	0
10	64QAM	25	25	17.46	17.22	16.83	16.83	17.04		
10	64QAM	50	0	17.38	17.04	16.81	16.69	16.96		
Channel				39675	40148	40620	41093	41565	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2498.5	2545.8	2593	2640.30	2687.5		
5	QPSK	1	0	16.67	16.65	16.83	16.67	16.67	18	0
5	QPSK	1	12	16.73	16.75	16.86	16.79	16.78		
5	QPSK	1	24	16.79	16.73	16.99	16.67	16.78		
5	QPSK	12	0	16.99	17.16	17.31	16.85	16.93	18	0
5	QPSK	12	7	16.98	17.24	17.33	16.97	16.91		
5	QPSK	12	13	17.07	17.21	17.29	16.94	16.80		
5	QPSK	25	0	16.95	17.16	17.25	16.76	16.76	18	0
5	16QAM	1	0	16.93	17.14	17.30	16.85	16.83		
5	16QAM	1	12	17.09	17.27	17.42	17.05	17.04		
5	16QAM	1	24	17.16	17.25	17.45	16.93	17.09	18	0
5	16QAM	12	0	17.12	17.21	17.44	16.55	16.50		
5	16QAM	12	7	17.12	17.30	17.46	16.68	16.66		
5	16QAM	12	13	17.19	17.28	17.34	16.61	16.61	18	0
5	16QAM	25	0	17.15	17.18	17.33	16.48	16.60		
5	64QAM	1	0	17.06	16.98	17.30	16.44	16.40		
5	64QAM	1	12	17.20	17.25	17.41	16.61	16.52	18	0
5	64QAM	1	24	17.27	17.25	17.45	16.37	16.53		
5	64QAM	12	0	17.19	17.22	16.94	16.48	16.51		
5	64QAM	12	7	17.25	17.25	16.95	16.59	16.68	18	0
5	64QAM	12	13	17.20	17.25	16.81	16.54	16.62		
5	64QAM	25	0	17.14	17.25	16.88	16.41	16.61		

<LTE Carrier Aggregation combinations>
General Note:

1. This device supports Carrier Aggregation on downlink only for intra band, Uplink CA is not supported. For the device supports combination bands and configurations are according to 3GPP.

2CC Downlink Carrier Aggregation			
Number	Combination	Restriction	Covered by Measurement Superset
1	41C		

<Power verification when LTE Carrier Aggregation Active>
General Note:

- i. According to KDB941225 D05A v01r02, Uplink maximum output power measurement with downlink carrier aggregation active should be measured, using the highest output channel measured without downlink carrier aggregation, to confirm that uplink maximum output power with downlink carrier aggregation active remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output measured without downlink carrier aggregation active.
- ii. Uplink maximum output power with downlink carrier aggregation active does not show more than ¼ dB higher than the maximum output power without downlink carrier aggregation active, therefore SAR evaluation with downlink carrier aggregation active can be excluded.
- iii. The device supports downlink two carrier aggregation. For power measurement were control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
- iv. Selected highest measured power when downlink carrier aggregation is inactive for conducted power comparison with downlink carrier aggregation is active, to confirm that when downlink carrier aggregation is active uplink maximum output power remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output power measured when downlink carrier aggregation inactive.
- v. For non-contiguous intra-band CA, the SCC selected to provide maximum separation from the PCC and must remain fully within the downlink transmission band.
- vi. For Intra-band, contiguous CA, the downlink channels selected to perform the uplink power measurement must satisfy 3GPP channel spacing (5.4.1A of 3GPP TS 36.521 or equivalent) and channel bandwidth (5.4.2A) requirements.

$$\text{Nominal channel spacing} = \left\lceil \frac{BW_{\text{Channel}(1)} + BW_{\text{Channel}(2)} - 0.1|BW_{\text{Channel}(1)} - BW_{\text{Channel}(2)}|}{0.6} \right\rceil 0.3 \text{ [MHz]}$$

<Two Carrier power verification>

Configure		PCC							SCC				Power	
		LTE Band	BW (MHz)	UL Freq. (MHz)	UL Channel	Mod.	UL# RB	UL RB Offset	LTE Band	BW (MHz)	DL Freq. (MHz)	DL Channel	With CA Tx.Power (dBm)	W/O CA Tx.Power (dBm)
Intra-Band	Contiguous	41	20	2680	41490	QPSK	1	99	41	20	2660.20	41292	17.35	17.39

<WLAN Conducted Power>**General Note:**

1. The maximum power in the tune-up exhibit that the single chain in SISO operation is the same single chain in MIMO operation.
2. For each antenna, transmit power in SISO operation is larger than (or equal to) the power in MIMO operation, RF exposure compliance of MIMO mode can be deduced from the compliance simultaneous transmission of antennas operating in SISO mode.
3. Per KDB 248227 D01v02r02, the simultaneous SAR provisions in KDB publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1g single transmission chain SAR measurements is $< 1.6\text{W/kg}$ and SAR peak to location ratio ≤ 0.04 , no additional SAR measurements for MIMO.
4. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
5. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
6. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
7. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.¹⁸ The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is $\leq 0.4\text{ W/kg}$, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is $> 0.4\text{ W/kg}$, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is $\leq 0.8\text{ W/kg}$ or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is $> 0.8\text{ W/kg}$, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is $\leq 1.2\text{ W/kg}$ or all required channels are tested.

<2.4GHz WLAN Chain 0>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	14.10	14.50	100.00
		6	2437	14.00	14.50	
		11	2462	14.20	14.50	
		12	2467	14.10	14.50	
		13	2472	12.10	12.63	
	802.11g 6Mbps	1	2412	10.00	10.41	97.31
		6	2437	14.70	15.00	
		11	2462	14.40	14.83	
		12	2467	11.50	12.06	
		13	2472	4.40	4.60	
	802.11n-HT20 MCS0	1	2412	3.60	4.18	98.80
		6	2437	14.70	15.00	
		11	2462	14.30	14.34	
		12	2467	8.90	9.26	
		13	2472	2.00	2.18	

<2.4GHz WLAN Chain 1>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	13.60	14.00	100.00
		6	2437	13.70	14.00	
		11	2462	13.70	14.00	
		12	2467	13.80	14.00	
		13	2472	10.40	10.50	
	802.11g 6Mbps	1	2412	8.80	8.86	97.31
		6	2437	14.40	14.70	
		11	2462	14.30	14.53	
		12	2467	9.00	9.20	
		13	2472	4.20	4.60	
	802.11n-HT20 MCS0	1	2412	2.40	2.61	98.80
		6	2437	14.40	14.70	
		11	2462	13.80	14.04	
		12	2467	10.60	10.80	
		13	2472	1.60	1.87	

<5GHz WLAN Chain 0>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	13.80	14.00	97.60
		40	5200	13.70	14.00	
		44	5220	13.80	14.00	
		48	5240	13.70	14.00	
	802.11n-HT20 MCS0	36	5180	13.60	14.00	99.20
		40	5200	13.60	14.00	
		44	5220	13.70	14.00	
		48	5240	13.80	14.00	
	802.11n-HT40 MCS0	38	5190	13.90	14.00	98.37
		46	5230	13.70	14.00	
	802.11ac-VHT20 MCS0	36	5180	13.50	14.00	99.30
		40	5200	13.50	14.00	
		44	5220	13.60	14.00	
		48	5240	13.70	14.00	
	802.11ac-VHT40 MCS0	38	5190	13.80	14.00	98.37
		46	5230	13.60	14.00	
	802.11ac-VHT80 MCS0	42	5210	13.80	14.00	97.01

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.3GHz WLAN	802.11a 6Mbps	52	5260	13.60	14.00	97.60
		56	5280	13.60	14.00	
		60	5300	13.70	14.00	
		64	5320	13.80	14.00	
	802.11n-HT20 MCS0	52	5260	13.90	14.00	99.20
		56	5280	13.80	14.00	
		60	5300	13.60	14.00	
		64	5320	13.60	14.00	
	802.11n-HT40 MCS0	54	5270	13.60	14.00	98.37
		62	5310	13.70	14.00	
	802.11ac-VHT20 MCS0	52	5260	13.80	14.00	99.30
		56	5280	13.50	14.00	
		60	5300	13.50	14.00	
		64	5320	13.50	14.00	
	802.11ac-VHT40 MCS0	54	5270	13.50	14.00	98.37
		62	5310	13.60	14.00	
	802.11ac-VHT80 MCS0	58	5290	13.80	14.00	97.01

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.5GHz WLAN	802.11a 6Mbps	100	5500	13.60	14.00	97.60
		116	5580	13.90	14.00	
		124	5620	13.70	14.00	
		132	5660	13.70	14.00	
		144	5720	13.70	14.00	
	802.11n-HT20 MCS0	100	5500	13.90	14.00	99.20
		116	5580	13.80	14.00	
		124	5620	13.80	14.00	
		132	5660	13.80	14.00	
		144	5720	13.90	14.00	
	802.11n-HT40 MCS0	102	5510	13.60	14.00	98.37
		110	5550	13.60	14.00	
		126	5630	13.60	14.00	
		134	5670	13.80	14.00	
		142	5710	13.70	14.00	
	802.11ac-VHT20 MCS0	100	5500	13.80	14.00	99.30
		116	5580	13.70	14.00	
		124	5620	13.70	14.00	
		132	5660	13.70	14.00	
		144	5720	13.80	14.00	
	802.11ac-VHT40 MCS0	102	5510	13.50	14.00	98.37
		110	5550	13.50	14.00	
		126	5630	13.50	14.00	
		134	5670	13.70	14.00	
		142	5710	13.60	14.00	
	802.11ac-VHT80 MCS0	106	5530	14.00	14.00	97.01
		122	5610	13.80	14.00	
		138	5690	13.70	14.00	

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.8GHz WLAN	802.11a MCS0	149	5745	13.60	14.00	97.60
		157	5785	13.90	14.00	
		165	5825	13.80	14.00	
	802.11n-HT20 MCS0	149	5745	13.90	14.00	99.20
		157	5785	13.90	14.00	
		165	5825	13.70	14.00	
	802.11n-HT40 MCS0	151	5755	13.60	14.00	98.37
		159	5795	13.50	14.00	
	802.11ac-VHT20 MCS0	149	5745	13.80	14.00	99.30
		157	5785	13.80	14.00	
		165	5825	13.60	14.00	
	802.11ac-VHT40 MCS0	151	5755	13.50	14.00	98.37
		159	5795	13.40	14.00	
	802.11ac-VHT80 MCS0	155	5775	13.50	14.00	97.01

<5GHz WLAN Chain 1>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	11.90	12.00	97.60
		40	5200	11.40	12.00	
		44	5220	11.40	12.00	
		48	5240	11.80	12.00	
	802.11n-HT20 MCS0	36	5180	11.80	12.00	99.20
		40	5200	11.50	12.00	
		44	5220	11.50	12.00	
		48	5240	11.70	12.00	
	802.11n-HT40 MCS0	38	5190	11.90	12.00	98.37
		46	5230	11.70	12.00	
	802.11ac-VHT20 MCS0	36	5180	11.70	12.00	99.30
		40	5200	11.40	12.00	
		44	5220	11.40	12.00	
		48	5240	11.60	12.00	
	802.11ac-VHT40 MCS0	38	5190	11.80	12.00	98.37
		46	5230	11.60	12.00	
	802.11ac-VHT80 MCS0	42	5210	11.80	12.00	97.01

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.3GHz WLAN	802.11a 6Mbps	52	5260	11.80	12.00	97.60
		56	5280	11.70	12.00	
		60	5300	11.80	12.00	
		64	5320	11.80	12.00	
	802.11n-HT20 MCS0	52	5260	11.80	12.00	99.60
		56	5280	11.70	12.00	
		60	5300	11.90	12.00	
		64	5320	11.80	12.00	
	802.11n-HT40 MCS0	54	5270	11.70	12.00	98.37
		62	5310	11.90	12.00	
	802.11ac-VHT20 MCS0	52	5260	11.70	12.00	99.30
		56	5280	11.70	12.00	
		60	5300	11.70	12.00	
		64	5320	11.70	12.00	
	802.11ac-VHT40 MCS0	54	5270	11.60	12.00	98.78
		62	5310	11.80	12.00	
	802.11ac-VHT80 MCS0	58	5290	11.60	12.00	97.01

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.5GHz WLAN	802.11a 6Mbps	100	5500	11.90	12.00	97.60
		116	5580	11.90	12.00	
		124	5620	11.80	12.00	
		132	5660	11.80	12.00	
		144	5720	11.80	12.00	
	802.11n-HT20 MCS0	100	5500	11.90	12.00	99.60
		116	5580	11.90	12.00	
		124	5620	11.70	12.00	
		132	5660	11.60	12.00	
		144	5720	11.60	12.00	
	802.11n-HT40 MCS0	102	5510	11.90	12.00	98.37
		110	5550	11.90	12.00	
		126	5630	11.80	12.00	
		134	5670	11.80	12.00	
		142	5710	11.70	12.00	
	802.11ac-VHT20 MCS0	100	5500	11.80	12.00	99.30
		116	5580	11.80	12.00	
		124	5620	11.70	12.00	
		132	5660	11.60	12.00	
		144	5720	11.50	12.00	
	802.11ac-VHT40 MCS0	102	5510	11.80	12.00	98.78
		110	5550	11.80	12.00	
		126	5630	11.60	12.00	
		134	5670	11.60	12.00	
		142	5710	11.60	12.00	
	802.11ac-VHT80 MCS0	106	5530	11.60	12.00	97.01
		122	5610	11.50	12.00	
		138	5690	11.60	12.00	

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.8GHz WLAN	802.11a MCS0	149	5745	11.70	12.00	97.60
		157	5785	11.80	12.00	
		165	5825	11.60	12.00	
	802.11n-HT20 MCS0	149	5745	11.70	12.00	99.60
		157	5785	11.80	12.00	
		165	5825	11.50	12.00	
	802.11n-HT40 MCS0	151	5755	11.80	12.00	98.37
		159	5795	11.90	12.00	
	802.11ac-VHT20 MCS0	149	5745	11.60	12.00	99.30
		157	5785	11.70	12.00	
		165	5825	11.40	12.00	
	802.11ac-VHT40 MCS0	151	5755	11.70	12.00	98.78
		159	5795	11.80	12.00	
	802.11ac-VHT80 MCS0	155	5775	11.50	12.00	97.01


<2.4GHz Bluetooth>

Mode	Channel	Frequency (MHz)	Average power (dBm)			Tune-up Limit		
			1Mbps	2Mbps	3Mbps	1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	10.38	6.97	6.98	12.73	10.38	10.38
	CH 39	2441	10.78	7.34	7.35	12.78	10.28	10.28
	CH 78	2480	9.48	6.28	6.30	11.67	9.75	9.75

Mode	Channel	Frequency (MHz)	Average power (dBm)		Tune-up Limit	
			1Mbps	2Mbps	1Mbps	2Mbps
LE	CH 00	2402	4.80	4.70	7.45	7.45
	CH 19	2440	5.20	5.10	7.19	7.19
	CH 39	2480	4.00	3.90	6.54	6.54

General Note:

- For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 76.84% considered in SAR testing, and the duty cycle would be scaled to theoretical 83.3% in reported SAR calculation.


12. RF Exposure Conditions

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN chain0	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm
2.4GHz WLAN chain1	≤ 25mm	≤ 25mm	>25mm	>25mm	>25mm	≤ 25mm
5GHz WLAN chain1	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN chain0	Yes	Yes	Yes	No	No	Yes
2.4GHz WLAN chain1	Yes	Yes	No	No	No	Yes
5GHz WLAN chain1	Yes	Yes	Yes	No	No	Yes

General Note:

- Referring to KDB 941225 D06 v02r01, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge, The detail antenna location please refers to Appendix D.

13. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
 - e. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result.
The Reported TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. Per KDB 648474 D04v01r03, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.
5. For 5GHz WLAN product specific SAR is necessary, due to an overall diagonal dimension is > 16 cm.

GSM Note:

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE / DTM modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE / DTM are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4/B12 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 17 SAR test was covered by Band 12; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. For WLAN SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.
6. Per KDB 248227 D01v02r02, the simultaneous SAR provisions in KDB publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg and SAR peak to location ratio ≤ 0.04 , no additional SAR measurements for MIMO.
7. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

13.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Right Cheek	0mm	128	824.2	26.81	27.20	1.094	-0.07	0.160	0.175
	GSM850	GPRS (4 Tx slots)	Right Tilted	0mm	128	824.2	26.81	27.20	1.094	0.03	0.062	0.068
01	GSM850	GPRS (4 Tx slots)	Left Cheek	0mm	128	824.2	26.81	27.20	1.094	0.06	0.199	0.218
	GSM850	GPRS (4 Tx slots)	Left Tilted	0mm	128	824.2	26.81	27.20	1.094	-0.15	0.072	0.079
02	GSM1900	GPRS (4 Tx slots)	Right Cheek	0mm	661	1880	21.99	22.70	1.178	0.12	0.012	0.014
	GSM1900	GPRS (4 Tx slots)	Right Tilted	0mm	661	1880	21.99	22.70	1.178	0.12	0.001	0.001
	GSM1900	GPRS (4 Tx slots)	Left Cheek	0mm	661	1880	21.99	22.70	1.178	0.09	0.012	0.014
	GSM1900	GPRS (4 Tx slots)	Left Tilted	0mm	661	1880	21.99	22.70	1.178	0.17	0.004	0.005

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
03	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	9400	1880	18.53	18.70	1.040	0.12	0.023	0.024
	WCDMA II	RMC 12.2Kbps	Right Tilted	0mm	9400	1880	18.53	18.70	1.040	0.18	0.008	0.008
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9400	1880	18.53	18.70	1.040	0.12	0.020	0.021
	WCDMA II	RMC 12.2Kbps	Left Tilted	0mm	9400	1880	18.53	18.70	1.040	0.15	0.011	0.011
04	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	1312	1712.4	18.69	18.70	1.002	-0.1	0.033	0.033
	WCDMA IV	RMC 12.2Kbps	Right Tilted	0mm	1312	1712.4	18.69	18.70	1.002	-0.1	0.012	0.012
	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1312	1712.4	18.69	18.70	1.002	0.13	0.015	0.015
	WCDMA IV	RMC 12.2Kbps	Left Tilted	0mm	1312	1712.4	18.69	18.70	1.002	0.1	0.020	0.020

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Right Cheek	0mm	18900	1880	18.78	19.00	1.052	0.15	0.020	0.021
	LTE Band 2	20M	QPSK	50	0	Right Cheek	0mm	18900	1880	18.90	19.00	1.023	0.16	0.019	0.019
	LTE Band 2	20M	QPSK	1	0	Right Tilted	0mm	18900	1880	18.78	19.00	1.052	0.11	0.006	0.006
	LTE Band 2	20M	QPSK	50	0	Right Tilted	0mm	18900	1880	18.90	19.00	1.023	0.12	0.006	0.006
	LTE Band 2	20M	QPSK	1	0	Left Cheek	0mm	18900	1880	18.78	19.00	1.052	0.15	0.021	0.022
05	LTE Band 2	20M	QPSK	50	0	Left Cheek	0mm	18900	1880	18.90	19.00	1.023	-0.13	0.022	0.023
	LTE Band 2	20M	QPSK	1	0	Left Tilted	0mm	18900	1880	18.78	19.00	1.052	0.15	0.007	0.008
	LTE Band 2	20M	QPSK	50	0	Left Tilted	0mm	18900	1880	18.90	19.00	1.023	0.17	0.008	0.009
	LTE Band 4	20M	QPSK	1	0	Right Cheek	0mm	20175	1732.5	18.73	19.00	1.064	-0.07	0.040	0.043
06	LTE Band 4	20M	QPSK	50	0	Right Cheek	0mm	20175	1732.5	18.93	19.00	1.016	0.17	0.042	0.043
	LTE Band 4	20M	QPSK	1	0	Right Tilted	0mm	20175	1732.5	18.73	19.00	1.064	0.11	0.016	0.017
	LTE Band 4	20M	QPSK	50	0	Right Tilted	0mm	20175	1732.5	18.93	19.00	1.016	0.17	0.018	0.018
	LTE Band 4	20M	QPSK	1	0	Left Cheek	0mm	20175	1732.5	18.73	19.00	1.064	0.14	0.021	0.022
	LTE Band 4	20M	QPSK	50	0	Left Cheek	0mm	20175	1732.5	18.93	19.00	1.016	0.16	0.021	0.021
	LTE Band 4	20M	QPSK	1	0	Left Tilted	0mm	20175	1732.5	18.73	19.00	1.064	0.08	0.016	0.017
	LTE Band 4	20M	QPSK	50	0	Left Tilted	0mm	20175	1732.5	18.93	19.00	1.016	-0.18	0.016	0.016
	LTE Band 12	10M	QPSK	1	0	Right Cheek	0mm	23095	707.5	24.03	25.00	1.250	0.03	0.243	0.304
	LTE Band 12	10M	QPSK	25	12	Right Cheek	0mm	23095	707.5	23.08	24.00	1.236	-0.02	0.205	0.253
	LTE Band 12	10M	QPSK	1	0	Right Tilted	0mm	23095	707.5	24.03	25.00	1.250	0.17	0.115	0.144
	LTE Band 12	10M	QPSK	25	12	Right Tilted	0mm	23095	707.5	23.08	24.00	1.236	0.08	0.093	0.115
07	LTE Band 12	10M	QPSK	1	0	Left Cheek	0mm	23095	707.5	24.03	25.00	1.250	-0.04	0.305	0.381
	LTE Band 12	10M	QPSK	25	12	Left Cheek	0mm	23095	707.5	23.08	24.00	1.236	0.04	0.246	0.304
	LTE Band 12	10M	QPSK	1	0	Left Tilted	0mm	23095	707.5	24.03	25.00	1.250	-0.14	0.125	0.156
	LTE Band 12	10M	QPSK	25	12	Left Tilted	0mm	23095	707.5	23.08	24.00	1.236	0.05	0.097	0.120

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	0	Right Cheek	0mm	39750	2506	17.41	18.00	1.146	62.9	1.006	0.17	0.010	0.011
	LTE Band 41	20M	QPSK	50	24	Right Cheek	0mm	39750	2506	17.56	18.00	1.107	62.9	1.006	0.04	0.011	0.012
	LTE Band 41	20M	QPSK	1	0	Right Tilted	0mm	39750	2506	17.41	18.00	1.146	62.9	1.006	0	0.001	0.001
	LTE Band 41	20M	QPSK	50	24	Right Tilted	0mm	39750	2506	17.56	18.00	1.107	62.9	1.006	0.13	0.003	0.004
08	LTE Band 41	20M	QPSK	1	0	Left Cheek	0mm	39750	2506	17.41	18.00	1.146	62.9	1.006	-0.16	0.017	0.020
	LTE Band 41	20M	QPSK	50	24	Left Cheek	0mm	39750	2506	17.56	18.00	1.107	62.9	1.006	0.18	0.009	0.010
	LTE Band 41	20M	QPSK	1	0	Left Tilted	0mm	39750	2506	17.41	18.00	1.146	62.9	1.006	0.15	0.004	0.005
	LTE Band 41	20M	QPSK	50	24	Left Tilted	0mm	39750	2506	17.56	18.00	1.107	62.9	1.006	0.12	0.006	0.006

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
09	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Chain 0	11	2462	14.20	14.50	1.072	100	1.000	-0.11	0.340	0.364
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	Chain 0	11	2462	14.20	14.50	1.072	100	1.000	-0.03	0.049	0.053
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Chain 0	11	2462	14.20	14.50	1.072	100	1.000	0.06	0.074	0.079
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	Chain 0	11	2462	14.20	14.50	1.072	100	1.000	0.19	0.017	0.018
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Chain 1	12	2467	13.80	14.00	1.047	100	1.000	0.1	0.001	0.001
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	Chain 1	12	2467	13.80	14.00	1.047	100	1.000	-0.01	0.001	0.001
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Chain 1	12	2467	13.80	14.00	1.047	100	1.000	-0.1	0.001	0.001
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	Chain 1	12	2467	13.80	14.00	1.047	100	1.000	-0.11	0.001	0.001
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 0	58	5290	13.80	14.00	1.047	97.01	1.031	0.03	0.111	0.120
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 0	58	5290	13.80	14.00	1.047	97.01	1.031	0.04	0.013	0.014
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 0	58	5290	13.80	14.00	1.047	97.01	1.031	0.01	0.028	0.030
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 0	58	5290	13.80	14.00	1.047	97.01	1.031	-0.04	0.011	0.012
10	WLAN5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 1	58	5290	11.60	12.00	1.096	97.01	1.031	0.05	0.121	0.137
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 1	58	5290	11.60	12.00	1.096	97.01	1.031	-0.06	0.065	0.073
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 1	58	5290	11.60	12.00	1.096	97.01	1.031	-0.07	0.067	0.076
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 1	58	5290	11.60	12.00	1.096	97.01	1.031	-0.06	0.059	0.067
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 0	106	5530	14.00	14.00	1.000	97.01	1.031	-0.07	0.106	0.109
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 0	106	5530	14.00	14.00	1.000	97.01	1.031	0	0.001	0.001
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 0	106	5530	14.00	14.00	1.000	97.01	1.031	-0.06	0.030	0.031
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 0	106	5530	14.00	14.00	1.000	97.01	1.031	0.08	0.007	0.007
11	WLAN5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 1	106	5530	11.60	12.00	1.096	97.01	1.031	0.17	0.219	0.248
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 1	106	5530	11.60	12.00	1.096	97.01	1.031	-0.03	0.179	0.202
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 1	106	5530	11.60	12.00	1.096	97.01	1.031	-0.03	0.078	0.088
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 1	106	5530	11.60	12.00	1.096	97.01	1.031	-0.16	0.072	0.081
12	WLAN5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 0	155	5775	13.50	14.00	1.122	97.01	1.031	-0.1	0.083	0.096
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 0	155	5775	13.50	14.00	1.122	97.01	1.031	-0.1	0.004	0.005
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 0	155	5775	13.50	14.00	1.122	97.01	1.031	-0.18	0.012	0.014
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 0	155	5775	13.50	14.00	1.122	97.01	1.031	-0.13	0.001	0.001
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Chain 1	155	5775	11.50	12.00	1.122	97.01	1.031	0.14	0.077	0.089
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Chain 1	155	5775	11.50	12.00	1.122	97.01	1.031	-0.03	0.065	0.075
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Chain 1	155	5775	11.50	12.00	1.122	97.01	1.031	-0.17	0.022	0.025
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Chain 1	155	5775	11.50	12.00	1.122	97.01	1.031	-0.12	0.019	0.022

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
13	Bluetooth	1Mbps	Right Cheek	0mm	Chain 0	39	2441	10.78	12.78	1.584	76.84	1.084	0.07	0.118	0.203
	Bluetooth	1Mbps	Right Tilted	0mm	Chain 0	39	2441	10.78	12.78	1.584	76.84	1.084	-0.08	0.015	0.026
	Bluetooth	1Mbps	Left Cheek	0mm	Chain 0	39	2441	10.78	12.78	1.584	76.84	1.084	0.14	0.027	0.046
	Bluetooth	1Mbps	Left Tilted	0mm	Chain 0	39	2441	10.78	12.78	1.584	76.84	1.084	-0.1	0.003	0.005

13.2 Hotspot SAR
<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Front	10mm	128	824.2	26.81	27.20	1.094	-0.08	0.131	0.143
	GSM850	GPRS (4 Tx slots)	Back	10mm	128	824.2	26.81	27.20	1.094	0	0.128	0.140
14	GSM850	GPRS (4 Tx slots)	Left Side	10mm	128	824.2	26.81	27.20	1.094	0.02	0.153	0.167
	GSM850	GPRS (4 Tx slots)	Right Side	10mm	128	824.2	26.81	27.20	1.094	-0.01	0.088	0.096
	GSM850	GPRS (4 Tx slots)	Bottom Side	10mm	128	824.2	26.81	27.20	1.094	0.11	0.097	0.106
	GSM1900	GPRS (4 Tx slots)	Front	10mm	661	1880	21.99	22.70	1.178	0.02	0.199	0.234
	GSM1900	GPRS (4 Tx slots)	Back	10mm	661	1880	21.99	22.70	1.178	0.09	0.173	0.204
	GSM1900	GPRS (4 Tx slots)	Left Side	10mm	661	1880	21.99	22.70	1.178	-0.03	0.023	0.027
	GSM1900	GPRS (4 Tx slots)	Right Side	10mm	661	1880	21.99	22.70	1.178	-0.04	0.019	0.022
15	GSM1900	GPRS (4 Tx slots)	Bottom Side	10mm	661	1880	21.99	22.70	1.178	0.03	0.444	0.523

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	10mm	9400	1880	18.53	18.70	1.040	-0.04	0.363	0.377
	WCDMA II	RMC 12.2Kbps	Back	10mm	9400	1880	18.53	18.70	1.040	0	0.329	0.342
	WCDMA II	RMC 12.2Kbps	Left Side	10mm	9400	1880	18.53	18.70	1.040	0.14	0.038	0.040
	WCDMA II	RMC 12.2Kbps	Right Side	10mm	9400	1880	18.53	18.70	1.040	0.03	0.029	0.030
16	WCDMA II	RMC 12.2Kbps	Bottom Side	10mm	9400	1880	18.53	18.70	1.040	-0.07	0.703	0.731
	WCDMA IV	RMC 12.2Kbps	Front	10mm	1312	1712.4	18.69	18.70	1.002	0.03	0.416	0.417
	WCDMA IV	RMC 12.2Kbps	Back	10mm	1312	1712.4	18.69	18.70	1.002	-0.01	0.418	0.419
	WCDMA IV	RMC 12.2Kbps	Left Side	10mm	1312	1712.4	18.69	18.70	1.002	-0.19	0.020	0.020
	WCDMA IV	RMC 12.2Kbps	Right Side	10mm	1312	1712.4	18.69	18.70	1.002	-0.09	0.047	0.047
17	WCDMA IV	RMC 12.2Kbps	Bottom Side	10mm	1312	1712.4	18.69	18.70	1.002	-0.01	0.618	0.619

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Front	10mm	18900	1880	18.78	19.00	1.052	-0.04	0.369	0.388
	LTE Band 2	20M	QPSK	50	0	Front	10mm	18900	1880	18.90	19.00	1.023	0.03	0.371	0.380
	LTE Band 2	20M	QPSK	1	0	Back	10mm	18900	1880	18.78	19.00	1.052	0.04	0.340	0.358
	LTE Band 2	20M	QPSK	50	0	Back	10mm	18900	1880	18.90	19.00	1.023	0	0.341	0.349
	LTE Band 2	20M	QPSK	1	0	Left Side	10mm	18900	1880	18.78	19.00	1.052	0.08	0.040	0.042
	LTE Band 2	20M	QPSK	50	0	Left Side	10mm	18900	1880	18.90	19.00	1.023	-0.06	0.040	0.041
	LTE Band 2	20M	QPSK	1	0	Right Side	10mm	18900	1880	18.78	19.00	1.052	-0.01	0.029	0.031
	LTE Band 2	20M	QPSK	50	0	Right Side	10mm	18900	1880	18.90	19.00	1.023	0.16	0.030	0.031
18	LTE Band 2	20M	QPSK	1	0	Bottom Side	10mm	18900	1880	18.78	19.00	1.052	0	0.707	0.744
	LTE Band 2	20M	QPSK	50	0	Bottom Side	10mm	18900	1880	18.90	19.00	1.023	-0.01	0.719	0.736
	LTE Band 4	20M	QPSK	1	0	Front	10mm	20175	1732.5	18.73	19.00	1.064	0.06	0.380	0.404
	LTE Band 4	20M	QPSK	50	0	Front	10mm	20175	1732.5	18.93	19.00	1.016	0	0.394	0.400
	LTE Band 4	20M	QPSK	1	0	Back	10mm	20175	1732.5	18.73	19.00	1.064	-0.03	0.416	0.443
	LTE Band 4	20M	QPSK	50	0	Back	10mm	20175	1732.5	18.93	19.00	1.016	-0.03	0.430	0.437
	LTE Band 4	20M	QPSK	1	0	Left Side	10mm	20175	1732.5	18.73	19.00	1.064	-0.11	0.019	0.020
	LTE Band 4	20M	QPSK	50	0	Left Side	10mm	20175	1732.5	18.93	19.00	1.016	0.11	0.020	0.020
	LTE Band 4	20M	QPSK	1	0	Right Side	10mm	20175	1732.5	18.73	19.00	1.064	0.1	0.047	0.050
	LTE Band 4	20M	QPSK	50	0	Right Side	10mm	20175	1732.5	18.93	19.00	1.016	0.01	0.050	0.051
	LTE Band 4	20M	QPSK	1	0	Bottom Side	10mm	20175	1732.5	18.73	19.00	1.064	-0.05	0.618	0.658
19	LTE Band 4	20M	QPSK	50	0	Bottom Side	10mm	20175	1732.5	18.93	19.00	1.016	-0.01	0.654	0.665
	LTE Band 12	10M	QPSK	1	0	Front	10mm	23095	707.5	24.03	25.00	1.250	0.02	0.238	0.298
	LTE Band 12	10M	QPSK	25	12	Front	10mm	23095	707.5	23.08	24.00	1.236	0	0.191	0.236
20	LTE Band 12	10M	QPSK	1	0	Back	10mm	23095	707.5	24.03	25.00	1.250	-0.01	0.256	0.320
	LTE Band 12	10M	QPSK	25	12	Back	10mm	23095	707.5	23.08	24.00	1.236	-0.01	0.204	0.252
	LTE Band 12	10M	QPSK	1	0	Left Side	10mm	23095	707.5	24.03	25.00	1.250	0	0.240	0.300
	LTE Band 12	10M	QPSK	25	12	Left Side	10mm	23095	707.5	23.08	24.00	1.236	0.01	0.190	0.235
	LTE Band 12	10M	QPSK	1	0	Right Side	10mm	23095	707.5	24.03	25.00	1.250	0.01	0.185	0.231
	LTE Band 12	10M	QPSK	25	12	Right Side	10mm	23095	707.5	23.08	24.00	1.236	0.01	0.150	0.185
	LTE Band 12	10M	QPSK	1	0	Bottom Side	10mm	23095	707.5	24.03	25.00	1.250	-0.02	0.087	0.109
	LTE Band 12	10M	QPSK	25	12	Bottom Side	10mm	23095	707.5	23.08	24.00	1.236	0.06	0.073	0.090

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	0	Front	10mm	39750	2506	17.41	18.00	1.146	62.9	1.006	-0.1	0.042	0.048
	LTE Band 41	20M	QPSK	50	24	Front	10mm	39750	2506	17.56	18.00	1.107	62.9	1.006	0.05	0.047	0.052
	LTE Band 41	20M	QPSK	1	0	Back	10mm	39750	2506	17.41	18.00	1.146	62.9	1.006	0.02	0.046	0.053
	LTE Band 41	20M	QPSK	50	24	Back	10mm	39750	2506	17.56	18.00	1.107	62.9	1.006	-0.06	0.047	0.052
	LTE Band 41	20M	QPSK	1	0	Left Side	10mm	39750	2506	17.41	18.00	1.146	62.9	1.006	0.12	0.010	0.011
	LTE Band 41	20M	QPSK	50	24	Left Side	10mm	39750	2506	17.56	18.00	1.107	62.9	1.006	0.03	0.012	0.013
	LTE Band 41	20M	QPSK	1	0	Right Side	10mm	39750	2506	17.41	18.00	1.146	62.9	1.006	-0.1	0.028	0.032
	LTE Band 41	20M	QPSK	50	24	Right Side	10mm	39750	2506	17.56	18.00	1.107	62.9	1.006	0.01	0.029	0.032
	LTE Band 41	20M	QPSK	1	0	Bottom Side	10mm	39750	2506	17.41	18.00	1.146	62.9	1.006	0.09	0.081	0.093
21	LTE Band 41	20M	QPSK	50	24	Bottom Side	10mm	39750	2506	17.56	18.00	1.107	62.9	1.006	0.04	0.086	0.096

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Chain 0	11	2462	14.20	14.50	1.072	100	1.000	-0.19	0.051	0.055
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Chain 0	11	2462	14.20	14.50	1.072	100	1.000	-0.17	0.076	0.081
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Chain 0	11	2462	14.20	14.50	1.072	100	1.000	-0.13	0.096	0.103
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	Chain 0	11	2462	14.20	14.50	1.072	100	1.000	-0.19	0.001	0.001
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Chain 1	12	2467	13.80	14.00	1.047	100	1.000	0.18	0.001	0.001
22	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Chain 1	12	2467	13.80	14.00	1.047	100	1.000	-0.17	0.161	0.169
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Chain 1	12	2467	13.80	14.00	1.047	100	1.000	-0.1	0.018	0.019

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	10mm	Chain 0	39	2441	10.78	12.78	1.584	76.84	1.084	-0.1	0.013	0.022
	Bluetooth	1Mbps	Back	10mm	Chain 0	39	2441	10.78	12.78	1.584	76.84	1.084	-0.12	0.023	0.039
23	Bluetooth	1Mbps	Left Side	10mm	Chain 0	39	2441	10.78	12.78	1.584	76.84	1.084	-0.12	0.028	0.048
	Bluetooth	1Mbps	Top Side	10mm	Chain 0	39	2441	10.78	12.78	1.584	76.84	1.084	0	0.001	0.002

13.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
24	GSM850	GPRS (4 Tx slots)	Front	15mm	128	824.2	26.81	27.20	1.094	-0.02	0.127	0.139
	GSM850	GPRS (4 Tx slots)	Back	15mm	128	824.2	26.81	27.20	1.094	-0.02	0.126	0.138
25	GSM1900	GPRS (4 Tx slots)	Front	15mm	661	1880	21.99	22.70	1.178	-0.06	0.125	0.147
	GSM1900	GPRS (4 Tx slots)	Back	15mm	661	1880	21.99	22.70	1.178	0.06	0.099	0.117

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
26	WCDMA II	RMC 12.2Kbps	Front	15mm	9400	1880	18.53	18.70	1.040	-0.04	0.167	0.174
	WCDMA II	RMC 12.2Kbps	Back	15mm	9400	1880	18.53	18.70	1.040	-0.1	0.156	0.162
	WCDMA IV	RMC 12.2Kbps	Front	15mm	1312	1712.4	18.69	18.70	1.002	-0.03	0.196	0.196
27	WCDMA IV	RMC 12.2Kbps	Back	15mm	1312	1712.4	18.69	18.70	1.002	-0.01	0.216	0.216

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
28	LTE Band 2	20M	QPSK	1	0	Front	15mm	18900	1880	18.78	19.00	1.052	0.03	0.169	0.178
	LTE Band 2	20M	QPSK	50	0	Front	15mm	18900	1880	18.90	19.00	1.023	0.04	0.172	0.176
	LTE Band 2	20M	QPSK	1	0	Back	15mm	18900	1880	18.78	19.00	1.052	0.01	0.156	0.164
	LTE Band 2	20M	QPSK	50	0	Back	15mm	18900	1880	18.90	19.00	1.023	0.03	0.158	0.162
	LTE Band 4	20M	QPSK	1	0	Front	15mm	20175	1732.5	18.73	19.00	1.064	-0.04	0.188	0.200
	LTE Band 4	20M	QPSK	50	0	Front	15mm	20175	1732.5	18.93	19.00	1.016	0.01	0.195	0.198
29	LTE Band 4	20M	QPSK	1	0	Back	15mm	20175	1732.5	18.73	19.00	1.064	0	0.214	0.228
	LTE Band 4	20M	QPSK	50	0	Back	15mm	20175	1732.5	18.93	19.00	1.016	-0.03	0.220	0.224
	LTE Band 12	10M	QPSK	1	0	Front	15mm	23095	707.5	24.03	25.00	1.250	-0.01	0.233	0.291
	LTE Band 12	10M	QPSK	25	12	Front	15mm	23095	707.5	23.08	24.00	1.236	-0.01	0.187	0.231
30	LTE Band 12	10M	QPSK	1	0	Back	15mm	23095	707.5	24.03	25.00	1.250	0	0.233	0.291
	LTE Band 12	10M	QPSK	25	12	Back	15mm	23095	707.5	23.08	24.00	1.236	0	0.188	0.232

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	0	Front	15mm	39750	2506	17.41	18.00	1.146	62.9	1.006	0.04	0.025	0.029
	LTE Band 41	20M	QPSK	50	24	Front	15mm	39750	2506	17.56	18.00	1.107	62.9	1.006	0.11	0.025	0.028
31	LTE Band 41	20M	QPSK	1	0	Back	15mm	39750	2506	17.41	18.00	1.146	62.9	1.006	0.05	0.026	0.030
	LTE Band 41	20M	QPSK	50	24	Back	15mm	39750	2506	17.56	18.00	1.107	62.9	1.006	-0.07	0.026	0.029

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	15mm	Chain 0	11	2462	14.20	14.50	1.072	100	1.000	-0.17	0.017	0.018
	WLAN2.4GHz	802.11b 1Mbps	Back	15mm	Chain 0	11	2462	14.20	14.50	1.072	100	1.000	-0.16	0.031	0.033
	WLAN2.4GHz	802.11b 1Mbps	Front	15mm	Chain 1	12	2467	13.80	14.00	1.047	100	1.000	0.11	0.001	0.001
32	WLAN2.4GHz	802.11b 1Mbps	Back	15mm	Chain 1	12	2467	13.80	14.00	1.047	100	1.000	-0.15	0.057	0.060
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	15mm	Chain 0	58	5290	13.80	14.00	1.047	97.01	1.031	-0.14	0.000	0.001
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	15mm	Chain 0	58	5290	13.80	14.00	1.047	97.01	1.031	-0.15	0.016	0.017
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	15mm	Chain 1	58	5290	11.60	12.00	1.096	97.01	1.031	0	0.001	0.001
33	WLAN5GHz	802.11ac-VHT80 MCS0	Back	15mm	Chain 1	58	5290	11.60	12.00	1.096	97.01	1.031	0.18	0.017	0.019
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	15mm	Chain 0	106	5530	14.00	14.00	1.000	97.01	1.031	-0.14	0.001	0.001
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	15mm	Chain 0	106	5530	14.00	14.00	1.000	97.01	1.031	-0.07	0.015	0.015
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	15mm	Chain 1	106	5530	11.60	12.00	1.096	97.01	1.031	-0.12	0.004	0.005
34	WLAN5GHz	802.11ac-VHT80 MCS0	Back	15mm	Chain 1	106	5530	11.60	12.00	1.096	97.01	1.031	-0.18	0.113	0.128
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	15mm	Chain 0	155	5775	13.50	14.00	1.122	97.01	1.031	0	0.006	0.007
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	15mm	Chain 0	155	5775	13.50	14.00	1.122	97.01	1.031	0.13	0.003	0.004
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	15mm	Chain 1	155	5775	11.50	12.00	1.122	97.01	1.031	0.13	0.001	0.001
35	WLAN5GHz	802.11ac-VHT80 MCS0	Back	15mm	Chain 1	155	5775	11.50	12.00	1.122	97.01	1.031	-0.11	0.124	0.143

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	15mm	Chain 0	39	2441	10.78	12.78	1.584	76.84	1.084	-0.09	0.003	0.005
36	Bluetooth	1Mbps	Back	15mm	Chain 0	39	2441	10.78	12.78	1.584	76.84	1.084	0.1	0.008	0.013



13.4 Product Specific SAR

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	0mm	Chain 0	58	5290	13.80	14.00	1.047	97.01	1.031	0.12	0.096	0.104
37	WLAN5GHz	802.11ac-VHT80 MCS0	Back	0mm	Chain 0	58	5290	13.80	14.00	1.047	97.01	1.031	0.19	0.397	0.429
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 0	58	5290	13.80	14.00	1.047	97.01	1.031	-0.18	0.134	0.145
	WLAN5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 0	58	5290	13.80	14.00	1.047	97.01	1.031	0.01	0.001	0.001
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	0mm	Chain 1	58	5290	11.60	12.00	1.096	97.01	1.031	0.13	0.075	0.085
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	0mm	Chain 1	58	5290	11.60	12.00	1.096	97.01	1.031	-0.18	0.162	0.183
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 1	58	5290	11.60	12.00	1.096	97.01	1.031	-0.11	0.006	0.007
	WLAN5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 1	58	5290	11.60	12.00	1.096	97.01	1.031	-0.14	0.017	0.019
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	0mm	Chain 0	106	5530	14.00	14.00	1.000	97.01	1.031	0.14	0.095	0.098
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	0mm	Chain 0	106	5530	14.00	14.00	1.000	97.01	1.031	-0.18	0.286	0.295
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 0	106	5530	14.00	14.00	1.000	97.01	1.031	-0.17	0.112	0.115
	WLAN5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 0	106	5530	14.00	14.00	1.000	97.01	1.031	0	0.001	0.001
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	0mm	Chain 1	106	5530	11.60	12.00	1.096	97.01	1.031	0.09	0.094	0.106
38	WLAN5GHz	802.11ac-VHT80 MCS0	Back	0mm	Chain 1	106	5530	11.60	12.00	1.096	97.01	1.031	-0.18	0.463	0.523
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 1	106	5530	11.60	12.00	1.096	97.01	1.031	-0.09	0.034	0.038
	WLAN5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 1	106	5530	11.60	12.00	1.096	97.01	1.031	-0.13	0.069	0.078
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	0mm	Chain 0	155	5775	13.50	14.00	1.122	97.01	1.031	0.15	0.053	0.061
	WLAN5GHz	802.11ac-VHT80 MCS0	Back	0mm	Chain 0	155	5775	13.50	14.00	1.122	97.01	1.031	-0.12	0.191	0.221
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 0	155	5775	13.50	14.00	1.122	97.01	1.031	-0.15	0.066	0.076
	WLAN5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 0	155	5775	13.50	14.00	1.122	97.01	1.031	0	0.001	0.001
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	0mm	Chain 1	155	5775	11.50	12.00	1.122	97.01	1.031	0.16	0.038	0.044
39	WLAN5GHz	802.11ac-VHT80 MCS0	Back	0mm	Chain 1	155	5775	11.50	12.00	1.122	97.01	1.031	-0.12	0.461	0.533
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Side	0mm	Chain 1	155	5775	11.50	12.00	1.122	97.01	1.031	-0.01	0.029	0.034
	WLAN5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Chain 1	155	5775	11.50	12.00	1.122	97.01	1.031	-0.16	0.066	0.076

14. Simultaneous Transmission Analysis

Case	Cellular	WLAN Chain0 / BT	WLAN Chain1
1	GSM/GPRS/EDGE	BT/BLE	(None)
2	GSM/GPRS/EDGE	WLAN 2.4G	WLAN 2.4G
3	GSM/GPRS/EDGE	WLAN 5G	WLAN 5G
4	UMTS/HSPA	BT/BLE	(None)
5	UMTS/HSPA	WLAN 2.4G	WLAN 2.4G
6	UMTS/HSPA	WLAN 5G	WLAN 5G
7	LTE	BT/BLE	(None)
8	LTE	WLAN 2.4G	WLAN 2.4G
9	LTE	WLAN 5G	WLAN 5G
10	(None)	BT/BLE WLAN 5G	WLAN 5G
11	GSM/GPRS/EDGE	BT/BLE WLAN 5G	WLAN 5G
12	UMTS/HSPA	BT/BLE WLAN 5G	WLAN 5G
13	LTE	BT/BLE WLAN 5G	WLAN 5G
14	GSM/GPRS/EDGE	WLAN 2.4G	WLAN 5G
15	UMTS/HSPA	WLAN 2.4G	WLAN 5G
16	LTE	WLAN 2.4G	WLAN 5G

General Note:

1. This device WLAN 2.4GHz supports Hotspot operation and Bluetooth support tethering applications.
2. 2.4GHz WLAN and Bluetooth share the same antenna 0, and cannot transmit simultaneously.
3. All licensed modes share the same antenna part and cannot transmit simultaneously
4. The Scaled SAR summation is calculated based on the same configuration and test position.
5. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\min. \text{ separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.



14.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	5	6	1+2+3 Summed 1g SAR (W/kg)	1+4+5+6 Summed 1g SAR (W/kg)	1+2+5 Summed 1g SAR (W/kg)	1+6 Summed 1g SAR (W/kg)	1+4+5 Summed 1g SAR (W/kg)	4+5+6 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN Chain 0	2.4GHz WLAN Chain 1	5GHz WLAN Chain 0	5GHz WLAN Chain 1	Bluetooth Chain 0						
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)						
GSM	GSM850	Right Cheek	0.175	0.364	0.001	0.120	0.248	0.203	0.540	0.746	0.787	0.378	0.543	0.571
		Right Tilted	0.068	0.053	0.001	0.014	0.202	0.026	0.122	0.310	0.323	0.094	0.284	0.242
		Left Cheek	0.218	0.079	0.001	0.031	0.088	0.046	0.298	0.383	0.385	0.264	0.337	0.165
		Left Tilted	0.079	0.018	0.001	0.012	0.081	0.005	0.098	0.177	0.178	0.084	0.172	0.098
	GSM1900	Right Cheek	0.014	0.364	0.001	0.120	0.248	0.203	0.379	0.585	0.626	0.217	0.382	0.571
		Right Tilted	0.001	0.053	0.001	0.014	0.202	0.026	0.055	0.243	0.256	0.027	0.217	0.242
		Left Cheek	0.014	0.079	0.001	0.031	0.088	0.046	0.094	0.179	0.181	0.060	0.133	0.165
		Left Tilted	0.005	0.018	0.001	0.012	0.081	0.005	0.024	0.103	0.104	0.010	0.098	0.098
WCDMA	WCDMA II	Right Cheek	0.024	0.364	0.001	0.120	0.248	0.203	0.389	0.595	0.636	0.227	0.392	0.571
		Right Tilted	0.008	0.053	0.001	0.014	0.202	0.026	0.062	0.250	0.263	0.034	0.224	0.242
		Left Cheek	0.021	0.079	0.001	0.031	0.088	0.046	0.101	0.186	0.188	0.067	0.140	0.165
		Left Tilted	0.011	0.018	0.001	0.012	0.081	0.005	0.030	0.109	0.110	0.016	0.104	0.098
	WCDMA IV	Right Cheek	0.033	0.364	0.001	0.120	0.248	0.203	0.398	0.604	0.645	0.236	0.401	0.571
		Right Tilted	0.012	0.053	0.001	0.014	0.202	0.026	0.066	0.254	0.267	0.038	0.228	0.242
		Left Cheek	0.015	0.079	0.001	0.031	0.088	0.046	0.095	0.180	0.182	0.061	0.134	0.165
		Left Tilted	0.020	0.018	0.001	0.012	0.081	0.005	0.039	0.118	0.119	0.025	0.113	0.098
LTE	LTE Band 2	Right Cheek	0.021	0.364	0.001	0.120	0.248	0.203	0.386	0.592	0.633	0.224	0.389	0.571
		Right Tilted	0.006	0.053	0.001	0.014	0.202	0.026	0.060	0.248	0.261	0.032	0.222	0.242
		Left Cheek	0.023	0.079	0.001	0.031	0.088	0.046	0.103	0.188	0.190	0.069	0.142	0.165
		Left Tilted	0.009	0.018	0.001	0.012	0.081	0.005	0.028	0.107	0.108	0.014	0.102	0.098
	LTE Band 4	Right Cheek	0.043	0.364	0.001	0.120	0.248	0.203	0.408	0.614	0.655	0.246	0.411	0.571
		Right Tilted	0.018	0.053	0.001	0.014	0.202	0.026	0.072	0.260	0.273	0.044	0.234	0.242
		Left Cheek	0.022	0.079	0.001	0.031	0.088	0.046	0.102	0.187	0.189	0.068	0.141	0.165
		Left Tilted	0.017	0.018	0.001	0.012	0.081	0.005	0.036	0.115	0.116	0.022	0.110	0.098
	LTE Band 12	Right Cheek	0.304	0.364	0.001	0.120	0.248	0.203	0.669	0.875	0.916	0.507	0.672	0.571
		Right Tilted	0.144	0.053	0.001	0.014	0.202	0.026	0.198	0.386	0.399	0.170	0.360	0.242
		Left Cheek	0.381	0.079	0.001	0.031	0.088	0.046	0.461	0.546	0.548	0.427	0.500	0.165
		Left Tilted	0.156	0.018	0.001	0.012	0.081	0.005	0.175	0.254	0.255	0.161	0.249	0.098
	LTE Band 41	Right Cheek	0.012	0.364	0.001	0.120	0.248	0.203	0.377	0.583	0.624	0.215	0.380	0.571
		Right Tilted	0.004	0.053	0.001	0.014	0.202	0.026	0.058	0.246	0.259	0.030	0.220	0.242
		Left Cheek	0.020	0.079	0.001	0.031	0.088	0.046	0.100	0.185	0.187	0.066	0.139	0.165
		Left Tilted	0.006	0.018	0.001	0.012	0.081	0.005	0.025	0.104	0.105	0.011	0.099	0.098

14.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	3	6	1+2+3 Summed 1g SAR (W/kg)	1+6 Summed 1g SAR (W/kg)
			WWAN 1g SAR (W/kg)	2.4GHz WLAN Chain 0 1g SAR (W/kg)	2.4GHz WLAN Chain 1 1g SAR (W/kg)	Bluetooth Chain 0 1g SAR (W/kg)		
GSM	GSM850	Front	0.143	0.055	0.001	0.022	0.199	0.165
		Back	0.140	0.081	0.169	0.039	0.390	0.179
		Left side	0.167	0.103	0.019	0.048	0.289	0.215
		Right side	0.096				0.096	0.096
		Top side		0.001		0.002	0.001	0.002
		Bottom side	0.106				0.106	0.106
	GSM1900	Front	0.234	0.055	0.001	0.022	0.290	0.256
		Back	0.204	0.081	0.169	0.039	0.454	0.243
		Left side	0.027	0.103	0.019	0.048	0.149	0.075
		Right side	0.022				0.022	0.022
		Top side		0.001		0.002	0.001	0.002
		Bottom side	0.523				0.523	0.523
WCDMA	WCDMA II	Front	0.377	0.055	0.001	0.022	0.433	0.399
		Back	0.342	0.081	0.169	0.039	0.592	0.381
		Left side	0.040	0.103	0.019	0.048	0.162	0.088
		Right side	0.030				0.030	0.030
		Top side		0.001		0.002	0.001	0.002
		Bottom side	0.731				0.731	0.731
	WCDMA IV	Front	0.417	0.055	0.001	0.022	0.473	0.439
		Back	0.419	0.081	0.169	0.039	0.669	0.458
		Left side	0.020	0.103	0.019	0.048	0.142	0.068
		Right side	0.047				0.047	0.047
		Top side		0.001		0.002	0.001	0.002
		Bottom side	0.619				0.619	0.619
LTE	LTE Band 2	Front	0.388	0.055	0.001	0.022	0.444	0.410
		Back	0.358	0.081	0.169	0.039	0.608	0.397
		Left side	0.042	0.103	0.019	0.048	0.164	0.090
		Right side	0.031				0.031	0.031
		Top side		0.001		0.002	0.001	0.002
		Bottom side	0.744				0.744	0.744
	LTE Band 4	Front	0.404	0.055	0.001	0.022	0.460	0.426
		Back	0.443	0.081	0.169	0.039	0.693	0.482
		Left side	0.020	0.103	0.019	0.048	0.142	0.068
		Right side	0.051				0.051	0.051
		Top side		0.001		0.002	0.001	0.002
		Bottom side	0.665				0.665	0.665
	LTE Band 12	Front	0.298	0.055	0.001	0.022	0.354	0.320
		Back	0.320	0.081	0.169	0.039	0.570	0.359
		Left side	0.300	0.103	0.019	0.048	0.422	0.348
		Right side	0.231				0.231	0.231
		Top side		0.001		0.002	0.001	0.002
		Bottom side	0.109				0.109	0.109
	LTE Band 41	Front	0.052	0.055	0.001	0.022	0.108	0.074
		Back	0.053	0.081	0.169	0.039	0.303	0.092
		Left side	0.013	0.103	0.019	0.048	0.135	0.061
		Right side	0.032				0.032	0.032
		Top side		0.001		0.002	0.001	0.002
		Bottom side	0.096				0.096	0.096

14.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	5	6	1+2+3 Summed 1g SAR (W/kg)	1+4+5+6 Summed 1g SAR (W/kg)	1+2+5 Summed 1g SAR (W/kg)	1+6 Summed 1g SAR (W/kg)	1+4+5 Summed 1g SAR (W/kg)	4+5+6 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN Chain 0	2.4GHz WLAN Chain 1	5GHz WLAN Chain 0	5GHz WLAN Chain 1	Bluetooth Chain 0						
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)						
GSM	GSM850	Front	0.139	0.018	0.001	0.007	0.005	0.005	0.158	0.156	0.162	0.144	0.151	0.017
		Back	0.138	0.033	0.060	0.017	0.143	0.013	0.231	0.311	0.314	0.151	0.298	0.173
	GSM1900	Front	0.147	0.018	0.001	0.007	0.005	0.005	0.166	0.164	0.170	0.152	0.159	0.017
		Back	0.117	0.033	0.060	0.017	0.143	0.013	0.210	0.290	0.293	0.130	0.277	0.173
WCDMA	WCDMA II	Front	0.174	0.018	0.001	0.007	0.005	0.005	0.193	0.191	0.197	0.179	0.186	0.017
		Back	0.162	0.033	0.060	0.017	0.143	0.013	0.255	0.335	0.338	0.175	0.322	0.173
	WCDMA IV	Front	0.196	0.018	0.001	0.007	0.005	0.005	0.215	0.213	0.219	0.201	0.208	0.017
		Back	0.216	0.033	0.060	0.017	0.143	0.013	0.309	0.389	0.392	0.229	0.376	0.173
LTE	LTE Band 2	Front	0.178	0.018	0.001	0.007	0.005	0.005	0.197	0.195	0.201	0.183	0.190	0.017
		Back	0.164	0.033	0.060	0.017	0.143	0.013	0.257	0.337	0.340	0.177	0.324	0.173
	LTE Band 4	Front	0.200	0.018	0.001	0.007	0.005	0.005	0.219	0.217	0.223	0.205	0.212	0.017
		Back	0.228	0.033	0.060	0.017	0.143	0.013	0.321	0.401	0.404	0.241	0.388	0.173
	LTE Band 12	Front	0.291	0.018	0.001	0.007	0.005	0.005	0.310	0.308	0.314	0.296	0.303	0.017
		Back	0.291	0.033	0.060	0.017	0.143	0.013	0.384	0.464	0.467	0.304	0.451	0.173
	LTE Band 41	Front	0.029	0.018	0.001	0.007	0.005	0.005	0.048	0.046	0.052	0.034	0.041	0.017
		Back	0.030	0.033	0.060	0.017	0.143	0.013	0.123	0.203	0.206	0.043	0.190	0.173

14.4 Product Specific Exposure Conditions

Exposure Position	1	2	1+2 Summed 10g SAR (W/kg)
	5GHz WLAN Chain 0	5GHz WLAN Chain 1	
	10g SAR (W/kg)	10g SAR (W/kg)	
Front	0.104	0.106	0.210
Back	0.429	0.533	0.962
Left side	0.145	0.038	0.183
Right side			0.000
Top side	0.001	0.078	0.079
Bottom side			0.000

Remark:

1. According to KDB 648474 D04v01r03, for WWAN / 2.4GHz WLAN / Bluetooth SAR was excluded, due to Hotspot SAR was < 1.2W/kg.
2. According to KDB 941225 D06 v02r01, for 5GHz WLAN SAR was excluded for that position, due to transmitting antenna located larger 25mm from that surface or edge.

Test Engineer : Neil Hsiang Randy Lin Andy Jiang Willy Yu Ted Hsieh Jay Jian Thomas Wang White
Huang Wilson Lin and Carter Chuang

15. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

16. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D05A v01r02, "Rel. 10 LTE SAR Test Guidance and KDB Inquiries", Oct 2015
- [11] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [12] FCC KDB 941225 D07 v01r02, "SAR EVALUATION PROCEDURES FOR UMPC MINI-TABLET DEVICES", Oct. 2015
- [13] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [14] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.