



CERTIFICATION TEST REPORT

Report Number. : 11740661-E1V2

Applicant : SONY MOBILE COMMUNICATIONS INC.
4-12-3 HIGASHI-SHINAGAWA,
SHINAGAWA -KU,TOKYO, 140-0002, JAPAN

FCC ID : PY7-81775I

EUT Description : GSM/WCDMA/LTE Phone with BT,DTS/UNII a/b/g/n/ac, GPS & NFC

Test Standard(s) : FCC CFR47 PART 22 SUBPART H
FCC CFR47 PART 24 SUBPART E
FCC CFR47 PART 27 SUBPART F, H, L, and M
FCC CFR47 PART 90 SUBPART S

Date Of Issue:

July 09, 2017

Prepared by:

UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888



NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
V1	6/23/17	Initial Issue	D. Corona
V2	7/09/17	Updated Section 5.1, 6.1, 6.3, 11.2, 11.6, 11.8-11.9 & 13.1	D. Corona

TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	5
2.	TEST METHODOLOGY	6
3.	FACILITIES AND ACCREDITATION	6
4.	CALIBRATION AND UNCERTAINTY	6
4.1.	MEASURING INSTRUMENT CALIBRATION	6
4.2.	SAMPLE CALCULATION	6
4.3.	MEASUREMENT UNCERTAINTY	7
5.	EQUIPMENT UNDER TEST	7
5.1.	DESCRIPTION OF EUT	7
6.	MAXIMUM OUTPUT POWER	8
6.1.	MAXIMUM OUTPUT POWER (GSM/EGPRS)	8
6.2.	MAXIMUM OUTPUT POWER (WCDMA)	9
6.3.	MAXIMUM OUTPUT POWER (LTE)	10
7.	DESCRIPTION OF AVAILABLE ANTENNAS	14
8.	DESCRIPTION OF TEST SETUP	15
9.	TEST AND MEASUREMENT EQUIPMENT	18
10.	SUMMARY TABLE	19
11.	RF POWER OUTPUT VERIFICATION	20
11.1.	GSM/GPRS/EDGE	21
11.2.	GSM OUTPUT POWER RESULT	22
11.3.	UMTS REL 99	24
11.4.	UMTS REL 99 OUTPUT POWER RESULT	25
11.5.	UMTS HSDPA	26
11.6.	UMTS HSDPA OUTPUT POWER RESULT	27
11.7.	UMTS HSUPA	28
11.8.	UMTS HSUPA OUTPUT POWER RESULT	29
11.9.	UMTS DC-HSDPA	31
11.10.	UMTS DC-HSDPA OUTPUT POWER RESULT	33
11.11.	LTE OUTPUT POWER RESULT	34
12.	PEAK TO AVERAGE RATIO	92
12.1.	CONDUCTED PEAK TO AVERAGE RESULT	93
13.	OCCUPIED BANDWIDTH	108

13.1.	OCCUPIED BANDWIDTH RESULTS AND PLOTS	109
14.	BAND EDGE EMISSIONS.....	136
14.1.	BAND EDGE PLOTS.....	138
14.2.	EMISSION MASK PLOTS	180
15.	OUT OF BAND EMISSIONS	195
15.1.	OUT OF BAND EMISSIONS RESULT AND PLOTS.....	196
16.	FREQUENCY STABILITY	222
16.1.	FREQUENCY STABILITY RESULTS.....	223
17.	RADIATED TEST RESULTS.....	226
17.1.	FIELD STRENGTH OF SPURIOUS RADIATION.....	226
17.1.1.	SPURIOUS RADIATION PLOTS.....	227
18.	SETUP PHOTOS	243

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SONY MOBILE COMMUNICATIONS, INC.
4-12-3 HIGASHI-SHINAGAWA,
SHINAGAWA-KU, TOKYO, 140-0002, JAPAN

EUT DESCRIPTION: GSM/WCDMA/LTE PHONE with BT, DTS/UNII a/b/g/n/ac & NFC

SERIAL NUMBER: QV7000PR0P, QV7000EA0P, QV7001V40N, QV7001NG0N

DATE TESTED: June 6- June 21, 2017

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 22H, 24E, 27H, 27F, 27L, 27M, 90S	PASS

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:

Prepared By:



DAN CORONIA
CONSUMER TECHNOLOGY DIVISION
WISE PROJECT LEAD
UL VERIFICATION SERVICES INC



KIYA KEDIDA
CONSUMER TECHNOLOGY DIVISION
WISE ENGINEER
UL VERIFICATION SERVICES INC

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with TIA-603-D, FCC CFR 47 Part 2, FCC KDB 971168 D01 v02r02, Part 22, Part 24, Part 27 and Part 90.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☐ Chamber A(IC: 2324B-1)	☐ Chamber D(IC: 22541-1)
☐ Chamber B(IC: 2324B-2)	☐ Chamber E(IC: 22541-2)
☒ Chamber C(IC: 2324B-3)	☐ Chamber F(IC: 22541-3)
	☐ Chamber G(IC: 22541-4)
	☐ Chamber H(IC: 22541-5)

The above test sites and facilities are covered under FCC Test Firm Registration # 208313.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0.

Chambers A through C are covered under Industry Canada company address code 2324B with site numbers 2324B -1 through 2324B-3, respectively. Chambers D through H are covered under Industry Canada company address code 22541 with site numbers 22541 -1 through 22541-5, respectively.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

EURP = PSA reading with EUT worst orientation (dBm) + Path loss (dB) – cable loss (between the SG and substitution antenna) + Substitution Antenna Factor (dBi)

ERP = PSA reading with EUT worst orientation (dBm) + Path loss (dB) – cable loss (between the SG and substitution antenna)

(Path loss = Signal generator output – PSA reading with substitution antenna)

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Occupied Channel Bandwidth	± 1.1 %
RF output power, conducted	± 0.35 dB
Power Spectral Density, conducted	± 0.39 dB
Unwanted Emissions, conducted	± 2.9 dB
All emissions, radiated	± 5.36 dB
Temperature	± 0.9 °C
Humidity	± 2.26 % RH
Supply Voltages	± 0.45 %
Time	± 0.2 %

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

This EUT is a GSM/WCDMA/LTE PHONE with BT, DTS/UNII a/b/g/n/ac, GPS & NFC.

6. MAXIMUM OUTPUT POWER

6.1. MAXIMUM OUTPUT POWER (GSM/EGPRS)

The transmitter has a maximum peak conducted and ERP / EIRP output powers as follows:

FCC Part 22/24						
Band	Frequency Range(MHz)	Modulation	Conducted (Average)		ERP/EIRP (Average)	
			AVG(dBm)	AVG(mW)	dBm	mW
850	824~849	GPRS	33.5	2238.72	27.60	575.44
	824~849	EGPRS	27.1	512.86	21.20	131.83
1900	1850~1910	GPRS	26.9	489.78	25.40	346.74
	1850~1910	EGPRS	25.9	389.05	24.40	275.42

6.2. MAXIMUM OUTPUT POWER (WCDMA)

The transmitter has a maximum peak conducted and ERP / EIRP output powers as follows:

FCC Part 22/24/27						
Band	Frequency Range(MHz)	Modulation	Conducted (Average)		ERP/EIRP (Average)	
			AVG(dBm)	AVG(mW)	dBm	mW
Band 2	1850~1910	REL99	18.9	77.62	17.4	54.95
	1850~1910	HSDPA	18.5	70.79	17.0	50.12
	1850~1910	HSUPA	18.2	66.07	16.7	46.77
Band 4	1710~1755	REL99	20.4	109.65	17.2	52.48
	1710~1755	HSDPA	19.8	95.50	16.4	43.65
	1710~1755	HSUPA	19.7	93.33	16.5	44.67
Band 5	824~849	REL99	24.7	295.12	18.8	75.86
	824~849	HSDPA	23.8	239.88	17.9	61.66
	824~849	HSUPA	23.7	234.42	17.8	60.26

6.3. MAXIMUM OUTPUT POWER (LTE)

The transmitter has a maximum peak conducted and ERP/EIRP output powers as follows:

LTE Band 7

FCC Part 27							
Band	Frequency Range(MHz)	BandWidth (MHz)	Modulation	Conducted (Average)		EIRP (Average)	
				AVG(dBm)	AVG(mW)	dBm	mW
LTE7	2500~2570	5MHz	QPSK	22.1	162.18	19.00	79.43
			16QAM	21.7	147.91	18.60	72.44
		10MHz	QPSK	22.1	162.18	19.00	79.43
			16QAM	21.8	151.36	18.70	74.13
		15MHz	QPSK	21.1	128.82	19.00	79.43
			16QAM	21.9	154.88	18.80	75.86
		20MHz	QPSK	21.1	128.82	19.00	79.43
			16QAM	22.0	158.49	18.9	77.62

LTE Band 12

FCC Part 27							
Band	Frequency Range(MHz)	BandWidth (MHz)	Modulation	Conducted (Average)		ERP (Average)	
				AVG(dBm)	AVG(mW)	dBm	mW
LTE12	699~716	1.4MHz	QPSK	24.0	251.19	15.00	31.62
			16QAM	24.0	251.19	15.00	31.62
		3MHz	QPSK	24.1	257.04	15.10	32.36
			16QAM	24.1	257.04	15.00	31.62
		5MHz	QPSK	24.0	251.19	15.00	31.62
			16QAM	24.0	251.19	15.00	31.62
		10MHz	QPSK	24.0	251.19	15.00	31.62
			16QAM	23.6	229.09	14.60	28.84

LTE Band 13

FCC Part 27							
Band	Frequency Range(MHz)	BandWidth (MHz)	Modulation	Conducted (Average)		ERP (Average)	
				AVG(dBm)	AVG(mW)	dBm	mW
LTE13	777~787	5MHz	QPSK	23.6	229.09	17.70	58.88
			16QAM	22.7	186.21	16.80	47.86
		10MHz	QPSK	23.7	234.42	17.80	60.26
			16QAM	22.7	186.21	16.80	47.86

LTE Band 25

FCC Part 24							
Band	Frequency Range(MHz)	BandWidth (MHz)	Modulation	Conducted (Average)		ERIP (Average)	
				AVG(dBm)	AVG(mW)	dBm	mW
LTE25	1850~1915	1.4MHz	QPSK	18.7	74.13	17.20	52.48
			16QAM	18.3	67.61	16.80	47.86
		3MHz	QPSK	18.7	74.13	17.2	52.48
			16QAM	18.4	69.18	16.90	48.98
		5MHz	QPSK	18.7	74.13	17.20	52.48
			16QAM	18.3	67.61	16.80	47.86
		10MHz	QPSK	18.7	74.13	17.20	52.48
			16QAM	18.5	70.79	17.00	50.12
		15MHz	QPSK	18.5	70.79	17.00	50.12
			16QAM	18.2	66.07	16.70	46.77
		20MHz	QPSK	18.7	74.13	17.20	52.48
			16QAM	18.7	74.13	17.20	52.48

LTE Band 26 PART 90

FCC Part 90							
Band	Frequency Range(MHz)	BandWidth (MHz)	Modulation	Conducted (Average)		ERP (Average)	
				AVG(dBm)	AVG(mW)	dBm	mW
LTE26	814~824	1.4MHz	QPSK	24.9	309.03	19.00	79.43
			16QAM	23.9	245.47	18.00	63.10
		3MHz	QPSK	24.5	281.84	18.60	72.44
			16QAM	24.1	257.04	18.60	72.44
		5MHz	QPSK	24.6	288.40	18.70	74.13
			16QAM	23.8	239.88	17.90	61.66
		10MHz	QPSK	24.5	281.84	18.60	72.44
			16QAM	24.1	257.04	18.20	66.07

LTE Band 26 PART 22

FCC Part 22							
Band	Frequency Range(MHz)	BandWidth (MHz)	Modulation	Conducted (Average)		ERP (Average)	
				AVG(dBm)	AVG(mW)	dBm	mW
LTE26	824~849	1.4MHz	QPSK	24.9	309.03	19.00	79.43
			16QAM	23.9	245.47	18.00	63.10
		3MHz	QPSK	24.5	281.84	18.60	72.44
			16QAM	24.1	257.04	18.60	72.44
		5MHz	QPSK	24.6	288.40	18.70	74.13
			16QAM	23.8	239.88	17.90	61.66
		10MHz	QPSK	24.5	281.84	18.60	72.44
			16QAM	24.1	257.04	18.20	66.07
		15MHz	QPSK	24.9	309.03	19.00	79.43
			16QAM	23.8	239.88	17.90	61.66

LTE Band 41

FCC Part 27							
Band	Frequency Range(MHz)	BandWidth (MHz)	Modulation	Conducted (Average)		EIRP (Average)	
				AVG(dBm)	AVG(mW)	dBm	mW
LTE41	2496~2690	5MHz	QPSK	23.6	229.09	20.90	123.03
			16QAM	23.0	199.53	20.30	107.15
		10MHz	QPSK	23.7	234.42	21.00	125.89
			16QAM	23.5	223.87	20.80	120.23
		15MHz	QPSK	23.8	239.88	21.10	128.82
			16QAM	23.2	208.93	20.50	112.20
		20MHz	QPSK	23.8	239.88	21.10	128.82
			16QAM	23.8	239.88	20.80	120.23

LTE Band 66

FCC Part 24							
Band	Frequency Range(MHz)	BandWidth (MHz)	Modulation	Conducted (Average)		EIRP (Average)	
				AVG(dBm)	AVG(mW)	AVG(dBm)	AVG(mW)
LTE66	1710~1780	1.4MHz	QPSK	20.2	104.71	17.90	61.66
			16QAM	20.1	102.33	17.80	60.26
		3MHz	QPSK	20.3	107.15	18.0	63.10
			16QAM	20.1	102.33	17.80	60.26
		5MHz	QPSK	20.4	109.65	18.10	64.57
			16QAM	20.3	107.15	18.00	63.10
		10MHz	QPSK	20.3	107.15	18.00	63.10
			16QAM	20.2	104.71	17.80	60.26
		15MHz	QPSK	20.4	109.65	18.10	64.57
			16QAM	20.3	107.15	18.00	63.10
		20MHz	QPSK	20.5	112.20	18.20	66.07
			16QAM	20.3	107.15	18.00	63.10

7. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a PIFA antenna for the [List the bands supported] with a maximum peak gain as follow:

Frequency (MHz)	Peak Gain (dBi)
GSM850, 824~849MHz	-5.9
GSM1900, 1850~1910MHz	-1.5
WCDMA Band 2, 1850~1910	-1.5
WCDMA Band 4, 1710~1755	-3.2
WCDMA Band 5, 824~849	-5.9
LTE Band 7, 2500~2570MHz	-3.1
LTE Band 12, 699~716MHz	-9.0
LTE Band 13, 777~787MHz	-5.9
LTE Band 25, 1850~1915MHz	-1.5
LTE Band 26, 824~849MHz	-5.9
LTE Band 41, 2496~2690MHz	-2.7
LTE Band 66, 1710~1780MHz	-2.3

8. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	SONY	1300-7137.1	4016W40310044	NA
Earphone	SONY	N/A	N/A	N/A

I/O CABLES (CONDUCTED SETUP)

I/O Cable List						
Cable No	Port	# of Identical ports	Connector Type	Serial Type	Cable Length (m)	Remarks
1	RF Out	1	Spectrum Analyzer	Shielded	None	NA
2	Antenna Port	1	EUT	Shielded	0.1m	NA
3	RF In/Out	1	Communication Test Set	Shielded	1m	NA


I/O CABLES (RADIATED SETUP)

I/O Cable List						
Cable No	Port	# of Identical ports	Connector Type	Serial Type	Cable Length (m)	Remarks
1	USB	1	AC Adapter	Un-shielded	1.2m	No
2	Jack	1	Headset	Shielded	1m	No
3	RF In/out	1	Communication Test Set	Un-shielded	2m	Yes


TEST SETUP

The EUT is continuously communicated to the call box during the tests.

SETUP DIAGRAM FOR TESTS (CONDUCTED TEST SETUP)



SETUP DIAGRAM FOR TESTS (RADIATED TEST SETUP)



9. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List					
Description	Manufacturer	Model	T Number	Cal Date	Cal Due
Amplifier, 1 to 18 GHz	Miteq	AFS43-00101800-25-S-42	493	02/15/17	02/15/18
Amplifier, 1 to 8 GHz	Miteq	AMF-4D-01000800-30-29P	1156	02/15/17	02/15/18
Amplifier, 10KHz to 1GHz, 32dB	Keysight	8447D	10	02/15/17	02/15/18
Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences	JB3	408	11/10/16	11/10/17
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A	907	01/23/17	01/23/18
Highpass Filter, 2.7 GHz	Micro-Circuits	H2G518G6	T772	7/5/16	07/5/18
Highpass Filter, 1 GHz	Micro-Tronics	HPM18129	T889	2/21/17	02/21/18
Highpass Filter, 4GHz	Micro-Tronics	HPM13351	T1241	7/19/16	07/19/17
Amplifier, 1-18GHz	Miteq	AFS42-00101800-25-S-42	931	08/26/16	08/26/17
Amplifier, 10KHz to 1GHz, 32dB	Keysight	8447D	15	08/26/16	08/26/17
Antenna, Broadband Hybrid 30MHz to 2000MHz	Sunol Sciences	JB3	408	11/10/16	11/10/17
Antenna, Horn 1-18GHz	ETS Lindgren	3117	712	01/30/17	01/30/18
Spectrum Analyzer, PXA, 3Hz to 44GHz	Keysight	N9030A	905	01/11/17	01/11/18
DC power supply, 8 V @ 3 A or 15 V @ 2 A	Agilent / HP	E3610A	None	CNR	None
Antenna, Tuned Dipole 400~1000 MHz	ETS	3121C DB4	T273	6/08/17	6/08/18
Directional Coupler	Mini-Circuits	ZUDC10-183+	T1136	6/18/17	6/18/18

Test Equipment List			
Description	Manufacturer	Model	T Number
Radiated Software	UL	UL EMC	Ver 9.5, June 24, 2015
Conducted Software	UL	UL EMC	Ver 9.5, May 26, 2015
CLT Software	UL	UL RF	Ver 1.0, Feb 2, 2015
Antenna Port Software	UL	UL RF	Ver 3.7, Nov 12, 2015

10. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result
2.1049	Occupied Bandwidth (99%)	N/A	Conducted	Pass
22.917(a) 24.238(a) 27.53(g) 90.691	Band Edge / Conducted Spurious Emission	-13dBm		Pass
27.53(m)		-25dBm		
2.1046	Conducted output power	N/A		Pass
27.53(m) 90.691	Emission Mask	Please refer to limit under section 14		Pass
22.355 90.213	Frequency Stability	2.5PPM		Pass
24.235 27.54		Please refer to limit under section 16		Pass
22.913(a)(2) 27.50©(10) 90.635	Effective Radiated Power	38dBm 34.77dBm 50dBm	Radiated	Pass Pass Pass
	Equivalent Isotropic Radiated Power	36.98dBm 40.6dBm		Pass Pass
24.232(c) 27.50(h)(2)		33dBm		Pass
27.50(d)(4)		30dBm		Pass
22.917(a) 24.238(a) 27.53(g) 90.691	Radiated Spurious Emission	-13dBm		Pass
27.53(m)		-25dBm		Pass

11. RF POWER OUTPUT VERIFICATION

TEST PROCEDURE

ANSI C63.26:2015/ TIA / EIA 603-D Clause 2.2.17
KDB 971168 Section 5.6

$$\text{ERP/EIRP} = \text{PMeas} + \text{GT} - \text{LC}$$

where: ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as PMeas, typically dBW or dBm);

PMeas = measured transmitter output power or PSD, in dBm or dBW;

GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

For devices utilizing multiple antennas, KDB 662911 provides guidance for determining the effective array transmit antenna gain term to be used in the above equation.

MODES TESTED

- GSM 850
- GSM 1900
- WCDMA Band 2
- WCDMA Band 4
- WCDMA Band 5
- LTE Band 7
- LTE Band 12
- LTE Band 13
- LTE Band 17
- LTE Band 25
- LTE Band 26
- LTE Band 41
- LTE Band 66

11.1. GSM/GPRS/EDGE

Using CMW500 Communication Test Set

Function: Menu select > GSM Mobile Station > GSM 850/900/1800/1900

Press Connection control to choose the different menus

Press RESET > choose all to reset all settings

Connection	Press Signal Off to turn off the signal and change settings Network Support > GSM+GPRS or GSM+EGPRS Main Service > Packet Data Service selection > Test Mode A – Auto Slot Config. off
MS Signal	Press Slot Config bottom on the right twice to select and change the number of time slots and power setting > Slot configuration > Uplink/Gamma > 33 dBm for GPRS 850/900 > 27 dBm for EGPRS 850/900 > 30 dBm for GPRS1800/1900 > 26 dBm for EGPRS1800/1900
BS Signal	Enter the same channel number for TCH channel (test channel) and BCCH channel Frequency Offset > + 0 Hz Mode > BCCH and TCH BCCH Level > -85 dBm (May need to adjust if link is not stable) BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel] Channel Type > Off P0> 4 dB Slot Config > Unchanged (if already set under MS Signal) TCH > choose desired test channel Hopping > Off Main Timeslot > 3 (Default)
Network	Coding Scheme > CS 4 (GPRS) and MCS5-9 (EGPRS) Bit Stream > 2E9-1PSR Bit Pattern
AF/RF	Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input
Connection	Press Signal On to turn on the signal and change settings

11.2. GSM OUTPUT POWER RESULT

Tested By	Tony Soares / AJ Newcomer
Date	6/5/2017

GSM 850

Antenna gain (dBi)		-5.90					
Mode	Ch.	f (MHz)	Modulation	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
GPRS	128	824.2	1 Time slot	33.3	27.4	38.5	-11.1
	190	836.6		33.5	27.6	38.5	-10.9
	251	848.8		33.5	27.6	38.5	-10.9
	128	824.2	2 Time slot	31.6	25.7	38.5	-12.8
	190	836.6		31.7	25.8	38.5	-12.7
	251	848.8		31.8	25.9	38.5	-12.6
	128	824.2	3 Time slot	29.7	23.8	38.5	-14.7
	190	836.6		29.7	23.8	38.5	-14.7
	251	848.8		29.7	23.8	38.5	-14.7
	128	824.2	4 Time slot	28.6	22.7	38.5	-15.8
	190	836.6		28.7	22.8	38.5	-15.7
	251	848.8		28.7	22.8	38.5	-15.7
EGPRS	128	824.2	1 Time slot	27.1	21.2	38.5	-17.3
	190	836.6		27.1	21.2	38.5	-17.3
	251	848.8		27.1	21.2	38.5	-17.3
	128	824.2	2 Time slot	25.0	19.1	38.5	-19.4
	190	836.6		25.1	19.2	38.5	-19.3
	251	848.8		25.1	19.2	38.5	-19.3
	128	824.2	3 Time slot	23.1	17.2	38.5	-21.3
	190	836.6		23.2	17.3	38.5	-21.2
	251	848.8		23.2	17.3	38.5	-21.2
	128	824.2	4 Time slot	22.3	16.4	38.5	-22.1
	190	836.6		22.4	16.5	38.5	-22
	251	848.8		22.3	16.4	38.5	-22.1

GSM 1900

Antenna gain (dBi)		-1.50					
Mode	Ch.	f (MHz)	Modulation	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
GPRS	512	1850.2	1 Time slot	26.9	25.4	33.0	-7.6
	661	1880		26.8	25.3	33.0	-7.7
	810	1909.8		26.9	25.4	33.0	-7.6
	512	1850.2	2 Time slot	25.7	24.2	33.0	-8.8
	661	1880		25.6	24.1	33.0	-8.9
	810	1909.8		25.7	24.2	33.0	-8.8
	512	1850.2	3 Time slot	24.5	23	33.0	-10.0
	661	1880		24.4	22.9	33.0	-10.1
	810	1909.8		24.5	23.0	33.0	-10.0
	512	1850.2	4 Time slot	22.7	21.2	33.0	-11.8
	661	1880		22.6	21.1	33.0	-11.9
	810	1909.8		22.7	21.2	33.0	-11.8
EGPRS	512	1850.2	1 Time slot	25.9	24.4	33.0	-8.6
	661	1880		25.8	24.3	33.0	-8.7
	810	1909.8		25.9	24.4	33.0	-8.6
	512	1850.2	2 Time slot	24.1	22.6	33.0	-10.4
	661	1880		24.0	22.5	33.0	-10.5
	810	1909.8		24.1	22.6	33.0	-10.4
	512	1850.2	3 Time slot	21.8	20.3	33.0	-12.7
	661	1880		21.6	20.1	33.0	-12.9
	810	1909.8		21.8	20.3	33.0	-12.7
	512	1850.2	4 Time slot	20.5	19	33.0	-14.0
	661	1880		20.5	19	33.0	-14.0
	810	1909.8		20.5	19.0	33.0	-14.0

11.3. UMTS REL 99

TEST PROCEDURE

Release 99 Setup Procedures used to establish the test signals

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 specification. The DUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7).

The following summary of these settings are illustrated below:

Mode	Subtest	Rel99
WCDMA General Settings	Loopback Mode	Test Mode 2
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c/β_d	8/15

RESULTS

Tested By	Tony Soares / AJ Newcomer
Date	6/5/2017

11.4. UMTS REL 99 OUTPUT POWER RESULT

Antenna gain Band 5 (dBi)	-5.90
Antenna gain Band 2 (dBi)	-1.50
Antenna gain Band 4 (dBi)	-3.20

Part 22 / RSS 132 850MHz Band (5)

Band	UL Channel	DL Channel	Frequency (MHz)	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
UMTS Rel. 99 850MHz	4132	4357	826.4	24.3	18.4	38.5	-20.1
	4183	4408	836.6	24.5	18.6	38.5	-19.9
	4233	4458	846.6	24.7	18.8	38.5	-19.7

Part 24 / RSS 133 1900MHz Band (2)

Band	UL Channel	DL Channel	Frequency (MHz)	Peak Power (dBm)	ERIP Average (dBm)	ERIP Limit (dBm)	Margin (dB)
UMTS Rel. 99 1900MHz	9262	9662	1852.4	18.7	17.2	33.0	-15.8
	9400	9800	1880.0	18.9	17.4	33.0	-15.6
	9538	9938	1907.6	18.8	17.3	33.0	-15.7

Part 27 / RSS 139 1700MHz Band (4)

Band	UL Channel	DL Channel	Frequency (MHz)	Peak Power (dBm)	ERIP Average (dBm)	ERIP Limit (dBm)	Margin (dB)
UMTS Rel. 99 1700MHz	1312	1537	1712.4	20.2	17.0	30.0	-13.0
	1413	1638	1732.6	20.4	17.2	30.0	-12.8
	1513	1738	1752.6	20.4	17.2	30.0	-12.8

11.5. UMTS HSDPA

HSDPA Setup Procedures used to establish the test signals

The following 4 Sub-tests were completed according to Release 5 procedures in section 5.2 of 3GPP TS34.121.

Summary of settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
W-CDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set 1			
	Power Control Algorithm	Algorithm 2			
	β_c	2/15	11/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	Bd (SF)	64			
	β_c/β_d	2/15	11/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
HSDPA Specific Settings	MPR (dB)	0	0	0.5	0.5
	D_{ACK}	8			
	D_{NAK}	8			
	DCQI	8			
	Ack-Nack repetition factor	3			
	CQI Feedback (Table 5.2B.4)	4ms			
	CQI Repetition Factor (Table 5.2B.4)	2			
	$A_{hs}=\beta_{hs}/\beta_c$	30/15			

RESULTS

Tested By	Tony Soares / AJ Newcomer
Date	6/5/2017

11.6. UMTS HSDPA OUTPUT POWER RESULT

Antenna gain Band 5 (dBi)	-5.90
Antenna gain Band 2 (dBi)	-1.50
Antenna gain Band 4 (dBi)	-3.20

Part 22 / RSS 132 850MHz Band (5)

Band	Subtest	UL Channel	DL Channel	Frequency (MHz)	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
UMTS HSDPA 850MHz	1	4132	4357	826.4	23.4	17.5	38.5	-15.1
		4183	4408	836.6	23.5	17.6	38.5	-15.0
		4233	4458	846.6	23.8	17.9	38.5	-14.7
	2	4132	4357	826.4	23.4	17.5	38.5	-15.1
		4183	4408	836.6	23.5	17.6	38.5	-15.0
		4233	4458	846.6	23.8	17.9	38.5	-14.7
	3	4132	4357	826.4	23.0	17.1	38.5	-15.5
		4183	4408	836.6	23.2	17.3	38.5	-15.3
		4233	4458	846.6	23.2	17.3	38.5	-15.3
	4	4132	4357	826.4	23.0	17.1	38.5	-15.5
		4183	4408	836.6	23.2	17.3	38.5	-15.3
		4233	4458	846.6	23.2	17.3	38.5	-15.3

Part 24 / RSS 133 1900MHz Band (2)

Band	Subtest	UL Channel	DL Channel	Frequency (MHz)	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
UMTS HSDPA 1900MHz	1	9262	9662	1852.4	18.5	17.0	33.0	-14.5
		9400	9800	1880.0	18.4	16.9	33.0	-14.6
		9538	9938	1907.6	18.4	16.9	33.0	-14.6
	2	9262	9662	1852.4	18.5	17.0	33.0	-14.5
		9400	9800	1880.0	18.4	16.9	33.0	-14.6
		9538	9938	1907.6	18.4	16.9	33.0	-14.6
	3	9262	9662	1852.4	18.0	16.5	33.0	-15.0
		9400	9800	1880.0	18.0	16.5	33.0	-15.0
		9538	9938	1907.6	17.8	16.3	33.0	-15.2
	4	9262	9662	1852.4	18.0	16.5	33.0	-15.0
		9400	9800	1880.0	18.0	16.5	33.0	-15.0
		9538	9938	1907.6	17.8	16.3	33.0	-15.2

Part 27 / RSS 139 1700MHz Band (4)

Band	Subtest	UL Channel	DL Channel	Frequency (MHz)	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
UMTS HSDPA 1700MHz	1	1312	1537	1712.4	19.8	16.6	30.0	-10.2
		1413	1638	1732.6	19.6	16.4	30.0	-10.4
		1513	1738	1752.6	19.6	16.4	30.0	-10.4
	2	1312	1537	1712.4	19.8	16.6	30.0	-10.2
		1413	1638	1732.6	19.6	16.4	30.0	-10.4
		1513	1738	1752.6	19.6	16.4	30.0	-10.4
	3	1312	1537	1712.4	19.2	16.0	30.0	-10.8
		1413	1638	1732.6	19.3	16.1	30.0	-10.7
		1513	1738	1752.6	18.8	15.6	30.0	-11.2
	4	1312	1537	1712.4	19.2	16.0	30.0	-10.8
		1413	1638	1732.6	19.3	16.1	30.0	-10.7
		1513	1738	1752.6	18.8	15.6	30.0	-11.2

11.7. UMTS HSUPA

The following 5 Sub-tests were completed according to Release 6 procedures in Table C.11.1.3 of 3GPP TS 34.121-1 v13

Summary of settings are illustrated below:

	Mode	HSPA				
	Subtest	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2 kbps RMC				
	HSDPA FRC	H-Set 1				
	HSUPA Test	HSPA				
	Power Control Algorithm	Algorithm 2				Algorithm 1
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c/β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	β_{ed}	1309/225	94/75	47/15	56/75	47/15
HSDPA Specific Settings	CM (dB)	1	3	2	3	1
	MPR (dB)	0	2	1	2	0
	DACK	8				0
	DNAK	8				0
	DCQI	8				0
	Ack-Nack repetition factor	3				
	CQI Feedback (Table 5.2B.4)	4ms				
	CQI Repetition Factor (Table 5.2B.4)	2				
HSUPA Specific Settings	A _{hs} = β_{hs}/β_c	30/15				
	E-DPDCCH	6	8	8	5	0
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	12
	ETFCI (from 34.121 Table C.11.1.3)	75	67	92	71	67
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E-TFCIs	5	5	2	5	1
	Reference E-TFCI	11	11	11	11	67
	Reference E-TFCI PO	4	4	4	4	18
	Reference E-TFCI	67	67	92	67	67
	Reference E-TFCI PO	18	18	18	18	18
	Reference E-TFCI	71	71	71	71	71
	Reference E-TFCI PO	23	23	23	23	23
	Reference E-TFCI	75	75	75	75	75
	Reference E-TFCI PO	26	26	26	26	26
	Reference E-TFCI	81	81	81	81	81
	Reference E-TFCI PO	27	27	27	27	27
	Maximum Channelization Codes	2xSF2				SF4

RESULT

Tested By	Tony Soares / AJ Newcomer
Date	6/5/2017

11.8. UMTS HSUPA OUTPUT POWER RESULT

Antenna gain Band 5 (dBi)	-5.90
Antenna gain Bnad 2 (dBi)	-1.50

Part 22 / RSS 132 850MHz Band (5)

Band	Subtest	UL Channel	DL Channel	Frequency (MHz)	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
UMTS HSUPA 850MHz	1	4132	4357	826.4	23.2	17.3	38.5	-15.3
		4183	4408	836.6	23.5	17.6	38.5	-15.0
		4233	4458	846.6	23.7	17.8	38.5	-14.8
	2	4132	4357	826.4	21.3	15.4	38.5	-17.2
		4183	4408	836.6	21.4	15.5	38.5	-17.1
		4233	4458	846.6	21.8	15.9	38.5	-16.7
	3	4132	4357	826.4	22.5	16.6	38.5	-16.0
		4183	4408	836.6	22.5	16.6	38.5	-16.0
		4233	4458	846.6	22.6	16.7	38.5	-15.9
	4	4132	4357	826.4	21.3	15.4	38.5	-17.2
		4183	4408	836.6	21.4	15.5	38.5	-17.1
		4233	4458	846.6	21.8	15.9	38.5	-16.7
	5	4132	4357	826.4	23.2	17.3	38.5	-15.3
		4183	4408	836.6	23.5	17.6	38.5	-15.0
		4233	4458	846.6	23.7	17.8	38.5	-14.8

Part 24 / RSS 133 1900MHz Band (2)

Band	Subtest	UL Channel	DL Channel	Frequency (MHz)	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
UMTS HSUPA 1900MHz	1	9262	9662	1852.4	18.2	16.7	33.0	-14.8
		9400	9800	1880.0	18.2	16.7	33.0	-14.8
		9538	9938	1907.6	18.2	16.7	33.0	-14.8
	2	9262	9662	1852.4	16.4	14.9	33.0	-16.6
		9400	9800	1880.0	16.3	14.8	33.0	-16.7
		9538	9938	1907.6	16.5	15.0	33.0	-16.5
	3	9262	9662	1852.4	16.8	15.3	33.0	-16.2
		9400	9800	1880.0	17.4	15.9	33.0	-15.6
		9538	9938	1907.6	17.5	16.0	33.0	-15.5
	4	9262	9662	1852.4	16.4	14.9	33.0	-16.6
		9400	9800	1880.0	16.3	14.8	33.0	-16.7
		9538	9938	1907.6	16.5	15.0	33.0	-16.5
	5	9262	9662	1852.4	18.2	16.7	33.0	-14.8
		9400	9800	1880.0	18.2	16.7	33.0	-14.8
		9538	9938	1907.6	18.2	16.7	33.0	-14.8

Antenna gain Band 4 (dBi)	-3.20
---------------------------	-------

Part 27 / RSS 139 1700MHz Band (4)

Band	Subtest	UL Channel	DL Channel	Frequency (MHz)	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
UMTS HSUPA 1700MHz	1	1312	1537	1712.4	19.4	16.2	30.0	-10.6
		1413	1638	1732.6	19.7	16.5	30.0	-10.3
		1513	1738	1752.6	19.6	16.4	30.0	-10.4
	2	1312	1537	1712.4	17.4	14.2	30.0	-12.6
		1413	1638	1732.6	17.4	14.2	30.0	-12.6
		1513	1738	1752.6	17.3	14.1	30.0	-12.7
	3	1312	1537	1712.4	18.5	15.3	30.0	-11.5
		1413	1638	1732.6	18.5	15.3	30.0	-11.5
		1513	1738	1752.6	18.3	15.1	30.0	-11.7
	4	1312	1537	1712.4	17.4	14.2	30.0	-12.6
		1413	1638	1732.6	17.4	14.2	30.0	-12.6
		1513	1738	1752.6	17.3	14.1	30.0	-12.7
	5	1312	1537	1712.4	19.4	16.2	30.0	-10.6
		1413	1638	1732.6	19.7	16.5	30.0	-10.3
		1513	1738	1752.6	19.6	16.4	30.0	-10.4

11.9. UMTS DC-HSDPA

The following tests were completed according to procedures in section 7.3.13 of 3GPP TS34.108 v9.5.0. A summary of these settings are illustrated below:

Downlink Physical Channels are set as per 3GPP TS34.121-1 v9.0.0 E.5.0

Table E.5.0: Levels for HSDPA connection setup

Parameter During Connection setup	Unit	Value
P-CPICH_Ec/Ior	dB	-10
P-CCPCH and SCH_Ec/Ior	dB	-12
PICH_Ec/Ior	dB	-15
HS-PDSCH	dB	off
HS-SCCH_1	dB	off
DPCH_Ec/Ior	dB	-5
OCNS_Ec/Ior	dB	-3.1

Call is set up as per 3GPP TS34.108 v9.5.0 sub clause 7.3.13

The configurations of the fixed reference channels for HSDPA RF tests are described in 3GPP TS 34.121, annex C for FDD and 3GPP TS 34.122.

Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{inf})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		




Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)

The following 4 Sub-tests for HSDPA were completed according to Release 8 procedures in section 5.2 of 3GPP TS34.121. A summary of subtest settings are illustrated below:

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subtest	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set 1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	11/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_d (SF)	64			
	β_c/β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
HSDPA Specific	MPR (dB)	0	0	0.5	0.5
	DACK	8			
	DNAK	8			

Settings	DCQI	8
	Ack-Nack Repetition factor	3
	CQI Feedback	4ms
	CQI Repetition Factor	2
	Ahs = β_{hs} / β_c	30/15

HSPA+

Since 16QAM is not used for uplink, the uplink Category and release is same as HSUPA, i.e., Rel. 7 Therefore, the RF conducted power is not measured.

11.10. UMTS DC-HSDPA OUTPUT POWER RESULT

Antenna gain Band 5 (dBi)	-5.90
Antenna gain Band 2 (dBi)	-1.50
Antenna gain Band 4 (dBi)	-3.20

Part 22 / RSS 132 850MHz Band (5)

Band	Subtest	UL Channel	DL Channel	Frequency (MHz)	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
UMTS DC-HSDPA 850MHz	1	4132	4357	826.4	23.2	17.3	38.5	-15.3
		4183	4408	836.6	23.4	17.5	38.5	-15.1
		4233	4458	846.6	23.6	17.7	38.5	-14.9
	2	4132	4357	826.4	23.1	17.2	38.5	-15.4
		4183	4408	836.6	23.3	17.4	38.5	-15.2
		4233	4458	846.6	23.5	17.6	38.5	-15.0
	3	4132	4357	826.4	23.3	17.4	38.5	-15.2
		4183	4408	836.6	23.5	17.6	38.5	-15.0
		4233	4458	846.6	23.4	17.5	38.5	-15.1
	4	4132	4357	826.4	23.2	17.3	38.5	-15.3
		4183	4408	836.6	23.7	17.8	38.5	-14.8
		4233	4458	846.6	23.5	17.6	38.5	-15.0

Part 24 / RSS 133 1900MHz Band (2)

Band	Subtest	UL Channel	DL Channel	Frequency (MHz)	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
UMTS DC-HSDPA 1900MHz	1	9262	9662	1852.4	17.7	16.2	33.0	-15.3
		9400	9800	1880.0	17.8	16.3	33.0	-15.2
		9538	9938	1907.6	17.7	16.2	33.0	-15.3
	2	9262	9662	1852.4	18.3	16.8	33.0	-14.7
		9400	9800	1880.0	17.8	16.3	33.0	-15.2
		9538	9938	1907.6	17.8	16.3	33.0	-15.2
	3	9262	9662	1852.4	18.0	16.5	33.0	-15.0
		9400	9800	1880.0	17.8	16.3	33.0	-15.2
		9538	9938	1907.6	18.0	16.5	33.0	-15.0
	4	9262	9662	1852.4	17.5	16.0	33.0	-15.5
		9400	9800	1880.0	18.0	16.5	33.0	-15.0
		9538	9938	1907.6	18.0	16.5	33.0	-15.0

Part 27 / RSS 139 1700MHz Band (4)

Band	Subtest	UL Channel	DL Channel	Frequency (MHz)	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
UMTS DC-HSDPA 1700MHz	1	1312	1537	1712.4	19.3	16.1	30.0	-10.7
		1413	1638	1732.6	19.3	16.1	30.0	-10.7
		1513	1738	1752.6	19.4	16.2	30.0	-10.6
	2	1312	1537	1712.4	19.1	15.9	30.0	-10.9
		1413	1638	1732.6	19.1	15.9	30.0	-10.9
		1513	1738	1752.6	19.4	16.2	30.0	-10.6
	3	1312	1537	1712.4	18.8	15.6	30.0	-11.2
		1413	1638	1732.6	19.5	16.3	30.0	-10.5
		1513	1738	1752.6	19.2	16.0	30.0	-10.8
	4	1312	1537	1712.4	19.0	15.8	30.0	-11.0
		1413	1638	1732.6	19.5	16.3	30.0	-10.5
		1513	1738	1752.6	19.2	16.0	30.0	-10.8

11.11. LTE OUTPUT POWER RESULT

Note(s):

LTE Band 2 Measured Results

LTE Band 2 (Frequency range: 1850-1910MHz) is covered by LTE Band 25 (Frequency range:1850-1915 MHz) no testing is necessary due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth and same modulations.

LTE Band 4 Measured Results

LTE Band 4 (Frequency range: 1710-1755MHz) is covered by LTE Band 66 (Frequency range: 1710-1780 MHz) and no testing is necessary due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth and same modulations.

LTE Band 5 Measured Results

LTE Band 5 (Frequency range: 824-849 MHz) is covered by LTE Band 26 (Frequency range: 814-849 MHz) due to similar frequency range, same maximum tune-up limit and same channel bandwidth.

LTE Band 17 Measured Results

LTE Band 17 (Frequency range: 704-716) is covered by LTE Band 12 (Frequency range: 699-716MHz) no testing is necessary due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth and same modulations.

LTE Band 38 Measured Results

LTE Band 38 (Frequency range: 2570-2620 MHz) is covered by LTE Band 41 (Frequency range: 2496-2690 MHz) and no testing is necessary due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth and same modulations.

64QAM Measured Results

Measured QPSK,16QAM & 64QAM Mode Output power and found that QPSK and 16QAM results was the worst case. All testing were performed using QPSK and 16QAM mode to represent the worst case mode.

Tested By	AJ Newcomer/ Vanessa Moestopo
Date	6/5-12/2017

LTE Band 7

Antenna gain (dBi)		-3.10							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
5.0	20775	2052.5	QPSK	1	0	21.9	18.8	33.0	-14.3
				1	12	21.7	18.6	33.0	-14.4
				1	24	21.7	18.6	33.0	-14.4
				12	0	22.0	18.9	33.0	-14.2
				12	7	21.8	18.7	33.0	-14.3
				12	13	21.8	18.7	33.0	-14.3
			16QAM	25	0	21.8	18.7	33.0	-14.3
				1	0	21.6	18.5	33.0	-14.5
				1	12	21.5	18.4	33.0	-14.6
				1	24	21.5	18.4	33.0	-14.6
				12	0	21.5	18.4	33.0	-14.6
				12	7	21.4	18.3	33.0	-14.7
				12	13	21.4	18.3	33.0	-14.7
				25	0	21.4	18.3	33.0	-14.7
			64QAM	1	0	21.3	18.2	33.0	-14.8
				1	12	21.3	18.2	33.0	-14.8
				1	24	21.3	18.2	33.0	-14.8
				12	0	20.6	17.5	33.0	-15.5
				12	7	20.6	17.5	33.0	-15.5
				12	13	20.5	17.4	33.0	-15.6
5.0	21100	2535.0	QPSK	25	0	20.5	17.4	33.0	-15.6
				1	0	22.0	18.9	33.0	-14.2
				1	12	22.0	18.9	33.0	-14.1
				1	24	21.9	18.8	33.0	-14.2
				12	0	22.0	18.9	33.0	-14.1
				12	7	22.0	18.9	33.0	-14.1
			16QAM	12	13	22.0	18.9	33.0	-14.2
				25	0	21.9	18.8	33.0	-14.2
				1	0	21.9	18.8	33.0	-14.2
				1	2	22.0	18.9	33.0	-14.1
				1	5	21.9	18.8	33.0	-14.2
				3	0	21.7	18.6	33.0	-14.5
			64QAM	3	1	21.7	18.6	33.0	-14.4
				3	2	21.6	18.5	33.0	-14.5
				6	0	21.5	18.4	33.0	-14.6
				1	0	21.2	18.1	33.0	-14.9
				1	12	21.2	18.1	33.0	-14.9
				1	24	21.2	18.1	33.0	-14.9
			64QAM	12	0	20.6	17.5	33.0	-15.5
				12	7	20.6	17.5	33.0	-15.5
				12	13	20.5	17.4	33.0	-15.6
				25	0	20.5	17.4	33.0	-15.6

Antenna gain (dBi)		-3.10							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
5.0	21425	2567.5	QPSK	1	0	22.0	18.9	33.0	-14.1
				1	12	22.0	18.9	33.0	-14.1
				1	24	22.0	18.9	33.0	-14.1
				12	0	22.0	18.9	33.0	-14.1
				12	7	22.1	19.0	33.0	-14.0
				12	13	22.1	19.0	33.0	-14.0
				25	0	22.0	18.9	33.0	-14.1
			16QAM	1	0	21.6	18.5	33.0	-14.5
				1	12	21.6	18.5	33.0	-14.5
				1	24	21.7	18.6	33.0	-14.4
				12	0	21.6	18.5	33.0	-14.5
				12	7	21.7	18.6	33.0	-14.5
				12	13	21.6	18.5	33.0	-14.5
				25	0	21.5	18.4	33.0	-14.6
			64QAM	1	0	21.4	18.3	33.0	-14.7
				1	12	21.2	18.1	33.0	-14.9
				1	24	21.1	18.0	33.0	-15.0
				12	0	20.9	17.8	33.0	-15.2
				12	7	20.6	17.5	33.0	-15.5
				12	13	20.5	17.4	33.0	-15.6
				25	0	20.5	17.4	33.0	-15.6

Antenna gain (dBi)		-3.10							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
10.0	20880	2505.0	QPSK	1	0	21.9	18.8	33.0	-14.2
				1	25	21.9	18.8	33.0	-14.2
				1	49	21.8	18.7	33.0	-14.3
				25	0	22.0	18.9	33.0	-14.2
				25	12	22.0	18.9	33.0	-14.1
				25	25	21.9	18.8	33.0	-14.2
				50	0	22.0	18.9	33.0	-14.1
			16QAM	1	0	21.4	18.3	33.0	-14.7
				1	25	21.4	18.3	33.0	-14.7
				1	49	21.2	18.1	33.0	-14.9
				25	0	21.5	18.4	33.0	-14.6
				25	12	21.5	18.4	33.0	-14.6
				25	25	21.5	18.4	33.0	-14.7
				50	0	21.5	18.4	33.0	-14.6
			64QAM	1	0	21.2	18.1	33.0	-14.9
				1	25	21.2	18.1	33.0	-14.9
				1	49	21.0	17.9	33.0	-15.1
				25	0	20.7	17.6	33.0	-15.4
				25	12	20.7	17.6	33.0	-15.4
				25	25	20.6	17.5	33.0	-15.5
				50	0	20.6	17.5	33.0	-15.5
10.0	21100	2535.0	QPSK	1	0	22.0	18.9	33.0	-14.1
				1	25	21.9	18.8	33.0	-14.2
				1	49	21.8	18.7	33.0	-14.4
				25	0	21.9	18.8	33.0	-14.2
				25	12	22.0	18.9	33.0	-14.1
				25	25	21.9	18.8	33.0	-14.2
				50	0	22.0	18.9	33.0	-14.1
			16QAM	1	0	21.4	18.3	33.0	-14.7
				1	25	21.4	18.3	33.0	-14.7
				1	49	21.2	18.1	33.0	-14.9
				25	0	21.5	18.4	33.0	-14.6
				25	12	21.5	18.4	33.0	-14.6
				25	25	21.5	18.4	33.0	-14.6
				50	0	21.5	18.4	33.0	-14.6
			64QAM	1	0	21.2	18.1	33.0	-14.9
				1	25	21.2	18.1	33.0	-14.9
				1	49	21.2	18.1	33.0	-14.9
				25	0	20.5	17.4	33.0	-15.6
				25	12	20.6	17.5	33.0	-15.5
				25	25	20.5	17.4	33.0	-15.6
				50	0	20.6	17.5	33.0	-15.5

Antenna gain (dBi)		-3.10							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
10.0	21400	2565.0	QPSK	1	0	22.0	18.9	33.0	-14.1
				1	25	21.9	18.8	33.0	-14.2
				1	49	22.0	18.9	33.0	-14.1
				25	0	22.1	19.0	33.0	-14.0
				25	12	22.0	18.9	33.0	-14.1
				25	25	22.0	18.9	33.0	-14.1
				50	0	22.0	18.9	33.0	-14.1
			16QAM	1	0	21.8	18.7	33.0	-14.3
				1	25	21.7	18.6	33.0	-14.4
				1	49	21.8	18.7	33.0	-14.3
				25	0	21.6	18.5	33.0	-14.5
				25	12	21.6	18.5	33.0	-14.6
				25	25	21.6	18.5	33.0	-14.5
				50	0	21.5	18.4	33.0	-14.6
			64QAM	1	0	21.4	18.3	33.0	-14.7
				1	25	21.2	18.1	33.0	-14.9
				1	49	21.2	18.1	33.0	-14.9
				25	0	20.5	17.4	33.0	-15.6
				25	12	20.5	17.4	33.0	-15.6
				25	25	20.5	17.4	33.0	-15.6
				50	0	20.4	17.3	33.0	-15.7

Antenna gain (dBi)		-3.10							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
15.0	20825	2507.5	QPSK	1	0	21.9	18.8	33.0	-14.2
				1	37	21.8	18.7	33.0	-14.3
				1	74	21.7	18.6	33.0	-14.4
				36	0	22.0	18.9	33.0	-14.1
				36	20	22.0	18.9	33.0	-14.2
				36	39	21.8	18.7	33.0	-14.3
			16QAM	75	0	21.9	18.8	33.0	-14.2
				1	0	21.4	18.3	33.0	-14.8
				1	37	21.3	18.2	33.0	-14.8
				1	74	21.1	18.0	33.0	-15.0
				36	0	21.5	18.4	33.0	-14.6
				36	20	21.5	18.4	33.0	-14.6
				36	39	21.4	18.3	33.0	-14.7
				75	0	21.5	18.4	33.0	-14.6
			64QAM	1	0	21.6	18.5	33.0	-14.5
				1	37	21.4	18.3	33.0	-14.7
				1	74	21.3	18.2	33.0	-14.8
				36	0	20.6	17.5	33.0	-15.5
				36	20	20.6	17.5	33.0	-15.5
				36	39	20.5	17.4	33.0	-15.6
15.0	21100	2535.0	QPSK	75	0	20.5	17.4	33.0	-15.6
				1	0	21.9	18.8	33.0	-14.2
				1	37	21.8	18.7	33.0	-14.3
				1	74	21.7	18.6	33.0	-14.4
				36	0	22.0	18.9	33.0	-14.1
				36	20	22.0	18.9	33.0	-14.1
			16QAM	36	39	21.9	18.8	33.0	-14.2
				75	0	21.9	18.8	33.0	-14.2
				1	0	21.3	18.2	33.0	-14.8
				1	37	21.3	18.2	33.0	-14.8
				1	74	21.1	18.0	33.0	-15.0
				36	0	21.5	18.4	33.0	-14.6
				36	20	21.5	18.4	33.0	-14.6
				36	39	21.4	18.3	33.0	-14.7
				75	0	21.5	18.4	33.0	-14.7
			64QAM	1	0	21.4	18.3	33.0	-14.7
				1	37	21.2	18.1	33.0	-14.9
				1	74	21.1	18.0	33.0	-15.0
				36	0	20.6	17.5	33.0	-15.5
				36	20	20.6	17.5	33.0	-15.5
				36	39	20.5	17.4	33.0	-15.6
				75	0	20.5	17.4	33.0	-15.6

Antenna gain (dBi)		-3.10							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
15.0	21375	2562.5	QPSK	1	0	22.0	18.9	33.0	-14.1
				1	37	21.9	18.8	33.0	-14.2
				1	74	21.9	18.8	33.0	-14.2
				36	0	22.1	19.0	33.0	-14.0
				36	20	22.0	18.9	33.0	-14.1
				36	39	21.9	18.8	33.0	-14.2
				75	0	22.0	18.9	33.0	-14.1
			16QAM	1	0	21.9	18.8	33.0	-14.2
				1	37	21.8	18.7	33.0	-14.4
				1	74	21.7	18.6	33.0	-14.4
				36	0	21.6	18.5	33.0	-14.5
				36	20	21.6	18.5	33.0	-14.5
				36	39	21.5	18.4	33.0	-14.6
				75	0	21.5	18.4	33.0	-14.6
			64QAM	1	0	21.2	18.1	33.0	-14.9
				1	37	21.2	18.1	33.0	-14.9
				1	74	21.1	18.0	33.0	-15.0
				36	0	20.9	17.8	33.0	-15.2
				36	20	20.6	17.5	33.0	-15.5
				36	39	20.5	17.4	33.0	-15.6
				75	0	20.5	17.4	33.0	-15.6

Antenna gain (dBi)		-3.10							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
20.0	20850	2510.0	QPSK	1	0	22.0	18.9	33.0	-14.1
				1	49	21.9	18.8	33.0	-14.2
				1	99	21.8	18.7	33.0	-14.3
				50	0	22.0	18.9	33.0	-14.1
				50	24	22.0	18.9	33.0	-14.1
				50	50	21.9	18.8	33.0	-14.3
			16QAM	100	0	21.9	18.8	33.0	-14.2
				1	0	22.0	18.9	33.0	-14.1
				1	49	21.9	18.8	33.0	-14.2
				1	99	21.8	18.7	33.0	-14.3
				50	0	21.5	18.4	33.0	-14.6
				50	24	21.5	18.4	33.0	-14.6
				50	50	21.4	18.3	33.0	-14.7
				100	0	21.4	18.3	33.0	-14.7
			64QAM	1	0	21.4	18.3	33.0	-14.7
				1	49	21.1	18.0	33.0	-15.0
				1	99	21.1	18.0	33.0	-15.0
				50	0	20.6	17.5	33.0	-15.5
				50	24	20.5	17.4	33.0	-15.6
				50	50	20.5	17.4	33.0	-15.6
20.0	21100	2535.0	QPSK	100	0	20.6	17.5	33.0	-15.5
				1	0	22.0	18.9	33.0	-14.1
				1	49	21.9	18.8	33.0	-14.2
				1	99	21.8	18.7	33.0	-14.3
				50	0	22.0	18.9	33.0	-14.1
				50	24	21.9	18.8	33.0	-14.2
			16QAM	50	50	21.8	18.7	33.0	-14.3
				100	0	21.9	18.8	33.0	-14.2
				1	0	22.0	18.9	33.0	-14.1
				1	49	21.9	18.8	33.0	-14.2
				1	99	21.8	18.7	33.0	-14.3
				50	0	21.6	18.5	33.0	-14.6
				50	24	21.5	18.4	33.0	-14.6
				50	50	21.4	18.3	33.0	-14.7
			64QAM	100	0	21.4	18.3	33.0	-14.7
				1	0	21.4	18.3	33.0	-14.7
				1	49	21.2	18.1	33.0	-14.9
				1	99	21.2	18.1	33.0	-14.9
				50	0	20.6	17.5	33.0	-15.5
				50	24	20.6	17.5	33.0	-15.5
				50	50	20.5	17.4	33.0	-15.6
				100	0	20.6	17.5	33.0	-15.5

Antenna gain (dBi)		-3.10							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
20.0	21350	2560.0	QPSK	1	0	22.1	19.0	33.0	-14.0
				1	49	21.9	18.8	33.0	-14.2
				1	99	22.0	18.9	33.0	-14.1
				50	0	22.0	18.9	33.0	-14.1
				50	24	22.0	18.9	33.0	-14.1
				50	50	21.9	18.8	33.0	-14.2
				100	0	22.0	18.9	33.0	-14.1
			16QAM	1	0	22.0	18.9	33.0	-14.1
				1	49	21.8	18.7	33.0	-14.3
				1	99	21.8	18.7	33.0	-14.3
				50	0	21.5	18.4	33.0	-14.6
				50	24	21.5	18.4	33.0	-14.6
				50	50	21.4	18.3	33.0	-14.7
				100	0	21.5	18.4	33.0	-14.6
			64QAM	1	0	21.3	18.2	33.0	-14.8
				1	49	21.1	18.0	33.0	-15.0
				1	99	21.0	17.9	33.0	-15.1
				50	0	20.5	17.4	33.0	-15.6
				50	24	20.5	17.4	33.0	-15.6
				50	50	20.4	17.3	33.0	-15.7
				100	0	20.5	17.4	33.0	-15.6

LTE Band 12

Antenna gain (dBi)		-9.00							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
1.4	23017	699.7	QPSK	1	0	23.8	14.8	34.7	-19.9
				1	3	23.9	14.9	34.7	-19.8
				1	5	23.8	14.8	34.7	-19.9
				3	0	23.9	14.9	34.7	-19.8
				3	1	23.9	14.9	34.7	-19.8
				3	3	23.9	14.9	34.7	-19.8
			16QAM	6	0	23.6	14.6	34.7	-20.1
				1	0	23.7	14.7	34.7	-20.0
				1	3	23.7	14.7	34.7	-20.0
				1	5	23.7	14.7	34.7	-20.0
				3	0	23.6	14.6	34.7	-20.1
				3	1	23.7	14.7	34.7	-20.0
				3	3	23.6	14.6	34.7	-20.1
				6	0	22.7	13.7	34.7	-21.0
			64QAM	1	0	22.5	13.5	34.7	-21.2
				1	3	22.5	13.5	34.7	-21.2
				1	5	22.5	13.5	34.7	-21.2
				3	0	22.4	13.4	34.7	-21.3
				3	1	22.4	13.4	34.7	-21.3
				3	3	22.4	13.4	34.7	-21.3
1.4	23095	707.5	QPSK	6	0	21.3	12.3	34.7	-22.4
				1	0	23.9	14.9	34.7	-19.8
				1	3	24.0	15.0	34.7	-19.7
				1	5	23.9	14.9	34.7	-19.8
				3	0	24.0	15.0	34.7	-19.7
				3	1	24.0	15.0	34.7	-19.7
			16QAM	3	3	24.0	15.0	34.7	-19.7
				6	0	23.7	14.7	34.7	-20.0
				1	0	24.0	15.0	34.7	-19.7
				1	3	24.0	15.0	34.7	-19.7
				1	5	24.0	15.0	34.7	-19.7
				3	0	23.8	14.8	34.7	-19.9
			64QAM	3	1	23.9	14.9	34.7	-19.8
				3	3	23.9	14.9	34.7	-19.8
				6	0	22.6	13.6	34.7	-21.1
				1	0	22.5	13.5	34.7	-21.2
				1	3	22.5	13.5	34.7	-21.2
				1	5	22.5	13.5	34.7	-21.2
				3	0	22.4	13.4	34.7	-21.3
				3	1	22.4	13.4	34.7	-21.3
				3	3	22.4	13.4	34.7	-21.3
				6	0	21.3	12.3	34.7	-22.4

Antenna gain (dBi)		-9.00							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
1.4	23173	715.3	QPSK	1	0	23.8	14.8	34.7	-19.9
				1	3	23.9	14.9	34.7	-19.8
				1	5	23.8	14.8	34.7	-19.9
				3	0	23.9	14.9	34.7	-19.8
				3	1	23.9	14.9	34.7	-19.8
				3	3	23.9	14.9	34.7	-19.8
				6	0	23.4	14.4	34.7	-20.3
			16QAM	1	0	23.4	14.4	34.7	-20.3
				1	3	23.5	14.5	34.7	-20.2
				1	5	23.4	14.4	34.7	-20.3
				3	0	23.6	14.6	34.7	-20.1
				3	1	23.6	14.6	34.7	-20.1
				3	3	23.6	14.6	34.7	-20.1
				6	0	22.6	13.6	34.7	-21.1
			64QAM	1	0	22.1	13.1	34.7	-21.6
				1	3	22.2	13.2	34.7	-21.5
				1	5	22.2	13.2	34.7	-21.5
				3	0	22.2	13.2	34.7	-21.5
				3	1	22.2	13.2	34.7	-21.5
				3	3	22.2	13.2	34.7	-21.5
				6	0	21.1	12.1	34.7	-22.6

Antenna gain (dBi)		-9.00							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
3.0	23025	700.5	QPSK	1	0	23.9	14.9	34.7	-19.8
				1	8	24.0	15.0	34.7	-19.7
				1	14	24.0	15.0	34.7	-19.7
				8	0	23.8	14.8	34.7	-19.9
				8	4	23.8	14.8	34.7	-19.9
				8	7	23.7	14.7	34.7	-20.0
			16QAM	15	0	23.7	14.7	34.7	-20.0
				1	0	23.6	14.6	34.7	-20.1
				1	8	23.7	14.7	34.7	-20.0
				1	14	23.7	14.7	34.7	-20.0
				8	0	22.9	13.9	34.7	-20.8
				8	4	22.9	13.9	34.7	-20.8
				8	7	22.9	13.9	34.7	-20.8
			64QAM	15	0	22.8	13.8	34.7	-20.9
				1	0	22.7	13.7	34.7	-21.0
				1	8	22.6	13.6	34.7	-21.1
				1	14	22.7	13.7	34.7	-21.0
				8	0	21.5	12.5	34.7	-22.2
				8	4	21.5	12.5	34.7	-22.2
				8	7	21.5	12.5	34.7	-22.2
				15	0	21.4	12.4	34.7	-22.3
3.0	23095	707.5	QPSK	1	0	23.9	14.9	34.7	-19.8
				1	8	24.1	15.1	34.7	-19.6
				1	14	24.0	15.0	34.7	-19.7
				8	0	23.8	14.8	34.7	-19.9
				8	4	23.8	14.8	34.7	-19.9
				8	7	23.8	14.8	34.7	-19.9
			16QAM	15	0	23.7	14.7	34.7	-20.0
				1	0	24.0	15.0	34.7	-19.7
				1	8	24.0	15.0	34.7	-19.7
				1	14	24.0	15.0	34.7	-19.7
				8	0	22.7	13.7	34.7	-21.0
				8	4	22.7	13.7	34.7	-21.0
				8	7	22.7	13.7	34.7	-21.0
			64QAM	15	0	22.8	13.8	34.7	-20.9
				1	0	22.4	13.4	34.7	-21.3
				1	8	22.5	13.5	34.7	-21.2
				1	14	22.4	13.4	34.7	-21.3
				8	0	21.4	12.4	34.7	-22.3
				8	4	21.5	12.5	34.7	-22.2
				8	7	21.4	12.4	34.7	-22.3
				15	0	21.4	12.4	34.7	-22.3

Antenna gain (dBi)		-9.00							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
3.0	23165	714.5	QPSK	1	0	23.9	14.9	34.7	-19.8
				1	8	24.0	15.0	34.7	-19.7
				1	14	23.8	14.8	34.7	-19.9
				8	0	23.5	14.5	34.7	-20.2
				8	4	23.5	14.5	34.7	-20.2
				8	7	23.5	14.5	34.7	-20.2
				15	0	23.5	14.5	34.7	-20.2
			16QAM	1	0	23.6	14.6	34.7	-20.1
				1	8	23.6	14.6	34.7	-20.1
				1	14	23.5	14.5	34.7	-20.2
				8	0	22.7	13.7	34.7	-21.0
				8	4	22.7	13.7	34.7	-21.0
				8	7	22.7	13.7	34.7	-21.0
				15	0	22.5	13.5	34.7	-21.2
			64QAM	1	0	22.3	13.3	34.7	-21.4
				1	8	22.3	13.3	34.7	-21.4
				1	14	22.2	13.2	34.7	-21.5
				8	0	21.2	12.2	34.7	-22.5
				8	4	21.2	12.2	34.7	-22.5
				8	7	21.2	12.2	34.7	-22.5
				15	0	21.2	12.2	34.7	-22.5

Antenna gain (dBi)		-9.00							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
5.0	23035	701.5	QPSK	1	0	24.0	15.0	34.7	-19.7
				1	12	24.0	15.0	34.7	-19.7
				1	24	24.0	15.0	34.7	-19.7
				12	0	23.8	14.8	34.7	-19.9
				12	7	23.9	14.9	34.7	-19.8
				12	13	23.8	14.8	34.7	-19.9
			16QAM	25	0	23.8	14.8	34.7	-19.9
				1	0	24.0	15.0	34.7	-19.7
				1	12	24.0	15.0	34.7	-19.7
				1	24	24.0	15.0	34.7	-19.7
				12	0	22.8	13.8	34.7	-20.9
				12	7	22.9	13.9	34.7	-20.8
				12	13	22.9	13.9	34.7	-20.8
				25	0	22.9	13.9	34.7	-20.8
			64QAM	1	0	22.7	13.7	34.7	-21.0
				1	12	22.8	13.8	34.7	-20.9
				1	24	22.8	13.8	34.7	-20.9
				12	0	21.5	12.5	34.7	-22.2
				12	7	21.5	12.5	34.7	-22.2
				12	13	21.6	12.6	34.7	-22.1
5.0	23095	707.5	QPSK	25	0	21.5	12.5	34.7	-22.2
				1	0	24.0	15.0	34.7	-19.7
				1	12	24.0	15.0	34.7	-19.7
				1	24	24.0	15.0	34.7	-19.7
				12	0	23.8	14.8	34.7	-19.9
				12	7	23.7	14.7	34.7	-20.0
			16QAM	12	13	23.7	14.7	34.7	-20.0
				25	0	23.7	14.7	34.7	-20.0
				1	0	24.0	15.0	34.7	-19.7
				1	2	24.0	15.0	34.7	-19.7
				1	5	24.0	15.0	34.7	-19.7
				3	0	22.9	13.9	34.7	-20.8
				3	1	22.9	13.9	34.7	-20.8
				3	2	22.9	13.9	34.7	-20.8
			64QAM	6	0	22.8	13.8	34.7	-20.9
				1	0	22.5	13.5	34.7	-21.2
				1	12	22.5	13.5	34.7	-21.2
				1	24	22.6	13.6	34.7	-21.1
				12	0	21.5	12.5	34.7	-22.2
				12	7	21.4	12.4	34.7	-22.3
				12	13	21.4	12.4	34.7	-22.3
				25	0	21.4	12.4	34.7	-22.3

Antenna gain (dBi)		-9.00							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
5.0	23155	713.5	QPSK	1	0	24.0	15.0	34.7	-19.7
				1	12	23.9	14.9	34.7	-19.8
				1	24	23.9	14.9	34.7	-19.8
				12	0	23.6	14.6	34.7	-20.1
				12	7	23.6	14.6	34.7	-20.1
				12	13	23.6	14.6	34.7	-20.1
				25	0	23.5	14.5	34.7	-20.2
			16QAM	1	0	23.7	14.7	34.7	-20.0
				1	12	23.6	14.6	34.7	-20.1
				1	24	23.6	14.6	34.7	-20.1
				12	0	22.6	13.6	34.7	-21.1
				12	7	22.6	13.6	34.7	-21.1
				12	13	22.6	13.6	34.7	-21.1
				25	0	22.5	13.5	34.7	-21.2
			64QAM	1	0	22.5	13.5	34.7	-21.2
				1	12	22.5	13.5	34.7	-21.2
				1	24	22.5	13.5	34.7	-21.2
				12	0	21.3	12.3	34.7	-22.4
				12	7	21.3	12.3	34.7	-22.4
				12	13	21.3	12.3	34.7	-22.4
				25	0	21.2	12.2	34.7	-22.5

Antenna gain (dBi)		-9.00							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
10.0	23095	707.5	QPSK	1	0	24.0	15.0	34.7	-19.7
				1	25	24.0	15.0	34.7	-19.7
				1	49	23.9	14.9	34.7	-19.8
				25	0	23.7	14.7	34.7	-20.0
				25	12	23.8	14.8	34.7	-19.9
				25	25	23.7	14.7	34.7	-20.0
				50	0	23.7	14.7	34.7	-20.0
			16QAM	1	0	23.6	14.6	34.7	-20.1
				1	25	23.6	14.6	34.7	-20.1
				1	49	23.5	14.5	34.7	-20.2
				25	0	22.7	13.7	34.7	-21.0
				25	12	22.8	13.8	34.7	-20.9
				25	25	22.7	13.7	34.7	-21.0
				50	0	22.7	13.7	34.7	-21.0
			64QAM	1	0	22.5	13.5	34.7	-21.2
				1	25	22.6	13.6	34.7	-21.1
				1	49	22.5	13.5	34.7	-21.2
				25	0	21.4	12.4	34.7	-22.3
				25	12	21.4	12.4	34.7	-22.3
				25	25	21.4	12.4	34.7	-22.3
				50	0	21.4	12.4	34.7	-22.3

LTE Band 13

Antenna gain (dBi)		-5.90							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
5.0	23230	782.0	QPSK	1	0	23.6	17.7	34.7	-17.0
				1	12	23.5	17.6	34.7	-17.1
				1	24	23.6	17.7	34.7	-17.0
				12	0	22.6	16.7	34.7	-18.0
				12	7	22.6	16.7	34.7	-18.0
				12	13	22.6	16.7	34.7	-18.0
				25	0	22.5	16.6	34.7	-18.1
			16QAM	1	0	22.7	16.8	34.7	-17.9
				1	12	22.6	16.7	34.7	-18.0
				1	24	22.7	16.8	34.7	-17.9
				12	0	21.6	15.7	34.7	-19.0
				12	7	21.6	15.7	34.7	-19.0
				12	13	21.7	15.8	34.7	-18.9
				25	0	21.5	15.6	34.7	-19.1
			64QAM	1	0	21.5	15.6	34.7	-19.1
				1	12	21.4	15.5	34.7	-19.2
				1	24	21.5	15.6	34.7	-19.1
				12	0	20.2	14.3	34.7	-20.4
				12	7	20.2	14.3	34.7	-20.4
				12	13	20.2	14.3	34.7	-20.4
				25	0	20.2	14.3	34.7	-20.4

Antenna gain (dBi)		5.90							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
10.0	23230	782.0	QPSK	1	0	23.7	29.6	34.7	-5.1
				1	25	23.5	29.4	34.7	-5.3
				1	49	23.6	29.5	34.7	-5.2
				25	0	22.6	28.5	34.7	-6.2
				25	12	22.6	28.5	34.7	-6.2
				25	25	22.6	28.5	34.7	-6.2
				50	0	22.7	28.6	34.7	-6.1
			16QAM	1	0	22.7	28.6	34.7	-6.1
				1	25	22.6	28.5	34.7	-6.2
				1	49	22.7	28.6	34.7	-6.1
				25	0	21.7	27.6	34.7	-7.1
				25	12	21.7	27.6	34.7	-7.1
				25	25	21.7	27.6	34.7	-7.1
				50	0	21.7	27.6	34.7	-7.1
			64QAM	1	0	21.5	27.4	34.7	-7.3
				1	25	21.4	27.3	34.7	-7.4
				1	49	21.4	27.3	34.7	-7.4
				25	0	20.2	26.1	34.7	-8.6
				25	12	20.2	26.1	34.7	-8.6
				25	25	20.2	26.1	34.7	-8.6
				50	0	20.3	26.2	34.7	-8.5

LTE Band 25

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
1.4	26047	1850.7	QPSK	1	0	18.4	16.9	33.0	-16.1
				1	3	18.5	17.0	33.0	-16.0
				1	5	18.4	16.9	33.0	-16.1
				3	0	18.5	17.0	33.0	-16.0
				3	1	18.5	17.0	33.0	-16.0
				3	3	18.5	17.0	33.0	-16.0
				6	0	18.5	17.0	33.0	-16.1
			16QAM	1	0	18.0	16.5	33.0	-16.5
				1	3	18.1	16.6	33.0	-16.4
				1	5	18.0	16.5	33.0	-16.5
				3	0	18.0	16.5	33.0	-16.5
				3	1	18.1	16.6	33.0	-16.5
				3	3	18.1	16.6	33.0	-16.5
				6	0	18.1	16.6	33.0	-16.4
			64QAM	1	0	17.7	16.2	33.0	-16.8
				1	3	17.9	16.4	33.0	-16.6
				1	5	17.9	16.4	33.0	-16.6
				3	0	17.7	16.2	33.0	-16.8
				3	1	17.7	16.2	33.0	-16.8
				3	3	17.6	16.1	33.0	-16.9
				6	0	17.6	16.1	33.0	-16.9
1.4	26365	1882.5	QPSK	1	0	18.5	17.0	33.0	-16.0
				1	3	18.6	17.1	33.0	-15.9
				1	5	18.6	17.1	33.0	-15.9
				3	0	18.5	17.0	33.0	-16.0
				3	1	18.6	17.1	33.0	-15.9
				3	3	18.7	17.2	33.0	-15.8
				6	0	18.6	17.1	33.0	-15.9
			16QAM	1	0	18.3	16.8	33.0	-16.2
				1	3	18.4	16.9	33.0	-16.1
				1	5	18.4	16.9	33.0	-16.1
				3	0	18.2	16.7	33.0	-16.3
				3	1	18.3	16.8	33.0	-16.3
				3	3	18.3	16.8	33.0	-16.2
				6	0	18.1	16.6	33.0	-16.5
			64QAM	1	0	17.9	16.4	33.0	-16.6
				1	3	18.0	16.5	33.0	-16.5
				1	5	18.0	16.5	33.0	-16.5
				3	0	17.4	15.9	33.0	-17.1
				3	1	17.4	15.9	33.0	-17.1
				3	3	17.4	15.9	33.0	-17.1
				6	0	17.8	16.3	33.0	-16.7

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
1.4	26683	1914.3	QPSK	1	0	18.5	17.0	33.0	-16.0
				1	3	18.6	17.1	33.0	-15.9
				1	5	18.5	17.0	33.0	-16.0
				3	0	18.6	17.1	33.0	-15.9
				3	1	18.7	17.2	33.0	-15.8
				3	3	18.7	17.2	33.0	-15.8
				6	0	18.6	17.1	33.0	-15.9
			16QAM	1	0	18.1	16.6	33.0	-16.4
				1	3	18.1	16.6	33.0	-16.4
				1	5	18.1	16.6	33.0	-16.4
				3	0	18.2	16.7	33.0	-16.3
				3	1	18.3	16.8	33.0	-16.2
				3	3	18.3	16.8	33.0	-16.2
				6	0	18.3	16.8	33.0	-16.2
			64QAM	1	0	17.1	15.6	33.0	-17.4
				1	3	17.1	15.6	33.0	-17.4
				1	5	17.1	15.6	33.0	-17.4
				3	0	17.7	16.2	33.0	-16.8
				3	1	17.7	16.2	33.0	-16.8
				3	3	17.8	16.3	33.0	-16.7
				6	0	17.7	16.2	33.0	-16.8

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
3.0	20655	1851.5	QPSK	1	0	18.5	17.0	33.0	-16.0
				1	8	18.6	17.1	33.0	-15.9
				1	14	18.5	17.0	33.0	-16.0
				8	0	18.6	17.1	33.0	-16.0
				8	4	18.5	17.0	33.0	-16.0
				8	7	18.6	17.1	33.0	-15.9
			16QAM	15	0	18.5	17.0	33.0	-16.0
				1	0	17.9	16.4	33.0	-16.6
				1	8	18.0	16.5	33.0	-16.5
				1	14	17.9	16.4	33.0	-16.6
				8	0	18.2	16.7	33.0	-16.4
				8	4	18.2	16.7	33.0	-16.4
				8	7	18.1	16.6	33.0	-16.4
			64QAM	15	0	18.1	16.6	33.0	-16.4
				1	0	17.7	16.2	33.0	-16.8
				1	8	18.0	16.5	33.0	-16.5
				1	14	17.8	16.3	33.0	-16.7
				8	0	17.7	16.2	33.0	-16.8
				8	4	17.7	16.2	33.0	-16.8
				8	7	17.7	16.2	33.0	-16.8
				15	0	17.7	16.2	33.0	-16.8
3.0	26365	1882.5	QPSK	1	0	18.4	16.9	33.0	-16.1
				1	8	18.6	17.1	33.0	-15.9
				1	14	18.5	17.0	33.0	-16.0
				8	0	18.4	16.9	33.0	-16.1
				8	4	18.4	16.9	33.0	-16.1
				8	7	18.5	17.0	33.0	-16.0
			16QAM	15	0	18.5	17.0	33.0	-16.0
				1	0	18.2	16.7	33.0	-16.3
				1	8	18.4	16.9	33.0	-16.1
				1	14	18.3	16.8	33.0	-16.2
				8	0	17.8	16.3	33.0	-16.7
				8	4	17.8	16.3	33.0	-16.7
				8	7	17.9	16.4	33.0	-16.6
			64QAM	15	0	18.0	16.5	33.0	-16.5
				1	0	17.5	16.0	33.0	-17.0
				1	8	17.7	16.2	33.0	-16.8
				1	14	17.6	16.1	33.0	-16.9
				8	0	17.6	16.1	33.0	-16.9
				8	4	17.6	16.1	33.0	-16.9
				8	7	17.7	16.2	33.0	-16.8
				15	0	17.5	16.0	33.0	-17.0

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
3.0	26675	1913.5	QPSK	1	0	18.5	17.0	33.0	-16.0
				1	8	18.7	17.2	33.0	-15.8
				1	14	18.6	17.1	33.0	-15.9
				8	0	18.7	17.2	33.0	-15.8
				8	4	18.7	17.2	33.0	-15.8
				8	7	18.7	17.2	33.0	-15.8
				15	0	18.7	17.2	33.0	-15.8
			16QAM	1	0	18.1	16.6	33.0	-16.4
				1	8	18.3	16.8	33.0	-16.2
				1	14	18.2	16.7	33.0	-16.4
				8	0	18.4	16.9	33.0	-16.1
				8	4	18.4	16.9	33.0	-16.1
				8	7	18.4	16.9	33.0	-16.1
				15	0	18.1	16.6	33.0	-16.4
			64QAM	1	0	17.5	16.0	33.0	-17.0
				1	8	17.5	16.0	33.0	-17.0
				1	14	17.7	16.2	33.0	-16.8
				8	0	17.7	16.2	33.0	-16.8
				8	4	17.7	16.2	33.0	-16.8
				8	7	17.7	16.2	33.0	-16.8
				15	0	17.6	16.1	33.0	-16.9

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
5.0	26065	1852.5	QPSK	1	0	18.5	17.0	33.0	-16.0
				1	12	18.5	17.0	33.0	-16.0
				1	24	18.5	17.0	33.0	-16.0
				12	0	18.6	17.1	33.0	-16.0
				12	7	18.6	17.1	33.0	-16.0
				12	13	18.5	17.0	33.0	-16.0
				25	0	18.5	17.0	33.0	-16.0
			16QAM	1	0	18.3	16.8	33.0	-16.2
				1	12	18.2	16.7	33.0	-16.3
				1	24	18.2	16.7	33.0	-16.3
				12	0	18.1	16.6	33.0	-16.4
				12	7	18.1	16.6	33.0	-16.4
				12	13	18.1	16.6	33.0	-16.4
				25	0	18.1	16.6	33.0	-16.4
			64QAM	1	0	18.0	16.5	33.0	-16.5
				1	12	17.9	16.4	33.0	-16.6
				1	24	17.8	16.3	33.0	-16.7
				12	0	17.7	16.2	33.0	-16.8
				12	7	17.7	16.2	33.0	-16.8
				12	13	17.7	16.2	33.0	-16.8
				25	0	17.7	16.2	33.0	-16.8
5.0	26365	1882.5	QPSK	1	0	18.5	17.0	33.0	-16.1
				1	12	18.5	17.0	33.0	-16.0
				1	24	18.5	17.0	33.0	-16.0
				12	0	18.4	16.9	33.0	-16.1
				12	7	18.5	17.0	33.0	-16.0
				12	13	18.5	17.0	33.0	-16.0
				25	0	18.5	17.0	33.0	-16.0
			16QAM	1	0	18.5	17.0	33.0	-16.1
				1	2	18.5	17.0	33.0	-16.0
				1	5	18.5	17.0	33.0	-16.0
				3	0	18.1	16.6	33.0	-16.4
				3	1	18.2	16.7	33.0	-16.3
				3	2	18.2	16.7	33.0	-16.4
				6	0	18.1	16.6	33.0	-16.4
			64QAM	1	0	17.8	16.3	33.0	-16.7
				1	12	17.8	16.3	33.0	-16.7
				1	24	17.7	16.2	33.0	-16.8
				12	0	17.6	16.1	33.0	-16.9
				12	7	17.6	16.1	33.0	-16.9
				12	13	17.7	16.2	33.0	-16.8
				25	0	17.6	16.1	33.0	-16.9

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
5.0	26665	1912.5	QPSK	1	0	18.6	17.1	33.0	-15.9
				1	12	18.5	17.0	33.0	-16.0
				1	24	18.6	17.1	33.0	-15.9
				12	0	18.6	17.1	33.0	-15.9
				12	7	18.6	17.1	33.0	-15.9
				12	13	18.7	17.2	33.0	-15.8
				25	0	18.6	17.1	33.0	-15.9
			16QAM	1	0	18.3	16.8	33.0	-16.3
				1	12	18.2	16.7	33.0	-16.4
				1	24	18.3	16.8	33.0	-16.2
				12	0	18.2	16.7	33.0	-16.3
				12	7	18.1	16.6	33.0	-16.4
				12	13	18.2	16.7	33.0	-16.3
				25	0	18.0	16.5	33.0	-16.5
			64QAM	1	0	17.6	16.1	33.0	-16.9
				1	12	17.9	16.4	33.0	-16.6
				1	24	18.0	16.5	33.0	-16.5
				12	0	17.6	16.1	33.0	-16.9
				12	7	17.7	16.2	33.0	-16.8
				12	13	17.7	16.2	33.0	-16.8
				25	0	17.7	16.2	33.0	-16.8

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
10.0	26090	1855.0	QPSK	1	0	18.1	16.6	33.0	-16.4
				1	25	17.7	16.2	33.0	-16.8
				1	49	17.9	16.4	33.0	-16.6
				25	0	17.9	16.4	33.0	-16.6
				25	12	17.9	16.4	33.0	-16.6
				25	25	17.8	16.3	33.0	-16.7
				50	0	17.9	16.4	33.0	-16.6
			16QAM	1	0	18.1	16.6	33.0	-16.4
				1	25	17.7	16.2	33.0	-16.8
				1	49	17.9	16.4	33.0	-16.6
				25	0	17.9	16.4	33.0	-16.6
				25	12	17.9	16.4	33.0	-16.6
				25	25	17.9	16.4	33.0	-16.6
				50	0	17.9	16.4	33.0	-16.6
			64QAM	1	0	18.0	16.5	33.0	-16.5
				1	25	17.8	16.3	33.0	-16.7
				1	49	17.9	16.4	33.0	-16.6
				25	0	17.5	16.0	33.0	-17.0
				25	12	17.5	16.0	33.0	-17.0
				25	25	17.5	16.0	33.0	-17.0
				50	0	17.5	16.0	33.0	-17.0
10.0	26365	1882.5	QPSK	1	0	18.2	16.7	33.0	-16.3
				1	25	17.8	16.3	33.0	-16.7
				1	49	18.1	16.6	33.0	-16.4
				25	0	18.0	16.5	33.0	-16.6
				25	12	17.9	16.4	33.0	-16.6
				25	25	18.0	16.5	33.0	-16.5
				50	0	18.1	16.6	33.0	-16.4
			16QAM	1	0	18.5	17.0	33.0	-16.0
				1	25	18.2	16.7	33.0	-16.3
				1	49	18.5	17.0	33.0	-16.0
				25	0	18.0	16.5	33.0	-16.5
				25	12	18.0	16.5	33.0	-16.5
				25	25	18.1	16.6	33.0	-16.4
				50	0	18.1	16.6	33.0	-16.4
			64QAM	1	0	17.9	16.4	33.0	-16.6
				1	25	17.9	16.4	33.0	-16.6
				1	49	18.0	16.5	33.0	-16.5
				25	0	17.5	16.0	33.0	-17.0
				25	12	17.6	16.1	33.0	-16.9
				25	25	17.6	16.1	33.0	-16.9
				50	0	17.6	16.1	33.0	-16.9

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
10.0	26640	1910.0	QPSK	1	0	18.1	16.6	33.0	-16.4
				1	25	18.0	16.5	33.0	-16.5
				1	49	18.1	16.6	33.0	-16.4
				25	0	18.1	16.6	33.0	-16.4
				25	12	18.1	16.6	33.0	-16.4
				25	25	18.1	16.6	33.0	-16.5
			16QAM	50	0	18.1	16.6	33.0	-16.4
				1	0	18.2	16.7	33.0	-16.3
				1	25	18.0	16.5	33.0	-16.5
				1	49	18.1	16.6	33.0	-16.4
				25	0	18.2	16.7	33.0	-16.3
				25	12	18.2	16.7	33.0	-16.3
				25	25	18.2	16.7	33.0	-16.3
			64QAM	50	0	18.1	16.6	33.0	-16.4
				1	0	17.5	16.0	33.0	-17.0
				1	25	17.3	15.8	33.0	-17.2
				1	49	17.3	15.8	33.0	-17.2
				25	0	17.7	16.2	33.0	-16.8
				25	12	17.7	16.2	33.0	-16.8
				25	25	17.6	16.1	33.0	-16.9
				50	0	17.6	16.1	33.0	-16.9

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
15.0	26115	1857.0	QPSK	1	0	18.4	16.9	33.0	-16.1
				1	37	18.2	16.7	33.0	-16.3
				1	74	18.4	16.9	33.0	-16.1
				36	0	18.4	16.9	33.0	-16.1
				36	20	18.3	16.8	33.0	-16.2
				36	39	18.3	16.8	33.0	-16.2
				75	0	18.3	16.8	33.0	-16.2
			16QAM	1	0	17.9	16.4	33.0	-16.6
				1	37	17.7	16.2	33.0	-16.8
				1	74	17.7	16.2	33.0	-16.8
				36	0	18.0	16.5	33.0	-16.6
				36	20	17.9	16.4	33.0	-16.6
				36	39	17.8	16.3	33.0	-16.7
				75	0	17.9	16.4	33.0	-16.6
			64QAM	1	0	18.0	16.5	33.0	-16.5
				1	37	17.8	16.3	33.0	-16.7
				1	74	17.8	16.3	33.0	-16.7
				36	0	17.6	16.1	33.0	-16.9
				36	20	17.5	16.0	33.0	-17.0
				36	39	17.6	16.1	33.0	-16.9
				75	0	17.5	16.0	33.0	-17.0
15.0	26365	1882.5	QPSK	1	0	18.5	17.0	33.0	-16.0
				1	37	18.5	17.0	33.0	-16.1
				1	74	18.5	17.0	33.0	-16.1
				36	0	18.5	17.0	33.0	-16.0
				36	20	18.4	16.9	33.0	-16.1
				36	39	18.5	17.0	33.0	-16.0
				75	0	18.6	17.1	33.0	-16.0
			16QAM	1	0	18.4	16.9	33.0	-16.1
				1	37	18.3	16.8	33.0	-16.2
				1	74	18.3	16.8	33.0	-16.2
				36	0	18.1	16.6	33.0	-16.4
				36	20	18.0	16.5	33.0	-16.5
				36	39	18.1	16.6	33.0	-16.4
				75	0	18.1	16.6	33.0	-16.4
			64QAM	1	0	18.0	16.5	33.0	-16.5
				1	37	17.9	16.4	33.0	-16.6
				1	74	17.8	16.3	33.0	-16.7
				36	0	17.6	16.1	33.0	-16.9
				36	20	17.7	16.2	33.0	-16.8
				36	39	17.6	16.1	33.0	-16.9
				75	0	17.6	16.1	33.0	-16.9

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
15.0	26615	1907.5	QPSK	1	0	18.7	17.2	33.0	-15.8
				1	37	18.5	17.0	33.0	-16.0
				1	74	18.7	17.2	33.0	-15.8
				36	0	18.7	17.2	33.0	-15.8
				36	20	18.6	17.1	33.0	-15.9
				36	39	18.6	17.1	33.0	-15.9
				75	0	18.6	17.1	33.0	-15.9
			16QAM	1	0	18.7	17.2	33.0	-15.8
				1	37	18.5	17.0	33.0	-16.0
				1	74	18.6	17.1	33.0	-15.9
				36	0	18.2	16.7	33.0	-16.3
				36	20	18.1	16.6	33.0	-16.4
				36	39	18.1	16.6	33.0	-16.4
				75	0	18.1	16.6	33.0	-16.4
			64QAM	1	0	18.0	16.5	33.0	-16.5
				1	37	17.8	16.3	33.0	-16.7
				1	74	17.9	16.4	33.0	-16.6
				36	0	17.7	16.2	33.0	-16.8
				36	20	17.7	16.2	33.0	-16.8
				36	39	17.6	16.1	33.0	-16.9
				75	0	17.6	16.1	33.0	-16.9

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
20.0	26140	1860.0	QPSK	1	0	18.6	17.1	33.0	-15.9
				1	49	18.3	16.8	33.0	-16.2
				1	99	18.6	17.1	33.0	-15.9
				50	0	18.4	16.9	33.0	-16.1
				50	24	18.3	16.8	33.0	-16.2
				50	50	18.4	16.9	33.0	-16.1
				100	0	18.4	16.9	33.0	-16.1
			16QAM	1	0	18.1	16.6	33.0	-16.4
				1	49	17.7	16.2	33.0	-16.8
				1	99	17.9	16.4	33.0	-16.6
				50	0	17.9	16.4	33.0	-16.6
				50	24	17.9	16.4	33.0	-16.6
				50	50	17.9	16.4	33.0	-16.6
				100	0	17.9	16.4	33.0	-16.6
			64QAM	1	0	18.0	16.5	33.0	-16.5
				1	49	17.8	16.3	33.0	-16.7
				1	99	17.9	16.4	33.0	-16.6
				50	0	17.5	16.0	33.0	-17.0
				50	24	17.5	16.0	33.0	-17.0
				50	50	17.5	16.0	33.0	-17.0
				100	0	17.5	16.0	33.0	-17.0
20.0	26365	1882.5	QPSK	1	0	18.9	17.4	33.0	-15.6
				1	49	18.4	16.9	33.0	-16.1
				1	99	18.7	17.2	33.0	-15.8
				50	0	18.5	17.0	33.0	-16.0
				50	24	18.6	17.1	33.0	-15.9
				50	50	18.5	17.0	33.0	-16.0
				100	0	18.6	17.1	33.0	-15.9
			16QAM	1	0	18.8	17.3	33.0	-15.7
				1	49	18.2	16.7	33.0	-16.3
				1	99	18.5	17.0	33.0	-16.0
				50	0	18.1	16.6	33.0	-16.4
				50	24	18.1	16.6	33.0	-16.4
				50	50	18.1	16.6	33.0	-16.4
				100	0	18.1	16.6	33.0	-16.4
			64QAM	1	0	18.1	16.6	33.0	-16.4
				1	49	17.9	16.4	33.0	-16.6
				1	99	18.0	16.5	33.0	-16.5
				50	0	17.7	16.2	33.0	-16.8
				50	24	17.7	16.2	33.0	-16.8
				50	50	17.7	16.2	33.0	-16.8
				100	0	17.7	16.2	33.0	-16.8

Antenna gain (dBi)		-1.50							
Bandwidth	UL Channel	-1.5	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
20.0	590	1905.0	QPSK	1	0	18.6	17.1	33.0	-15.9
				1	49	18.4	16.9	33.0	-16.1
				1	99	18.5	17.0	33.0	-16.0
				50	0	18.6	17.1	33.0	-15.9
				50	24	18.5	17.0	33.0	-16.0
				50	50	18.5	17.0	33.0	-16.0
				100	0	18.5	17.0	33.0	-16.0
			16QAM	1	0	18.5	17.0	33.0	-16.0
				1	49	18.3	16.8	33.0	-16.2
				1	99	18.4	16.9	33.0	-16.1
				50	0	18.1	16.6	33.0	-16.4
				50	24	18.0	16.5	33.0	-16.5
				50	50	18.0	16.5	33.0	-16.5
				100	0	18.1	16.6	33.0	-16.4
			64QAM	1	0	17.6	16.1	33.0	-16.9
				1	49	17.5	16.0	33.0	-17.0
				1	99	17.6	16.1	33.0	-16.9
				50	0	17.6	16.1	33.0	-16.9
				50	24	17.6	16.1	33.0	-16.9
				50	50	17.6	16.1	33.0	-16.9
				100	0	17.6	16.1	33.0	-16.9

LTE Band 26

Antenna gain (dBi)		-5.90							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
1.4	26697	814.7	QPSK	1	0	24.8	18.9	38.5	-19.6
				1	3	24.7	18.8	38.5	-19.7
				1	5	24.8	18.9	38.5	-19.6
				3	0	24.8	18.9	38.5	-19.6
				3	1	24.9	19.0	38.5	-19.5
				3	3	24.8	18.9	38.5	-19.6
			16QAM	6	0	23.8	17.9	38.5	-20.6
				1	0	23.8	17.9	38.5	-20.5
				1	3	23.9	18.0	38.5	-20.5
				1	5	23.8	17.9	38.5	-20.5
				3	0	23.9	18.0	38.5	-20.5
				3	1	23.9	18.0	38.5	-20.4
				3	3	23.9	18.0	38.5	-20.4
				6	0	23.0	17.1	38.5	-21.3
			64QAM	1	0	22.2	16.3	38.5	-22.2
				1	3	22.4	16.5	38.5	-22.0
				1	5	22.3	16.4	38.5	-22.1
				3	0	22.2	16.3	38.5	-22.2
				3	1	22.2	16.3	38.5	-22.2
				3	3	22.2	16.3	38.5	-22.2
1.4	26865	831.5	QPSK	6	0	21.2	15.3	38.5	-23.2
				1	0	24.5	18.6	38.5	-19.9
				1	3	24.5	18.6	38.5	-19.9
				1	5	24.4	18.5	38.5	-20.0
				3	0	24.4	18.5	38.5	-20.0
				3	1	24.5	18.6	38.5	-19.9
			16QAM	3	3	24.4	18.5	38.5	-20.0
				6	0	23.7	17.8	38.5	-20.7
				1	0	24.0	18.1	38.5	-20.3
				1	3	24.1	18.2	38.5	-20.3
				1	5	24.0	18.1	38.5	-20.4
				3	0	23.9	18.0	38.5	-20.5
			64QAM	3	1	23.9	18.0	38.5	-20.5
				3	3	23.9	18.0	38.5	-20.5
				6	0	22.6	16.7	38.5	-21.8
				1	0	22.2	16.3	38.5	-22.2
				1	3	22.2	16.3	38.5	-22.2
				1	5	22.2	16.3	38.5	-22.2
				3	0	22.2	16.3	38.5	-22.2
				3	1	22.2	16.3	38.5	-22.2
				3	3	22.2	16.3	38.5	-22.2
				6	0	21.2	15.3	38.5	-23.2

Antenna gain (dBi)		-5.90							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
1.4	27033	848.3	QPSK	1	0	24.2	18.3	38.5	-20.2
				1	3	24.3	18.4	38.5	-20.1
				1	5	24.2	18.3	38.5	-20.2
				3	0	24.3	18.4	38.5	-20.1
				3	1	24.4	18.5	38.5	-20.0
				3	3	24.4	18.5	38.5	-20.0
			16QAM	6	0	23.8	17.9	38.5	-20.6
				1	0	23.7	17.8	38.5	-20.7
				1	3	23.8	17.9	38.5	-20.6
				1	5	23.8	17.9	38.5	-20.6
				3	0	23.9	18.0	38.5	-20.5
				3	1	23.9	18.0	38.5	-20.5
				3	3	24.0	18.1	38.5	-20.4
				6	0	22.9	17.0	38.5	-21.5
			64QAM	1	0	22.4	16.5	38.5	-22.0
				1	3	22.4	16.5	38.5	-22.0
				1	5	22.4	16.5	38.5	-22.0
				3	0	22.4	16.5	38.5	-22.0
				3	1	22.4	16.5	38.5	-22.0
				3	3	22.4	16.5	38.5	-22.0
				6	0	21.3	15.4	38.5	-23.1

Antenna gain (dBi)		-5.90							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
3.0	26705	815.5	QPSK	1	0	24.5	18.6	38.5	-19.9
				1	8	24.4	18.5	38.5	-20.0
				1	14	24.5	18.6	38.5	-19.9
				8	0	23.9	18.0	38.5	-20.5
				8	4	23.9	18.0	38.5	-20.5
				8	7	23.9	18.0	38.5	-20.5
			16QAM	15	0	23.8	17.9	38.5	-20.6
				1	0	23.9	18.0	38.5	-20.5
				1	8	24.0	18.1	38.5	-20.4
				1	14	23.9	18.0	38.5	-20.5
				8	0	23.2	17.3	38.5	-21.2
				8	4	23.2	17.3	38.5	-21.2
				8	7	23.2	17.3	38.5	-21.2
			64QAM	15	0	22.9	17.0	38.5	-21.5
				1	0	22.3	16.4	38.5	-22.1
				1	8	22.4	16.5	38.5	-22.0
				1	14	22.4	16.5	38.5	-22.0
				8	0	21.2	15.3	38.5	-23.2
				8	4	21.2	15.3	38.5	-23.2
				8	7	21.2	15.3	38.5	-23.2
				15	0	21.2	15.3	38.5	-23.2
3.0	26865	831.5	QPSK	1	0	24.5	18.6	38.5	-19.9
				1	8	24.5	18.6	38.5	-19.9
				1	14	24.5	18.6	38.5	-19.9
				8	0	23.7	17.8	38.5	-20.7
				8	4	23.7	17.8	38.5	-20.7
				8	7	23.7	17.8	38.5	-20.7
			16QAM	15	0	23.7	17.8	38.5	-20.7
				1	0	23.5	17.6	38.5	-20.9
				1	8	23.7	17.8	38.5	-20.7
				1	14	23.6	17.7	38.5	-20.8
				8	0	22.8	16.9	38.5	-21.6
				8	4	22.9	17.0	38.5	-21.5
				8	7	22.8	16.9	38.5	-21.6
			64QAM	15	0	22.8	16.9	38.5	-21.6
				1	0	22.2	16.3	38.5	-22.2
				1	8	22.2	16.3	38.5	-22.2
				1	14	22.3	16.4	38.5	-22.1
				8	0	21.2	15.3	38.5	-23.2
				8	4	21.2	15.3	38.5	-23.2
				8	7	21.2	15.3	38.5	-23.2
				15	0	21.2	15.3	38.5	-23.2

Antenna gain (dBi)		-5.90							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
3.0	27025	847.5	QPSK	1	0	24.3	18.4	38.5	-20.1
				1	8	24.5	18.6	38.5	-19.9
				1	14	24.3	18.4	38.5	-20.1
				8	0	23.8	17.9	38.5	-20.6
				8	4	23.8	17.9	38.5	-20.6
				8	7	23.8	17.9	38.5	-20.6
				15	0	23.9	18.0	38.5	-20.5
			16QAM	1	0	24.0	18.1	38.5	-20.4
				1	8	23.5	17.6	38.5	-20.9
				1	14	24.1	18.2	38.5	-20.3
				8	0	22.6	16.7	38.5	-21.8
				8	4	22.6	16.7	38.5	-21.8
				8	7	22.7	16.8	38.5	-21.7
				15	0	22.9	17.0	38.5	-21.5
			64QAM	1	0	22.3	16.4	38.5	-22.1
				1	8	22.2	16.3	38.5	-22.2
				1	14	22.2	16.3	38.5	-22.2
				8	0	21.2	15.3	38.5	-23.2
				8	4	21.2	15.3	38.5	-23.2
				8	7	21.2	15.3	38.5	-23.2
				15	0	21.2	15.3	38.5	-23.2

Antenna gain (dBi)		-5.90							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
5.0	26715	816.5	QPSK	1	0	24.5	18.6	38.5	-19.9
				1	12	24.5	18.6	38.5	-19.9
				1	24	24.5	18.6	38.5	-19.9
				12	0	23.8	17.9	38.5	-20.6
				12	7	23.9	18.0	38.5	-20.5
				12	13	23.9	18.0	38.5	-20.5
				25	0	23.9	18.0	38.5	-20.5
			16QAM	1	0	24.0	18.1	38.5	-20.4
				1	12	24.0	18.1	38.5	-20.4
				1	24	24.1	18.2	38.5	-20.3
				12	0	23.0	17.1	38.5	-21.4
				12	7	23.1	17.2	38.5	-21.3
				12	13	23.1	17.2	38.5	-21.3
				25	0	23.1	17.2	38.5	-21.3
			64QAM	1	0	22.3	16.4	38.5	-22.1
				1	12	22.2	16.3	38.5	-22.2
				1	24	22.2	16.3	38.5	-22.2
				12	0	21.6	15.7	38.5	-22.8
				12	7	21.6	15.7	38.5	-22.8
				12	13	21.6	15.7	38.5	-22.8
				25	0	21.6	15.7	38.5	-22.8
			QPSK	1	0	24.6	18.7	38.5	-19.8
				1	12	24.5	18.6	38.5	-19.9
				1	24	24.5	18.6	38.5	-19.9
				12	0	23.6	17.7	38.5	-20.8
				12	7	23.8	17.9	38.5	-20.6
				12	13	23.7	17.8	38.5	-20.7
				25	0	23.7	17.8	38.5	-20.7
			16QAM	1	0	23.8	17.9	38.5	-20.6
				1	2	23.7	17.8	38.5	-20.7
				1	5	23.8	17.9	38.5	-20.6
				3	0	22.8	16.9	38.5	-21.6
				3	1	22.9	17.0	38.5	-21.5
				3	2	22.8	16.9	38.5	-21.6
			64QAM	6	0	22.8	16.9	38.5	-21.6
				1	0	22.2	16.3	38.5	-22.2
				1	12	22.2	16.3	38.5	-22.2
				1	24	22.2	16.3	38.5	-22.2
				12	0	21.3	15.4	38.5	-23.1
				12	7	21.3	15.4	38.5	-23.1
				12	13	21.3	15.4	38.5	-23.1
				25	0	21.3	15.4	38.5	-23.1

Antenna gain (dBi)		-5.90							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
5.0	27015	846.5	QPSK	1	0	24.3	18.4	38.5	-20.1
				1	12	24.3	18.4	38.5	-20.1
				1	24	24.3	18.4	38.5	-20.1
				12	0	23.9	18.0	38.5	-20.5
				12	7	23.9	18.0	38.5	-20.5
				12	13	23.9	18.0	38.5	-20.5
				25	0	23.9	18.0	38.5	-20.5
			16QAM	1	0	23.9	18.0	38.5	-20.5
				1	12	23.8	17.9	38.5	-20.6
				1	24	23.9	18.0	38.5	-20.5
				12	0	22.9	17.0	38.5	-21.5
				12	7	22.9	17.0	38.5	-21.5
				12	13	22.9	17.0	38.5	-21.5
				25	0	22.8	16.9	38.5	-21.6
			64QAM	1	0	22.3	16.4	38.5	-22.1
				1	12	22.2	16.3	38.5	-22.2
				1	24	22.2	16.3	38.5	-22.2
				12	0	21.4	15.5	38.5	-23.0
				12	7	21.4	15.5	38.5	-23.0
				12	13	21.4	15.5	38.5	-23.0
				25	0	21.4	15.5	38.5	-23.0

Antenna gain (dBi)		-5.90							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
10.0	26740	819.0	QPSK	1	0	24.5	18.6	38.5	-19.9
				1	25	24.5	18.6	38.5	-19.9
				1	49	24.4	18.5	38.5	-20.0
				25	0	24.0	18.1	38.5	-20.4
				25	12	24.0	18.1	38.5	-20.4
				25	25	23.9	18.0	38.5	-20.5
			16QAM	50	0	23.9	18.0	38.5	-20.5
				1	0	23.8	17.9	38.5	-20.6
				1	25	23.8	17.9	38.5	-20.6
				1	49	23.8	17.9	38.5	-20.6
				25	0	23.1	17.2	38.5	-21.3
				25	12	23.2	17.3	38.5	-21.2
				25	25	23.1	17.2	38.5	-21.3
			64QAM	50	0	23.0	17.1	38.5	-21.4
				1	0	22.5	16.6	38.5	-21.9
				1	25	22.3	16.4	38.5	-22.1
				1	49	22.3	16.4	38.5	-22.1
				25	0	21.2	15.3	38.5	-23.2
				25	12	21.2	15.3	38.5	-23.2
10.0	26865	831.5	QPSK	25	25	21.2	15.3	38.5	-23.2
				50	0	21.2	15.3	38.5	-23.2
			16QAM	1	0	24.4	18.5	38.5	-20.0
				1	25	24.5	18.6	38.5	-19.9
				1	49	24.5	18.6	38.5	-19.9
				25	0	23.7	17.8	38.5	-20.7
				25	12	23.8	17.9	38.5	-20.6
			64QAM	25	25	23.8	17.9	38.5	-20.6
				50	0	23.8	17.9	38.5	-20.6
				1	0	24.1	18.2	38.5	-20.3
				1	25	24.1	18.2	38.5	-20.3
				1	49	24.1	18.2	38.5	-20.3
				25	0	22.7	16.8	38.5	-21.7
			16QAM	25	12	22.8	16.9	38.5	-21.6
				25	25	22.8	16.9	38.5	-21.6
				50	0	22.8	16.9	38.5	-21.6
			64QAM	1	0	22.2	16.3	38.5	-22.2
				1	25	22.2	16.3	38.5	-22.2
				1	49	22.2	16.3	38.5	-22.2
				25	0	21.2	15.3	38.5	-23.2
				25	12	21.2	15.3	38.5	-23.2
				25	25	21.2	15.3	38.5	-23.2
			64QAM	50	0	21.2	15.3	38.5	-23.2
				50	0	21.2	15.3	38.5	-23.2

Antenna gain (dBi)		-5.90							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
10.0	26990	844.0	QPSK	1	0	24.3	18.4	38.5	-20.1
				1	25	24.3	18.4	38.5	-20.1
				1	49	24.3	18.4	38.5	-20.1
				25	0	23.8	17.9	38.5	-20.6
				25	12	23.9	18.0	38.5	-20.5
				25	25	23.8	17.9	38.5	-20.6
				50	0	23.9	18.0	38.5	-20.5
			16QAM	1	0	23.9	18.0	38.5	-20.5
				1	25	23.8	17.9	38.5	-20.6
				1	49	23.7	17.8	38.5	-20.7
				25	0	22.9	17.0	38.5	-21.5
				25	12	23.0	17.1	38.5	-21.4
				25	25	22.9	17.0	38.5	-21.5
				50	0	22.9	17.0	38.5	-21.5
			64QAM	1	0	22.2	16.3	38.5	-22.2
				1	25	22.3	16.4	38.5	-22.1
				1	49	22.2	16.3	38.5	-22.2
				25	0	21.2	15.3	38.5	-23.2
				25	12	21.3	15.4	38.5	-23.1
				25	25	21.2	15.3	38.5	-23.2
				50	0	21.2	15.3	38.5	-23.2

Antenna gain (dBi)		-5.90							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	ERP Average (dBm)	ERP Limit (dBm)	Margin (dB)
15.0	26865	831.5	QPSK	1	0	24.6	18.7	38.5	-19.8
				1	37	24.7	18.8	38.5	-19.7
				1	74	24.9	19.0	38.5	-19.5
				36	0	23.7	17.8	38.5	-20.7
				36	20	23.8	17.9	38.5	-20.6
				36	39	23.8	17.9	38.5	-20.6
				75	0	23.7	17.8	38.5	-20.7
			16QAM	1	0	23.6	17.7	38.5	-20.8
				1	37	23.6	17.7	38.5	-20.8
				1	74	23.8	17.9	38.5	-20.6
				36	0	22.7	16.8	38.5	-21.7
				36	20	22.8	16.9	38.5	-21.6
				36	39	22.8	16.9	38.5	-21.6
				75	0	22.8	16.9	38.5	-21.6
			64QAM	1	0	22.2	16.3	38.5	-22.2
				1	37	22.3	16.4	38.5	-22.1
				1	74	22.4	16.5	38.5	-22.0
				36	0	21.2	15.3	38.5	-23.2
				36	20	21.2	15.3	38.5	-23.2
				36	39	21.2	15.3	38.5	-23.2
				75	0	21.2	15.3	38.5	-23.2

LTE Band 41

Antenna gain (dBi)		-2.70							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
5.0	39675	2498.5	QPSK	1	0	23.5	20.8	33.0	-12.2
				1	12	23.5	20.8	33.0	-12.2
				1	24	23.4	20.7	33.0	-12.3
				12	0	23.4	20.7	33.0	-12.3
				12	7	23.4	20.7	33.0	-12.3
				12	13	23.4	20.7	33.0	-12.3
			16QAM	25	0	23.4	20.7	33.0	-12.3
				1	0	22.8	20.1	33.0	-12.9
				1	12	22.8	20.1	33.0	-12.9
				1	24	22.8	20.1	33.0	-12.9
				12	0	21.9	19.2	33.0	-13.8
				12	7	21.9	19.2	33.0	-13.8
				12	13	21.9	19.2	33.0	-13.8
				25	0	21.9	19.2	33.0	-13.8
			64QAM	1	0	21.5	18.8	33.0	-14.2
				1	12	21.5	18.8	33.0	-14.2
				1	24	21.5	18.8	33.0	-14.2
				12	0	20.5	17.8	33.0	-15.2
				12	7	20.5	17.8	33.0	-15.2
				12	13	20.5	17.8	33.0	-15.2
5.0	40620	2593.0	QPSK	25	0	20.5	17.8	33.0	-15.2
				1	0	23.6	20.9	33.0	-12.1
				1	12	23.6	20.9	33.0	-12.2
				1	24	23.5	20.8	33.0	-12.2
				12	0	23.6	20.9	33.0	-12.1
				12	7	23.6	20.9	33.0	-12.1
			16QAM	12	13	23.6	20.9	33.0	-12.1
				25	0	23.6	20.9	33.0	-12.1
				1	0	23.0	20.3	33.0	-12.7
				1	12	23.0	20.3	33.0	-12.7
				1	24	23.0	20.3	33.0	-12.7
				12	0	22.0	19.3	33.0	-13.7
			64QAM	12	7	22.0	19.3	33.0	-13.7
				12	13	22.0	19.3	33.0	-13.7
				25	0	22.0	19.3	33.0	-13.7
				1	0	21.4	18.7	33.0	-14.3
				1	12	21.5	18.8	33.0	-14.2
				1	24	21.4	18.7	33.0	-14.3
				12	0	20.3	17.6	33.0	-15.4
				12	7	20.3	17.6	33.0	-15.4
				12	13	20.3	17.6	33.0	-15.4
				25	0	20.3	17.6	33.0	-15.4

Antenna gain (dBi)		-2.70							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
5.0	41565	2687.5	QPSK	1	0	23.5	20.8	33.0	-12.2
				1	12	23.5	20.8	33.0	-12.2
				1	24	23.4	20.7	33.0	-12.3
				12	0	23.5	20.8	33.0	-12.2
				12	7	23.5	20.8	33.0	-12.2
				12	13	23.5	20.8	33.0	-12.2
				25	0	23.5	20.8	33.0	-12.2
			16QAM	1	0	23.0	20.3	33.0	-12.7
				1	12	23.0	20.3	33.0	-12.7
				1	24	23.0	20.3	33.0	-12.7
				12	0	22.0	19.3	33.0	-13.7
				12	7	22.0	19.3	33.0	-13.7
				12	13	22.0	19.3	33.0	-13.7
				25	0	22.0	19.3	33.0	-13.7
			64QAM	1	0	21.2	18.5	33.0	-14.5
				1	12	21.1	18.4	33.0	-14.6
				1	24	21.2	18.5	33.0	-14.5
				12	0	20.2	17.5	33.0	-15.5
				12	7	20.2	17.5	33.0	-15.5
				12	13	20.2	17.5	33.0	-15.5
				25	0	20.2	17.5	33.0	-15.5

Antenna gain (dBi)		-2.70							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
10.0	39700	2501.0	QPSK	1	0	23.4	20.7	33.0	-12.3
				1	25	23.4	20.7	33.0	-12.3
				1	49	23.4	20.7	33.0	-12.4
				25	0	23.4	20.7	33.0	-12.3
				25	12	23.4	20.7	33.0	-12.3
				25	25	23.4	20.7	33.0	-12.3
			16QAM	50	0	23.4	20.7	33.0	-12.3
				1	0	23.0	20.3	33.0	-12.7
				1	25	23.0	20.3	33.0	-12.7
				1	49	22.9	20.2	33.0	-12.8
				25	0	22.0	19.3	33.0	-13.7
				25	12	22.0	19.3	33.0	-13.8
				25	25	21.9	19.2	33.0	-13.8
				50	0	21.9	19.2	33.0	-13.8
			64QAM	1	0	21.3	18.6	33.0	-14.4
				1	25	21.3	18.6	33.0	-14.4
				1	49	21.2	18.5	33.0	-14.5
				25	0	20.5	17.8	33.0	-15.2
				25	12	20.5	17.8	33.0	-15.2
				25	25	20.4	17.7	33.0	-15.3
				50	0	20.5	17.8	33.0	-15.2
10.0	40620	2593.0	QPSK	1	0	23.6	20.9	33.0	-12.2
				1	25	23.4	20.7	33.0	-12.3
				1	49	23.4	20.7	33.0	-12.3
				25	0	23.5	20.8	33.0	-12.2
				25	12	23.6	20.9	33.0	-12.1
				25	25	23.5	20.8	33.0	-12.2
			16QAM	50	0	23.6	20.9	33.0	-12.1
				1	0	23.0	20.3	33.0	-12.7
				1	25	23.0	20.3	33.0	-12.7
				1	49	23.0	20.3	33.0	-12.7
				25	0	22.0	19.3	33.0	-13.7
				25	12	22.0	19.3	33.0	-13.7
				25	25	22.0	19.3	33.0	-13.7
				50	0	22.0	19.3	33.0	-13.7
			64QAM	1	0	21.4	18.7	33.0	-14.3
				1	25	21.3	18.6	33.0	-14.4
				1	49	21.3	18.6	33.0	-14.4
				25	0	20.3	17.6	33.0	-15.4
				25	12	20.3	17.6	33.0	-15.4
				25	25	20.3	17.6	33.0	-15.4
				50	0	20.3	17.6	33.0	-15.4

Antenna gain (dBi)		-2.70							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
10.0	41540	2685.0	QPSK	1	0	18.1	15.4	33.0	-17.6
				1	25	23.7	21.0	33.0	-12.0
				1	49	23.5	20.8	33.0	-12.2
				25	0	23.4	20.7	33.0	-12.3
				25	12	23.6	20.9	33.0	-12.1
				25	25	23.5	20.8	33.0	-12.2
				50	0	23.5	20.8	33.0	-12.2
			16QAM	1	0	23.5	20.8	33.0	-12.2
				1	25	23.0	20.3	33.0	-12.7
				1	49	23.0	20.3	33.0	-12.7
				25	0	23.0	20.3	33.0	-12.8
				25	12	22.0	19.3	33.0	-13.7
				25	25	22.0	19.3	33.0	-13.7
				50	0	22.0	19.3	33.0	-13.8
			64QAM	1	0	22.0	19.3	33.0	-13.7
				1	25	21.1	18.4	33.0	-14.6
				1	49	21.0	18.3	33.0	-14.7
				25	0	21.0	18.3	33.0	-14.7
				25	12	20.3	17.6	33.0	-15.4
				25	25	20.2	17.5	33.0	-15.5
				50	0	20.2	17.5	33.0	-15.5

Antenna gain (dBi)		-2.70							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
15.0	39725	2503.5	QPSK	1	0	23.5	20.8	33.0	-12.2
				1	37	23.3	20.6	33.0	-12.4
				1	74	23.3	20.6	33.0	-12.5
				36	0	23.4	20.7	33.0	-12.3
				36	20	23.4	20.7	33.0	-12.3
				36	39	23.4	20.7	33.0	-12.3
				75	0	23.4	20.7	33.0	-12.3
			16QAM	1	0	23.0	20.3	33.0	-12.7
				1	37	22.8	20.1	33.0	-12.9
				1	74	22.7	20.0	33.0	-13.0
				36	0	22.0	19.3	33.0	-13.7
				36	20	21.9	19.2	33.0	-13.8
				36	39	21.8	19.1	33.0	-13.9
				75	0	21.9	19.2	33.0	-13.8
			64QAM	1	0	21.6	18.9	33.0	-14.1
				1	37	21.6	18.9	33.0	-14.1
				1	74	21.4	18.7	33.0	-14.3
				36	0	20.5	17.8	33.0	-15.2
				36	20	20.5	17.8	33.0	-15.2
				36	39	20.5	17.8	33.0	-15.2
				75	0	20.4	17.7	33.0	-15.3
15.0	40620	2593.0	QPSK	1	0	23.8	21.1	33.0	-11.9
				1	37	23.5	20.8	33.0	-12.2
				1	74	23.4	20.7	33.0	-12.3
				36	0	23.6	20.9	33.0	-12.1
				36	20	23.6	20.9	33.0	-12.1
				36	39	23.5	20.8	33.0	-12.2
				75	0	23.5	20.8	33.0	-12.2
			16QAM	1	0	23.2	20.5	33.0	-12.5
				1	37	23.0	20.3	33.0	-12.7
				1	74	22.9	20.2	33.0	-12.8
				36	0	22.1	19.4	33.0	-13.6
				36	20	22.1	19.4	33.0	-13.6
				36	39	22.0	19.3	33.0	-13.7
				75	0	22.1	19.4	33.0	-13.6
			64QAM	1	0	21.5	18.8	33.0	-14.2
				1	37	21.4	18.7	33.0	-14.3
				1	74	21.2	18.5	33.0	-14.5
				36	0	20.4	17.7	33.0	-15.3
				36	20	20.3	17.6	33.0	-15.4
				36	39	20.3	17.6	33.0	-15.4
				75	0	20.3	17.6	33.0	-15.4

Antenna gain (dBi)		-2.70							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
15.0	41515	2682.5	QPSK	1	0	23.6	20.9	33.0	-12.1
				1	37	23.5	20.8	33.0	-12.2
				1	74	23.2	20.5	33.0	-12.5
				36	0	23.7	21.0	33.0	-12.1
				36	20	23.6	20.9	33.0	-12.1
				36	39	23.5	20.8	33.0	-12.2
				75	0	23.5	20.8	33.0	-12.3
			16QAM	1	0	23.3	20.6	33.0	-12.4
				1	37	23.1	20.4	33.0	-12.6
				1	74	22.9	20.2	33.0	-12.8
				36	0	22.2	19.5	33.0	-13.5
				36	20	22.1	19.4	33.0	-13.6
				36	39	22.0	19.3	33.0	-13.8
				75	0	22.1	19.4	33.0	-13.6
			64QAM	1	0	21.5	18.8	33.0	-14.2
				1	37	21.4	18.7	33.0	-14.3
				1	74	21.0	18.3	33.0	-14.7
				36	0	20.3	17.6	33.0	-15.4
				36	20	20.2	17.5	33.0	-15.5
				36	39	20.1	17.4	33.0	-15.6
				75	0	20.1	17.4	33.0	-15.6

Antenna gain (dBi)		-2.70							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
20.0	39750	2506.0	QPSK	1	0	23.6	20.9	33.0	-12.1
				1	49	23.4	20.7	33.0	-12.3
				1	99	23.3	20.6	33.0	-12.4
				50	0	23.5	20.8	33.0	-12.2
				50	24	23.4	20.7	33.0	-12.3
				50	50	23.3	20.6	33.0	-12.4
				100	0	23.4	20.7	33.0	-12.3
			16QAM	1	0	23.0	20.3	33.0	-12.7
				1	49	22.8	20.1	33.0	-12.9
				1	99	22.7	20.0	33.0	-13.0
				50	0	21.9	19.2	33.0	-13.8
				50	24	21.9	19.2	33.0	-13.8
				50	50	21.8	19.1	33.0	-13.9
				100	0	21.9	19.2	33.0	-13.8
			64QAM	1	0	21.5	18.8	33.0	-14.2
				1	49	21.5	18.8	33.0	-14.2
				1	99	21.4	18.7	33.0	-14.3
				50	0	20.5	17.8	33.0	-15.2
				50	24	20.4	17.7	33.0	-15.3
				50	50	20.4	17.7	33.0	-15.3
				100	0	20.4	17.7	33.0	-15.3
20.0	40620	2593.0	QPSK	1	0	23.7	21.0	33.0	-12.0
				1	49	23.5	20.8	33.0	-12.2
				1	99	23.4	20.7	33.0	-12.3
				50	0	23.7	21.0	33.0	-12.1
				50	24	23.6	20.9	33.0	-12.1
				50	50	23.5	20.8	33.0	-12.2
				100	0	23.6	20.9	33.0	-12.1
			16QAM	1	0	23.1	20.4	33.0	-12.6
				1	49	22.9	20.2	33.0	-12.8
				1	99	22.8	20.1	33.0	-12.9
				50	0	22.2	19.5	33.0	-13.6
				50	24	22.1	19.4	33.0	-13.6
				50	50	22.0	19.3	33.0	-13.7
				100	0	22.1	19.4	33.0	-13.6
			64QAM	1	0	21.6	18.9	33.0	-14.1
				1	49	21.3	18.6	33.0	-14.4
				1	99	21.2	18.5	33.0	-14.5
				50	0	20.5	17.8	33.0	-15.2
				50	24	20.3	17.6	33.0	-15.4
				50	50	20.3	17.6	33.0	-15.4
				100	0	20.3	17.6	33.0	-15.4

Antenna gain (dBi)		-2.70							
Bandwidth	UL Channel	-1.5	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
20.0	41490	2680.0	QPSK	1	0	23.8	21.1	33.0	-11.9
				1	49	23.6	20.9	33.0	-12.1
				1	99	23.4	20.7	33.0	-12.3
				50	0	23.7	21.0	33.0	-12.1
				50	24	23.6	20.9	33.0	-12.1
				50	50	23.4	20.7	33.0	-12.3
				100	0	23.3	20.6	33.0	-12.4
			16QAM	1	0	23.5	20.8	33.0	-12.2
				1	49	23.2	20.5	33.0	-12.5
				1	99	22.9	20.2	33.0	-12.8
				50	0	22.2	19.5	33.0	-13.5
				50	24	22.2	19.5	33.0	-13.5
				50	50	22.0	19.3	33.0	-13.7
				100	0	22.1	19.4	33.0	-13.6
			64QAM	1	0	21.4	18.7	33.0	-14.3
				1	49	21.3	18.6	33.0	-14.4
				1	99	21.1	18.4	33.0	-14.6
				50	0	20.3	17.6	33.0	-15.4
				50	24	20.3	17.6	33.0	-15.4
				50	50	20.2	17.5	33.0	-15.5
				100	0	20.2	17.5	33.0	-15.5

LTE Band 66

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
1.4	131979	1710.7	QPSK	1	0	20.1	17.8	33.0	-15.2
				1	3	20.1	17.8	33.0	-15.2
				1	5	20.1	17.8	33.0	-15.2
				3	0	20.2	17.9	33.0	-15.1
				3	1	20.2	17.9	33.0	-15.1
				3	3	20.2	17.9	33.0	-15.1
			16QAM	6	0	20.1	17.8	33.0	-15.2
				1	0	20.0	17.7	33.0	-15.3
				1	3	20.1	17.8	33.0	-15.2
				1	5	20.0	17.7	33.0	-15.3
				3	0	19.9	17.6	33.0	-15.4
				3	1	20.0	17.7	33.0	-15.3
				3	3	19.9	17.6	33.0	-15.4
				6	0	19.6	17.3	33.0	-15.7
			64QAM	1	0	19.3	17.0	33.0	-16.0
				1	3	19.4	17.1	33.0	-15.9
				1	5	19.3	17.0	33.0	-16.0
				3	0	19.1	16.8	33.0	-16.2
				3	1	19.2	16.9	33.0	-16.1
				3	3	19.1	16.8	33.0	-16.2
1.4	132322	1745.0	QPSK	6	0	19.1	16.8	33.0	-16.2
				1	0	20.0	17.7	33.0	-15.3
				1	3	20.0	17.7	33.0	-15.3
				1	5	20.0	17.7	33.0	-15.3
				3	0	20.0	17.7	33.0	-15.3
				3	1	20.0	17.7	33.0	-15.3
			16QAM	3	3	20.0	17.7	33.0	-15.3
				6	0	20.0	17.7	33.0	-15.3
				1	0	19.3	17.0	33.0	-16.0
				1	3	19.4	17.1	33.0	-15.9
				1	5	19.3	17.0	33.0	-16.0
				3	0	19.7	17.4	33.0	-15.6
				3	1	19.7	17.4	33.0	-15.6
				3	3	19.7	17.4	33.0	-15.6
				6	0	19.7	17.4	33.0	-15.6
			64QAM	1	0	18.8	16.5	33.0	-16.5
				1	3	18.9	16.6	33.0	-16.4
				1	5	18.8	16.5	33.0	-16.5
				3	0	18.7	16.4	33.0	-16.6
				3	1	18.8	16.5	33.0	-16.5
				3	3	18.7	16.4	33.0	-16.6
				6	0	18.7	16.4	33.0	-16.6

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
1.4	132665	1779.3	QPSK	1	0	19.9	17.6	33.0	-15.4
				1	3	19.9	17.6	33.0	-15.4
				1	5	19.9	17.6	33.0	-15.4
				3	0	19.9	17.6	33.0	-15.4
				3	1	20.0	17.7	33.0	-15.3
				3	3	19.9	17.6	33.0	-15.4
				6	0	19.9	17.6	33.0	-15.4
			16QAM	1	0	19.1	16.8	33.0	-16.2
				1	3	19.2	16.9	33.0	-16.1
				1	5	19.2	16.9	33.0	-16.1
				3	0	19.5	17.2	33.0	-15.8
				3	1	19.5	17.2	33.0	-15.8
				3	3	19.5	17.2	33.0	-15.8
				6	0	19.6	17.3	33.0	-15.7
			64QAM	1	0	18.5	16.2	33.0	-16.8
				1	3	18.5	16.2	33.0	-16.8
				1	5	18.5	16.2	33.0	-16.8
				3	0	18.5	16.2	33.0	-16.8
				3	1	18.5	16.2	33.0	-16.8
				3	3	18.5	16.2	33.0	-16.8
				6	0	18.5	16.2	33.0	-16.8

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
3.0	131987	1711.5	QPSK	1	0	20.2	17.9	33.0	-15.1
				1	8	20.2	17.9	33.0	-15.1
				1	14	20.2	17.9	33.0	-15.1
				8	0	20.2	17.9	33.0	-15.1
				8	4	20.3	18.0	33.0	-15.0
				8	7	20.2	17.9	33.0	-15.1
			16QAM	15	0	20.2	17.9	33.0	-15.1
				1	0	20.1	17.8	33.0	-15.2
				1	8	20.1	17.8	33.0	-15.2
				1	14	20.1	17.8	33.0	-15.2
				8	0	19.8	17.5	33.0	-15.5
				8	4	19.9	17.6	33.0	-15.4
				8	7	19.8	17.5	33.0	-15.5
			64QAM	15	0	19.8	17.5	33.0	-15.5
				1	0	19.3	17.0	33.0	-16.0
				1	8	19.3	17.0	33.0	-16.0
				1	14	19.3	17.0	33.0	-16.0
				8	0	19.1	16.8	33.0	-16.2
				8	4	19.1	16.8	33.0	-16.2
				8	7	19.1	16.8	33.0	-16.2
				15	0	19.1	16.8	33.0	-16.2
3.0	132322	1745.0	QPSK	1	0	20.0	17.7	33.0	-15.3
				1	8	20.0	17.7	33.0	-15.3
				1	14	20.0	17.7	33.0	-15.3
				8	0	20.1	17.8	33.0	-15.2
				8	4	20.1	17.8	33.0	-15.2
				8	7	20.1	17.8	33.0	-15.2
			16QAM	15	0	20.1	17.8	33.0	-15.2
				1	0	19.5	17.2	33.0	-15.8
				1	8	19.5	17.2	33.0	-15.8
				1	14	19.5	17.2	33.0	-15.8
				8	0	19.7	17.4	33.0	-15.6
				8	4	19.7	17.4	33.0	-15.6
				8	7	19.6	17.3	33.0	-15.7
			64QAM	15	0	19.7	17.4	33.0	-15.6
				1	0	18.6	16.3	33.0	-16.7
				1	8	18.5	16.2	33.0	-16.8
				1	14	18.5	16.2	33.0	-16.8
				8	0	18.7	16.4	33.0	-16.6
				8	4	18.8	16.5	33.0	-16.5
				8	7	18.7	16.4	33.0	-16.6
				15	0	18.7	16.4	33.0	-16.6

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
3.0	132657	1778.5	QPSK	1	0	20.0	17.7	33.0	-15.3
				1	8	19.9	17.6	33.0	-15.4
				1	14	19.9	17.6	33.0	-15.4
				8	0	20.0	17.7	33.0	-15.3
				8	4	20.0	17.7	33.0	-15.3
				8	7	20.0	17.7	33.0	-15.3
				15	0	20.0	17.7	33.0	-15.3
			16QAM	1	0	19.3	17.0	33.0	-16.0
				1	8	19.2	16.9	33.0	-16.1
				1	14	19.2	16.9	33.0	-16.1
				8	0	19.5	17.2	33.0	-15.8
				8	4	19.5	17.2	33.0	-15.8
				8	7	19.5	17.2	33.0	-15.8
				15	0	19.5	17.2	33.0	-15.8
			64QAM	1	0	18.5	16.2	33.0	-16.8
				1	8	18.5	16.2	33.0	-16.8
				1	14	18.5	16.2	33.0	-16.8
				8	0	18.5	16.2	33.0	-16.8
				8	4	18.5	16.2	33.0	-16.8
				8	7	18.5	16.2	33.0	-16.8
				15	0	18.5	16.2	33.0	-16.8

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
5.0	131997	1712.5	QPSK	1	0	20.3	18.0	33.0	-15.0
				1	12	20.2	17.9	33.0	-15.1
				1	24	20.2	17.9	33.0	-15.1
				12	0	20.3	18.0	33.0	-15.0
				12	7	20.3	18.0	33.0	-15.0
				12	13	20.3	18.0	33.0	-15.0
			16QAM	25	0	20.3	18.0	33.0	-15.0
				1	0	20.4	18.1	33.0	-14.9
				1	12	20.4	18.1	33.0	-14.9
				1	24	20.4	18.1	33.0	-14.9
				12	0	19.9	17.6	33.0	-15.4
				12	7	19.9	17.6	33.0	-15.4
			64QAM	12	13	19.9	17.6	33.0	-15.4
				25	0	19.9	17.6	33.0	-15.4
				1	0	19.1	16.8	33.0	-16.2
				1	12	19.0	16.7	33.0	-16.3
				1	24	19.0	16.7	33.0	-16.3
				12	0	18.9	16.6	33.0	-16.4
			5.0	132322	1745.0	QPSK	12	7	18.9
12	13	18.8					16.5	33.0	-16.5
25	0	18.8					16.5	33.0	-16.5
1	0	20.3					18.0	33.0	-15.0
1	12	20.2					17.9	33.0	-15.1
1	24	20.2					17.9	33.0	-15.1
16QAM	12	0				20.2	17.9	33.0	-15.1
	12	7				20.2	17.9	33.0	-15.1
	12	13				20.1	17.8	33.0	-15.2
	25	0				20.2	17.9	33.0	-15.1
	1	0				19.7	17.4	33.0	-15.6
	1	2				19.6	17.3	33.0	-15.7
64QAM	1	5				19.6	17.3	33.0	-15.7
	3	0				19.7	17.4	33.0	-15.6
	3	1				19.7	17.4	33.0	-15.6
	3	2				19.7	17.4	33.0	-15.6
	6	0				19.7	17.4	33.0	-15.6
	1	0				18.7	16.4	33.0	-16.6
64QAM	1	12				18.6	16.3	33.0	-16.7
	1	24	18.6	16.3	33.0	-16.7			
	12	0	18.6	16.3	33.0	-16.7			
	12	7	18.6	16.3	33.0	-16.7			
	12	13	18.6	16.3	33.0	-16.7			
	25	0	18.6	16.3	33.0	-16.7			

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
5.0	132647	1777.5	QPSK	1	0	20.0	17.7	33.0	-15.3
				1	12	19.9	17.6	33.0	-15.4
				1	24	19.9	17.6	33.0	-15.4
				12	0	20.0	17.7	33.0	-15.3
				12	7	20.0	17.7	33.0	-15.3
				12	13	20.0	17.7	33.0	-15.3
				25	0	20.0	17.7	33.0	-15.3
			16QAM	1	0	19.6	17.3	33.0	-15.7
				1	12	19.5	17.2	33.0	-15.8
				1	24	19.5	17.2	33.0	-15.8
				12	0	19.7	17.4	33.0	-15.6
				12	7	19.7	17.4	33.0	-15.6
				12	13	19.6	17.3	33.0	-15.7
				25	0	19.5	17.2	33.0	-15.8
			64QAM	1	0	18.3	16.0	33.0	-17.0
				1	12	18.5	16.2	33.0	-16.8
				1	24	18.5	16.2	33.0	-16.8
				12	0	18.5	16.2	33.0	-16.8
				12	7	18.5	16.2	33.0	-16.8
				12	13	18.5	16.2	33.0	-16.8
				25	0	18.5	16.2	33.0	-16.8

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
10.0	132022	1715.0	QPSK	1	0	20.3	18.0	33.0	-15.0
				1	25	20.2	17.9	33.0	-15.1
				1	49	20.2	17.9	33.0	-15.1
				25	0	20.3	18.0	33.0	-15.0
				25	12	20.3	18.0	33.0	-15.0
				25	25	20.3	18.0	33.0	-15.0
			16QAM	50	0	20.3	18.0	33.0	-15.0
				1	0	20.2	17.9	33.0	-15.1
				1	25	20.1	17.8	33.0	-15.2
				1	49	20.2	17.9	33.0	-15.1
				25	0	19.9	17.6	33.0	-15.4
				25	12	19.9	17.6	33.0	-15.4
				25	25	19.8	17.5	33.0	-15.5
				50	0	19.8	17.5	33.0	-15.5
			64QAM	1	0	19.2	16.9	33.0	-16.1
				1	25	19.1	16.8	33.0	-16.2
				1	49	19.1	16.8	33.0	-16.2
				25	0	18.8	16.5	33.0	-16.5
				25	12	18.8	16.5	33.0	-16.5
				25	25	18.8	16.5	33.0	-16.5
10.0	132322	1745.0	QPSK	50	0	18.8	16.5	33.0	-16.5
				1	0	20.0	17.7	33.0	-15.3
				1	25	20.0	17.7	33.0	-15.3
				1	49	20.0	17.7	33.0	-15.3
				25	0	20.2	17.9	33.0	-15.1
				25	12	20.2	17.9	33.0	-15.1
			16QAM	25	25	20.1	17.8	33.0	-15.2
				50	0	20.1	17.8	33.0	-15.2
				1	0	19.6	17.3	33.0	-15.7
				1	25	19.6	17.3	33.0	-15.7
				1	49	19.5	17.2	33.0	-15.8
				25	0	19.8	17.5	33.0	-15.5
			64QAM	25	12	19.8	17.5	33.0	-15.5
				25	25	19.7	17.4	33.0	-15.6
				50	0	19.7	17.4	33.0	-15.6
				1	0	18.6	16.3	33.0	-16.7
				1	25	18.6	16.3	33.0	-16.7
				1	49	18.5	16.2	33.0	-16.8
				25	0	18.5	16.2	33.0	-16.8
				25	12	18.5	16.2	33.0	-16.8
				25	25	18.6	16.3	33.0	-16.7
				50	0	18.5	16.2	33.0	-16.8

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
10.0	132622	1775.0	QPSK	1	0	20.2	17.9	33.0	-15.1
				1	25	20.0	17.7	33.0	-15.3
				1	49	20.0	17.7	33.0	-15.3
				25	0	20.2	17.9	33.0	-15.1
				25	12	20.1	17.8	33.0	-15.2
				25	25	20.0	17.7	33.0	-15.3
				50	0	20.1	17.8	33.0	-15.2
			16QAM	1	0	19.5	17.2	33.0	-15.8
				1	25	19.3	17.0	33.0	-16.0
				1	49	19.3	17.0	33.0	-16.0
				25	0	19.9	17.6	33.0	-15.4
				25	12	19.7	17.4	33.0	-15.6
				25	25	19.7	17.4	33.0	-15.6
				50	0	19.6	17.3	33.0	-15.7
			64QAM	1	0	18.6	16.3	33.0	-16.7
				1	25	18.3	16.0	33.0	-17.0
				1	49	18.5	16.2	33.0	-16.8
				25	0	18.5	16.2	33.0	-16.8
				25	12	18.5	16.2	33.0	-16.8
				25	25	18.5	16.2	33.0	-16.8
				50	0	18.5	16.2	33.0	-16.8

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
15.0	132047	1717.5	QPSK	1	0	20.4	18.1	33.0	-14.9
				1	37	20.2	17.9	33.0	-15.1
				1	74	20.2	17.9	33.0	-15.1
				36	0	20.3	18.0	33.0	-15.0
				36	20	20.2	17.9	33.0	-15.1
				36	39	20.3	18.0	33.0	-15.0
				75	0	20.2	17.9	33.0	-15.1
			16QAM	1	0	20.3	18.0	33.0	-15.0
				1	37	20.1	17.8	33.0	-15.2
				1	74	20.1	17.8	33.0	-15.2
				36	0	19.9	17.6	33.0	-15.4
				36	20	19.8	17.5	33.0	-15.5
				36	39	19.9	17.6	33.0	-15.4
				75	0	19.8	17.5	33.0	-15.5
			64QAM	1	0	19.3	17.0	33.0	-16.0
				1	37	19.0	16.7	33.0	-16.3
				1	74	19.1	16.8	33.0	-16.2
				36	0	18.9	16.6	33.0	-16.4
				36	20	18.8	16.5	33.0	-16.5
				36	39	18.9	16.6	33.0	-16.4
				75	0	18.8	16.5	33.0	-16.5
15.0	132322	1745.0	QPSK	1	0	20.1	17.8	33.0	-15.2
				1	37	19.9	17.6	33.0	-15.4
				1	74	19.9	17.6	33.0	-15.4
				36	0	20.0	17.7	33.0	-15.3
				36	20	20.1	17.8	33.0	-15.2
				36	39	20.1	17.8	33.0	-15.2
				75	0	20.1	17.8	33.0	-15.2
			16QAM	1	0	19.6	17.3	33.0	-15.7
				1	37	19.5	17.2	33.0	-15.8
				1	74	19.4	17.1	33.0	-15.9
				36	0	19.7	17.4	33.0	-15.6
				36	20	19.7	17.4	33.0	-15.6
				36	39	19.7	17.4	33.0	-15.6
				75	0	19.7	17.4	33.0	-15.6
			64QAM	1	0	19.0	16.7	33.0	-16.3
				1	37	18.9	16.6	33.0	-16.4
				1	74	18.8	16.5	33.0	-16.5
				36	0	18.7	16.4	33.0	-16.6
				36	20	18.8	16.5	33.0	-16.5
				36	39	18.7	16.4	33.0	-16.6
				75	0	18.7	16.4	33.0	-16.6

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
15.0	132572	1772.5	QPSK	1	0	20.3	18.0	33.0	-15.0
				1	37	20.0	17.7	33.0	-15.3
				1	74	19.9	17.6	33.0	-15.4
				36	0	20.1	17.8	33.0	-15.2
				36	20	20.1	17.8	33.0	-15.2
				36	39	20.0	17.7	33.0	-15.3
				75	0	20.0	17.7	33.0	-15.3
			16QAM	1	0	19.9	17.6	33.0	-15.4
				1	37	19.6	17.3	33.0	-15.7
				1	74	19.4	17.1	33.0	-15.9
				36	0	19.5	17.2	33.0	-15.8
				36	20	19.7	17.4	33.0	-15.6
				36	39	19.5	17.2	33.0	-15.8
				75	0	19.5	17.2	33.0	-15.8
			64QAM	1	0	18.8	16.5	33.0	-16.5
				1	37	18.5	16.2	33.0	-16.8
				1	74	18.3	16.0	33.0	-17.0
				36	0	18.4	16.1	33.0	-16.9
				36	20	18.3	16.0	33.0	-17.0
				36	39	18.5	16.2	33.0	-16.8
				75	0	18.5	16.2	33.0	-16.8

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	Frequency (MHz)	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
20.0	132072	1720.0	QPSK	1	0	20.3	18.0	33.0	-15.0
				1	49	20.2	17.9	33.0	-15.1
				1	99	20.2	17.9	33.0	-15.1
				50	0	20.3	18.0	33.0	-15.0
				50	24	20.3	18.0	33.0	-15.0
				50	50	20.2	17.9	33.0	-15.1
				100	0	20.3	18.0	33.0	-15.0
				1	0	20.5	18.2	33.0	-14.8
			16QAM	1	49	20.3	18.0	33.0	-15.0
				1	99	20.4	18.1	33.0	-14.9
				50	0	19.8	17.5	33.0	-15.5
				50	24	19.8	17.5	33.0	-15.5
				50	50	19.7	17.4	33.0	-15.6
				100	0	19.8	17.5	33.0	-15.5
				1	0	19.4	17.1	33.0	-15.9
				1	49	19.1	16.8	33.0	-16.2
			64QAM	1	99	19.2	16.9	33.0	-16.1
				50	0	19.1	16.8	33.0	-16.2
				50	24	19.1	16.8	33.0	-16.2
				50	50	19.0	16.7	33.0	-16.3
				100	0	19.0	16.7	33.0	-16.3
20.0	132322	1745.0	QPSK	1	0	20.4	18.1	33.0	-14.9
				1	49	20.1	17.8	33.0	-15.2
				1	99	20.0	17.7	33.0	-15.3
				50	0	20.3	18.0	33.0	-15.0
				50	24	20.2	17.9	33.0	-15.1
				50	50	20.1	17.8	33.0	-15.2
				100	0	20.2	17.9	33.0	-15.1
			16QAM	1	0	20.2	17.9	33.0	-15.1
				1	49	19.8	17.5	33.0	-15.5
				1	99	19.8	17.5	33.0	-15.5
				50	0	19.7	17.4	33.0	-15.6
				50	24	19.7	17.4	33.0	-15.6
				50	50	19.6	17.3	33.0	-15.7
				100	0	19.7	17.4	33.0	-15.6
			64QAM	1	0	19.0	16.7	33.0	-16.3
				1	49	18.9	16.6	33.0	-16.4
				1	99	18.7	16.4	33.0	-16.6
				50	0	18.8	16.5	33.0	-16.5
				50	24	18.7	16.4	33.0	-16.6
				50	50	18.5	16.2	33.0	-16.8
				100	0	18.7	16.4	33.0	-16.6

Antenna gain (dBi)		-2.30							
Bandwidth	UL Channel	-1.5	Modulation	RB Size	RB Offset	Conducted Average (dBm)	EIRP Average (dBm)	EIRP Limit (dBm)	Margin (dB)
20.0	132572	1770.0	QPSK	1	0	20.4	18.1	33.0	-14.9
				1	12	20.1	17.8	33.0	-15.2
				1	24	20.1	17.8	33.0	-15.2
				12	0	20.3	18.0	33.0	-15.0
				12	7	20.3	18.0	33.0	-15.0
				12	13	20.1	17.8	33.0	-15.2
				25	0	20.3	18.0	33.0	-15.0
			16QAM	1	0	20.2	17.9	33.0	-15.1
				1	12	19.8	17.5	33.0	-15.5
				1	24	19.8	17.5	33.0	-15.5
				12	0	19.9	17.6	33.0	-15.4
				12	7	19.8	17.5	33.0	-15.5
				12	13	19.6	17.3	33.0	-15.7
				25	0	19.8	17.5	33.0	-15.5
			64QAM	1	0	18.9	16.6	33.0	-16.4
				1	12	18.5	16.2	33.0	-16.8
				1	24	18.5	16.2	33.0	-16.8
				12	0	18.6	16.3	33.0	-16.7
				12	7	18.5	16.2	33.0	-16.8
				12	13	18.3	16.0	33.0	-17.0
				25	0	18.5	16.2	33.0	-16.8

12. PEAK TO AVERAGE RATIO

TEST PROCEDURE


Per KDB 971168 D01 Power Meas License Digital Systems v02r02

TEST SPEC


In addition, when the transmitter power is measured in terms of average value, the peak-to-average ratio of the power shall not exceed 13 dB.

12.1. CONDUCTED PEAK TO AVERAGE RESULT


GSM




WCDMA





LTE Band 7






LTE Band 12







LTE Band 13





LTE Band 25







LTE Band 26







LTE Band 41





LTE Band 66





13. OCCUPIED BANDWIDTH

RULE PART(S)

FCC: §2.1049

LIMITS

For reporting purposes only

TEST PROCEDURE


The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the low, middle and high channel in each band. The -26dB bandwidth was also measured and recorded.

(KDB 971168 D01 Power Meas License Digital Systems v02r02)

13.1. OCCUPIED BANDWIDTH RESULTS AND PLOTS


GSM

Band	Mode	Channel	f (MHz)	99% BW (kHz)	-26dB (kHz)
GSM 850	GPRS	128	824.2	242.0	320.9
		190	836.6	242.7	312.5
		251	848.8	244.3	311.6
	EGPRS	128	824.2	252.5	324.1
		190	836.6	245.7	307.9
		251	848.8	236.0	308.5
GSM 1900	GPRS	512	1850.2	243.4	310.1
		661	1880	253.3	318.5
		810	1909.8	244.8	320.0
	EGPRS	512	1850.2	249.1	318.6
		661	1880	241.3	304.2
		810	1909.8	242.3	305.4




WCDMA


Band	Mode	Channel	f (MHz)	99% BW (MHz)	-26dB (MHz)
Band 2	REL99	9262	1852.4	4.12	4.66
		9400	1880	4.12	4.69
		9538	1907.6	4.10	4.68
	HSDPA	9262	1852.4	4.11	4.68
		9400	1880	4.12	4.70
		9538	1907.6	4.14	4.66
Band 4	REL99	9262	1712.4	4.12	4.68
		9400	1732.6	4.13	4.70
		9538	1752.6	4.12	4.66
	HSDPA	9262	1712.4	4.11	4.65
		9400	1732.6	4.12	4.68
		9538	1752.6	4.12	4.65
Band 5	REL99	4132	826.4	4.12	4.69
		4183	836.6	4.14	4.70
		4233	846.6	4.11	4.70
	HSDPA	4132	826.4	4.13	4.71
		4183	836.6	4.13	4.67
		4233	846.6	4.11	4.71



LTE Band 7


Band	BW(MHz)	Mode	RB/RB Size	f (MHz)	99% BW (MHz)	-26dB BW
LTE7	5	QPSK	50/0	2505	4.50	4.90
			50/0	2535	4.50	4.94
			50/0	2565	4.50	4.94
		16QAM	25/0	2502.5	4.49	4.89
			25/0	2535	4.49	4.95
			25/0	2567.5	4.49	4.90
	10	QPSK	50/0	2505	8.93	9.60
			50/0	2535	8.94	9.72
			50/0	2565	8.95	9.67
		16QAM	50/0	2505	8.96	9.67
			50/0	2535	8.95	9.65
			50/0	2565	8.98	9.67
	15	QPSK	75/0	2507.5	13.38	14.41
			75/0	2535	13.40	14.54
			75/0	2562.5	13.39	14.33
		16QAM	75/0	2507.5	13.38	14.33
			75/0	2535	13.38	14.51
			75/0	2562.5	13.40	14.42
	20	QPSK	100/0	2510	17.86	19.27
			100/0	2535	17.91	19.24
			100/0	2560	17.82	19.07
		16QAM	100/0	2510	17.79	19.25
			100/0	2535	17.87	19.32
			100/0	2560	17.88	19.16






LTE Band 12

Band	BW(MHz)	Mode	RB/RB Size	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
LTE12	1.4	QPSK	6/0	699.7	1.09	1.23
			6/0	707.5	1.08	1.22
			6/0	715.3	1.09	1.23
		16QAM	6/0	699.7	1.08	1.23
			6/0	707.5	1.08	1.22
			6/0	715.3	1.09	1.22
	3	QPSK	15/0	700.5	2.69	3.0
			15/0	707.5	2.69	2.98
			15/0	714.5	2.69	2.96
		16QAM	15/0	700.5	2.68	3.0
			15/0	707.5	2.69	2.96
			15/0	714.5	2.69	2.96
	5	QPSK	25/0	701.5	4.52	4.89
			25/0	707.5	4.49	4.94
			25/0	713.5	4.49	4.95
		16QAM	25/0	701.5	4.49	4.9
			25/0	707.5	4.51	4.94
			25/0	713.5	4.49	4.91
	10	QPSK	50/0	704	8.96	9.69
			50/0	707.5	8.94	9.72
			50/0	711	8.93	9.64
		16QAM	50/0	704	8.99	9.68
			50/0	707.5	8.93	9.65
			50/0	711	8.95	9.59





LTE Band 13


Band	BW(MHz)	Mode	RB/RB Size	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
LTE13	5	QPSK	25/0	779.5	4.49	4.92
			25/0	782	4.5	4.93
			25/0	784.5	4.5	4.91
		16QAM	25/0	779.5	4.50	4.95
			25/0	782	4.49	4.93
			25/0	784.5	4.49	4.95
	10	QPSK	50/0			
			50/0	782	8.94	9.66
			50/0			
		16QAM	50/0			
			50/0	782	8.95	9.66
			50/0			




LTE Band 25

Band	BW(MHz)	Mode	RB/RB Size	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
LTE25	1.4	QPSK	6/0	1850.7	1.09	1.23
			6/0	1882.5	1.08	1.23
			6/0	1914.3	1.08	1.22
		16QAM	6/0	1850.7	1.09	1.22
			6/0	1882.5	1.09	1.23
			6/0	1914.3	1.08	1.22
	3	QPSK	15/0	1851.5	2.69	2.94
			15/0	1882.5	2.69	2.99
			15/0	1913.5	2.69	2.97
		16QAM	15/0	1851.5	2.69	3.01
			15/0	1882.5	2.69	2.96
			15/0	1913.5	2.69	3.0
	5	QPSK	25/0	1852.5	4.5	4.83
			25/0	1882.5	4.48	4.91
			25/0	1912.5	4.49	4.91
		16QAM	25/0	1852.5	4.49	4.89
			25/0	1882.5	4.49	4.95
			25/0	1912.5	4.49	4.92
	10	QPSK	50/0	1855	8.97	9.73
			50/0	1882.5	8.95	9.81
			50/0	1910	8.97	9.73
		16QAM	50/0	1855	8.95	9.68
			50/0	1882.5	8.97	9.64
			50/0	1910	8.95	9.62

Band	BW(MHz)	Mode	RB/RB Size	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
LTE25	15	QPSK	75/0	1857.5	13.37	14.38
			75/0	1882.5	13.40	14.46
			75/0	1907.5	13.39	14.49
		16QAM	75/0	1857.5	13.38	14.55
			75/0	1882.5	13.44	14.41
			75/0	1907.5	13.41	14.45
	20	QPSK	100/0	1860	17.83	19.18
			100/0	1882.5	17.85	19.15
			100/0	1905	17.87	19.24
		16QAM	100/0	1860	17.84	19.32
			100/0	1882.5	17.86	19.24
			100/0	1905	17.84	19.07






LTE Band 26

Band	BW(MHz)	Mode	RB/RB Size	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
LTE26	1.4	QPSK	6/0	814.7	1.09	1.23
			6/0	831.5	1.08	1.22
			6/0	848.3	1.08	1.23
		16QAM	6/0	814.7	1.08	1.23
			6/0	831.5	1.08	1.23
			6/0	848.3	1.09	1.24
	3	QPSK	25/0	815.5	2.68	2.94
			25/0	831.5	2.69	2.98
			25/0	847.5	2.68	2.96
		16QAM	25/0	815.5	2.68	3.0
			25/0	831.5	2.68	2.95
			25/0	847.5	2.69	2.97
	5	QPSK	25/0	816.5	4.5	4.93
			25/0	831.5	4.5	4.9
			25/0	846.5	4.49	4.96
		16QAM	25/0	816.5	4.49	4.94
			25/0	831.5	4.5	4.89
			25/0	846.5	4.48	4.89
	10	QPSK	50/0	819	8.94	9.73
			50/0	831.5	8.98	9.71
			50/0	844	8.97	9.78
		16QAM	50/0	819	8.95	9.68
			50/0	831.5	8.95	9.73
			50/0	844	8.96	9.73


Band	BW(MHz)	Mode	RB/RB Size	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
	15	QPSK	75/0	831.5	13.4	14.52
			75/0	836.5	13.39	14.50
			75/0	841.5	13.41	14.38
		16QAM	75/0	831.5	13.39	14.54
			75/0	836.5	13.38	14.45
			75/0	841.5	13.39	14.43






LTE Band 41

Band	BW(MHz)	Mode	RB/RB Size	f (MHz)	99% BW (MHz)	-26dB BW
LTE41	5	QPSK	25/0	2498.5	4.49	4.94
			25/0	2593	4.49	4.97
			25/0	2687.5	4.50	4.93
		16QAM	25/0	2498.5	4.48	4.88
			25/0	2593	4.49	4.90
			25/0	2687.5	4.49	4.94
	10	QPSK	50/0	2501	8.95	9.51
			50/0	2593	8.96	9.75
			50/0	2685	8.95	9.67
		16QAM	50/0	2501	8.97	9.73
			50/0	2593	8.94	9.61
			50/0	2685	8.94	9.58
	15	QPSK	75/0	2503.5	13.40	14.33
			75/0	2593	13.42	14.51
			75/0	2682.5	13.40	14.40
		16QAM	75/0	2503.5	13.38	14.38
			75/0	2593	13.38	14.33
			75/0	2682.5	13.41	14.37
	20	QPSK	100/0	2506	17.79	19.12
			100/0	2593	17.87	18.99
			100/0	2680	17.75	18.90
		16QAM	100/0	2506	17.87	19.28
			100/0	2593	17.85	19.10
			100/0	2680	17.76	19.05







LTE Band 66

Band	BW(MHz)	Mode	RB/RB Size	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
LTE66	1.4	QPSK	6/0	1710.7	1.08	1.21
			6/0	1745	1.08	1.23
			6/0	1779.3	1.09	1.22
		16QAM	6/0	1710.7	1.08	1.23
			6/0	1745	1.09	1.24
			6/0	1779.3	1.08	1.23
	3	QPSK	15/0	1711.5	2.69	2.98
			15/0	1745	2.69	2.98
			15/0	1778.5	2.69	2.98
		16QAM	15/0	1711.5	2.69	2.98
			15/0	1745	2.69	2.95
			15/0	1778.5	2.69	2.98
	5	QPSK	25/0	1712.5	4.51	4.92
			25/0	1745	4.53	4.96
			25/0	1777.5	4.50	4.96
		16QAM	25/0	1712.5	4.50	4.94
			25/0	1745	4.51	4.93
			25/0	1777.5	4.50	4.95
	10	QPSK	50/0	1715	8.97	9.72
			50/0	1745	8.96	9.81
			50/0	1775	8.96	9.80
		16QAM	50/0	1715	8.97	9.75
			50/0	1745	8.94	9.74
			50/0	1775	8.93	9.77

Band	BW(MHz)	Mode	RB/RB Size	f (MHz)	99% BW (MHz)	-26dB BW (MHz)
LTE66	15	QPSK	75/0	1717.5	13.41	14.60
			75/0	1745	13.42	14.57
			75/0	1772.5	13.40	14.50
		16QAM	75/0	1717.5	13.39	14.26
			75/0	1745	13.41	14.63
			75/0	1772.5	13.42	14.60
	20	QPSK	100/0	1720	17.83	19.37
			100/0	1745	17.89	19.38
			100/0	1770	17.89	19.32
		16QAM	100/0	1720	17.84	19.19
			100/0	1745	17.89	19.35
			100/0	1770	17.89	19.31





14. BAND EDGE EMISSIONS

RULE PART(S)

FCC: §22.359, §24.238, §27.53 and § 90.691

FCC LIMITS

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

Part 27: (m)(4) (4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 90:

(a)(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10} (f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(a)(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz. {NOTE: Use 100 kHz reference bandwidth.}

TEST PROCEDURE


Per KDB 971168 D01 Power Meas License Digital Systems v02r02


The transmitter output was connected to an Agilent 8960 or a CMW500 Test Set and configured to operate at maximum power. The band edge emissions were measured at the required operating frequencies in each band on the Spectrum Analyzer.

For each band edge measurement:


- Set the spectrum analyzer span to include the block edge frequency.
- Set a marker to point the corresponding band edge frequency in each test case.
- Set display line at -13 dBm
- Set resolution bandwidth to at least 1% of emission bandwidth.


14.1. BAND EDGE PLOTS GSM







WCDMA








LTE Band 7



















LTE Band 12


















LTE Band 13











LTE Band 25
























LTE Band 26-Part 22









LTE B26 3MHz 16QAM Low Channel 1RB




LTE B26 3MHz 16QAM High Channel 1RB




LTE B26 3MHz 16QAM Low Channel FRB




LTE B26 3MHz 16QAM High Channel FRB




LTE B26 5MHz QPSK Low Channel 1RB




LTE B26 5MHz QPSK High Channel 1RB







LTE B26 10MHz QPSK Low Channel 1RB




LTE B26 10MHz QPSK High Channel 1RB




LTE B26 10MHz QPSK Low Channel FRB




LTE B26 10MHz QPSK High Channel FRB




z 16QAM Low Channel 1RB



LTE B26 10MHz 16QAM High Channel 1RB





LTE Band 66

