



# ELEMENT WASHINGTON DC LLC

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.element.com>

## MEASUREMENT REPORT FCC Part 15B Receiver Spurious Emissions

**Applicant Name:**  
Sony Corporation  
1-7-1 Konan Minato-ku  
Tokyo, 108-0075  
Japan

**Date of Testing:**  
02/08/2023 - 03/03/2023  
**Test Report Issue Date:**  
03/31/2023  
**Test Site/Location:**  
Element lab. Columbia, MD, USA  
**Test Report Serial No.:**  
1M2302060006-12.PY7

|                   |                         |
|-------------------|-------------------------|
| <b>FCC ID:</b>    | <b>PY7-84558E</b>       |
| <b>APPLICANT:</b> | <b>Sony Corporation</b> |

**Application Type:** Certification  
**EUT Type:** Portable Handset  
**FCC Classification:** Communications Rcvr for use w/ licensed Tx and CBs (CXX)  
**FCC Rule Part(s):** FCC Part 15 Subpart B  
**Test Procedure(s):** ANSI C63.4-2014

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in ANSI C63.4-2014 (See Test Report). The results shown herein are also deemed satisfactory evidence of compliance with RSS-Gen. These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

**RJ Ortanez**  
**Executive Vice President**



|  |   |                                      |  |
|--|---|--------------------------------------|--|
| <b>FCC ID:</b> PY7-84558E                      | <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2302060006-12.PY7 | <b>Test Dates:</b><br>02/08/2023 - 03/03/2023 | <b>EUT Type:</b><br>Portable Handset | Page 1 of 17                             |



## T A B L E O F C O N T E N T S

|     |   |    |
|-----|---|----|
| 1.0 | INTRODUCTION.....                                       | 3  |
| 1.1 | Scope.....  | 3  |
| 1.2 | Element Test Location .....                             | 3  |
| 1.3 | Test Facility / Accreditations .....                    | 3  |
| 2.0 | PRODUCT INFORMATION .....                               | 4  |
| 2.1 | Equipment Description.....                              | 4  |
| 2.2 | Device Capabilities .....                               | 4  |
| 2.3 | Test Configuration .....                                | 4  |
| 2.4 | Software and Firmware.....                              | 4  |
| 2.5 | EMI Suppression Device(s)/Modifications.....            | 4  |
| 3.0 | DESCRIPTION OF TESTS.....                               | 5  |
| 3.1 | Evaluation Procedure .....                              | 5  |
| 3.2 | AC Line Conducted Emissions .....                       | 5  |
| 3.3 | Radiated Emissions .....                                | 6  |
| 3.4 | Environmental Conditions .....                          | 6  |
| 4.0 | SAMPLE CALCULATIONS.....                                | 7  |
| 4.1 | Conducted Emission Measurement Sample Calculation ..... | 7  |
| 4.2 | Radiated Emission Measurement Sample Calculation .....  | 7  |
| 5.0 | MEASUREMENT UNCERTAINTY .....                           | 8  |
| 6.0 | TEST EQUIPMENT CALIBRATION DATA.....                    | 9  |
| 7.0 | TEST DATA .....   | 10 |
| 7.1 | Summary .....   | 10 |
| 7.2 | Radiated Measurement Data .....                         | 11 |
| 7.3 | Line-Conducted Test Data .....                          | 14 |
| 8.0 | CONCLUSION .....  | 17 |

|  |   |                                      |  |
|--|---|--------------------------------------|--|
| <b>FCC ID:</b> PY7-84558E                      | <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2302060006-12.PY7 | <b>Test Dates:</b><br>02/08/2023 - 03/03/2023 | <b>EUT Type:</b><br>Portable Handset | Page 2 of 17                             |



## 1.0 INTRODUCTION

### 1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and Innovation, Science and Economic Development Canada.

### 1.2 Element Test Location

These measurement tests were conducted at the Element laboratory facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

### 1.3 Test Facility / Accreditations

Measurements were performed at Element lab located in Columbia, MD 21046, U.S.A.

- Element Washington DC LLC is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Washington DC LLC facility is a registered (2451B) test laboratory with the site description on file with ISED.
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

|   |  |                               |                                   |
|---|--|-------------------------------|-----------------------------------|
| FCC ID: PY7-84558E                      | MEASUREMENT REPORT<br>(CERTIFICATION)  |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2302060006-12.PY7 | Test Dates:<br>02/08/2023 - 03/03/2023 | EUT Type:<br>Portable Handset | Page 3 of 17                      |

## 2.0 PRODUCT INFORMATION

### 2.1 Equipment Description

The Equipment Under Test (EUT) is the **Sony Portable Handset FCC ID: PY7-84558E**. The test data contained in this report pertains only to the emissions due to receiver circuitry of the licensed transmitter of the EUT.

**Test Device Serial No.:** 85463

### 2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, Multi-band 5G NR FR1, 802.11b/g/n/ax WLAN, 802.11a/n/ac/ax UNII (5 and 6 GHz), Bluetooth (1x, EDR, LE), NFC, Wireless Power Transfer

The device contains receivers which tune and operate between 30MHz – 960MHz in the following bands:

GSM/GPRS850, WCDMA 850, LTE Band 5, LTE Band 71, LTE Band 12, LTE Band 17, LTE Band 13, n5, n71, LTE Band 29 (DL only).

### 2.3 Test Configuration

The EUT was tested while operating in licensed band Rx mode. All licensed band receivers that tune in the range of 30MHz – 960MHz, as listed in Section 2.2, are investigated. Only the worst-case emissions are reported.

All equipment is placed on the test tabletop and arranged in a typical configuration in accordance with ANSI C63.4-2014 and manipulated to obtain worst case emissions.

For more information, please see Section 7.0 for test data and the test setup photos document for the test setup photographs.

### 2.4 Software and Firmware

The test was conducted with firmware version 0.621 installed on the EUT.

### 2.5 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added, and no modifications were made during testing.

|  |   |                                      |  |
|--|---|--------------------------------------|--|
| FCC ID: PY7-84558E                             | <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2302060006-12.PY7 | <b>Test Dates:</b><br>02/08/2023 - 03/03/2023 | <b>EUT Type:</b><br>Portable Handset | Page 4 of 17                             |



## 3.0 DESCRIPTION OF TESTS

### 3.1 Evaluation Procedure

The measurement procedure described in the American National Standard for Methods of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C63.4-2014) was used in the measurement of the EUT.

**Deviation from measurement procedure.....None**

### 3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.3 The EMI Receiver mode of the Agilent MXE was used to perform AC line conducted emissions testing.

|  |   |                                      |  |
|--|---|--------------------------------------|--|
| FCC ID: PY7-84558E                             | <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2302060006-12.PY7 | <b>Test Dates:</b><br>02/08/2023 - 03/03/2023 | <b>EUT Type:</b><br>Portable Handset | Page 5 of 17                             |



### 3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2014. A raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. . An 80cm tall test table made of Styrodur is placed on top of the turn table.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

All radiated measurements are performed in a chamber that meets the site requirements per ANSI C63.4-2014.

### 3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

|   |  |                               |                                   |
|---|--|-------------------------------|-----------------------------------|
| FCC ID: PY7-84558E                      | MEASUREMENT REPORT<br>(CERTIFICATION)  |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2302060006-12.PY7 | Test Dates:<br>02/08/2023 - 03/03/2023 | EUT Type:<br>Portable Handset | Page 6 of 17                      |

## 4.0 SAMPLE CALCULATIONS

### 4.1 Conducted Emission Measurement Sample Calculation

@ 20.3 MHz

|                       |  |
|-----------------------|--|
| <b>Class B limit</b>  | <b>= 60.0 dB<math>\mu</math>V (Quasi-peak limit)</b> |
| Reading               | = - 57.8 dBm (calibrated quasi-peak level)           |
| Convert to dB $\mu$ V | = - 57.8 + 107 = 49.2 dB $\mu$ V                     |
| Margin                | = 49.2 - 60.0 = - 10.8 dB                            |
|                       | <b>= 10.8 dB below limit</b>                         |

### 4.2 Radiated Emission Measurement Sample Calculation

@ 66.7 MHz

|                             |   |
|-----------------------------|---|
| <b>Class B limit</b>        | <b>= 100 <math>\mu</math>V/m = 40.0 dB<math>\mu</math>V/m</b> |
| Reading                     | = - 76.0 dBm (calibrated level)                               |
| Convert to dB $\mu$ V       | = - 76.0 + 107 = 31.0 dB $\mu$ V                              |
| Antenna Factor + Cable Loss | = 5.8 dB/m  |
| Total                       | = 36.8 dB $\mu$ V/m   |
| Margin                      | = 36.8 - 40.0 = - 3.2 dB                                      |
|                             | <b>= 3.2 dB below limit</b>                                   |

#### Note:

$$\text{Level [dB}\mu\text{V]} = 20 \log_{10} (\text{Level } [\mu\text{V/m}])$$

$$\text{Level [dB}\mu\text{V]} = \text{Level [dBm]} + 107$$

|   |   |                               |                                   |
|---|---|-------------------------------|-----------------------------------|
| FCC ID: PY7-84558E                      | <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2302060006-12.PY7 | Test Dates:<br>02/08/2023 - 03/03/2023        | EUT Type:<br>Portable Handset | Page 7 of 17                      |

## 5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Contribution                 | Expanded Uncertainty ( $\pm$ dB) |
|------------------------------|----------------------------------|
| Radiated Disturbance (<1GHz) | 4.98                             |
| Radiated Disturbance (>1GHz) | 5.07                             |

|   |  |                               |                                   |
|---|--|-------------------------------|-----------------------------------|
| FCC ID: PY7-84558E                      | MEASUREMENT REPORT<br>(CERTIFICATION)  |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2302060006-12.PY7 | Test Dates:<br>02/08/2023 - 03/03/2023 | EUT Type:<br>Portable Handset | Page 8 of 17                      |



## 6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

| Manufacturer    | Model    | Description                          | Cal Date  | Cal Interval | Cal Due   | Serial Number |
|-----------------|----------|--------------------------------------|-----------|--------------|-----------|---------------|
| -               | AP2-001  | EMC Cable and Switch System          | 8/11/2022 | Annual       | 8/11/2023 | AP2-001       |
| -               | AP2-002  | EMC Cable and Switch System          | 8/11/2022 | Annual       | 8/11/2023 | AP2-002       |
| Agilent         | N9038A   | MXE EMI Receiver                     | 1/21/2022 | Annual       | 7/21/2023 | MY51210133    |
| Com-Power       | AL-130   | 9kHz - 30MHz Loop Antenna            | 4/13/2022 | Biennial     | 4/13/2024 | 121034        |
| Emco            | 3115     | Horn Antenna (1-18GHz)               | 8/8/2022  | Biennial     | 8/8/2024  | 9704-5182     |
| ETS-Lindgren    | 3816/2NM | Line Impedance Stabilization Network | 8/11/2022 | Biennial     | 8/11/2024 | 00114451      |
| Pasternack      | NMLC-2   | Line Conducted Emissions Cable (NM)  | 1/11/2023 | Annual       | 1/11/2024 | NMLC-2        |
| Rohde & Schwarz | ESU26    | EMI Test Receiver (26.5GHz)          | 8/29/2022 | Annual       | 8/29/2023 | 100342        |
| Rohde & Schwarz | ESU40    | EMI Test Receiver (40GHz)            | 8/25/2022 | Annual       | 8/25/2023 | 100348        |
| Rohde & Schwarz | CMW500   | Radio Communication Tester           | N/A       |              |           | 112347        |
| Sunol           | DRH-118  | Horn Antenna (1-18 GHz)              | 1/14/2022 | Biennial     | 1/14/2024 | A042511       |
| Sunol           | JB5      | Bi-Log Antenna (30M - 5GHz)          | 8/30/2022 | Biennial     | 8/30/2024 | A051107       |

**Table 6-1. Annual Test Equipment Calibration Schedule**

**Note:**

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

|   |   |                               |                                   |
|---|---|-------------------------------|-----------------------------------|
| FCC ID: PY7-84558E                      | <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2302060006-12.PY7 | Test Dates:<br>02/08/2023 - 03/03/2023        | EUT Type:<br>Portable Handset | Page 9 of 17                      |

## 7.0 TEST DATA

### 7.1 Summary

Test Date(s): 02/08/2023 – 03/03/2023

Test Engineer: Jon Snyder

| FCC Part 15 Section | Description                                   | Result |
|---------------------|---|--------|
| 15.109              | Radiated Emissions                            | PASS   |
| 15.107              | AC Line Conducted Emissions<br>(150kHz-30MHz) | PASS   |

**Table 7-1. Summary of Test Results**

|   |   |                               |                                   |
|---|---|-------------------------------|-----------------------------------|
| FCC ID: PY7-84558E                      | <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2302060006-12.PY7 | Test Dates:<br>02/08/2023 - 03/03/2023        | EUT Type:<br>Portable Handset | Page 10 of 17                     |



## 7.2 Radiated Measurement Data

### Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst-case emissions are reported in this section.

**All out of band emissions must not exceed the limits shown in Table 7-2 per FCC Part 15.109.**

| Frequency [MHz] | Field Strength Limit [ $\mu\text{V/m}$ ] |
|-----------------|--|
| 30 – 88         | 100                                      |
| 88 – 216        | 150                                      |
| 216 – 960       | 200                                      |
| > 960           | 500                                      |

**Table 7-2. 3-Meter Radiated Limits (Section 15.109)**

### Test Procedures Used

ANSI C63.4-2014

### Test Settings

#### Field Strength Measurements

1. Analyzer frequency set to the frequency of the radiated spurious emission of interest
2. RBW = 100kHz, VBW = 300kHz (for emissions between 30MHz – 1GHz)
3. RBW = 1MHz, VBW = 3MHz (for emissions above 1GHz)
4. Detector = Quasi-peak (for emissions between 30MHz – 1GHz)
5. Detector = Peak (for emissions above 1GHz)
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

### Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.


| FCC ID: PY7-84558E                      | MEASUREMENT REPORT (CERTIFICATION)     |                               | Approved by:<br>Technical Manager |
|---|--|-------------------------------|-----------------------------------|
| Test Report S/N:<br>1M2302060006-12.PY7 | Test Dates:<br>02/08/2023 - 03/03/2023 | EUT Type:<br>Portable Handset | Page 11 of 17                     |




**Test Notes**

1. All modes of operation were investigated, and the worst-case emissions are reported.
2. Radiated emissions were measured from 30MHz – 10GHz to ensure that the provisions of 15.33(b)(1) are satisfied with respect to the upper frequency scanning range.
3. The radiated limits for unintentional radiators at 3 meters are used in the table above, as specified in 15.109(a).
4. All readings are calibrated by a signal generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
5. AFCL (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
6. Level (dB $\mu$ V/m) = Analyzer Reading (dBm) + AFCL (dB/m) + 107
7. Margin (dB) = Field strength (dB $\mu$ V/m) – Limit (dB $\mu$ V/m)
8. Measurements are made using a CISPR quasi-peak detector with a 120kHz resolution bandwidth. Above 1GHz, peak measurements are made using a peak detector with a resolution bandwidth of 1MHz and a video bandwidth of 3MHz and average measurements are made with a RMS detector using a resolution bandwidth of 1MHz and a video bandwidth of 3MHz.
9. Calibrated linearly polarized broadband and horn antennas were used for measurements below and above 1GHz, respectively. For measurements made below 1GHz, the results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antennas was found to be less than 2:1.
10. Calibrated low-loss microwaves cables and broadband amplifiers are used.

|  |   |                                      |  |
|--|---|--------------------------------------|--|
| <b>FCC ID:</b> PY7-84558E                      | <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2302060006-12.PY7 | <b>Test Dates:</b><br>02/08/2023 - 03/03/2023 | <b>EUT Type:</b><br>Portable Handset | Page 12 of 17                            |



**Plot 7-1. Radiated Spurious Plot below 1GHz**



**Plot 7-2. Radiated Spurious Plot above 1GHz**

| Frequency [MHz] | Detector   | Ant. Pol. [H/V] | Antenna Height [cm] | Turntable Azimuth [degree] | Analyzer Level [dBm] | AFCL [dB/m] | Field Strength [dBµV/m] | Limit [dBµV/m] | Margin [dB] |
|-----------------|------------|-----------------|---------------------|----------------------------|----------------------|-------------|-------------------------|----------------|-------------|
| 80.00           | Quasi-Peak | H               | -                   | -                          | -98.96               | 14.57       | 22.61                   | 40.00          | -17.39      |
| 150.00          | Quasi-Peak | H               | -                   | -                          | -99.80               | 19.72       | 26.92                   | 43.52          | -16.61      |
| 200.00          | Quasi-Peak | H               | -                   | -                          | -99.42               | 20.36       | 27.94                   | 43.52          | -15.59      |
| 300.00          | Quasi-Peak | H               | -                   | -                          | -100.03              | 21.05       | 28.02                   | 46.02          | -18.00      |
| 500.00          | Quasi-Peak | H               | -                   | -                          | -99.54               | 25.84       | 33.30                   | 46.02          | -12.72      |
| 700.00          | Quasi-Peak | H               | -                   | -                          | -99.35               | 28.46       | 36.11                   | 46.02          | -9.91       |

**Table 7-3. Radiated Measurements at 3-meters**

| FCC ID: PY7-84558E                      | MEASUREMENT REPORT (CERTIFICATION)     |                               | Approved by:<br>Technical Manager |
|---|--|-------------------------------|-----------------------------------|
| Test Report S/N:<br>1M2302060006-12.PY7 | Test Dates:<br>02/08/2023 - 03/03/2023 | EUT Type:<br>Portable Handset | Page 13 of 17                     |



## 7.3 Line-Conducted Test Data

### Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst-case emissions are reported in this section.

**All conducted emissions must not exceed the limits shown in the table below per FCC Part 15.107.**

| Frequency of emission (MHz) | Conducted Limit (dB $\mu$ V) |           |
|-----------------------------|------------------------------|-----------|
|                             | Quasi-peak                   | Average   |
| 0.15 – 0.5                  | 66 to 56*                    | 56 to 46* |
| 0.5 – 5                     | 56                           | 46        |
| 5 – 30                      | 60                           | 50        |

**Table 7-4. Conducted Limits**

\*Decreases with the logarithm of the frequency.

### Test Procedures Used

ANSI C63.4-2014

### Test Settings

#### Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize


#### Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

|   |  |                               |                                   |
|---|--|-------------------------------|-----------------------------------|
| FCC ID: PY7-84558E                      | MEASUREMENT REPORT<br>(CERTIFICATION)  |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2302060006-12.PY7 | Test Dates:<br>02/08/2023 - 03/03/2023 | EUT Type:<br>Portable Handset | Page 14 of 17                     |

## Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




**Figure 7-1. Test Instrument & Measurement Setup**


## Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.107.
3.  $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4.  $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5.  $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

|   |   |                               |                                   |
|---|---|-------------------------------|-----------------------------------|
| FCC ID: PY7-84558E                      | <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                               | Approved by:<br>Technical Manager |
| Test Report S/N:<br>1M2302060006-12.PY7 | Test Dates:<br>02/08/2023 - 03/03/2023        | EUT Type:<br>Portable Handset | Page 15 of 17                     |



Plot 7-3. Line Conducted Plot (L1)



Plot 7-4. Line Conducted Plot (N)

| FCC ID: PY7-84558E                      |  | MEASUREMENT REPORT (CERTIFICATION) |               | Approved by:<br>Technical Manager |
|---|--|------------------------------------|---------------|-----------------------------------|
| Test Report S/N:<br>1M2302060006-12.PY7 | Test Dates:<br>02/08/2023 - 03/03/2023 | EUT Type:<br>Portable Handset      | Page 16 of 17 |                                   |

## 8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Sony Portable Handset FCC ID: PY7-84558E** has been tested to comply with the requirements specified in §15.107 and §15.109 of the FCC rules.

|  |   |                                      |  |
|--|---|--------------------------------------|--|
| <b>FCC ID:</b> PY7-84558E                      | <b>MEASUREMENT REPORT<br/>(CERTIFICATION)</b> |                                      | <b>Approved by:</b><br>Technical Manager |
| <b>Test Report S/N:</b><br>1M2302060006-12.PY7 | <b>Test Dates:</b><br>02/08/2023 - 03/03/2023 | <b>EUT Type:</b><br>Portable Handset | Page 17 of 17                            |