



# FCC EMI TEST REPORT

**FCC ID** : PY7-86211X  
**Equipment** : GSM/WCDMA/LTE/5G Phone with BT, DTS/UNII  
a/b/g/n/ac/ax, GPS, WPC and NFC  
**Brand Name** : Sony  
**Applicant** : Sony Corporation  
1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan  
**Manufacturer** : Sony Corporation  
1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan  
**Standard** : FCC 47 CFR FCC Part 15 Subpart B Class B

The product was received on Mar. 17, 2021 and testing was started from Mar. 22, 2021 and completed on Apr. 01, 2021. We, Sporton International Inc. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

*Louis Wu*

Approved by: Louis Wu

**Sporton International Inc. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)



## Table of Contents

<b>History of this test report.....</b>	<b>3</b>
<b>Summary of Test Result.....</b>	<b>4</b>
<b>1. General Description .....</b>	<b>5</b>
1.1. Product Feature of Equipment Under Test .....	5
1.2. Modification of EUT .....	6
1.3. Test Location .....	6
1.4. Applicable Standards .....	6
<b>2. Test Configuration of Equipment Under Test .....</b>	<b>7</b>
2.1. Test Mode .....	7
2.2. Connection Diagram of Test System .....	8
2.3. Support Unit used in test configuration and system.....	9
2.4. EUT Operation Test Setup .....	9
<b>3. Test Result .....</b>	<b>10</b>
3.1. Test of AC Conducted Emission Measurement .....	10
3.2. Test of Radiated Emission Measurement .....	12
<b>4. List of Measuring Equipment.....</b>	<b>14</b>
<b>5. Uncertainty of Evaluation .....</b>	<b>15</b>
<b>Appendix A. AC Conducted Emission Test Result</b>	
<b>Appendix B. Radiated Emission Test Result</b>	





### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.107	AC Conducted Emission	Pass	Under limit 7.50 dB at 4.214 MHz
3.2	15.109	Radiated Emission	Pass	Under limit 5.25 dB at 59.100 MHz

<b>Declaration of Conformity:</b>
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
<b>Comments and Explanations:</b>
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Dara Chiu

Report Producer: Celery Wei



# 1. General Description

## 1.1. Product Feature of Equipment Under Test

GSM/WCDMA/LTE/5G NR, Bluetooth, DTS/UNII a/b/g/n/ac/ax, NFC, WPC/WPT, and GNSS.

Product Specification subjective to this standard	
<b>Antenna Type</b>	WWAN: Loop Antenna WLAN: <Chain 0>: Loop Antenna <Chain 1>: Monopole Antenna Bluetooth: Loop Antenna GPS/Glonass/Galileo/BDS: Loop Antenna NFC: Loop Antenna WPC/WPT: Loop Antenna

**Remark:** The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

EUT Information List			
HW Version	SW Version	S/N	Performed Test Item
A	0.747	QV7200U76T	Conducted Emission Radiated Emission

Accessory List	
<b>AC Adapter</b>	Model Name : XQZ-UC1
	S/N: 0020W51300024
<b>Earphone</b>	Model Name : MH750
	S/N : N/A
<b>Bluetooth Earphone</b>	Model Name : SBH82D
	S/N : N/A
<b>USB Cable</b>	Model Name : XQZ-UB1
	S/N : N/A
<b>Wireless Charger</b>	Model Name : F7U050
	S/N : 26S10EHC828473

**Note:**

1. Above EUT list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test, and the serial number of each type of accessories is listed in each section of this report.
3. For other wireless features of this EUT, test report will be issued separately.



## 1.2. Modification of EUT

No modifications are made to the EUT during all test items.

## 1.3. Test Location

<b>Test Site</b>	Sporton International Inc. EMC & Wireless Communications Laboratory
<b>Test Site Location</b>	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
<b>Test Site No.</b>	<b>Sporton Site No.</b> CO05-HY

<b>Test Site</b>	Sporton International Inc. Wensan Laboratory
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
<b>Test Site No.</b>	<b>Sporton Site No.</b> 03CH10-HY (TAF Code: 3786)
<b>Remark</b>	The Radiated Emission test item subcontracted to Sporton International Inc. Wensan Laboratory

FCC designation No.: TW1093 and TW1098

## 1.4. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B Class B
- ♦ ANSI C63.4-2014

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



## 2. Test Configuration of Equipment Under Test


### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
<b>AC Conducted Emission</b>	Mode 1 : GSM850 (Middle Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + Camera (Front) + Earphone + Battery + USB Cable (Charging from Adapter) + SIM 1
	Mode 2 : WCDMA Band V (Middle Channel) Idle + Bluetooth Idle + WLAN (5GHz) Idle + Camera (Rear) + Earphone + Battery + USB Cable (Charging from Adapter) + SIM 2
	Mode 3 : LTE Band 5 (Middle Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + MPEG 4 + Earphone + Battery + USB Cable (Charging from Adapter) + SIM 1
	Mode 4 : LTE Band 12 (Middle Channel) Idle + Bluetooth Idle + WLAN (5GHz) Idle + NFC On + Earphone + Battery + USB Cable (Charging from Adapter) + SIM 1
	Mode 5 : LTE Band 13 (Middle Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + GPS Rx + Earphone + Battery + WPC Charging pad (Charging from Adapter) + SIM 1
	Mode 6 : Flight Mode + Earphone + Battery + USB Cable (Data Link with Notebook) + SIM 1
<b>Radiated Emissions</b>	Mode 1 : GSM850 (Middle Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + Camera (Front) + Earphone + Battery + USB Cable (Charging from Adapter) + SIM 1
	Mode 2 : WCDMA Band V (Middle Channel) Idle + Bluetooth Idle + WLAN (5GHz) Idle + Camera (Rear) + Earphone + Battery + USB Cable (Charging from Adapter) + SIM 2
	Mode 3 : LTE Band 5 (Middle Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + MPEG 4 + Earphone + Battery + USB Cable (Charging from Adapter) + SIM 1
	Mode 4 : LTE Band 12 (Middle Channel) Idle + Bluetooth Idle + WLAN (5GHz) Idle + NFC On + Earphone + Battery + WPT Charging with Phone + SIM 1
	Mode 5 : LTE Band 13 (Middle Channel) Idle + Bluetooth Idle + WLAN (2.4GHz) Idle + GPS Rx + Earphone + Battery + WPC Charging pad (Charging from Adapter) + SIM 1
	Mode 6 : Flight Mode + Earphone + Battery + USB Cable (Data Link with Notebook) + SIM 1
<b>Remark:</b>	
<ol style="list-style-type: none"> <li>1. For radiation emission after pre-scanned the cellular band between 30MHz ~ 960MHz (GSM850/WCDMA Band V/LTE Band 5/12/13/17/26/5G NR n5); only the worst case for cellular band test data of this mode was reported.</li> <li>2. Data Link with Notebook means data application transferred mode between EUT and Notebook.</li> <li>3. For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane and WPC Charging Mode) were recorded in this report.</li> </ol>	

## 2.2. Connection Diagram of Test System



Conduction Test Setup									
No.	Wireless Station	Connection Type	Test Mode						
			1	2	3	4	5	6	-
A1	BT Earphone	Bluetooth	X	X	X	X	X	-	-
A2	System Simulator	GSM/WCDMA/LTE	X	X	X	X	X	-	-
A3	GPS Station	GPS	-	-	-	-	X	-	-
A4	AP router	WiFi	X	X	X	X	X	-	-
A5	WPC pad	WPC	-	-	-	-	X	-	-
No.	Power Source	Connection Type	1	2	3	4	5	6	-
B1	AC : 120V/60Hz	AC Power Cable	X	X	X	X	-	-	-
B2	Power from system	Type C Cable	-	-	-	-	-	X	-
B3	Power from WPC	AC Power Cable	-	-	-	-	X	-	-
No.	Setup Peripherals	Connection Type	1	2	3	4	5	6	-
C1	Notebook	USB cable	-	-	-	-	-	X	-
C1-1	iPod	USB Cable to C1	-	-	-	-	-	X	-
C1-2	AP router	RJ-45 Cable to C1	-	-	-	-	-	X	-
C2	Earphone	Earphone jack	X	X	X	X	X	X	-
C3	SD card	SD I/O interface without cable	X	X	X	X	X	X	-

Radiation Test Setup									
No.	Wireless Station	Connection Type	Test Mode						
			1	2	3	4	5	6	-
A1	BT Earphone	Bluetooth	X	X	X	X	X	-	-
A2	System Simulator	GSM/WCDMA/LTE	X	X	X	X	X	-	-
A3	GPS Station	GPS	-	-	-	-	X	-	-
A4	AP router	WiFi	X	X	X	X	X	-	-
A5	WPC pad	WPC	-	-	-	-	X	-	-
A6	Phone	WPT	-	-	-	X	-	-	-
No.	Power Source	Connection Type	1	2	3	4	5	6	-
B1	AC : 120V/60Hz	Type C Cable	X	X	X	X	-	-	-
B2	Power from system	Type C Cable	-	-	-	X	-	X	-
B3	Power from WPC	AC Power Cable	-	-	-	-	X	-	-
No.	Setup Peripherals	Connection Type	1	2	3	4	5	6	-
C1	Notebook	Type C Cable	-	-	-	-	-	X	-
C1-1	iPod	USB Cable to C1	-	-	-	-	-	X	-
C1-2	AP router	RJ 45 Cable to C1	-	-	-	-	-	X	-
C2	Earphone	Earphone jack	X	X	X	X	X	X	-
C3	SD card	SD I/O interface without Cable	X	X	X	X	X	X	-

### 2.3. Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	Pendulum	GSG-54	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
4.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
5.	Notebook	Dell	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
6.	Notebook	Dell	Latitude 5480	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
7.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A
8.	Phone	Sony	XQ-BC52	PY7-07452G	N/A	N/A

### 2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the test. The EUT was synchronized with the BCCH, and had been continuous receiving mode by setting paging reorganization of the system simulator.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test:

1. Data application is transferred between Laptop and EUT via USB cable.
2. Execute "GPS Test" to make the EUT receive continuous signals from GPS station.
3. Execute "Video player" to play MPEG4 files.
4. Turn on camera to capture images.
5. Turn on NFC function.



### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1. Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


##### 3.1.2. Measuring Instruments

Refer a test equipment and calibration data table in this test report.

##### 3.1.3. Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.1.4. Test Setup



### 3.1.5. Test Result of AC Conducted Emission

Please refer to Appendix A.

## 3.2. Test of Radiated Emission Measurement

### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.2.2. Measuring Instruments


Refer a test equipment and calibration data table in this test report.

### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120 kHz/VBW=300 kHz for frequency below 1 GHz; RBW=1 MHz VBW=3 MHz (Peak), RBW=1 MHz/VBW=10 Hz (Average) for frequency above 1 GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.2.5. Test Result of Radiated Emission

Please refer to Appendix B.



### 4. List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Oct. 21, 2020	Mar. 26, 2021~ Mar. 31, 2021	Oct. 20, 2021	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N -06	35413 & 02	30MHz~1GHz	Feb. 10, 2021	Mar. 26, 2021~ Mar. 31, 2021	Feb. 09, 2022	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-02114	1GHz~18GHz	Aug. 04, 2020	Mar. 26, 2021~ Mar. 31, 2021	Aug. 03, 2021	Radiation (03CH10-HY)
Preamplifier	Jet-Power	JAP00101800- 30-10P	160118550004	1GHz~18GHz	Mar. 01, 2021	Mar. 26, 2021~ Mar. 31, 2021	Feb. 28, 2022	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY53470118	10Hz~44GHz	Jan. 15, 2021	Mar. 26, 2021~ Mar. 31, 2021	Jan. 14, 2022	Radiation (03CH10-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Mar. 26, 2021~ Mar. 31, 2021	N/A	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Mar. 26, 2021~ Mar. 31, 2021	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	Mar. 26, 2021~ Mar. 31, 2021	N/A	Radiation (03CH10-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	Mar. 26, 2021~ Mar. 31, 2021	N/A	Radiation (03CH10-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY55420170	20MHz~8.4GHz	May 21, 2020	Mar. 26, 2021~ Mar. 31, 2021	May 20, 2021	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE, MY11693/4PE, MY2855/2	30MHz~1GHz	Nov. 06, 2020	Mar. 26, 2021~ Mar. 31, 2021	Nov. 05, 2021	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / 102	MY11692/4PE, MY11693/4PE, MY2855/2	1GHz~18GHz	Nov. 06, 2020	Mar. 26, 2021~ Mar. 31, 2021	Nov. 05, 2021	Radiation (03CH10-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Mar. 22, 2021~ Apr. 01, 2021	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 30, 2020	Mar. 22, 2021~ Apr. 01, 2021	Nov. 29, 2021	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 18, 2020	Mar. 22, 2021~ Apr. 01, 2021	Nov. 17, 2021	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 01, 2020	Mar. 22, 2021~ Apr. 01, 2021	Nov. 30, 2021	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 16, 2020	Mar. 22, 2021~ Apr. 01, 2021	Nov. 15, 2021	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Mar. 22, 2021~ Apr. 01, 2021	N/A	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 31, 2020	Mar. 22, 2021~ Apr. 01, 2021	Dec. 30, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Feb. 25, 2021	Mar. 22, 2021~ Apr. 01, 2021	Feb. 24, 2022	Conduction (CO05-HY)



## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3
---	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.7
---	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1
---	-----




## Appendix A. AC Conducted Emission Test Results

Test Engineer :	Tom Lee	Temperature :	23~26°C
		Relative Humidity :	40~50%

# EUT Information

Report NO : 0D2213  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum



# Final\_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	29.77	55.88	26.11	L1	OFF	19.7
0.152250	50.41	---	65.88	15.47	L1	OFF	19.7
0.163500	---	29.66	55.28	25.62	L1	OFF	19.7
0.163500	46.53	---	65.28	18.75	L1	OFF	19.7
0.174750	---	26.87	54.73	27.86	L1	OFF	19.7
0.174750	49.94	---	64.73	14.79	L1	OFF	19.7
0.186000	---	31.15	54.21	23.06	L1	OFF	19.7
0.186000	46.64	---	64.21	17.57	L1	OFF	19.7
0.197250	---	27.49	53.73	26.24	L1	OFF	19.7
0.197250	46.08	---	63.73	17.65	L1	OFF	19.7
0.213000	---	28.40	53.09	24.69	L1	OFF	19.7
0.213000	48.43	---	63.09	14.66	L1	OFF	19.7
0.224250	---	23.48	52.66	29.18	L1	OFF	19.7
0.224250	37.07	---	62.66	25.59	L1	OFF	19.7
0.235500	---	33.30	52.25	18.95	L1	OFF	19.7
0.235500	41.88	---	62.25	20.37	L1	OFF	19.7
0.246750	---	21.03	51.87	30.84	L1	OFF	19.7
0.246750	40.61	---	61.87	21.26	L1	OFF	19.7
0.269250	---	24.04	51.14	27.10	L1	OFF	19.7
0.269250	40.99	---	61.14	20.15	L1	OFF	19.7
0.291750	---	23.30	50.47	27.17	L1	OFF	19.7

0.291750	39.63	---	60.47	20.84	L1	OFF	19.7
0.318750	---	21.52	49.74	28.22	L1	OFF	19.7
0.318750	40.83	---	59.74	18.91	L1	OFF	19.7
0.339000	---	32.06	49.23	17.17	L1	OFF	19.7
0.339000	40.35	---	59.23	18.88	L1	OFF	19.7
0.361500	---	25.23	48.69	23.46	L1	OFF	19.7
0.361500	37.38	---	58.69	21.31	L1	OFF	19.7
0.393000	---	20.38	48.00	27.62	L1	OFF	19.7
0.393000	34.82	---	58.00	23.18	L1	OFF	19.7
0.449250	---	17.83	46.89	29.06	L1	OFF	19.8
0.449250	33.04	---	56.89	23.85	L1	OFF	19.8
0.498750	---	32.22	46.02	13.80	L1	OFF	19.8
0.498750	38.13	---	56.02	17.89	L1	OFF	19.8
0.532500	---	23.20	46.00	22.80	L1	OFF	19.9
0.532500	32.52	---	56.00	23.48	L1	OFF	19.9
0.586500	---	22.69	46.00	23.31	L1	OFF	19.9
0.586500	32.01	---	56.00	23.99	L1	OFF	19.9
1.862250	---	19.39	46.00	26.61	L1	OFF	20.2
1.862250	34.40	---	56.00	21.60	L1	OFF	20.2
16.890000	---	17.16	50.00	32.84	L1	OFF	20.0
16.890000	22.58	---	60.00	37.42	L1	OFF	20.0

## EUT Information

Report NO : 0D2213  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	26.52	55.88	29.36	N	OFF	19.7
0.152250	43.77	---	65.88	22.11	N	OFF	19.7
0.161250	---	24.48	55.40	30.92	N	OFF	19.7
0.161250	43.51	---	65.40	21.89	N	OFF	19.7
0.172500	---	28.54	54.84	26.30	N	OFF	19.7
0.172500	50.12	---	64.84	14.72	N	OFF	19.7
0.188250	---	22.60	54.11	31.51	N	OFF	19.7
0.188250	41.02	---	64.11	23.09	N	OFF	19.7
0.231000	---	31.95	52.41	20.46	N	OFF	19.7
0.231000	39.35	---	62.41	23.06	N	OFF	19.7
0.343500	---	30.40	49.12	18.72	N	OFF	19.7
0.343500	36.83	---	59.12	22.29	N	OFF	19.7
0.584250	---	27.06	46.00	18.94	N	OFF	20.0
0.584250	38.20	---	56.00	17.80	N	OFF	20.0
1.704750	---	26.09	46.00	19.91	N	OFF	20.2
1.704750	33.78	---	56.00	22.22	N	OFF	20.2
17.504250	---	17.25	50.00	32.75	N	OFF	20.1
17.504250	23.69	---	60.00	36.31	N	OFF	20.1

# EUT Information

Report NO : 0D2213  
 Test Mode : Mode 2  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154500	---	29.86	55.75	25.89	L1	OFF	19.7
0.154500	44.18	---	65.75	21.57	L1	OFF	19.7
0.498750	---	32.66	46.02	13.36	L1	OFF	19.9
0.498750	36.41	---	56.02	19.61	L1	OFF	19.9
0.588750	---	27.33	46.00	18.67	L1	OFF	20.0
0.588750	33.77	---	56.00	22.23	L1	OFF	20.0
1.023000	---	26.84	46.00	19.16	L1	OFF	20.3
1.023000	30.26	---	56.00	25.74	L1	OFF	20.3
1.970250	---	24.71	46.00	21.29	L1	OFF	20.2
1.970250	28.87	---	56.00	27.13	L1	OFF	20.2
8.169000	---	25.46	50.00	24.54	L1	OFF	20.1
8.169000	26.68	---	60.00	33.32	L1	OFF	20.1

# EUT Information

Report NO : 0D2213  
 Test Mode : Mode 2  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final\_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	28.61	55.88	27.27	N	OFF	19.7
0.152250	40.47	---	65.88	25.41	N	OFF	19.7
0.161250	---	28.04	55.40	27.36	N	OFF	19.7
0.161250	39.94	---	65.40	25.46	N	OFF	19.7
0.174750	---	28.97	54.73	25.76	N	OFF	19.7
0.174750	38.78	---	64.73	25.95	N	OFF	19.7
0.188250	---	25.35	54.11	28.76	N	OFF	19.7
0.188250	33.38	---	64.11	30.73	N	OFF	19.7
0.201750	---	25.44	53.54	28.10	N	OFF	19.7
0.201750	35.73	---	63.54	27.81	N	OFF	19.7
0.233250	---	34.34	52.33	17.99	N	OFF	19.7
0.233250	37.07	---	62.33	25.26	N	OFF	19.7
0.498750	---	32.78	46.02	13.24	N	OFF	19.9
0.498750	36.52	---	56.02	19.50	N	OFF	19.9
0.582000	---	26.62	46.00	19.38	N	OFF	20.0
0.582000	31.46	---	56.00	24.54	N	OFF	20.0
1.025250	---	29.18	46.00	16.82	N	OFF	20.3
1.025250	33.69	---	56.00	22.31	N	OFF	20.3
1.707000	---	28.93	46.00	17.07	N	OFF	20.3
1.707000	34.71	---	56.00	21.29	N	OFF	20.3
9.287250	---	25.62	50.00	24.38	N	OFF	20.2

9.287250	27.06	---	60.00	32.94	N	OFF	20.2
----------	-------	-----	-------	-------	---	-----	------

## EUT Information

Report NO : 0D2213  
 Test Mode : Mode 3  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum



## Final\_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	30.36	55.88	25.52	L1	OFF	19.7
0.152250	44.72	---	65.88	21.16	L1	OFF	19.7
0.161250	---	33.01	55.40	22.39	L1	OFF	19.7
0.161250	45.32	---	65.40	20.08	L1	OFF	19.7
0.174750	---	27.65	54.73	27.08	L1	OFF	19.7
0.174750	42.51	---	64.73	22.22	L1	OFF	19.7
0.188250	---	26.36	54.11	27.75	L1	OFF	19.7
0.188250	37.93	---	64.11	26.18	L1	OFF	19.7
0.204000	---	29.77	53.45	23.68	L1	OFF	19.7
0.204000	40.99	---	63.45	22.46	L1	OFF	19.7
0.498750	---	32.87	46.02	13.15	L1	OFF	19.9
0.498750	37.11	---	56.02	18.91	L1	OFF	19.9
0.570750	---	29.52	46.00	16.48	L1	OFF	19.9
0.570750	38.61	---	56.00	17.39	L1	OFF	19.9
0.602250	---	27.00	46.00	19.00	L1	OFF	20.0
0.602250	32.61	---	56.00	23.39	L1	OFF	20.0
1.023000	---	29.87	46.00	16.13	L1	OFF	20.3
1.023000	34.53	---	56.00	21.47	L1	OFF	20.3
1.857750	---	25.10	46.00	20.90	L1	OFF	20.2
1.857750	32.45	---	56.00	23.55	L1	OFF	20.2
11.908500	---	25.44	50.00	24.56	L1	OFF	20.3

11.908500	26.83	---	60.00	33.17	L1	OFF	20.3
-----------	-------	-----	-------	-------	----	-----	------

# EUT Information

Report NO : 0D2213  
 Test Mode : Mode 3  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final\_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	31.89	55.88	23.99	N	OFF	19.7
0.152250	45.53	---	65.88	20.35	N	OFF	19.7
0.161250	---	27.87	55.40	27.53	N	OFF	19.7
0.161250	43.65	---	65.40	21.75	N	OFF	19.7
0.170250	---	28.32	54.95	26.63	N	OFF	19.7
0.170250	43.28	---	64.95	21.67	N	OFF	19.7
0.183750	---	28.57	54.31	25.74	N	OFF	19.7
0.183750	41.14	---	64.31	23.17	N	OFF	19.7
0.199500	---	25.52	53.63	28.11	N	OFF	19.7
0.199500	36.91	---	63.63	26.72	N	OFF	19.7
0.215250	---	28.13	53.00	24.87	N	OFF	19.7
0.215250	38.20	---	63.00	24.80	N	OFF	19.7
0.233250	---	34.48	52.33	17.85	N	OFF	19.7
0.233250	37.22	---	62.33	25.11	N	OFF	19.7
0.501000	---	33.33	46.00	12.67	N	OFF	19.9
0.501000	36.99	---	56.00	19.01	N	OFF	19.9
0.568500	---	30.08	46.00	15.92	N	OFF	20.0
0.568500	37.15	---	56.00	18.85	N	OFF	20.0
1.023000	---	30.10	46.00	15.90	N	OFF	20.3
1.023000	35.06	---	56.00	20.94	N	OFF	20.3
1.929750	---	25.43	46.00	20.57	N	OFF	20.3

<b>1.929750</b>	<b>33.40</b>	<b>---</b>	<b>56.00</b>	<b>22.60</b>	<b>N</b>	<b>OFF</b>	<b>20.3</b>
<b>12.207750</b>	<b>---</b>	<b>25.50</b>	<b>50.00</b>	<b>24.50</b>	<b>N</b>	<b>OFF</b>	<b>20.3</b>
<b>12.207750</b>	<b>27.02</b>	<b>---</b>	<b>60.00</b>	<b>32.98</b>	<b>N</b>	<b>OFF</b>	<b>20.3</b>

# EUT Information

Report NO : 0D2213  
 Test Mode : Mode 4  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	28.56	55.88	27.32	L1	OFF	19.7
0.152250	38.63	---	65.88	27.25	L1	OFF	19.7
0.234960	---	32.30	52.27	19.97	L1	OFF	19.7
0.234960	36.16	---	62.27	26.11	L1	OFF	19.7
0.569760	---	31.87	46.00	14.13	L1	OFF	19.9
0.569760	38.52	---	56.00	17.48	L1	OFF	19.9
1.029120	---	29.04	46.00	16.96	L1	OFF	20.3
1.029120	32.75	---	56.00	23.25	L1	OFF	20.3
3.095250	---	26.53	46.00	19.47	L1	OFF	20.1
3.095250	32.13	---	56.00	23.87	L1	OFF	20.1
13.560000	---	40.04	50.00	9.96	L1	OFF	20.3
13.560000	51.31	---	60.00	8.69	L1	OFF	20.3
24.607680	---	26.02	50.00	23.98	L1	OFF	20.7
24.607680	28.05	---	60.00	31.95	L1	OFF	20.7

# EUT Information

Report NO : 0D2213  
 Test Mode : Mode 4  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152160	---	28.96	55.88	26.92	N	OFF	19.7
0.152160	38.72	---	65.88	27.16	N	OFF	19.7
0.343140	---	34.65	49.13	14.48	N	OFF	19.8
0.343140	38.65	---	59.13	20.48	N	OFF	19.8
0.496500	---	29.96	46.06	16.10	N	OFF	19.9
0.496500	33.59	---	56.06	22.47	N	OFF	19.9
0.591000	---	29.46	46.00	16.54	N	OFF	20.0
0.591000	36.32	---	56.00	19.68	N	OFF	20.0
2.509440	---	26.07	46.00	19.93	N	OFF	20.2
2.509440	30.91	---	56.00	25.09	N	OFF	20.2
6.965250	---	26.09	50.00	23.91	N	OFF	20.2
6.965250	27.66	---	60.00	32.34	N	OFF	20.2
13.560000	---	39.80	50.00	10.20	N	OFF	20.4
13.560000	51.00	---	60.00	9.00	N	OFF	20.4

# EUT Information

Report NO : 0D2213  
 Test Mode : Mode 5  
 Test Voltage : Power From WPC  
 Phase : Line

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	38.40	55.88	17.48	L1	OFF	19.7
0.152250	55.15	---	65.88	10.73	L1	OFF	19.7
0.159000	---	31.48	55.52	24.04	L1	OFF	19.7
0.159000	50.37	---	65.52	15.15	L1	OFF	19.7
0.235500	---	33.71	52.25	18.54	L1	OFF	19.7
0.235500	40.40	---	62.25	21.85	L1	OFF	19.7
0.496500	---	32.09	46.06	13.97	L1	OFF	19.9
0.496500	36.31	---	56.06	19.75	L1	OFF	19.9
0.568500	---	31.40	46.00	14.60	L1	OFF	19.9
0.568500	35.58	---	56.00	20.42	L1	OFF	19.9
3.448500	---	38.10	46.00	7.90	L1	OFF	20.1
3.448500	38.63	---	56.00	17.37	L1	OFF	20.1
3.702750	---	38.17	46.00	7.83	L1	OFF	20.1
3.702750	38.64	---	56.00	17.36	L1	OFF	20.1
3.959250	---	38.16	46.00	7.84	L1	OFF	20.1
3.959250	38.64	---	56.00	17.36	L1	OFF	20.1
28.477500	---	36.34	50.00	13.66	L1	OFF	20.8
28.477500	40.32	---	60.00	19.68	L1	OFF	20.8

# EUT Information

Report NO : 0D2213  
 Test Mode : Mode 5  
 Test Voltage : Power From WPC  
 Phase : Neutral

Full Spectrum




## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	37.36	55.88	18.52	N	OFF	19.7
0.152250	54.08	---	65.88	11.80	N	OFF	19.7
0.159000	---	31.18	55.52	24.34	N	OFF	19.7
0.159000	48.84	---	65.52	16.68	N	OFF	19.7
0.231000	---	34.40	52.41	18.01	N	OFF	19.7
0.231000	41.76	---	62.41	20.65	N	OFF	19.7
0.501000	---	34.64	46.00	11.36	N	OFF	19.9
0.501000	38.04	---	56.00	17.96	N	OFF	19.9
0.568500	---	30.96	46.00	15.04	N	OFF	20.0
0.568500	35.21	---	56.00	20.79	N	OFF	20.0
2.427000	---	37.24	46.00	8.76	N	OFF	20.2
2.427000	37.98	---	56.00	18.02	N	OFF	20.2
3.957000	---	37.77	46.00	8.23	N	OFF	20.1
3.957000	38.24	---	56.00	17.76	N	OFF	20.1
4.213500	---	38.50	46.00	7.50	N	OFF	20.1
4.213500	38.88	---	56.00	17.12	N	OFF	20.1
27.838500	---	39.25	50.00	10.75	N	OFF	20.9
27.838500	41.29	---	60.00	18.71	N	OFF	20.9

# EUT Information

Report NO : 0D2213  
 Test Mode : Mode 6  
 Test Voltage : Power From System  
 Phase : Line

Full Spectrum



## Final\_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	39.00	55.88	16.88	L1	OFF	19.7
0.152250	56.05	---	65.88	9.83	L1	OFF	19.7
0.159000	---	39.22	55.52	16.30	L1	OFF	19.7
0.159000	55.56	---	65.52	9.96	L1	OFF	19.7
0.168000	---	36.75	55.06	18.31	L1	OFF	19.7
0.168000	54.19	---	65.06	10.87	L1	OFF	19.7
0.179250	---	35.96	54.52	18.56	L1	OFF	19.7
0.179250	52.61	---	64.52	11.91	L1	OFF	19.7
0.188250	---	33.94	54.11	20.17	L1	OFF	19.7
0.188250	49.48	---	64.11	14.63	L1	OFF	19.7
0.201750	---	30.98	53.54	22.56	L1	OFF	19.7
0.201750	47.06	---	63.54	16.48	L1	OFF	19.7
0.213000	---	31.38	53.09	21.71	L1	OFF	19.7
0.213000	45.53	---	63.09	17.56	L1	OFF	19.7
0.231000	---	34.33	52.41	18.08	L1	OFF	19.7
0.231000	43.44	---	62.41	18.97	L1	OFF	19.7
0.246750	---	29.00	51.87	22.87	L1	OFF	19.7
0.246750	41.46	---	61.87	20.41	L1	OFF	19.7
0.312000	---	27.69	49.92	22.23	L1	OFF	19.7
0.312000	37.58	---	59.92	22.34	L1	OFF	19.7
0.498750	---	33.98	46.02	12.04	L1	OFF	19.8

0.498750	39.03	---	56.02	16.99	L1	OFF	19.8
1.250250	---	32.25	46.00	13.75	L1	OFF	20.2
1.250250	37.94	---	56.00	18.06	L1	OFF	20.2
1.315500	---	33.50	46.00	12.50	L1	OFF	20.2
1.315500	38.92	---	56.00	17.08	L1	OFF	20.2
1.380750	---	34.88	46.00	11.12	L1	OFF	20.2
1.380750	40.16	---	56.00	15.84	L1	OFF	20.2
1.448250	---	34.71	46.00	11.29	L1	OFF	20.2
1.448250	40.25	---	56.00	15.75	L1	OFF	20.2
1.513500	---	34.31	46.00	11.69	L1	OFF	20.2
1.513500	39.56	---	56.00	16.44	L1	OFF	20.2
1.578750	---	33.27	46.00	12.73	L1	OFF	20.2
1.578750	38.53	---	56.00	17.47	L1	OFF	20.2
1.646250	---	31.65	46.00	14.35	L1	OFF	20.2
1.646250	37.37	---	56.00	18.63	L1	OFF	20.2
1.711500	---	30.96	46.00	15.04	L1	OFF	20.2
1.711500	36.21	---	56.00	19.79	L1	OFF	20.2
1.776750	---	29.68	46.00	16.32	L1	OFF	20.2
1.776750	35.19	---	56.00	20.81	L1	OFF	20.2
1.842000	---	28.96	46.00	17.04	L1	OFF	20.2
1.842000	34.36	---	56.00	21.64	L1	OFF	20.2
13.812000	---	23.23	50.00	26.77	L1	OFF	20.0
13.812000	28.10	---	60.00	31.90	L1	OFF	20.0

# EUT Information

Report NO : 0D2213  
 Test Mode : Mode 6  
 Test Voltage : Power From System  
 Phase : Neutral

Full Spectrum



## Final\_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	36.55	55.88	19.33	N	OFF	19.7
0.152250	53.90	---	65.88	11.98	N	OFF	19.7
0.161250	---	35.94	55.40	19.46	N	OFF	19.7
0.161250	51.54	---	65.40	13.86	N	OFF	19.7
0.172500	---	33.52	54.84	21.32	N	OFF	19.7
0.172500	52.69	---	64.84	12.15	N	OFF	19.7
0.183750	---	32.51	54.31	21.80	N	OFF	19.7
0.183750	47.62	---	64.31	16.69	N	OFF	19.7
0.199500	---	26.92	53.63	26.71	N	OFF	19.7
0.199500	43.86	---	63.63	19.77	N	OFF	19.7
0.210750	---	28.77	53.18	24.41	N	OFF	19.7
0.210750	43.66	---	63.18	19.52	N	OFF	19.7
0.222000	---	29.03	52.74	23.71	N	OFF	19.7
0.222000	43.79	---	62.74	18.95	N	OFF	19.7
0.235500	---	34.51	52.25	17.74	N	OFF	19.7
0.235500	41.06	---	62.25	21.19	N	OFF	19.7
0.249000	---	24.42	51.79	27.37	N	OFF	19.7
0.249000	37.71	---	61.79	24.08	N	OFF	19.7
0.267000	---	24.93	51.21	26.28	N	OFF	19.7
0.267000	36.66	---	61.21	24.55	N	OFF	19.7
0.503250	---	33.47	46.00	12.53	N	OFF	19.9

0.503250	37.53	---	56.00	18.47	N	OFF	19.9
0.564000	---	29.34	46.00	16.66	N	OFF	19.9
0.564000	34.94	---	56.00	21.06	N	OFF	19.9
1.142250	---	27.99	46.00	18.01	N	OFF	20.2
1.142250	34.11	---	56.00	21.89	N	OFF	20.2
1.232250	---	30.65	46.00	15.35	N	OFF	20.2
1.232250	35.88	---	56.00	20.12	N	OFF	20.2
1.299750	---	33.04	46.00	12.96	N	OFF	20.2
1.299750	38.53	---	56.00	17.47	N	OFF	20.2
1.380750	---	34.86	46.00	11.14	N	OFF	20.2
1.380750	40.13	---	56.00	15.87	N	OFF	20.2
1.466250	---	34.76	46.00	11.24	N	OFF	20.2
1.466250	40.19	---	56.00	15.81	N	OFF	20.2
1.574250	---	33.27	46.00	12.73	N	OFF	20.2
1.574250	38.68	---	56.00	17.32	N	OFF	20.2
1.682250	---	31.42	46.00	14.58	N	OFF	20.2
1.682250	36.56	---	56.00	19.44	N	OFF	20.2
1.785750	---	29.67	46.00	16.33	N	OFF	20.2
1.785750	35.08	---	56.00	20.92	N	OFF	20.2
1.914000	---	28.42	46.00	17.58	N	OFF	20.2
1.914000	34.51	---	56.00	21.49	N	OFF	20.2
13.506000	---	22.75	50.00	27.25	N	OFF	20.0
13.506000	27.37	---	60.00	32.63	N	OFF	20.0



## Appendix B. Radiated Emission Test Result

Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 HORIZONTAL  
 Project : OD2213  
 Power : 120Vac/60Hz  
 Mode : 1

	Freq	Level	Over Limit	Limit	Antenna Line Factor	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	41.64	20.82	-19.18	40.00	18.69	34.03	0.74	32.64	---	---	Peak
2	173.56	28.52	-14.98	43.50	15.33	44.23	1.48	32.52	---	---	Peak
3	709.00	30.55	-15.45	46.00	26.93	33.12	2.98	32.48	---	---	Peak
4	776.90	30.10	-15.90	46.00	28.61	30.72	3.15	32.38	---	---	Peak
5	838.98	30.49	-15.51	46.00	29.09	30.26	3.26	32.12	---	---	Peak
6 *	881.40	67.77			28.90	67.40	3.33	31.86	---	---	Peak
7	959.26	32.86	-13.14	46.00	31.05	29.44	3.50	31.13	100	0	Peak
8	2898.00	42.56	-31.44	74.00	28.10	66.18	6.40	58.12	---	---	Peak
9	4504.00	43.09	-30.91	74.00	30.41	62.85	8.22	58.39	---	---	Peak
10	6922.00	47.52	-26.48	74.00	34.94	61.29	10.93	59.64	---	---	Peak
11	8684.00	48.62	-25.38	74.00	37.44	59.15	11.87	59.84	---	---	Peak
12	10508.00	49.92	-24.08	74.00	39.50	56.99	13.12	59.69	---	---	Peak
13	11470.00	50.15	-23.85	74.00	39.67	55.22	13.88	58.62	100	0	Peak
14	16950.00	49.45	-24.55	74.00	39.55	50.81	17.94	58.85	---	---	Peak
15	26052.00	49.76	-24.24	74.00	38.80	40.86	23.47	53.37	---	---	Peak



Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Vertical
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 VERTICAL  
 Project : 0D2213  
 Power : 120Vac/60Hz  
 Mode : 1

	Freq	Level	Over Limit	Limit	Antenna Line Factor	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	41.64	31.88	-8.12	40.00	18.69	45.09	0.74	32.64	100	0	Peak
2	85.29	31.00	-9.00	40.00	14.00	48.55	1.05	32.60	---	---	Peak
3	94.99	29.50	-14.00	43.50	15.37	45.60	1.12	32.59	---	---	Peak
4	144.46	28.01	-15.49	43.50	17.14	42.07	1.35	32.55	---	---	Peak
5	703.18	31.03	-14.97	46.00	26.82	33.73	2.97	32.49	---	---	Peak
6 *	881.40	64.72			28.90	64.35	3.33	31.86	---	---	Peak
7	954.41	32.67	-13.33	46.00	30.89	29.47	3.49	31.18	---	---	Peak
8	2668.00	42.88	-31.12	74.00	27.74	67.15	6.07	58.08	---	---	Peak
9	4752.00	42.83	-31.17	74.00	31.00	61.77	8.51	58.45	---	---	Peak
10	6854.00	46.30	-27.70	74.00	34.53	60.68	10.71	59.62	---	---	Peak
11	8596.00	48.26	-25.74	74.00	37.19	58.92	11.86	59.71	---	---	Peak
12	10874.00	49.17	-24.83	74.00	40.02	54.69	13.41	58.95	---	---	Peak
13	11300.00	49.30	-24.70	74.00	39.40	54.80	13.75	58.65	---	---	Peak
14	17590.00	50.18	-23.82	74.00	42.40	47.32	18.44	57.98	100	0	Peak
15	28392.00	49.95	-24.05	74.00	39.81	40.05	24.36	54.27	---	---	Peak



Mode :	Mode 2	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 HORIZONTAL  
 Project : 0D2213  
 Power : 120Vac/60Hz  
 Mode : 2

	Freq	Level	Over Limit	Limit	Antenna Line Factor	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	30.97	21.36	-18.64	40.00	23.84	29.52	0.64	32.64	---	---	Peak
2	177.44	28.54	-14.96	43.50	15.12	44.44	1.50	32.52	---	---	Peak
3	735.19	29.46	-16.54	46.00	28.18	30.68	3.04	32.44	---	---	Peak
4	821.52	30.05	-15.95	46.00	28.32	30.71	3.24	32.22	---	---	Peak
5	853.53	30.96	-15.04	46.00	29.27	30.44	3.28	32.03	---	---	Peak
6 *	881.60	62.17			28.90	61.80	3.33	31.86	---	---	Peak
7	958.29	33.74	-12.26	46.00	31.02	30.37	3.49	31.14	100	0	Peak
8	2832.00	41.73	-32.27	74.00	27.96	65.57	6.31	58.11	---	---	Peak
9	4532.00	41.91	-32.09	74.00	30.46	61.63	8.22	58.40	---	---	Peak
10	6916.00	45.80	-28.20	74.00	34.93	59.60	10.91	59.64	---	---	Peak
11	8606.00	48.04	-25.96	74.00	37.21	58.70	11.86	59.73	---	---	Peak
12	10686.00	48.52	-25.48	74.00	39.50	55.09	13.26	59.33	---	---	Peak
13	11300.00	49.20	-24.80	74.00	39.40	54.70	13.75	58.65	---	---	Peak
14	17705.00	49.58	-24.42	74.00	43.47	45.69	18.53	58.11	---	---	Peak
15	25572.00	49.69	-24.31	74.00	38.84	41.02	23.23	53.40	100	0	Peak



Mode :	Mode 2	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Vertical
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 VERTICAL  
 Project : 0D2213  
 Power : 120Vac/60Hz  
 Mode : 2

	Freq	Level	Over Limit	Limit	Antenna Line	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	41.64	31.11	-8.89	40.00	18.69	44.32	0.74	32.64	100	0	Peak
2	85.29	27.10	-12.90	40.00	14.00	44.65	1.05	32.60	---	---	Peak
3	95.96	27.14	-16.36	43.50	15.53	43.08	1.12	32.59	---	---	Peak
4	142.52	27.04	-16.46	43.50	17.29	40.96	1.34	32.55	---	---	Peak
5	846.74	31.06	-14.94	46.00	29.22	30.64	3.27	32.07	---	---	Peak
6 *	881.60	60.00			28.90	59.63	3.33	31.86	---	---	Peak
7	959.26	32.73	-13.27	46.00	31.05	29.31	3.50	31.13	---	---	Peak
8	2790.00	42.17	-31.83	74.00	27.90	66.11	6.26	58.10	---	---	Peak
9	4752.00	41.88	-32.12	74.00	31.00	60.82	8.51	58.45	---	---	Peak
10	6914.00	45.30	-28.70	74.00	34.93	59.11	10.90	59.64	---	---	Peak
11	8812.00	47.61	-26.39	74.00	37.68	58.03	11.92	60.02	---	---	Peak
12	10600.00	49.66	-24.34	74.00	39.50	56.48	13.19	59.51	---	---	Peak
13	11456.00	49.68	-24.32	74.00	39.66	54.78	13.87	58.63	100	0	Peak
14	14925.00	49.44	-24.56	74.00	40.80	50.65	16.61	58.62	---	---	Peak
15	27240.00	48.28	-25.72	74.00	39.20	38.37	23.75	53.04	---	---	Peak



Mode :	Mode 3	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 HORIZONTAL  
 Project : OD2213  
 Power : 120Vac/60Hz  
 Mode : 3

	Freq	Level	Over Limit	Limit	Antenna Line Factor	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	34.85	22.13	-17.87	40.00	22.17	31.93	0.67	32.64	---	---	Peak
2	167.74	26.95	-16.55	43.50	15.80	42.22	1.46	32.53	---	---	Peak
3	175.50	29.93	-13.57	43.50	15.18	45.78	1.49	32.52	100	0	Peak
4	707.06	32.07	-13.93	46.00	26.89	34.68	2.98	32.48	---	---	Peak
5	838.98	31.03	-14.97	46.00	29.09	30.80	3.26	32.12	---	---	Peak
6 *	881.50	52.54			28.90	52.17	3.33	31.86	---	---	Peak
7	942.77	32.18	-13.82	46.00	30.31	29.72	3.46	31.31	---	---	Peak
8	2522.00	41.07	-32.93	74.00	27.24	66.03	5.85	58.05	---	---	Peak
9	4628.00	42.14	-31.86	74.00	30.81	61.46	8.29	58.42	---	---	Peak
10	6658.00	45.09	-28.91	74.00	34.22	59.89	10.53	59.55	---	---	Peak
11	8714.00	47.64	-26.36	74.00	37.53	58.12	11.87	59.88	---	---	Peak
12	10694.00	49.83	-24.17	74.00	39.50	56.37	13.27	59.31	100	0	Peak
13	11514.00	49.74	-24.26	74.00	39.67	54.80	13.92	58.65	---	---	Peak
14	17415.00	48.90	-25.10	74.00	40.90	47.76	18.30	58.06	---	---	Peak
15	28860.00	49.38	-24.62	74.00	40.24	39.17	24.51	54.54	---	---	Peak



Mode :	Mode 3	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Vertical
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 VERTICAL  
 Project : OD2213  
 Power : 120Vac/60Hz  
 Mode : 3

	Freq	Level	Over Limit	Limit	Antenna Line Factor	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	41.64	33.04	-6.96	40.00	18.69	46.25	0.74	32.64	100	0	Peak
2	86.26	31.82	-8.18	40.00	14.12	49.24	1.06	32.60	---	---	Peak
3	96.93	28.84	-14.66	43.50	15.63	44.67	1.13	32.59	---	---	Peak
4	145.43	29.63	-13.87	43.50	17.12	43.70	1.36	32.55	---	---	Peak
5	855.47	30.94	-15.06	46.00	29.28	30.40	3.28	32.02	---	---	Peak
6 *	881.50	49.36				28.90	48.99	3.33	31.86	---	Peak
7	959.26	33.23	-12.77	46.00	31.05	29.81	3.50	31.13	---	---	Peak
8	2838.00	41.90	-32.10	74.00	27.98	65.71	6.32	58.11	---	---	Peak
9	4562.00	42.78	-31.22	74.00	30.55	62.40	8.23	58.40	---	---	Peak
10	6718.00	44.90	-29.10	74.00	34.26	59.68	10.53	59.57	---	---	Peak
11	8298.00	48.14	-25.86	74.00	36.31	59.65	11.64	59.46	---	---	Peak
12	10690.00	49.43	-24.57	74.00	39.50	55.98	13.27	59.32	100	0	Peak
13	11528.00	49.33	-24.67	74.00	39.64	54.45	13.93	58.69	---	---	Peak
14	17580.00	49.01	-24.99	74.00	42.30	46.25	18.43	57.97	---	---	Peak
15	28788.00	49.41	-24.59	74.00	40.22	39.23	24.48	54.52	---	---	Peak



Mode :	Mode 4	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#4 is system simulator signal which can be ignored.		




Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 HORIZONTAL  
 Project : OD2213  
 Power : 120Vac/60Hz  
 Mode : 4

	Freq	Level	Over Limit	Limit	Antenna Line Factor	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	30.97	21.91	-18.09	40.00	23.84	30.07	0.64	32.64	---	---	Peak
2	147.37	19.69	-23.81	43.50	17.14	33.73	1.37	32.55	---	---	Peak
3	695.42	27.85	-18.15	46.00	26.72	30.67	2.95	32.49	---	---	Peak
4 *	737.50	54.03			28.28	55.14	3.05	32.44	---	---	Peak
5	860.32	31.24	-14.76	46.00	29.24	30.70	3.29	31.99	---	---	Peak
6	909.79	31.75	-14.25	46.00	28.96	31.05	3.39	31.65	---	---	Peak
7	956.35	32.34	-13.66	46.00	30.96	29.05	3.49	31.16	100	0	Peak
8	2162.00	42.04	-31.96	74.00	27.67	67.19	5.41	58.23	---	---	Peak
9	4714.00	42.56	-31.44	74.00	31.07	61.49	8.44	58.44	---	---	Peak
10	6960.00	45.79	-28.21	74.00	35.04	59.36	11.05	59.66	---	---	Peak
11	8988.00	48.39	-25.61	74.00	37.48	58.73	12.44	60.26	---	---	Peak
12	10968.00	49.65	-24.35	74.00	40.03	54.90	13.48	58.76	---	---	Peak
13	11090.00	50.16	-23.84	74.00	39.64	55.62	13.58	58.68	---	---	Peak
14	14265.00	50.01	-23.99	74.00	41.30	50.44	16.25	57.98	---	---	Peak
15	29640.00	50.59	-23.41	74.00	40.39	40.17	24.94	54.91	100	0	Peak



Mode :	Mode 4	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Vertical
Remark :	#4 is system simulator signal which can be ignored.		




Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 VERTICAL  
 Project : 0D2213  
 Power : 120Vac/60Hz  
 Mode : 4

	Freq	Level	Over Limit	Limit	Antenna Line	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	30.00	21.16	-18.84	40.00	24.38	28.80	0.63	32.65	---	---	Peak
2	623.64	27.51	-18.49	46.00	26.16	31.08	2.79	32.52	---	---	Peak
3	717.73	28.71	-17.29	46.00	27.23	30.95	3.00	32.47	---	---	Peak
4 *	737.50	53.19			28.28	54.30	3.05	32.44	---	---	Peak
5	791.45	29.91	-16.09	46.00	28.56	30.52	3.19	32.36	---	---	Peak
6	866.14	31.14	-14.86	46.00	29.14	30.65	3.30	31.95	---	---	Peak
7	953.44	33.47	-12.53	46.00	30.83	30.34	3.49	31.19	100	0	Peak
8	2324.00	42.20	-31.80	74.00	27.65	67.10	5.59	58.14	---	---	Peak
9	4666.00	42.04	-31.96	74.00	30.96	61.15	8.36	58.43	---	---	Peak
10	6984.00	45.99	-28.01	74.00	35.14	59.38	11.13	59.66	---	---	Peak
11	8970.00	47.86	-26.14	74.00	37.44	58.27	12.39	60.24	---	---	Peak
12	10744.00	49.94	-24.06	74.00	39.63	56.21	13.31	59.21	---	---	Peak
13	11346.00	50.48	-23.52	74.00	39.49	55.85	13.78	58.64	100	0	Peak
14	13595.00	50.08	-23.92	74.00	40.09	51.85	15.74	57.60	---	---	Peak
15	29856.00	49.64	-24.36	74.00	40.30	39.35	25.07	55.08	---	---	Peak



Mode :	Mode 5	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#5 is system simulator signal which can be ignored.		




Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 HORIZONTAL  
 Project : 0D2213  
 Power : 120Vac/60Hz  
 Mode : 5

	Freq	Level	Over Limit	Limit	Antenna Line Factor	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	59.10	24.52	-15.48	40.00	11.93	44.34	0.87	32.62	---	---	Peak
2	159.01	25.25	-18.25	43.50	16.59	39.77	1.43	32.54	---	---	Peak
3	308.39	27.57	-18.43	46.00	19.42	38.60	1.97	32.42	---	---	Peak
4	417.03	28.87	-17.13	46.00	22.62	36.36	2.28	32.39	---	---	Peak
5	751.00	43.18			28.57	43.95	3.08	32.42	---	---	Peak
6	874.87	30.99	-15.01	46.00	29.07	30.50	3.32	31.90	---	---	Peak
7	953.44	32.60	-13.40	46.00	30.83	29.47	3.49	31.19	100	0	Peak
8	2414.00	41.48	-32.52	74.00	27.37	66.51	5.69	58.09	---	---	Peak
9	4052.00	43.42	-30.58	74.00	29.50	64.45	8.01	58.54	---	---	Peak
10	6330.00	45.72	-28.28	74.00	33.12	61.81	9.94	59.15	---	---	Peak
11	8852.00	48.06	-25.94	74.00	37.60	58.49	12.04	60.07	---	---	Peak
12	10986.00	50.43	-23.57	74.00	40.01	55.64	13.50	58.72	100	0	Peak
13	11036.00	49.44	-24.56	74.00	39.86	54.72	13.54	58.68	---	---	Peak
14	17130.00	49.67	-24.33	74.00	39.53	50.72	18.08	58.66	---	---	Peak
15	23952.00	49.94	-24.06	74.00	39.12	41.91	22.41	53.50	---	---	Peak



Mode :	Mode 5	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Vertical
Remark :	#5 is system simulator signal which can be ignored.		




Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 VERTICAL  
 Project : 0D2213  
 Power : 120Vac/60Hz  
 Mode : 5

	Freq	Level	Over Limit	Limit	Antenna Line Factor	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	39.70	34.58	-5.42	40.00	19.64	46.86	0.72	32.64	---	---	Peak
2	59.10	34.75	-5.25	40.00	11.93	54.57	0.87	32.62	100	0	Peak
3	120.21	29.96	-13.54	43.50	17.42	43.89	1.22	32.57	---	---	Peak
4	714.82	30.17	-15.83	46.00	27.09	32.55	3.00	32.47	---	---	Peak
5 *	751.00	46.34			28.57	47.11	3.08	32.42	---	---	Peak
6	910.76	33.27	-12.73	46.00	28.98	32.54	3.39	31.64	---	---	Peak
7	958.29	32.94	-13.06	46.00	31.02	29.57	3.49	31.14	---	---	Peak
8	1566.00	40.35	-33.65	74.00	24.94	69.24	4.54	58.37	---	---	Peak
9	3974.00	42.46	-31.54	74.00	29.45	63.62	7.95	58.56	---	---	Peak
10	6538.00	46.50	-27.50	74.00	34.18	61.43	10.39	59.50	---	---	Peak
11	8316.00	48.06	-25.94	74.00	36.30	59.60	11.63	59.47	---	---	Peak
12	10884.00	49.32	-24.68	74.00	40.05	54.78	13.42	58.93	---	---	Peak
13	11040.00	50.56	-23.44	74.00	39.84	55.86	13.54	58.68	100	0	Peak
14	17280.00	49.73	-24.27	74.00	39.84	50.03	18.20	58.34	---	---	Peak
15	28656.00	49.40	-24.60	74.00	40.09	39.33	24.44	54.46	---	---	Peak



Mode :	Mode 6	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Horizontal




Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 HORIZONTAL  
 Project : OD2213  
 Power : From System  
 Mode : 6

	Freq	Level	Over Limit	Limit	Antenna Line Factor	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	30.00	21.90	-18.10	40.00	24.38	29.54	0.63	32.65	---	---	Peak
2	167.74	28.20	-15.30	43.50	15.80	43.47	1.46	32.53	---	---	Peak
3	375.32	34.11	-11.89	46.00	21.00	43.33	2.17	32.39	---	---	Peak
4	412.18	33.12	-12.88	46.00	22.42	40.82	2.27	32.39	---	---	Peak
5	480.08	38.65	-7.35	46.00	23.55	45.08	2.46	32.44	100	0	Peak
6	955.38	32.82	-13.18	46.00	30.93	29.57	3.49	31.17	---	---	Peak
7	2182.00	41.68	-32.32	74.00	27.79	66.67	5.44	58.22	---	---	Peak
8	4304.00	42.62	-31.38	74.00	29.92	63.04	8.12	58.46	---	---	Peak
9	5936.00	45.05	-28.95	74.00	32.37	61.79	9.36	58.47	---	---	Peak
10	8060.00	48.01	-25.99	74.00	37.00	58.82	11.51	59.32	---	---	Peak
11	10456.00	50.62	-23.38	74.00	39.50	57.82	13.08	59.78	100	0	Peak
12	11024.00	50.48	-23.52	74.00	39.90	55.74	13.53	58.69	---	---	Peak
13	15790.00	50.28	-23.72	74.00	37.04	54.12	17.09	57.97	---	---	Peak
14	29388.00	49.66	-24.34	74.00	40.50	39.33	24.79	54.96	---	---	Peak



Mode :	Mode 6	Temperature :	22~24°C
Test Engineer :	Donny Tang	Relative Humidity :	52~59%
Test Distance :	3m	Polarization :	Vertical



Site : 03CH10-HY  
 Condition : FCC CLASS-B 3m SHF HORN BBHA9170009 VERTICAL  
 Project : 0D2213  
 Power : From System  
 Mode : 6

	Freq	Level	Over Limit	Limit	Antenna Line	Read Level	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dB/m	dBuV	dB	dB	cm	deg	
1	78.50	30.02	-9.98	40.00	13.15	48.47	1.01	32.61	---	---	Peak
2	170.65	27.04	-16.46	43.50	15.59	42.51	1.47	32.53	---	---	Peak
3	480.08	38.83	-7.17	46.00	23.55	45.26	2.46	32.44	100	0	Peak
4	532.46	29.95	-16.05	46.00	23.91	35.93	2.59	32.48	---	---	Peak
5	883.60	31.16	-14.84	46.00	28.88	30.79	3.34	31.85	---	---	Peak
6	957.32	32.25	-13.75	46.00	30.99	28.92	3.49	31.15	---	---	Peak
7	2404.00	42.83	-31.17	74.00	27.39	67.86	5.68	58.10	---	---	Peak
8	4264.00	42.37	-31.63	74.00	29.83	62.92	8.09	58.47	---	---	Peak
9	6344.00	46.01	-27.99	74.00	33.18	62.04	9.97	59.18	---	---	Peak
10	8604.00	48.38	-25.62	74.00	37.21	59.04	11.86	59.73	---	---	Peak
11	10774.00	50.35	-23.65	74.00	39.72	56.45	13.33	59.15	---	---	Peak
12	11226.00	50.67	-23.33	74.00	39.40	56.24	13.69	58.66	100	0	Peak
13	17660.00	49.98	-24.02	74.00	43.04	46.51	18.49	58.06	---	---	Peak
14	28968.00	49.26	-24.74	74.00	40.29	39.02	24.54	54.59	---	---	Peak

—————THE END—————