



# FCC RF Test Report

**APPLICANT** : Sony Mobile Communications Inc.  
**EQUIPMENT** : Bluetooth device  
**BRAND NAME** : SONY  
**FCC ID** : PY7-87507R  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DSS) Spread Spectrum Transmitter

The product was received on Mar. 01, 2017 and testing was completed on Apr. 18, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.**

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : PY7-87507R

Page Number : 1 of 69

Report Issued Date : Apr. 19, 2017

Report Version : Rev. 02

Report Template No.: BU5-FR15CBT Version 1.1



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION..... 5**

    1.1 Applicant..... 5

    1.2 Manufacturer..... 5

    1.3 Product Feature of Equipment Under Test..... 5

    1.4 Modification of EUT ..... 5

    1.5 Testing Location ..... 6

    1.6 Applicable Standards..... 7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 8**

    2.1 Carrier Frequency Channel ..... 8

    2.2 Descriptions of Test Mode ..... 9

    2.3 Test Mode..... 10

    2.4 Connection Diagram of Test System..... 11

    2.5 Support Unit used in test configuration and system ..... 12

    2.6 EUT Operation Test Setup ..... 12

    2.7 Measurement Results Explanation Example..... 12

**3 TEST RESULT ..... 13**

    3.1 Number of Channel Measurement ..... 13

    3.2 Hopping Channel Separation Measurement ..... 15

    3.3 Dwell Time Measurement..... 22

    3.4 20dB and 99% Bandwidth Measurement ..... 24

    3.5 Peak Output Power Measurement ..... 37

    3.6 Conducted Band Edges Measurement..... 39

    3.7 Conducted Spurious Emission Measurement ..... 46

    3.8 Radiated Band Edges and Spurious Emission Measurement ..... 56

    3.9 AC Conducted Emission Measurement..... 64

    3.10 Antenna Requirements..... 66

**4 LIST OF MEASURING EQUIPMENT..... 67**

**5 UNCERTAINTY OF EVALUATION..... 69**

**APPENDIX A. AC CONDUCTED EMISSION TEST RESULT**

**APPENDIX B. RADIATED SPURIOUS EMISSION**

**APPENDIX C. RADIATED SPURIOUS EMISSION PLOTS**





### SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.4	-	99% Bandwidth	-	Pass	-
3.5	15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	≤ 20dBc	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 5.25 dB at 45.120 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 19.30 dB at 13.558 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



# 1 General Description

## 1.1 Applicant

**Sony Mobile Communications Inc.**

4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

## 1.2 Manufacturer

**Sony Mobile Communications Inc.**

4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

## 1.3 Product Feature of Equipment Under Test

Standards-related Product Specification	
Bluetooth Antenna Type / Gain	FPCB Pattern Antenna type with gain 0.06 dBi

EUT Information List			
HW Version	SW Version	S/N	Performed Test Item
A	v1.0.1	84C7EAF7316F	RF conducted measurement
		84C7EAF73152	Radiated Spurious Emission
		84C7EAF73159	Conducted Emission

Accessory List	
<b>Adapter</b>	Model No. : UCH20
	S/N : 1215W48600039
<b>Earphone</b>	Model No. : MH755
	S/N: 16482013D0B146C
<b>USB Cable</b>	Model No. : UCB20
	S/N : 1702A93700CBBA2

**Note:**

1. Above EUT list and accessory list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test.
3. For other wireless features of this EUT, test report will be issued separately.

## 1.4 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH05-HY	CO05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	03CH10-HY	

**Note:** The test site complies with ANSI C63.4 2014 requirement.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 30-2, Dingfu Tsuen, Linkou District, New Taipei City, Taiwan, R.O.C. TEL: +886-3-327-0868 FAX: +886-3-327-0855	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	OS03-LK	

**Note:** The test site complies with ANSI C63.4 2014 requirement



## 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2013

### **Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-



## 2.2 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	5.12 dBm	2.54 dBm	2.76 dBm
Ch39	2441MHz	5.21 dBm	2.78 dBm	3.00 dBm
Ch78	2480MHz	4.84 dBm	2.38 dBm	2.56 dBm

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower)..
- b. AC power line Conducted Emission was tested under maximum output power.




## 2.3 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
<b>Conducted Test Cases</b>	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
<b>Radiated Test Cases</b>	<b>Bluetooth 1Mbps GFSK / EDR 2Mbps <math>\pi/4</math>-DQPSK / EDR 3Mbps 8-DPSK</b>		
	Mode 1: CH00_2402 MHz for 1Mbps Mode 2: CH39_2441 MHz for 1Mbps Mode 3: CH78_2480 MHz for 1Mbps Mode 4: CH00_2402 MHz for 2Mbps Mode 5: CH39_2441 MHz for 2Mbps Mode 6: CH78_2480 MHz for 2Mbps Mode 7: CH00_2402 MHz for 3Mbps Mode 8: CH39_2441 MHz for 3Mbps Mode 9: CH78_2480 MHz for 3Mbps		
<b>AC Conducted Emission</b>	Mode 1 :Bluetooth Link + Earphone + Battery + USB Cable (Charging from Adapter)		

## 2.4 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>





## 2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	Smart Phone	Sony	-	PY7-84773W	N/A	N/A
3.	Notebook	DELL	Latitude E3340	FCC DoC/ Contains FCC ID: PD97260NGU	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

## 2.6 EUT Operation Test Setup

For RF test items, an engineering test program was provided and enabled to contact with Bluetooth base station for continuous transmitting and receiving signals

## 2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup




##### 3.1.5 Test Result of Number of Hopping Frequency


Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 9.APR.2017 11:00:40



Date: 9.APR.2017 11:01:53

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup






### 3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.5480	Pass
39	2441	1.002	0.5480	Pass
78	2480	1.008	0.5400	Pass


Channel Separation Plot on Channel 00 - 01



Date: 9.APR.2017 11:51:43




Channel Separation Plot on Channel 39 - 40



Date: 9.APR.2017 11:55:22

Channel Separation Plot on Channel 77 - 78




Date: 9.APR.2017 12:01:50



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8200	Pass
39	2441	1.002	0.8240	Pass
78	2480	1.002	0.8200	Pass


Channel Separation Plot on Channel 00 - 01



Date: 10.APR.2017 19:45:37




Channel Separation Plot on Channel 39 - 40



Date: 10.APR.2017 19:48:41

Channel Separation Plot on Channel 77 - 78




Date: 10.APR.2017 19:51:46



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8000	Pass
39	2441	1.002	0.8000	Pass
78	2480	1.002	0.8000	Pass


Channel Separation Plot on Channel 00 - 01



Date: 10.APR.2017 19:58:04




### Channel Separation Plot on Channel 39 - 40



Date: 10.APR.2017 20:01:46

### Channel Separation Plot on Channel 77 - 78



Date: 10.APR.2017 20:04:31

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup





### 3.3.5 Test Result of Dwell Time


Test Mode :	DH5	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.94	0.31	0.4	Pass
AFH	20	53.34	2.94	0.16	0.4	Pass

**Remark:**

- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.  
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),  
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.  
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),  
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

**Package Transfer Time Plot**



Date: 5.APR.2017 09:57:53

### 3.4 20dB and 99% Bandwidth Measurement

#### 3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.  
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 99% bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
6. Measure and record the results in the test report.

#### 3.4.4 Test Setup






3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.822
39	2441	0.822
78	2480	0.810


20 dB Bandwidth Plot on Channel 00



Date: 9.APR.2017 12:26:04




### 20 dB Bandwidth Plot on Channel 39



Date: 9.APR.2017 12:27:08

### 20 dB Bandwidth Plot on Channel 78




Date: 9.APR.2017 12:35:09



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.230
39	2441	1.236
78	2480	1.230


20 dB Bandwidth Plot on Channel 00



Date: 10.APR.2017 20:18:20




20 dB Bandwidth Plot on Channel 39



Date: 10.APR.2017 20:08:16

20 dB Bandwidth Plot on Channel 78




Date: 10.APR.2017 20:09:25



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.200
39	2441	1.200
78	2480	1.200


20 dB Bandwidth Plot on Channel 00



Date: 10.APR.2017 20:10:23




20 dB Bandwidth Plot on Channel 39



Date: 10.APR.2017 20:11:11

20 dB Bandwidth Plot on Channel 78



Date: 10.APR.2017 20:13:03




3.4.6 Test Result of 99% Occupied Bandwidth

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	0.868
39	2441	0.868
78	2480	0.872


99% Occupied Bandwidth Plot on Channel 00



Date: 9.APR.2017 11:45:17




99% Occupied Bandwidth Plot on Channel 39



Date: 9.APR.2017 11:53:29

99% Occupied Bandwidth Plot on Channel 78




Date: 9.APR.2017 11:57:04



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.176
39	2441	1.172
78	2480	1.172


99% Occupied Bandwidth Plot on Channel 00



Date: 10.APR.2017 19:43:05




99% Occupied Bandwidth Plot on Channel 39



Date: 10.APR.2017 19:47:16

99% Occupied Bandwidth Plot on Channel 78




Date: 10.APR.2017 19:50:13



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.152
39	2441	1.152
78	2480	1.152


99% Occupied Bandwidth Plot on Channel 00



Date: 10.APR.2017 19:55:58




99% Occupied Bandwidth Plot on Channel 39



Date: 10.APR.2017 19:59:37

99% Occupied Bandwidth Plot on Channel 78



Date: 10.APR.2017 20:03:19

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

### 3.5 Peak Output Power Measurement

#### 3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

#### 3.5.4 Test Setup





3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	5.12	20.97	Pass
39	2441	5.21	20.97	Pass
78	2480	4.84	20.97	Pass

Note: For AFH mode using 20 hopping channels, the maximum output power limit is 20.97dBm.

Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	2.54	20.97	Pass
39	2441	2.78	20.97	Pass
78	2480	2.38	20.97	Pass

Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	2.76	20.97	Pass
39	2441	3.00	20.97	Pass
78	2480	2.56	20.97	Pass

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup






### 3.6.5 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

Low Band Edge Plot on Channel 00



Date: 9.APR.2017 11:45:50

High Band Edge Plot on Channel 78




Date: 9.APR.2017 11:59:36




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

Low Band Edge Plot on Channel 00



Date: 10.APR.2017 19:43:54

High Band Edge Plot on Channel 78




Date: 10.APR.2017 19:50:33




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

Low Band Edge Plot on Channel 00



Date: 10.APR.2017 19:57:03

High Band Edge Plot on Channel 78




Date: 10.APR.2017 20:03:38



### 3.6.6 Test Result of Conducted Hopping Mode Band Edges


Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

1Mbps Hopping Mode Low Band Edge Plot



Date: 9.APR.2017 11:31:08

1Mbps Hopping Mode High Band Edge Plot




Date: 9.APR.2017 11:29:51




Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

2Mbps Hopping Mode Low Band Edge Plot



Date: 10.APR.2017 20:14:36

2Mbps Hopping Mode High Band Edge Plot




Date: 10.APR.2017 20:16:31




Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Aking Chang	Relative Humidity :	48~51%

3Mbps Hopping Mode Low Band Edge Plot



Date: 10.APR.2017 20:19:16

3Mbps Hopping Mode High Band Edge Plot



Date: 10.APR.2017 20:20:25

## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.7.4 Test Setup






### 3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 9.APR.2017 11:43:23

1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 9.APR.2017 11:43:44




Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 9.APR.2017 11:52:33

1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 9.APR.2017 11:52:55




Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 9.APR.2017 11:55:59

1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 9.APR.2017 11:56:20




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 10.APR.2017 19:39:51

2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 10.APR.2017 19:40:13




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 10.APR.2017 19:53:20

2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 10.APR.2017 19:53:42




Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 10.APR.2017 19:49:14

2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 10.APR.2017 19:49:36




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 10.APR.2017 19:54:56

3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 10.APR.2017 19:55:20




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 10.APR.2017 19:58:40

3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 10.APR.2017 19:59:02




Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Aking Chang

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 10.APR.2017 20:02:16

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 10.APR.2017 20:02:38



### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




### 3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1 \text{ GHz}$ , RBW=1MHz for  $f > 1\text{GHz}$  ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (24.67dB) derived from  $20 \log (\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

### 3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


Please refer to Appendix C.




### 3.8.6 Duty cycle correction factor for average measurement

<1Mbps>

#### DH5 on time (One Pulse) Plot on Channel 39



#### DH5 on time (Count Pulses) Plot on Channel 39




**Note:**

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.92 / 100 = 5.84 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.67 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported




<2Mbps>

2DH5 on time (One Pulse) Plot on Channel 39




DH5 on time (Count Pulses) Plot on Channel 39






<3Mbps>

3DH5 on time (One Pulse) Plot on Channel 39



DH5 on time (Count Pulses) Plot on Channel 39





**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.92 \text{ ms} \times 20 \text{ channels} = 58.4 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.92 \text{ ms} \times 2 = 5.84 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.84 \text{ ms}/100\text{ms}) = -24.67 \text{ dB}$$

**3.8.7 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix B and C.

**3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix B and C.



### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix A.



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB412923 44	300MHz~40GHz	Dec. 26, 2016	Apr. 05, 2017 ~ Apr. 10, 2017	Dec. 25, 2017	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US404415 48	300MHz~40GHz	Dec. 26, 2016	Apr. 05, 2017 ~ Apr. 10, 2017	Dec. 25, 2017	Conducted (TH05-HY)
Hygrometer	Testo	608-H2	41410069	N/A	Aug. 28, 2016	Apr. 05, 2017 ~ Apr. 10, 2017	Aug. 27, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Jul. 17, 2016	Apr. 05, 2017 ~ Apr. 10, 2017	Jul. 16, 2017	Conducted (TH05-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY842095 21	1GHz~26GHz	Dec. 02, 2016	Apr. 05, 2017 ~ Apr. 10, 2017	Dec. 01, 2017	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890094	1V~20V 0.5A~5A	Oct. 11, 2016	Apr. 05, 2017 ~ Apr. 10, 2017	Oct. 10, 2017	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Apr. 06, 2017	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	Apr. 06, 2017	Aug. 29, 2017	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Apr. 19, 2016	Apr. 06, 2017	Apr. 18, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 29, 2016	Apr. 06, 2017	Nov. 28, 2017	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 05, 2017	Apr. 06, 2017	Jan. 04, 2018	Conduction (CO05-HY)
Test Software	N/A	EMC32	8.40.0	N/A	N/A	Apr. 06, 2017	N/A	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Apr. 06, 2017 ~ Apr. 18, 2017	Sep. 01, 2017	Radiation (03CH10-HY)
Amplifier	SONOMA	310N	187311	9kHz~1GHz	Oct. 26, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Oct. 25, 2017	Radiation (03CH10-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35413&02	30MHz~1GHz	Jan. 07, 2017	Apr. 06, 2017 ~ Apr. 18, 2017	Jan. 06, 2018	Radiation (03CH10-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-132 5	1GHz ~ 18GHz	Sep. 30, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Sep. 29, 2017	Radiation (03CH10-HY)
Preamplifier	Keysight	83017A	MY532700 78	1GHz~26.5GHz	Oct. 26, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Oct. 25, 2017	Radiation (03CH10-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 85	10Hz ~ 44GHz	Oct. 17, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Oct. 16, 2017	Radiation (03CH10-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Apr. 06, 2017 ~ Apr. 18, 2017	N/A	Radiation (03CH10-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1~4m	N/A	Apr. 06, 2017 ~ Apr. 18, 2017	N/A	Radiation (03CH10-HY)
Turn Table	EMEC	TT 2200	N/A	0~360 Degree	N/A	Apr. 06, 2017 ~ Apr. 18, 2017	N/A	Radiation (03CH10-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1815698	1GHz~18GHz	Dec. 01, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Nov. 30, 2017	Radiation (03CH10-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Preamplifier	MITEQ	JS44-180040 00-33-8P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Jun. 13, 2017	Radiation (03CH10-HY)
EMI Test Receiver	Agilent	N9038A (MXE)	MY5329005 3	20Hz to 26.5GHz	Jan. 12, 2017	Apr. 06, 2017 ~ Apr. 18, 2017	Jan. 11, 2018	Radiation (03CH10-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA91705 84	18GHz- 40GHz	Nov. 08, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Nov. 07, 2017	Radiation (03CH10-HY)
Filter	Wainwright	WLKS1200-1 2SS	SN2	1.2G Low Pass	Sep. 19, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Sep. 18, 2017	Radiation (03CH10-HY)
Filter	Wainwright	H3G018G1	SN477221	3.0 G High Pass	N/A	Apr. 06, 2017 ~ Apr. 18, 2017	N/A	Radiation (03CH10-HY)
Hygrometer	TECEPEL	DTM-303B	TP140320	N/A	Nov. 14, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Nov. 13, 2017	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY249564 MY249524 MY283184	25GHz~40GHz	Sep. 30, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Sep. 29, 2017	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY249564 MY249524 MY283184	30MHz~1GHz	Sep. 30, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Sep. 29, 2017	Radiation (03CH10-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY249564 MY249524 MY283184	1GHz~25GHz	Sep. 30, 2016	Apr. 06, 2017 ~ Apr. 18, 2017	Sep. 29, 2017	Radiation (03CH10-HY)
Test Software	Audix	E3	6.2009-8-24	N/A	N/A	Apr. 06, 2017 ~ Apr. 18, 2017	N/A	Radiation (03CH10-HY)
Amplifier	HP	8447D	2944A0906 8	0.1MHz ~ 1.3GHz	Dec. 12, 2016	Apr. 18, 2017	Dec. 11, 2017	Radiation (OS03-LK)
Spectrum Analyzer	R&S	FSP 7	100641	9 kHz ~ 7 GHz	Jun. 23, 2016	Apr. 18, 2017	Jun. 22, 2017	Radiation (OS03-LK)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Apr. 18, 2017	Sep. 01, 2017	Radiation (OS03-LK)
Test Receiver	R&S	ESCS 30	836858/024	9 kHz ~ 2.75 GHz	Jun. 24, 2016	Apr. 18, 2017	Jun. 23, 2017	Radiation (OS03-LK)
Bilog Antenna with 5dB Attenuator	TESEQ & WOKEN	CBL6112D & 00800N1D01 N-05	25236 & 007	30 MHz ~ 1 GHz	Jul. 30, 2016	Apr. 18, 2017	Jul. 29, 2017	Radiation (OS03-LK)
Turn Table	EMCO	2080	9711-2021	0 ~ 360 degree	NCR	Apr. 18, 2017	NCR	Radiation (OS03-LK)
Antenna Mast	EMCO	2075	9711-2115	1 m ~ 4 m	NCR	Apr. 18, 2017	NCR	Radiation (OS03-LK)
Test Software	Audix	E3	4	N/A	N/A	Apr. 18, 2017	N/A	Radiation (OS03-LK)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.70
---	------

<03CH10-HY>

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.60
---	------

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.90
---	------

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.20
---	------

<OS03-LK>

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.10
---	------




## Appendix A. AC Conducted Emission Test Results

Test Engineer :	Kai-Chun Chu	Temperature :	23~24°C
		Relative Humidity :	52~53%

# EUT Information

Report NO : 730107  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

ENV216 Auto Test FCC Power Bar - L



## Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	39.0	Off	L1	19.6	27.0	66.0
0.286000	21.0	Off	L1	19.6	39.6	60.6
0.510000	22.5	Off	L1	19.6	33.5	56.0
0.766000	18.7	Off	L1	19.6	37.3	56.0
1.238000	18.4	Off	L1	19.6	37.6	56.0
1.750000	18.2	Off	L1	19.6	37.8	56.0
13.558000	34.3	Off	L1	20.2	25.7	60.0
26.390000	25.5	Off	L1	20.9	34.5	60.0


## Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	21.4	Off	L1	19.6	34.6	56.0
0.286000	17.0	Off	L1	19.6	33.6	50.6
0.510000	18.5	Off	L1	19.6	27.5	46.0
0.766000	15.6	Off	L1	19.6	30.4	46.0
1.238000	15.3	Off	L1	19.6	30.7	46.0
1.750000	15.4	Off	L1	19.6	30.6	46.0
13.558000	29.8	Off	L1	20.2	20.2	50.0
26.390000	19.8	Off	L1	20.9	30.2	50.0

# EUT Information

Report NO : 730107  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

ENV216 Auto Test FCC Power Bar - N



## Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	43.9	Off	N	19.5	22.1	66.0
0.230000	26.3	Off	N	19.5	36.1	62.4
0.502000	27.9	Off	N	19.5	28.1	56.0
0.726000	18.8	Off	N	19.5	37.2	56.0
2.534000	20.4	Off	N	19.3	35.6	56.0
13.558000	35.7	Off	N	20.3	24.3	60.0
26.382000	25.0	Off	N	21.0	35.0	60.0

## Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	21.6	Off	N	19.5	34.4	56.0
0.230000	20.2	Off	N	19.5	32.2	52.4
0.502000	20.7	Off	N	19.5	25.3	46.0
0.726000	15.6	Off	N	19.5	30.4	46.0
2.534000	14.7	Off	N	19.3	31.3	46.0
13.558000	30.7	Off	N	20.3	19.3	50.0
26.382000	20.0	Off	N	21.0	30.0	50.0



## Appendix B. Radiated Spurious Emission

Test Engineer :	Tsung Lee, Stan Hsieh, Kyle Chuang	Temperature :	24~25°C
		Relative Humidity :	45~50%

2.4GHz 2400~2483.5MHz

BT(1M) (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
		( MHz )	( dBμV/m )	( dB )	Limit	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
					Line	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
BT CH00 2402MHz		2387.7	41.2	-32.8	74	41.8	27.23	5.39	33.22	114	320	P	H	
		2387.7	16.53	-37.47	54							A	H	
	*	2402	100.88	-	-	101.47	27.23	5.39	33.21	114	320	P	H	
	*	2402	76.21	-	-							A	H	
													H	
														H
			2385.075	41.07	-32.93	74	41.71	27.19	5.39	33.22	100	82	P	V
			2385.075	16.4	-37.6	54							A	V
	*		2402	101.74	-	-	102.33	27.23	5.39	33.21	100	82	P	V
	*		2402	77.07	-	-							A	V
													V	
													V	
BT CH 39 2441MHz		2314.06	41.38	-32.62	74	42.34	27.01	5.27	33.24	139	319	P	H	
		2314.06	16.71	-37.29	54							A	H	
	*	2441	99.36	-	-	99.75	27.37	5.42	33.18	139	319	P	H	
	*	2441	74.69	-	-							A	H	
			2498.11	40.66	-33.34	74	40.86	27.5	5.46	33.16	139	319	P	H
			2498.11	15.99	-38.01	54							A	H
			2357.88	41.17	-32.83	74	41.93	27.14	5.33	33.23	100	80	P	V
			2357.88	16.5	-37.5	54							A	V
	*		2441	100.1	-	-	100.49	27.37	5.42	33.18	100	80	P	V
	*		2441	75.43	-	-							A	V
			2492.65	41.28	-32.72	74	41.48	27.5	5.46	33.16	100	80	P	V
			2492.65	16.61	-37.39	54							A	V



<b>BT CH 78 2480MHz</b>	*	2480	98.29	-	-	98.56	27.46	5.44	33.17	137	321	P	H
	*	2480	73.62	-	-							A	H
		2483.52	62.85	-11.15	74	63.1	27.46	5.46	33.17	137	321	P	H
		2483.52	38.18	-15.82	54							A	H
													H
													H
	*	2480	99.64	-	-	99.91	27.46	5.44	33.17	100	44	P	V
	*	2480	74.97	-	-							A	V
		2483.56	63.94	-10.06	74	64.19	27.46	5.46	33.17	100	44	P	V
		2483.56	39.27	-14.73	54							A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT(1M) (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BT CH 00 2402MHz		4804	44.89	-29.11	74	64.22	31.42	7.58	58.33	100	0	P	H
		4804	20.22	-33.78	54	-	-	-	-	100	0	A	H
													H
													H
		4804	44.97	-29.03	74	64.3	31.42	7.58	58.33	100	0	P	V
		4804	20.3	-33.7	54	-	-	-	-	100	0	A	V
													V
													V
BT CH 39 2441MHz		4882	46.66	-27.34	74	65.52	31.56	7.82	58.24	100	0	P	H
		4882	21.99	-32.01	54	-	-	-	-	100	0	A	H
		7323	59.2	-14.8	74	72.57	36.22	9.51	59.1	100	0	P	H
		7323	34.53	-19.47	54	-	-	-	-	100	0	A	H
		4882	46.01	-27.99	74	64.87	31.56	7.82	58.24	100	0	P	V
		4882	21.34	-32.66	54	-	-	-	-	100	0	A	V
		7323	56.97	-17.03	74	70.34	36.22	9.51	59.1	100	0	P	V
		7323	32.3	-21.7	54	-	-	-	-	100	0	A	V
BT CH 78 2480MHz		4960	48.67	-25.33	74	67.15	31.73	7.93	58.14	100	0	P	H
		4960	24	-30	54	-	-	-	-	100	0	A	H
		7440	58.28	-15.72	74	71.35	36.49	9.61	59.17	100	0	P	H
		7440	33.61	-20.39	54	-	-	-	-	100	0	A	H
		4960	47.92	-26.08	74	66.4	31.73	7.93	58.14	100	0	P	V
		4960	23.25	-30.75	54	-	-	-	-	100	0	A	V
		7440	54.13	-19.87	74	67.2	36.49	9.61	59.17	100	0	P	V
		7440	29.46	-24.54	54	-	-	-	-	100	0	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT(2M) (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
BT CH00 2402MHz		2345.805	41.14	-32.86	74	41.94	27.1	5.33	33.23	132	320	P	H	
		2345.805	16.47	-37.53	54							A	H	
	*	2402	97.83	-	-	98.42	27.23	5.39	33.21	132	320	P	H	
	*	2402	73.16	-	-							A	H	
													H	
														H
			2339.715	42.1	-31.9	74	42.9	27.1	5.33	33.23	100	81	P	V
			2339.715	17.43	-36.57	54							A	V
	*	2402	98.85	-	-	99.44	27.23	5.39	33.21	100	81	P	V	
	*	2402	74.18	-	-								A	V
														V
														V
BT CH 39 2441MHz		2383.64	40.37	-33.63	74	41.01	27.19	5.39	33.22	140	319	P	H	
		2383.64	15.7	-38.3	54							A	H	
	*	2441	96.78	-	-	97.17	27.37	5.42	33.18	140	319	P	H	
	*	2441	72.11	-	-							A	H	
			2496.92	40.39	-33.61	74	40.59	27.5	5.46	33.16	140	319	P	H
			2496.92	15.72	-38.28	54							A	H
			2333.8	40.99	-33.01	74	41.85	27.05	5.33	33.24	100	44	P	V
			2333.8	16.32	-37.68	54							A	V
	*	2441	97.27	-	-	97.66	27.37	5.42	33.18	100	44	P	V	
	*	2441	72.6	-	-								A	V
			2492.93	40.69	-33.31	74	40.89	27.5	5.46	33.16	100	44	P	V
			2492.93	16.02	-37.98	54							A	V



<b>BT CH 78 2480MHz</b>	*	2480	95.85	-	-	96.12	27.46	5.44	33.17	138	321	P	H
	*	2480	71.18	-	-							A	H
		2483.52	59.84	-14.16	74	60.09	27.46	5.46	33.17	138	321	P	H
		2483.52	35.17	-18.83	54							A	H
													H
													H
	*	2480	96.19	-	-	96.46	27.46	5.44	33.17	100	44	P	V
	*	2480	71.52	-	-							A	V
		2483.52	60.48	-13.52	74	60.73	27.46	5.46	33.17	100	44	P	V
		2483.52	35.81	-18.19	54							A	V
													V
													V
<b>Remark</b>	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT(2M) (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBµV/m )	Over Limit ( dB )	Limit Line ( dBµV/m )	Read Level ( dBµV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BT CH 00 2402MHz		4804	44.97	-29.03	74	64.3	31.42	7.58	58.33	100	0	P	H
		4804	20.3	-33.7	54					100	0	A	H
													H
													H
		4804	43.59	-30.41	74	62.92	31.42	7.58	58.33	100	0	P	V
		4804	18.92	-35.08	54	-	-	-	-	100	0	A	V
													V
													V
BT CH 39 2441MHz		4882	42.51	-31.49	74	61.49	31.56	7.7	58.24	100	0	P	H
		4882	17.84	-36.16	54	-	-	-	-	100	0	A	H
		7323	51	-23	74	64.39	36.22	9.49	59.1	100	0	P	H
		7323	26.33	-27.67	54	-	-	-	-	100	0	A	H
		4882	42.89	-31.11	74	61.87	31.56	7.7	58.24	100	0	P	V
		4882	18.22	-35.78	54	-	-	-	-	100	0	A	V
		7323	49.57	-24.43	74	62.96	36.22	9.49	59.1	100	0	P	V
		7323	24.9	-29.1	54	-	-	-	-	100	0	A	V
BT CH 78 2480MHz		4960	42.18	-31.82	74	60.66	31.73	7.93	58.14	100	0	P	H
		4960	17.51	-36.49	54	-	-	-	-	100	0	A	H
		7440	52.12	-21.88	74	65.19	36.49	9.61	59.17	100	0	P	H
		7440	27.45	-26.55	54	-	-	-	-	100	0	A	H
		4960	42.82	-31.18	74	61.3	31.73	7.93	58.14	100	0	P	V
		4960	18.15	-35.85	54	-	-	-	-	100	0	A	V
		7440	47.87	-26.13	74	60.94	36.49	9.61	59.17	100	0	P	V
		7440	23.2	-30.8	54	-	-	-	-	100	0	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT(3M) (Band Edge @ 3m)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
BT CH00 2402MHz		2339.925	40.78	-33.22	74	41.58	27.1	5.33	33.23	139	319	P	H	
		2339.925	16.11	-37.89	54							A	H	
	*	2402	98.33	-	-	98.92	27.23	5.39	33.21	139	319	P	H	
	*	2402	73.66	-	-							A	H	
													H	
													H	
			2363.76	40.61	-33.39	74	41.31	27.14	5.39	33.23	100	82	P	V
			2363.76	15.94	-38.06	54							A	V
	*	2402	99	-	-	99.59	27.23	5.39	33.21	100	82	P	V	
	*	2402	74.33	-	-								A	V
														V
														V
BT CH 39 2441MHz		2332.68	40.68	-33.32	74	41.54	27.05	5.33	33.24	143	320	P	H	
		2332.68	16.01	-37.99	54							A	H	
	*	2441	96.96	-	-	97.35	27.37	5.42	33.18	143	320	P	H	
	*	2441	72.29	-	-							A	H	
			2487.4	41.48	-32.52	74	41.73	27.46	5.46	33.17	143	320	P	H
			2487.4	16.81	-37.19	54							A	H
			2344.86	40.69	-33.31	74	41.49	27.1	5.33	33.23	100	80	P	V
			2344.86	16.02	-37.98	54							A	V
	*	2441	97.48	-	-	97.87	27.37	5.42	33.18	100	80	P	V	
	*	2441	72.81	-	-								A	V
			2496.29	42.34	-31.66	74	42.54	27.5	5.46	33.16	100	80	P	V
			2496.29	17.67	-36.33	54							A	V



<b>BT CH 78 2480MHz</b>	*	2480	95.97	-	-	96.24	27.46	5.44	33.17	136	321	P	H	
	*	2480	71.3	-	-							A	H	
		2483.52	59.95	-14.05	74	60.2	27.46	5.46	33.17	136	321	P	H	
		2483.52	35.28	-18.72	54							A	H	
													H	
													H	
	*	2480	96.14	-	-	96.41	27.46	5.44	33.17	100	46	P	V	
	*	2480	71.47	-	-								A	V
		2483.52	60.09	-13.91	74	60.34	27.46	5.46	33.17	100	46	P	V	
		2483.52	35.42	-18.58	54								A	V
														V
														V
<b>Remark</b>	5. No other spurious found. 6. All results are PASS against Peak and Average limit line.													



2.4GHz 2400~2483.5MHz

BT(3M) (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )
BT CH 00 2402MHz		4804	43.87	-30.13	74	63.2	31.42	7.58	58.33	100	0	P	H
		4804	19.2	-34.8	54	-	-	-	-	100	0	A	H
													H
													H
		4804	43.69	-30.31	74	63.02	31.42	7.58	58.33	100	0	P	V
		4804	19.02	-34.98	54	-	-	-	-	100	0	A	V
													V
													V
BT CH 39 2441MHz		4882	42.98	-31.02	74	61.96	31.56	7.7	58.24	100	0	P	H
		4882	18.31	-35.69	54	-	-	-	-	100	0	A	H
		7323	51.11	-22.89	74	64.5	36.22	9.49	59.1	100	0	P	H
		7323	26.44	-27.56	54	-	-	-	-	100	0	A	H
		4882	42.91	-31.09	74	61.89	31.56	7.7	58.24	100	0	P	V
		4882	18.24	-35.76	54	-	-	-	-	100	0	A	V
		7323	49.76	-24.24	74	63.15	36.22	9.49	59.1	100	0	P	V
		7323	25.09	-28.91	54	-	-	-	-	100	0	A	V
BT CH 78 2480MHz		4960	44.23	-29.77	74	62.71	31.73	7.93	58.14	100	0	P	H
		4960	19.56	-34.44	54	-	-	-	-	100	0	A	H
		7440	52.04	-21.96	74	65.11	36.49	9.61	59.17	100	0	P	H
		7440	27.37	-26.63	54	-	-	-	-	100	0	A	H
		4960	43.68	-30.32	74	62.16	31.73	7.93	58.14	100	0	P	V
		4960	19.01	-34.99	54	-	-	-	-		0	A	V
		7440	49.19	-24.81	74	62.26	36.49	9.61	59.17	100	0	P	V
		7440	24.52	-29.48	54	-	-	-	-	100	0	A	V
Remark	5. No other spurious found. 6. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
2.4GHz BT LF		30	23.58	-16.42	40	29.59	26.1	0.65	32.76	-	-	P	H	
		45.66	23.35	-16.65	40	37.88	17.28	0.93	32.74	-	-	P	H	
		76.44	18.19	-21.81	40	36.59	13.43	0.93	32.76	-	-	P	H	
		387.5	21.73	-24.27	46	30.23	22.12	2.13	32.75	-	-	P	H	
		742.4	28.9	-17.1	46	31.63	27.31	2.91	32.95	-	-	P	H	
		888.7	31.55	-14.45	46	32.01	28.7	3.2	32.36	100	0	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
			40.53	33.48	-6.52	40	45.64	19.94	0.65	32.75	-	-	P	V
			45.12	34.75	-5.25	40	49.28	17.28	0.93	32.74	100	0	P	V
			74.01	24.67	-15.33	40	43.42	13.07	0.93	32.75	-	-	P	V
			391	22.11	-23.89	46	30.55	22.19	2.13	32.76	-	-	P	V
			811	28.79	-17.21	46	30.48	28.07	3.07	32.83	-	-	P	V
			958.7	31.49	-14.51	46	29.85	30	3.29	31.65	-	-	P	V
													V	
													V	
												V		
												V		
												V		
												V		
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

- Level(dBμV/m) =  
Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

- Level(dBμV/m)  
= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
- Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



### Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Tsung Lee, Stan Hsieh, Kyle Chuang and	Temperature :	24~25°C
	Arthur Hsieh	Relative Humidity :	45~50%

Note symbol

-L	Low channel location
-R	High channel location





2.4GHz 2400~2483.5MHz

BT(1M) (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(1M) CH00 2402MHz	
1	Horizontal	Fundamental
Peak	<p>Site Condition : 03CH10-HY : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site Condition : 03CH10-HY : PEAK_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(1M) CH00 2402MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(1M) CH39 2441MHz	
1	Horizontal	Fundamental
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p><b>Left blank</b></p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(1M) CH39 2441MHz	
1	Vertical	Fundamental
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p><b>Left blank</b></p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(1M) CH78 2480MHz	
1	Horizontal	Fundamental
Peak	<p>Site : 03CH10-HV Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH10-HV Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(1M) CH78 2480MHz	
1	Vertical	Fundamental
<b>Peak</b>	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



2.4GHz 2400~2483.5MHz



BT (Harmonic @ 3m)

<b>BT</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>BT(1M) CH00 2402MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak Avg.</b>	 <p>Site : 03CH10-14Y Condition : PEAK_74 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH10-14Y Condition : PEAK_74 3m HORN_9170_406_0584 VERTICAL Detector : Peak</p>



<b>BT</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
<b>ANT</b>	<b>BT(1M) CH39 2441MHz</b>	
<b>1</b>	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak Avg.</b>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak</p>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 VERTICAL Detector : Peak</p>



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT(1M) CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 VERTICAL Detector : Peak</p>



2.4GHz 2400~2483.5MHz

BT(2M) (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(2M) CH00 2402MHz	
1	Horizontal	Fundamental
Peak	<p>Site Condition : 03CH10-HY : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site Condition : 03CH10-HY : PEAK_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(2M) CH00 2402MHz	
1	Vertical	Fundamental
Peak	<p>Site : 03CH10-HY Condition : PEAK_SE_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(2M) CH39 2441MHz	
1	Horizontal	Fundamental
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p><b>Left blank</b></p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(2M) CH39 2441MHz	
1	Vertical	Fundamental
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p><b>Left blank</b></p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(2M) CH78 2480MHz	
1	Horizontal	Fundamental
Peak	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(2M) CH78 2480MHz	
1	Vertical	Fundamental
Peak	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





2.4GHz 2400~2483.5MHz  
BT(2M) (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT(2M) CH00 2402MHz	
1	Horizontal	Vertical
<p><b>Peak</b> <b>Avg.</b></p>	<p>Site : 03CH10-4Y Condition : PEAK_74 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak</p>	<p>Site : 03CH10-4Y Condition : PEAK_74 3m HORN_9170_406_0584 VERTICAL Detector : Peak</p>



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT(2M) CH39 2441MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 VERTICAL Detector : Peak</p>



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT(2M) CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 VERTICAL Detector : Peak</p>





2.4GHz 2400~2483.5MHz

BT(3M) (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(3M) CH00 2402MHz	
1	Horizontal	Fundamental
<p>Peak</p>	<p>Site Condition : 03CH10-HY : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site Condition : 03CH10-HY : PEAK_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(3M) CH00 2402MHz	
1	Vertical	Fundamental
<b>Peak</b>	 <p>Site : 03CH10-HY Condition : PEAK_SE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(3M) CH39 2441MHz	
1	Horizontal	Fundamental
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p><b>Left blank</b></p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(3M) CH39 2441MHz	
1	Vertical	Fundamental
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
<p><b>Peak</b></p>	<p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 91200-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p><b>Left blank</b></p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(3M) CH78 2480MHz	
1	Horizontal	Fundamental
<p><b>Peak</b></p>	 <p>Site : 03CH10-HY Condition : PEAK_BE_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT(3M) CH78 2480MHz	
1	Vertical	Fundamental
<p><b>Peak</b></p>	 <p>Site : 03CH10-HY            Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH10-HY            Condition : PEAK_74 3m HORN 9120D-HF VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





2.4GHz 2400~2483.5MHz



BT(3M) (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT(3M) CH00 2402MHz	
1	Horizontal	Vertical
<p><b>Peak</b> <b>Avg.</b></p>	<p>Site : 03CH10-4Y Condition : PEAK_74 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak</p>	<p>Site : 03CH10-4Y Condition : PEAK_74 3m HORN_9170_406_0584 VERTICAL Detector : Peak</p>



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT(3M) CH39 2441MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 VERTICAL Detector : Peak</p>



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT(3M) CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH10-HY Condition : PEAK_74 3m HORN_9170_406_0584 VERTICAL Detector : Peak</p>





Emission below 1GHz  
2.4GHz BT (LF)

BT	2.4GHz 2400~2483.5MHz	
ANT	BT LF	
1	Horizontal	Vertical
QP / Peak	<p>Site : 03CH10-HY Condition : QP 3m BE-LOG 6111D-LF HORIZONTAL Detector : Peak</p>	<p>Site : 03CH10-HY Condition : QP 3m BE-LOG 6111D-LF VERTICAL Detector : Peak</p>



Emission below 30MHz

9kHz~30MHz

ANT	9kHz~30MHz																																																																																																																																																																																																									
1	Horizontal	Vertical																																																																																																																																																																																																								
QP / Avg.	 <p>Site : 05CH10-HY Condition : 15.209 LIMIT LINE 3m LOOP_HFH2-ZZ_100315 HORIZONTAL Project : 730107 Mode : IO</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Level</th> <th>Over</th> <th>Limit</th> <th>Read</th> <th>Antenna</th> <th>Cable</th> <th>A/Pos</th> <th>T/Pos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV/m</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> <th></th> </tr> </thead> <tbody> <tr><td>1</td><td>0.06</td><td>39.30</td><td>-72.66</td><td>111.96</td><td>19.23</td><td>20.06</td><td>0.01</td><td>---</td><td>--- Average</td></tr> <tr><td>2</td><td>0.09</td><td>35.71</td><td>-72.74</td><td>108.45</td><td>15.69</td><td>20.01</td><td>0.01</td><td>---</td><td>--- QP</td></tr> <tr><td>3</td><td>0.13</td><td>36.99</td><td>-68.68</td><td>105.59</td><td>17.01</td><td>19.97</td><td>0.01</td><td>---</td><td>--- Average</td></tr> <tr><td>4</td><td>0.17</td><td>46.44</td><td>-56.73</td><td>103.17</td><td>26.49</td><td>19.98</td><td>0.01</td><td>---</td><td>--- Average</td></tr> <tr><td>5</td><td>1.96</td><td>40.21</td><td>-29.79</td><td>70.00</td><td>20.19</td><td>19.94</td><td>0.09</td><td>100</td><td>0 QP</td></tr> <tr><td>6</td><td>11.52</td><td>36.58</td><td>-33.42</td><td>70.00</td><td>16.21</td><td>20.06</td><td>0.31</td><td>---</td><td>--- QP</td></tr> <tr><td>7</td><td>17.22</td><td>38.03</td><td>-31.97</td><td>70.00</td><td>17.49</td><td>20.14</td><td>0.40</td><td>---</td><td>--- QP</td></tr> <tr><td>8</td><td>29.36</td><td>36.85</td><td>-33.15</td><td>70.00</td><td>16.10</td><td>20.43</td><td>0.32</td><td>---</td><td>--- QP</td></tr> </tbody> </table>	Freq	Level	Over	Limit	Read	Antenna	Cable	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg		1	0.06	39.30	-72.66	111.96	19.23	20.06	0.01	---	--- Average	2	0.09	35.71	-72.74	108.45	15.69	20.01	0.01	---	--- QP	3	0.13	36.99	-68.68	105.59	17.01	19.97	0.01	---	--- Average	4	0.17	46.44	-56.73	103.17	26.49	19.98	0.01	---	--- Average	5	1.96	40.21	-29.79	70.00	20.19	19.94	0.09	100	0 QP	6	11.52	36.58	-33.42	70.00	16.21	20.06	0.31	---	--- QP	7	17.22	38.03	-31.97	70.00	17.49	20.14	0.40	---	--- QP	8	29.36	36.85	-33.15	70.00	16.10	20.43	0.32	---	--- QP	 <p>Site : 05CH10-HY Condition : 15.209 LIMIT LINE 3m LOOP_HFH2-ZZ_100315 VERTICAL Project : 730107 Mode : IO</p> <table border="1"> <thead> <tr> <th>Freq</th> <th>Level</th> <th>Over</th> <th>Limit</th> <th>Read</th> <th>Antenna</th> <th>Cable</th> <th>A/Pos</th> <th>T/Pos</th> <th>Remark</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV/m</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>cm</th> <th>deg</th> <th></th> </tr> </thead> <tbody> <tr><td>1</td><td>0.06</td><td>41.78</td><td>-70.20</td><td>111.98</td><td>21.71</td><td>20.06</td><td>0.01</td><td>---</td><td>--- Average</td></tr> <tr><td>2</td><td>0.09</td><td>34.83</td><td>-74.18</td><td>108.21</td><td>14.02</td><td>20.00</td><td>0.01</td><td>---</td><td>--- QP</td></tr> <tr><td>3</td><td>0.12</td><td>33.99</td><td>-72.34</td><td>106.33</td><td>14.00</td><td>19.98</td><td>0.01</td><td>---</td><td>--- Average</td></tr> <tr><td>4</td><td>0.15</td><td>45.32</td><td>-58.66</td><td>103.98</td><td>25.36</td><td>19.95</td><td>0.01</td><td>---</td><td>--- Average</td></tr> <tr><td>5</td><td>3.43</td><td>37.88</td><td>-32.12</td><td>70.00</td><td>17.83</td><td>19.92</td><td>0.13</td><td>100</td><td>0 QP</td></tr> <tr><td>6</td><td>9.78</td><td>37.69</td><td>-32.31</td><td>70.00</td><td>17.40</td><td>20.02</td><td>0.27</td><td>---</td><td>--- QP</td></tr> <tr><td>7</td><td>23.62</td><td>37.35</td><td>-32.65</td><td>70.00</td><td>16.42</td><td>20.57</td><td>0.36</td><td>---</td><td>--- QP</td></tr> <tr><td>8</td><td>27.33</td><td>36.91</td><td>-33.09</td><td>70.00</td><td>15.96</td><td>20.62</td><td>0.33</td><td>---</td><td>--- QP</td></tr> </tbody> </table>	Freq	Level	Over	Limit	Read	Antenna	Cable	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg		1	0.06	41.78	-70.20	111.98	21.71	20.06	0.01	---	--- Average	2	0.09	34.83	-74.18	108.21	14.02	20.00	0.01	---	--- QP	3	0.12	33.99	-72.34	106.33	14.00	19.98	0.01	---	--- Average	4	0.15	45.32	-58.66	103.98	25.36	19.95	0.01	---	--- Average	5	3.43	37.88	-32.12	70.00	17.83	19.92	0.13	100	0 QP	6	9.78	37.69	-32.31	70.00	17.40	20.02	0.27	---	--- QP	7	23.62	37.35	-32.65	70.00	16.42	20.57	0.36	---	--- QP	8	27.33	36.91	-33.09	70.00	15.96	20.62	0.33	---	--- QP
	Freq	Level	Over	Limit	Read	Antenna	Cable	A/Pos	T/Pos	Remark																																																																																																																																																																																																
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																																																																																																																																																																		
1	0.06	39.30	-72.66	111.96	19.23	20.06	0.01	---	--- Average																																																																																																																																																																																																	
2	0.09	35.71	-72.74	108.45	15.69	20.01	0.01	---	--- QP																																																																																																																																																																																																	
3	0.13	36.99	-68.68	105.59	17.01	19.97	0.01	---	--- Average																																																																																																																																																																																																	
4	0.17	46.44	-56.73	103.17	26.49	19.98	0.01	---	--- Average																																																																																																																																																																																																	
5	1.96	40.21	-29.79	70.00	20.19	19.94	0.09	100	0 QP																																																																																																																																																																																																	
6	11.52	36.58	-33.42	70.00	16.21	20.06	0.31	---	--- QP																																																																																																																																																																																																	
7	17.22	38.03	-31.97	70.00	17.49	20.14	0.40	---	--- QP																																																																																																																																																																																																	
8	29.36	36.85	-33.15	70.00	16.10	20.43	0.32	---	--- QP																																																																																																																																																																																																	
Freq	Level	Over	Limit	Read	Antenna	Cable	A/Pos	T/Pos	Remark																																																																																																																																																																																																	
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																																																																																																																																																																		
1	0.06	41.78	-70.20	111.98	21.71	20.06	0.01	---	--- Average																																																																																																																																																																																																	
2	0.09	34.83	-74.18	108.21	14.02	20.00	0.01	---	--- QP																																																																																																																																																																																																	
3	0.12	33.99	-72.34	106.33	14.00	19.98	0.01	---	--- Average																																																																																																																																																																																																	
4	0.15	45.32	-58.66	103.98	25.36	19.95	0.01	---	--- Average																																																																																																																																																																																																	
5	3.43	37.88	-32.12	70.00	17.83	19.92	0.13	100	0 QP																																																																																																																																																																																																	
6	9.78	37.69	-32.31	70.00	17.40	20.02	0.27	---	--- QP																																																																																																																																																																																																	
7	23.62	37.35	-32.65	70.00	16.42	20.57	0.36	---	--- QP																																																																																																																																																																																																	
8	27.33	36.91	-33.09	70.00	15.96	20.62	0.33	---	--- QP																																																																																																																																																																																																	



Verification of Radiated Spurious Emissions  
 below 30MHz at open-area test site  
 9kHz~30MHz

ANT	9kHz~30MHz																																																																																																																																																																																					
1	Horizontal	Vertical																																																																																																																																																																																				
QP / Avg.	<p>Site : OS03-LX            Condition : 15.209 LIMIT LINE 3m LOOP_HFH2_Z2_100315 HORIZONTAL            Project : 730107            Mode : 9kHz to 30MHz</p> <table border="1"> <thead> <tr> <th>Line</th> <th>Freq</th> <th>Level</th> <th>Limit</th> <th>Res</th> <th>Antenna</th> <th>Cable</th> <th>A/Fos</th> <th>T/Fos</th> <th>Remark</th> </tr> </thead> <tbody> <tr><td>1</td><td>0.06</td><td>14.41</td><td>-73.28</td><td>111.69</td><td>18.34</td><td>20.06</td><td>0.01</td><td>...</td><td>Average</td></tr> <tr><td>2</td><td>0.09</td><td>14.81</td><td>-73.53</td><td>109.34</td><td>14.80</td><td>20.00</td><td>0.01</td><td>...</td><td>QP</td></tr> <tr><td>3</td><td>0.14</td><td>15.35</td><td>-69.35</td><td>104.02</td><td>15.40</td><td>19.96</td><td>0.01</td><td>...</td><td>Average</td></tr> <tr><td>4</td><td>0.18</td><td>43.42</td><td>-59.10</td><td>103.05</td><td>23.47</td><td>19.94</td><td>0.01</td><td>...</td><td>Average</td></tr> <tr><td>5</td><td>2.22</td><td>38.24</td><td>-55.24</td><td>70.00</td><td>19.21</td><td>19.95</td><td>0.01</td><td>100</td><td>15 QP</td></tr> <tr><td>6</td><td>12.50</td><td>34.74</td><td>-55.26</td><td>70.00</td><td>14.35</td><td>20.06</td><td>0.33</td><td>...</td><td>QP</td></tr> <tr><td>7</td><td>13.58</td><td>38.49</td><td>-53.10</td><td>70.00</td><td>16.33</td><td>20.19</td><td>0.40</td><td>...</td><td>QP</td></tr> <tr><td>8</td><td>29.58</td><td>35.96</td><td>-54.04</td><td>70.00</td><td>15.24</td><td>20.38</td><td>0.32</td><td>...</td><td>QP</td></tr> </tbody> </table>	Line	Freq	Level	Limit	Res	Antenna	Cable	A/Fos	T/Fos	Remark	1	0.06	14.41	-73.28	111.69	18.34	20.06	0.01	...	Average	2	0.09	14.81	-73.53	109.34	14.80	20.00	0.01	...	QP	3	0.14	15.35	-69.35	104.02	15.40	19.96	0.01	...	Average	4	0.18	43.42	-59.10	103.05	23.47	19.94	0.01	...	Average	5	2.22	38.24	-55.24	70.00	19.21	19.95	0.01	100	15 QP	6	12.50	34.74	-55.26	70.00	14.35	20.06	0.33	...	QP	7	13.58	38.49	-53.10	70.00	16.33	20.19	0.40	...	QP	8	29.58	35.96	-54.04	70.00	15.24	20.38	0.32	...	QP	<p>Site : OS03-LX            Condition : 15.209 LIMIT LINE 3m LOOP_HFH2_Z2_100315 VERTICAL            Project : 730107            Mode : 9kHz to 30MHz</p> <table border="1"> <thead> <tr> <th>Line</th> <th>Freq</th> <th>Level</th> <th>Limit</th> <th>Res</th> <th>Antenna</th> <th>Cable</th> <th>A/Fos</th> <th>T/Fos</th> <th>Remark</th> </tr> </thead> <tbody> <tr><td>1</td><td>0.06</td><td>40.86</td><td>-71.01</td><td>111.03</td><td>20.79</td><td>20.06</td><td>0.01</td><td>...</td><td>Average</td></tr> <tr><td>2</td><td>0.10</td><td>32.35</td><td>-75.69</td><td>104.04</td><td>12.34</td><td>20.00</td><td>0.01</td><td>...</td><td>QP</td></tr> <tr><td>3</td><td>0.12</td><td>32.84</td><td>-73.38</td><td>104.04</td><td>12.87</td><td>19.98</td><td>0.01</td><td>...</td><td>Average</td></tr> <tr><td>4</td><td>0.17</td><td>45.03</td><td>-59.18</td><td>103.20</td><td>25.07</td><td>19.94</td><td>0.01</td><td>...</td><td>Average</td></tr> <tr><td>5</td><td>2.88</td><td>35.55</td><td>-54.47</td><td>70.00</td><td>15.45</td><td>19.97</td><td>0.11</td><td>...</td><td>QP</td></tr> <tr><td>6</td><td>12.50</td><td>34.94</td><td>-55.06</td><td>70.00</td><td>14.62</td><td>20.03</td><td>0.39</td><td>...</td><td>QP</td></tr> <tr><td>7</td><td>24.00</td><td>34.80</td><td>-53.09</td><td>70.00</td><td>15.93</td><td>20.27</td><td>0.36</td><td>100</td><td>27 QP</td></tr> <tr><td>8</td><td>27.86</td><td>34.96</td><td>-55.02</td><td>70.00</td><td>14.04</td><td>20.61</td><td>0.33</td><td>...</td><td>QP</td></tr> </tbody> </table>	Line	Freq	Level	Limit	Res	Antenna	Cable	A/Fos	T/Fos	Remark	1	0.06	40.86	-71.01	111.03	20.79	20.06	0.01	...	Average	2	0.10	32.35	-75.69	104.04	12.34	20.00	0.01	...	QP	3	0.12	32.84	-73.38	104.04	12.87	19.98	0.01	...	Average	4	0.17	45.03	-59.18	103.20	25.07	19.94	0.01	...	Average	5	2.88	35.55	-54.47	70.00	15.45	19.97	0.11	...	QP	6	12.50	34.94	-55.06	70.00	14.62	20.03	0.39	...	QP	7	24.00	34.80	-53.09	70.00	15.93	20.27	0.36	100	27 QP	8	27.86	34.96	-55.02	70.00	14.04	20.61	0.33	...	QP
	Line	Freq	Level	Limit	Res	Antenna	Cable	A/Fos	T/Fos	Remark																																																																																																																																																																												
1	0.06	14.41	-73.28	111.69	18.34	20.06	0.01	...	Average																																																																																																																																																																													
2	0.09	14.81	-73.53	109.34	14.80	20.00	0.01	...	QP																																																																																																																																																																													
3	0.14	15.35	-69.35	104.02	15.40	19.96	0.01	...	Average																																																																																																																																																																													
4	0.18	43.42	-59.10	103.05	23.47	19.94	0.01	...	Average																																																																																																																																																																													
5	2.22	38.24	-55.24	70.00	19.21	19.95	0.01	100	15 QP																																																																																																																																																																													
6	12.50	34.74	-55.26	70.00	14.35	20.06	0.33	...	QP																																																																																																																																																																													
7	13.58	38.49	-53.10	70.00	16.33	20.19	0.40	...	QP																																																																																																																																																																													
8	29.58	35.96	-54.04	70.00	15.24	20.38	0.32	...	QP																																																																																																																																																																													
Line	Freq	Level	Limit	Res	Antenna	Cable	A/Fos	T/Fos	Remark																																																																																																																																																																													
1	0.06	40.86	-71.01	111.03	20.79	20.06	0.01	...	Average																																																																																																																																																																													
2	0.10	32.35	-75.69	104.04	12.34	20.00	0.01	...	QP																																																																																																																																																																													
3	0.12	32.84	-73.38	104.04	12.87	19.98	0.01	...	Average																																																																																																																																																																													
4	0.17	45.03	-59.18	103.20	25.07	19.94	0.01	...	Average																																																																																																																																																																													
5	2.88	35.55	-54.47	70.00	15.45	19.97	0.11	...	QP																																																																																																																																																																													
6	12.50	34.94	-55.06	70.00	14.62	20.03	0.39	...	QP																																																																																																																																																																													
7	24.00	34.80	-53.09	70.00	15.93	20.27	0.36	100	27 QP																																																																																																																																																																													
8	27.86	34.96	-55.02	70.00	14.04	20.61	0.33	...	QP																																																																																																																																																																													