



FCC CFR47 PART 15 SUBPART C
CERTIFICATION TEST REPORT
FOR
GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac & NFC

FCC ID: PY7-PM0941

REPORT NUMBER: 16J22997-E6V2

ISSUE DATE: 3/30/2016

Prepared for
SONY MOBILE COMMUNICATIONS, INC.
4-12-3 Higashi-Shinagawa, Shinagawa-Ku
TOKYO, 140-0002 JAPAN

Prepared by
UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888



NVLAP LAB CODE 200065-0

Revision History

| <u>Rev.</u> | <u>Issue Date</u> | <u>Revisions</u> | <u>Revised By</u> |
|-------------|-------------------|--------------------------------|-------------------|
| V1 | 3/18/2016 | Initial issue | C. OOI |
| V2 | 3/30/2016 | Updated Information on Page 14 | C. OOI |

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. ATTESTATION OF TEST RESULTS | 4 |
| 2. TEST METHODOLOGY | 5 |
| 3. FACILITIES AND ACCREDITATION | 5 |
| 4. CALIBRATION AND UNCERTAINTY | 5 |
| 4.1. <i>MEASURING INSTRUMENT CALIBRATION</i> | <i>5</i> |
| 4.2. <i>SAMPLE CALCULATION</i> | <i>5</i> |
| 4.3. <i>MEASUREMENT UNCERTAINTY</i> | <i>6</i> |
| 5. EQUIPMENT UNDER TEST | 7 |
| 5.1. <i>DESCRIPTION OF EUT</i> | <i>7</i> |
| 5.2. <i>MAXIMUM OUTPUT POWER.....</i> | <i>7</i> |
| 5.3. <i>WORST-CASE CONFIGURATION AND MODE.....</i> | <i>7</i> |
| 5.4. <i>MODIFICATIONS</i> | <i>7</i> |
| 5.5. <i>DESCRIPTION OF TEST SETUP.....</i> | <i>8</i> |
| 6. TEST AND MEASUREMENT EQUIPMENT | 10 |
| 7. OCCUPIED BANDWIDTH | 11 |
| 8. RADIATED EMISSION TEST RESULTS..... | 12 |
| 8.1.1. <i>FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz)</i> | <i>14</i> |
| 8.1.2. <i>TX SPURIOUS EMISSION 30 TO 1000 MHz</i> | <i>17</i> |
| 9. AC MAINS LINE CONDUCTED EMISSIONS..... | 19 |
| 10. FREQUENCY STABILITY..... | 23 |
| 11. SETUP PHOTOS | 25 |

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SONY MOBILE COMMUNICATIONS, INC.
EUT DESCRIPTION: GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac & NFC
SERIAL NUMBER: CB5129YWE4
DATE TESTED: March 7 - 18, 2016

| APPLICABLE STANDARDS | |
|--------------------------|--------------|
| STANDARD | TEST RESULTS |
| CFR 47 Part 15 Subpart C | Pass |

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released
For UL Verification Services Inc. By:

Prepared By:



CHOON OOI
CONSUMER TECHNOLOGY DIVISION
PROJECT LEAD
UL VERIFICATION SERVICES INC

ROLLY ALEGRE
CONSUMER TECHNOLOGY DIVISION
WISE LAB ENGINEER
UL VERIFICATION SERVICES INC

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, and ANSI C63.10-2013.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

| 47173 Benicia Street | 47266 Benicia Street |
|---|------------------------------------|
| <input type="checkbox"/> Chamber A | <input type="checkbox"/> Chamber D |
| <input type="checkbox"/> Chamber B | <input type="checkbox"/> Chamber E |
| <input checked="" type="checkbox"/> Chamber C | <input type="checkbox"/> Chamber F |
| | <input type="checkbox"/> Chamber G |
| | <input type="checkbox"/> Chamber H |

The above test sites and facilities are covered under FCC Test Firm Registration # 208313.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0.

Chambers A through H are covered under Industry Canada company address code 2324B with site numbers 2324B -1 through 2324B-8, respectively.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss} \\ & \text{(dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| PARAMETER | UNCERTAINTY |
|---|-------------|
| Conducted Disturbance, 0.15 to 30 MHz | 3.52 dB |
| Radiated Disturbance, 9KHz to 30 MHz | 2.14 dB |
| Radiated Disturbance, 30 to 1000 MHz | 4.98 dB |
| Radiated Disturbance,1000 to 6000 MHz | 3.86 dB |
| Radiated Disturbance,6000 to 18000 MHz | 4.23 dB |
| Radiated Disturbance,18000 to 26000 MHz | 5.30 dB |
| Radiated Disturbance,26000 to 40000 MHz | 5.23 dB |

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE Phone with BT, DTS/UNII a/b/g/n/ac & NFC.

5.2. MAXIMUM OUTPUT POWER

The testing was performed at 1 meter. The transmitter maximum E-field at 30m distance is 23.61 dBuV/m which is converted from the 1 meter data.

5.3. WORST-CASE CONFIGURATION AND MODE

The NFC function was tested at its' fundamental and only operational frequency of 13.56 MHz. The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that the Z-orientation was the worst-case orientation, therefore, all final radiated testing was performed with the EUT in the Z-orientation while generating continuous emissions.

5.4. MODIFICATIONS

No modifications were made during testing.

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Radiated Emissions Above 30 MHz, AC Line Conducted Emissions and Frequency Stability:

| Support Equipment List | | | | |
|------------------------|--------------|-------------------|---------------|--------|
| Description | Manufacturer | Model | Serial Number | FCC ID |
| AC Adapter | Sony | UCH 20 1295-70821 | N/A | N/A |
| Earphone | Sony | N/A | N/A | N/A |

I/O CABLES

Radiated Emissions above 30 MHz, AC Line Conducted Emissions:


| I/O Cable List | | | | | | |
|----------------|----------|----------------------|----------------|-------------|------------------|---------|
| Cable No | Port | # of identical ports | Connector Type | Cable Type | Cable Length (m) | Remarks |
| 1 | DC Power | 1 | Micro-USB | Shielded | 1 m | None |
| 2 | Audio | 1 | Mini-Jack | Un-Shielded | 1 m | None |

TEST SETUP

The EUT is a stand-alone device configured and tested in a worst-case setup.

SETUP DIAGRAM FOR TESTS

Radiated Emissions Below 30 MHz:



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

| Test Equipment List | | | | |
|------------------------------------|----------------|---------------|-------|----------|
| Description | Manufacturer | Model | Asset | Cal Due |
| Spectrum Analyzer, 44 GHz | Agilent / HP | E4446A | T123 | 10/22/16 |
| Antenna, Loop, 30 MHz | EMCO | 6502 | T35 | 05/15/16 |
| Antenna, Biconolog, 30MHz-1 GHz | Sunol Sciences | JB1 | T243 | 09/25/16 |
| Preamplifier, 1300 MHz | Keysight | 8447D | T64 | 08/14/16 |
| EMI Test Receiver, 9 KHz to | Rohde & Schwa | ECSI7 | T284 | 09/10/16 |
| Peak Power Meter | Agilent / HP | N1914A | T254 | 06/08/16 |
| Peak / Average Power Sens | Keysight | E9327A | T388 | 04/16/16 |
| LISN, 30 MHz | Solar | 8012-50-R-24- | T28 | 07/28/16 |
| Temperature Chamber | CSZ | 2PHS-8-3 | T754 | 03/21/16 |

| Test Software List | | | |
|--------------------|--------------|--------|------------------------|
| Description | Manufacturer | Model | Version |
| Radiated Software | UL | UL EMC | Ver 9.5, June 24, 2015 |
| Conducted Software | UL | UL EMC | Ver 9.5, May 26, 2015 |

8. RADIATED EMISSION TEST RESULTS

LIMIT

§15.225

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110– 14.010 MHz and shall not exceed the general radiated emission limits in § 15.209 as follows:

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Limits for radiated disturbance of an intentional radiator | | |
|--|-----------------|--------------------------|
| Frequency range (MHz) | Limits (µV/m) | Measurement Distance (m) |
| 0.009 – 0.490 | 2400 / F (kHz) | 300 |
| 0.490 – 1.705 | 24000 / F (kHz) | 30 |
| 1.705 – 30.0 | 30 | 30 |
| 30 – 88 | 100** | 3 |
| 88 - 216 | 150** | 3 |
| 216 – 960 | 200** | 3 |
| Above 960 | 500 | 3 |

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

Formula for converting the filed strength from uV/m to dBuV/m is:

Limit (dBuV/m) = 20 log limit (uV/m)

In addition:

§15.209 (d) The emission limits shown the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

§15.209 (d) The provisions in §§ 15.225, measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

TEST PROCEDURE

ANSI C63.10-2013

The EUT is an intentional radiator that incorporates a digital device. The highest fundamental frequency generated or used in the device is 13.56 MHz. The frequency range was investigated from 0.15 MHz to the 10th harmonic of the highest fundamental frequency, or 1000 MHz, whichever is greater (1000MHz)

RESULTS

No non-compliance noted:

KDB 937606 OATS and Chamber Correlation Justification



- Device is a Smart Phone.
- Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.
- OATs and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

8.1.1. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz)

Fundamental

| FCC Part 15, Subpart B & C | | | | | | | | | | | | | 3 Meter Distance Measurement At Emissions Chamber | |
|---|-----------|-----------|-----------|-----------|--------------|--------------------------|-------------------------------|-------------------------------|-------------------|-------------------|----------------|----------------|---|--|
| Company: SOMC | | | | | | | | | | | | | | |
| Project #: 16J22997 | | | | | | | | | | | | | | |
| FCC ID #: PY7-PM0941 | | | | | | | | | | | | | | |
| Tester: Jude semana | | | | | | | | | | | | | | |
| Date: 3/11/2016 | | | | | | | | | | | | | | |
| Frequency (MHz) | PK (dBuV) | QP (dBuV) | AV (dBuV) | AF (dB/m) | Distance (m) | Distance Correction (dB) | PK Corrected Reading (dBuV/m) | AV Corrected Reading (dBuV/m) | QP Limit (dBuV/m) | AV Limit (dBuV/m) | PK Margin (dB) | AV Margin (dB) | Notes | |
| Loop Antenna Face On: Z-Position | | | | | | | | | | | | | | |
| Fundamental Field Strength & Within Bands: | | | | | | | | | | | | | | |
| 13.56 | 73.467 | | -- | 10.56 | 1 | -59.08 | 24.94 | -- | 84.00 | -- | -59.1 | -- | Fundamental @ 30m Dist | |
| 13.41 | 51.52 | | -- | 10.54 | 1 | -59.08 | 2.98 | -- | 50.48 | -- | -47.5 | -- | 13.41-13.553MHz Spurious @ 30m | |
| 13.553 | 67.83 | | -- | 10.56 | 1 | -59.08 | 19.30 | -- | 50.48 | -- | -31.2 | -- | 13.41-13.553MHz Spurious @ 30m | |
| 13.567 | 68.214 | | -- | 10.56 | 1 | -59.08 | 19.69 | -- | 50.48 | -- | -30.8 | -- | 13.567-13.710MHz Spurious @ 30m | |
| 13.664 | 52.651 | | -- | 10.57 | 1 | -59.08 | 4.13 | -- | 40.51 | -- | -36.4 | -- | 13.567-13.710MHz Spurious @ 30m | |
| 13.349 | 52.761 | | -- | 10.53 | 1 | -59.08 | 4.21 | -- | 40.51 | -- | -36.3 | -- | 13.110-13.410MHz Spurious @ 30m | |
| 13.772 | 50.967 | | -- | 10.58 | 1 | -59.08 | 2.46 | -- | 29.54 | -- | -27.1 | -- | 13.710-14.010MHz Spurious @ 30m | |
| Loop Antenna Face Off: Z-Position | | | | | | | | | | | | | | |
| Fundamental Field Strength & Within Bands: | | | | | | | | | | | | | | |
| 13.56 | 69.37 | | -- | 10.56 | 1 | -59.08 | 20.84 | -- | 84.00 | -- | -63.2 | -- | Fundamental @ 30m Dist | |
| 13.454 | 51.03 | | -- | 10.55 | 1 | -59.08 | 2.49 | -- | 50.48 | -- | -48.0 | -- | 13.41-13.553MHz Spurious @ 30m | |
| 13.553 | 62.88 | | -- | 10.56 | 1 | -59.08 | 14.35 | -- | 50.48 | -- | -36.1 | -- | 13.41-13.553MHz Spurious @ 30m | |
| 13.567 | 60.21 | | -- | 10.56 | 1 | -59.08 | 11.68 | -- | 50.48 | -- | -38.8 | -- | 13.567-13.710MHz Spurious @ 30m | |
| 13.66 | 50.43 | | -- | 10.57 | 1 | -59.08 | 1.91 | -- | 40.51 | -- | -38.6 | -- | 13.567-13.710MHz Spurious @ 30m | |
| 13.35 | 49.66 | | -- | 10.54 | 1 | -59.08 | 1.11 | -- | 40.51 | -- | -39.4 | -- | 13.110-13.410MHz Spurious @ 30m | |
| 13.773 | 50.88 | | -- | 10.58 | 1 | -59.08 | 2.37 | -- | 29.54 | -- | -27.2 | -- | 13.710-14.010MHz Spurious @ 30m | |
| Note: The emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 10000Mhz. Radiated emission limits in these three bands are based on measurements employing an average detector. | | | | | | | | | | | | | | |
| P.K. = Peak | | | | | | | | | | | | | | |
| Q.P. = Quasi Peak Readings | | | | | | | | | | | | | | |
| A.F. = Antenna factor | | | | | | | | | | | | | | |

Spurious Emissions (0.15 – 30 MHz)



Trace Markers

| Marker | Frequenc y (MHz) | Meter Reading (dBuV) | Det | Loop Antenna (dB/m) | Cbl (dB) | Dist Corr 300m | Corrected Reading (dBuVolts) | Peak Limit (dBuV/m) | Margin (dB) | Avg Limit (dBuV/m) | Margin (dB) | Azimuth (Degs) |
|--------|------------------------|----------------------------|-----|------------------------|----------|----------------|--|------------------------|----------------|-----------------------|----------------|-------------------|
| 6 | .03552 | 43 | Pk | 12.5 | 1.4 | -80 | -23.1 | 56.59 | -79.69 | 36.59 | -59.69 | 0-360 |
| 1 | .03553 | 42.18 | Pk | 12.5 | 1.4 | -80 | -23.92 | 56.59 | -80.51 | 36.59 | -60.51 | 0-360 |
| 2 | .0554 | 39.35 | Pk | 11.2 | 1.4 | -80 | -28.05 | 52.73 | -80.78 | 32.73 | -60.78 | 0-360 |
| 7 | .05603 | 38.04 | Pk | 11.2 | 1.4 | -80 | -29.36 | 52.64 | -82 | 32.64 | -62 | 0-360 |
| 8 | .07125 | 38.6 | Pk | 11 | 1.4 | -80 | -29 | 50.55 | -79.55 | 30.55 | -59.55 | 0-360 |
| 3 | .22723 | 44.43 | Pk | 10.8 | 1.5 | -80 | -23.27 | 40.48 | -63.75 | 20.48 | -43.75 | 0-360 |
| 9 | .31949 | 41.36 | Pk | 10.7 | 1.5 | -80 | -26.44 | 37.52 | -63.96 | 17.52 | -43.96 | 0-360 |



Pk - Peak detector

| Marker | Frequenc y (MHz) | Meter Reading (dBuV) | Det | Loop Antenna (dB/m) | Cbl (dB) | Dist Corr 30m | Corrected Reading (dBuVolts) | Peak Limit (dBuV/m) | Margin (dB) | Avg Limit (dBuV/m) | Margin (dB) | Azimuth (Degs) |
|--------|------------------------|----------------------------|-----|------------------------|----------|---------------|--|------------------------|----------------|-----------------------|----------------|-------------------|
| 4 | .71728 | 34.8 | Pk | 10.6 | 1.5 | -40 | 6.9 | 30.49 | -23.59 | - | - | 0-360 |
| 10 | 1.01056 | 31.15 | Pk | 10.7 | 1.5 | -40 | 3.35 | 27.51 | -24.16 | - | - | 0-360 |
| 11 | 4.31976 | 19.53 | Pk | 10.9 | 1.5 | -40 | -8.07 | 29.54 | -37.61 | - | - | 0-360 |
| 5 | 5.73089 | 16.45 | Pk | 10.9 | 1.5 | -40 | -11.15 | 29.54 | -40.69 | - | - | 0-360 |

Pk - Peak detector

FCC 15.209 Below 30MHz.TST 30915 30 Dec 2015
 Rev 9.5 07 Jan 2016

8.1.2. TX SPURIOUS EMISSION 30 TO 1000 MHz



Trace Markers

| Marker | Frequency (MHz) | Meter Reading (dBuV) | Det | AF T185 (dB/m) | Amp/Cbl (dB) | Corrected Reading (dBuV/m) | QPk Limit (dBuV/m) | Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|----------------|--------------|----------------------------|--------------------|-------------|----------------|-------------|----------|
| 1 | 30.9775 | 31.04 | Pk | 20.9 | -27.2 | 24.74 | 40 | -15.26 | 0-360 | 200 | H |
| 4 | 40.455 | 40.5 | Pk | 13.9 | -27 | 27.4 | 40 | -12.6 | 0-360 | 100 | V |
| 2 | 53.1625 | 30.84 | Pk | 7.4 | -26.9 | 11.34 | 40 | -28.66 | 0-360 | 300 | H |
| 5 | 66.5075 | 37.64 | Pk | 8.1 | -26.7 | 19.04 | 40 | -20.96 | 0-360 | 100 | V |
| 3 | 439.6 | 30.66 | Pk | 16.9 | -24.9 | 22.66 | 46.02 | -23.36 | 0-360 | 100 | H |
| 6 | 712.7 | 30.68 | Pk | 20.3 | -24.1 | 26.88 | 46.02 | -19.14 | 0-360 | 400 | V |

* - indicates frequency in 47 CFR §15.205/IC RSS-Gen §8.10 Restricted Band

Pk - Peak detector

9. AC MAINS LINE CONDUCTED EMISSIONS

LIMITS

§15.207

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

| Frequency range (MHz) | Limits (dB μ V) | |
|--------------------------|---------------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

Notes:
1. The lower limit shall apply at the transition frequencies
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.10.


The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.


RESULTS

No non-compliance noted:

LINE 1 PLOT



LINE 2 PLOT



LINE 1 & LINE 2 RESULTS

Trace Markers

| Range 1: Line-L1 .15 - 30MHz | | | | | | | | | | | |
|------------------------------|-----------------|----------------------|-----|-----------|---------------|--------------|------------------------|---------------------------|----------------|----------------------------|-----------------------|
| Marker | Frequency (MHz) | Meter Reading (dBuV) | Det | T24 IL L1 | LC Cables 1&3 | Limiter (dB) | Corrected Reading dBuV | CFR 47 Part 15 Class B QP | QP Margin (dB) | CFR 47 Part 15 Class B Avg | Av(CISPR) Margin (dB) |
| 1 | .411 | 22.54 | Qp | .4 | 0 | 10.1 | 33.04 | 57.63 | -24.59 | - | - |
| 2 | .4155 | 7.13 | Ca | .4 | 0 | 10.1 | 17.63 | - | - | 47.54 | -29.91 |
| 3 | 1.19625 | 12.96 | Qp | .3 | .1 | 10.1 | 23.46 | 56 | -32.54 | - | - |
| 4 | 1.194 | 3.04 | Ca | .3 | .1 | 10.1 | 13.54 | - | - | 46 | -32.46 |
| 5 | 1.5855 | 12.9 | Qp | .2 | .1 | 10.1 | 23.3 | 56 | -32.7 | - | - |
| 6 | 1.5855 | 2.84 | Ca | .2 | .1 | 10.1 | 13.24 | - | - | 46 | -32.76 |
| 7 | 2.31675 | 12.63 | Qp | .2 | .1 | 10.1 | 23.03 | 56 | -32.97 | - | - |
| 8 | 2.31675 | 3.07 | Ca | .2 | .1 | 10.1 | 13.47 | - | - | 46 | -32.53 |
| 9 | 2.70488 | 12.89 | Qp | .2 | .1 | 10.1 | 23.29 | 56 | -32.71 | - | - |
| 10 | 2.71163 | 3.47 | Ca | .2 | .1 | 10.1 | 13.87 | - | - | 46 | -32.13 |
| 11 | 13.56 | 36.84 | Qp | .2 | .2 | 10.2 | 47.44 | 60 | -12.56 | - | - |
| 12 | 13.56 | 25.21 | Ca | .2 | .2 | 10.2 | 35.81 | - | - | 50 | -14.19 |

Qp - Quasi-Peak detector

Ca - CISPR average detection

| Range 2: Line-L2 .15 - 30MHz | | | | | | | | | | | |
|------------------------------|-----------------|----------------------|-----|-----------|---------------|--------------|------------------------|---------------------------|----------------|----------------------------|-----------------------|
| Marker | Frequency (MHz) | Meter Reading (dBuV) | Det | T24 IL L2 | LC Cables 2&3 | Limiter (dB) | Corrected Reading dBuV | CFR 47 Part 15 Class B QP | QP Margin (dB) | CFR 47 Part 15 Class B Avg | Av(CISPR) Margin (dB) |
| 13 | .411 | 21.28 | Qp | .4 | 0 | 10.1 | 31.78 | 57.63 | -25.85 | - | - |
| 14 | .41325 | 5.43 | Ca | .4 | 0 | 10.1 | 15.93 | - | - | 47.58 | -31.65 |
| 15 | 1.1985 | 11.2 | Qp | .2 | .1 | 10.1 | 21.6 | 56 | -34.4 | - | - |
| 16 | 1.203 | -0.5 | Ca | .2 | .1 | 10.1 | 10.35 | - | - | 46 | -35.65 |
| 17 | 1.59 | 10.14 | Qp | .2 | .1 | 10.1 | 20.54 | 56 | -35.46 | - | - |
| 18 | 1.5855 | -6 | Ca | .2 | .1 | 10.1 | 9.8 | - | - | 46 | -36.2 |
| 19 | 2.31 | 10.89 | Qp | .2 | .1 | 10.1 | 21.29 | 56 | -34.71 | - | - |
| 20 | 2.319 | .84 | Ca | .2 | .1 | 10.1 | 11.24 | - | - | 46 | -34.76 |
| 21 | 2.7195 | 10.5 | Qp | .2 | .1 | 10.1 | 20.9 | 56 | -35.1 | - | - |
| 22 | 2.715 | 1.01 | Ca | .2 | .1 | 10.1 | 11.41 | - | - | 46 | -34.59 |
| 23 | 13.56 | 32.51 | Qp | .2 | .2 | 10.2 | 43.11 | 60 | -16.89 | - | - |
| 24 | 13.56 | 20.83 | Ca | .2 | .2 | 10.2 | 31.43 | - | - | 50 | -18.57 |

Qp - Quasi-Peak detector

Ca - CISPR average detection

10. FREQUENCY STABILITY

LIMIT

§15.225 (e) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency, over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.

TEST PROCEDURE

ANSI C63.10-2013

RESULTS

No non-compliance noted.

Frequency stability versus temperature & apply voltage

| Reference Frequency: EUT Channel 13.560000 MHz @ 20°C Limit: ± 100 ppm = 1.356 kHz | | | | |
|---|------------------------------|---|--------------|--------------|
| Power Supply (Vdc) | Environment Temperature (°C) | Frequency Deviation Measured with Time Elapse | | |
| | | (MHz) | Delta (ppm) | Limit (ppm) |
| 5.00 | 50 | 13.5598988 | -4.143 | ± 100 |
| 5.00 | 40 | 13.5598654 | -1.680 | ± 100 |
| 5.00 | 30 | 13.5598627 | -1.477 | ± 100 |
| 5.00 | 20 | 13.5598427 | 0.000 | ± 100 |
| 5.00 | 10 | 13.5598425 | 0.009 | ± 100 |
| 5.00 | 0 | 13.5598976 | -4.055 | ± 100 |
| 5.00 | -10 | 13.5598877 | -3.319 | ± 100 |
| 5.00 | -20 | 13.559756 | -9.801 | ± 100 |
| 5.00 | -30 | 13.5599765 | -9.870 | ± 100 |
| 4.25 | 20 | 13.5598723 | -2.183 | ± 100 |
| 5.75 | 20 | 13.5598652 | -1.663 | ± 100 |

Note: Frequency stability versus time interval measurements were taken and worst case results are reported in the above table.