

FCC RF Test Report


APPLICANT : Sony Mobile Communications Inc.
EQUIPMENT : Smart phone
BRAND NAME : Sony
FCC ID : PY7-PM0952
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on Feb. 04, 2016 and testing was completed on Feb. 26, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : PY7-PM0952

Page Number : 1 of 71

Report Issued Date : May 10, 2016

Report Version : Rev. 02

Report Template No.: BU5-FR15CBT Version 1.0



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Modification of EUT	6
1.5 Testing Location	6
1.6 Applicable Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Descriptions of Test Mode	8
2.2 Test Mode	9
2.3 Connection Diagram of Test System	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example	11
3 TEST RESULT	12
3.1 Number of Channel Measurement	12
3.2 Hopping Channel Separation Measurement	14
3.3 Dwell Time Measurement	21
3.4 20dB and 99% Bandwidth Measurement	24
3.5 Peak Output Power Measurement	37
3.6 Conducted Band Edges Measurement	39
3.7 Conducted Spurious Emission Measurement	46
3.8 Radiated Band Edges and Spurious Emission Measurement	56
3.9 AC Conducted Emission Measurement	64
3.10 Antenna Requirements	68
4 LIST OF MEASURING EQUIPMENT	69
5 UNCERTAINTY OF EVALUATION	71
APPENDIX A. RADIATED SPURIOUS EMISSION	
APPENDIX B. RADIATED SPURIOUS EMISSION PLOT	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR620405A	Rev. 01	Initial issue of report	Apr. 28, 2016
FR620405A	Rev. 02	Updating EUT information in section 1.3.	May 10, 2016



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	NA	Pass	-
3.4	-	99% Bandwidth	-	Pass	-
3.5	15.247(b)(1)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 9.71 dB at 30.270 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 15.90 dB at 0.478 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Sony Mobile Communications Inc.

4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

1.2 Manufacturer

Sony Mobile Communications Inc.

4-12-3 Higashi-Shinagawa, Shinagawa-ku, Tokyo, 140-0002, Japan

1.3 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, DTS/UNII, a/b/g/n, GPS and NFC

Product Specification subjective to this standard				
Antenna Type		Bluetooth : PIFA Antenna type with gain -2.30 dBi		
EUT Information List				
IMEI	HW Version	SW Version	S/N	Performed Test Item
004402455816987	A	36.0.A.1.28	WUJ01M8LEX	RF conducted measurement
004402455814016			WUJ01M8BA5	Radiated Spurious Emission
004402455814008			WUJ01M8BA4	Conducted Emission

Accessory List	
AC Adapter	Model No. : UCH20
	Type No. : AC-0060-US
	S/N :
	1315W52500072 (for radiated spurious emission) 1315W52500025 (for conducted emission)
Earphone	Model No. : MH410c
	Type No. : AG-1110
	S/N :
	1435204403A9122 (for radiated spurious emission) 14321E5F00817B2 (for conducted emission)
USB Cable	Model No. : UCB16
	Type No. : AI-0142
	S/N :
	1602A901000542E (for radiated spurious emission) 1602A90A000378C (for conducted emission)

Note:

1. Above EUT list and accessory list used are electrically identical per declared by manufacturer.
2. Above the accessories list are used to exercise the EUT during test.
3. For other wireless features of this EUT, test report will be issued separately.

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		
	TH05-HY	CO05-HY	03CH07-HY

Note: The test site complies with ANSI C63.4 2014 requirement.



1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	6.98 dBm	6.16 dBm	6.45 dBm
Ch39	2441MHz	7.24 dBm	6.66 dBm	6.88 dBm
Ch78	2480MHz	7.07 dBm	6.32 dBm	6.53 dBm

Remark:

1. All the test data for each data rate were verified, but only the worst case was reported.
 2. The data rate was set in 1Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (Y plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.


2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
AC Conducted Emission	Mode 1 :GSM1900 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		
Remark: For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and the conducted spurious emissions and conducted band edge measurement for each data rate are no worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	WLAN AP	D-Link	DIR-865L	KA2IR865LA1	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Bluetooth Earphone	Samsung	SBH20	PY7-RD0010	Unshielded, 0.75 m	N/A
6.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth test items, an engineering test program was provided and enabled to make EUT contact with Bluetooth base station for continuous transmitting and receiving signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency


Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 9.FEB.2016 10:11:28



Date: 9.FEB.2016 10:14:31

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup






3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.6240	Pass
39	2441	1.008	0.6213	Pass
78	2480	1.002	0.6187	Pass


Channel Separation Plot on Channel 00 - 01



Date: 9.FEB.2016 10:02:41




Channel Separation Plot on Channel 39 - 40



Date: 9.FEB.2016 10:32:38

Channel Separation Plot on Channel 77 - 78




Date: 9.FEB.2016 10:36:58



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	0.996	0.8440	Pass
39	2441	1.008	0.8440	Pass
78	2480	1.002	0.8440	Pass

Channel Separation Plot on Channel 00 - 01

Date: 9.FEB.2016 10:42:14




Channel Separation Plot on Channel 39 - 40



Date: 9.FEB.2016 10:45:56

Channel Separation Plot on Channel 77 - 78




Date: 9.FEB.2016 10:49:46



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	0.996	0.8280	Pass
39	2441	1.014	0.8360	Pass
78	2480	1.008	0.8360	Pass

Channel Separation Plot on Channel 00 - 01

Date: 9.FEB.2016 10:55:25




Channel Separation Plot on Channel 39 - 40



Date: 9.FEB.2016 11:07:21

Channel Separation Plot on Channel 77 - 78



Date: 9.FEB.2016 11:11:36

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Test Mode :	DH5	Temperature :	24~26℃
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%


Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.88	0.31	0.4	Pass
AFH	20	53.34	2.88	0.15	0.4	Pass

Remark:

- In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
- In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
- Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Package Transfer Time Plot



Date: 8.FEB.2016 12:21:03

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 99% bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup






3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.936
39	2441	0.932
78	2480	0.928


20 dB Bandwidth Plot on Channel 00



Date: 9.FEB.2016 10:05:03




20 dB Bandwidth Plot on Channel 39



Date: 9.FEB.2016 10:33:10

20 dB Bandwidth Plot on Channel 78




Date: 4.MAR.2016 15:37:02



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.266
39	2441	1.266
78	2480	1.266

20 dB Bandwidth Plot on Channel 00

Date: 9.FEB.2016 10:42:51




20 dB Bandwidth Plot on Channel 39



Date: 9.FEB.2016 10:46:40

20 dB Bandwidth Plot on Channel 78




Date: 9.FEB.2016 10:50:36



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.242
39	2441	1.254
78	2480	1.254

20 dB Bandwidth Plot on Channel 00

Date: 9.FEB.2016 10:55:54




20 dB Bandwidth Plot on Channel 39



Date: 9.FEB.2016 11:08:33

20 dB Bandwidth Plot on Channel 78



Date: 9.FEB.2016 11:12:07




3.4.6 Test Result of 99% Occupied Bandwidth

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	0.864
39	2441	0.860
78	2480	0.844


99% Occupied Bandwidth Plot on Channel 00



Date: 9.FEB.2016 10:27:24




99% Occupied Bandwidth Plot on Channel 39



Date: 9.FEB.2016 10:33:49

99% Occupied Bandwidth Plot on Channel 78




Date: 9.FEB.2016 10:39:33



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.164
39	2441	1.168
78	2480	1.164

99% Occupied Bandwidth Plot on Channel 00

Date: 9.FEB.2016 10:43:54




99% Occupied Bandwidth Plot on Channel 39



Date: 9.FEB.2016 10:47:32

99% Occupied Bandwidth Plot on Channel 78




Date: 9.FEB.2016 10:51:54



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.148
39	2441	1.156
78	2480	1.152

99% Occupied Bandwidth Plot on Channel 00

Date: 9.FEB.2016 10:57:01




99% Occupied Bandwidth Plot on Channel 39



Date: 9.FEB.2016 11:09:33

99% Occupied Bandwidth Plot on Channel 78



Date: 9.FEB.2016 11:13:19

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps is 1watt, and for 2Mbps, 3Mbps and AFH are 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	6.98	20.97	Pass
39	2441	7.24	20.97	Pass
78	2480	7.07	20.97	Pass

Note: For AFH mode using 20 hopping channels, the maximum output power limit is 20.97dBm.

Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	6.16	20.97	Pass
39	2441	6.66	20.97	Pass
78	2480	6.32	20.97	Pass

Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	6.45	20.97	Pass
39	2441	6.88	20.97	Pass
78	2480	6.53	20.97	Pass

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup




**3.6.5 Test Result of Conducted Band Edges**

Test Mode :	1Mbps	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

Low Band Edge Plot on Channel 00


Date: 9.FEB.2016 10:35:24

High Band Edge Plot on Channel 78


Date: 9.FEB.2016 10:38:40



Test Mode :	2Mbps	Temperature :	24~26℃
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

Low Band Edge Plot on Channel 00


Date: 9.FEB.2016 10:43:19

High Band Edge Plot on Channel 78


Date: 9.FEB.2016 10:51:06



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

Low Band Edge Plot on Channel 00

Date: 9.FEB.2016 10:56:25

High Band Edge Plot on Channel 78


Date: 9.FEB.2016 11:12:39



3.6.6 Test Result of Conducted Hopping Mode Band Edges


Test Mode :	1Mbps	Temperature :	24~26℃
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%

1Mbps Hopping Mode Low Band Edge Plot



Date: 9.FEB.2016 10:16:06


1Mbps Hopping Mode High Band Edge Plot




Date: 9.FEB.2016 10:17:17



Test Mode :	2Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%

2Mbps Hopping Mode Low Band Edge Plot


Date: 9.FEB.2016 10:19:22

2Mbps Hopping Mode High Band Edge Plot


Date: 9.FEB.2016 10:21:03



Test Mode :	3Mbps	Temperature :	24~26°C
Test Engineer :	Luffy Lin	Relative Humidity :	48~51%

3Mbps Hopping Mode Low Band Edge Plot

Date: 9.FEB.2016 10:23:43

3Mbps Hopping Mode High Band Edge Plot

Date: 9.FEB.2016 10:25:32

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 9.FEB.2016 10:28:50


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz




Date: 9.FEB.2016 10:29:12



Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 9.FEB.2016 10:34:24

1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 9.FEB.2016 10:34:46



Test Mode :	1Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 9.FEB.2016 10:40:04

1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 9.FEB.2016 10:40:26



Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz


Date: 9.FEB.2016 10:44:34

2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 9.FEB.2016 10:44:56



Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 9.FEB.2016 10:48:00

2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 9.FEB.2016 10:48:21



Test Mode :	2Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 9.FEB.2016 10:53:15

2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 9.FEB.2016 10:53:37



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz


Date: 9.FEB.2016 10:58:34

3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 9.FEB.2016 10:58:55



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 9.FEB.2016 11:09:59

3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 9.FEB.2016 11:10:21



Test Mode :	3Mbps	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	48~51%
		Test Engineer :	Luffy Lin

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz

Date: 9.FEB.2016 11:13:45

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz

Date: 9.FEB.2016 11:14:07



3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.8.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.




3.8.6 Duty cycle correction factor for average measurement

<1Mbps>

DH5 on time (One Pulse) Plot on Channel 39



DH5 on time (Count Pulses) Plot on Channel 39


**Note:**

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.87 / 100 = 5.74 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.82 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.




<2Mbps>

2DH5 on time (One Pulse) Plot on Channel 39



2DH5 on time (Count Pulses) Plot on Channel 39




Note:


1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. 2DH5 has the highest duty cycle worst case and is reported.

<3Mbps>

3DH5 on time (One Pulse) Plot on Channel 39



3DH5 on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.87 / 100 = 5.74 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.82 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.

**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.87 \text{ ms} \times 20 \text{ channels} = 57.4 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.87 \text{ ms} \times 2 = 5.74 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.74 \text{ ms}/100\text{ms}) = -24.82 \text{ dB}$$

3.8.7 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A and B.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A and B.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	23~24℃
Test Engineer :	Kai-Chun Chu	Relative Humidity :	48~49%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		




Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	41.3	Off	L1	19.6	24.3	65.6
0.190000	39.5	Off	L1	19.6	24.5	64.0
0.294000	34.5	Off	L1	19.6	25.9	60.4
0.374000	33.4	Off	L1	19.6	25.0	58.4
0.478000	40.5	Off	L1	19.6	15.9	56.4
1.446000	33.3	Off	L1	19.6	22.7	56.0
3.494000	31.7	Off	L1	19.6	24.3	56.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	29.0	Off	L1	19.6	26.6	55.6
0.190000	28.0	Off	L1	19.6	26.0	54.0
0.294000	26.4	Off	L1	19.6	24.0	50.4
0.374000	25.5	Off	L1	19.6	22.9	48.4
0.478000	28.5	Off	L1	19.6	17.9	46.4
1.446000	24.5	Off	L1	19.6	21.5	46.0
3.494000	21.4	Off	L1	19.6	24.6	46.0

Test Mode :	Mode 1	Temperature :	23~24°C
Test Engineer :	Kai-Chun Chu	Relative Humidity :	48~49%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Camera + Earphone + USB Cable (Charging from Adapter)		


Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	38.5	Off	N	19.6	27.1	65.6
0.214000	34.7	Off	N	19.6	28.3	63.0
0.422000	31.4	Off	N	19.6	26.0	57.4
0.510000	31.1	Off	N	19.6	24.9	56.0
0.750000	26.4	Off	N	19.6	29.6	56.0
1.438000	28.7	Off	N	19.6	27.3	56.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	27.4	Off	N	19.6	28.2	55.6
0.214000	25.2	Off	N	19.6	27.8	53.0
0.422000	23.7	Off	N	19.6	23.7	47.4
0.510000	24.1	Off	N	19.6	21.9	46.0
0.750000	21.8	Off	N	19.6	24.2	46.0
1.438000	23.1	Off	N	19.6	22.9	46.0



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Jan. 08, 2016	Feb. 08, 2016 ~ Feb. 09, 2016	Jan. 07, 2017	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Jan. 07, 2016	Feb. 08, 2016 ~ Feb. 09, 2016	Jan. 06, 2017	Conducted (TH05-HY)
Hygrometer	Testo	608-H2	41410069	N/A	Aug. 27, 2015	Feb. 08, 2016 ~ Feb. 09, 2016	Aug. 26, 2016	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 23, 2015	Feb. 08, 2016 ~ Feb. 09, 2016	Nov. 22, 2016	Conducted (TH05-HY)
RF Cable	JYEBAO	K30K30-50 03-1.5M40	N/A	0.1MHz~40GHz	Mar. 18, 2015	Feb. 08, 2016 ~ Feb. 09, 2016	Mar. 17, 2016	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000 W	N/A	N/A	N/A	Feb. 22, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	Feb. 22, 2016	Aug. 25, 2016	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Apr. 20, 2015	Feb. 22, 2016	Apr. 19, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Feb. 22, 2016	Dec. 01, 2016	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 06, 2016	Feb. 22, 2016	Jan. 05, 2017	Conduction (CO05-HY)
Test Software	N/A	EMC32	8.40.0	N/A	N/A	Feb. 22, 2016	N/A	Conduction (CO05-HY)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D	35419	30MHz to 1GHz	Jan. 13, 2016	Feb. 23, 2016 ~ Feb. 26, 2016	Jan. 12, 2017	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 21, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	Aug. 20, 2016	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz- 40GHz	Oct. 12, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	Oct. 11, 2016	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	Sep. 01, 2016	Radiation (03CH07-HY)
Hygrometer	Testo	608-H1	34897197	N/A	May 04, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	May 03, 2016	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-00101800-30-10P	1590075	1GHz ~ 18GHz	Apr. 20, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	Apr. 19, 2016	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1000MHz	Mar. 12, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	Mar. 11, 2016	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Oct. 19, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	Oct. 18, 2016	Radiation (03CH07-HY)
Preamplifier	MITEQ	JS44-18004000-33-8P	1840917	18GHz ~ 40GHz	Jun. 02, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	Jun. 01, 2016	Radiation (03CH07-HY)
Spectrum Analyzer	Agilent	N9010A	MY53470118	10Hz~44GHz	Mar. 03, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	Mar. 02, 2016	Radiation (03CH07-HY)
Controller	ChainTek	Chaintek 3000	N/A	Control Turn table	N/A	Feb. 23, 2016 ~ Feb. 26, 2016	N/A	Radiation (03CH07-HY)
Controller	Max-Full	MF7802	MF780208368	Control Ant Mast	N/A	Feb. 23, 2016 ~ Feb. 26, 2016	N/A	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Feb. 23, 2016 ~ Feb. 26, 2016	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 degree	N/A	Feb. 23, 2016 ~ Feb. 26, 2016	N/A	Radiation (03CH07-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY84209521	9KHz~40GHz	Dec. 03, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	Dec. 02, 2016	Radiation (03CH07-HY)
EMI Test Receiver	Agilent Technologies	N9038A(MXE)	MY53290045	20MHz~8.4GHz	Feb. 01, 2016	Feb. 23, 2016 ~ Feb. 26, 2016	Jan. 31, 2017	Radiation (03CH07-HY)
Test Software	N/A	E3	6.2009-8-24 (sporton)	N/A	N/A	Feb. 23, 2016 ~ Feb. 26, 2016	N/A	Radiation (03CH07-HY)
Filter	Wainwright	WLKS1200-8SS	SN3	1.2G Low Pass	Oct. 01, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	Sep. 30, 2016	Radiation (03CH07-HY)
Filter	Microwave	H3G018G1	SN477220	3.0G High Pass	Oct. 01, 2015	Feb. 23, 2016 ~ Feb. 26, 2016	Sep. 30, 2016	Radiation (03CH07-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.60
---	------



Appendix A. Radiated Spurious Emission

Test Engineer :	Ken Wu, James Chiu, and Jesse Wang	Temperature :	21~24°C
		Relative Humidity :	50~54%

<1Mbps>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH00 2402MHz		2369.02	46.85	-27.15	74	41.81	32.16	7.24	34.36	109	0	P	H
		2369.02	22.03	-31.97	54	-	-	-	-	-	-	A	H
	*	2402	96.41	-	-	91.24	32.18	7.31	34.32	109	0	P	H
	*	2402	71.59	-	-	-	-	-	-	-	-	A	H
													H
													H
		2324.56	47.94	-26.06	74	43.11	32.09	7.18	34.44	214	35	P	V
		2324.56	23.12	-30.88	54	-	-	-	-	-	-	A	V
	*	2402	98.21	-	-	93.04	32.18	7.31	34.32	214	35	P	V
	*	2402	73.39	-	-	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		2330.9	47.33	-26.67	74	42.5	32.09	7.18	34.44	112	0	P	H
		2330.9	22.51	-31.49	54	-	-	-	-	-	-	A	H
	*	2441	98.27	-	-	92.9	32.24	7.36	34.23	112	0	P	H
	*	2441	73.45	-	-	-	-	-	-	-	-	A	H
		2490.69	47.57	-26.43	74	42.06	32.3	7.4	34.19	112	0	P	H
		2490.69	22.75	-31.25	54	-	-	-	-	-	-	A	H
		2371.94	46.78	-27.22	74	41.74	32.16	7.24	34.36	150	4	P	V
		2371.94	21.96	-32.04	54	-	-	-	-	-	-	A	V
	*	2441	99.44	-	-	94.07	32.24	7.36	34.23	150	4	P	V
	*	2441	74.62	-	-	-	-	-	-	-	-	A	V
		2496.2	48.17	-25.83	74	42.62	32.3	7.4	34.15	150	4	P	V
		2496.2	23.35	-30.65	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480.12	98.31	-	-	92.82	32.28	7.4	34.19	328	359	P	H
	*	2480.12	73.49	-	-	-	-	-	-	-	-	A	H
		2484.04	47.01	-26.99	74	41.52	32.28	7.4	34.19	328	359	P	H
		2484.04	22.19	-31.81	54	-	-	-	-	-	-	A	H
													H
													H
	*	2479.91	99.1	-	-	93.61	32.28	7.4	34.19	226	62	P	V
	*	2479.91	74.28	-	-	-	-	-	-	-	-	A	V
		2483.52	47.51	-26.49	74	42.02	32.28	7.4	34.19	226	62	P	V
		2483.52	22.69	-31.31	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	43.84	-30.16	74	57.43	34.25	11.83	59.67	100	0	P	H
		4804	19.02	-34.98	54	-	-	-	-	-	-	A	H
													H
													H
		4804	41.12	-32.88	74	54.71	34.25	11.83	59.67	100	0	P	V
		4804	16.3	-37.7	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	43.32	-30.68	74	57.06	34.3	11.53	59.57	100	0	P	H
		4882	18.5	-35.5	54	-	-	-	-	-	-	A	H
		7323	40.27	-33.73	74	49.35	35.6	13.81	58.49	100	0	P	H
		7323	15.45	-38.55	54	-	-	-	-	-	-	A	H
		4882	39.86	-34.14	74	53.6	34.3	11.53	59.57	100	0	P	V
		4882	15.04	-38.96	54	-	-	-	-	-	-	A	V
		7323	39.97	-34.03	74	49.05	35.6	13.81	58.49	100	0	P	V
		7323	15.15	-38.85	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	42.56	-31.44	74	56.42	34.37	11.22	59.45	100	0	P	H
		4960	17.74	-36.26	54	-	-	-	-	-	-	A	H
		7440	41.93	-32.07	74	50.92	35.6	14.05	58.64	100	0	P	H
		7440	17.11	-36.89	54	-	-	-	-	-	-	A	H
		4960	41.25	-32.75	74	55.11	34.37	11.22	59.45	100	0	P	V
		4960	16.43	-37.57	54	-	-	-	-	-	-	A	V
		7440	40.94	-33.06	74	49.93	35.6	14.05	58.64	100	0	P	V
		7440	16.12	-37.88	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



<2Mbps>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH00 2402MHz		2338.86	47.93	-26.07	74	43.04	32.11	7.18	34.4	109	0	P	H
		2338.86	23.14	-30.86	54	-	-	-	-	-	-	A	H
	*	2402	95.19	-	-	90.02	32.18	7.31	34.32	109	0	P	H
	*	2402	70.4	-	-	-	-	-	-	-	-	A	H
													H
													H
		2377.08	46.92	-27.08	74	41.88	32.16	7.24	34.36	214	35	P	V
		2377.08	22.13	-31.87	54	-	-	-	-	-	-	A	V
	*	2402	96.92	-	-	91.75	32.18	7.31	34.32	214	35	P	V
	*	2402	72.13	-	-	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		2378.78	46.67	-27.33	74	41.63	32.16	7.24	34.36	112	0	P	H
		2378.78	21.88	-32.12	54	-	-	-	-	-	-	A	H
	*	2441	96.99	-	-	91.62	32.24	7.36	34.23	112	0	P	H
	*	2441	72.2	-	-	-	-	-	-	-	-	A	H
		2492.97	47.03	-26.97	74	41.48	32.3	7.4	34.15	112	0	P	H
		2492.97	22.24	-31.76	54	-	-	-	-	-	-	A	H
		2386.95	47.49	-26.51	74	42.36	32.18	7.31	34.36	150	5	P	V
		2386.95	22.7	-31.3	54	-	-	-	-	-	-	A	V
	*	2441	98.4	-	-	93.03	32.24	7.36	34.23	150	5	P	V
	*	2441	73.61	-	-	-	-	-	-	-	-	A	V
		2491.83	47.09	-26.91	74	41.54	32.3	7.4	34.15	150	5	P	V
		2491.83	22.3	-31.7	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	98.2	-	-	92.71	32.28	7.4	34.19	376	221	P	H
	*	2480	73.41	-	-	-	-	-	-	-	-	A	H
		2484.32	48.15	-25.85	74	42.66	32.28	7.4	34.19	376	221	P	H
		2484.32	23.36	-30.64	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	96.97	-	-	91.48	32.28	7.4	34.19	373	12	P	V
	*	2480	72.18	-	-	-	-	-	-	-	-	A	V
		2486.21	48.5	-25.5	74	43.01	32.28	7.4	34.19	373	12	P	V
		2486.21	23.71	-30.29	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	41.76	-32.24	74	55.35	34.25	11.83	59.67	100	0	P	H
		4804	16.97	-37.03	54	-	-	-	-	-	-	A	H
													H
													H
		4804	41.16	-32.84	74	54.75	34.25	11.83	59.67	100	0	P	V
		4804	16.37	-37.63	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	40.9	-33.1	74	54.64	34.3	11.53	59.57	100	0	P	H
		4882	16.11	-37.89	54	-	-	-	-	-	-	A	H
		7323	40.27	-33.73	74	49.35	35.6	13.81	58.49	100	0	P	H
		7323	15.48	-38.52	54	-	-	-	-	-	-	A	H
		4882	40.26	-33.74	74	54	34.3	11.53	59.57	100	0	P	V
		4882	15.47	-38.53	54	-	-	-	-	-	-	A	V
		7323	42.03	-31.97	74	51.11	35.6	13.81	58.49	100	0	P	V
		7323	17.24	-36.76	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	40.97	-33.03	74	54.83	34.37	11.22	59.45	100	0	P	H
		4960	16.18	-37.82	54	-	-	-	-	-	-	A	H
		7440	40.85	-33.15	74	49.84	35.6	14.05	58.64	100	0	P	H
		7440	16.06	-37.94	54	-	-	-	-	-	-	A	H
		4960	40.7	-33.3	74	54.56	34.37	11.22	59.45	100	0	P	V
		4960	15.91	-38.09	54	-	-	-	-	-	-	A	V
		7440	41.46	-32.54	74	50.45	35.6	14.05	58.64	100	0	P	V
		7440	16.67	-37.33	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
2.4GHz BT LF		30.54	27.79	-12.21	40	32.72	25.46	1.07	31.46	100	0	P	H
		98.31	22.69	-20.81	43.5	36.37	16.14	1.28	31.1	-	-	P	H
		159.87	25.98	-17.52	43.5	38.4	17	1.78	31.2	-	-	P	H
		454	26.16	-19.84	46	30.86	23.18	2.89	30.77	-	-	P	H
		714.4	29.3	-16.7	46	29.32	26.64	3.74	30.4	-	-	P	H
		964.3	33.42	-20.58	54	29.47	30.23	4.07	30.35	-	-	P	H
													H
													H
													H
													H
													H
													H
		30.27	30.29	-9.71	40	34.72	26	1.07	31.5	100	0	P	V
		62.94	24.8	-15.2	40	42.55	12.21	1.28	31.24	-	-	P	V
		288.12	28.19	-17.81	46	37.31	19.62	2.32	31.06	-	-	P	V
		426	25.06	-20.94	46	30.18	22.76	2.89	30.77	-	-	P	V
		761.3	30.48	-15.52	46	29.72	27.32	3.82	30.38	-	-	P	V
		860.7	33.66	-12.34	46	31.11	28.76	4.17	30.38	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



<3Mbps>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH00 2402MHz		2314.68	46.64	-27.36	74	41.83	32.07	7.18	34.44	109	0	P	H
		2314.68	21.82	-32.18	54	-	-	-	-	-	-	AA	H
	*	2402	95.33	-	-	90.16	32.18	7.31	34.32	109	0	P	H
	*	2402	70.51	-	-	-	-	-	-	-	-	AA	H
													H
													H
		2323.13	47.45	-26.55	74	42.62	32.09	7.18	34.44	214	35	P	V
		2323.13	22.63	-31.37	54	-	-	-	-	-	-	AA	V
	*	2402	97.17	-	-	92	32.18	7.31	34.32	214	35	P	V
	*	2402	72.35	-	-	-	-	-	-	-	-	AA	V
													V
													V
BT CH 39 2441MHz		2388.47	47.05	-26.95	74	41.92	32.18	7.31	34.36	112	0	P	H
		2388.47	22.23	-31.77	54	-	-	-	-	-	-	A	H
	*	2441	97.18	-	-	91.81	32.24	7.36	34.23	112	0	P	H
	*	2441	72.36	-	-	-	-	-	-	-	-	A	H
		2484.04	47.18	-26.82	74	41.69	32.28	7.4	34.19	112	0	P	H
		2484.04	22.36	-31.64	54	-	-	-	-	-	-	A	H
		2336.22	46.74	-27.26	74	41.89	32.11	7.18	34.44	150	5	P	V
		2336.22	21.92	-32.08	54	-	-	-	-	-	-	A	V
	*	2441	98.61	-	-	93.24	32.24	7.36	34.23	150	5	P	V
	*	2441	73.79	-	-	-	-	-	-	-	-	A	V
		2484.8	47.29	-26.71	74	41.8	32.28	7.4	34.19	150	5	P	V
		2484.8	22.47	-31.53	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	98.36	-	-	92.87	32.28	7.4	34.19	376	221	P	H
	*	2480	73.54	-	-	-	-	-	-	-	-	A	H
		2484.11	48.46	-25.54	74	42.97	32.28	7.4	34.19	376	221	P	H
		2484.11	23.64	-30.36	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	97.15	-	-	91.66	32.28	7.4	34.19	373	12	P	V
	*	2480	72.33	-	-	-	-	-	-	-	-	A	V
		2483.62	48.3	-25.7	74	42.81	32.28	7.4	34.19	373	12	P	V
		2483.62	23.48	-30.52	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4804	41.4	-32.6	74	54.99	34.25	11.83	59.67	100	0	P	H
		4804	16.58	-37.42	54	-	-	-	-	-	-	A	H
													H
													H
		4804	41.03	-32.97	74	54.62	34.25	11.83	59.67	100	0	P	V
		4804	16.21	-37.79	54	-	-	-	-	-	-	A	V
													V
													V
BT CH 39 2441MHz		4882	41.06	-32.94	74	54.8	34.3	11.53	59.57	100	0	P	H
		4882	16.24	-37.76	54	-	-	-	-	-	-	A	H
		7323	40.12	-33.88	74	49.2	35.6	13.81	58.49	100	0	P	H
		7323	15.3	-38.7	54	-	-	-	-	-	-	A	H
		4882	40.96	-33.04	74	54.7	34.3	11.53	59.57	100	0	P	V
		4882	16.14	-37.86	54	-	-	-	-	-	-	A	V
		7323	40.13	-33.87	74	49.21	35.6	13.81	58.49	100	0	P	V
		7323	15.31	-38.69	54	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	40.67	-33.33	74	54.53	34.37	11.22	59.45	100	0	P	H
		4960	15.85	-38.15	54	-	-	-	-	-	-	A	H
		7440	41.19	-32.81	74	50.18	35.6	14.05	58.64	100	0	P	H
		7440	16.37	-37.63	54	-	-	-	-	-	-	A	H
		4960	40.71	-33.29	74	54.57	34.37	11.22	59.45	100	0	P	V
		4960	15.89	-38.11	54	-	-	-	-	-	-	A	V
		7440	41.95	-32.05	74	50.94	35.6	14.05	58.64	100	0	P	V
		7440	17.13	-36.87	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.





Appendix B. Radiated Spurious Emission Plots

Test Engineer :	Ken Wu, James Chiu, and Jesse Wang	Temperature :	20~23°C
		Relative Humidity :	50~66%

<1Mbps>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak		



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Vertical
Peak	Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT, 130829 HORIZONTAL RBW: 1000.000kHz VEW: 3000.000kHz SWT: Auto Detector : Peak Project : 620405 Mode : 2	Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT, 130829 VERTICAL RBW: 1000.000kHz VEW: 3000.000kHz SWT: Auto Detector : Peak Project : 620405 Mode : 2





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak	117 Level (dBuV/m) Date: 2016-02-23 102.4 87.8 73.1 58.5 43.9 29.3 14.6 0 2430 2440 2450 2460 2470 2480 2490 2500 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT: 130829 HORIZONTAL Detector : Peak Project : 620405 Mode : 3	117 Level (dBuV/m) Date: 2016-02-23 102.4 87.8 73.1 58.5 43.9 29.3 14.6 0 2430 2440 2450 2460 2470 2480 2490 2500 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT: 130829 VERTICAL Detector : Peak Project : 620405 Mode : 3



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07.HY Condition : FCC CLASS-B 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 620405 Mode : 1	 Site : 03CH07.HY Condition : FCC CLASS-B 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 620405 Mode : 1





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2016-02-24 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 620405 Mode : 2	Level (dBuV/m) Date: 2016-02-24 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 620405 Mode : 2



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2016-02-24 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 620405 Mode : 3	Level (dBuV/m) Date: 2016-02-24 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 620405 Mode : 3



<2Mbps>
2.4GHz 2400~2483.5MHz
BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH074Y Condition : FCC CLASS-B 3m HF-ANT: 130829 HORIZONTAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 620405 Mode : 4	 Site : 03CH074Y Condition : FCC CLASS-B 3m HF-ANT: 130829 VERTICAL Detector : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Project : 620405 Mode : 4



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Vertical
Peak	117 Level (dBuV/m) Date: 2016-02-23 102.4 87.8 73.1 58.5 43.9 29.3 14.6 0 2310 2340 2360 2380 2400 2420 2440 2460 2480 2500 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT, 130829 HORIZONTAL Detector : Peak Project : 620405 Mode : 5	117 Level (dBuV/m) Date: 2016-02-23 102.4 87.8 73.1 58.5 43.9 29.3 14.6 0 2310 2340 2360 2380 2400 2420 2440 2460 2480 2500 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT, 130829 VERTICAL Detector : Peak Project : 620405 Mode : 5





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak	117 Level (dBuV/m) Date: 2016-02-23 102.4 87.8 73.1 58.5 43.9 29.3 14.6 0 2430 2440 2450 2460 2470 2480 2490 2500 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT: 130829 HORIZONTAL Detector : Peak Project : 620405 Mode : 6	117 Level (dBuV/m) Date: 2016-02-23 102.4 87.8 73.1 58.5 43.9 29.3 14.6 0 2430 2440 2450 2460 2470 2480 2490 2500 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT: 130829 VERTICAL Detector : Peak Project : 620405 Mode : 6



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 620405 Mode : 4	 Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 620405 Mode : 4



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Vertical
Peak Avg.	Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 620405 Mode : S	Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 620405 Mode : S





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2016-02-24 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 620405 Mode : G	Level (dBuV/m) Date: 2016-02-24 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 620405 Mode : G



Emission below 1GHz

2.4GHz BT (LF)

BT	2.4GHz 2400~2483.5MHz	
ANT	BT LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH07-HY Condition : FCC CLASS-B 3m LF-ANT-35419(6) HORIZONTAL Detector : Peak Project : 620405 Mode : 10	 Site : 03CH07-HY Condition : FCC CLASS-B 3m LF-ANT-35419(6) VERTICAL Detector : Peak Project : 620405 Mode : 10



<3Mbps>

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak	Site : 03CH074Y Condition : FCC CLASS-B 3m HF-ANT: 130829 HORIZONTAL Detector : Peak Project : 620405 Mode : 7	Site : 03CH074Y Condition : FCC CLASS-B 3m HF-ANT: 130829 VERTICAL Detector : Peak Project : 620405 Mode : 7



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Vertical
Peak	117 Level (dBuV/m) Date: 2016-02-23 102.4 87.8 73.1 58.5 43.9 29.3 14.6 0 2310 2340 2360 2380 2400 2420 2440 2460 2480 2500 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT: 130829 HORIZONTAL Detector : Peak Project : 620405 Mode : 0	117 Level (dBuV/m) Date: 2016-02-23 102.4 87.8 73.1 58.5 43.9 29.3 14.6 0 2310 2340 2360 2380 2400 2420 2440 2460 2480 2500 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT: 130829 VERTICAL Detector : Peak Project : 620405 Mode : 0





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak	117 Level (dBuV/m) Date: 2016-02-23 102.4 87.8 73.1 58.5 43.9 29.3 14.6 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT: 130829 HORIZONTAL Detector : Peak Project : 620405 Mode : 9	117 Level (dBuV/m) Date: 2016-02-23 102.4 87.8 73.1 58.5 43.9 29.3 14.6 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m HF-ANT: 130829 VERTICAL Detector : Peak Project : 620405 Mode : 9



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 620405 Mode : 7	 Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 620405 Mode : 7



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH39 2441MHz	
1	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2016-02-24 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 620405 Mode : 8	Level (dBuV/m) Date: 2016-02-24 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 620405 Mode : 8



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BT CH78 2480MHz	
1	Horizontal	Vertical
Peak Avg.	Level (dBuV/m) Date: 2016-02-24 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 HORIZONTAL Detector : Peak Project : 620405 Mode : 9	Level (dBuV/m) Date: 2016-02-24 Frequency (MHz) Site : 03CH07-HY Condition : FCC CLASS-B 3m SHF-EHF_131029 VERTICAL Detector : Peak Project : 620405 Mode : 9