RF Exposure REPORT

No. I14Z47405-GPM01

for

Sony Mobile Communications Inc

Bluetooth Wristband

Type: RD-0140

Model : SWR30

FCC ID: PY7-RD0140

IC ID: 4170B-RD0140

with

Hardware Version: AP2

Software Version: 1.0.0.216.tar.gz

Issued Date: 2014-08-26

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No.18A, Kangding Street, Beijing Economical Development Area, Beijing, China 100176

Tel:+86(0)10-67857376, Fax:+86(0)10-67857376 Email:welcome@emcite.com. www.emcite.com.

CONTENTS

1. Test Laboratory

1.1. Testing Location

Company Name:	TMC Beijing, Telecommunication Metrology Center of MIIT
Address:	No 52, Huayuan beilu, Haidian District, Beijing,P.R.China
Postal Code:	100191
Telephone:	00861062304633
Fax:	00861062304793

1.2. Testing Environment

Normal Temperature:	15-35℃
Relative Humidity:	20-75%

1.3. Project data

Project Leader:	Li Guang
Testing Start Date:	2014-08-05
Testing End Date:	2014-08-21

1.4. Signature

Li Guang

(Prepared this test report)



Sun Xiangqian

(Reviewed this test report)

Song Chongwen

Deputy Director of the laboratory

(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name:	Sony Mobile Communications(China) Co., Ltd.
Address /Post:	19/F, Sony Building, No.16, Guangshun South street, Chaoyang District
City:	Beijing
Postal Code:	100102
Country:	China
Contact Person:	Ma, Gang
Telephone:	+86-10-58656312
Fax:	+86-10-58659049

2.2. Manufacturer Information

Company Name:	Sony Mobile Communications Inc
Address /Post:	1-8-15 Konan, Minato-ku, Tokyo
City:	Tokyo
Postal Code:	108-0075
Country:	Japan

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Bluetooth Wristband
Type	RD-0140
Model	SWR30
FCC ID	PY7-RD0140
IC ID	4170B-RD0140
Frequency Range	ISM 2400MHz~2483.5MHz
Type of Modulation	GFSK/ π /4 DQPSK
Number of Channels	79
MAX Radiated Power	9.94dBm EIRP
MAX Conducted Power	10.32dBm
Power Supply	3.7VDC

Note1: Photographs of EUT are shown in ANNEX A of this test report.

3.2. Internal Identification of EUT

EUT ID*	HW Version	SW Version
UT01a	AP2	1.0.0.216.tar.gz
UT02a	AP2	1.0.0.216.tar.gz

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE ID*	Description	SN
AE1	USB Cable	---

*AE ID: is used to identify the test sample in the lab internally.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
RSS-102	Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)	Issue 4
KDB447498	Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies	v05r01

5. RF Exposure compliance

According to RSS-102 Issue 2, section 2.5 and FCC KDB447498, and the maximum output power listed below, the device is exempt from the routine evaluation and is fulfill RF exposure compliance with FCC and IC requirement.

The output power and operating frequency of the device are:

Frequency	Maximum Output Power	
	Conducted	Radiated
2402 ~ 2480MHz	10.32dBm	9.94dBm

*****END OF REPORT*****