

**Limited Internal
MARKING DRAWING**

Prepared (also subject responsible if other)

LD/SEM/GUP/P Gunilla Novak

Approved

LD/SEM/GUP/P (Gunilla Novak)

Checked

No.

151 86-SVV 107 88/1 Uen

Date

2002-05-22

Rev

PA4

Reference

Approved according to: 000 21 – LXE 107 42/1

Type 1130601-BV.

Label

The label used for marking is defined in the Manufacturing Specification on the SVF 930 327.

Placing

The label shall be placed on the back of the telephone according to the Assembly Drawing (151 88) for the KRH.

Print layout

Sony Ericsson Trademark Sony Ericsson Type number G H Y ¹ Y ² Y ³ field Country approval mark 1 CDA number Country approval mark 2 Repair week Production week IMEI-numbers as barcode IMEI-numbers as characters Serial number as barcode Serial number as characters Approval marks (1, 2, 3)	Additional field Model name Marking of origin "DPY" number R-state
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------

Example on approved label layout



Definitions:

SonyEricsson trademark	The SonyEricsson trademark shall be according to the corporate standard 190 89- EN/LZT 108 5347.
Additional field	The field shall be left blank unless otherwise stated in a separate 151 86 document for the SVV.
Sony Ericsson	Shall be printed: Sony Ericsson
Type number	The type number is 1130601-BV and shall be printed "Type 1130601-BV"
G-field	R-state identification of the CXC-module According to the Marking data 1/15186 for the SVV.
H-field	R-state identification of the hardware according to the Marking data 1/15186 for the SVV.
Y ¹ -field	R-state identification of the KRH according to the Marking data 1/151 86 for the SVV.
Y ² -field	ROA structure identification according to the Marking data 1/151 86 for the SVV.
Y ³ -field	R-state identification of the ROA according to

Prepared (also subject responsible if other)

LD/SEM/GUP/P Gunilla Novak

Approved

LD/SEM/GUP/P (Gunilla Novak)

 Limited Internal
 MARKING DRAWING

No.

151 86-SVV 107 88/1 Uen

Checked

Date

2002-05-22

Rev

PA4

Reference

Country approval mark 1	the Marking data 1/151 86 for the SVV.
CDA number	Consist of text: FCC ID: PY71130601 Within a frame with height > 1,5 mm.
Country approval mark 2	The number of the CDA file loaded including the R-state of the file.
Repair week	Consist of text: IC: 4170B-1130601
Production week	The field shall be left blank unless a repair centre repairs the unit. The repair week shall then be given as Rywwxx (R = repair, y = year, ww = week, xx = Revision eg. 1A)
IMEI number as bar code	The production week shall be given as yyWww (yy = year, ww = week) according to the ISO 8601 standard.
IMEI number as characters	See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no-). The IMEI number has format: TAC-FAC-SNR-CD TAC = will be defined at ETA SNR = A serial number 000000 to 999 999. CD = A check digit, from 0-9, calculated according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Serial number as bar code	According to Ericsson corporate standard 102 01 - 109.
Serial number as characters	According to Ericsson group standard 0012-101. Ericsson group factory number system according the Ericsson corporate standard 1120-101 Factory codes: Linköping A61 Beijing CB5 Nanjing CB9 Shah Alam BD3 Hungary TZ4
Approval marks	1. According to 1424 - SVF 930 52 2. The notified body number according to the TTE Annex III certificate for the production plant. If this is not available, use the notified body number from the type approval certificate (normally 0682). The print size (height) for the notified body number (e.g. 0682) and the corresponding approval marks shall be minimum 5 mm. This is a regulatory requirement.
Model name	3. According to 1424 - SVF 930 196 The model name T300

Prepared (also subject responsible if other)

LD/SEM/GUP/P Gunilla Novak

Approved

LD/SEM/GUP/P (Gunilla Novak)

Limited Internal
MARKING DRAWING

No.

151 86-SVV 107 88/1 Uen

Checked

Date

Rev

Reference

2002-05-22

PA4

Marking of origin

The field shall be left blank unless otherwise stated in a separate 2/151 86-SVV document.

“DPY” number

The DPY number for the product without DPY 101 e.g. if you are producing DPY 101 2554/1 the printing should be 2554/1.

R-state

The R-state for the DPY according to the 1095 for the DPY.

Print regulations

The printing shall be well readable and permanent.

Typeface	OCR-B
Type size	min 1.1 mm
Line spacing	min 1.5 mm
Trademark	min 2.25 mm
Approval marks	min 5.0 mm