

Picture of label

Application: PY71272101



Public

Prepared (also subject responsible if other)

LD/SEM/BGUU Magnus Nilsson

Approved

LD/SEM/BGUU (Magnus Nilsson)

Checked

ecsniln

No.

151 86-SVV 107 057/3 Uen

Date

2003-06-02

Rev

A

Reference

Approved according to: 000 21 – LXE 107 42/1

Type 1272101-BV.

Label

The label used for marking is defined in the Manufacturing Specification on the SVF 930 808.

Placing

The label shall be placed on the back of the telephone according to the Assembly Drawing (151 88) for the KRH.

Print layout

Sony Ericsson stylized name	Model Name	"DPY" number R-state
Type number	G – H field	
Productionweek	KRC number R-state Repair week	
Country approval mark 1	CDA number	
Country approval mark 2		
IMEI-numbers as barcode		
IMEI-numbers as characters		
Serial number as barcode		
Serial number as characters	Additional Field	
Approval marks (1, 2, Marking of origin		

Definitions:

Sony Ericsson trademark	Sony Ericsson and the Sony Ericsson trademark shall be according to the corporate standard 190 89-EN/LZT 108 5347.
Additional field	The field shall be left blank unless otherwise stated in a separate 151 86 document for the SVV.
Type number	The type number is 1272101-BV and shall be printed "Type 1272101-BV"
G-field	R-state identification of the CXC-module according to the Marking data 1/151 86 for the SVV.
H-field	R-state identification of the hardware according to the Marking data 1/151 86 for the SVV.
Country approval mark 1	Consist of text: FCC ID: PY71272101 <i>Within a frame</i> with height > 1,5 mm.
CDA number	The number of the CDA file loaded including the R-state of the file.
Country approval mark 2	Consist of text: IC:4170B-1272101

Public

Prepared (also subject responsible if other)

LD/SEM/BGUU Magnus Nilsson

Approved

LD/SEM/BGUU (Magnus Nilsson)

No.

151 86-SVV 107 057/3 Uen

Checked

Date

Rev

Reference

ecsniln

2003-06-02

A

Repair week	The field shall be left blank unless a repair centre repairs the unit. The repair week shall then be given as Rywwxx (R = repair, y = year, ww = week, xx = Revision eg. 1A)
Production week	The production week shall be given as yyWww (yy = year, ww = week) according to the ISO 8601 standard.
IMEI number as bar code	See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no-).
IMEI number as characters	The IMEI number has format: TAC-SNR-CD TAC = 01016400 Example: 01016400-000 000-0 SNR = A serial number from 000 000 to 999 999 Arima use: 000 000 to 299 999 Flextronics, MX use: 300 000 to 999 999 CD = A check digit, from 0-9, calculated according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Serial number as bar code	According to Ericsson corporate standard 102 01 - 109.
Serial number as characters	According to Ericsson group standard 0012-101. Ericsson group factory number system according the Ericsson corporate standard 1120-101 Factory codes: Beijing CB5 Dashi TP7 Yingko Factory TP8 Flex, Mexico TF5 Flex, Brazil SOR
Approval marks	<ol style="list-style-type: none"> 1. According to 1424 - SVF 930 52 2. The notified body number according to the TTE Annex III certificate for the production plant. If this is not available, use the notified body number from the type approval certificate (normally 0682). The print size (height) for the notified body number (e.g. 0682) and the corresponding approval marks shall be minimum 5 mm. This is a regulatory requirement. 3. According to 1424 - SVF 930 196
Model name	The model name T106
Marking of origin	The field shall be left blank unless otherwise stated in a separate 2/151 86-SVV document.
“DPY” number	The DPY number for the product without DPY 101 e.g. if you are producing DPY 101 2595/2 the

Public

Prepared (also subject responsible if other)

LD/SEM/BGUU Magnus Nilsson

Approved

LD/SEM/BGUU (Magnus Nilsson)

Checked

ecsniln

No.

151 86-SVV 107 057/3 Uen

Date

2003-06-02

Rev

A

Reference

printing should be 2595/2.

R-state

The R-state for the DPY according to the 1095 for the DPY.

Print regulations

The printing shall be well readable and permanent.

Typeface	OCR-B
Type size	min 1.1 mm
Line spacing	min 1.5 mm
Trademark	min 1.5 mm
Approval marks	min 5.0 mm