



Prepared (also subject responsible if other)

SEM/BGGINB Håkan Sjöberg +46 46 193559

Approved

Checked

SEM/BGG/INM Mats Hansson

Company Internal
STATEMENT

No.

GUG/N04:081 Uen

Date

Rev

Reference

2004-05-12

A

Receiver

Federal Communication Commission

Application PY7A1021041

Statement on output power

For the FCC SAR and EMC (Part 24) measurements of Sony Ericsson phone K700, FCC ID PY7A1021041, we have used two different units since the testing took place at two different test houses.

The conducted output power was measured on both units at Sony Ericsson's SAR laboratory before the EMC unit was sent to Cetecom Saarbrücken for the EMC measurements. This was made in order to ensure that the output power was the same on both units.

Below follows the results from the different measurements:

Measurement results; SAR laboratory, Sony Ericsson

Unit	Channel 512	Channel 661	Channel 810
A6101TWY2M (EMC)	30,1 dBm	30,4 dBm	30,3 dBm

Measurement results; Cetecom, Saarbrücken

Unit	Channel 512	Channel 661	Channel 810
A6101TWY2M (EMC)	29,80 dBm	30,1 dBm	30,0 dBm

Based on results presented above, the reason for the difference of approximately 0,4 dBm between the SAR and EMC report is due to measurement uncertainties between different test houses / test equipments.

Best regards,

Mats Hansson
Technical Manager
EMF & Safety
Type Approval Department