



| | | | | |
|--|----------------|---------------------------|-----------------|---|
| <i>Prepared</i> RT/SEM/CA/KA Christer Andersson | | <i>Date</i> 2005-07-07 | <i>Rev</i> A | <i>Doc no.</i> 1/151 86-DPY 101 1500 |
| <i>Approved</i> CA/KA (Christer Andersson) | <i>Checked</i> | | | <i>File</i> |

Marking Drawing T292a

Type AAA-1061011-BV = T292a



Label

The Label used for marking is defined in the Manufacturing Specification 1301-SVF 930 2239.

Placing

The label shall be placed on the back of the telephone according to the Assembly Drawing for the KRH.

Print Layout





| | | | |
|--|---------------------------|-----------------|---|
| <i>Prepared</i> RT/SEM/CA/KA Christer Andersson | <i>Date</i> 2005-07-07 | <i>Rev</i> A | <i>Doc no.</i> 1/151 86-DPY 101 1500 |
| <i>Approved</i> CA/KA (Christer Andersson) | <i>Checked</i> | | <i>File</i> |

| Line | Text |
|-------------|---|
| 1. | Sony Ericsson Trademark |
| 2. | IMEI Number as Bar Code |
| 3. | IMEI Number as Characters |
| 4. | Serial Number as Bar Code |
| 5. | Serial Number as Characters |
| 6. | Country Approval mark 1 |
| 7. | Country Approval mark 2. |
| | |
| 8. | Model number, Reduced DPY number & r-state, Type approval number GHY1 fields. |
| 9. | |
| 10. | Marking of Origin Build week |

Definitions:

| | |
|-----------------------------|--|
| Sony Ericsson trademark | Sony Ericsson trademark shall be according to the corporate standard 190 89-EN/LZT 108 5347. |
| IMEI number as bar code | See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no -). |
| IMEI number as characters | The IMEI number has format: 01AAAAAA-BBBBBB-C AAAAAA = (see 1/151-86-KRH 101 295 latest rev for this information) BBBBBB = assigned serial number C = A check digit, from 0-9, calculated according to the Luhn formula (ISO/IEC 7812), GSM 02.16. |
| Serial number as bar code | As desired by supplier (only actual number, with data identifier). |
| Serial number as characters | Supplier's identification for traceability of the KRH, as desired by the supplier. |
| Country approval mark 1 | Consist of text: FCC ID: PY7-A1061011 <i>Within a frame</i> with height > 1,5 mm. |
| Country approval mark 2 | Consist of text: IC: 4170B-A1061011 |

| | | | |
|---------------------------------|----------------|------------|-----------------------|
| <i>Prepared</i> | <i>Date</i> | <i>Rev</i> | <i>Doc no.</i> |
| RT/SEM/CA/KA Christer Andersson | 2005-07-07 | A | 1/151 86-DPY 101 1500 |
| <i>Approved</i> | <i>Checked</i> | | <i>File</i> |
| CA/KA (Christer Andersson) | | | |

| | |
|-----------------------|--|
| Model Number | The model number is T292a and shall be printed "T292a" |
| Reduced DPY | Reduced DPY-Number & r-state. The reduced DPY number leaves out the 3 digit number prefix (ex: DPY 101 1500 R1A would be printed DPY 1500 R1A) |
| Type Number | The type number is AAA 1061011-BV and shall be printed "AAA-1061011-BV" |
| G – Field | R-State identification of the CXC-module according to the Marking Data 1/151-86-KRH 101 295. |
| H-field | R-state identification of the KRH according to the Marking data 1/151-86-KRH 101 295. |
| Y ¹ -field | R-state identification of the ROA according to the Marking data 1/151-86-KRH 101 295. |
| Marking of origin | "Made in" statement should reflect the country of origin of the 1/KRH (i.e. Made in Malaysia). |
| Build Week | Build Week, in format year W XX, ie 05W18 is equal to build year 2005, Week 18. |

Print regulations

The printing shall be well readable and permanent.

| | |
|----------------|------------|
| Typeface | OCR-B |
| Type size | min 1.1 mm |
| Line spacing | min 1.5 mm |
| Trademark | min 1.5 mm |
| Approval Marks | min 5.0 mm |

Revision Table

| Revision | Date | Reason |
|----------|------------|-----------------|
| A | 2005-07-07 | Initial Release |