

Prepared (also subject responsible if other)

SEM/BGLDA, Dan Hopkins

Approved

SEM/BGLDB, (Patrik Jonsson)

Checked

 Company Internal  
 MARKING DRAWING  
 No.

1203-5000

Date

2007-08-27

Rev

1

Reference

5

Approved according to 000 21-LXE 107 42/1

## Mobile Phone label content, No Made in...

### 1 General information

- Label Content Part No: 1203-4999.

If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.

“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

The label shall be placed on the back of the telephone according to the Assembly Drawing for the KRH.

### 2 Barcode Information

All bar codes, when applicable, are according to Ericsson corporate standard 102 01–109 Uen. No bar codes are allowed to be closer to a label edge than 2 mm! (quiet zone).

Minimum print quality: C  
 (according to ANSI X3.182-1990 as stated in Ericsson corporate standard 102 01–1003 Uen.)

### 3 Printing information

	Content	Format
Line 1 (6,3/30,3)	SIM-card logo	Graphics, height 7,3 mm. According to 1200-9812. Rotated 90° counter clockwise.
Line 2a (8,5/16,3)	Sony Ericsson stylized name.	Graphics, height 1,5 mm. According to 1200-1925
Line 2b (8,5/31,0)	Model Name “Z750a”	Text, height 1,2 mm.
Line 3a (10,6/16,3)	Product number without revision of the Sales Item in which the phone is packed, if applicable. “SI XXXX-XXXX”	Text, height 1,2 mm.
Line 3b (10,6/31,0)	Repair week, if applicable. “Ry’W’ww” (y = year, ww = week)	Text, height 1,2 mm.
Line 4 (12,5/16,3)	“TYPE: AAD-3252023-BV”	Text, height 1,2 mm.

Prepared (also subject responsible if other)

SEM/BGLDA, Dan Hopkins

Approved

SEM/BGLDB, (Patrik Jonsson)

Checked

 Company Internal  
 MARKING DRAWING

No.

1203-5000

Date

2007-08-27

Rev

1

Reference

5

	<b>Content</b>	<b>Format</b>
Line 5a (14,4/16,3)	"FCC ID: PY7A3252023"	Text, height 1,2 mm.
Line 5b (14,4/31,0)	Location code of where the phone is flashed, if applicable, "XXX"	Text, height 1,2 mm.
Line 6 (16,3/16,3)	"IC: 4170B-A3252023"	Text, height 1,2 mm.
Line 7a (20,2/18)	Production week (flash), "yy'W'ww" (yy = year, ww = week)	Text, height 1,2 mm.
Line 7b (20,2/26,6)	HW & SW identification field, if applicable; "FG"	Text, height 1,2 mm. According to Type-testing report in BOM pos 1C.
Line 8 (24,0/1,0)	Supplier's identification for traceability of the telephone, as desired by supplier (e.g. "S/N: nnn...." for serial number).	Text, height 1,2 mm. Defined by supplier.
Line 9 (25,7/36,9)	The Notified body number. "0682"	Text, height 1,2 mm. Rotated 90° counter clockwise.
Line 10 (26,7/2,6)	Line 10a in bar code. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 11 (28,4/1,0)	Actual electronic serial number (IMEI) of the phone, "IMEI: 00000000-000000-0"	Text, height 1,2 mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM (IMEI number part). CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.

Prepared (also subject responsible if other)

SEM/BGLDA, Dan Hopkins

Approved

SEM/BGLDB, (Patrik Jonsson)

Checked

 Company Internal  
 MARKING DRAWING

No.

1203-5000

Date

2007-08-27

Rev

1

Reference

5

Line 12a (33,0/2,6)	Line 13 in bar code (only actual number, without data identifier).	Bar code, height 4,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.
Line 12b (33,0/36,9)	CE approval symbol.	Graphics, height 5 mm. According to 1202-5482. Rotated 90° counter clockwise.

## 4 Marking of Origin

### 4.1 Content

“Made in Xxx”;

“Xxx” = actual country of production of the included telephone, in English.

## 5 Layout

The conceptual picture (for Zebra 90XiII printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

### 5.1 Conceptual picture



double underlined = major changes since last revision.

Prepared (also subject responsible if other)

SEM/BGLDA, Dan Hopkins

Approved

SEM/BGLDB, (Patrik Jonsson)

Checked

Company Internal  
MARKING DRAWING

No.

1203-5000

Date

2007-08-27

Rev

1

Reference

5

## 5.1 Label placement

To find the label follow these steps:

1. Remove the cover on the rear side of the product.
2. Remove the battery.
3. The label is located under the battery.

