



Accredited testing-laboratory

DAR registration number: DAT-P-176/94-D1

**Federal Motor Transport Authority (KBA)
DAR registration number: KBA-P 00070-97**

Recognized by the Federal Communications Commission

Anechoic chamber registration no.: 90462 (FCC)

Anechoic chamber registration no.: 3463A-1 (IC)

Certification ID: DE 0001

Accreditation ID: DE 0002

Accredited Bluetooth® Test Facility (BQTF)

*The Bluetooth word mark and logos are owned by the Bluetooth SIG,
Inc. and any use of such marks by Cetecom ICT is under license*

Test report no. : 2-4883-57-04/08
Type identification : AAD-3880001-BV
Applicant : Sony Ericsson Mobile Communications AB
FCC ID : PY7A3880001
IC Certification No : 4170B-A3880001
Test standards : 47 CFR Part 15
RSS - 210 Issue 7

Table of contents

1	General information	3
1.1	Notes	3
1.2	Testing laboratory	4
1.3	Details of applicant	4
1.4	Application details	4
2	Test standard/s:	5
3	Technical tests	6
3.1	Details of manufacturer.....	6
3.1.1	Test item.....	6
3.1.2	Additional EUT information For IC Canada (appendix 2).....	7
3.1.3	RF Technical Brief Cover Sheet acc. To RSS-102	8
3.1.4	EUT operating modes.....	9
3.1.5	Extreme conditions testing values.....	9
4	Summary of Measurement Results and list of all performed test cases	10
5	RF measurement testing	11
5.1	Description of test set-up.....	11
5.1.1	Radiated measurements.....	11
5.1.2	Conducted measurements.....	11
5.2	Referenced documents	12
5.3	Additional comments	12
5.4	Antenna gain	12
5.5	Carrier frequency separation §15.247(a)(1)	13
5.6	Number of hopping channels §15.247(a)(1)	16
5.7	Time of occupancy (dwell time) §15.247(a)(1)(iii).....	17
5.8	Power Spectral density (Hybrid system in Inquiry mode/Page scan) §15.247(e)	18
5.9	Spectrum Bandwidth of a FHSS System / 20dB Bandwidth §15.247(a)(1).....	19
5.10	Maximum output power (conducted) § 15.247 (b)(1).....	24
5.11	Max. peak output power (radiated) § 15.247 (b)(1)	29
5.12	Band-edge compliance of conducted emissions §15.247 (d)	30
5.13	Band-edge compliance of radiated emissions §15.205	37
5.14	Spurious Emissions - conducted (Transmitter) § 15.247 (c)(1)	46
5.15	Spurious Emissions > 30 MHz- radiated (Transmitter) § 15.247 (c)(1).....	52
5.16	Spurious Emissions - radiated (Receiver) § 15.109	61
5.17	Spurious Emissions < 30 MHz - Transmitter radiated § 15.209	65
5.18	Conducted Emissions <30 MHz § 15.107/207.....	66
6	Test equipment and ancillaries used for tests	68
7	Photographs of the Test Set-up	72
8	Photographs of the EUT	74

1 General information


1.1 Notes

The test results of this test report relate exclusively to the test item specified in 3.1.1. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

Test laboratory manager:

2008-09-12

Marco Bertolino



Date

Name

Signature

Technical responsibility for area of testing:

2008-09-12

Stefan Bös



Date

Name

Signature

1.2 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6 - 10

66117 Saarbrücken

Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

e-mail: info@ICT.cetecom.de

Internet: http://www.cetecom-ict.de

State of accreditation: The test laboratory (area of testing) is accredited according to
DIN EN ISO/IEC 17025
DAR registration number: DAT-P-176/94-D1

Accredited by: Federal Motor Transport Authority (KBA)
DAR registration number: KBA-P 00070-97

Testing location, if different from CETECOM ICT Services GmbH:

Name :
Street :
Town :
Country :
Phone :
Fax :

1.3 Details of applicant

Name:	Sony Ericsson Mobile Communications AB
Street:	Nya Vattentornet
Town:	22188 Lund
Country:	Sweden
Telephone:	+46-46-19-3000
Fax:	+46-46-19-3295
Contact:	Peter Lindeborg
E-mail:	peter.lindeborg@sonyericsson.com
Telephone:	+46-46-212-6180

1.4 Application details

Date of receipt of order:	2008-08-27
Date of receipt of test item:	2008-09-08
Date of start test:	2008-09-11
Date of end test:	2008-09-12
Persons(s) who have been present during the test:	-/-

2 Test standard/s:

47 CFR Part 15	2007-09	Title 47 of the Code of Federal Regulations; Chapter I- Federal Communications Commission subchapter A - general, Part 15-Radio frequency devices
RSS - 210 Issue 7	2007-06	Spectrum Management and Telecommunications - Radio Standards Specification Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

3 Technical tests

3.1 Details of manufacturer

Name:	Sony Ericsson Mobile Communications AB
Street:	Nya Vattentorget
Town:	22188 Lund
Country:	Sweden

3.1.1 Test item

Kind of test item	: GSM Mobile 850/900/1800/1900; EDGE; WLAN; BT
Type identification	: AAD-3880001-BV
S/N serial number	: GT200004KZ (BT radiated) GT200004KW (BT radiated) GT200004KE (BT conducted)
HW hardware status	: A
SW software status	: Windows Mobile 6.1 Professional ROM: 1.00.0.11 Radio: 1.01.25.27 Protocol: 52.31.25.13U ExtPkg: 1.0.0.0
Frequency Band [MHz]	: ISM 2.400 - 2.483,5
Type of Modulation	: GFSK, Pi/4 DQPSK, 8 DPSK
Number of channels	: 79
Antenna	: Integrated antenna
Power Supply	: 3.8 V Dc by power supply / Li-Polymer battery BST-41
Temperature Range	: -20 °C to +55 °C

Max. power radiated: -0.32 dBm

Max. power conducted: 1.80 dBm

FCC ID: PY7A3880001

IC: 4170B-A3880001

3.1.2 Additional EUT information For IC Canada (appendix 2)

IC Registration Number:	4170B-A3880001
Model Name:	AAD-3880001-BV
Manufacturer (complete Address):	Sony Ericsson Mobile Communications AB Nya Vattentorget 22188 Lund Sweden
Tested to Radio Standards Specification (RSS) No.:	RSS-210 Issue 7
Open Area Test Site Industry Canada Number:	IC 3463A-1
Frequency Range (or fixed frequency) [MHz]:	2400 – 2483.5 MHz
RF: Power [W] (max):	GFSK modulation: Rad. EIRP: 0.73 mW Conducted : 1.19 mW Pi/4 DQPSK modulation Rad. EIRP: 0.93 mW Conducted : 1.51 mW 8DPSK modulation Rad. EIRP: 0.84 mW Conducted : 1.36 mW
Antenna Type:	Integrated antenna
Occupied Bandwidth (99% BW) [kHz]:	878 (GFSK) 1305 (Pi/4 DQPSK) 1244 (8 DPSK)
Type of Modulation:	GFSK, Pi/4 DQPSK, 8 DPSK
Emission Designator (TRC-43):	878KFXD (GFSK) 1M31GXD (Pi/4 DQPSK) 1M24GXD (8 DPSK)
Transmitter Spurious (worst case) [dBμV]:	32.02 dBμV
Receiver Spurious (worst case) [dBμV]:	31.03 dBμV

ATTESTATION:

I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned departmental standard(s), and that the radio equipment identified in this application has been subject to all applicable test conditions specified in the departmental standards and all of the requirements of the standards have been met.

Signature:



Test engineer: Marco Bertolino Date: 2008-09-12

3.1.3 RF Technical Brief Cover Sheet acc. To RSS-102

All Fields must be completed with the requested information or the following codes: N/A for Not Applicable, N/P for Not Performed or N/V for Not Available. Where applicable, check appropriate box.

1. COMPANY NUMBER: **4170B**
2. MODEL NUMBER: **AAD-3880001-BV**
3. MANUFACTURER: **Sony Ericsson Mobile Communications AB**
4. TYPE OF EVALUATION: **(c) RF Evaluation**

- Evaluated against exposure limits: General Public Use Controlled Use
 - Duty cycle used in evaluation: 100 %
 - Standard used for evaluation: RSS-102 Issue 2 (2005-11)
 - Measurement distance: 0.20 m
 - RF value: 0.001 V/m A/m W/m²
- Measured Computed Calculated

Declaration of RF Exposure Compliance

ATTESTATION:

I attest that the information provided in this test report are correct; that a Technical Brief was prepared and the information it contains is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed and that the device meets the SAR and/or RF exposure limits of RSS-102.

Name: Marco Bertolino
Title: Dipl.-Ing. (FH)
Company: Cetecom ICT Services GmbH

3.1.4 EUT operating modes

EUT operating mode no. *)	Description of operating modes	Additional information
Op. 0	Normal mode	Normal temperature and power source conditions
Op. 1		low temperature, low power source conditions
Op. 2		low temperature, high power source conditions
Op. 3		high temperature, low power source conditions
Op. 4		high temperature, high power source conditions

*) EUT operating mode no. is used to simplify the test plan

3.1.5 Extreme conditions testing values

Description	Shortcut	Unit	Value
Nominal Temperature	T _{nom}	°C	20
Nominal Humidity	H _{nom}	%	52
Nominal Power Source	V _{nom}	V	3.8

Type of power source: **Dc by power supply / Li-Polymer battery BST-41**

Deviations from these values are reported in chapter 2

4 Summary of Measurement Results and list of all performed test cases

- No deviations from the technical specifications were ascertained
- There were deviations from the technical specifications ascertained

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC Part 15 §15.247 - CANADA RSS-210	passed	2008-09-12	-/-

Test Specification Clause	Test Case	Modulation	Pass	Fail	N/A	Not performed
None	Antenna Gain	GFSK	Yes			
§15.247(a1)	Carrier frequency separation	GFSK	Yes			
§15.247(a1)	Number of hopping channels	GFSK	Yes			
§15.247(a)(1)(iii)	Time of occupancy (dwell time)	--	Yes			
§15.247(e)	Power Spectral density (Hybrid system in Inquiry mode/Page scan)	--			Yes	
§15.247(a)(1)	Spectrum Bandwidth of a FHSS System / 20dB Bandwith	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (b)(1)	Maximum output power (conducted)	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (b)(1)	Max. peak output power (radiated)	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (d)	Band-edge compliance of conducted emissions	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.205	Band-edge compliance of radiated emissions	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (d)	Spurious Emission - conducted (Transmitter)	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (d)	Spurious Emission - radiated (Transmitter) >30 MHz	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.109	Spurious Emissions - radiated (Receiver)	Pi/4 DQPSK	Yes			
§ 15.209	Spurious Emissions - radiated (Transmitter) <30 MHz	Pi/4 DQPSK	Yes			
§ 15.107/207	Conducted Emissions <30 MHz	Pi/4 DQPSK	Yes			

5 RF measurement testing

5.1 Description of test set-up

5.1.1 Radiated measurements

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 25 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63.2-1996 clause 15 and ANSI C63.4-2003 clause 4.1.5. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63-4-2003 clause 4.2. Antennas are confirmed with ANSI C63.2-1996 item 15.


9 kHz - 150 kHz: Quasi Peak measurement, 200 Hz Bandwidth, passive loop antenna.
150 kHz - 30 MHz: Quasi Peak measurement, 9 kHz Bandwidth, passive loop antenna.
30 MHz - 200 MHz: Quasi Peak measurement, 120 kHz Bandwidth, bi-conical antenna
200MHz - 1GHz: Quasi Peak measurement, 120 kHz Bandwidth, log periodic antenna
>1GHz: Average, RBW 1MHz, VBW 10 Hz, waveguide horn

All measurements are done in accordance with the Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems DA 00-705 and Appendix A “BLUETOOTH APPROVALS”

The EUT is powered by an external power supply with nominal voltage. The signalling is performed from outside the chamber with a signalling unit (CMU200 or other) by air link using signalling antenna.

5.1.2 Conducted measurements

The EUT's RF signal is coupled out by the antenna connector which is supplied by the manufacturer. The signal is first 10dB attenuated before it is power divided (~6dB loss per branch). One of the signal paths is connected to the communication base Station (CMU200 or other), the other one is connected to the spectrum analyzer. The specific losses for both signal paths are first checked within a calibration. The measurement readings on the signalling unit/spectrum analyzer are corrected by the specific test set-up loss. The attenuator, power divider, signalling unit and the spectrum analyzer are impedance matched on 50 Ohm.



5.2 Referenced documents

None

5.3 Additional comments

None

5.4 Antenna gain


The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

	low channel 2402 MHz	middle channel 2441 MHz	high channel 2480 MHz
Conducted power [dBm] Measured, GFSK modulation	0.36	0.55	0.74
Radiated power [dBm] Measured, GFSK modulation	-1.38	-1.61	-2.01
Gain [dBi] Calculated	-1.74	-2.16	-2.75

5.5 Carrier frequency separation §15.247(a)(1)

Modulation: GFSK


Plot 1 of 1:



Result: Channel separation is: ~ 1 MHz

Modulation: Pi/4 DQPSK


Plot 1 of 1:



Result: Channel separation is: ~ 1 MHz

Modulation: 8 DPSK

Plot 1 of 1:



Result: Channel separation is: ~ 1 MHz


Limits:

Under normal test conditions only	Minimum 25 kHz or 20 dB Bandwidth of the hopping system
-----------------------------------	---


5.6 Number of hopping channels §15.247(a)(1)

Modulation: GFSK

Plot 1 of 2:



Plot 2 of 2:



Result: The number of hopping channels is: 79

Limits:

Under normal test conditions only	at least 15 non-overlapping channels
-----------------------------------	--------------------------------------

5.7 Time of occupancy (dwell time) §15.247(a)(1)(iii)

For Bluetooth devices:

The dwell time of 0.4 s within a 31.6 second period in data mode is independent from the packet type (packet length). The calculation for a 31.6 second period is as follows:

Dwell time = time slot length * hop rate / number of hopping channels * 31.6 s

Example for a DH1 packet (with a maximum length of one time slot)

Dwell time = $625 \mu\text{s} * 1600 \text{ 1/s} / 79 * 31.6 \text{ s} = 0.4 \text{ s}$ (in a 31.6 s period)

For multi-slot packet the hopping is reduced according to the length of the packet.

Example for a DH5 packet (with a maximum length of five time slots)

Dwell time = $5 * 625 \mu\text{s} * 1600 * 1/5 * 1/s / 79 * 31.6 \text{ s} = 0.4 \text{ s}$ (in a 31.6 s period)

This is according to the Bluetooth Core Specification V 1.1 & V 1.2 & V2.0 (+ critical errata) for all Bluetooth devices. Therefore, all Bluetooth devices comply with the FCC dwell time requirement in the data mode.

This was checked during the Bluetooth Qualification tests.

The Dwell time in hybrid mode is approximately 2.6 ms (in a 12.8s period)

**5.8 Power Spectral density (Hybrid system in Inquiry mode/Page scan)
§15.247(e)**

Not applicable !


Result: Power density: - dBm/Hz = - dBm / 3 kHz
Correction factor from dBm/Hz to dBm / 3 kHz is +34.8 dB

Limits:


Under normal test conditions only	For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission
-----------------------------------	---

5.9 Spectrum Bandwidth of a FHSS System / 20dB Bandwidth §15.247(a)(1)


Plot 1: GFSK




Plot 2: GFSK




Plot 3: GFSK




Plot 4: Pi/4 DQPSK




Plot 5: Pi/4 DQPSK




Plot 6: Pi/4 DQPSK




Plot 7: 8DPSK



Plot 8: 8DPSK



Plot 9: 8DPSK



Result:

Modulation	20 dB BANDWIDTH [kHz]		
	2402	2441	2480
Frequency [MHz]			
<i>GFSK</i>	878	878	878
<i>Pi/4 DQPSK</i>	1305	1305	1305
<i>8DPSK</i>	1244	1244	1244
Measurement uncertainty	±1kHz		

RBW / VBW as provided in the „Measurement Guidelines“ (DA 00-705, March 30, 2000).


RBW: 10 kHz / VBW 10 kHz

Limits:


Under normal test conditions only	<p>GFSK < 1000 kHz</p> <p>Pi/4 DQPSK < 1500</p> <p>8DPSK < 1500</p>
-----------------------------------	--

5.10 Maximum output power (conducted) § 15.247 (b)(1)


Plot 1: GFSK




Plot 2: GFSK




Plot 3: GFSK




Plot 4: Pi/4 DQPSK




Plot 5: Pi/4 DQPSK




Plot 6: Pi/4 DQPSK




Plot 7: 8DPSK



Plot 8: 8DPSK



Plot 9: 8DPSK



Results:

Modulation	Max. peak output power [dBm]		
	2402	2441	2480
Frequency [MHz]	2402	2441	2480
<i>GFSK</i>	0.36	0.55	0.74
<i>Pi/4 DQPSK</i>	1.42	1.65	1.80
<i>8DPSK</i>	0.99	1.18	1.35
Measurement uncertainty	±2dB		

RBW / VBW: 3 MHz

Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
--	---------------

5.11 Max. peak output power (radiated) § 15.247 (b)(1)

Modulation: GFSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
		2402	2442	2480
Frequency [MHz]				
T _{nom}	V _{nom}	-1.38	-1.61	-2.01
Measurement uncertainty		±3dB		

RBW / VBW: 3 MHz

Measured at a distance of 3m

Modulation: Pi/4 DQPSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
		2402	2442	2480
Frequency [MHz]				
T _{nom}	V _{nom}	-0.32	-0.51	-0.95
Measurement uncertainty		±3dB		

RBW / VBW: 3 MHz

Measured at a distance of 3m

Modulation: 8 DPSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
		2402	2442	2480
Frequency [MHz]				
T _{nom}	V _{nom}	-0.75	-0.98	-1.40
Measurement uncertainty		±3dB		

RBW / VBW: 3 MHz

Measured at a distance of 3m


Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
--	---------------


5.12 Band-edge compliance of conducted emissions §15.247 (d)

Modulation: GFSK


Plot 1 of 4 (hopping off, lowest frequency):




Plot 2 of 4 (hopping on, lowest frequency):



Plot 3 of 4 (hopping off, highest frequency):



Plot 4 of 4 (hopping on, highest frequency):




Results:


SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB

Modulation: Pi/4 DQPSK


Plot 1 of 4 (hopping off, lowest frequency):




Plot 2 of 4 (hopping on, lowest frequency):



Plot 3 of 4 (hopping off, highest frequency):



Plot 4 of 4 (hopping on, highest frequency):




Results:


SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB

Modulation: 8 DPSK


Plot 1 of 4 (hopping off, lowest frequency):




Plot 2 of 4 (hopping on, lowest frequency):



Plot 3 of 4 (hopping off, highest frequency):



Plot 4 of 4 (hopping on, highest frequency):



Results:

SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB


Limits:

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).
-----------------------------------	--

5.13 Band-edge compliance of radiated emissions §15.205


Modulation: GFSK

Plot 1: Max field strength in 3m distance (single frequency)



Result: 99.10 dB μ V/m


Plot 2: Marker-Delta Method (single carrier)



Marker-Delta-Value: 48.60 dB

This measurement was made to show that the behaviour of the system is conform to FCC 15.205 (restricted bands)


Plot 3: Marker-Delta Method (hopping)




Marker-Delta-Value: 50.40 dB

This measurement was made to show that the behaviour of the system is conform to FCC 15.205 (restricted bands)

Plot 4: Restricted Bands low



Plot 5: Restricted Bands high



Results & Limits:


Radiated field strength

The field strength was measured with an EMI measuring receiver and 1 MHz RBW / VBW for peak and with 1MHz RBW / 10Hz VBW for average at a distance of 3m.

high channel	setup	measured value (3m)	correction factor (3m)	calculated value (3m)
Max. peak value	1 MHz RBW 1 MHz VBW	99.10 dB μ V/m	-6.40	92.70 dB μ V/m
Max. average value	Calculated with duty cycle correction factor	92.70 dB μ V/m peak	-1,07dB duty cycle correction factor (worst case DH5)	91.63 dB μ V/m
Delta value	Peak 100 kHz RBW/VBW	48.60 dB (single carrier) 50.40 dB (hopping mode)	-	-
Value at band edge	limit 54 dB μ V/m			43.03 dB μ V/m (single carrier) 41.23 dB μ V/m (hopping mode)
Statement:				Complies


Modulation: Pi/4 DQPSK

Plot 1: Max field strength in 3m distance (single frequency)



Result: 98.40 dB μ V/m


Plot 2: Marker-Delta Method (single carrier)



Marker-Delta-Value: 50.80 dB

This measurement was made to show that the behaviour of the system is conform to FCC 15.205 (restricted bands)


Plot 3: Marker-Delta Method (hopping)




Marker-Delta-Value: 49.50 dB

This measurement was made to show that the behaviour of the system is conform to FCC 15.205 (restricted bands)

Plot 4: Restricted Bands low



Plot 5: Restricted Bands high



Results & Limits:


Radiated field strength

The field strength was measured with an EMI measuring receiver and 1 MHz RBW / VBW for peak and with 1MHz RBW / 10Hz VBW for average at a distance of 3m.

high channel	setup	measured value (3m)	correction factor (3m)	calculated value (3m)
Max. peak value	1 MHz RBW 1 MHz VBW	98.40 dB μ V/m	-6.40	92.00 dB μ V/m
Max. average value	Calculated with duty cycle correction factor	92.00 dB μ V/m peak	-1,07dB duty cycle correction factor (worst case DH5)	90.93 dB μ V/m
Delta value	Peak 100 kHz RBW/VBW	50.80 dB (single carrier) 49.50 dB (hopping mode)	-	-
Value at band edge	limit 54 dB μ V/m			40.13 dB μ V/m (single carrier) 41.43 dB μ V/m (hopping mode)
Statement:				Complies


Modulation: 8 DPSK

Plot 1: Max field strength in 3m distance (single frequency)



Result: 97.70 dB μ V/m


Plot 2: Marker-Delta Method (single carrier)



Marker-Delta-Value: 49.90 dB

This measurement was made to show that the behaviour of the system is conform to FCC 15.205 (restricted bands)


Plot 3: Marker-Delta Method (hopping)




Marker-Delta-Value: 49.50 dB

This measurement was made to show that the behaviour of the system is conform to FCC 15.205 (restricted bands)

Plot 4: Restricted Bands low



Plot 5: Restricted Bands high



Results & Limits:

Radiated field strength


The field strength was measured with an EMI measuring receiver and 1 MHz RBW / VBW for peak and with 1MHz RBW / 10Hz VBW for average at a distance of 3m.

high channel	setup	measured value (3m)	correction factor (3m)	calculated value (3m)
Max. peak value	1 MHz RBW 1 MHz VBW	97.70 dB μ V/m	-6.40	91.30 dB μ V/m
Max. average value	Calculated with duty cycle correction factor	91.30 dB μ V/m peak	-1,07dB duty cycle correction factor (worst case DH5)	90.23 dB μ V/m
Delta value	Peak 100 kHz RBW/VBW	49.90 dB (single carrier) 49.50 dB (hopping mode)	-	-
Value at band edge	limit 54 dB μ V/m			40.33 dB μ V/m (single carrier) 40.73 dB μ V/m (hopping mode)
Statement:				Complies


5.14 Spurious Emissions - conducted (Transmitter) § 15.247 (c)(1)

Modulation: GFSK


Plot 1 of 3: lowest channel



Plot 2 of 3: middle channel



Plot 3 of 3: highest channel




Result & Limits:

Emission Limitation					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402		0.02	30 dBm		Operating frequency
No critical peaks detected ! All found peaks are below -30 dBm			-20 dBc		complies
2441		0.20	30 dBm		Operating frequency
No critical peaks detected ! All found peaks are below -30 dBm			-20 dBc		complies
2480		0.40	30 dBm		Operating frequency
No critical peaks detected ! All found peaks are below -30 dBm			-20 dBc		complies
Measurement uncertainty			± 3dB		


F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
 F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Modulation: Pi/4 DQPSK


Plot 1 of 3: lowest channel



Plot 2 of 3: middle channel



Plot 3 of 3: highest channel




Result & Limits:

Emission Limitation					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402		0.51	30 dBm		Operating frequency
No critical peaks detected ! All found peaks are below -30 dBm			-20 dBc		complies
2441		0.71	30 dBm		Operating frequency
No critical peaks detected ! All found peaks are below -30 dBm			-20 dBc		complies
2480		0.92	30 dBm		Operating frequency
No critical peaks detected ! All found peaks are below -30 dBm			-20 dBc		complies
Measurement uncertainty			± 3dB		


F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
 F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Modulation: 8 DPSK


Plot 1 of 3: lowest channel



Plot 2 of 3: middle channel



Plot 3 of 3: highest channel



Result & Limits:

Emission Limitation					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402		0.10	30 dBm		Operating frequency complies
No critical peaks detected ! All found peaks are below -30 dBm			-20 dBc		
2441		0.19	30 dBm		Operating frequency complies
No critical peaks detected ! All found peaks are below -30 dBm			-20 dBc		
2480		0.38	30 dBm		Operating frequency complies
No critical peaks detected ! All found peaks are below -30 dBm			-20 dBc		
Measurement uncertainty			± 3dB		

F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
 F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
-----------------------------------	--

Note: For emissions that fall into restricted bands you find the radiated emissions later in the report.

5.15 Spurious Emissions > 30 MHz- radiated (Transmitter) § 15.247 (c)(1)

Modulation: GFSK

Plot 1: 0.03 - 1 GHz vertical/horizontal (lowest channel)


Common Information

EUT: AAD-3880001-BV + CAA-0003005-BV
 Serial Number: GT200004KZ (BT radiated)
 Test Description: FCC part 15 B class B @ 10 m
 Operating Conditions: BT CH 0 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: FCC_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver




Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
37.433050	9.3	15000.000	120.000	139.0	V	43.0	13.4	20.7	30.0	
45.980450	10.7	15000.000	120.000	114.0	V	158.0	13.5	19.3	30.0	
47.695350	9.3	15000.000	120.000	151.0	H	179.0	13.6	20.7	30.0	
47.830400	9.1	15000.000	120.000	220.0	H	233.0	13.6	20.9	30.0	
51.233400	8.9	15000.000	120.000	175.0	H	323.0	13.5	21.1	30.0	
53.000850	10.1	15000.000	120.000	169.0	V	220.0	13.3	19.9	30.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]


Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 3.32, CAL 07.01.2009
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW ---, CAL 08.04.2010 Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cabel with switch (0408)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 2: 1 - 4 GHz vertical/horizontal (lowest channel)




Carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 3: 4 - 12 GHz vertical/horizontal (lowest channel)



Plot 4: 12 - 25 GHz vertical/horizontal (valid for all channels)



Plot 5: 0.03 - 1 GHz vertical/horizontal (middle channel)


Common Information

EUT: AAD-3880001-BV + CAA-0003005-BV
 Serial Number: GT200004KZ (BT radiated)
 Test Description: FCC part 15 B class B @ 10 m
 Operating Conditions: BT CH 39 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: FCC_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver




Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
34.148700	9.5	15000.000	120.000	220.0	V	238.0	13.1	20.5	30.0	
44.821800	10.7	15000.000	120.000	220.0	V	314.0	13.5	19.3	30.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]


Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 3.32, CAL 07.01.2009
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW ---, CAL 08.04.2010 Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cabel with switch (0408)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 6: 1 - 4 GHz vertical/horizontal (middle channel)



Carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 7: 4 - 12 GHz vertical/horizontal (middle channel)



Plot 8: 0.03 - 1 GHz vertical/horizontal (highest channel)


Common Information

EUT: AAD-3880001-BV + CAA-0003005-BV
 Serial Number: GT200004KZ (BT radiated)
 Test Description: FCC part 15 B class B @ 10 m
 Operating Conditions: BT CH 78 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: FCC_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver




Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
33.463800	8.8	15000.000	120.000	100.0	V	50.0	13.0	21.2	30.0	
51.047900	11.1	15000.000	120.000	165.0	V	324.0	13.5	18.9	30.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]


Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 3.32, CAL 07.01.2009
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW ---, CAL 08.04.2010 Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cabel with switch (0408)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 9: 1 - 4 GHz vertical/horizontal (highest channel)



Carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 10: 4 - 12 GHz vertical/horizontal (highest channel)



Results:

SPURIOUS EMISSIONS LEVEL (dB μ V/m)								
2402 MHz			2441 MHz			2480 MHz		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
See Table above			No critical peaks found			No critical peaks found		
Measurement uncertainty			±3 dB					

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

Limits:

§ 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limits:

§ 15.109

Frequency (MHz)	Field strength (dB μ V/m)	Measurement distance (m)
30 - 88	30.0	10
88 - 216	33.5	10
216 - 960	36.0	10
above 960	54.0	3

5.16 Spurious Emissions - radiated (Receiver) § 15.109

Modulation: GFSK

Plot 1: 0.03 - 1 GHz vertical/horizontal (receiver)


Common Information

EUT: AAD-3880001-BV + CAA-0003005-BV
 Serial Number: GT200004KZ (BT radiated)
 Test Description: FCC part 15 B class B @ 10 m
 Operating Conditions: BT RX + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: FCC_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver




Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
33.217600	8.6	15000.000	120.000	163.0	V	78.0	13.0	21.4	30.0	
50.160200	11.8	15000.000	120.000	100.0	V	34.0	13.6	18.2	30.0	
103.194100	7.8	15000.000	120.000	195.0	V	235.0	12.0	25.7	33.5	


Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 3.32, CAL 07.01.2009
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW ---, CAL 08.04.2010 Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cabel with switch (0408)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


Plot 2: 1 - 4 GHz vertical/horizontal (receiver)



Plot 3: 4 - 12 GHz vertical/horizontal (receiver)



Plot 4: 12 - 25 GHz vertical/horizontal (receiver)



Results:

Spurious Emissions level [dB μ V/m]		
F[MHz]	Detector	Level [dB μ V/m]
No critical peaks detected !		
Measurement uncertainty		± 3 dB

f < 1 GHz: RBW/VBW: 100 kHz

f \geq 1GHz : RBW/VBW: 1 MHz

See above plots

Measurement distance see table

Limits:

§ 15.109

Frequency (MHz)	Field strength (dB μ V/m)	Measurement distance (m)
30 - 88	30.0	10
88 - 216	33.5	10
216 - 960	36.0	10
above 960	54.0	3


5.17 Spurious Emissions < 30 MHz - Transmitter radiated § 15.209

Modulation: GFSK

Measured at 3 m distance.

Values recalculated with 40 dB/decade according to FCC rules.

Plot 1:




Limits:

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30 / 29.5 dB $\mu\text{V/m}$	30


5.18 Conducted Emissions <30 MHz § 15.107/207

Modulation: GFSK


Plot 1:




Plot 2:



Plot 3:



Plot 4:



Limits:

Under normal test conditions only	See plots
-----------------------------------	-----------

6 Test equipment and ancillaries used for tests

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

All reported calibration intervals are calibrations according to the EN/ISO/IEC 17025 standard. These calibrations were performed from an accredited external calibration laboratory.

Additional to these calibrations the laboratory performed comparison measurements with other calibrated systems and performed a weekly chamber inspection.

All used devices are connected with a 10 MHz external reference.

According to the manufacturers' instruction is it possible to establish a calibration interval for the FSP unit of 24 month, if the device has an external 10 MHz reference.

Anechoic chamber C:

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Anechoic chamber	MWB	87400/02	300000996	Monthly verification		
2	System-Rack 85900	HP I.V.	*	300000222	n.a.		
3	Measurement System 1						
4	Spektrum Analyzer 8566B	HP	3138A07614	300001207	13.12.2007	24	13.12.2009
5	Spektrum Analyzer Display 85662A	HP	3144A28627	300001208	13.12.2007	24	13.12.2009
6	Quasi-Peak-Adapter 85650A	HP	2811A01204	300002308	13.12.2007	24	13.12.2009
7	RF-Preselector 85685A	HP	2837A00778	300002448	13.12.2007	24	13.12.2009
8	PC Vectra VL	HP		300001688	n.a.		
9	Software EMI	HP		300000983	n.a.		
10	Measurement System 2						
11	FSP 30	R&S	100886	300003575	25.08.2008	24	25.08.2010
12	PC	F+W			n.a.		
13	TILE	TILE			n.a.		
14	Biconical antenna	EMCO	S/N: 860 942/003		Monthly verification (System cal.)		
15	Log. Period. Antenna 3146	EMCO	2130	300001603	Monthly verification (System cal.)		
16	Double Ridged Antenna HP 3115P	EMCO	3088	300001032	Monthly verification (System cal.)		
17	Active Loop Antenna 6502	EMCO	2210	300001015	Monthly verification (System cal.)		
18	Power Supply 6032A	HP	2818A03450	300001040	12.05.2007	36	12.05.2010
19	Busisolator	Kontron		300001056	n.a.		
20	Leitungsteiler 11850C	HP		300000997	Monthly verification (System cal.)		
21	Power attenuator 8325	Byrd	1530	300001595	Monthly verification (System cal.)		
22	Band reject filter WRCG1855/1910	Wainwright	7	300003350	Monthly verification (System cal.)		
23	Band reject filter WRCG2400/2483	Wainwright	11	300003351	Monthly verification (System cal.)		

System Rack Room 005 :

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	FSP 30	R&S	100886	300003575	25.08.2008	24	25.08.2010
2	CBT	R&S	100313	300003516	03.09.2008	24	03.09.2010
3	Switch Matrix	HP		300000929	n.a.		
4	Power Supply	HP	3041A00544	300002270	13.05.2007	36	13.05.2010
5	Signal Generator	R&S	836206/0092	300002680	30.05.2007	36	30.05.2010

Signalling Units:

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	CBT	R&S	100313	300003516	24.10.2006	24	24.10.2008
2	CBT	R&S	100185	300003416	21.02.2006	24	21.02.2008
3	CMU-200	R&S	103992	300003231	27.04.2007	12	27.04.2008
4	CMU-200	R&S	106240	300003321	02.05.2006	24	02.05.2008
5	CMU-200	R&S	832221/0055	300002862	20.03.2008	24	20.03.2010

Climatic Box:

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Climatic box VT 4002	Heraeus Vötsch	58566046820010	300003019	11.05.2007	24	11.05.2009
2	Climatic box CTS T-40/50	CTS	064023	300003540	03.01.2007	24	03.01.2009

SRD Laboratory Room 002:

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	System Controller PSM 12	R&S	835259/007	3000002681-00xx	n.a.		
2	Memory Extension PSM-K10	R&S	To 1	3000002681	n.a.		
3	Operating Software PSM-B2	R&S	To 1	3000002681	n.a.		
4	19" Monitor		22759020-ED	3000002681	n.a.		
5	Mouse		LZE 0095/6639	3000002681	n.a.		
6	Keyboard		G00013834L461	3000002681	n.a.		
7	Spectrum Analyser FSIQ 26	R&S	835540/018	3000002681-0005	01.08.2006	24	01.08.2008
8	Tracking Generator FSIQ-B10	R&S	835107/015	3000002681	s.No.7		
10	RF-Generator SMIQ03 (B1 Signal)	R&S	835541/056	3000002681-0002	01.08.2006	36	01.08.2009
11	Modulation Coder SMIQ-B20	R&S	To 10	3000002681	s.No.10		
12	Data Generator SMIQ-B11	R&S	To 10	3000002681	s.No.10		
13	RF Rear Connection SMIQ-B19	R&S	To 10	3000002681	s.No.10		
14	Fast CPU SM-B50	R&S	To 10	3000002681	s.No.10		
15	FM Modulator SM-B5	R&S	835676/033	3000002681	s.No.10		
16	RF-Generator SMIQ03 (B2 Signal)	R&S	835541/055	3000002681-0001	01.08.2006	36	01.08.2009
17	Modulation Coder SMIQ-B20	R&S	To 16	3000002681	s.No.16		
18	Data Generator SMIQ-B11	R&S	To 16	3000002681	s.No.16		
19	RF Rear Connection SMIQ-B19	R&S	To 16	3000002681	s.No.16		
20	Fast CPU SM-B50	R&S	To 16	3000002681	s.No.16		
21	FM Modulator SM-B5	R&S	836061/022	3000002681	s.No.16		
22	RF-Generator SMP03 (B3 Signal)	R&S	835133/011	3000002681-0003	01.08.2006	36	01.08.2009
23	Attenuator SMP-B15	R&S	835136/014	3000002681	S.No.22		
24	RF Rear Connection SMP-B19	R&S	834745/007	3000002681	S.No.22		
25	Power Meter NRVD	R&S	835430/044	3000002681-0004	01.08.2006	24	01.08.2008
26	Power Sensor NRVD-Z1	R&S	833894/012	3000002681-0013	01.08.2006	24	01.08.2008
27	Power Sensor NRVD-Z1	R&S	833894/011	3000002681-0010	01.08.2006	24	01.08.2008
28	Rubidium Standard RUB	R&S		3000002681-0009	01.08.2006	24	01.08.2008

29	Switching and Signal Conditioning Unit SSCU	R&S	338864/003	3000002681-0006	01.08.2006	24	01.08.2008
30	Laser Printer HP Deskjet 2100	HP	N/A	3000002681-0011	n.a.		
31	19" Rack	R&S	11138363000004	3000002681	n.a.		
32	RF-cable set	R&S	N/A	3000002681	n.a.		
33	IEEE-cables	R&S	N/A	3000002681	n.a.		
34	Sampling System FSIQ-B70	R&S	835355/009	3000002681	s.No.7		
35	RSP programmable attenuator	R&S	834500/010	3000002681-0007	01.08.2006	24	01.08.2008
36	Signalling Unit	R&S	838312/011	3000002681	n.a.		
37	NGPE programmable Power Supply for EUT	R&S	192.033.41	3000002681			
39	Power Splitter 6005-3	Inmet Corp.	none	300002841	23.12.2006	24	23.12.2008
40	SMA Cables SPS-1151-985-SPS	Insulated Wire	different	different	n.a.		
41	CBT32 with EDR Signalling Unit	R&S					
42	Coupling unit	Narda	N/A	--	n.a.		
43	2xSwitch Matrix PSU	R&S	872584/021	300001329	n.a.		
44	RF-cable set	R&S	N/A	different	n.a.		
45	IEEE-cables	R&S	N/A	--	n.a.		

Note: 3000002681-00xx inventoried as a system

SRD Laboratory Room 005:

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Spektrum Analyzer 8566B	HP	2747A05275	300000219	08.11.2006	24	08.11.2008
2	Spektrum Analyzer Display 85662A	HP	2816A16497	300001690	08.11.2006	24	08.11.2008
3	Quasi-Peak-Adapter 85650A	HP	2811A01135	300000216	08.11.2006	24	08.11.2008
4	Power Supply	Heiden	003202	300001187	12.05.2007	36	12.05.2010
5	Power Supply	Heiden	1701	300001392	12.05.2007	36	12.05.2010

SRD Laboratory Room 011:

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	NRP Power Meter	R&S	100212	300003780	27.02.2008	24	27.02.2010

Anechoic chamber F:

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Control Computer	F+W	FW0502032	300003303	-/-	-/-	-/-
2	Trilog Antenna	9163-295	-/-	-/-	30.04.2008	24	30.04.2010
3	Amplifier - 0518C-138	Veritech Micro-wave Inc.	-/-	-/-	-/-	-/-	-/-
4	Switch - 3488A	HP		300000368	-/-	-/-	-/-
5	EMI Test receiver - ESCI	R&S	100083	300003312	31.01.2009	24	31.01.2009
6	Turntable Controller - 1061 3M	EMCO	1218	300000661	-/-	-/-	-/-
7	Tower Controller 1051 Controller	EMCO	1262	300000625	-/-	-/-	-/-
8	Tower - 1051	EMCO	1262	300000625	-/-	-/-	-/-
10	Ultra Notch-Filter Rejected band Ch. 62	WRCD	9	-/-	-/-	-/-	-/-

C.BER Bluetooth Rack Room AC2:

No	Equipment/Type	Manuf.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	System Controller with XP Prof. & C.BER Control Software	F&W	300003580	na		
2	GPIO to USB Converter	Agilent	300003426	na		
3	Spectrum Analyser FSIQ26	R&S	300002681-005	01.08.2006	24	01.08.2008
	Sampling System FSIQ-B70	R&S	300002681-005	01.08.2006	24	01.08.2008
	Tracking Generator FSIQ-B10 for FSIQ26	R&S	300002681-005	01.08.2006	24	01.08.2008
4	RF-Generator SMIQ03 (Interferer Signal)	R&S	300002681-001	01.08.2006	24	01.08.2008
	Modulation Coder SMIQ-B20	R&S	300002681-001	01.08.2006	24	01.08.2008
	Data Generator SMIQ-B11	R&S	300002681-001	01.08.2006	24	01.08.2008
	RF Rear Connection SMIQ-B19	R&S	300002681-001	01.08.2006	24	01.08.2008
	Fast CPU SM-B50	R&S	300002681-001	01.08.2006	24	01.08.2008
	FM Modulator SM-B5	R&S	300002681-001	01.08.2006	24	01.08.2008
5	Rubidium Standard RUB	R&S	300002681-009	01.08.2006	24	01.08.2008
6	Switching Unit 3488A including 2 44476A cards	HP	300000926	Verified with path compensation		
	44472A VHF switch	HP	300000926	Verified with path compensation		
7	Signalling Unit: CBT with EDR	R&S	300003416	24.06.2006	24	24.06.2008
8	RF-cable set	different	no	Verified with path compensation		
9	IEEE-cables	R&S	no	na		
10	NGPE programmable Power Supply for EUT	R&S	400000078	01.08.2006	24	01.08.2008
11	Coupling Unit 4324-2	Narda	no	Verified with path compensation		
12	Climatic Chamber VT4002	Voetch	300003019	11.05.2007	24	11.05.2009
13	6 dB Attenuator 1W	Narda	no	Verified with path compensation		
14	DC Blocker 30 MHz to 12.75 GHz 1W	Narda	no	Verified with path compensation		