



Accredited testing-laboratory

DAR registration number: DAT-P-176/94-D1

**Federal Motor Transport Authority (KBA)
DAR registration number: KBA-P 00070-97**

Recognized by the Federal Communications Commission

Anechoic chamber registration no.: 90462 (FCC)

Anechoic chamber registration no.: 3462C-1 (IC)

Certification ID: DE 0001

Accreditation ID: DE 0002

Accredited Bluetooth® Test Facility (BQTF)

*The Bluetooth word mark and logos are owned by the Bluetooth SIG,
Inc. and any use of such marks by Cetecom ICT is under license*

Test report no. : 1-1065-22-04/09-A
Type identification : AAD-3880023-BV
Applicant : Sony Ericsson Mobile Communications AB
FCC ID : PY7A3880023
IC Certification No : 4170B-A3880023
Test standards : 47 CFR Part 15
RSS - 210 Issue 7

Table of contents

1	General information.....	3
1.1	Notes	3
1.2	Testing laboratory	4
1.3	Details of applicant	4
1.4	Application details	4
2	Test standard/s	5
3	Technical tests	6
3.1	Details of manufacturer.....	6
3.1.1	Test item.....	6
3.1.2	Additional EUT information For IC Canada (appendix 2).....	7
3.1.3	EUT operating modes.....	8
3.1.4	Extreme conditions testing values	8
4	Summary of Measurement Results and list of all performed test cases	9
5	RF measurement testing	10
5.1	Description of test set-up.....	10
5.1.1	Radiated measurements.....	10
5.1.2	Conducted measurements.....	10
5.2	Referenced documents	11
5.3	Additional comments	11
5.4	Antenna gain	11
5.5	Carrier frequency separation §15.247(a)(1)	12
5.6	Number of hopping channels §15.247(a)(1)	13
5.7	Time of occupancy (dwell time) §15.247(a)(1)(iii).....	14
5.8	Power Spectral density (Hybrid system in Inquiry mode/Page scan) §15.247(e)	15
5.9	Spectrum Bandwidth of a FHSS System / 20dB Bandwidth §15.247(a)(1).....	16
5.10	Maximum output power (conducted) § 15.247 (b)(1).....	21
5.11	Max. peak output power (radiated) § 15.247 (b)(1)	26
5.12	Band-edge compliance of conducted emissions §15.247 (d)	27
5.13	Band-edge compliance of radiated emissions §15.205	34
5.14	Spurious Emissions - conducted (Transmitter) § 15.247 (c)(1)	37
5.15	Spurious Emissions > 30 MHz- radiated (Transmitter) § 15.247 (c)(1).....	43
5.16	Spurious Emissions - radiated (Receiver) § 15.109	51
5.17	Spurious Emissions < 30 MHz - Transmitter radiated § 15.209	54
5.18	Conducted Emissions <30 MHz § 15.107/207.....	55
6	Test equipment and ancillaries used for tests	56
7	Photographs of the Test Set-up.....	59
8	Photographs of the EUT	61

1 General information

1.1 Notes

The test results of this test report relate exclusively to the test item specified in 3.1.1. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

Test laboratory manager:

2009-04-02 **Joerg Warken**

Date

Name

Signature

2009-04-02 **Andreas Keller**

Date

Name

Signature

2009-04-02 **Jakob Reschke**

Date

Name

Signature

Technical responsibility for area of testing:

2009-04-02 **Michael Berg**

Date

Name

Signature

1.2 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6 - 10

66117 Saarbrücken

Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

e-mail: info@ICT.cetecom.de

Internet: <http://www.cetecom-ict.de>

State of accreditation: The test laboratory (area of testing) is accredited according to
DIN EN ISO/IEC 17025
DAR registration number: DAT-P-176/94-D1

Accredited by: Federal Motor Transport Authority (KBA)
DAR registration number: KBA-P 00070-97

Testing location, if different from CETECOM ICT Services GmbH:

Name :
Street :
Town :
Country :
Phone :
Fax :

1.3 Details of applicant

Name:	Sony Ericsson Mobile Communications AB
Street:	Mobilvägen 10
Town:	22188 Lund
Country:	Sweden
Telephone:	+46-46-19-3000
Fax:	+46-10-800-2441
Contact:	Mr. Peter Lindeborg
E-mail:	peter.lindeborg@sonyericsson.com
Telephone:	+46-10-802-43 68

1.4 Application details

Date of receipt of order:	2009-03-11
Date of receipt of test item:	2009-03-11
Date of start test:	2009-03-11
Date of end test	2009-03-31
Persons(s) who have been present during the test:	-/-

2 Test standard/s

47 CFR Part 15	2008-07	Title 47 of the Code of Federal Regulations; Chapter I- Federal Communications Commission subchapter A - general, Part 15-Radio frequency devices
RSS - 210 Issue 7	2007-06	Spectrum Management and Telecommunications - Radio Standards Specification Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

3 Technical tests

3.1 Details of manufacturer

Name:	Sony Ericsson Mobile Communications AB
Street:	Mobilvägen 10
Town:	22188 Lund
Country:	Sweden

3.1.1 Test item

Kind of test item	:	Mobile Phone GSM 850/900/1800/1900 / UMTS FDD 1/8, HSDPA, HSUPA / BT2.0+EDR / GPS / AGPS / WLAN / Flight Mode
Type identification	:	AAD-3880023-BV
S/N serial number	:	Rad. CB5A10TNPG Cond. CB5A10TNGJ, CB5A10WUDF
HW hardware status	:	A
SW software status	:	-/-
Frequency Band [MHz]	:	ISM 2.400 - 2.483,5
Type of Modulation	:	FHSS
Number of channels	:	79
Antenna	:	Integrated antenna
Power Supply	:	3.60 V DC by Li-Polymer Battery (BST-38) and Power Supply
Temperature Range	:	-20 °C to 60 °C

Max. power radiated: 1.48 dBm

Max. power conducted: 4.19 dBm

FCC ID: PY7A3880023

IC: 4170B-A3880023

3.1.2 Additional EUT information For IC Canada (appendix 2)

IC Registration Number:	4170B-A3880023
Model Name:	AAD-3880023-BV
Manufacturer (complete Address):	Sony Ericsson Mobile Communications AB Mobilvägen 10 22188 Lund Sweden
Tested to Radio Standards Specification (RSS) No.:	RSS-210 Issue 7
Open Area Test Site Industry Canada Number:	IC 3462C-1
Frequency Range (or fixed frequency) [MHz]:	2400 – 2483.5 MHz
RF: Power [W] (max):	<u>GFSK</u> Rad. EIRP: 1.37 mW Conducted : 2.55 mW <u>Pi/4 DQPSK</u> Rad. EIRP: 1.32 mW Conducted : 2.48 mW <u>8 DPSK</u> Rad. EIRP: 1.41 mW Conducted : 2.62 mW
Antenna Type:	Integrated antenna
Occupied Bandwidth (99% BW) [kHz]:	GFSK: 920 Pi/4 DQPSK: 1329 8 DPSK: 1269
Type of Modulation:	GFSK, Pi/4 DQPSK, 8 DPSK
Emission Designator (TRC-43):	GFSK: 920KFXD Pi/4 DQPSK: 1M33GXD 8 DPSK: 1M27GXD
Transmitter Spurious (worst case) [μ V/m in 3m]:	112 (noise floor)
Receiver Spurious (worst case) [μ V/m in 3m]:	112 (noise floor)

ATTESTATION:

I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned departmental standard(s), and that the radio equipment identified in this application has been subject to all applicable test conditions specified in the departmental standards and all of the requirements of the standards have been met.

Signature:



Test engineer: Joerg Warken

Date: 2009-03-31

3.1.3 EUT operating modes

EUT operating mode no. *)	Description of operating modes	Additional information
Op. 0	Normal mode	Normal temperature and power source conditions
Op. 1		low temperature, low power source conditions
Op. 2		low temperature, high power source conditions
Op. 3		high temperature, low power source conditions
Op. 4		high temperature, high power source conditions

*) EUT operating mode no. is used to simplify the test plan

3.1.4 Extreme conditions testing values

Description	Shortcut	Unit	Value
Nominal Temperature	T _{nom}	°C	22
Nominal Humidity	H _{nom}	%	53
Nominal Power Source	V _{nom}	V	3.60

Type of power source: **DC by Li-Polymer Battery (BST-38) and Power Supply**

Deviations from these values are reported in chapter 2

4 Summary of Measurement Results and list of all performed test cases

☒ No deviations from the technical specifications were ascertained

☐ There were deviations from the technical specifications ascertained

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC Part 15 §15.247 - CANADA RSS-210	PASS	2009-03-31	-/-

Test Specification Clause	Test Case	Modulation	Pass	Fail	N/A	Not performed
None	Antenna Gain	GFSK	Yes			
§15.247(a1)	Carrier frequency separation	GFSK	Yes			
§15.247(a1)	Number of hopping channels	GFSK	Yes			
§15.247(a)(1)(iii)	Time of occupancy (dwell time)	--	Yes			
§15.247(e)	Power Spectral density (Hybrid system in Inquiry mode/Page scan)	--			Yes	
§15.247(a)(1)	Spectrum Bandwidth of a FHSS System / 20dB Bandwidth	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (b)(1)	Maximum output power (conducted)	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (b)(1)	Max. peak output power (radiated)	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (d)	Band-edge compliance of conducted emissions	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.205	Band-edge compliance of radiated emissions	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (d)	Spurious Emission - conducted (Transmitter)	GFSK Pi/4 DQPSK 8 DPSK	Yes Yes Yes			
§ 15.247 (d)	Spurious Emission - radiated (Transmitter) >30 MHz	8 DPSK	Yes			
§ 15.109	Spurious Emissions - radiated (Receiver)	GFSK	Yes			
§ 15.209	Spurious Emissions - radiated (Transmitter) <30 MHz	8 DPSK	Yes			
§ 15.107/207	Conducted Emissions <30 MHz	8 DPSK	Yes			

5 RF measurement testing

5.1 Description of test set-up

5.1.1 Radiated measurements

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 25 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63.2-1996 clause 15 and ANSI C63.4-2003 clause 4.1.5. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63-4-2003 clause 4.2. Antennas are confirmed with ANSI C63.2-1996 item 15.


9 kHz - 150 kHz: Quasi Peak measurement, 200 Hz Bandwidth, passive loop antenna.
150 kHz - 30 MHz: Quasi Peak measurement, 9 kHz Bandwidth, passive loop antenna.
30 MHz - 200 MHz: Quasi Peak measurement, 120 kHz Bandwidth, bi-conical antenna
200MHz - 1GHz: Quasi Peak measurement, 120 kHz Bandwidth, log periodic antenna
>1GHz: Average, RBW 1MHz, VBW 10 Hz, waveguide horn

All measurements are done in accordance with the Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems DA 00-705 and Appendix A "BLUETOOTH APPROVALS"

The EUT is powered by an external power supply with nominal voltage. The signalling is performed from outside the chamber with a signalling unit (CMU200 or other) by air link using signalling antenna.

5.1.2 Conducted measurements

The EUT's RF signal is coupled out by the antenna connector which is supplied by the manufacturer. The signal is first 10dB attenuated before it is power divided (~6dB loss per branch). One of the signal paths is connected to the communication base Station (CMU200 or other), the other one is connected to the spectrum analyzer. The specific losses for both signal paths are first checked within a calibration. The measurement readings on the signalling unit/spectrum analyzer are corrected by the specific test set-up loss. The attenuator, power divider, signalling unit and the spectrum analyzer are impedance matched on 50 Ohm.



5.2 Referenced documents

None

5.3 Additional comments

None

5.4 Antenna gain


The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

	low channel 2402 MHz	mid channel 2441 MHz	high channel 2480 MHz
Conducted power [dBm] Measured, GFSK modulation	4.07	4.07	3.57
Radiated power [dBm] Measured, GFSK modulation	-0.14	1.07	1.38
Gain [dBi] Calculated	-4.21	-3.00	-2.19

5.5 Carrier frequency separation §15.247(a)(1)

Modulation: GFSK

Plot 1 of 1:



Result: Channel separation is: ~ 1 MHz


Limits:

Under normal test conditions only	Minimum 25 kHz or 20 dB Bandwidth of the hopping system
-----------------------------------	---


5.6 Number of hopping channels §15.247(a)(1)

Modulation: GFSK

Plot 1 of 2:



Plot 2 of 2:



Result: The number of hopping channels is: 79

Limits:

Under normal test conditions only	at least 15 non-overlapping channels
-----------------------------------	--------------------------------------

5.7 Time of occupancy (dwell time) §15.247(a)(1)(iii)

For Bluetooth devices:

The dwell time of 0.4 s within a 31.6 second period in data mode is independent from the packet type (packet length). The calculation for a 31.6 second period is as follows:

Dwell time = time slot length * hop rate / number of hopping channels * 31.6 s

Example for a DH1 packet (with a maximum length of one time slot)

Dwell time = $625 \mu\text{s} * 1600 \text{ 1/s} / 79 * 31.6 \text{ s} = 0.4 \text{ s}$ (in a 31.6 s period)

For multi-slot packet the hopping is reduced according to the length of the packet.

Example for a DH5 packet (with a maximum length of five time slots)

Dwell time = $5 * 625 \mu\text{s} * 1600 * 1/5 * 1/s / 79 * 31.6 \text{ s} = 0.4 \text{ s}$ (in a 31.6 s period)

This is according to the Bluetooth Core Specification V 1.1 & V 1.2 & V2.0 (+ critical errata) for all Bluetooth devices.

Therefore, all Bluetooth devices comply with the FCC dwell time requirement in the data mode.

This was checked during the Bluetooth Qualification tests.

The Dwell time in hybrid mode is approximately 2.6 ms (in a 12.8s period)

5.8 Power Spectral density (Hybrid system in Inquiry mode/Page scan) §15.247(e)

Plot 1 of 1:

Not applicable


Result: Power density: - dBm/Hz = - dBm / 3 kHz
Correction factor from dBm/Hz to dBm / 3 kHz is +34,8 dB

Limits:


Under normal test conditions only	For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission
-----------------------------------	---

5.9 Spectrum Bandwidth of a FHSS System / 20dB Bandwidth §15.247(a)(1)


Plot 1: GFSK




Plot 2: GFSK




Plot 3: GFSK




Plot 4: Pi/4 DQPSK




Plot 5: Pi/4 DQPSK




Plot 6: Pi/4 DQPSK




Plot 7: 8DPSK



Plot 8: 8DPSK



Plot 9: 8DPSK



Result:

Modulation Frequency [MHz]	20 dB BANDWIDTH [kHz]		
	2402	2441	2480
GFSK	920	920	920
Pi/4 DQPSK	1329	1329	1329
8DPSK	1269	1269	1263
Measurement uncertainty	±1kHz		


RBW / VBW as provided in the „Measurement Guidelines“ (DA 00-705, March 30, 2000)
RBW: 10 kHz / VBW 10 kHz

Limits:


Under normal test conditions only	GFSK < 1000 kHz Pi/4 DQPSK < 1500 8DPSK < 1500
-----------------------------------	--

5.10 Maximum output power (conducted) § 15.247 (b)(1)

Plot 1: GFSK




Plot 2: GFSK




Plot 3: GFSK




Plot 4: Pi/4 DQPSK




Plot 5: Pi/4 DQPSK




Plot 6: Pi/4 DQPSK




Plot 7: 8DPSK



Plot 8: 8DPSK



Plot 9: 8DPSK



Results:

Modulation Frequency [MHz]	Max. peak output power [dBm]		
	2402	2441	2480
GFSK	4.07	4.07	3.57
Pi/4 DQPSK	3.92	3.95	3.41
8DPSK	4.19	4.19	3.67
Measurement uncertainty	±2dB		

RBW / VBW: 3 MHz

Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
--	---------------

5.11 Max. peak output power (radiated) § 15.247 (b)(1)

Modulation: GFSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2402	2442	2480
T _{nom}	V _{nom}	-0.14	1.07	1.38
Measurement uncertainty		±3dB		

Modulation: Pi/4 DQPSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2402	2442	2480
T _{nom}	V _{nom}	-0.29	0.95	1.22
Measurement uncertainty		±3dB		

Modulation: 8 DPSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2402	2442	2480
T _{nom}	V _{nom}	-0.02	1.19	1.48
Measurement uncertainty		±3dB		

RBW / VBW: 3 MHz

Measured at a distance of 3m


Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
--	---------------


5.12 Band-edge compliance of conducted emissions §15.247 (d)

Modulation: GFSK


Plot 1 of 4 (hopping off, lowest frequency):




Plot 2 of 4 (hopping on, lowest frequency):



Plot 3 of 4 (hopping off, highest frequency):



Plot 4 of 4 (hopping on, highest frequency):




Results:


SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB

Modulation: Pi/4 DQPSK

Plot 1 of 4 (hopping off, lowest frequency):




Plot 2 of 4 (hopping on, lowest frequency):




Plot 3 of 4 (hopping off, highest frequency):

C.BER by Cetecom Saarbruecken Germany



Plot 4 of 4 (hopping on, highest frequency):

C.BER by Cetecom Saarbruecken Germany




Results:


SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB

Modulation: 8 DPSK


Plot 1 of 4 (hopping off, lowest frequency):




Plot 2 of 4 (hopping on, lowest frequency):



Plot 3 of 4 (hopping off, highest frequency):



Plot 4 of 4 (hopping on, highest frequency):



Results:

SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB


Limits:

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).
-----------------------------------	--


5.13 Band-edge compliance of radiated emissions §15.205

Modulation: GFSK

Plot 1: Band edge compliance and far away emissions – Lowest Channel



Plot 2: Band edge compliance and far away emissions – Highest Channel




Date: 25.MAR.2009 16:45:47

Limit: 54 dBμV


Verdict: Pass

Modulation: Pi/4 DQPSK

Plot 1: Band edge compliance and far away emissions – Lowest Channel



Plot 2: Band edge compliance and far away emissions – Highest Channel




Date: 25.MAR.2009 16:51:10

Limit: 54 dBμV


Verdict: Pass

Modulation: 8 DPSK

Plot 1: Band edge compliance and far away emissions – Lowest Channel



Plot 2: Band edge compliance and far away emissions – Highest Channel



Date: 25.MAR.2009 16:52:26


Limit: 54 dBμV

Verdict: Pass


5.14 Spurious Emissions - conducted (Transmitter) § 15.247 (c)(1)

Modulation: GFSK


Plot 1 of 3: lowest channel



Plot 2 of 3: middle channel



Plot 3 of 3: highest channel


Result & Limits:

Emission Limitation					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402		3.99	30 dBm		Operating frequency
			-20 dBc		
2441		3.95	30 dBm		Operating frequency
			-20 dBc		
2480		3.44	30 dBm		Operating frequency
			-20 dBc		
Measurement uncertainty		± 3dB			


F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
 F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Modulation: Pi/4 DQPSK


Plot 1 of 3: lowest channel



Plot 2 of 3: middle channel



Plot 3 of 3: highest channel




Result & Limits:

Emission Limitation					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402		3.48	30 dBm		Operating frequency
			-20 dBc		
2441		3.41	30 dBm		Operating frequency
			-20 dBc		
2480		2.86	30 dBm		Operating frequency
			-20 dBc		
Measurement uncertainty			± 3dB		


F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Modulation: 8 DPSK


Plot 1 of 3: lowest channel



Plot 2 of 3: middle channel



Plot 3 of 3: highest channel

Result & Limits:

Emission Limitation					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402		3.51	30 dBm		Operating frequency
			-20 dBc		
2441		3.43	30 dBm		Operating frequency
			-20 dBc		
2480		2.81	30 dBm		Operating frequency
			-20 dBc		
Measurement uncertainty		± 3dB			

F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
 F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
-----------------------------------	--

Note: For emissions that fall into restricted bands you find the radiated emissions later in the report.

5.15 Spurious Emissions > 30 MHz- radiated (Transmitter) § 15.247 (c)(1)

Modulation: 8 DPSK

Plot 1: 0.03 - 1 GHz vertical/horizontal (lowest channel)


Common Information

EUT:	AAD-3880023-BV + CAA 0002001-BV
Serial Number:	IMEI: 00440107-728091-1
Test Description:	FCC Part 15B
Operating Conditions:	BT: Tx channel 0 + charging
Operator Name:	COA
Comment:	Powered by 115 V/ 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)
Level Unit:	dB μ V/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver



Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
46.473100	9.1	15000.000	120.000	220.0	V	151.0	13.5	20.9	30.0	
46.503700	9.4	15000.000	120.000	165.0	V	207.0	13.5	20.6	30.0	
49.019550	13.8	15000.000	120.000	135.0	V	35.0	13.5	16.2	30.0	
50.196900	10.5	15000.000	120.000	220.0	V	160.0	13.5	19.5	30.0	
52.579050	11.2	15000.000	120.000	98.0	V	40.0	13.3	18.8	30.0	
458.768850	13.9	15000.000	120.000	220.0	V	84.0	18.2	22.1	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1

Frequency Range: 30 MHz - 2 GHz

Receiver: Receiver [ESCI 3]
@ GPIB0 (ADR 20), SN 100083/003, FW 4.32


Signal Path: without Notch
FW 1.0

Antenna: VULB 9163
SN 9163-295, FW ---
Correction Table (vertical): VULP6113
Correction Table (horizontal): VULP6113
Correction Table: Cable_EN_1GHz (0109)


Antenna Tower: Tower [EMCO 2090 Antenna Tower]
@ GPIB0 (ADR 8), FW REV 3.12

Turntable: Turntable [EMCO Turntable]
@ GPIB0 (ADR 9), FW REV 3.12

Plot 2: 1 - 12 GHz vertical/horizontal (lowest channel)



Plot 3: 12 - 25 GHz vertical/horizontal (valid for all channels)



Start 12 GHz

1.45 GHz/

Stop 26.5 GHz

Date:

25.MAR.2009 18:32:12

Plot 4: 0.03 - 1 GHz vertical/horizontal (middle channel)


Common Information

EUT:	AAD-3880023-BV + CAA 0002001-BV
Serial Number:	IMEI: 00440107-728091-1
Test Description:	FCC Part 15B
Operating Conditions:	BT: Tx channel 39 + charging
Operator Name:	COA
Comment:	Powered by 115 V/ 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)
Level Unit:	dB μ V/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
45.470550	9.8	15000.000	120.000	157.0	V	233.0	13.4	20.2	30.0	
47.029450	13.9	15000.000	120.000	161.0	V	246.0	13.5	16.1	30.0	
49.063950	11.8	15000.000	120.000	112.0	V	274.0	13.5	18.2	30.0	
49.498750	10.2	15000.000	120.000	118.0	V	-2.0	13.5	19.8	30.0	
629.838200	18.3	15000.000	120.000	122.0	V	-1.0	21.6	17.7	36.0	
693.735300	19.7	15000.000	120.000	117.0	V	273.0	22.8	16.3	36.0	

Hardware Setup: EMI radiated/Electric Field (NOS) - [EMI radiated]

Subrange 1

Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0109)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 5: 1 - 12 GHz vertical/horizontal (middle channel)



Plot 6: 0.03 - 1 GHz vertical/horizontal (highest channel)


Common Information

EUT:	AAD-3880023-BV + CAA 0002001-BV
Serial Number:	IMEI: 00440107-728091-1
Test Description:	FCC Part 15B
Operating Conditions:	BT: Tx channel 78 + charging
Operator Name:	COA
Comment:	Powered by 115 V/ 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)
Level Unit:	dB μ V/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver



Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
45.989700	15.3	15000.000	120.000	220.0	V	192.0	13.4	14.7	30.0	
49.996000	13.7	15000.000	120.000	112.0	V	323.0	13.5	16.3	30.0	
51.988750	515.5	15000.000	120.000	178.0	V	207.0	13.4	-485.5	30.0	
53.828850	11.3	15000.000	120.000	220.0	V	186.0	13.2	18.7	30.0	
54.087450	10.2	15000.000	120.000	152.0	V	167.0	13.2	19.8	30.0	
74.681800	7.1	15000.000	120.000	220.0	V	100.0	9.5	22.9	30.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1

Frequency Range: 30 MHz - 2 GHz

Receiver: Receiver [ESCI 3]
@ GPIB0 (ADR 20), SN 100083/003, FW 4.32


Signal Path: without Notch
FW 1.0

Antenna: VULB 9163
SN 9163-295, FW ---
Correction Table (vertical): VULP6113
Correction Table (horizontal): VULP6113
Correction Table: Cable_EN_1GHz (0109)

Antenna Tower: Tower [EMCO 2090 Antenna Tower]
@ GPIB0 (ADR 8), FW REV 3.12

Turntable: Turntable [EMCO Turntable]
@ GPIB0 (ADR 9), FW REV 3.12

Plot 7: 1 - 12 GHz vertical/horizontal (highest channel)



Results:

SPURIOUS EMISSIONS LEVEL (dB μ V/m)								
2402 MHz			2441 MHz			2480 MHz		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
No critical peaks found			No critical peaks found			No critical peaks found		
Measurement uncertainty			± 3 dB					

$f < 1$ GHz : RBW/VBW: 100 kHz

$f \geq 1$ GHz : RBW/VBW: 1 MHz

Limits: § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limits: § 15.209

Frequency (MHz)	Field strength (dB μ V/m)	Measurement distance (m)
30 - 88	30.0	10
88 - 216	33.5	10
216 - 960	36.0	10
above 960	54.0	3

5.16 Spurious Emissions - radiated (Receiver) § 15.109

Modulation: GFSK

Plot 1: 0.03 - 1 GHz vertical/horizontal (receiver)


Common Information

EUT:	AAD-3880023-BV + CAA 0002001-BV
Serial Number:	IMEI: 00440107-728091-1
Test Description:	FCC Part 15B
Operating Conditions:	BT: Rx + charging
Operator Name:	COA
Comment:	Powered by 115 V/ 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)
Level Unit:	dB μ V/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
44.981100	12.5	15000.000	120.000	98.0	V	232.0	13.4	17.5	30.0	
46.980250	14.6	15000.000	120.000	199.0	V	132.0	13.5	15.4	30.0	
49.992750	14.0	15000.000	120.000	204.0	V	46.0	13.5	16.0	30.0	
69.975400	9.1	15000.000	120.000	220.0	V	87.0	9.6	20.9	30.0	
675.699400	19.1	15000.000	120.000	145.0	H	239.0	22.4	16.9	36.0	
691.556900	19.6	15000.000	120.000	147.0	V	9.0	22.8	16.4	36.0	

Hardware Setup: EMI radiated/Electric Field (NOS) - [EMI radiated]


Subrange 1

Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0109)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 2: 1 - 12 GHz vertical/horizontal (receiver)



Plot 3: 12 - 25 GHz vertical/horizontal (receiver)

Results:

Spurious Emissions level [dBμV/m]		
f[MHz]	Detector	Level [dBμV/m]
No critical peaks found		
Measurement uncertainty		±3 dB

f < 1 GHz: RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

See above plots

Measurement distance see table

Limits: § 15.109

Frequency (MHz)	Field strength (dBμV/m)	Measurement distance (m)
30 - 88	30.0	10
88 - 216	33.5	10
216 - 960	36.0	10
above 960	54.0	3


5.17 Spurious Emissions < 30 MHz - Transmitter radiated § 15.209

Modulation: 8 DPSK

Measured at 3 m distance.

Values recalculated with 40 dB/decade according to FCC rules.

Plot 1:




Limits:

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30 / 29.5 dB $\mu\text{V/m}$	30


5.18 Conducted Emissions <30 MHz § 15.107/207

Modulation: 8 DPSK

Plot 1: Phase Line



Plot 2: Neutral Line



Limits:

Under normal test conditions only	See plots
-----------------------------------	-----------

6 Test equipment and ancillaries used for tests

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

All reported calibration intervals are calibrations according to the EN/ISO/IEC 17025 standard. These calibrations were performed from an accredited external calibration laboratory.

Additional to these calibrations the laboratory performed comparison measurements with other calibrated systems and performed a weekly chamber inspection.

All used devices are connected with a 10 MHz external reference.

According to the manufacturers' instruction is it possible to establish a calibration interval for the FSP unit of 24 month, if the device has an external 10 MHz reference.

Anechoic chamber A:

No.	Instrument/Ancillary	Manufacturer	Type	Serial-No.	Internal identification
Radiated emission in chamber A					
A-1	Spectrum Analyzer	Rohde & Schwarz	ESU26	100037	300003555
A-2	Signal Generator	Rohde & Schwarz	SMR20B11	1104.0002.20	300003593
A-3	RF System Panel	Rohde & Schwarz	TS RSP	---	300003556
A-4	Relais Matrix	Rohde & Schwarz	PSN	860673/009	300001385
A-5	Horn Antenna	EMCO	3115	9709-5290	300000212
A-6	Bilog.-Log. Antenna	Schwarzbeck	VULB 9163	02/00	300003696
A-7	Notch Filter GSM 900	Wainwright	WRCD 901.9/903.1EE	9	---
A-8	Notch Filter GSM 1800	Wainwright	WRCD 1747/1748-5EE	1	---
A-9	Notch Filter GSM 1900	Wainwright	WRCB 1879.5/1880.5EE	9	---
A-10	Notch Filter GSM 850	Wainwright	WRCT 837-0.2/50-8EE	1	---
A-11	Notch Filter UMTS	Wainwright	WRCD 1800/2000-0.2/40-5EEK	2	---
A-12	Notch Filter ISM 2400	Wainwright	WRCG 2400/ 2483-2375/2505-50/10SS	26	---
A-13	High Pass Filter 1.1 GHz	Wainwright	WHK 1.1/15G-10SS	---	---
A-14	High Pass Filter 2.6 GHz	Wainwright	WHKX 2.6/18G-12SS	---	---
A-15	High Pass Filter 7 GHz	Wainwright	WHKX 7.0/18G-8SS	---	---
A-14	Amplifier	Miteq	AFS4-00201800-15-10P-6	US42-0050 2650-28-5A	300003204
A-16	Controller	Inn co	CO 2000	2020507	---
A-17	DC Power Supply	Hewlet Packard	HP6632A	---	300000924
A-18	Computer	F+W	---	---	300003303

SRD Laboratory Room 002:

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	System Controller PSM 12	R&S	835259/007	3000002681-00xx	n.a.		
2	Memory Extension PSM-K10	R&S	To 1	3000002681	n.a.		
3	Operating Software PSM-B2	R&S	To 1	3000002681	n.a.		
4	19" Monitor		22759020-ED	3000002681	n.a.		
5	Mouse		LZE 0095/6639	3000002681	n.a.		
6	Keyboard		G00013834L461	3000002681	n.a.		
7	Spectrum Analyser FSIQ 26	R&S	835540/018	3000002681-0005	10.01.2008	24	10.01.2010
8	Tracking Generator FSIQ-B10	R&S	835107/015	3000002681	s.No.7		
10	RF-Generator SMIQ03 (B1 Signal)	R&S	835541/056	3000002681-0002	26.08.2008	36	26.08.2011
11	Modulation Coder SMIQ-B20	R&S	To 10	3000002681	s.No.10		
12	Data Generator SMIQ-B11	R&S	To 10	3000002681	s.No.10		
13	RF Rear Connection SMIQ-B19	R&S	To 10	3000002681	s.No.10		
14	Broadband horn antenna (1-18 GHz)	EMCO	9107-3696	300001604	16.04.2008	24	16.04.2010
15	Broadband horn antenna (1-18 GHz)	EMCO	9107-3697	300001605	21.08.2008	24	21.08.2010
16	Std gain horn antenna (18-26.5 GHz)	Narda	Model no. 638	3000000486	n.a.		
17	Std gain horn antenna (18-26.5 GHz)	Narda	Model no. 638	3000000487	n.a.		
18	Sleeve dipole antenna Model 3126-880	ETS-Lindgren	00040887	3000000	n.a.		
19	Fast CPU SM-B50	R&S	To 10	3000002681	s.No.10		
20	FM Modulator SM-B5	R&S	835676/033	3000002681	s.No.10		
21	RF-Generator SMIQ03 (B2 Signal)	R&S	835541/055	3000002681-0001	25.08.2008	36	25.08.2011
22	Modulation Coder SMIQ-B20	R&S	To 16	3000002681	s.No.16		
23	Data Generator SMIQ-B11	R&S	To 16	3000002681	s.No.16		
24	RF Rear Connection SMIQ-B19	R&S	To 16	3000002681	s.No.16		
25	Fast CPU SM-B50	R&S	To 16	3000002681	s.No.16		
26	FM Modulator SM-B5	R&S	836061/022	3000002681	s.No.16		
27	RF-Generator SMP03 (B3 Signal)	R&S	835133/011	3000002681-0003	26.08.2008	36	26.08.2011
28	Attenuator SMP-B15	R&S	835136/014	3000002681	S.No.22		
29	RF Rear Connection SMP-B19	R&S	834745/007	3000002681	S.No.22		
30	Power Meter NRVD	R&S	835430/044	3000002681-0004	26.08.2008	24	26.08.2010
31	Power Sensor NRVD-Z1	R&S	833894/012	3000002681-0013	26.08.2008	24	26.08.2010
32	Power Sensor NRVD-Z1	R&S	833894/011	3000002681-0010	26.08.2008	24	26.08.2010
33	Rubidium Standard RUB	R&S		3000002681-0009	27.08.2008	24	27.08.2010
34	Switching and Signal Conditioning Unit SSCU	R&S	338864/003	3000002681-0006	Verified with path compensation		
35	Laser Printer HP Deskjet 2100	HP	N/A	3000002681-0011	n.a.		
36	19" Rack	R&S	11138363000004	3000002681	n.a.		
37	RF-cable set	R&S	N/A	3000002681	n.a.		
39	IEEE-cables	R&S	N/A	3000002681	n.a.		
40	Sampling System FSIQ-B70	R&S	835355/009	3000002681	s.No.7		
41	RSP programmable attenuator	R&S	834500/010	3000002681-0007	26.08.2008	24	26.08.2010
42	Signalling Unit	R&S	838312/011	3000002681	n.a.		
43	NGPE programmable Power Supply for EUT	R&S	192.033.41	3000002681			
44	SMA Cables SPS-1151-985-SPS	Insulated Wire	different	different	n.a.		
45	CBT32 with EDR Signaling Unit	R&S					
46	Coupling unit	Narda	N/A	--	n.a.		

47	2xSwitch Matrix PSU	R&S	872584/021	300001329	n.a.		
48	RF-cable set	R&S	N/A	different	n.a.		
49	IEEE-cables	R&S	N/A	--	n.a.		

Note: 3000002681-00xx inventoried as a system

Anechoic chamber F:

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Control Computer	F+W	FW0502032	300003303	-/-	-/-	-/-
2	Trilog Antenna VULB 9163	Schwarzbeck	295	300003787	01.04.2008	24	01.04.2010
3	Amplifier - 0518C-138	Veritech Micro-wave Inc.	-/-	-/-	-/-	-/-	-/-
4	Switch - 3488A	HP		300000368	-/-	-/-	-/-
5	EMI Test receiver - ESCI	R&S	100083	300003312	31.01.2007	24	31.01.2009
6	Turntable Controller - 1061 3M	EMCO	1218	300000661	-/-	-/-	-/-
7	Tower Controller 1051 Controller	EMCO	1262	300000625	-/-	-/-	-/-
8	Tower - 1051	EMCO	1262	300000625	-/-	-/-	-/-
10	Ultra Notch-Filter Rejected band Ch. 62	WRCD	9	-/-	-/-	-/-	-/-

C.BER Bluetooth Rack Room AC2:

No	Equipment/Type	Manuf.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	System Controller with XP Prof. & C.BER Control Software	F&W	300003580	na		
2	GPB to USB Converter	Agilent	300003426	na		
3	Spectrum Analyser FSIQ26	R&S	300002681-005	10.01.2008	24	10.01.2010
	Sampling System FSIQ-B70	R&S	300002681-005	s.No.3		
	Tracking Generator FSIQ-B10 for FSIQ26	R&S	300002681-005	s.No.3		
4	RF-Generator SMIQ03 (Interferer Signal)	R&S	300002681-001	25.08.2008	36	25.08.2011
	Modulation Coder SMIQ-B20	R&S	300002681-001	s.No.4		
	Data Generator SMIQ-B11	R&S	300002681-001	s.No.4		
	RF Rear Connection SMIQ-B19	R&S	300002681-001	s.No.4		
	Fast CPU SM-B50	R&S	300002681-001	s.No.4		
	FM Modulator SM-B5	R&S	300002681-001	s.No.4		
5	Rubidium Standard RUB	R&S	300002681-009	27.08.2008	24	27.08.2010
6	Switching Unit 3488A including 2 44476A cards	HP	300000926	Verified with path compensation		
	44472A VHF switch	HP	300000926	Verified with path compensation		
7	Signalling Unit: CBT with EDR	R&S	300003416	27.08.2008	24	27.08.2010
8	RF-cable set	different	no	Verified with path compensation		
9	IEEE-cables	R&S	no	na		
10	NGPE programmable Power Supply for EUT	R&S	400000078	27.08.2008	24	27.08.2010
11	Coupling Unit 4324-2	Narda	no	Verified with path compensation		
12	Climatic Chamber VT4002	Voetch	300003019	11.05.2007	24	11.05.2009
13	6 dB Attenuator 1W	Narda	no	Verified with path compensation		
14	DCBlocker 30 MHz to 12.75 GHz 1W	Narda	no	Verified with path compensation		