



## Accredited testing-laboratory

**DAR registration number: DGA-PL-176/94-D1**

**Federal Motor Transport Authority (KBA)  
DAR registration number: KBA-P 00070-97**

**Recognized by the Federal Communications Commission**

**Anechoic chamber registration no.: 90462 (FCC)**

**Anechoic chamber registration no.: 3462C-1 (IC)**

**Certification ID: DE 0001**

**Accreditation ID: DE 0002**

**Accredited Bluetooth® Test Facility (BQTF)**

*The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Cetecom ICT is under license*

**Test report no. : 1-1954-06-09/10**  
**Type identification : AAD-3880070-BV**  
**Applicant : Sony Ericsson Mobile Communications AB**  
**FCC ID : PY7A3880070**  
**IC Certification No : 4170B-A3880070**  
**Test standards : 47 CFR Part 15**  
**RSS - 210 Issue 7**

## Table of contents

<b>1</b>	<b>General information</b>	<b>3</b>
1.1	Notes	3
1.2	Testing laboratory	4
1.3	Details of applicant	4
1.4	Application details	4
<b>2</b>	<b>Technical tests</b>	<b>5</b>
2.1	Details of manufacturer	5
2.1.1	Test item	5
2.1.2	Additional EUT information For IC Canada (appendix 2)	6
2.1.3	EUT operating modes	7
2.1.4	Extreme conditions testing values	7
<b>3</b>	<b>Summary of Measurement Results and list of all performed test cases</b>	<b>8</b>
<b>4</b>	<b>RF measurement testing</b>	<b>9</b>
4.1	Description of test set-up	9
4.1.1	Radiated measurements	9
4.1.2	Conducted measurements	9
4.2	Referenced Documents	10
4.3	Additional comments	10
4.4	Antenna gain	10
4.5	Peak Power Spectral density (digitally modulated systems) §15.247(e)	11
4.6	Spectrum Bandwidth of a DSSS System / 6 dB Bandwidth §15.247(a)(2)	15
4.7	Spectrum Bandwidth of a DSSS System / 20 dB Bandwidth	19
4.8	Maximum output power (conducted) §15.247 (b)(3)	23
4.9	Max. peak output power (radiated) §15.247 (b)(3)	28
4.10	Band-edge compliance of conducted emissions §15.247 (d)	29
4.11	Band-edge compliance of radiated emissions §15.205	32
4.12	Spurious Emissions - conducted (Transmitter) §15.247 (c)	34
4.13	Spurious Emissions - radiated (Transmitter) §15.209	44
4.14	Spurious Emissions - radiated (Receiver) §15.109 / 209	52
4.15	Spurious Emissions - radiated <30 MHz §15.209	55
4.16	Conducted Emissions <30 MHz §15.107/207	56
<b>5</b>	<b>Test equipment and ancillaries used for tests</b>	<b>57</b>
<b>6</b>	<b>Photographs of the Test Set-up</b>	<b>59</b>
<b>7</b>	<b>Photographs of the EUT</b>	<b>61</b>

---

## 1 General information

### 1.1 Notes

The test results of this test report relate exclusively to the test item specified in 3.1.1. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

#### Test laboratory manager:

**2010-03-09**

**Jakob Reschke**




Date

Name

Signature

**2010-03-09**

**Daniel Muyunga**



Date

Name

Signature

#### Technical responsibility for area of testing:

**2010-03-09**

**Michael Berg**



Date

Name

Signature

## 1.2 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6 - 10

66117 Saarbrücken

Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

e-mail: info@ICT.cetecom.de

Internet: http://www.cetecom-ict.de

**State of accreditation:** The test laboratory (area of testing) is accredited according to  
DIN EN ISO/IEC 17025  
DAR registration number: DGA-PL-176/94-D1

**Accredited by:** Federal Motor Transport Authority (KBA)  
DAR registration number: KBA-P 00070-97

**Testing location, if different from CETECOM ICT Services GmbH:**

Name :  
Street :  
Town :  
Country :  
Phone :  
Fax :

## 1.3 Details of applicant

<b>Name:</b>	Sony Ericsson Mobile Communications AB
<b>Street:</b>	Nya Vattentornet
<b>Town:</b>	22188 Lund
<b>Country:</b>	Sweden
<b>Telephone:</b>	+46-46-19-3000
<b>Fax:</b>	+46 (0) 46 19 32 95
<b>Contact:</b>	Johan Wedin
<b>E-mail:</b>	johan.wedin@sonyericsson.com
<b>Telephone:</b>	+46 (0) 707 19 57 36

## 1.4 Application details

<b>Date of receipt of order:</b>	2010-02-10
<b>Date of receipt of test item:</b>	2010-03-08
<b>Date of start test:</b>	2010-03-08
<b>Date of end test:</b>	2010-03-09
<b>Persons(s) who have been present during the test:</b>	-/-

## 2 Technical tests

### 2.1 Details of manufacturer

Name:	Sony Ericsson Mobile Communications AB
Street:	Nya Vattentorget
Town:	22188 Lund
Country:	Sweden

#### 2.1.1 Test item

Kind of test item :	Mobile Phone GSM 850/900/1800/1900, UMTS FDD1/FDD2/FDD5 / HSDPA / WLAN / BT EDR / A-GPS / FM-Rx
Type identification :	AAD-3880070-BV
S/N serial number :	Rad. BX901AZ6L4 Cond. BX901AZ6CS
HW hardware status :	AP2.1
SW software status :	R2BA026V ATP
Frequency Band [MHz] :	ISM 2.400 - 2.483,5
Type of Modulation :	DSSS & OFDM / BPSK; QPSK; (16 & 64) QAM
Number of channels :	11
Antenna :	Integrated antenna
Power Supply :	3.70 V DC by Li-Polymer Battery (EP500) and Power Supply
Temperature Range :	-/- °C to -/- °C

#### DSSS

Max. power radiated: 18.99 dBm  
Max. power conducted: 19.95 dBm

#### OFDM

Max. power radiated: 23.37 dBm  
Max. power conducted: 24.33 dBm

FCC ID: PY7A3880070  
IC: 4170B-A3880070

**2.1.2 Additional EUT information For IC Canada (appendix 2)**

IC Registration Number:	<b>4170B-A3880070</b>
Model Name:	<b>AAD-3880070-BV</b>
Manufacturer (complete Address):	<b>Sony Ericsson Mobile Communications AB Nya Vattentorget 22188 Lund Sweden</b>
Tested to Radio Standards Specification (RSS) No.:	<b>RSS-210 Issue 7</b>
Open Area Test Site Industry Canada Number:	<b>IC 3462C-1</b>
Frequency Range (or fixed frequency) [MHz]:	<b>2400 – 2483.5 MHz</b>
RF: Power [W] (max):	<b>DSSS: Rad. EIRP: 18.99 mW Conducted : 98.86 mW  OFDM: Rad. EIRP: 217.27 mW Conducted : 271.02 mW</b>
Antenna Type:	<b>Integrated antenna</b>
Occupied Bandwidth (99% BW) [kHz]:	<b>DSSS: 16152 OFDM: 17675</b>
Type of Modulation:	<b>DSSS &amp; OFDM BPSK; QPSK; (16 &amp; 64) QAM</b>
Emission Designator (TRC-43):	<b>16M2G1D (DSSS) 17M7G1D (OFDM)</b>
Transmitter Spurious (worst case) [ $\mu$ V/m in 3m]:	<b>316 (noise floor)</b>
Receiver Spurious (worst case) [ $\mu$ V/m in 3m]:	<b>251 (noise floor)</b>

ATTESTATION: I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned departmental standard(s), and that the radio equipment identified in this application has been subject to all applicable test conditions specified in the departmental standards and all of the requirements of the standards have been met.

Signature:



Test engineer: Jakob Reschke

Date: 2010-03-09

### 2.1.3 EUT operating modes

EUT operating mode no. *)	Description of operating modes	Additional information
Op. 0	Normal mode	Normal temperature and power source conditions
Op. 1		low temperature, low power source conditions
Op. 2		low temperature, high power source conditions
Op. 3		high temperature, low power source conditions
Op. 4		high temperature, high power source conditions

\*) EUT operating mode no. is used to simplify the test plan

### 2.1.4 Extreme conditions testing values

Description	Shortcut	Unit	Value
Nominal Temperature	T <sub>nom</sub>	°C	22
Nominal Humidity	H <sub>nom</sub>	%	52
Nominal Power Source	V <sub>nom</sub>	V	3.70

Type of power source: DC by Li-Polymer Battery (EP500) and Power Supply

### 3 Summary of Measurement Results and list of all performed test cases

- No deviations from the technical specifications were ascertained
- There were deviations from the technical specifications ascertained

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC Part 15 §15.247 - CANADA RSS-210	PASS	2010-03-09	-/-

Test Specification Clause	Test Case	Pass	Fail	Not applicable	Not performed
None	Antenna Gain	Yes			
§15.247 (e)	Peak power spectral density	Yes			
§15.247(a)(2)	Spectrum Bandwidth of a DSSS System / 6dB BW	Yes			
§15.247(a)(2)	Spectrum Bandwidth of a DSSS System / 20dB BW	Yes			
§ 15.247 (b)(3)	Maximum output power (conducted)	Yes			
§ 15.247 (b)(3)	Max. peak output power (radiated)	Yes			
§15.247 (d)	Band-edge compliance of conducted emissions	Yes			
§15.205	Band-edge compliance of radiated emissions	Yes			
§15.247 (d)	Spurious Emission - conducted (Transmitter)	Yes			
§ 15.209	Spurious Emission -radiated (Transmitter)	Yes			
§ 15.109	Spurious Emissions-radiated (Receiver)	Yes			
§ 15.209	Spurious Emissions-radiated <30 MHz	Yes			
§ 15.107/207	Conducted Emissions <30 MHz	Yes			

## 4 RF measurement testing

### 4.1 Description of test set-up

#### 4.1.1 Radiated measurements

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 20 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63.2-1996 clause 15 and ANSI C63.4-2003 clause 4.1.5. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test set-ups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received.

The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.4-2003 clause 4.2.

Antennas are confirmed with ANSI C63.2-1996 item 15.

9 kHz - 150 MHz: Quasi Peak measurement, 200 Hz Bandwidth, active loop antenna.

150 kHz - 30 MHz: Quasi Peak measurement, 9 kHz Bandwidth, active loop antenna.


30 MHz - 1GHz: Quasi Peak measurement, 120 kHz Bandwidth, trilob antenna

>1GHz: Average, RBW 1MHz, VBW 10 Hz, wave guide horn

All measurement settings are according to FCC 15.209 and 15.207

#### 4.1.2 Conducted measurements

The EUT's RF signal is coupled out by the antenna connector which is supplied by the manufacturer. The signal is connected to the spectrum analyzer. The specific losses for signal path are first checked within a calibration. The measurement readings on the spectrum analyzer are corrected by the specific test set-up loss. The attenuator, power divider, signalling unit and the spectrum analyzer are impedance matched on 50 Ohm.



#### 4.2 Referenced Documents

None

#### 4.3 Additional comments

The following power settings were used:

DSSS: 17 dBm  
 OFDM: 13 dBm

#### 4.4 Antenna gain

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.


Calculated with DSSS Modulation

	low channel	mid channel	high channel
Conducted power [dBm] <i>(measured)</i>	19.37	19.95	19.18
Radiated power [dBm] <i>(measured)</i>	18.89	18.99	18.91
Gain [dBi] <i>(calculated)</i>	-0.48	-0.96	-0.28


4.5 Peak Power Spectral density (digitally modulated systems) §15.247(e)

DSSS


Plot 1:



Plot 2:




Plot 3:




Results: Plot 1: Power density: -4.14 dBm / 3 kHz  
 Plot 2: Power density: -4.19 dBm / 3 kHz  
 Plot 3: Power density: -4.42 dBm / 3 kHz

**OFDM**


Plot 1:



Plot 2:



Plot 3:



Results: Plot 1: Power density: -8.72 dBm / 3 kHz  
 Plot 2: Power density: -9.12 dBm / 3 kHz  
 Plot 3: Power density: -8.69 dBm / 3 kHz


Limits :

Under normal test conditions only	For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission
-----------------------------------	---


4.6 Spectrum Bandwidth of a DSSS System / 6 dB Bandwidth §15.247(a)(2)

DSSS


Plot 1:



Plot 2:



Plot 3:




Results:

Test conditions		6 dB BANDWIDTH [MHz]		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	9.62	10.02	10.02
Measurement uncertainty		±100kHz		


RBW: 100 kHz / VBW 100 kHz

**OFDM**


Plot 1:



Plot 2:



Plot 3:



Results:

Test conditions		6 dB BANDWIDTH [MHz]		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	16.43	16.51	16.47
Measurement uncertainty		±100kHz		

RBW: 100 kHz / VBW 100 kHz


Limits:

Under normal test conditions only	> 500 kHz
-----------------------------------	-----------


### 4.7 Spectrum Bandwidth of a DSSS System / 20 dB Bandwidth

#### DSSS


Plot 1:



Plot 2:



Plot 3:




Results:

Test conditions		20 dB BANDWIDTH [MHz]		
		2412	2437	2462
Frequency [MHz]				
T <sub>nom</sub>	V <sub>nom</sub>	16.11	16.15	16.11
Measurement uncertainty		±100kHz		


RBW: 100 kHz / VBW 100 kHz

**OFDM**


Plot 1:



Plot 2:



Plot 3:



Results:


Test conditions		20 dB BANDWIDTH [MHz]		
		2412	2437	2462
Frequency [MHz]				
T <sub>nom</sub>	V <sub>nom</sub>	17.68	17.68	17.52
Measurement uncertainty		±100kHz		

RBW: 100 kHz / VBW 100 kHz

### 4.8 Maximum output power (conducted) §15.247 (b)(3)


#### DSSS

Plot 1:




Date: 8.MAR.2010 13:09:28

Plot 2:



Date: 8.MAR.2010 13:12:22

Plot 3:



Date: 8.MAR.2010 13:14:13

Results:


Test conditions		Max. peak output power [dBm]		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	19.37	19.95	19.18
Measurement uncertainty		±3dB		

RBW: 20 MHz  
 VBW: 30 MHz

Test conditions		Average output power [dBm]		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	17.5	17.9	17.0
Measurement uncertainty		±3dB		


**OFDM**

Plot 1:




Date: 8.MAR.2010 13:11:28

Plot 2:



Date: 8.MAR.2010 13:13:21

Plot 3:



Date: 8.MAR.2010 13:15:25

Results:

Test conditions		Max. peak output power [dBm]		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	23.81	24.33	23.43
Measurement uncertainty		±3dB		

RBW: 50 MHz  
VBW: 30 MHz

Test conditions		Average output power [dBm]		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	15.1	15.1	15.1
Measurement uncertainty		±3dB		

Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt / 30 dBm
--	------------------------

### MPE calculation

These equations are generally accurate in the far field of an antenna but will over predict power density in the near field, where they could be used for making a “worst case” prediction.

$$S = PG/4\pi R^2$$

where S = power density ( in appropriate units, e.g. mW/cm<sup>2</sup>)  
P = power input to the antenna (in appropriate units e.g. mW)  
G = power gain of the antenna in the direction of interest relative to the isotropic radiator  
R = distance to the centre of radiation of the antenna (appropriate units e.g. cm)

Or

$$S = EIRP/4\pi R^2$$

where EIRP = equivalent isotropically radiated power

#### Calculation:

(Calculated for max. EIRP)

EIRP: 23.37 dBm (217.27 mW)

calculated at distance of 20 cm:

$$\text{power density} = 217.27/4\pi 20^2 = 0.043 \text{ mW/ cm}^2$$

Limit:

1mW/ cm<sup>2</sup> is the reference level for general public exposure according to the OET Bulletin 65,  
Edition 97-01 Table 1.

**4.9 Max. peak output power (radiated) §15.247 (b)(3)**

**DSSS**

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	18.89	18.99	18.91
Measurement uncertainty		±3dB		

RBW: 20 MHz

VBW: 30 MHz

Test conditions		Average output power [dBm] Calculated with antenna gain		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	17.02	16.94	16.72
Measurement uncertainty		±3dB		

**OFDM**

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	23.33	23.37	23.15
Measurement uncertainty		±3dB		

RBW: 50 MHz

VBW: 30 MHz

Test conditions		Average output power [dBm] Calculated with antenna gain		
Frequency [MHz]		2412	2437	2462
T <sub>nom</sub>	V <sub>nom</sub>	14.62	14.14	14.82
Measurement uncertainty		±3dB		


Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
--	---------------


**4.10 Band-edge compliance of conducted emissions §15.247 (d)**

**DSSS**

Plot 1: lowest channel




Plot 2: highest channel




**OFDM**

Plot 1: lowest channel



Plot 2: highest channel



Limits:




---

<p>Under normal test conditions only</p>	<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).</p>
--	---


### 4.11 Band-edge compliance of radiated emissions §15.205

#### DSSS

Plot 1: Restricted Band low



Plot 2 : Restricted Band high




Limit: 54 dBµV/m at 3m


Result: Pass

## OFDM

Plot 1: Restricted Band low



Plot 2 : Restricted Band high




Limit: 54 dBµV/m at 3m

Result: Pass


4.12 Spurious Emissions - conducted (Transmitter) §15.247 (c)

DSSS

Plot 1: Lowest Channel (9 kHz – 1 GHz)




Plot 2: Lowest Channel (1 GHz – 12 GHz)






Plot 5: Middle Channel (1 GHz – 12 GHz)




Plot 6: Middle Channel (12 GHz – 25 GHz)





Plot 9: Highest Channel (12 GHz – 25 GHz)




Result & Limits:

Emission Limitations					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emmission power	actual attenuation below frequency of operation [dB]	results
2412			30 dBm	-	Operating frequency
<i>No peaks detected</i>			-20 dBc		
2437			30 dBm		Operating frequency
<i>No peaks detected</i>			-20 dBc		
2462			30 dBm		Operating frequency
<i>No peaks detected</i>			-20 dBc		
Measurement uncertainty		± 3dB			


F < 1 GHz: RBW: 100 kHz VBW: 100 kHz  
 F > 1 GHz: RBW: 1 MHz VBW: 1 MHz



Plot 3: Lowest Channel (12 GHz – 25 GHz)




Plot 4: Middle Channel (9 kHz – 1 GHz)







Plot 9: Highest Channel (12 GHz – 25 GHz)



Result & Limits:

Emission Limitations					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2412			30 dBm	-	Operating frequency
	<i>No peaks detected</i>		-20 dBc		
2437			30 dBm		Operating frequency
	<i>No peaks detected</i>		-20 dBc		
2462			30 dBm		Operating frequency
	<i>No peaks detected</i>		-20 dBc		
Measurement uncertainty		± 3dB			

F < 1 GHz: RBW: 100 kHz VBW: 100 kHz  
 F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
-----------------------------------	--

Note: For emissions that fall into restricted bands you find the radiated emissions later in the report.

**4.13 Spurious Emissions - radiated (Transmitter) §15.209**

Plot 1: 0.03 - 1 GHz (lowest channel)


**Common Information**

**EUT:** AAD-3880070-BV + CAA-0003005-BV  
**Serial Number:** IMEI: 00440214-025490-9 + SN: 5908W49308170  
**Test Description:** FCC Part 15 @ 10 m  
**Operating Conditions:** WLAN TX CH 1  
**Operator Name:** ZAK  
 Powered by 115 V / 60 Hz

**Scan Setup: STAN\_Fin [EMI radiated]**

**Hardware Setup:** Electric Field (NOS)  
**Level Unit:** dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1,05 GHz	QuasiPeak	120 kHz	15 s	Receiver




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
39.407250	9.0	15000.000	120.000	220.0	H	49.0	13.4	21.0	30.0	
51.027900	14.7	15000.000	120.000	205.0	V	33.0	13.3	15.3	30.0	
103.272750	8.0	15000.000	120.000	191.0	V	315.0	11.6	25.5	33.5	
766.410750	20.8	15000.000	120.000	140.0	V	70.0	23.7	15.2	36.0	
837.023850	21.5	15000.000	120.000	220.0	V	301.0	24.4	14.5	36.0	
903.900600	22.5	15000.000	120.000	220.0	H	245.0	25.2	13.5	36.0	

**Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]**

<b>Subrange 1</b>	
<b>Frequency Range:</b>	30 MHz - 2 GHz
<b>Receiver:</b>	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
<b>Signal Path:</b>	without Notch FW 1.0
<b>Antenna:</b>	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0909)
<b>Antenna Tower:</b>	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
<b>Turntable:</b>	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 2: 1 - 12 GHz (lowest channel)



*Carrier notched with 2.4 GHz rejection filter*



Plot 4: 0.03 - 1 GHz (middle channel)


**Common Information**

**EUT:** AAD-3880070-BV + CAA-0003005-BV  
**Serial Number:** IMEI: 00440214-025490-9 + SN: 5908W49308170  
**Test Description:** FCC Part 15 @ 10 m  
**Operating Conditions:** WLAN TX CH 6  
**Operator Name:** ZAK  
**Comment:** Powered by 115 V / 60 Hz

**Scan Setup: STAN\_Fin [EMI radiated]**

**Hardware Setup:** Electric Field (NOS)  
**Level Unit:** dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1,05 GHz	QuasiPeak	120 kHz	15 s	Receiver




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
35.982750	14.6	15000.000	120.000	105.0	V	225.0	13.1	15.4	30.0	
50.971950	15.9	15000.000	120.000	98.0	V	69.0	13.3	14.1	30.0	
98.455050	7.9	15000.000	120.000	217.0	H	-1.0	11.7	25.6	33.5	
227.193600	8.3	15000.000	120.000	194.0	V	323.0	12.5	27.7	36.0	
733.510050	20.6	15000.000	120.000	171.0	H	179.0	23.2	15.4	36.0	
898.674750	22.5	15000.000	120.000	217.0	H	88.0	25.2	13.5	36.0	

**Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]**

<b>Subrange 1</b>	
<b>Frequency Range:</b>	30 MHz - 2 GHz
<b>Receiver:</b>	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
<b>Signal Path:</b>	without Notch FW 1.0
<b>Antenna:</b>	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0909)
<b>Antenna Tower:</b>	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
<b>Turntable:</b>	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 5: 1 - 12 GHz (middle channel)



*Carrier notched with 2.4 GHz rejection filter*

Plot 6: 0.03 - 1 GHz (highest channel)


### Common Information

<b>EUT:</b>	AAD-3880070-BV + CAA-0003005-BV
<b>Serial Number:</b>	IMEI: 00440214-025490-9 + SN: 5908W49308170
<b>Test Description:</b>	FCC Part 15 @ 10 m
<b>Operating Conditions:</b>	WLAN TX CH 11
<b>Operator Name:</b>	ZAK
<b>Comment:</b>	Powered by 115 V / 60 Hz

### Scan Setup: STAN\_Fin [EMI radiated]

<b>Hardware Setup:</b>	Electric Field (NOS)
<b>Level Unit:</b>	dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1,05 GHz	QuasiPeak	120 kHz	15 s	Receiver




### Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
35.988150	13.7	15000.000	120.000	168.0	V	166.0	13.1	16.3	30.0	
50.985900	16.3	15000.000	120.000	113.0	V	49.0	13.3	13.7	30.0	
181.962150	6.5	15000.000	120.000	178.0	V	3.0	10.5	27.0	33.5	
240.285000	8.5	15000.000	120.000	205.0	V	98.0	12.9	27.5	36.0	
756.467700	20.9	15000.000	120.000	98.0	H	39.0	23.6	15.1	36.0	
927.854100	22.6	15000.000	120.000	120.0	V	168.0	25.3	13.4	36.0	

## Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

<b>Subrange 1</b>	
<b>Frequency Range:</b>	30 MHz - 2 GHz
<b>Receiver:</b>	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
<b>Signal Path:</b>	without Notch FW 1.0
<b>Antenna:</b>	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0909)
<b>Antenna Tower:</b>	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
<b>Turntable:</b>	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 7: 1 - 12 GHz (highest channel)



*Carrier notched with 2.4 GHz rejection filter*



**4.14 Spurious Emissions - radiated (Receiver) §15.109 / 209**

Plot 1: 0.03 - 1 GHz vertical / horizontal (receiver)


**Common Information**

**EUT:** AAD-3880070-BV + CAA-0003005-BV  
**Serial Number:** IMEI: 00440214-025490-9 + SN: 5908W49308170  
**Test Description:** FCC Part 15 @ 10 m  
**Operating Conditions:** WLAN RX Mode  
**Operator Name:** ZAK  
**Comment:** Powered by 115 V / 60 Hz

**Scan Setup: STAN\_Fin [EMI radiated]**

**Hardware Setup:** Electric Field (NOS)  
**Level Unit:** dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1,05 GHz	QuasiPeak	120 kHz	15 s	Receiver




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
35.959500	12.8	15000.000	120.000	142.0	V	268.0	13.1	17.2	30.0	
51.014400	15.5	15000.000	120.000	220.0	V	309.0	13.3	14.5	30.0	
160.024800	7.0	15000.000	120.000	220.0	V	49.0	9.2	26.5	33.5	
499.107300	15.3	15000.000	120.000	98.0	H	21.0	18.7	20.7	36.0	
769.589550	20.8	15000.000	120.000	220.0	H	42.0	23.7	15.2	36.0	
874.344300	22.3	15000.000	120.000	129.0	H	93.0	24.9	13.7	36.0	


**Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]**

<b>Subrange 1</b>	
<b>Frequency Range:</b>	30 MHz - 2 GHz
<b>Receiver:</b>	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
<b>Signal Path:</b>	without Notch FW 1.0
<b>Antenna:</b>	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0909)
<b>Antenna Tower:</b>	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
<b>Turntable:</b>	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 2: 1 - 12 GHz vertical / horizontal (receiver)



Plot 3: 12- 25 GHz (receiver)



Results:

Spurious Emissions level [dB $\mu$ V/m]		
f[MHz]	Detector	Level [dB $\mu$ V/m]
No critical peaks detected		
Measurement uncertainty	±3 dB	

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

See above plots

Measurement distance see table


Limits: § 15.109

Frequency (MHz)	Field strength (dB $\mu$ V/m)	Measurement distance (m)
30 - 88	30.0	10
88 - 216	33.5	10
216 - 960	36.0	10
above 960	54.0	3

#### 4.15 Spurious Emissions - radiated <30 MHz §15.209

Measured at 3 m distance.  
 Values recalculated with 40 dB/decade according to FCC rules.

Plot 1:




Limits:


Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30 / 29.5 dBµ V/m	30
30 - 88	100 / 40 dBµ V/m	3
88 - 216	150 / 43.5 dBµ V/m	3
216 - 960	200 / 46 dBµ V/m	3
above 960	54 dBµ V/m	3

4.16 Conducted Emissions <30 MHz §15.107/207

Plot 1: CISPR 22 (Phase Line)



Plot 2: CISPR 22 (Neutral Line)



We measured in TX and RX mode, L1 and N floating and grounded, max value was hold.

Limits:

Under normal test conditions only	See plots
-----------------------------------	-----------

## 5 Test equipment and ancillaries used for tests

In order to simplify the identification of the equipment used at each specific test, each item of test equipment and ancillaries are provided with an identifier or number in the equipment list below.

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, rf-generating and signalling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

No.	Labor / Item	Equipment	Type	Manufact.	Serial No.	INV. No Cetecom	Kal. Art	Last Calibration	Next Calibration
1	n. a.	Netzgerät	6032A	HP Meßtechnik	2818A03450	300001040	Ve	08.01.2009	08.01.2012
2	n. a.	Power Dämpfungsglied	8325	Byrd	1530	300001595			
3	n. a.	Horn Antenne 1- 26.5GHz	3115	EMCO	8812-3088	300001032	vKI!	05.03.2009	05.03.2011
4	n. a.	Active Loop Antenne	6502	EMCO	2210	300001015	ne		
5	n. a.	Busisolator		Kontron		300001056	g		
6	n. a.	Absorberhalle		MWB	87400/02	300000996			
7	Spec.A. 2_2e	System-Rack	85900	HP I.V.	*	300000222	ne		
8	9	Netznachbildung Artificial Mains 9 kHz to 30 MHz	ESH3-Z5	R&S	828576/020	300001210	Ve	06.01.2010	06.01.2012
9	n. a.	Relais Matrix	3488A	HP Meßtechnik	2719A15013	300001156	ne		
10	n. a.	Relais Matrix	PSU	R&S	890167/024	300001168	ne		
11	n. a.	Trenntrafo	RT5A	Grundig	9242	300001263	ne		
12	n. a.	Leitungsteiler	11850C	HP Meßtechnik		300000997	ne		
13	n. a.	Switch / Control Unit	3488A	HP	2605e08770	300001443	ne		
14	n. a.	Band Reject filter	WRCG1855/1910- 1835/1925-40/8SS	Wainwright	7	300003350	ev		
15	n. a.	Band Reject filter	WRCG2400/2483- 2375/2505- 50/10SS	Wainwright	11	300003351	ev		
16	n. a.	TILE-Software Emission	Quantum Change, Modell TILE- ICS/FULL	EMCO	none	300003451	ne		
17	n. a.	Hochpassfilter	WHKX2.9/18G- 12SS	Wainwright	1	300003492	ev		
18	n. a.	Hochpassfilter	WHK1.1/15G- 10SS	Wainwright	3	300003255	ev		
19	n. a.	Hochpassfilter	WHKX7.0/18G- 8SS	Wainwright	18	300003789	ne		
20	n. a.	PSA- Spektrumanalysator 3 Hz - 26,5 GHz	E4440A	Agilent Vertr. Bad Hom	MY48250080	300003812	k	05.08.2008	05.08.2010
21	n. a.	Microwave Analog Signal Generator	N5183A	Agilent Vertr. Bad Hom	MY47420220	300003813	k	06.08.2008	06.08.2010
22	n. a.	EMI Preselector 9kHz - 1 GHz	N9039A	Agilent Vertr. Bad Hom	MY48260003	300003825	vKI!	19.08.2008	19.08.2010
23	n. a.	TRILOG Super Breitband Antenne	VULB9163	Schwarzbeck	371	300003854	vKI!	17.12.2008	17.12.2010

24	45	Switch-Unit	3488A	HP Meßtechnik	2719A14505	300000368	g		
25	50	Netzgerät	6032A	HP Meßtechnik	2920A04466	300000580	k	06.01.2009	06.01.2011
26	n. a.	software	SPS_PHE 1.4f	Spitzberger & Spieß	B5981; 5D1081;B5979	300000210	k	03.09.2001	03.09.2003
27	n. a.	EMI- Messem Empfänger Analysator	ESCI 1166.5950.03	R&S	100083	300003312	k	08.01.2010	08.01.2012
28	n. a.	Referenz-System (Harmonics u. Flicker)	ARS 16/1	SPS	A3509 07/0 0205	300003314	k	06.06.2007	06.06.2009
29	n. a.	Amplifier	JS42-00502650- 28-5A	MITEQ	1084532	300003379	ev		
30	n. a.	Antennenmast	Model 2175	ETS- LINDGREN	64762	300003745	izw		
31	n. a.	Steuergerät	Model 2090	ETS- LINDGREN	64672	300003746	izw		
32	n. a.	Interface-Box für Drehtisch	Model 105637	ETS- LINDGREN	44583	300003747	izw		
33	n. a.	Breitbandantenne	VULB9163	Schwarzbeck	295	300003787	k	01.04.2008	01.04.2010
34	n. a.	Spectrum-Analyzer Signal Analyzer	FSU26	R&S	200809	300003874	k	08.01.2010	08.01.2012
35	n. a.	20Hz-26,5GHz-150 to + 30 DBM	FSiQ26	R&S	835111/0004	300002678	Ve	06.01.2009	06.01.2011
36	n. a.	Spektrumanalysator 20 Hz - 50 GHz	FSU50	R&S	200012	300003443	ve	05.06.2008	05.06.2010