**CETECOM™****CETECOM ICT Services**
consulting - testing - certification >>>**TEST REPORT**

Test report no.: 1-2977-40-06/11

**Testing laboratory**

CETECOM ICT Services GmbH
Untertuerkheimer Strasse 6 – 10
66117 Saarbruecken / Germany
Phone: + 49 681 5 98 - 0
Fax: + 49 681 5 98 - 9075
Internet: <http://www.cetecom.com>
e-mail: ict@cetecom.com

Accredited test laboratory:
The test laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025
DAkkS registration number: D-PL-12076-01-01

Area of Testing: Radio/Satellite Communication

Applicant

Sony Ericsson Mobile Communications AB
Nya Vattentornet
22188 Lund / SWEDEN
Phone: +46 46 19 30 00
Fax: +46 46 19 32 95
Contact: Håkan Sjöberg
e-mail: hakan.sjoberg@sonyericsson.com
Phone: +46 46 19 35 59

Manufacturer

Sony Ericsson Mobile Communications AB
Nya Vattentornet
22188 Lund / SWEDEN

Test standard/s

47 CFR Part 15

Title 47 of the Code of Federal Regulations; Chapter I
Part 15 - Radio frequency devices

RSS - 210 Issue 8

Spectrum Management and Telecommunications - Radio Standards Specification
Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands):
Category I Equipment

For further applied test standards please refer to section 3 of this test report.

Test item

Kind of test item: GSM Mobile Phone 850/900/1800/1900; GPRS/EGPRS; UMTS FDDI/FDDVIII
HSDPA/HSUPA; BT+EDR; WLAN; A-GPS

Model name: AAD-3880107-BV

FCC ID: PY7A3880107

IC: 4170B-A3880107

Frequency: ISM band 2400 MHz to 2483.5 MHz
(Lowest channel 01 – 2412 MHz, Highest channel 11 – 2462 MHz)

Power supply: 3.70 V DC by power supply / battery EP500 + charger EP800

Temperature range: -20 °C to +55 °C

Test performed:

2011-06-06 Marco Bertolino

Test report authorised:

2011-06-06 Stefan Bös

1	Table of contents	
1	Table of contents	2
2	General information	3
2.1	Notes	3
2.2	Application details	3
3	Test standard/s	3
4	Test environment	3
5	Test item	4
6	Test laboratories sub-contracted	4
7	Summary of measurement results	5
8	RF measurement testing	6
8.1	Description of test setup	6
8.1.1	Radiated measurements	6
8.1.2	Conducted measurements	7
8.2	Additional comments	7
8.3	RSP100 test report cover sheet / performance test data	8
9	Measurement results	9
9.1	Maximum output power (conducted)	9
9.2	Antenna gain	20
9.3	Maximum output power	23
9.4	Power spectral density	30
9.5	Spectrum bandwidth of a FHSS system – 6 dB bandwidth	36
9.6	Spectrum bandwidth of a FHSS system – 20 dB bandwidth	42
9.7	Band edge compliance conducted	48
9.8	Band edge compliance radiated	52
9.9	TX spurious emissions conducted	59
9.10	TX spurious emissions radiated	77
9.11	RX spurious emissions radiated	115
9.12	TX spurious emissions radiated < 30 MHz	120
9.13	TX spurious emissions conducted < 30 MHz	126
10	Test equipment and ancillaries used for tests	131
Annex A	Photographs of the test setup	133
Annex B	External photographs of the EUT	138
Annex C	Internal photographs of the EUT	144
Annex D	Document history	154
Annex E	Further information	154

2 General information

2.1 Notes

The test results of this test report relate exclusively to the test item specified in this test report. CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM ICT Services GmbH.

2.2 Application details

Date of receipt of order:	2011-05-16
Date of receipt of test item:	2011-05-30
Start of test:	2011-05-30
End of test:	2011-06-02
Person(s) present during the test:	-/-

3 Test standard/s

Test standard	Version	Test standard description
47 CFR Part 15	2009-10	Title 47 of the Code of Federal Regulations; Chapter I Part 15 - Radio frequency devices
RSS - 210 Issue 8	2010-12	Spectrum Management and Telecommunications - Radio Standards Specification Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

4 Test environment

Temperature:	T_{nom}	+20 °C during room temperature tests
	T_{max}	+55 °C during high temperature test
	T_{min}	-20 °C during low temperature test
Relative humidity content:		55 %
Air pressure:		not relevant for this kind of testing
Power supply:	V_{nom}	3.70 V DC by power supply / battery EP500 + charger EP800
	V_{max}	4.07 V
	V_{min}	3.33 V

5 Test item

Kind of test item	:	GSM Mobile Phone 850/900/1800/1900; GPRS/EGPRS; UMTS FDDI/FDDVIII HSDPA/HSUPA; BT+EDR; WLAN; A-GPS
Type identification	:	AAD-3880107-BV
S/N serial number	:	WLAN radiated units: BX902D9ZMM, BX902D9ZM7 WLAN conducted units: BX902DADYG, BX902D9ZJT
HW hardware status	:	AP2
SW software status	:	4.0.B.2.5 RTP R1A034
Frequency band [MHz]	:	ISM band 2400 MHz to 2483.5 MHz (Lowest channel 01 – 2412 MHz, Highest channel 11 – 2462 MHz)
Type of modulation	:	DSSS and OFDM technology with BPSK, QPSK, 16 - & 64 - QAM modulation.
Number of channels	:	11
Antenna	:	Integrated printed antenna → for more information, please take a look at the annex – internal photos of the EUT.
Power supply	:	3.70 V DC by power supply / battery EP500 + charger EP800
Temperature range	:	-20 °C to +55 °C

6 Test laboratories sub-contracted

None

7 Summary of measurement results

- No deviations from the technical specifications were ascertained
- There were deviations from the technical specifications ascertained

TC Identifier	Description	Verdict	Date	Remark
RF-Testing	CFR Part 15 RSS 210, Issue 8, Annex 8	Passed	2011-06-06	-/-

Test specification clause	Test case	Temperature conditions	Power source voltages	Mode	Pass	Fail	NA	NP	Results (max.)
§15.247(b)(4) RSS 210 / A8.4(2)	Antenna gain	Nominal	Nominal	DSSS	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(e) RSS 210 / A8.2(b)	Power spectral density	Nominal	Nominal	DSSS OFDM g & n	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	complies
§15.247(a)(2) RSS 210 / A8.2(a)	Spectrum bandwidth of a FHSS system 6dB bandwidth	Nominal	Nominal	DSSS OFDM g & n	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	complies
§15.247(a)(2) RSS 210 / A8.2(a)	Spectrum bandwidth of a FHSS system 20dB bandwidth	Nominal	Nominal	DSSS OFDM g & n	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	complies
§15.247(b)(3) RSS-210 / A8.4(4)	Maximum output power	Nominal	Nominal	DSSS OFDM g & n	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	complies
§15.247(d) RSS-210 / A8.5	Band edge compliance conducted	Nominal	Nominal	DSSS OFDM g & n	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	complies
§15.205 RSS-210 / A8.5	Band edge compliance radiated	Nominal	Nominal	DSSS OFDM g & n	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	complies
§15.247(d) RSS-210 / A8.5	TX spurious emissions conducted	Nominal	Nominal	DSSS OFDM g & n	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	complies
§15.247(d) RSS-210 / A8.5	TX spurious emissions radiated	Nominal	Nominal	DSSS OFDM g & n	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	complies
§15.109 RSS-Gen.	RX spurious emissions radiated	Nominal	Nominal	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.209(a) RSS-Gen	TX spurious emissions radiated < 30 MHz	Nominal	Nominal	DSSS OFDM g & n	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	complies
§15.107(a)	Conducted emissions < 30 MHz	Nominal	Nominal	DSSS OFDM g & n	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/>	complies

Note: NA = Not Applicable; NP = Not Performed

8 RF measurement testing


8.1 Description of test setup

8.1.1 Radiated measurements

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 25 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63.2-1996 clause 15 and ANSI C63.4-2009 clause 4.1.5. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63-4-2009 clause 4.2.

Antennas are confirmed with ANSI C63.2-1996 item 15.

Semi anechoic chamber




Picture 1: Diagram radiated measurements

9 kHz - 30 MHz:	active loop antenna
30 MHz – 1 GHz:	tri-log antenna
> 1 GHz:	horn antenna

The EUT is powered by an external power supply with nominal voltage. The signalling is performed from outside the chamber with a signalling unit (CMU200 or other) by air link using signalling antenna.

8.1.2 Conducted measurements

The EUT's RF signal is coupled out by the antenna connector which is supplied by the manufacturer. The signal is first 10dB attenuated before it is power divided (~6dB loss per branch). One of the signal paths is connected to the communication base Station (CMU200 or other), the other one is connected to the spectrum analyzer. The specific losses for both signal paths are first checked within a calibration. The measurement readings on the signalling unit/spectrum analyzer are corrected by the specific test set-up loss. The attenuator, power divider, signalling unit and the spectrum analyzer are impedance matched on 50 Ohm.



Picture 2: Diagram conducted measurements

8.2 Additional comments

Reference documents: None

Special test descriptions: power index 18 is used according to manufacturer instruction.
(for all modes DSSS / OFDM g & n)

Configuration descriptions: None

Test mode:

- No test mode available.
lperf was used to ping another device with the largest support packet size
- Special software is used.
EUT is transmitting pseudo random data by itself

8.3 RSP100 test report cover sheet / performance test data

Test report number	:	1-2977-40-06/11
Equipment model number	:	AAD-3880107-BV
Certification number	:	4170B-A3880107
Manufacturer (complete address)	:	Sony Ericsson Mobile Communications AB Nya Vattentorget 22188 Lund / SWEDEN
Tested to radio standards specification no.	:	RSS 210, Issue 8, Annex 8
Open area test site IC No.	:	IC 3462C-1
Frequency range	:	ISM band 2400 MHz to 2483.5 MHz (Lowest channel 01 – 2412 MHz, Highest channel 11 – 2462 MHz)
RF-power [W] (max.)	:	Conducted: DSSS / b – mode: 114.55 mW OFDM / g – mode: 303.39 mW OFDM / n – mode: 293.09 mW Radiated: DSSS / b – mode: 101.62 mW OFDM / g – mode: 271.64 mW OFDM / n – mode: 262.42 mW
Occupied bandwidth (99%-BW)	:	DSSS / b – mode: 16.11 MHz OFDM / g – mode: 17.98 MHz OFDM / n – mode: 18.86 MHz
Type of modulation	:	DSSS & OFDM technology with BPSK, QPSK, 16- and 64 QAM modulation.
Emission designator (TRC-43)	:	DSSS / b – mode: 16M1G1D OFDM / g – mode: 18M0G7D OFDM / n – mode: 18M9G7D
Antenna information	:	Integrated printed antenna → for more information, please take a look at the annex – internal photos of the EUT.
Transmitter spurious (worst case) [dB μ V/m @ 3m]:		DSSS / b – mode: 45.0 @ 12 GHz (1 MHz / 1 MHz) OFDM / g – mode: 45.0 @ 12 GHz (1 MHz / 1 MHz) OFDM / n – mode: 45.0 @ 12 GHz (1 MHz / 1 MHz) 45.0 @ 12 GHz (noise floor @ 1 MHz)
Receiver spurious (worst case) [dB μ V/m @ 3m]:		44.5 @ 12 GHz (1 MHz / 1 MHz / noise floor)

ATTESTATION:


DECLARATION OF COMPLIANCE:

I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned Industry Canada standard(s); and that the equipment identified in this application has been subjected to all the applicable test conditions specified in the Industry Canada standards and all of the requirements of the standard have been met.

Laboratory manager:

2011-06-06
Date

Marco Bertolino
Name


Signature

9 Measurement results

9.1 Maximum output power (conducted)

Description:

Measurement of the maximum output power conducted. This measurement is performed only at the middle channel in both modes and all data rates to determine the data rate per mode which results in the highest output power. This mode will be selected for all further measurements.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	1s
Video bandwidth:	30 MHz
Resolution bandwidth:	50 MHz
Span:	100 MHz
Trace-Mode:	Max Hold

Results:

DSSS / b – mode Data Rate [MBit/s]	Maximum Output Power Conducted [dBm]			
	1	2	5.5	11
Ch 6 - 2437 MHz	20.45	20.40	20.15	20.12
Measurement uncertainty	± 1.5 dB			

OFDM / g – mode Data Rate [MBit/s]	Maximum Output Power Conducted [dBm]							
	6	9	12	18	24	36	48	54
Ch 6 - 2437 MHz	24.37	24.40	24.21	24.26	24.19	24.24	24.18	24.27
Measurement uncertainty	± 1.5 dB							

OFDM / n – mode Data Rate [MBit/s]	Maximum Output Power Conducted [dBm]							
	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Ch 6 - 2437 MHz	24.21	24.16	24.33	24.27	24.29	24.39	24.26	24.10
Measurement uncertainty	± 1.5 dB							

Result: Selected data rate for all measurements:

DSSS / b – mode:

OFDM / g – mode:

OFDM / n – mode:


1 MBit/s

9 MBit/s

MCS5


Plots: DSSS / b – mode

Plot 1: TX mode, middle channel, 1 MBit/s




Date: 1.JUN.2011 10:23:07

Plot 2: TX mode, middle channel, 2 MBit/s




Date: 1.JUN.2011 10:24:16

Plot 3: TX mode, middle channel, 5.5 MBit/s



Date: 1.JUN.2011 10:25:15


Plot 4: TX mode, middle channel, 11 MBit/s



Date: 1.JUN.2011 10:26:20


Plots: OFDM / g – mode

Plot 1: TX mode, middle channel, 6 MBit/s




Date: 1.JUN.2011 10:30:31

Plot 2: TX mode, middle channel, 9 MBit/s




Date: 1.JUN.2011 10:31:55

Plot 3: TX mode, middle channel, 12 MBit/s




Date: 1.JUN.2011 10:32:47

Plot 4: TX mode, middle channel, 18 MBit/s




Date: 1.JUN.2011 10:33:36

Plot 5: TX mode, middle channel, 24 MBit/s




Date: 1.JUN.2011 10:34:39

Plot 6: TX mode, middle channel, 36 MBit/s




Date: 1.JUN.2011 10:43:38

Plot 7: TX mode, middle channel, 48 MBit/s



Date: 1.JUN.2011 10:44:40


Plot 8: TX mode, middle channel, 54 MBit/s



Date: 1.JUN.2011 10:46:22


Plots: OFDM / n – mode

Plot 1: TX mode, middle channel, MCS0




Date: 1.JUN.2011 10:51:55

Plot 2: TX mode, middle channel, MCS1




Date: 1.JUN.2011 10:52:55

Plot 3: TX mode, middle channel, MCS2




Date: 1.JUN.2011 10:54:50

Plot 4: TX mode, middle channel, MCS3




Date: 1.JUN.2011 10:55:43

Plot 5: TX mode, middle channel, MCS4




Date: 1.JUN.2011 10:57:32

Plot 6: TX mode, middle channel, MCS5




Date: 1.JUN.2011 10:58:29

Plot 7: TX mode, middle channel, MCS6



Date: 1.JUN.2011 10:59:51

Plot 8: TX mode, middle channel, MCS7



Date: 1.JUN.2011 11:01:33

9.2 Antenna gain

Measurement:

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal WLAN devices, the DSSS mode is used.

Measurement parameters:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Video bandwidth:	3 MHz
Resolution bandwidth:	3 MHz
Trace-Mode:	Max hold

Limits:

FCC	IC
CFR Part 15.247 (b)(4)	RSS 210, Issue 8, A 8.4(2)
Antenna Gain	
6 dBi	


Results:

T _{nom}	V _{nom}	lowest channel 2412 MHz	middle channel 2437 MHz	highest channel 2462 MHz
Conducted power [dBm] Measured with DSSS modulation		17.89	17.77	17.96
Radiated power [dBm] Measured with DSSS modulation		17.41	16.64	15.46
Gain [dBi] Calculated		-0.48	-1.13	-2.50
Measurement uncertainty		± 1.5 dB (cond.) / ± 3 dB (rad.)		

Result: The result of the measurement is passed.


Plots: DSSS / b – mode

Plot 1: TX mode, lowest channel, conducted




Date: 1.JUN.2011 11:11:10

Plot 2: TX mode, middle channel, conducted



Date: 1.JUN.2011 11:12:17

Plot 3: TX mode, highest channel, conducted



Date: 1.JUN.2011 11:14:32

9.3 Maximum output power

Description:

Measurement of the maximum output power conducted and radiated. The measurements are performed using the data rate producing the highest conducted output power. The determination of these data rates was performed at the beginning of the tests.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	1s / auto
Video bandwidth:	30 MHz
Resolution bandwidth:	50 MHz
Span:	100 MHz
Trace-Mode:	Max Hold

Limits:

FCC	IC
CFR Part 15.247 (b)(3)	RSS 210, Issue 8, A 8.4(4)
Maximum Output Power	
Conducted: 1.0 W – Antenna Gain max. 6 dBi	

Results: DSSS / b – mode

DSSS / b – mode Frequency	Maximum Output Power [dBm]		
	2412 MHz	2437 MHz	2462 MHz
Peak Output Power Conducted	20.55	20.45	20.59
Output Power Radiated – EIRP*)	20.07	19.32	18.09
Measurement uncertainty	± 1.5 dB (cond.) / ± 3 dB (rad.)		

*) calculated with Antenna gain

Result: The result of the measurement is passed.

Results: OFDM / g – mode

OFDM / g – mode Frequency	Maximum Output Power [dBm]		
	2412 MHz	2437 MHz	2462 MHz
Peak Output Power Conducted	24.82	24.40	24.39
Output Power Radiated – EIRP*)	24.34	23.27	21.89
Measurement uncertainty	± 1.5 dB (cond.) / ± 3 dB (rad.)		

*) calculated with Antenna gain

Result: The result of the measurement is passed.**Results: OFDM / n – mode**


OFDM / n – mode Frequency	Maximum Output Power [dBm]		
	2412 MHz	2437 MHz	2462 MHz
Peak Output Power Conducted	24.67	24.39	24.36
Output Power Radiated – EIRP*)	24.19	23.26	21.86
Measurement uncertainty	± 1.5 dB (cond.) / ± 3 dB (rad.)		

*) calculated with Antenna gain

Result: The result of the measurement is passed.


Plots: DSSS / b - mode

Plot 1: TX mode, lowest channel, conducted




Date: 1.JUN.2011 10:27:45

Plot 2: TX mode, middle channel, conducted



Date: 1.JUN.2011 10:23:07


Plot 3: TX mode, highest channel, conducted



Date: 1.JUN.2011 10:29:09


Plots: OFDM / g – mode

Plot 1: TX mode, lowest channel, conducted




Date: 1.JUN.2011 10:48:46

Plot 2: TX mode, middle channel, conducted



Date: 1.JUN.2011 10:31:55


Plot 3: TX mode, highest channel, conducted



Date: 1.JUN.2011 10:49:52


Plots: OFDM / n – mode

Plot 1: TX mode, lowest channel, conducted




Date: 1.JUN.2011 11:03:18

Plot 2: TX mode, middle channel, conducted



Date: 1.JUN.2011 10:58:29

Plot 3: TX mode, highest channel, conducted



Date: 1.JUN.2011 11:04:49

9.4 Power spectral density

Description:

Measurement of the power spectral density of a digital modulated system. The measurement is repeated for both modulations at the lowest, middle and highest channel.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	500 s
Video bandwidth:	3 kHz
Resolution bandwidth:	3 kHz
Span:	1.5 MHz
Trace-Mode:	Max Hold

Limits:

FCC	IC
CFR Part 15.247 (e)	RSS 210, Issue 8, A 8.2(b)
Power Spectral Density	
The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission or over 1.0 second if the transmission exceeds 1.0-second duration.	


Results:

Modulation Frequency	Power Spectral density [dBm/3kHz]		
	2412 MHz	2437 MHz	2462 MHz
DSSS / b – mode	-4.64	-4.85	-4.71
OFDM / g – mode	-8.15	-9.10	-8.12
OFDM / n – mode	-10.84	-10.84	-10.39
Measurement uncertainty	± 1.5 dB		

Result: The result of the measurement is passed.


Plots: DSSS / b – mode

Plot 1: TX mode, lowest channel




Date: 1.JUN.2011 12:42:45

Plot 2: TX mode, middle channel



Date: 1.JUN.2011 12:52:59


Plot 3: TX mode, highest channel



Date: 1.JUN.2011 13:04:53


Plots: OFDM / g – mode

Plot 1: TX mode, lowest channel




Date: 1.JUN.2011 13:15:28

Plot 2: TX mode, middle channel



Date: 1.JUN.2011 13:26:40


Plot 3: TX mode, highest channel



Date: 1.JUN.2011 13:36:10


Plots: OFDM / n – mode

Plot 1: TX mode, lowest channel




Date: 1.JUN.2011 13:45:50

Plot 2: TX mode, middle channel



Date: 1.JUN.2011 13:55:53

Plot 3: TX mode, highest channel



Date: 1.JUN.2011 14:05:14

9.5 Spectrum bandwidth of a FHSS system – 6 dB bandwidth

Description:

Measurement of the 6 dB bandwidth of the modulated signal.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	10 s
Video bandwidth:	100 kHz
Resolution bandwidth:	100 kHz
Span:	35 MHz
Trace-Mode:	Max Hold

Limits:

FCC	IC
CFR Part 15.247 (a)(2)	RSS 210, Issue 8, A 8.2(a)
Spectrum Bandwidth of a FHSS System – 6 dB Bandwidth	
Systems using digital modulation techniques may operate in the 2400–2483.5 MHz band. The minimum 6 dB bandwidth shall be at least 500 kHz.	


Results:

Modulation Frequency	6 dB BANDWIDTH [MHz]		
	2412 MHz	2437 MHz	2462 MHz
DSSS / b – mode	10.04	9.98	9.99
OFDM / g – mode	16.27	16.28	16.24
OFDM / n – mode	17.61	17.68	17.59
Measurement uncertainty	± 100 kHz		

Result: The result of the measurement is passed.


Plots: DSSS / b - mode

Plot 1: TX mode, lowest channel, 6 dB bandwidth




Date: 1.JUN.2011 11:21:29

Plot 2: TX mode, middle channel, 6 dB bandwidth



Date: 1.JUN.2011 11:23:44


Plot 3: TX mode, highest channel, 6 dB bandwidth



Date: 1.JUN.2011 11:26:43


Plots: OFDM / g – mode

Plot 1: TX mode, lowest channel, 6 dB bandwidth




Date: 1.JUN.2011 11:31:30

Plot 2: TX mode, middle channel, 6 dB bandwidth



Date: 1.JUN.2011 11:34:51


Plot 3: TX mode, highest channel, 6 dB bandwidth



Date: 1.JUN.2011 11:37:41


Plots: OFDM / n – mode

Plot 1: TX mode, lowest channel, 6 dB bandwidth




Date: 1.JUN.2011 12:11:19

Plot 2: TX mode, middle channel, 6 dB bandwidth



Date: 1.JUN.2011 12:14:13

Plot 3: TX mode, highest channel, 6 dB bandwidth



Date: 1.JUN.2011 12:16:45

9.6 Spectrum bandwidth of a FHSS system – 20 dB bandwidth

Description:

Measurement of the 20 dB bandwidth of the modulated signal.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	10 s
Video bandwidth:	100 kHz
Resolution bandwidth:	100 kHz
Span:	35 MHz
Trace-Mode:	Max Hold

Limits:

FCC	IC
CFR Part 15.247 (a)(2)	RSS 210, Issue 8, A 8.2(a)
Spectrum Bandwidth of a FHSS System – 20 dB Bandwidth	
Systems using digital modulation techniques may operate in the 2400–2483.5 MHz band. The minimum 6 dB bandwidth shall be at least 500 kHz.	


Results:

Modulation	20 dB BANDWIDTH [MHz]		
	2412 MHz	2437 MHz	2462 MHz
Frequency			
DSSS / b – mode	16.10	16.10	16.11
OFDM / g – mode	17.95	17.91	17.98
OFDM / n – mode	18.85	18.86	18.65
Measurement uncertainty	± 100 kHz		

Result: The result of the measurement is passed.


Plots: DSSS / b - mode

Plot 1: TX mode, lowest channel, 20 dB bandwidth




Date: 1.JUN.2011 11:22:02

Plot 2: TX mode, middle channel, 20 dB bandwidth



Date: 1.JUN.2011 11:24:21


Plot 3: TX mode, highest channel, 20 dB bandwidth



Date: 1.JUN.2011 11:27:35


Plots: OFDM / g – mode

Plot 1: TX mode, lowest channel, 20 dB bandwidth




Date: 1.JUN.2011 11:32:26

Plot 2: TX mode, middle channel, 20 dB bandwidth



Date: 1.JUN.2011 11:35:31


Plot 3: TX mode, highest channel, 20 dB bandwidth



Date: 1.JUN.2011 11:38:17


Plots: OFDM / n – mode

Plot 1: TX mode, lowest channel, 20 dB bandwidth




Date: 1.JUN.2011 12:12:02

Plot 2: TX mode, middle channel, 20 dB bandwidth



Date: 1.JUN.2011 12:15:02

Plot 3: TX mode, highest channel, 20 dB bandwidth



Date: 1.JUN.2011 12:17:19

9.7 Band edge compliance conducted

Description:

Measurement of the conducted band edge compliance. EUT is measured at the lower and upper band edge in both modes.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Video bandwidth:	500 kHz
Resolution bandwidth:	100 kHz
Span:	Lower Band Edge: 2300 – 2425 MHz Upper Band Edge: 2450 – 2500 MHz
Trace-Mode:	Max Hold

Limits:

FCC	IC
CFR Part 15.247 (d)	RSS 210, Issue 8, A 8.5
Band Edge Compliance Conducted	
<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.</p>	


Results:

Scenario Modulation	Band Edge Compliance Conducted [dB]		
	DSSS / b – mode	OFDM / g – mode	OFDM / n – mode
Lower Band Edge – Channel 1	> 20 dB (see plot 1)	> 20 dB (see plot 3)	> 20 dB (see plot 5)
Upper Band Edge – Channel 11	> 20 dB (see plot 2)	> 20 dB (see plot 4)	> 20 dB (see plot 6)
Measurement uncertainty	± 1.5 dB		

Result: The result of the measurement is passed.


Plots: DSSS / b – mode

Plot 1: TX mode, lower band edge



Date: 1.JUN.2011 12:22:27


Plot 2: TX mode, upper band edge



Date: 1.JUN.2011 12:31:41


Plots: OFDM / g – mode

Plot 1: TX mode, lower band edge



Date: 1.JUN.2011 12:24:31


Plot 2: TX mode, upper band edge




Date: 1.JUN.2011 12:30:10

Plots: OFDM / n – mode

Plot 1: TX mode, lower band edge



Plot 2: TX mode, upper band edge



9.8 Band edge compliance radiated

Description:

Measurement of the radiated band edge compliance. The EUT is turned in the position that results in the maximum level at the band edge. Then a sweep over the corresponding restricted band is performed. The EUT is set to channel 1 for the lower restricted band and to channel 11 for the upper restricted band. The measurement is repeated for all modulations. Measurement distance is 3m.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Video bandwidth:	10 Hz
Resolution bandwidth:	1 MHz
Span:	Lower Band: 2300 – 2400 MHz Higher Band: 2480 – 2500 MHz
Trace-Mode:	Max Hold

Limits:

FCC	IC
CFR Part 15.205	RSS 210, Issue 8, A 8.5
Band Edge Compliance Radiated	
<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).</p>	
54 dBµV/m AVG	


Results:

Szenario Modulation	Band Edge Compliance Conducted [dB]		
	DSSS / b – mode	OFDM / g – mode	OFDM / n – mode
Lower Band Edge – Channel 1	> 20 dB	> 20 dB	> 20 dB
Upper Band Edge – Channel 11	> 20 dB	> 20 dB	> 20 dB
Measurement uncertainty	± 3 dB		


Result: The result of the measurement is passed.

Plots: DSSS / b – mode


Plot 1: TX mode, lower band edge, vertical polarization



Plot 2: TX mode, upper band edge, vertical polarization



Plot 3: TX mode, lower band edge, horizontal polarization




Plot 4: TX mode, upper band edge, horizontal polarization




Plots: OFDM / g – mode


Plot 1: TX mode, lower band edge, vertical polarization




Plot 2: TX mode, upper band edge, vertical polarization



Plot 3: TX mode, lower band edge, horizontal polarization




Plot 4: TX mode, upper band edge, horizontal polarization



Plots: OFDM / n – mode


Plot 1: TX mode, lower band edge, vertical polarization




Plot 2: TX mode, upper band edge, vertical polarization



Plot 3: TX mode, lower band edge, horizontal polarization



Plot 4: TX mode, upper band edge, horizontal polarization



9.9 TX spurious emissions conducted

Description:

Measurement of the conducted spurious emissions in transmit mode. The measurement is performed at channel 1, 6 and 11. The measurement is repeated for all modulations.

Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	1 s / GHz
Video bandwidth:	F < 1 GHz: 100 kHz F > 1 GHz: 100 kHz
Resolution bandwidth:	F < 1 GHz: 100 kHz F > 1 GHz: 100 kHz
Span:	9 kHz to 25 GHz
Trace-Mode:	Max Hold

Limits:

FCC	IC
CFR Part 15.247(d)	RSS 210, Issue 8, A 8.5
TX Spurious Emissions Conducted	
<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required</p>	

Results: DSSS / b – mode

TX Spurious Emissions Conducted					
DSSS - mode					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2412		9.40	30 dBm		Operating frequency
No critical peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc		complies
2437		9.38	30 dBm		Operating frequency
No critical peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc		complies
2462		9.80	30 dBm		Operating frequency
No critical peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc		complies
Measurement uncertainty		± 3 dB			

Result: The result of the measurement is passed.

Results: OFDM / g – mode

TX Spurious Emissions Conducted					
OFDM - mode					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2412		5.59	30 dBm		Operating frequency
No critical peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc		complies
2437		5.70	30 dBm		Operating frequency
No critical peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc		complies
2462		5.88	30 dBm		Operating frequency
No critical peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc		complies
Measurement uncertainty		± 3 dB			

Result: The result of the measurement is passed.


Results: OFDM / n – mode

TX Spurious Emissions Conducted					
OFDM - mode					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2412		6.41	30 dBm		Operating frequency
No critical peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc		complies
2437		6.03	30 dBm		Operating frequency
No critical peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc		complies
2462		6.13	30 dBm		Operating frequency
No critical peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc		complies
Measurement uncertainty		± 3 dB			

Result: The result of the measurement is passed.

Plots: DSSS / b – mode


Plot 1: TX mode, lowest channel, up to 1 GHz



Date: 2.JUN.2011 12:08:36


The peak at the beginning of the plot is the LO from the SA.

Plot 2: TX mode, lowest channel, 1 GHz to 12 GHz




Date: 2.JUN.2011 12:17:42

Plot 3: TX mode, lowest channel, 12 GHz to 25 GHz



Date: 2.JUN.2011 12:28:44


Plot 4: TX mode, middle channel, up to 1 GHz



Date: 2.JUN.2011 12:09:48


The peak at the beginning of the plot is the LO from the SA.

Plot 5: TX mode, middle channel, 1 GHz to 12 GHz




Date: 2.JUN.2011 12:18:41

Plot 6: TX mode, middle channel, 12 GHz to 25 GHz



Date: 2.JUN.2011 12:29:36


Plot 7: TX mode, highest channel, up to 1 GHz



Date: 2.JUN.2011 12:10:30


The peak at the beginning of the plot is the LO from the SA.

Plot 8: TX mode, highest channel, 1 GHz to 12 GHz



Date: 2.JUN.2011 12:19:46


Plot 9: TX mode, highest channel, 12 GHz to 25 GHz



Date: 2.JUN.2011 12:30:15

Plots: OFDM / g – mode


Plot 1: TX mode, lowest channel, up to 1 GHz



Date: 2.JUN.2011 12:11:28


The peak at the beginning of the plot is the LO from the SA.

Plot 2: TX mode, lowest channel, 1 GHz to 12 GHz




Date: 2.JUN.2011 12:21:08

Plot 3: TX mode, lowest channel, 12 GHz to 25 GHz



Date: 2.JUN.2011 12:31:06


Plot 4: TX mode, middle channel, up to 1 GHz



Date: 2.JUN.2011 12:12:14


The peak at the beginning of the plot is the LO from the SA.

Plot 5: TX mode, middle channel, 1 GHz to 12 GHz




Date: 2.JUN.2011 12:22:12

Plot 6: TX mode, middle channel, 12 GHz to 25 GHz



Date: 2.JUN.2011 12:31:52


Plot 9: TX mode, highest channel, 12 GHz to 25 GHz



Date: 2.JUN.2011 12:32:26

Plots: OFDM / n – mode


Plot 1: TX mode, lowest channel, up to 1 GHz



Date: 2.JUN.2011 12:14:00


The peak at the beginning of the plot is the LO from the SA.

Plot 2: TX mode, lowest channel, 1 GHz to 12 GHz




Date: 2.JUN.2011 12:24:15

Plot 3: TX mode, lowest channel, 12 GHz to 25 GHz



Date: 2.JUN.2011 12:33:12


Plot 4: TX mode, middle channel, up to 1 GHz



Date: 2.JUN.2011 12:14:50


The peak at the beginning of the plot is the LO from the SA.

Plot 5: TX mode, middle channel, 1 GHz to 12 GHz




Date: 2.JUN.2011 12:25:23

Plot 6: TX mode, middle channel, 12 GHz to 25 GHz



Date: 2.JUN.2011 12:34:03


Plot 7: TX mode, highest channel, up to 1 GHz



Date: 2.JUN.2011 12:15:55


The peak at the beginning of the plot is the LO from the SA.

Plot 8: TX mode, highest channel, 1 GHz to 12 GHz



Date: 2.JUN.2011 12:25:59

Plot 9: TX mode, highest channel, 12 GHz to 25 GHz



Date: 2.JUN.2011 12:34:35

9.10 TX spurious emissions radiated

Description:

Measurement of the radiated spurious emissions in transmit mode. The measurement is performed at channel 1, 6 and 11. The measurement is repeated for all modulations.

Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Video bandwidth:	Sweep: 100 kHz Remeasurement: 10 Hz
Resolution bandwidth:	F < 1 GHz: 100 kHz F > 1 GHz: 1 MHz
Span:	30 MHz to 26 GHz
Trace-Mode:	Max Hold
Measured Modulation	<input checked="" type="checkbox"/> DSSS b – mode <input checked="" type="checkbox"/> OFDM g – mode <input checked="" type="checkbox"/> OFDM n – mode

The modulation with the highest output power was used to perform the transmitter spurious emissions. If spurious were detected a re-measurement was performed on the detected frequency with each modulation.

Limits:

FCC		IC	
CFR Part 15.247(d)		RSS 210, Issue 8, A 8.5	
TX Spurious Emissions Radiated			
<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).</p>			
§15.209			
Frequency (MHz)	Field Strength (dBµV/m)	Measurement distance	
30 - 88	30.0	10	
88 – 216	33.5	10	
216 – 960	36.0	10	
Above 960	54.0	3	

Results: DSSS / b – mode

TX Spurious Emissions Radiated [dBμV/m]								
DSSS – mode								
2412 MHz			2437 MHz			2462 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
No emissions detected between 1 GHz and 12.75 GHz.			No emissions detected between 1 GHz and 12.75 GHz.			No emissions detected between 1 GHz and 12.75 GHz.		
For emissions above 12.75 GHz, please take a look at the plots.			For emissions above 12.75 GHz, please take a look at the plots.			For emissions above 12.75 GHz, please take a look at the plots.		
Measurement uncertainty						± 3 dB		

Result: The result of the measurement is passed.

Results: OFDM / g – mode

TX Spurious Emissions Radiated [dBμV/m]								
OFDM – mode (g – mode)								
2412 MHz			2437 MHz			2462 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
No emissions detected between 1 GHz and 12.75 GHz.			No emissions detected between 1 GHz and 12.75 GHz.			No emissions detected between 1 GHz and 12.75 GHz.		
For emissions above 12.75 GHz, please take a look at the plots.			For emissions above 12.75 GHz, please take a look at the plots.			For emissions above 12.75 GHz, please take a look at the plots.		
Measurement uncertainty						± 3 dB		

Result: The result of the measurement is passed.

Results: OFDM / n – mode

TX Spurious Emissions Radiated [dBμV/m]								
OFDM – mode (n – mode)								
2412 MHz			2437 MHz			2462 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
No emissions detected between 1 GHz and 12.75 GHz.			No emissions detected between 1 GHz and 12.75 GHz.			No emissions detected between 1 GHz and 12.75 GHz.		
For emissions above 12.75 GHz, please take a look at the plots.			For emissions above 12.75 GHz, please take a look at the plots.			For emissions above 12.75 GHz, please take a look at the plots.		
Measurement uncertainty						± 3 dB		

Result: The result of the measurement is passed.

Plots: DSSS / b – mode

Plot 1: Lowest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


CETECOM ICT Services GmbH

Common Information

EUT: AAD-3880107-BV
 Serial Number: BX902D9ZMM | IMEI: 00440214-260460-6
 Test Description: FCC part 15 class B @ 10 m
 Operating Conditions: WLAN b mode TX Ch. 1 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dBµV/m
Subrange **Detectors** **IF Bandwidth** **Meas. Time** **Receiver**
 30 MHz - 2 GHz QuasiPeak 120 kHz 15 s Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
35.809650	10.4	15000.000	120.000	163.0	H	8.0	13.1	19.6	30.0	
41.007900	10.6	15000.000	120.000	155.0	V	283.0	13.4	19.4	30.0	
44.331450	11.8	15000.000	120.000	106.0	V	196.0	13.3	18.2	30.0	
54.280350	9.4	15000.000	120.000	145.0	V	283.0	13.0	20.6	30.0	
742.378200	20.9	15000.000	120.000	170.0	V	274.0	23.5	15.1	36.0	
929.912100	22.6	15000.000	120.000	115.0	V	95.0	25.3	13.4	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.42
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (1005)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


EMC 32 Version 8.10.00

Plot 2: Lowest channel, 1 GHz to 12.75 GHz, vertical polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 3: Lowest channel, 1 GHz to 12.75 GHz, horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: Lowest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Date: 2 JUN 2011 13:42:17

Plot 5: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 14:01:58

Plot 6: Middle channel, 30 MHz to 1 GHz, vertical & horizontal polarization


CETECOM ICT Services GmbH

Common Information

EUT: AAD-3880107-BV
 Serial Number: BX902D9ZMM | IMEI: 00440214-260460-6
 Test Description: FCC part 15 class B @ 10 m
 Operating Conditions: WLAN b mode TX Ch. 6 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dB μ V/m
Subrange **Detectors** **IF Bandwidth** **Meas. Time** **Receiver**
 30 MHz - 2 GHz QuasiPeak 120 kHz 15 s Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
37.484250	9.6	15000.000	120.000	170.0	V	-3.0	13.2	20.4	30.0	
43.142850	10.5	15000.000	120.000	146.0	V	106.0	13.3	19.5	30.0	
53.116200	9.2	15000.000	120.000	98.0	H	13.0	13.1	20.8	30.0	
664.815000	18.9	15000.000	120.000	170.0	V	-3.0	21.5	17.1	36.0	
920.205900	22.4	15000.000	120.000	98.0	V	13.0	25.3	13.6	36.0	
953.528400	22.5	15000.000	120.000	98.0	V	13.0	25.4	13.5	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.42
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (1005)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


EMC 32 Version 8.10.00

Plot 7: Middle channel, 1 GHz to 12.75 GHz, vertical polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 8: Middle channel, 1 GHz to 12.75 GHz, horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 9: Middle channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 13:45:12

Plot 10: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 14:03:33

Plot 11: Highest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


CETECOM ICT Services GmbH

Common Information

EUT: AAD-3880107-BV
 Serial Number: BX902D9ZMM | IMEI: 00440214-260460-6
 Test Description: FCC part 15 class B @ 10 m
 Operating Conditions: WLAN b mode TX Ch. 11 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dB μ V/m
Subrange **Detectors** **IF Bandwidth** **Meas. Time** **Receiver**
 30 MHz - 2 GHz QuasiPeak 120 kHz 15 s Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
41.479500	10.4	15000.000	120.000	155.0	V	87.0	13.4	19.6	30.0	
43.838850	11.2	15000.000	120.000	164.0	V	177.0	13.3	18.8	30.0	
49.421100	9.8	15000.000	120.000	156.0	H	12.0	13.4	20.2	30.0	
634.590450	18.3	15000.000	120.000	98.0	H	12.0	21.0	17.7	36.0	
729.374550	20.5	15000.000	120.000	170.0	H	173.0	23.2	15.5	36.0	
878.329950	22.4	15000.000	120.000	124.0	H	260.0	24.9	13.6	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.42
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (1005)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


EMC 32 Version 8.10.00

Plot 12: Highest channel, 1 GHz to 12.75 GHz, vertical polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 13: Highest channel, 1 GHz to 12.75 GHz, horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 14: Highest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 13:47:55

Plot 15: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 14:04:30

Plots: OFDM / g – mode

Plot 1: Lowest channel, 30 MHz to 1 GHz, vertical & horizontal polarization

CETECOM ICT Services GmbH


Common Information

EUT: AAD-3880107-BV
 Serial Number: BX902D9ZMM | IMEI: 00440214-260460-6
 Test Description: FCC part 15 class B @ 10 m
 Operating Conditions: WLAN g mode TX Ch. 1 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 2 GHz	QuasiPeak	120 kHz	15 s	Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
34.907700	10.0	15000.000	120.000	125.0	V	261.0	13.0	20.0	30.0	
43.749900	11.4	15000.000	120.000	127.0	V	183.0	13.3	18.6	30.0	
45.879900	10.4	15000.000	120.000	143.0	V	8.0	13.3	19.6	30.0	
710.682150	20.2	15000.000	120.000	174.0	V	183.0	22.8	15.8	36.0	
791.413800	21.0	15000.000	120.000	174.0	H	91.0	23.8	15.0	36.0	
884.509050	22.5	15000.000	120.000	174.0	H	92.0	25.0	13.5	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.42
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (1005)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


EMC 32 Version 8.10.00

Plot 2: Lowest channel, 1 GHz to 12.75 GHz, vertical polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 3: Lowest channel, 1 GHz to 12.75 GHz, horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: Lowest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 13:51:22

Plot 5: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 14:05:56

Plot 6: Middle channel, 30 MHz to 1 GHz, vertical & horizontal polarization


CETECOM ICT Services GmbH

Common Information

EUT: AAD-3880107-BV
 Serial Number: BX902D9ZMM | IMEI: 00440214-260460-6
 Test Description: FCC part 15 class B @ 10 m
 Operating Conditions: WLAN g mode TX Ch. 6 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dB μ V/m
Subrange **Detectors** **IF Bandwidth** **Meas. Time** **Receiver**
 30 MHz - 2 GHz QuasiPeak 120 kHz 15 s Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
33.193500	9.5	15000.000	120.000	98.0	V	102.0	12.8	20.5	30.0	
43.513500	10.9	15000.000	120.000	147.0	V	196.0	13.3	19.1	30.0	
56.393850	9.6	15000.000	120.000	175.0	V	196.0	12.5	20.4	30.0	
704.588400	20.0	15000.000	120.000	175.0	H	196.0	22.6	16.0	36.0	
899.594100	22.5	15000.000	120.000	132.0	H	183.0	25.2	13.5	36.0	
957.913350	22.6	15000.000	120.000	175.0	V	86.0	25.4	13.4	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.42
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (1005)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


EMC 32 Version 8.10.00

Plot 7: Middle channel, 1 GHz to 12.75 GHz, vertical polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 8: Middle channel, 1 GHz to 12.75 GHz, horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 9: Middle channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Date: 2 JUN 2011 13:52:23

Plot 10: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 14:07:03

Plot 11: Highest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


CETECOM ICT Services GmbH

Common Information

EUT: AAD-3880107-BV
 Serial Number: BX902D9ZMM | IMEI: 00440214-260460-6
 Test Description: FCC part 15 class B @ 10 m
 Operating Conditions: WLAN g mode TX Ch. 11 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dB μ V/m
Subrange **Detectors** **IF Bandwidth** **Meas. Time** **Receiver**
 30 MHz - 2 GHz QuasiPeak 120 kHz 15 s Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
43.356900	10.8	15000.000	120.000	170.0	V	173.0	13.3	19.2	30.0	
45.203700	10.6	15000.000	120.000	136.0	V	106.0	13.3	19.4	30.0	
55.540200	9.6	15000.000	120.000	170.0	V	-5.0	12.7	20.4	30.0	
730.819800	20.6	15000.000	120.000	157.0	V	182.0	23.2	15.4	36.0	
819.813150	21.3	15000.000	120.000	124.0	V	8.0	24.1	14.7	36.0	
946.113300	22.5	15000.000	120.000	170.0	H	106.0	25.3	13.5	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.42
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (1005)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


EMC 32 Version 8.10.00

Plot 12: Highest channel, 1 GHz to 12.75 GHz, vertical polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 13: Highest channel, 1 GHz to 12.75 GHz, horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 14: Highest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 13:53:42

Plot 15: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 14:07:39

Plots: OFDM / n – mode

Plot 1: Lowest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


CETECOM ICT Services GmbH

Common Information

EUT: AAD-3880107-BV
 Serial Number: BX902D9ZMM | IMEI: 00440214-260460-6
 Test Description: FCC part 15 class B @ 10 m
 Operating Conditions: WLAN n mode TX Ch. 1 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dBµV/m
Subrange **Detectors** **IF Bandwidth** **Meas. Time** **Receiver**
 30 MHz - 2 GHz QuasiPeak 120 kHz 15 s Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
42.513600	10.4	15000.000	120.000	142.0	V	8.0	13.3	19.6	30.0	
44.558400	13.4	15000.000	120.000	125.0	V	180.0	13.3	16.6	30.0	
52.155900	10.3	15000.000	120.000	136.0	V	264.0	13.2	19.7	30.0	
666.780900	18.9	15000.000	120.000	135.0	H	8.0	21.6	17.1	36.0	
732.343500	20.6	15000.000	120.000	170.0	H	196.0	23.3	15.4	36.0	
927.012150	22.3	15000.000	120.000	122.0	V	94.0	25.3	13.7	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.42
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (1005)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


EMC 32 Version 8.10.00

Plot 2: Lowest channel, 1 GHz to 12.75 GHz, vertical polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 3: Lowest channel, 1 GHz to 12.75 GHz, horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 4: Lowest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 13:55:04

Plot 5: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 14:09:37

Plot 6: Middle channel, 30 MHz to 1 GHz, vertical & horizontal polarization


CETECOM ICT Services GmbH

Common Information

EUT: AAD-3880107-BV
 Serial Number: BX902D9ZMM | IMEI: 00440214-260460-6
 Test Description: FCC part 15 class B @ 10 m
 Operating Conditions: WLAN n mode TX Ch. 6 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dBµV/m
Subrange **Detectors** **IF Bandwidth** **Meas. Time** **Receiver**
 30 MHz - 2 GHz QuasiPeak 120 kHz 15 s Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
35.981700	10.9	15000.000	120.000	170.0	V	260.0	13.1	19.1	30.0	
44.093550	13.4	15000.000	120.000	137.0	V	173.0	13.3	16.6	30.0	
55.439850	9.6	15000.000	120.000	138.0	V	-7.0	12.8	20.4	30.0	
694.161150	19.7	15000.000	120.000	170.0	H	-5.0	22.3	16.3	36.0	
745.449600	20.8	15000.000	120.000	114.0	V	-6.0	23.6	15.2	36.0	
906.174150	22.4	15000.000	120.000	148.0	V	94.0	25.2	13.6	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.42
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (1005)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


EMC 32 Version 8.10.00

Plot 7: Middle channel, 1 GHz to 12.75 GHz, vertical polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 8: Middle channel, 1 GHz to 12.75 GHz, horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 9: Middle channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 13:56:14

Plot 10: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 14:10:50

Plot 11: Highest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


CETECOM ICT Services GmbH

Common Information

EUT: AAD-3880107-BV
 Serial Number: BX902D9ZMM | IMEI: 00440214-260460-6
 Test Description: FCC part 15 class B @ 10 m
 Operating Conditions: WLAN n mode TX Ch. 11 + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dB μ V/m
Subrange **Detectors** **IF Bandwidth** **Meas. Time** **Receiver**
 30 MHz - 2 GHz QuasiPeak 120 kHz 15 s Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
34.443000	9.5	15000.000	120.000	135.0	H	196.0	13.0	20.5	30.0	
43.042050	11.2	15000.000	120.000	170.0	V	8.0	13.3	18.8	30.0	
51.653700	10.8	15000.000	120.000	136.0	V	-7.0	13.2	19.2	30.0	
709.406550	20.1	15000.000	120.000	170.0	H	177.0	22.7	15.9	36.0	
793.890150	21.0	15000.000	120.000	170.0	H	196.0	23.8	15.0	36.0	
896.730450	22.5	15000.000	120.000	170.0	V	196.0	25.2	13.5	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.42
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (1005)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12


EMC 32 Version 8.10.00

Plot 12: Highest channel, 1 GHz to 12.75 GHz, vertical polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 13: Highest channel, 1 GHz to 12.75 GHz, horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 14: Highest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 13:57:46

Plot 15: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 14:12:02

9.11 RX spurious emissions radiated

Description:

Measurement of the radiated spurious emissions in idle/receive mode. The results are valid for both modes.

Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Video bandwidth:	Sweep: 100 kHz Remeasurement: 10 Hz
Resolution bandwidth:	F < 1 GHz: 100 kHz F > 1 GHz: 1 MHz
Span:	30 MHz to 26 GHz
Trace-Mode:	Max Hold

Limits:

FCC		IC	
CFR Part 15.109		RSS Gen, Issue 2, 4.10	
RX Spurious Emissions Radiated			
Frequency (MHz)	Field Strength (dB μ V/m)	Measurement distance	
30 - 88	30.0	10	
88 – 216	33.5	10	
216 – 960	36.0	10	
Above 960	54.0	3	

Results:

RX Spurious Emissions Radiated [dB μ V/m]		
F [MHz]	Detector	Level [dB μ V/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
No emissions detected between 1 GHz and 12.75 GHz.		
For emissions above 12.75 GHz, please take a look at the plots.		
Measurement uncertainty	± 3 dB	

Result: The result of the measurement is passed.

Plots: RX / Idle – mode

Plot 1: 30 MHz to 1 GHz, vertical & horizontal polarization


CETECOM ICT Services GmbH

Common Information

EUT: AAD-3880107-BV
 Serial Number: BX902D9ZMM | IMEI: 00440214-260460-6
 Test Description: FCC part 15 class B @ 10 m
 Operating Conditions: WLAN idle + charging
 Operator Name: Hennemann
 Comment: AC: 115 V / 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Level Unit: dBµV/m
Subrange **Detectors** **IF Bandwidth** **Meas. Time** **Receiver**
 30 MHz - 2 GHz QuasiPeak 120 kHz 15 s Receiver



Final Result 1


Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
38.162700	9.7	15000.000	120.000	115.0	V	270.0	13.3	20.3	30.0	
44.228250	13.5	15000.000	120.000	126.0	V	79.0	13.3	16.5	30.0	
53.254200	9.8	15000.000	120.000	136.0	V	196.0	13.1	20.2	30.0	
732.399600	20.6	15000.000	120.000	170.0	V	271.0	23.3	15.4	36.0	
760.417650	21.0	15000.000	120.000	164.0	V	196.0	23.7	15.0	36.0	
858.915150	22.0	15000.000	120.000	170.0	H	184.0	24.7	14.0	36.0	

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]


Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.42
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (1005)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

EMC 32 Version 8.10.00


Plot 2: 1 GHz to 12.75 GHz, vertical polarization



Plot 3: 1 GHz to 12.75 GHz, horizontal polarization




Plot 4: 12.75 GHz to 18 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 13:59:02

Plot 5: 18 GHz to 26 GHz, vertical & horizontal polarization



Date: 2.JUN.2011 14:00:50

9.12 TX spurious emissions radiated < 30 MHz

Description:

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The EUT is set to channel 6. This measurement is representative for all channels and modes. If critical peaks are found channel 1 and channel 11 will be measured too. The measurement is performed with the data rate producing the highest output power. The limits are recalculated to a measurement distance of 3 m with 40 dB/decade according CFR Part 2.

Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Video bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Resolution bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace-Mode:	Max Hold

Limits:

FCC		IC	
CFR Part 15.209(a)		RSS –Gen	
TX Spurious Emissions Radiated < 30 MHz			
Frequency (MHz)	Field Strength (dB μ V/m)	Measurement distance	
0.009 – 0.490	2400/F(kHz)	300	
0.490 – 1.705	24000/F(kHz)	30	
1.705 – 30.0	30	30	


Results:

TX Spurious Emissions Radiated < 30 MHz [dB μ V/m]		
F [MHz]	Detector	Level [dB μ V/m]
No peaks detected.		
Measurement uncertainty	± 3 dB	


Result: The result of the measurement is passed.

Plots: DSSS / b – mode


Plot 1: Lowest channel, 9 kHz to 30 MHz



Plot 2: Middle channel, 9 kHz to 30 MHz




Plot 3: Highest channel, 9 kHz to 30 MHz




Plots: OFDM / g – mode


Plot 1: Lowest channel, 9 kHz to 30 MHz



Plot 2: Middle channel, 9 kHz to 30 MHz




Plot 3: Highest channel, 9 kHz to 30 MHz




Plots: OFDM / n – mode


Plot 1: Lowest channel, 9 kHz to 30 MHz



Plot 2: Middle channel, 9 kHz to 30 MHz




Plot 3: Highest channel, 9 kHz to 30 MHz



Plots: RX / Idle – mode

Plot 1: 9 kHz to 30 MHz



9.13 TX spurious emissions conducted < 30 MHz

Description:

Measurement of the conducted spurious emissions in transmit mode below 30 MHz. The EUT is set to channel 6. This measurement is repeated for DSSS and OFDM modulation. If critical peaks are found channel 1 and channel 11 will be measured too. The measurement is performed with the data rate producing the highest output power. Both power lines, phase and neutral line, are measured. Found peaks are remeasured with average and quasi peak detection to show compliance to the limits.

Measurement:

Measurement parameter	
Detector:	Peak - Quasi Peak / Average
Sweep time:	Auto
Video bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Resolution bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace-Mode:	Max Hold

Limits:

FCC		IC	
CFR Part 15.107(a)		ICES-003, Issue 4	
TX Spurious Emissions Conducted < 30 MHz			
Frequency (MHz)	Quasi-Peak (dBµV/m)	Average (dBµV/m)	
0.15 – 0.5	66 to 56*	56 to 46*	
0.5 – 5	56	46	
5 – 30.0	60	50	

*Decreases with the logarithm of the frequency


Results:

TX Spurious Emissions Conducted < 30 MHz [dBµV/m]		
F [MHz]	Detector	Level [dBµV/m]
No peaks detected.		
Measurement uncertainty	± 3 dB	


Result: The result of the measurement is passed.

Plots:


Plot 1: DSSS / b – mode, 9 kHz to 30 MHz, phase line




Plot 2: DSSS / b – mode, 9 kHz to 30 MHz, neutral line




Plot 3: OFDM / g – mode, 9 kHz to 30 MHz, phase line




Plot 4: OFDM / g – mode, 9 kHz to 30 MHz, neutral line




Plot 5: OFDM / n – mode, 9 kHz to 30 MHz, phase line




Plot 6: OFDM / n – mode, 9 kHz to 30 MHz, neutral line



Plot 7: RX / Idle – mode, 9 kHz to 30 MHz, phase line



Plot 8: RX / Idle – mode, 9 kHz to 30 MHz, neutral line



10 Test equipment and ancillaries used for tests

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, rf-generating and signalling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Labor/Item).

No.	Lab / Item	Equipment	Type	Manufact.	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	n. a.	Isolating Transformer	RT5A	Grundig	8041	300001626	g		
2	n. a.	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	8812-3088	300001032	vkII	05.03.2009	05.09.2011
3	n. a.	Active Loop Antenna	6502	EMCO	2210	300001015	ne		
4	n. a.	Anechoic chamber	FAC 3/5m	MWB / TDK	87400/02	300000996		23.03.2009	
5	n. a.	Relais Matrix	3488A	HP Meßtechnik	2719A15013	300001156	ne		
6	n. a.	Relais Matrix	PSU	R&S	890167/024	300001168	ne		
7	n. a.	Isolating Transformer	RT5A	Grundig	9242	300001263	ne		
8	n. a.	Three-Way Power Splitter, 50 Ohm	11850C	HP Meßtechnik		300000997	ne		
9	n. a.	Switch / Control Unit	3488A	HP	2605e08770	300001443	ne		
10	n. a.	Amplifier	js42-00502650-28-5a	Parzich GMBH	928979	300003143	ne		
11	n. a.	Band Reject filter	WRCG2400/2483-2375/2505-50/10SS	Wainwright	11	300003351	ev		
12	n. a.	TILE-Software Emission	Quantum Change, Modell TILE-ICS/FULL	EMCO	none	300003451	ne		
13	n. a.	PSA Spectrum Analyzer 3 Hz - 26.5 GHz	E4440A	Agilent Technologies	MY48250080	300003812	k	08.09.2010	08.09.2012
14	n. a.	RF Filter Section 9kHz - 1GHz	N9039A	Agilent Technologies	MY48260003	300003825	vkII	08.09.2010	08.09.2012
15	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	371	300003854	vkII	17.12.2008	17.12.2011
16	45	Switch-Unit	3488A	HP Meßtechnik	2719A14505	300000368	g		
17	n. a.	software	SPS_PHE 1.4f	Spitzberger & Spieß	B5981; 5D1081;B5979	300000210	ne		
18	n. a.	EMI Test Receiver	ESCI 1166.5950.03	R&S	100083	300003312	k	05.01.2011	05.01.2013
19	n. a.	Amplifier	JS42-00502650-28-5A	MITEQ	1084532	300003379	ev		
20	n. a.	Antenna Tower	Model 2175	ETS-LINDGREN	64762	300003745	izw		
21	n. a.	Positioning Controller	Model 2090	ETS-LINDGREN	64672	300003746	izw		
22	n. a.	Turntable Interface-Box	Model 105637	ETS-LINDGREN	44583	300003747	izw		
23	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	295	300003787	k	01.04.2010	01.04.2012
24	n. a.	Spectrum-Analyzer	FSU26	R&S	200809	300003874	k	10.01.2011	10.01.2013

25	11b	Microwave System Amplifier, 0.5-26.5 GHz; 25 dB gain	83017A	HP Meßtechnik	00419	300002268	ev	10.03.2011	
26	A026	Std. Gain Horn Antenna 12.4 to 18.0 GHz	639	Narda		300000787	ne		
27	A029	Std. Gain Horn Antenna 18.0 to 26.5 GHz	638	Narda		300002442	ne		
28	n. a.	DC Power Supply 0 – 32V	1108-32	Heiden	001802	300001383	Ve	23.06.2010	23.06.2013
29	n. a.	Spectrum Analyzer 20 Hz - 50 GHz	FSU50	R&S	200012	300003443	ve	01.07.2010	01.07.2012

Agenda: Kind of Calibration

k calibration / calibrated
 ne not required (k, ev, izw, zw not required)
 ev periodic self verification
 Ve long-term stability recognized
 vkl! Attention: extended calibration interval
 NK! Attention: not calibrated

EK limited calibration
 zw cyclical maintenance (external cyclical maintenance)
 izw internal cyclical maintenance
 g blocked for accredited testing
 *) next calibration ordered / currently in progress