



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6554
<http://www.pctestlab.com>



CERTIFICATE OF COMPLIANCE FCC Part 22/24 Test Report

Applicant:
SONY ERICSSON MOBILE COMMUNICATION INC.
7001 Development Drive
Research Triangle Park, NC 27709
USA

Date of Testing:
January 15, 2009
Test Site/Location:
PCTEST Lab., Columbia, MD, USA
Test Report Serial No.:
0901050027.PY7

FCC ID: PY7A5880002
Applicant: SONY ERICSSON MOBILE COMMUNICATION INC.

Application Type: Certification
FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
FCC Rule Part(s): §2; §22(H); §24(E)
EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver
Model(s): PTX-932
Tx Frequency Range: 824.70 - 848.31MHz (Cell. CDMA) / 1850.20 - 1909.80MHz (PCS GSM)
Max. RF Output Power: 0.259 W ERP Cell. CDMA (24.14 dBm)
1.047 W EIRP PCS GSM (30.20 dBm)
Emission Designator(s): 1M28F9W (CDMA) / 243KGXW (PCS GSM)
Test Device Serial No.: *identical prototype* [S/N: 3114 & 3156]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Power output listed is ERP for Part 22 and EIRP for Part 24

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.

Randy Ortanez
President



FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 1 of 34

T A B L E O F C O N T E N T S


FCC PART 22/24 MEASUREMENT REPORT.....		3
1.0 INTRODUCTION		4
1.1 SCOPE		4
1.2 TESTING FACILITY.....		4
2.0 PRODUCT INFORMATION.....		5
2.1 EQUIPMENT DESCRIPTION		5
2.2 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS		5
2.3 LABELING REQUIREMENTS.....		5
3.0 DESCRIPTION OF TESTS		6
3.1 MEASUREMENT PROCEDURE		6
3.2 OCCUPIED BANDWIDTH EMISSION LIMITS		6
3.3 CELLULAR - BASE FREQUENCY BLOCKS.....		7
3.4 CELLULAR - MOBILE FREQUENCY BLOCKS.....		7
3.5 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....		8
3.6 RADIATED SPURIOUS AND HARMONIC EMISSIONS		8
3.7 FREQUENCY STABILITY / TEMPERATURE VARIATION		8
4.0 TEST EQUIPMENT CALIBRATION DATA		9
5.0 SAMPLE CALCULATIONS		10
6.0 TEST RESULTS.....		11
6.1 SUMMARY.....		11
6.2 EFFECTIVE RADIATED POWER AND EQUIVALENT ISOTROPIC RADIATED POWER DATA.....		12
6.3 CELLULAR CDMA AND PCS GSM RADIATED MEASUREMENTS.....		13
6.4 CELLULAR CDMA FREQUENCY STABILITY MEASUREMENTS		19
6.5 PCS GSM FREQUENCY STABILITY MEASUREMENTS.....		21
7.0 PLOT(S) OF EMISSIONS		23
8.0 CONCLUSION.....		34

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 2 of 34



MEASUREMENT REPORT

FCC Part 22/24





§2.1033 General Information

APPLICANT: SONY ERICSSON MOBILE COMMUNICATION INC.
APPLICANT ADDRESS: 7001 Development Drive
 Research Triangle Park, NC 27709
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 6660-B Dobbin Road, Columbia, MD 21045 USA
FCC RULE PART(S): §2; §22(H); §24(E)
BASE MODEL: PTX-932
FCC CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)
EMISSION DESIGNATOR(S): 1M28F9W (CDMA) / 243KGXW (PCS GSM)
MODE: CDMA850 / GSM1900
FREQUENCY TOLERANCE: ±0.00025 % (2.5 ppm)
Test Device Serial No.: 3114 & 3156 Production Pre-Production Engineering
DATE(S) OF TEST: January 15, 2009
TEST REPORT S/N: 0901050027.PY7

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab. located in Columbia, MD 21045, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.



FCC ID: PY7A5880002	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)	 Sony Ericsson	Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 3 of 34	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity area, the Baltimore-Washington Internt'l (BWI) airport, the city of Baltimore and the Washington, DC area. (see **Figure 1-1**).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 27, 2006 and Industry Canada.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: PY7A5880002	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)	Sony Ericsson	Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 4 of 34

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **SONY ERICSSON Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver FCC ID: PY7A5880002**. The EUT consisted of the following component(s):

Trade Name	FCC ID	Description
SONY ERICSSON	PY7A5880002	Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver

Table 2-1. EUT Equipment Description

2.2 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

2.3 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

Per 15.19; Docket 95-19

In addition to this requirement, a device subject to certification shall be labeled as follows:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 5 of 34	

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (see Figure 3-1). The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.




Figure 3-1. Diagram of 3-meter outdoor test range

Deviation from Measurement Procedure.....None


3.2 Occupied Bandwidth Emission Limits

§2.1049, 22.917(a)

- a. On any frequency outside a licensee’s frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB.
- b. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.
- c. When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the licensee’s frequency block edges, both upper and lower, as the design permits.
- d. The measurement of emission power can be expressed in peak or average values, provided they are expressed in the same parameters as the transmitter power.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 6 of 34	

3.3 Cellular - Base Frequency Blocks




BLOCK 1: 869 – 880 MHz (A* Low + A)

BLOCK 3: 890 – 891.5 MHz (A* High)

BLOCK 2: 880 – 890 MHz (B)

BLOCK 4: 891.5 – 894 MHz (B*)

3.4 Cellular - Mobile Frequency Blocks



BLOCK 1: 824 – 835 MHz (A* Low + A)

BLOCK 3: 845 – 846.5 MHz (A* High)

BLOCK 2: 835 – 845 MHz (B)

BLOCK 4: 846.5 – 849 MHz (B*)

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 7 of 34	

3.5 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, 22.917(a), 24.238(a)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic.

3.6 Radiated Spurious and Harmonic Emissions

§2.1053, 22.917(a), 24.238(a)

Spurious and harmonic radiated emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits.

3.7 Frequency Stability / Temperature Variation

§2.1055, 22.355, 24.235

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.

Time Period and Procedure:

1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
2. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A sufficient stabilization period at each temperature shall be used prior to each frequency requirement.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 8 of 34	

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	263-10dB	(DC-18GHz) 10 dB Attenuator	N/A		N/A	N/A
-	No.165	(30MHz - 1000MHz) RG58 Coax Cable	N/A		N/A	N/A
-	No.166	(1000-26500MHz) Microwave RF Cable	N/A		N/A	N/A
-	No.167	(100kHz - 100MHz) RG58 Coax Cable	N/A		N/A	N/A
Agilent	11713A	Attenuation/Switch Driver	12/4/2008	Annual	12/4/2009	3439A02645
Agilent	8449B	(1-26.5GHz) Pre-Amplifier	12/4/2008	Annual	12/4/2009	3008A00985
Agilent	8495A	(0-70dB) DC-4GHz Attenuator	N/A		N/A	N/A
Agilent	85650A	Quasi-Peak Adapter	3/13/2008	Annual	3/13/2009	2043A00301
Agilent	8566B	(100Hz-22GHz) Spectrum Analyzer	12/5/2008	Annual	12/5/2009	3638A08713
Agilent	8566B	Opt. 462 Impulse Bandwidth	12/5/2008	Annual	12/5/2009	3701A22204
Agilent	8591A	(9kHz-1.8GHz) Spectrum Analyzer	8/19/2008	Annual	8/19/2009	3144A02458
Agilent	8648D	(9kHz-4GHz) Signal Generator	10/11/2007	Biennial	10/11/2009	3613A00315
Agilent	8901A	Modulation Analyzer	8/18/2008	Annual	8/18/2009	2432A03467
Agilent	8903B	Audio Analyzer	8/18/2008	Annual	8/18/2009	3011A09025
Agilent	E4407B	ESA Spectrum Analyzer	3/13/2008	Annual	3/13/2009	US39210313
Agilent	E4432B	ESG-D Series Signal Generator	8/18/2008	Annual	8/18/2009	US40053896
Agilent	E4448A	(3Hz-50GHz) Spectrum Analyzer	12/5/2008	Annual	12/5/2009	US42510244
Agilent	E5515C	Wireless Communications Test Set	6/8/2007	Biennial	6/8/2009	GB46110872
Agilent	E5515C	Wireless Communications Test Set	6/8/2007	Biennial	6/8/2009	GB46310798
Agilent	E5515C	Wireless Communications Test Set	9/10/2008	Biennial	9/10/2010	GB41450275
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/8/2007	Biennial	3/8/2009	MY45470194
Compliance Design	Roberts	Dipole Set	11/9/2007	Biennial	11/9/2009	146
Compliance Design	Roberts	Dipole Set	11/9/2007	Biennial	11/9/2009	147
Emco	3115	Horn Antenna (1-18GHz)	9/24/2007	Biennial	9/24/2009	9704-5182
Emco	3115	Horn Antenna (1-18GHz)	10/4/2007	Biennial	10/4/2009	9205-3874
Emco	3121C-DB4	Dipole Antenna	1/23/2007	Biennial	1/23/2009	23951
Espec	ESX-2CA	Environmental Chamber	3/12/2008	Annual	3/12/2009	17620
Gigatronics	80701A	(0.05-18GHz) Power Sensor	8/18/2008	Annual	8/18/2009	1833460
Gigatronics	8651A	Universal Power Meter	8/18/2008	Annual	8/18/2009	1835299
Gigatronics	8651A	Universal Power Meter	8/18/2008	Annual	8/18/2009	8650319
K & L	11SH10	Band Pass Filter	N/A	Annual	N/A	1300/4000
K & L	11SH10	Band Pass Filter	N/A	Annual	N/A	4000/12000
MiniCircuits	VHF-1300+	High Pass Filter	N/A		N/A	30716
MiniCircuits	VHF-3100+	High Pass Filter	N/A		N/A	30721
Pasternack	PE2208-6	Bidirectional Coupler	N/A		N/A	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	5/29/2008	Annual	5/29/2009	836371/0079
Rohde & Schwarz	CMU200	Base Station Simulator	7/23/2008	Annual	7/23/2009	109892
Rohde & Schwarz	NRVD	Dual Channel Power Meter	8/20/2008	Biennial	8/20/2010	101695
Rohde & Schwarz	NRVS	Single Channel Power Meter	7/3/2007	Biennial	7/3/2009	835360/0079
Rohde & Schwarz	NRV-Z32	Peak Power Sensor (100uW-2W)	12/5/2008	Biennial	12/5/2010	100155
Rohde & Schwarz	NRV-Z33	Peak Power Sensor (1mW-20W)	12/5/2008	Biennial	12/5/2010	100004
Rohde & Schwarz	NRV-Z53	Power Sensor	7/3/2007	Biennial	7/3/2009	846076/0007
Schwarzbeck	UHA9105	Dipole Antenna (400 - 1GHz) Rx	6/19/2007	Biennial	6/18/2009	9105-2404
Schwarzbeck	UHA9105	Dipole Antenna (400 - 1GHz) Tx	6/19/2007	Biennial	6/18/2009	9105-2403
Solar Electronics	8012-50-R-24-BNC	LISN	11/8/2007	Biennial	11/8/2009	310233
Sunol	DRH-118	Horn Antenna (1 - 18GHz)	5/9/2007	Biennial	5/9/2009	A050307

Table 4-1. Test Equipment

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 9 of 34	

5.0 SAMPLE CALCULATIONS

Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission - PCS Band

Example: Channel 25 PCS Mode 2nd Harmonic (3702.50 MHz)

The receive analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the receive analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 10 of 34

6.0 TEST RESULTS

6.1 Summary

Company Name: SONY ERICSSON MOBILE COMMUNICATION INC.
 FCC ID: PY7A5880002
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): CDMA850 / GSM1900

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)					
2.1049, 22.917(a), 24.238(a)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.0
2.1051, 22.917(a), 24.238(a)	Band Edge / Conducted Spurious Emissions	< 43 + 10log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Section 7.0
SAR Measurement Procedures for 3G Devices, June '06	Conducted Power Measurements for 3G Devices	N/A		PASS	FCC 3G Power Table
22.913(a)(2)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 6.2
24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 6.2
2.1053, 22.917(a), 24.238(a)	Undesirable Emissions	< 43 + 10log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Sections 6.3
2.1055, 22.355, 24,235	Frequency Stability	< 2.5 ppm		PASS	Sections 6.4
RECEIVER MODE (RX) / DIGITAL EMISSIONS					
15.107	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.107 limits	LINE CONDUCTED	PASS	Pt. 15B Test Report
15.109	General Field Strength Limits (Restricted Bands and Radiated Emissions Limits)	< FCC 15.109 limits	RADIATED (30MHz-1GHz) (1-25 GHz)	PASS	Pt. 15B Test Report
RF EXPOSURE					
2.1091 / 2.1093	SAR Test	1.6 W/kg (SAR Limit)	SAR	PASS	SAR Report

Table 6-1. Summary of Test Results

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 11 of 34	

6.2 Effective Radiated Power and Equivalent Isotropic Radiated Power Data §22.913(a)(2), §24.232(c).

POWER: "All Up" Bits (Cellular CDMA Mode)

Frequency [MHz]	Mode	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBd]	Pol [H/V]	ERP [dBm]	ERP [Watts]	Battery Type
824.70	CDMA850	-15.800	23.14	0.00	H	23.14	0.206	Standard
836.52	CDMA850	-14.800	24.14	0.00	H	24.14	0.259	Standard
848.31	CDMA850	-15.400	23.54	0.00	H	23.54	0.226	Standard

Table 6-2. Effective Radiated Power Output Data

Frequency [MHz]	Mode	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	Battery Type
1850.20	GSM1900	-14.350	22.20	8.00	H	30.20	1.047	Standard
1880.00	GSM1900	-14.730	21.82	8.00	H	29.82	0.959	Standard
1909.80	GSM1900	-14.840	21.71	8.00	H	29.71	0.935	Standard

Table 6-3 Equivalent Isotropic Radiated Power

NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 12 of 34	

6.3 Cellular CDMA and PCS GSM Radiated Measurements §2.1053, 22.917(a)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 1013
 MEASURED OUTPUT POWER: 24.140 dBm = 0.259 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W)$: 37.14 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-46.25	6.08	-40.17	H	64.3
2474.10	-59.15	6.08	-53.07	H	77.2
3298.80	-56.20	6.53	-49.67	H	73.8
4123.50	-94.05	6.87	-87.18	H	111.3
4948.20	-91.89	7.21	-84.68	H	108.8

Table 6-4. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 13 of 34

Cellular CDMA Radiated Measurements (Cont'd)
§2.1053, 22.917(a)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.52 MHz
 CHANNEL: 384
 MEASURED OUTPUT POWER: 24.140 dBm = 0.259 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W)$: 37.14 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1673.04	-43.43	6.09	-37.34	H	61.5
2509.56	-54.53	6.55	-47.97	H	72.1
3346.08	-93.93	6.89	-87.03	H	111.2
4182.60	-92.09	7.43	-84.66	H	108.8
5019.12	-90.81	8.35	-82.46	H	106.6

Table 6-5. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 14 of 34	

Cellular CDMA Radiated Measurements (Cont'd)
§2.1053, 22.917(a)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.31 MHz
 CHANNEL: 777
 MEASURED OUTPUT POWER: 24.140 dBm = 0.259 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W)$: 37.14 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
1696.62	-42.10	6.09	-36.01	H	60.1
2544.93	-51.18	6.57	-44.61	H	68.7
3393.24	-53.21	6.91	-46.30	H	70.4
4241.55	-92.29	7.65	-84.65	H	108.8
5089.86	-90.48	8.33	-82.15	H	106.3

Table 6-6. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 15 of 34	

PCS GSM Radiated Measurements (Cont'd)
§2.1053, 24.238(a); RSS-133 (6.5.1)

OPERATING FREQUENCY: 1850.20 MHz
 CHANNEL: 512
 MEASURED OUTPUT POWER: 30.200 dBm = 1.047 W
 MODULATION SIGNAL: GSM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 43.20 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3700.40	-92.31	9.02	-83.30	V	113.5
5550.60	-42.87	10.40	-32.47	V	62.7
7400.80	-85.97	10.50	-75.47	V	105.7
9251.00	-38.97	11.85	-27.12	V	57.3
11101.20	-82.61	12.76	-69.85	V	100.1

Table 6-7 Radiated Spurious Data (PCS GSM Mode - Ch512)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 16 of 34	

PCS GSM Radiated Measurements (Cont'd)
§2.1053, 24.238(a); RSS-133 (6.5.1)

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 661
 MEASURED OUTPUT POWER: 30.200 dBm = 1.047 W
 MODULATION SIGNAL: GSM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 43.20 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-92.10	8.99	-83.11	V	113.3
5640.00	-39.13	10.40	-28.73	V	58.9
7520.00	-85.96	10.62	-75.34	V	105.5
9400.00	-37.98	11.70	-26.28	V	56.5
11280.00	-81.89	12.69	-69.20	V	99.4

Table 6-8 Radiated Spurious Data (PCS GSM Mode – Ch661)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
 according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 17 of 34	

PCS GSM Radiated Measurements (Cont'd)
§2.1053, 24.238(a); RSS-133 (6.5.1)

OPERATING FREQUENCY: 1909.80 MHz
 CHANNEL: 810
 MEASURED OUTPUT POWER: 30.200 dBm = 1.047 W
 MODULATION SIGNAL: GSM (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 43.20 dBc

FREQ. (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	CORRECT GENERATOR LEVEL (dBm)	POL (H/V)	(dBc)
3819.60	-91.89	8.97	-82.92	V	113.1
5729.40	-44.20	10.40	-33.80	V	64.0
7639.20	-85.84	10.71	-75.13	V	105.3
9549.00	-37.41	11.64	-25.77	V	56.0
11458.80	-81.18	12.62	-68.56	V	98.8

Table 6-9 Radiated Spurious Data (PCS GSM Mode – Ch810)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5 MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC3/SO55 with "All Up" power control bits. This unit was tested with its standard battery.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 18 of 34	

6.4 Cellular CDMA Frequency Stability Measurements

§2.1055, 22.355

OPERATING FREQUENCY: 836,520,000 Hz
 CHANNEL: 384
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	836,519,988	-12	-0.000001
100 %		- 30	836,519,981	-19	-0.000002
100 %		- 20	836,519,979	-21	-0.000003
100 %		- 10	836,519,976	-24	-0.000003
100 %		0	836,519,983	-17	-0.000002
100 %		+ 10	836,519,985	-15	-0.000002
100 %		+ 20	836,519,988	-12	-0.000001
100 %		+ 30	836,520,015	15	0.000002
100 %		+ 40	836,519,981	-19	-0.000002
100 %		+ 50	836,520,016	16	0.000002
115 %		4.26	+ 20	836,519,979	-21
BATT. ENDPOINT	3.30	+ 20	836,519,974	-26	-0.000003

Table 6-10. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 19 of 34	

Cellular CDMA Frequency Stability Measurements (Cont'd)
§2.1055, 22.355




Figure 6-1. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 20 of 34	

6.5 PCS GSM Frequency Stability Measurements

§2.1055, 24.235; RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz
 CHANNEL: 661
 REFERENCE VOLTAGE: 3.7 VDC
 DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	3.70	+ 20 (Ref)	1,879,999,983	-17	-0.000001
100 %		- 30	1,879,999,979	-21	-0.000001
100 %		- 20	1,879,999,982	-18	-0.000001
100 %		- 10	1,880,000,014	14	0.000001
100 %		0	1,880,000,012	12	0.000001
100 %		+ 10	1,879,999,981	-19	-0.000001
100 %		+ 20	1,879,999,983	-17	-0.000001
100 %		+ 30	1,880,000,014	14	0.000001
100 %		+ 40	1,879,999,978	-22	-0.000001
100 %		+ 50	1,880,000,019	19	0.000001
115 %		4.26	+ 20	1,879,999,975	-25
BATT. ENDPOINT	3.30	+ 20	1,879,999,971	-29	-0.000002

Table 6-11. Frequency Stability Data (PCS GSM Mode – Ch. 661)

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 21 of 34	

PCS GSM Frequency Stability Measurements (Cont'd)
§2.1055, 24.235; RSS-133 (6.3)






Figure 6-2. Frequency Stability Graph (PCS GSM Mode – Ch. 661)

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 22 of 34

7.0 PLOT(S) OF EMISSIONS




Plot 7-1. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)



Plot 7-2. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 23 of 34




Plot 7-3. Band Edge Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-4. 4MHz Span Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: PY7A5880002	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 24 of 34




Plot 7-5. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-6. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: PY7A5880002	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 25 of 34




Plot 7-7. Occupied Bandwidth Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-8. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: PY7A5880002	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 26 of 34



Plot 7-9. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-10. Band Edge Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: PY7A5880002	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 27 of 34




Plot 7-11. 4MHz Span Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-12. Conducted spurious Plot (PCS GSM Mode – Ch. 512)

FCC ID: PY7A5880002	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 28 of 34




Plot 7-13. Conducted spurious Plot (PCS GSM Mode – Ch. 512)




Plot 7-14. Band Edge Plot (PCS GSM Mode – Ch. 512)

FCC ID: PY7A5880002	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 29 of 34




Plot 7-15. Conducted spurious Plot (PCS GSM Mode – Ch. 661)



Plot 7-16. Conducted spurious Plot (PCS GSM Mode – Ch. 661)

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 30 of 34	




Plot 7-17. Occupied Bandwidth Plot (PCS GSM Mode – Ch. 661)




Plot 7-18. Peak to Average Ratio Plot (PCS GSM Mode – Ch. 661)

FCC ID: PY7A5880002	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)	Sony Ericsson	Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 31 of 34	




Plot 7-19. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)



Plot 7-20. Conducted Spurious Plot (PCS GSM Mode – Ch. 810)

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 32 of 34



Plot 7-21. Band Edge Plot (PCS GSM Mode – Ch. 810)

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver		Page 33 of 34

8.0 CONCLUSION

The data collected show that the **SONY ERICSSON Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver FCC ID: PY7A5880002** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules.

FCC ID: PY7A5880002		FCC Pt. 22/24 CDMA850 / GSM1900 MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0901050027.PY7	Test Dates: January 15, 2009	EUT Type: Cellular CDMA / PCS GSM Phone with Bluetooth, RFID and GPS Receiver	Page 34 of 34	