



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

## Exhibit 11: SAR Test Report of Portable Cellular Phone FCC ID: PY7AC052014 Model : Z525A

**Date of test:** August 24 - August 28, 2005  
**Date of Report:** January 29 – February 14, 2006 (PTT Testing)  
 March 3, 2006

**Laboratory:** SAR Testing Laboratory Sony Ericsson Mobile Communications, Inc. 7001 Development Drive, P.O. Box 13969, Research Triangle Park, NC, 27709, USA

**Tested by:** Rodney Dixon  
 Eng. Technician III, Product Verification Group

**Test Responsible:** Gerard Hayes *Gerard Hayes 03 March 2006*  
 Technical Manager, Electromechanical Development Group, M2M

**Accreditation:** This laboratory is accredited to ISO/IEC 17025-1999 to perform the following electromagnetic exposure tests:



- Specific Absorption Rate (SAR)
- Dielectric parameters
- RF power measurement

On the following types of products:  
 Wireless communications devices. A2LA certificate #1650-01

**Statement of Compliance:** Sony Ericsson Mobile Communications, Inc declares under its sole responsibility that portable cellular telephone FCC ID PY7AC052014 model Z525A to which this declaration relates, is in conformity with the appropriate General Population/Uncontrolled RF exposure standards, recommendations and guidelines (FCC 47 CFR §2.1093). It also declares that the product was tested in accordance with the appropriate measurement standards, guidelines and recommended practices. Any deviations from these standards, guidelines and recommended practices are noted below:

(none)

© Sony Ericsson Mobile Communications, Inc. 2006

This test report shall not be reproduced except in full, without written approval of the laboratory.

The results and statements contained herein relate only to the items tested. The names of individuals involved may be mentioned only in connection with the statements or results from this report.

Sony Ericsson Mobile Communications encourages all feedback, both positive and negative, on this test report.



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

## Table of Contents

<b>1. Introduction</b>	<b>3</b>
<b>2. Description of the Device Under Test</b>	<b>3</b>
<i>2.1 Antenna description</i>	3
<i>2.2 Device description</i>	3
<b>3. Test Equipment Used</b>	<b>5</b>
<i>3.1 Dosimetric System</i>	5
<i>3.2 Additional Equipment</i>	5
<b>4. Electrical parameters of the tissue simulating liquid</b>	<b>6</b>
<b>5. System Accuracy Verification</b>	<b>8</b>
<b>6. Test Results</b>	<b>9</b>
<i>6.1 Head Adjacent Test Results</i>	9
<i>6.2 Body-Worn Test Results</i>	13
<b>References</b>	<b>15</b>
<b>Appendix 1: SAR distribution comparison for system accuracy verification</b>	<b>16</b>
<b>Appendix 2: SAR distribution plots for Phantom Head Adjacent Use</b>	<b>37</b>
<b>Appendix 3: SAR distribution plots for Body Worn Configuration</b>	<b>122</b>
<b>Appendix 4: Probe Calibration Certificate</b>	<b>147</b>
<b>Appendix 5: Measurement Uncertainty Budget</b>	<b>156</b>
<b>Appendix 6: Photographs of the device under test</b>	<b>167</b>



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

## 1. Introduction

The Sony Ericsson SAR Laboratory has performed measurements of the maximum potential exposure to the user of portable cellular phone FCC ID PY7AC052014 model Z525A. This phone is identical to FCC ID PY7AC052012 model Z520a with added push-to-talk (PTT) functionality that is enabled in GSM Mode with 1/8 duty cycle. The Specific Absorption Rate (SAR) of this product was measured. The applicable RF safety guidelines and the SAR measurement specifications used for the test are described in [1].

## 2. Description of the Device Under Test

### 2.1 Antenna description

<b>Type</b>	PIFA- Type Antenna	
<b>Location</b>	External plastic loop, near the hinge	
<b>Dimensions</b>	Width	40 mm
	Length	30 mm
	Height	8mm

### 2.2 Device description

<b>FCC ID Number / Device Model</b>	PY7AC052014 / Z525A (formerly FCC ID PY7AC052012 / Z520a)							
<b>Serial number</b>	BD30246HHE BD3ZZYJGGQ		BD302466ZH BD3ZZYJHY5		BD302466ZH BD3ZZYJHY5		BD30246HHE BD3ZZYJJU4	
<b>Mode(s) of Operation</b>	GSM 800		GSM 900		GSM 1800		GSM 1900	
<b>Modulation Mode(s)</b>	TDMA		TDMA		TDMA		TDMA	
<b>Target Value and Factory Tolerance Window for Maximum Output Power Setting</b>  GSM Mode: 1/8 Duty Cycle (PTT included in this mode.)	$f_{low}$	32.2 dBm +0.4/ -1.2 dB	$f_{low}$	31.3 dBm +0.2/ -0.3 dB	$f_{low}$	30.0 dBm +0.5/ -1.5 dB	$f_{low}$	30.0 dBm +0.5/ -1.5 dB
	$f_{mid}$	31.7 dBm +0.4/ -0.7 dB	$f_{mid}$	32.1 dBm +0.5/ -1.1 dB	$f_{mid}$	30.0 dBm +0.5/ -1.5 dB	$f_{mid}$	30.0 dBm +0.5/ -1.5 dB
	$f_{high}$	31.7 dBm +0.3/ -0.7 dB	$f_{high}$	32.3 dBm +0.5/ -1.3 dB	$f_{high}$	30.0 dBm +0.5/ -1.5 dB	$f_{high}$	30.0 dBm +0.5/ -1.5 dB
<b>GPRS Mode: 2/8 Duty Cycle</b>  Target Maximum Output Power Setting (adjusted from GSM mode)	$f_{low}$	32.2 max	$f_{low}$	30.8 $\pm 0.3$	$f_{low}$	Same as GSM 1:8	$f_{low}$	Same as GSM 1:8
	$f_{mid}$	31.6 max	$f_{mid}$	32.2 max	$f_{mid}$	Same as GSM 1:8	$f_{mid}$	Same as GSM 1:8
	$f_{high}$	31.2 $\pm 0.3$	$f_{high}$	32.7 max	$f_{high}$	Same as GSM 1:8	$f_{high}$	Same as GSM 1:8
<b>Calibration Frequency</b> ( $f_{low}$ , $f_{mid}$ , $f_{high}$ )	$f_{high}$		$f_{low}$		$f_{mid}$		$f_{mid}$	
<b>Transmitting Frequency Rang(s)</b>	824-849 MHz		880-915 MHz		1710-1785 MHz		1850-1910 MHz	
<b>Production Unit or Identical Prototype (47 CFR §2.908)</b>	Identical Prototype							
<b>Device Category</b>	Portable							



REPORT

4(175)

Prepared (also subject responsible if other)		No.	
SEM/CV/PF/P Gerard Hayes and Rodney Dixon		REP 2006 001 Z525A 01	
Approved	Checked		
SEM/CV/PF/P Gerard Hayes		A	X:\SAR Chamber\FCC reports\Z525A\Final

<b>RF Exposure Limits</b>	General Population / Uncontrolled
---------------------------	-----------------------------------



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final

### 3. Test Equipment Used

#### 3.1 Dosimetric System

The Sony Ericsson SAR Laboratory utilizes Dosimetric Assessment Systems (Dasy3™ v3.1d for body-worn measurements and Dasy4™ for adjacent to head measurements) manufactured by Schmid & Partner Engineering AG (SPEAG™), of Zurich Switzerland. The overall RSS uncertainty of the measurement system is ±10.77% (K=1) with an expanded uncertainty of ±21.55% (K=2) for Dasy3™ v3.1d and ±9.49% (K=1) with an expanded uncertainty of ±18.74% (K=2) for Dasy4™. The measurement uncertainty budget is given in Appendix 5 for both systems. The list of calibrated equipment used for the measurements is shown in the following table.

Description	Serial Number	Cal Due Date
DASY3 DAE V1	345	10-Nov-2006
DASY3 DAE V1	416	10-Nov-2006
DASY3 DAE V1	417	11-Nov-2006
E-Field Probe ETDV6	1539	22-Nov-2006
E-Field Probe ETDV6	1586	26-May-2006
E-Field Probe ETDV6	1587	26-May-2006
Dipole Validation Kit, DV835V2	438	24-May-2006
Dipole Validation Kit, DV835V2	429	21-Nov-2006
Dipole Validation Kit, DV900V2	035	24-May-2006
Dipole Validation Kit, DV900V2	049	21-Nov-2006
Dipole Validation Kit, DV1800V2	238	11-May-2006
Dipole Validation Kit, DV1800V2	217	15-Nov-2006
Dipole Validation Kit, DV1900V2	536	19-May-2006
Dipole Validation Kit, DV1900V2	537	15-Nov-2006
S.A.M. Phantom used for 835MHz (Head)	1251	
S.A.M. Phantom used for 835MHz (Body)	1031	
S.A.M. Phantom used for 900MHz (Head and Body)	1251	
S.A.M. Phantom used for 1800MHz (Head and Body)	1335	
S.A.M. Phantom used for 1900MHz (Head)	1335	
S.A.M. Phantom used for 1900MHz (Body)	1020	

#### 3.2 Additional Equipment

Description	Serial Number	Cal Due Date
Signal Generator HP8648C	3537A01598	August 30, 2006
Power Meter 437B	3125U16382	December 5, 2006
Power Meter 437B	3125U13729	June 3, 2006
Power Sensor - 8482H	MY41090240	April 29, 2006
Power Sensor - 8482H	MY41090239	April 29, 2006
Dielectric Probe Kit HP85070B	US33020390	August 29, 2006
Digital Thermometer 61220-601 And Probe (61220-604)	350078	November 9, 2006
Digital Hygrometer/ Thermometer	21242911	November 9, 2006



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

HP RF Amplifier 8347A	3307A1069	May 4, 2006
-----------------------	-----------	-------------

#### 4. Electrical parameters of the tissue simulating liquid

Prior to conducting SAR measurements, the relative permittivity,  $\epsilon_r$ , and the conductivity,  $\sigma$ , of the tissue simulating liquids were measured with the dielectric probe kit. These values, along with the temperature of the simulated tissue are shown in the table below. A mass density of  $\rho=1\text{g/cm}^3$  was entered into the system in all the cases. It can be seen that the measured parameters are within tolerance of the recommended limits [1]. During the tests, the ambient temperature of the laboratory was in the range 22.2-24.8°C, the relative humidity was 30.2%- 53.9 %, and the liquid depth above the ear reference points was more than 15.0 cm for all the cases. It is seen that the measured parameters are satisfactory for compliance testing.

f (MHz)	Tissue type	Limits / Measured	Dielectric Parameters		
			$\epsilon_r$	s (S/m)	Simulated Tissue Temp (°C)
835	Head	Measured, 26-Aug-05	41.91	.913	22.6
		<b>Recommended Limits</b>	<b>41.50</b>	<b>0.90</b>	<b>20-25</b>
	Body	Measured, 27-Aug-05	54.21	1.003	22.3
		<b>Recommended Limits</b>	<b>55.20</b>	<b>0.97</b>	<b>20-25</b>
	Head	Measured, 28-Aug-05	40.2	.877	22.2
		<b>Recommended Limits</b>	<b>41.50</b>	<b>0.90</b>	<b>20-25</b>
		Measured, 29-Jan-06	41.37	0.898	24.1
		Measured 14-Feb-06	41.60	0.898	22.5
		<b>Recommended Limits</b>	<b>41.50</b>	<b>0.90</b>	<b>20-25</b>
900	Head	Measured, 24-Aug-05	41.55	.973	23
		<b>Recommended Limits</b>	<b>41.50</b>	<b>.97</b>	<b>20-25</b>
		Measured, 01-Feb-06	40.21	.953	24.5
	Body	<b>Recommended Limits</b>	<b>41.50</b>	<b>.97</b>	<b>20-25</b>
		Measured, 25-Aug-05	39.87	.937	22.1
		<b>Recommended Limits</b>	<b>41.50</b>	<b>.97</b>	<b>20-25</b>
1800	Head	Measured, 27-Aug-05	39.24	1.398	22
		<b>Recommended Limits</b>	<b>40.00</b>	<b>1.40</b>	<b>20-25</b>
		Measured, 31-Jan-06	38.81	1.382	21.7
	Body	<b>Recommended Limits</b>	<b>40.00</b>	<b>1.40</b>	<b>20-25</b>
		Measured, 26-Aug-05	39.1	1.37	21
		<b>Recommended Limits</b>	<b>40.00</b>	<b>1.40</b>	<b>20-25</b>
1900	Head	Measured, 25-Aug-05	38.26	1.469	22
		<b>Recommended Limits</b>	<b>40.00</b>	<b>1.40</b>	<b>20-25</b>
		Measured, 29-Jan-06	38.7	1.47	24.2
		Measured 14-Feb-06	38.8	1.47	23.2
	Body	<b>Recommended Limits</b>	<b>40.00</b>	<b>1.40</b>	<b>20-25</b>
		Measured, 24-Aug-05	51.04	1.507	22.5
<b>Recommended Limits</b>	<b>53.30</b>	<b>1.52</b>	<b>20-25</b>		



REPORT

7(175)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

The list of ingredients and the percent composition used for the simulated tissue are indicated in the table below.

<b>Ingredient</b>	<b>800/900 MHz Head 900MHz Body</b>	<b>800MHz Body</b>	<b>1800/1900 MHz Head 1800MHz Body</b>	<b>1900MHz Body</b>
Sugar	57.99%	56.00%	--	--
DGBE	--	--	44.92%	30.82%
Water	39.72%	41.76%	54.90%	68.89%
Salt	1.18%	0.76%	0.18%	0.29%
HEC	0.92%	1.21%	--	--
Bact.	0.19%	0.27%	--	--



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

#### 4. System Accuracy Verification

A system accuracy verification of the DASY3 was performed using the measurement equipment listed in Section 3.1. The daily system accuracy verification occurs within the flat section of the SAM phantom.

A SAR measurement was performed to see if the measured SAR was within +/- 10% from the target SAR indicated on the dipole certification sheet. These tests were done at 835MHz/900MHz and/or 1800MHz/1900MHz. These frequencies are within 100MHz of the mid-band frequency of the test device, according to [1]. The test was conducted on the same days as the measurement of the DUT. The results from the system accuracy verification are displayed in the table below (SAR values are normalized to 1W forward power delivered to the dipole). During these tests, the ambient temperature of the laboratory was in the range 22.6-24.8 °C, the relative humidity was in the range 30.2 – 51.5 % and the liquid depth above the ear reference points was above 15.0 cm in all the cases. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values. The SAR distributions are shown in Appendix 1.

Daily, prior to conducting tests, measurements were made with the RF sources powered off to determine the system noise level. The highest system noise was 0.000232 W/kg, which is below the recommended limit in [1].

f (MHz)	Tissue Type	Description	SAR (W/kg) 1g / 10g		Dielectric Parameters		Tissue Temp (°C)
			e <sub>r</sub>	s (S/m)	e <sub>r</sub>	s (S/m)	
835	Head	Measured, 26-Aug-05	9.6	6.1	41.91	.913	22.6
		<b>Recommended Limits</b>	<b>9.50</b>	<b>6.20</b>	<b>41.50</b>	<b>0.90</b>	<b>20-25</b>
		Measured, 29-Jan-06	8.9	5.8	41.37	.898	24.1
		Measured, 14-Feb-06	9.0	5.9	41.6	0.898	22.5
	<b>Recommended Limits</b>	<b>9.50</b>	<b>6.20</b>	<b>41.50</b>	<b>0.90</b>	<b>20-25</b>	
	Body	Measured, 27-Aug-05	10	6.5	54.21	1.003	22.3
<b>Recommended Limits</b>	<b>9.90</b>	<b>6.46</b>	<b>55.20</b>	<b>0.97</b>	<b>20-25</b>		
835	Head	Measured, 28-Aug-05	9.8	6.3	40.2	.877	22.2
		<b>Recommended Limits</b>	<b>9.50</b>	<b>6.20</b>	<b>41.50</b>	<b>0.90</b>	<b>20-25</b>
900	Head	Measured, 24-Aug-05	9.9	6.3	41.55	.973	23
		<b>Recommended Limits</b>	<b>10.8</b>	<b>6.9</b>	<b>41.5</b>	<b>0.97</b>	<b>20-25</b>
		Measured, 01-Feb-06	10	6.4	40.21	.953	24.5
		<b>Recommended Limits</b>	<b>10.8</b>	<b>6.9</b>	<b>41.5</b>	<b>0.97</b>	<b>20-25</b>
	Body	Measured, 25-Aug-05	9.8	6.3	39.87	.937	22.1
	<b>Recommended Limits</b>	<b>10.8</b>	<b>6.9</b>	<b>41.5</b>	<b>0.97</b>	<b>20-25</b>	
1800	Head	Measured, 27-Aug-05	36.3	19.6	39.24	1.398	22
		<b>Recommended Limits</b>	<b>38.1</b>	<b>19.80</b>	<b>40.00</b>	<b>1.40</b>	<b>20-25</b>
		Measured, 31-Jan-06	36.3	19.4	38.81	1.382	21.7
		<b>Recommended Limits</b>	<b>38.1</b>	<b>19.80</b>	<b>40.00</b>	<b>1.40</b>	<b>20-25</b>
	Body	Measured, 26-Aug-05	35.2	18.9	39.1	1.37	21
	<b>Recommended Limits</b>	<b>38.1</b>	<b>19.80</b>	<b>40.00</b>	<b>1.40</b>	<b>20-25</b>	
1900	Head	Measured, 25-Aug-05	40.3	21.1	38.26	1.469	22
		<b>Recommended Limits</b>	<b>39.70</b>	<b>20.50</b>	<b>40.00</b>	<b>1.40</b>	<b>20-25</b>
		Measured, 29-Jan-06	40.3	21.1	38.7	1.47	24.2
		Measured, 14-Feb-06	41.0	21.3	38.8	1.47	23.2
	<b>Recommended Limits</b>	<b>39.70</b>	<b>20.50</b>	<b>40.00</b>	<b>1.40</b>	<b>20-25</b>	
	Body	Measured, 24-Aug-05	43.2	22.2	51.04	1.507	22.5
<b>Recommended Limits</b>	<b>40.50</b>	<b>20.89</b>	<b>53.30</b>	<b>1.52</b>	<b>20-25</b>		



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

## 6.5. Test Results

For head measurements (with a 1/8 GSM duty cycle) and body measurements (2/8 EGPRS duty cycle), the test sample was operated using a base station simulator that allows control of the transmitter using the signally software that installed on the phone call. For the purposes of these tests, the unit is commanded to set to the proper channel, transmitter power level and transmit mode of operation. The phone was tested in the configurations stipulated in [1,2]. The phone was positioned into these configurations using the positioner supplied with the DASY 3.1d SAR measurement system.

The Cellular Phone FCC ID PY7AC052014 has the following battery option:  
BKB 193 203 (BST-37) Standard Lithium Polymer Battery

The phone was placed in the SAR measurement system with a fully charged battery.

### 6.1 Head Adjacent Test Results

The SAR results shown in Tables 1 through 3 are maximum SAR values averaged over 1 gram and 10 grams of phantom tissue. Also shown are the measured conducted output powers, the temperature of the test facility during the test, the temperature of the simulated tissue, the measured drift, and the extrapolated SAR. The extrapolated SAR corresponds to the measured SAR scaled to the maximum conducted output power.

The humidity and ambient temperature of the test facility were in the ranges 30.2 – 54.6 % and 20.6 -24.8°C, respectively. The SAR measurements were performed using the SAM phantoms listed in section 3.1.

The test conditions indicated as bold numbers in the following table are included in Appendix 2. All other test conditions measured lower SAR values than those included.

Summary of Maximum Extrapolated SAR Results : Head Adjacent			
Frequency	Extrapolated SAR (W/kg)		Test Configuration
	1 g	10 g	
<b>800 GSM</b>	1.474	0.937	Left head, cheek/touch position, 824 MHz BST-37 battery
<b>900 GSM</b>	0.602	0.370	Left head, cheek/touch position, 880 MHz BST-37 battery
<b>1800 GSM</b>	0.560	0.288	Right head, cheek/touch position, 1785 MHz BST-37 battery with Bluetooth on
<b>1900 GSM</b>	0.818	0.407	Right head, cheek/touch position, 1880 MHz BST-37 battery



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

f (MHz)	Channel/ frequency	Conducted Output Power (dBm)  GSM 1:8 Duty Cycle	FCC ID PYAC052014 with Standard Battery BST-37						
			Left Head (Cheek / Touch Position)						
			Measured (W/kg) 1g / 10g		Drift (dB)	Extrapolated (W/kg) 1g / 10g		Ambi ent Temp (°C)	Simulate Temp (°C)
800 GSM	<b>128 / 824</b>	<b>32.5</b>	<b>1.440</b>	<b>0.916</b>	<b>-0.13</b>	<b>1.474</b>	<b>0.937</b>	<b>23.7</b>	<b>22.6</b>
	189 / 837	32.0	1.430	0.906	0.05	1.463	0.927	23.7	22.6
	251 / 849	31.9	1.200	0.752	-0.03	1.228	0.770	23.7	22.6
Bluetooth on	<b>128 / 824</b>	<b>32.5</b>	<b>1.440</b>	<b>0.915</b>	<b>-0.11</b>	<b>1.474</b>	<b>0.936</b>	<b>22.5</b>	<b>23.1</b>
900 GSM	<b>975 / 880</b>	<b>31.4</b>	<b>0.588</b>	<b>0.362</b>	<b>-0.10</b>	<b>0.602</b>	<b>0.370</b>	<b>22.8</b>	<b>23.0</b>
	38 / 897	32.3	0.537	0.327	-0.09	0.550	0.335	22.8	23.0
	124 / 914	32.5	0.503	0.303	-0.16	0.515	0.310	22.8	23.0
Bluetooth on	<b>975 / 880</b>	<b>31.4</b>	<b>0.540</b>	<b>0.334</b>	<b>-0.06</b>	<b>0.553</b>	<b>0.342</b>	<b>21.9</b>	<b>22.3</b>
1800 GSM	512 / 1710	30.5	0.285	0.151	-0.17	0.285	0.151	22.2	22.0
	699 / 1748	30.4	0.363	0.196	-0.17	0.363	0.196	22.2	22.0
	<b>885 / 1785</b>	<b>30.4</b>	<b>0.375</b>	<b>0.199</b>	<b>-0.03</b>	<b>0.375</b>	<b>0.199</b>	<b>22.2</b>	<b>22.0</b>
1900 GSM	512 / 1850	30.4	0.515	0.265	-0.10	0.527	0.271	22.2	22.0
	<b>660/1880</b>	<b>30.3</b>	<b>0.523</b>	<b>0.264</b>	<b>-0.01</b>	<b>0.535</b>	<b>0.270</b>	<b>22.2</b>	<b>22.0</b>
	810/1910	30.3	0.491	0.246	-0.16	0.502	0.252	22.2	22.0
f (MHz)	Channel/ frequency	Conducted Output Power (dBm)  GSM 1:8 Duty Cycle	FCC ID PYAC052014 with Standard Battery BST-37						
			Left Head (15° Tilt Position)						
			Measured (W/kg) 1g / 10g		Drift (dB)	Extrapolated (W/kg) 1g / 10g		Ambi ent Temp (°C)	Simulate Temp (°C)
800 GSM	<b>128 / 824</b>	<b>32.5</b>	<b>0.361</b>	<b>0.264</b>	<b>-0.14</b>	<b>0.369</b>	<b>0.270</b>	<b>24</b>	<b>23.2</b>
	189 / 837	32.0	0.317	0.231	-0.03	0.324	0.236	24	23.2
	251 / 849	31.9	0.296	0.215	-0.15	0.303	0.220	24	23.2
900 GSM	<b>975 / 880</b>	<b>31.4</b>	<b>0.149</b>	<b>0.108</b>	<b>-0.05</b>	<b>0.152</b>	<b>0.111</b>	<b>22.8</b>	<b>23.1</b>
	38 / 897	32.3	0.145	0.105	-0.05	0.148	0.107	22.8	23.1
	124 / 914	32.5	0.144	0.104	-0.06	0.147	0.106	22.8	23.1
1800 GSM	512 / 1710	30.5	0.079	0.052	0.11	0.079	0.052	21.6	20.5
	<b>699 / 1748</b>	<b>30.4</b>	<b>0.089</b>	<b>0.058</b>	<b>-0.11</b>	<b>0.089</b>	<b>0.058</b>	<b>21.6</b>	<b>20.5</b>
	885 / 1785	30.4	0.078	0.051	-0.06	0.078	0.051	21.6	20.5
1900 GSM	512 / 1850	30.4	0.118	0.073	-0.10	0.121	0.075	21.2	21.1
	660/1880	30.3	0.128	0.079	-0.07	0.131	0.081	21.2	21.1
	<b>810/1910</b>	<b>30.3</b>	<b>0.130</b>	<b>0.080</b>	<b>-0.13</b>	<b>0.133</b>	<b>0.082</b>	<b>21.2</b>	<b>21.1</b>

**Table 1: SAR measurement results for the portable cellular telephone FCC ID PY7AC052014 model Z525A at maximum output power with Standard Battery BST-37. Measured against the left head.**



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

f (MHz)	Channel/ frequency	Conducted Output Power (dBm)  GSM 1:8 Duty Cycle	FCC ID PYAC052014 with Standard Battery BST-37						
			Right Head (Cheek / Touch Position)				Ambi ent Temp (°C)	Simulate Temp (°C)	
			Measured (W/kg) 1g / 10g		Drift (dB)	Extrapolated (W/kg) 1g / 10g			
800 GSM	<b>128 / 824</b>	<b>32.5</b>	<b>1.410</b>	<b>0.914</b>		<b>-0.06</b>	<b>1.443</b>	<b>0.935</b>	<b>22.6</b>
	189 / 837	32.0	1.240	0.800	0.09	1.269	0.819	22.6	22.2
	251 / 849	31.9	1.070	0.687	-0.05	1.095	0.703	22.6	22.2
900 GSM	<b>975 / 880</b>	<b>31.4</b>	<b>0.540</b>	<b>0.338</b>	<b>0.02</b>	<b>0.553</b>	<b>0.346</b>	<b>22.2</b>	<b>22.6</b>
	38 / 897	32.3	0.494	0.308	0.13	0.506	0.315	22.2	22.6
	124 / 914	32.5	0.459	0.282	0.05	0.470	0.289	22.2	22.6
1800 GSM	512 / 1710	30.5	0.385	0.209	-0.11	0.385	0.209	21.9	21.1
	699 / 1748	30.4	0.459	0.244	0.15	0.459	0.244	21.9	21.1
	<b>885 / 1785</b>	<b>30.4</b>	<b>0.556</b>	<b>0.287</b>	<b>0.00</b>	<b>0.556</b>	<b>0.287</b>	<b>21.9</b>	<b>21.1</b>
Bluetooth On	<b>885 / 1785</b>	<b>30.4</b>	<b>0.560</b>	<b>0.288</b>	<b>-0.08</b>	<b>0.560</b>	<b>0.288</b>	<b>21.7</b>	<b>21.3</b>
1900 GSM	512 / 1850	30.4	0.742	0.373	0.01	0.759	0.382	20.6	20.6
	<b>660/1880</b>	<b>30.3</b>	<b>0.799</b>	<b>0.398</b>	<b>-0.02</b>	<b>0.818</b>	<b>0.407</b>	<b>20.6</b>	<b>20.6</b>
	810/1910	30.3	0.704	0.346	-0.18	0.720	0.354	20.6	20.6
Bluetooth On	<b>660/1880</b>	<b>30.3</b>	<b>0.787</b>	<b>0.389</b>	<b>-0.10</b>	<b>0.805</b>	<b>0.398</b>	<b>21.5</b>	<b>20.5</b>
f (MHz)	Channel/ frequency	Conducted Output Power (dBm)  GSM 1:8 Duty Cycle	FCC ID PYAC052014 with Standard Battery BST-37						
			Right Head (15° Tilt Position)				Ambi ent Temp (°C)	Simulate Temp (°C)	
			Measured (W/kg) 1g / 10g		Drift (dB)	Extrapolated (W/kg) 1g / 10g			
800 GSM	<b>128 / 824</b>	<b>32.5</b>	<b>0.335</b>	<b>0.247</b>		<b>-0.07</b>	<b>0.343</b>	<b>0.253</b>	<b>22.4</b>
	189 / 837	32.0	0.294	0.216	0.00	0.301	0.221	22.4	22.1
	251 / 849	31.9	0.268	0.197	-0.05	0.274	0.202	22.4	22.1
900 GSM	<b>975 / 880</b>	<b>31.4</b>	<b>0.156</b>	<b>0.113</b>	<b>0.02</b>	<b>0.160</b>	<b>0.116</b>	<b>21.9</b>	<b>22.3</b>
	38 / 897	32.3	0.153	0.110	0.03	0.157	0.113	21.9	22.3
	124 / 914	32.5	0.150	0.109	-0.07	0.153	0.112	21.9	22.3
1800 GSM	512 / 1710	30.5	0.109	0.068	-0.17	0.109	0.068	21.8	20.9
	<b>699 / 1748</b>	<b>30.4</b>	<b>0.118</b>	<b>0.074</b>	<b>-0.13</b>	<b>0.118</b>	<b>0.074</b>	<b>21.8</b>	<b>20.9</b>
	885 / 1785	30.4	0.115	0.072	0.16	0.115	0.072	21.8	20.9
1900 GSM	512 / 1850	30.4	0.138	0.085	-0.05	0.141	0.087	21.3	20.7
	<b>660/1880</b>	<b>30.3</b>	<b>0.166</b>	<b>0.102</b>	<b>-0.06</b>	<b>0.170</b>	<b>0.104</b>	<b>21.3</b>	<b>20.7</b>
	810/1910	30.3	0.144	0.087	-0.116	0.147	0.089	21.3	20.7

**Table 2: SAR measurement results for the portable cellular telephone FCC ID PY7AC052014 model Z525A at maximum output power with Standard Battery BST-37. Measured against the right head.**



Prepared (also subject responsible if other) <b>SEM/CV/PF/P Gerard Hayes and Rodney Dixon</b>		No. <b>REP 2006 001 Z525A 01</b>	
Approved <b>SEM/CV/PF/P Gerard Hayes</b>	Checked	<b>A</b>	X:\SAR Chamber\FCC reports\Z525A\Final

f (MHz)	Channel/ frequency	Conducted Output Power (dBm)  GSM 1:8 Duty Cycle	FCC ID PYAC052014 with Standard Battery BST-37						
			PTT Flat Phantom Open position						
			Measured (W/kg) 1g / 10g		Drift (dB)	Extrapolated (W/kg) 1g / 10g		Ambient Temp (°C)	Simulate Temp (°C)
800 GSM	<b>128 / 824</b>	<b>32.6</b>	<b>0.500</b>	<b>0.354</b>	<b>-0.02</b>	<b>0.500</b>	<b>0.354</b>	24.8	24.1
	189 / 837	32.1	0.485	0.342	-0.01	0.485	0.342		
	251 / 849	32.0	0.404	0.283	-0.08	0.404	0.283		
Bluetooth On	128 / 824	32.6	0.523	0.370	-0.02	0.523	0.370		
900 GSM	975 / 880	31.5	0.166	0.116	0.05	0.166	0.116	24.6	24.5
	38 / 897	32.2	0.184	0.128	0.06	0.184	0.128		
	<b>124 / 914</b>	<b>32.4</b>	<b>0.212</b>	<b>0.148</b>	<b>0.07</b>	<b>0.212</b>	<b>0.148</b>		
Bluetooth On	124 / 914	32.4	0.202	0.141	0.02	0.202	0.141		
1800 GSM	512 / 1710	30.4	0.118	0.072	-0.18	0.121	0.074	24.6	21.7
	699 / 1748	30.4	0.114	0.070	0.02	0.117	0.072		
	<b>885 / 1785</b>	<b>30.4</b>	<b>0.150</b>	<b>0.091</b>	<b>-0.10</b>	<b>0.153</b>	<b>0.093</b>		
Bluetooth On	885 / 1785	30.4	0.147	0.089	-0.00	0.150	0.091		
1900 GSM	512 / 1850	30.4	0.121	0.070	-0.17	0.124	0.072	24.1	24.2
	660/1880	30.2	0.107	0.064	0.02	0.109	0.065		
	810/1910	30.1	0.124	0.073	0.14	0.127	0.075		
Bluetooth On	<b>810/1910</b>	<b>30.1</b>	<b>0.118</b>	<b>0.068</b>	<b>-0.09</b>	<b>0.121</b>	<b>0.069</b>		
f (MHz)	Channel/ frequency	Conducted Output Power (dBm)  GSM 1:8 Duty Cycle	FCC ID PYAF052014 with Standard Battery BST-37						
			PTT Flat Phantom / Closed position						
			Measured (W/kg) 1g / 10g		Drift (dB)	Extrapolated (W/kg) 1g / 10g		Ambient Temp (°C)	Simulate Temp (°C)
800 GSM	128 / 824	32.6	0.191	0.138	0.05	0.191	0.138	24.6	24.2
	189 / 837	32.1	0.160	0.116	-0.12	0.160	0.116		
	251 / 849	32.0	0.137	0.099	-0.01	0.137	0.099		
Bluetooth On	<b>128 / 824</b>	<b>32.6</b>	<b>0.190</b>	<b>0.138</b>	<b>-0.04</b>	<b>0.190</b>	<b>0.138</b>		
900 GSM	975 / 880	31.5	0.057	0.040	0.10	0.057	0.040	24.7	24.6
	38 / 897	32.2	0.052	0.037	-0.06	0.052	0.037		
	124 / 914	32.4	0.053	0.038	-0.01	0.053	0.038		
Bluetooth On	<b>975 / 880</b>	<b>31.5</b>	<b>0.055</b>	<b>0.039</b>	<b>-0.06</b>	<b>0.055</b>	<b>0.039</b>		
1800 GSM	<b>512 / 1710</b>	<b>30.4</b>	<b>0.091</b>	<b>0.060</b>	<b>-0.02</b>	<b>0.093</b>	<b>0.061</b>	22.6	21.5
	699 / 1748	30.4	0.078	0.051	-0.02	0.080	0.052		
	885 / 1785	30.4	0.082	0.052	-0.12	0.084	0.053		
Bluetooth On	512 / 1710	30.4	0.083	0.054	-0.04	0.085	0.055		
1900 GSM	<b>512 / 1850</b>	<b>30.4</b>	<b>0.132</b>	<b>0.082</b>	<b>-0.07</b>	<b>0.135</b>	<b>0.084</b>	24.2	24.2
	660/1880	30.2	0.114	0.073	-0.03	0.117	0.075		
	810/1910	30.1	0.118	0.075	-0.06	0.121	0.077		
Bluetooth On	512 / 1850	30.4	0.121	0.075	-0.15	0.124	0.077		

**Table 3: SAR measurement results for the portable cellular telephone FCC ID PY7AC052014 model Z525A at maximum output power with Standard Battery BST-37. Measured against the flat phantom.**



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

## 6.2 Body-Worn Test Results

The SAR results shown in Table 4 are the maximum SAR values averaged over 1 gram and 10 grams of phantom tissue. Also shown are the measured conducted output powers, the temperature of the test facility during the test, the temperature of the simulated tissue after the test, the measured drift and the extrapolated SAR. The extrapolated SAR corresponds to the measured SAR scaled to the maximum conducted output power. The humidity and ambient temperature of the test facility were in the ranges 41.1– 51.5 % and 21.6-23.8°C, respectively.

A “flat” phantom was used for the body-worn tests. This “flat” phantom corresponds to the flat portion of the SAM phantom. The tissue stimulant depth above the ear canal was verified to be above 15.0 cm in all the measurements. The same device holder described in section 6 was used for positioning the phone. The cellular phone was tested with a headset (HBP-20) connected to the device for all body-worn SAR measurements.

The following body-worn accessory was tested for this phone: 20 mm spacer

A full data set output of the test conditions with the highest SAR values from the DASY™ measurement system is included as Appendix 3. These test conditions included are indicated as bold numbers in the following tables. All other test conditions measured lower SAR values than those included.

Summary of Maximum Extrapolated SAR Results: Body-worn			
Frequency	Extrapolated SAR (W/kg)		Test Configuration
	1 g	10 g	
<b>800 GSM</b>	1.484	1.043	20MM SPACER Carry Accessory, back of phone facing body, 849 MHz, 2:8 Duty Cycle, BST-37 battery, Bluetooth on
<b>900 GSM</b>	0.475	0.326	20MM SPACER Carry Accessory, back of phone facing body, 880 MHz, 2:8 Duty Cycle, BST-37 battery, Bluetooth On
<b>1800 GSM</b>	0.293	0.180	20MM SPACER Carry Accessory, back of phone facing body, 1785 MHz, 2:8 Duty Cycle, BST-37 battery, Bluetooth on
<b>1900 GSM</b>	0.395	0.243	20MM SPACER Carry Accessory, front of phone facing body, 1850MHz, 2:8 Duty Cycle BST-37 battery, Bluetooth on



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

f (MHz)	Operating Condition	Channel/ frequency	Condu cted Output Power (dBm)	FCC ID PYAC052014 with Standard Battery BST-37							
				Body Worn			Carry Accessory: 20MM SPACER				
				Back of phone facing body							Measured (W/kg) 1g / 10g
<b>Back of phone facing body</b>											
800 GSM	2:8 Duty Cycle	128 / 824	32.0	1.390	0.963	-0.02	1.456	1.008	22.2	22.3	
		189 / 837	31.4	1.160	0.793	-0.04	1.215	0.830	22.2	22.3	
		251 / 849	31.4	0.893	0.608	-0.07	0.935	0.637	22.2	22.3	
	Bluetooth On	128 / 824	32.0	1.450	0.996	0.02	1.484	1.043	21.8	21.8	
	1:8 Duty Cycle	128 / 824	32.5	0.679	0.476	-0.04	0.695	0.498	21.8	21.8	
900 GSM	2:8 Duty Cycle	975 / 880	30.9	0.453	0.311	0.01	0.474	0.326	22.4	22.1	
		38 / 897	31.9	0.415	0.284	-0.03	0.435	0.297	22.4	22.1	
		124 / 914	32.1	0.409	0.281	0.07	0.428	0.294	22.4	22.1	
	Bluetooth On	975 / 880	30.9	0.454	0.310	0.03	0.475	0.325	23.8	22.7	
	1:8 Duty Cycle	975 / 880	31.4	0.236	0.163	-0.04	0.247	0.163	23.8	22.7	
1800 GSM	2:8 Duty Cycle	512 / 1710	30.5	0.215	0.137	-0.10	0.215	0.137	22.2	21.0	
		699 / 1748	30.4	0.216	0.137	-0.13	0.216	0.137	22.2	21.0	
		885 / 1785	30.4	0.285	0.178	0.08	0.285	0.178	22.2	21.0	
	Bluetooth On	885 / 1785	30.4	0.293	0.180	-0.03	0.293	0.180	22.5	21.1	
	1:8 Duty Cycle	885 / 1785	30.4	0.143	0.088	0.07	0.143	0.088	22.5	21.1	
1900 GSM	2:8 Duty Cycle	512 / 1850	30.4	0.331	0.206	-0.05	0.339	0.211	22.6	22.2	
		660/1880	30.3	0.360	0.216	0.04	0.368	0.221	22.6	22.2	
		810/1910	30.3	0.357	0.213	-0.09	0.365	0.218	22.6	22.2	
<b>Front of phone facing body</b>											
800 GSM	2:8 Duty Cycle	128 / 824	32.0	0.466	0.333	0.06	0.488	0.349	21.6	21.9	
		189 / 837	31.4	0.399	0.283	-0.13	0.418	0.296	21.6	21.9	
		251 / 849	31.3	0.287	0.204	-0.03	0.301	0.214	21.6	21.9	
900 GSM	2:8 Duty Cycle	975 / 880	30.9	0.148	0.105	0.02	0.155	0.110	23.3	22.3	
		38 / 897	31.9	0.133	0.095	0.09	0.139	0.099	23.3	22.3	
		124 / 914	32.1	0.138	0.098	0.05	0.145	0.103	23.3	22.3	
1800 GSM	2:8 Duty Cycle	512 / 1710	30.5	0.202	0.129	-0.10	0.202	0.129	22.3	20.4	
		699 / 1748	30.4	0.213	0.135	-0.07	0.213	0.135	22.3	20.4	
		885 / 1785	30.4	0.280	0.173	-0.19	0.280	0.173	22.3	20.4	
1900 GSM	2:8 Duty Cycle	512 / 1850	30.4	0.326	0.204	-0.13	0.334	0.209	22.5	22.5	
		660/1880	30.3	0.328	0.203	-0.04	0.336	0.208	22.5	22.5	
		810/1910	30.3	0.386	0.237	-0.14	0.395	0.243	22.5	22.5	
	Bluetooth On	810/1910	30.3	0.359	0.217	-0.10	0.367	0.222	23.1	22.9	
	1:8 Duty Cycle	810/1910	30.3	0.177	0.109	-0.02	0.181	0.112	23.1	22.9	

**Table 4: SAR measurement results for the portable cellular telephone FCC ID PY7AC052014 model Z525A at maximum output power with Standard Battery BST-37. Measured against the body with carry accessory 20MM Spacer.**



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**References**

- [1] FCC, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields: Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions," Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01).
- [2] IEEE, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques," Std 1528-200X, Draft 6.5 – August 20, 2001.



Prepared (also subject responsible if other)		No.	
SEM/CV/PF/P Gerard Hayes and Rodney Dixon		REP 2006 001 Z525A 01	
Approved	Checked		
SEM/CV/PF/P Gerard Hayes		A	X:\SAR Chamber\FCC reports\Z525A\Final

### Appendix 1

### SAR distribution comparison for the system accuracy verification



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**835 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on August 26, 2005 (Using head tissue).**

**Validation\_835Head\_438\_1251\_26Aug05\_T01**

File Name: [Validation\\_835Head\\_438\\_1251\\_26Aug05\\_T01.da4](#)

Phantom: SAM with CRP (Low Band Head) Phantom section: Flat Section

Probe: ET3DV6 - SN1586ConvF(6.58, 6.58, 6.58) Duty Cycle: 1:1 Frequency: 835 MHz

Medium parameters used: f = 835 MHz; s = 0.913 mho/m;  $\epsilon_r = 41.9$ ;  $\rho = 1000 \text{ kg/m}^3$

Measurement Standard: DASy4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):**

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.08 mW/g

**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 36.0 V/m; Power Drift = -0.013 dB

Peak SAR (extrapolated) = 1.67 W/kg

**SAR(1 g) = 1.02 mW/g; SAR(10 g) = 0.629 mW/g**

Maximum value of SAR (measured) = 1.11 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 36.0 V/m; Power Drift = -0.013 dB


Peak SAR (extrapolated) = 1.61 W/kg

**SAR(1 g) = 0.995 mW/g; SAR(10 g) = 0.614 mW/g**

Maximum value of SAR (measured) = 1.06 mW/g

Procedure Notes: Pin: before 99.7mW / after 99.8mW

Humidity: 40.7% Ambient Temp: 23.7 C Simulant Temp: 22.6 C



0 dB = 1.06mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**835 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on August 28, 2005 (Using head tissue).  
Validation\_835Head\_438\_1251\_28Aug05\_T01**

File Name: [Validation\\_835Head\\_438\\_1251\\_28Aug05\\_T01.da4](#)

Phantom: SAM with CRP (Low Band Head) Phantom section: Flat Section  
 Probe: ET3DV6 - SN1586ConvF(6.58, 6.58, 6.58) Duty Cycle: 1:1 Frequency: 835 MHz  
 Medium parameters used: f = 835 MHz; s = 0.877 mho/m;  $\epsilon_r = 40.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Measurement Standard: DASy4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):**  
 Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 0.951 mW/g


**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:**  
 Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 34.0 V/m; Power Drift = -0.01 dB  
 Peak SAR (extrapolated) = 1.32 W/kg

**SAR(1 g) = 0.889 mW/g; SAR(10 g) = 0.579 mW/g**  
 Maximum value of SAR (measured) = 0.955 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:**  
 Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 34.0 V/m; Power Drift = -0.01 dB  
 Peak SAR (extrapolated) = 1.31 W/kg

**SAR(1 g) = 0.874 mW/g; SAR(10 g) = 0.571 mW/g**  
 Maximum value of SAR (measured) = 0.936 mW/g

Procedure Notes: Pin: before 101.4mW / after 101.2mW  
 Humidity: 43.5% Ambient Temp: 22.6 C Simulant Temp: 22.2 C



0 dB = 0.936mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**835 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on February 14, 2005 (Using head tissue).**

**Validation\_835Head\_429\_1251\_14Feb06\_T01**

File Name: [Validation\\_835Head\\_429\\_1251\\_14Feb06\\_T01.da4](#)

Phantom: SAM with CRP (Low Band Head) Phantom section: Flat Section  
 Probe: ET3DV6 - SN1586ConvF(6.58, 6.58, 6.58) Duty Cycle: 1:1 Frequency: 835 MHz  
 Medium parameters used: f = 835 MHz; s = 0.898 mho/m;  $\epsilon_r = 41.6$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Measurement Standard: DASy4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 0.954 mW/g


**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 33.6 V/m; Power Drift = 0.039 dB  
 Peak SAR (extrapolated) = 1.34 W/kg

**SAR(1 g) = 0.896 mW/g; SAR(10 g) = 0.585 mW/g**  
 Maximum value of SAR (measured) = 0.973 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 33.6 V/m; Power Drift = 0.039 dB  
 Peak SAR (extrapolated) = 1.36 W/kg

**SAR(1 g) = 0.907 mW/g; SAR(10 g) = 0.589 mW/g**  
 Maximum value of SAR (measured) = 0.979 mW/g

Procedure Notes: Pin: before 100.2 mW / after 100.1 mW Humidity: 30.9% Ambient Temp: 23.3 C Simulant Temp: 22.5 C




0 dB = 0.979mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final

**835 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on August 27, 2005 (Using body tissue).**





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**835 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on January 29, 2006 PTT (Using head tissue).**

**Validation\_835Head\_429\_1251\_29Jan06\_T01**

File Name: [Validation\\_835Head\\_429\\_1251\\_29Jan06\\_T01.da4](#)

Phantom: SAM with CRP (Low Band Head)Phantom section: Flat Section  
 Probe: ET3DV6 - SN1586ConvF(6.58, 6.58, 6.58)Duty Cycle: 1:1Frequency: 835 MHz  
 Medium parameters used: f = 835 MHz; s = 0.898 mho/m;  $\epsilon_r = 41.4$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Measurement Standard: DASy4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):**

Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 0.949 mW/g

**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 33.4 V/m; Power Drift = 0.011 dB  
 Peak SAR (extrapolated) = 1.33 W/kg

**SAR(1 g) = 0.893 mW/g; SAR(10 g) = 0.583 mW/g**

Maximum value of SAR (measured) = 0.966 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 33.4 V/m; Power Drift = 0.011 dB  
 Peak SAR (extrapolated) = 1.32 W/kg

**SAR(1 g) = 0.882 mW/g; SAR(10 g) = 0.574 mW/g**

Maximum value of SAR (measured) = 0.953 mW/g

Procedure Notes: Pin: before 100.6 mW / after 100.8 mW

Humidity: 30.2% Ambient Temp: 24.2 C Simulant Temp: 24.2 C





REPORT

22(175)

Prepared (also subject responsible if other)		No.	
SEM/CV/PF/P Gerard Hayes and Rodney Dixon		REP 2006 001 Z525A 01	
Approved	Checked		
SEM/CV/PF/P Gerard Hayes		A	X:\SAR Chamber\FCC reports\Z525A\Final

0 dB = 0.953mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

900 MHz SAR Distribution of Validation Dipole Antenna  
**System Performance Check on August 24, 2005 (Using head tissue).**

**Validation\_900Head\_035\_1251\_24Aug05\_T01**

File Name: [Validation\\_900Head\\_035\\_1251\\_24Aug05\\_T01.da4](#)

Phantom: SAM with CRP (Low Band Head) Phantom section: Flat Section  
 Probe: ET3DV6 - SN1586ConvF(6.46, 6.46, 6.46) Duty Cycle: 1:1 Frequency: 900 MHz  
 Medium parameters used: f = 900 MHz; s = 0.974 mho/m;  $\epsilon_r = 41.6$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Measurement Standard: DASy4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):**

Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 1.09 mW/g

**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 34.5 V/m; Power Drift = -0.00 dB  
 Peak SAR (extrapolated) = 1.52 W/kg

**SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.647 mW/g**

Maximum value of SAR (measured) = 1.09 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 34.5 V/m; Power Drift = -0.00 dB  
 Peak SAR (extrapolated) = 1.50 W/kg

**SAR(1 g) = 0.980 mW/g; SAR(10 g) = 0.628 mW/g**

Maximum value of SAR (measured) = 1.07 mW/g

Procedure Notes: Pin: before - 100.7 mW after - 100.4 mW

Humidity: 43.7 % Ambient Temp: 22.8 C Simulant Temp: 23 C



0 dB = 1.07mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**900 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on August 25, 2005 (Using body tissue).**

**Validation\_900Body\_035\_1251\_25Aug05\_T01**

File Name: [Validation\\_900Body\\_035\\_1251\\_25Aug05\\_T01.da4](#)

Phantom: SAM with CRP (Low Band Head) Phantom section: Flat Section  
 Probe: ET3DV6 - SN1586ConvF(6.46, 6.46, 6.46) Duty Cycle: 1:1 Frequency: 900 MHz  
 Medium parameters used: f = 900 MHz; s = 0.938 mho/m;  $\epsilon_r = 39.9$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Measurement Standard: DASy4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):**

Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 1.06 mW/g

**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 34.4 V/m; Power Drift = 0.056 dB  
 Peak SAR (extrapolated) = 1.50 W/kg

**SAR(1 g) = 0.992 mW/g; SAR(10 g) = 0.635 mW/g**

Maximum value of SAR (measured) = 1.08 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 34.4 V/m; Power Drift = 0.056 dB  
 Peak SAR (extrapolated) = 1.48 W/kg

**SAR(1 g) = 0.983 mW/g; SAR(10 g) = 0.630 mW/g**

Maximum value of SAR (measured) = 1.06 mW/g

Procedure Notes: Pin: before - 100.5 mW after - 100.6mW

Humidity: 44.8 % Ambient Temp: 22.4 C Simulant Temp: 22.1 C



0 dB = 1.06mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**900 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on February 01, 2006 PTT (Using head tissue).  
Validation\_900Head\_049\_1251\_01Feb06\_T01**

File Name: [Validation\\_900Head\\_049\\_1251\\_01Feb06\\_T01.da4](#)

Phantom: SAM with CRP (Low Band Head) Phantom section: Flat Section  
 Probe: ET3DV6 - SN1586ConvF(6.46, 6.46, 6.46) Duty Cycle: 1:1 Frequency: 900 MHz  
 Medium parameters used: f = 900 MHz; s = 0.953 mho/m;  $\epsilon_r = 40.2$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Measurement Standard: DAS4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):**

Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 1.08 mW/g

**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 34.9 V/m; Power Drift = 0.018 dB  
 Peak SAR (extrapolated) = 1.53 W/kg

**SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.649 mW/g**

Maximum value of SAR (measured) = 1.10 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:**


Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 34.9 V/m; Power Drift = 0.018 dB  
 Peak SAR (extrapolated) = 1.51 W/kg

**SAR(1 g) = 0.995 mW/g; SAR(10 g) = 0.636 mW/g**

Maximum value of SAR (measured) = 1.08 mW/g

Procedure Notes: Pin: before - 99.6 mW after - 100.2 mW

Humidity: 30.4 % Ambient Temp: 24.6 C Simulant Temp: 24.5 C





REPORT

26(175)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final

0 dB = 1.08mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**1800 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on August 27, 2005 (Using head tissue).**

**Validation\_1800Head\_238\_1335\_27Aug05\_T01**

File Name: [Validation\\_1800Head\\_238\\_1335\\_27Aug05\\_T01.da4](#)

Phantom: SAM with CRP (High Band Head) Phantom section: Flat Section

Probe: ET3DV6 - SN1587ConvF(5.45, 5.45, 5.45) Duty Cycle: 1:1 Frequency: 1800 MHz

Medium parameters used: f = 1800 MHz; s = 1.4 mho/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000 \text{ kg/m}^3$

Measurement Standard: DAS Y4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):**

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 4.53 mW/g

**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.0 V/m; Power Drift = 0.013 dB

Peak SAR (extrapolated) = 6.18 W/kg

**SAR(1 g) = 3.63 mW/g; SAR(10 g) = 1.96 mW/g**

Maximum value of SAR (measured) = 4.10 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.0 V/m; Power Drift = 0.013 dB


Peak SAR (extrapolated) = 6.19 W/kg

**SAR(1 g) = 3.64 mW/g; SAR(10 g) = 1.96 mW/g**

Maximum value of SAR (measured) = 4.13 mW/g

Procedure Notes: Pin: before 100.1 mW / after 100.2 mW

Humidity: 43.5 % Ambient Temp: 22.2 C Simulant Temp: 22 C



0 dB = 4.13mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**1800 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on August 26, 2005 (Using body tissue).**

**Validation\_1800Body\_238\_1335\_26Aug05\_T01**

File Name: [Validation\\_1800Body\\_238\\_1335\\_26Aug05\\_T01.da4](#)

Phantom: SAM with CRP (High Band Head)Phantom section: Flat Section

Probe: ET3DV6 - SN1587ConvF(5.45, 5.45, 5.45)Duty Cycle: 1:1Frequency: 1800 MHz

Medium parameters used: f = 1800 MHz; s = 1.38 mho/m;  $\epsilon_r = 39.1$ ;  $\rho = 1000 \text{ kg/m}^3$

Measurement Standard: DASy4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):**

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 4.64 mW/g

**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 55.7 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 6.16 W/kg

**SAR(1 g) = 3.56 mW/g; SAR(10 g) = 1.91 mW/g**

Maximum value of SAR (measured) = 4.05 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 55.7 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 6.11 W/kg

**SAR(1 g) = 3.55 mW/g; SAR(10 g) = 1.9 mW/g**

Procedure Notes: Pin: before 100.6 mW / after 101.2 mW

Humidity: 51.5 % Ambient Temp: 22.2 C Simulant Temp: 21 C





REPORT

29(175)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**1800 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on January 31, 2006 PTT (Using head tissue).  
Validation\_1800Head\_217\_1335\_31Jan06\_T01**

File Name: [Validation\\_1800Head\\_217\\_1335\\_31Jan06\\_T01.da4](#)

Phantom: SAM with CRP (High Band Head) Phantom section: Flat Section  
 Probe: ET3DV6 - SN1539 ConvF(4.76, 4.76, 4.76) Duty Cycle: 1:1 Frequency: 1800 MHz  
 Medium parameters used: f = 1800 MHz; s = 1.38 mho/m;  $\epsilon_r = 38.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Measurement Standard: DAS Y4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):**

Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (interpolated) = 4.55 mW/g

**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 58.1 V/m; Power Drift = -0.009 dB  
 Peak SAR (extrapolated) = 6.47 W/kg

**SAR(1 g) = 3.69 mW/g; SAR(10 g) = 1.97 mW/g**

Maximum value of SAR (measured) = 4.11 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm  
 Reference Value = 58.1 V/m; Power Drift = -0.009 dB  
 Peak SAR (extrapolated) = 6.29 W/kg

**SAR(1 g) = 3.58 mW/g; SAR(10 g) = 1.91 mW/g**

Maximum value of SAR (measured) = 4.00 mW/g

Procedure Notes: Pin: before 100.0 mW / after 100.1 mW

Humidity: 31.4% Ambient Temp: 24.6 C Simulant Temp: 21.7 C




Exhibit 11



REPORT

31(175)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final

0 dB = 4.00mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**1900 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on August 25, 2005 (Using head tissue).**

**Validation\_1900Head\_536\_1335\_25Aug05\_T01**

File Name: [Validation\\_1900Head\\_536\\_1335\\_25Aug05\\_T01.da4](#)

Phantom: SAM with CRP (High Band Head) Phantom section: Flat Section

Probe: ET3DV6 - SN1587 ConvF(5.05, 5.05, 5.05) Duty Cycle: 1:1 Frequency: 1900 MHz

Medium parameters used: f = 1900 MHz; s = 1.47 mho/m;  $\epsilon_r = 38.3$ ;  $\rho = 1000 \text{ kg/m}^3$

Measurement Standard: DASy4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):**

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 5.19 mW/g

**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 58.8 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 7.10 W/kg

**SAR(1 g) = 4.04 mW/g; SAR(10 g) = 2.12 mW/g**

Maximum value of SAR (measured) = 4.51 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 58.8 V/m; Power Drift = 0.01 dB


Peak SAR (extrapolated) = 7.18 W/kg

**SAR(1 g) = 4.07 mW/g; SAR(10 g) = 2.12 mW/g**

Maximum value of SAR (measured) = 4.58 mW/g

Procedure Notes: Pin: before 100.4 mW / after 100.9 mW

Humidity: 49.5% Ambient Temp: 22.2 C Simulant Temp: 22 C



0 dB = 4.58mW/g



REPORT

33(175)

Prepared (also subject responsible if other)	No.	
SEM/CV/PF/P Gerard Hayes and Rodney Dixon	REP 2006 001 Z525A 01	
Approved	Checked	
SEM/CV/PF/P Gerard Hayes	A	X:\SAR Chamber\FCC reports\Z525A\Final



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**1900 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on February 14, 2006 (Using head tissue).  
Validation\_1900Head\_537\_1335\_14Feb06\_T01**

File Name: [Validation\\_1900Head\\_537\\_1335\\_14Feb06\\_T01.da4](#)

Phantom: SAM with CRP (High Band Head) Phantom section: Flat Section  
 Probe: ET3DV6 - SN1539ConvF(4.55, 4.55, 4.55) Duty Cycle: 1:1 Frequency: 1900 MHz  
 Medium parameters used: f = 1900 MHz; s = 1.47 mho/m;  $\epsilon_r = 38.8$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Measurement Standard: DAS4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 5.21 mW/g

**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 59.9 V/m; Power Drift = 0.019 dB

Peak SAR (extrapolated) = 7.36 W/kg

**SAR(1 g) = 4.18 mW/g; SAR(10 g) = 2.17 mW/g**

Maximum value of SAR (measured) = 4.69 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 59.9 V/m; Power Drift = 0.019 dB

Peak SAR (extrapolated) = 7.10 W/kg

**SAR(1 g) = 4.03 mW/g; SAR(10 g) = 2.1 mW/g**

Maximum value of SAR (measured) = 4.54 mW/g

Procedure Notes: Pin: before 100.1 mW / after 99.9 mW Humidity: 30.3% Ambient Temp: 22.9 C Simulant Temp: 23.2 C




0 dB = 4.54mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**1900 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on August 24, 2005 (Using body tissue).**





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**1900 MHz SAR Distribution of Validation Dipole Antenna  
System Performance Check on January 29, 2006 PTT (Using head tissue).  
Validation\_1900Head\_537\_1335\_29Jan06\_T01**

File Name: [Validation\\_1900Head\\_537\\_1335\\_29Jan06\\_T01.da4](#)

Phantom: SAM with CRP (High Band Head) Phantom section: Flat Section  
 Probe: ET3DV6 - SN1539ConvF(4.55, 4.55, 4.55) Duty Cycle: 1:1 Frequency: 1900 MHz  
 Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $s = 1.47 \text{ mho/m}$ ;  $\epsilon_r = 38.7$ ;  $\rho = 1000 \text{ kg/m}^3$   
 Measurement Standard: DASy4 (High Precision Assessment)

**Dipole at 10 mm/Area Scan (61x61x1):**

Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$   
 Maximum value of SAR (interpolated) = 5.16 mW/g

**Dipole at 10 mm/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 59.7 V/m; Power Drift = 0.047 dB  
 Peak SAR (extrapolated) = 7.14 W/kg

**SAR(1 g) = 4.1 mW/g; SAR(10 g) = 2.14 mW/g**

Maximum value of SAR (measured) = 4.65 mW/g

**Dipole at 10 mm/Zoom Scan 2 (7x7x7)/Cube 0:**


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$   
 Reference Value = 59.7 V/m; Power Drift = 0.047 dB  
 Peak SAR (extrapolated) = 6.95 W/kg

**SAR(1 g) = 3.99 mW/g; SAR(10 g) = 2.1 mW/g**

Maximum value of SAR (measured) = 4.43 mW/g

Procedure Notes: Pin: before 100.2 mW / after 100.4 mW

Humidity: 30.2% Ambient Temp: 24.2 C Simulant Temp: 24.2 C





Prepared (also subject responsible if other)		No.	
SEM/CV/PF/P Gerard Hayes and Rodney Dixon		REP 2006 001 Z525A 01	
Approved	Checked		
SEM/CV/PF/P Gerard Hayes		A	X:\SAR Chamber\FCC reports\Z525A\Final

0 dB = 4.43mW/g

## Appendix 2

### SAR distribution plots for Phantom Head Adjacent Use



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final

**800 GSM Band: SAR Distribution and Extrapolation of Maximum SAR  
Model: Z525A SN: BD30246HHE with Standard Battery: BST-37  
Right Side, Cheek/Touch Position.**

Date/Time: 8/28/2005 10:05:49 AM Date/Time: 8/28/2005 10:11:41 AM

File Name: [28Aug05\\_Z525A\\_GSM850\\_6HHE\\_RC01.da4](#)

**DUT: Z525A**

Program Notes: Battery BST-37 Humidity: 43.5% Ambient Temp: 22.6 Simulant Temp: 22.2

Communication System: GSM 850; Frequency: 824 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 824 MHz; s = 0.866 mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.58, 6.58, 6.58); Calibrated: 5/26/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn417; Calibrated: 11/11/2004
- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

**Unnamed procedure/Area Scan (51x81x1):**

Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (interpolated) = 1.54 mW/g

**Unnamed procedure/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.5 V/m; Power Drift = -0.060 dB

Peak SAR (extrapolated) = 2.23 W/kg

**SAR(1 g) = 1.41 mW/g; SAR(10 g) = 0.914 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (measured) = 1.54 mW/g

**Unnamed procedure/Zoom Scan (31x31x36)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 12.5 V/m; Power Drift = -0.060 dB

[Info: Interpolated medium parameters used for SAR evaluation!](#)


Maximum value of SAR (interpolated) = 2.23 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 2.23mW/g





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**800 GSM Band: Distribution and Extrapolation of Maximum SAR  
Model: Z525A SN: BD30246HHE with Standard Battery: BST-37  
Right Side, Tilt Position.**

Date/Time: 8/28/2005 11:48:23 AM Date/Time: 8/28/2005 11:53:57 AM

File Name: [28Aug05\\_Z525A\\_GSM850\\_6HHE\\_RT01.da4](#)

**DUT: Z525A**

Program Notes: Battery BST-37 Humidity: 49.7% Ambient Temp: 23 Simulant Temp: 23.9

Communication System: GSM 850; Frequency: 824 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 824 MHz; s = 0.866 mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.58, 6.58, 6.58); Calibrated: 5/26/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn417; Calibrated: 11/11/2004
- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

**Unnamed procedure/Area Scan (51x81x1):**

Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (interpolated) = 0.357 mW/g

**Unnamed procedure/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.6 V/m; Power Drift = -0.067 dB

Peak SAR (extrapolated) = 0.431 W/kg

**SAR(1 g) = 0.335 mW/g; SAR(10 g) = 0.247 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (measured) = 0.353 mW/g

**Unnamed procedure/Zoom Scan (31x31x36)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 12.6 V/m; Power Drift = -0.067 dB

[Info: Interpolated medium parameters used for SAR evaluation!](#)


Maximum value of SAR (interpolated) = 0.431 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 0.431mW/g





**Sony Ericsson**

REPORT

42(175)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**800 GSM Band: Distribution and Extrapolation of Maximum SAR  
Model: Z525A SN: BD30246HHE with Standard Battery: BST-37  
Left Side, Cheek/Touch Position.**

Date/Time: 8/26/2005 12:05:32 PM Date/Time: 8/26/2005 12:11:29 PM

File Name: [26Aug05\\_Z525A\\_GSM850\\_6HHE\\_LC01.da4](#)

**DUT: Z525A**

Program Notes: Battery BST-37 Humidity: 40.7% Ambient Temp: 23.7 Simulant Temp: 22.6

Communication System: GSM 850; Frequency: 824 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 824 MHz; s = 0.903 mho/m;  $\epsilon_r = 42$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.58, 6.58, 6.58); Calibrated: 5/26/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn417; Calibrated: 11/11/2004
- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

**Unnamed procedure/Area Scan (51x81x1):**

Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (interpolated) = 1.49 mW/g

**Unnamed procedure/Zoom Scan (9x9x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = -0.133 dB

Peak SAR (extrapolated) = 2.07 W/kg

**SAR(1 g) = 1.44 mW/g; SAR(10 g) = 0.916 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (measured) = 1.49 mW/g

**Unnamed procedure/Zoom Scan (41x41x36)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 11.6 V/m; Power Drift = -0.133 dB

[Info: Interpolated medium parameters used for SAR evaluation!](#)


Maximum value of SAR (interpolated) = 2.07 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 2.07mW/g





REPORT

45(175)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**800 GSM Band: Distribution and Extrapolation of Maximum SAR  
Model: Z525A SN: BD30246HHE with Standard Battery: BST-37  
Left Side, Tilt Position.**

Date/Time: 8/26/2005 3:00:27 PM Date/Time: 8/26/2005 3:06:02 PM

File Name: [26Aug05\\_Z525A\\_GSM850\\_6HHE\\_LT01.da4](#)

**DUT: Z525A**

Program Notes: Battery BST-37 Humidity: 39.4% Ambient Temp: 24 Simulant Temp: 23.2

Communication System: GSM 850; Frequency: 824 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 824 MHz; s = 0.903 mho/m;  $\epsilon_r = 42$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.58, 6.58, 6.58); Calibrated: 5/26/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn417; Calibrated: 11/11/2004
- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

**Unnamed procedure/Area Scan (51x81x1):**

Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (interpolated) = 0.387 mW/g

**Unnamed procedure/Zoom Scan (9x9x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.8 V/m; Power Drift = -0.140 dB

Peak SAR (extrapolated) = 0.463 W/kg

**SAR(1 g) = 0.361 mW/g; SAR(10 g) = 0.264 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (measured) = 0.372 mW/g

**Unnamed procedure/Zoom Scan (41x41x36)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 12.8 V/m; Power Drift = -0.140 dB

[Info: Interpolated medium parameters used for SAR evaluation!](#)


Maximum value of SAR (interpolated) = 0.463 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 0.463mW/g





REPORT

48(175)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**800 GSM Band: Distribution and Extrapolation of Maximum SAR**

**Model: Z525A SN: BD30246HHE with Standard Battery: BST-37**

**Left Side, Cheek/Touch Position with Blue Tooth.**

Date/Time: 8/28/2005 4:55:11 PM Date/Time: 8/28/2005 5:00:45 PM

File Name: [28Aug05\\_Z525A\\_GSM850\\_6HHE\\_BT\\_LC01.da4](#)

**DUT: Z525A**

Program Notes: Battery BST-37 Humidity: 49.6% Ambient Temp: 22.5 Simulant Temp: 23.1

Communication System: GSM 850; Frequency: 824 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 824 MHz; s = 0.866 mho/m;  $\epsilon_r = 40.3$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.58, 6.58, 6.58); Calibrated: 5/26/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn417; Calibrated: 11/11/2004
- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

**Unnamed procedure/Area Scan (51x81x1):**

Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (interpolated) = 1.53 mW/g

**Unnamed procedure/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.92 V/m; Power Drift = -0.106 dB

Peak SAR (extrapolated) = 2.14 W/kg

**SAR(1 g) = 1.44 mW/g; SAR(10 g) = 0.915 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (measured) = 1.53 mW/g

**Unnamed procedure/Zoom Scan (31x31x36)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 9.92 V/m; Power Drift = -0.106 dB

[Info: Interpolated medium parameters used for SAR evaluation!](#)


Maximum value of SAR (interpolated) = 2.14 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 2.14mW/g





REPORT

51(175)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**800 GSM Band: SAR Distribution and Extrapolation of Maximum SAR**

**Model: Z525A SN: BD3ZZYJGGQ with Standard Battery: BST-37**

PTT, 25mm Separation, Flat section, Open Position.

File Name: [14Feb06\\_Z525A\\_GSM850\\_JGGQ\\_open\\_PTT01.da4](#)

**DUT: Z525A**

Program Notes: Battery BST-37 Humidity: 30.5% Ambient Temp: 23.5 C Simulant Temp: 22.4 C

Communication System: GSM 850; Frequency: 824 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 824 MHz; s = 0.888 mho/m;  $\epsilon_r = 41.8$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.58, 6.58, 6.58); Calibrated: 5/26/2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn416; Calibrated: 11/10/2005

- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251

- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

**Unnamed procedure/Area Scan (61x121x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.536 mW/g

**Unnamed procedure/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.5 V/m; Power Drift = -0.021 dB

Peak SAR (extrapolated) = 0.670 W/kg

**SAR(1 g) = 0.500 mW/g; SAR(10 g) = 0.354 mW/g**

Maximum value of SAR (measured) = 0.529 mW/g


**Unnamed procedure/Zoom Scan (31x31x36)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.5 V/m; Power Drift = -0.021 dB


Maximum value of SAR (interpolated) = 0.670 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 0.670mW/g





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**800 GSM Band: SAR Distribution and Extrapolation of Maximum SAR  
Model: Z525A SN: BD3ZZYJGGQ with Standard Battery: BST-37  
PTT, 25mm Separation, Flat section, Open Position with Bluetooth on.**

File Name: [14Feb06\\_Z525A\\_GSM850\\_JGGQ\\_open\\_BT\\_PTT01.da4](#)

**DUT: Z525A**

Program Notes: Battery BST-37 Humidity: 30.5% Ambient Temp: 23.5 C Simulant Temp: 22.4 C

Communication System: GSM 850; Frequency: 824 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 824 MHz; s = 0.888 mho/m;  $\epsilon_r = 41.8$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.58, 6.58, 6.58); Calibrated: 5/26/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn416; Calibrated: 11/10/2005
- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

**Unnamed procedure/Area Scan (71x121x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.560 mW/g

**Unnamed procedure/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.5 V/m; Power Drift = -0.023 dB

Peak SAR (extrapolated) = 0.703 W/kg

**SAR(1 g) = 0.523 mW/g; SAR(10 g) = 0.370 mW/g**

Maximum value of SAR (measured) = 0.555 mW/g


**Unnamed procedure/Zoom Scan (31x31x36)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.5 V/m; Power Drift = -0.023 dB


Maximum value of SAR (interpolated) = 0.703 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 0.703mW/g





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**800 GSM Band: SAR Distribution and Extrapolation of Maximum SAR**

**Model: Z525A SN: BD3ZZYJGGQ with Standard Battery: BST-37**

**PTT, 25mm Separation, Flat section, Closed Position.**

File Name: [14Feb06\\_Z525A\\_GSM850\\_JGGQ\\_closed\\_PTT01.da4](#)

**DUT: Z525A**

Program Notes: Battery BST-37 Humidity: 30.9% Ambient Temp: 23.3 C Simulant Temp: 22.5 C

Communication System: GSM 850; Frequency: 824 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 824 MHz; s = 0.888 mho/m;  $\epsilon_r = 41.8$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.58, 6.58, 6.58); Calibrated: 5/26/2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn416; Calibrated: 11/10/2005

- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251

- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

**Unnamed procedure/Area Scan (61x121x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.203 mW/g

**Unnamed procedure/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.0 V/m; Power Drift = 0.046 dB

Peak SAR (extrapolated) = 0.249 W/kg

**SAR(1 g) = 0.191 mW/g; SAR(10 g) = 0.138 mW/g**

Maximum value of SAR (measured) = 0.201 mW/g


**Unnamed procedure/Zoom Scan (31x31x36)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.0 V/m; Power Drift = 0.046 dB


Maximum value of SAR (interpolated) = 0.249 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 0.249mW/g





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**800 GSM Band: SAR Distribution and Extrapolation of Maximum SAR  
Model: Z525A SN: BD3ZZYJGGQ with Standard Battery: BST-37  
PTT, 25mm Separation, Flat section, Closed Position with Blue Tooth on.**

File Name: [14Feb06 Z525A GSM850 JGGQ closed BT PTT01.da4](#)

**DUT: Z525A**

Program Notes: Battery BST-37 Humidity: 30.9% Ambient Temp: 23.3 C Simulant Temp: 22.5 C

Communication System: GSM 850; Frequency: 824 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 824 MHz; s = 0.888 mho/m;  $\epsilon_r = 41.8$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.58, 6.58, 6.58); Calibrated: 5/26/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn416; Calibrated: 11/10/2005
- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

**Unnamed procedure/Area Scan (61x121x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.204 mW/g

**Unnamed procedure/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.5 V/m; Power Drift = -0.039 dB

Peak SAR (extrapolated) = 0.246 W/kg

**SAR(1 g) = 0.190 mW/g; SAR(10 g) = 0.138 mW/g**

Maximum value of SAR (measured) = 0.201 mW/g


**Unnamed procedure/Zoom Scan (31x31x36)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.5 V/m; Power Drift = -0.039 dB


Maximum value of SAR (interpolated) = 0.246 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 0.246mW/g





REPORT

60(175)

Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon	No. REP 2006 001 Z525A 01
Approved SEM/CV/PF/P Gerard Hayes	Checked A X:\SAR Chamber\FCC reports\Z525A\Final

**900 GSM Band: SAR Distribution and Extrapolation of Maximum SAR  
Model: Z525A SN: BD302466Q7 with Standard Battery: BST-37  
Right Side, Cheek/Touch Position.**

Date/Time: 8/24/2005 1:18:22 PM Date/Time: 8/24/2005 1:24:52 PM

File Name: [24Aug05\\_Z525A\\_GSM900\\_66Q7\\_RC01.da4](#)

**DUT: Z525A**

Program Notes: Battery: BST-37 Humidity: 50.4% Ambient Temp: 22.2 Simulant Temp: 22.6

Communication System: GSM 900; Frequency: 890.2 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 890.2 MHz; s = 0.962 mho/m;  $\epsilon_r = 41.6$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.46, 6.46, 6.46); Calibrated: 5/26/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn417; Calibrated: 11/11/2004
- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

**Unnamed procedure/Area Scan (61x81x1):**

Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (interpolated) = 0.568 mW/g

**Unnamed procedure/Zoom Scan (7x9x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.65 V/m; Power Drift = 0.019 dB

Peak SAR (extrapolated) = 0.891 W/kg

**SAR(1 g) = 0.540 mW/g; SAR(10 g) = 0.338 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (measured) = 0.575 mW/g

**Unnamed procedure/Zoom Scan (31x41x36)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 6.65 V/m; Power Drift = 0.019 dB

[Info: Interpolated medium parameters used for SAR evaluation!](#)


Maximum value of SAR (interpolated) = 0.891 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 0.891mW/g





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**900 GSM Band: Distribution and Extrapolation of Maximum SAR  
Model: Z525A SN: BD302466Q7 with Standard Battery: BST-37  
Right Side, Tilt Position.**

Date/Time: 8/24/2005 10:39:22 AM Date/Time: 8/24/2005 10:45:52 AM

File Name: [24Aug05\\_Z525A\\_GSM900\\_66Q7\\_RT01.da4](#)

**DUT: Z525A**

Program Notes: Battery: BST-37 Humidity: 49.2% Ambient Temp: 21.9 Simulant Temp: 22.3

Communication System: GSM 900; Frequency: 890.2 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 890.2 MHz; s = 0.962 mho/m;  $\epsilon_r = 41.6$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.46, 6.46, 6.46); Calibrated: 5/26/2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn417; Calibrated: 11/11/2004

- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

**Unnamed procedure/Area Scan (61x81x1):**

Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (interpolated) = 0.163 mW/g

**Unnamed procedure/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.93 V/m; Power Drift = 0.021 dB

Peak SAR (extrapolated) = 0.206 W/kg

**SAR(1 g) = 0.156 mW/g; SAR(10 g) = 0.113 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (measured) = 0.165 mW/g

**Unnamed procedure/Zoom Scan (31x31x36)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 7.93 V/m; Power Drift = 0.021 dB

[Info: Interpolated medium parameters used for SAR evaluation!](#)


Maximum value of SAR (interpolated) = 0.206 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 0.206mW/g





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**900 GSM Band: Distribution and Extrapolation of Maximum SAR  
Model: Z525A SN: BD302466Q7 with Standard Battery: BST-37  
Left Side, Cheek/Touch Position.**

Date/Time: 8/24/2005 8:19:16 AM Date/Time: 8/24/2005 8:24:51 AM

File Name: [24Aug05\\_Z525A\\_GSM900\\_66Q7\\_LC01.da4](#)

**DUT: Z525A**

Program Notes: Battery: BST-37 Humidity: 43.7 % Ambient Temp: 22.8 C Simulant Temp: 23

Communication System: GSM 900; Frequency: 890.2 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 890.2 MHz; s = 0.962 mho/m;  $\epsilon_r = 41.6$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.46, 6.46, 6.46); Calibrated: 5/26/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn417; Calibrated: 11/11/2004
- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

**Unnamed procedure/Area Scan (51x81x1):**

Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (interpolated) = 0.616 mW/g

**Unnamed procedure/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.90 V/m; Power Drift = -0.097 dB

Peak SAR (extrapolated) = 0.892 W/kg

**SAR(1 g) = 0.588 mW/g; SAR(10 g) = 0.362 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (measured) = 0.634 mW/g

**Unnamed procedure/Zoom Scan (31x31x36)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 6.90 V/m; Power Drift = -0.097 dB

[Info: Interpolated medium parameters used for SAR evaluation!](#)


Maximum value of SAR (interpolated) = 0.892 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 0.892mW/g





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**900 GSM Band: Distribution and Extrapolation of Maximum SAR  
Model: Z525A SN: BD302466Q7 with Standard Battery: BST-37  
Left Side, Tilt Position.**

Date/Time: 8/24/2005 10:16:28 AM Date/Time: 8/24/2005 10:22:05 AM

File Name: [24Aug05\\_Z525A\\_GSM900\\_66Q7\\_LT01.da4](#)

**DUT: Z525A**

Program Notes: Battery: BST-37 Humidity: 48.9 % Ambient Temp: 22.8 C Simulant Temp: 23.1

Communication System: GSM 900; Frequency: 890.2 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 890.2 MHz; s = 0.962 mho/m;  $\epsilon_r = 41.6$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.46, 6.46, 6.46); Calibrated: 5/26/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn417; Calibrated: 11/11/2004
- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

**Unnamed procedure/Area Scan (51x81x1):**

Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (interpolated) = 0.161 mW/g

**Unnamed procedure/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.76 V/m; Power Drift = -0.045 dB

Peak SAR (extrapolated) = 0.199 W/kg

**SAR(1 g) = 0.149 mW/g; SAR(10 g) = 0.108 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (measured) = 0.159 mW/g

**Unnamed procedure/Zoom Scan (31x31x36)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 6.76 V/m; Power Drift = -0.045 dB

[Info: Interpolated medium parameters used for SAR evaluation!](#)


Maximum value of SAR (interpolated) = 0.199 mW/g



Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final



0 dB = 0.199mW/g





Prepared (also subject responsible if other) SEM/CV/PF/P Gerard Hayes and Rodney Dixon		No. REP 2006 001 Z525A 01	
Approved SEM/CV/PF/P Gerard Hayes	Checked	A	X:\SAR Chamber\FCC reports\Z525A\Final

**900 GSM Band: Distribution and Extrapolation of Maximum SAR  
Model: Z525A SN: BD302466Q7 with Standard Battery: BST-37  
Left Side, Cheek/Touch Position with Blue Tooth.**

Date/Time: 8/24/2005 3:45:11 PM Date/Time: 8/24/2005 3:50:50 PM

File Name: [24Aug05\\_Z525A\\_GSM900\\_66Q7\\_BT\\_LC01.da4](#)

**DUT: Z525A**

Program Notes: Battery: BST-37 Humidity: 49.2% Ambient Temp: 21.9 Simulant Temp: 22.3

Communication System: GSM 900; Frequency: 890.2 MHz; Duty Cycle: 1:8.3

Medium: Head 835/900 MHz Medium parameters used (interpolated): f = 890.2 MHz; s = 0.962 mho/m;  $\epsilon_r = 41.6$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1586; ConvF(6.46, 6.46, 6.46); Calibrated: 5/26/2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn417; Calibrated: 11/11/2004
- Phantom: SAM with CRP (Low Band Head); Type: SAM; Serial: 1251
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

**Unnamed procedure/Area Scan (51x81x1):**

Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (interpolated) = 0.566 mW/g

**Unnamed procedure/Zoom Scan (7x7x7)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.35 V/m; Power Drift = -0.062 dB

Peak SAR (extrapolated) = 0.788 W/kg

**SAR(1 g) = 0.540 mW/g; SAR(10 g) = 0.334 mW/g**

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (measured) = 0.552 mW/g

**Unnamed procedure/Zoom Scan (31x31x36)/Cube 0:**

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.35 V/m; Power Drift = -0.062 dB

[Info: Interpolated medium parameters used for SAR evaluation!](#)

Maximum value of SAR (interpolated) = 0.788 mW/g