

Prepared (also subject responsible if other)
SEM/CGVIOA MARK 2 WANG
 Approved
 SoMC/CGOVIOA/Mark Wang

Checked

Company Internal
MARKING DRAWINGTECHNICAL
 No.
 27/0363-1/FCP 119 1293
 Date Rev Reference
 2012-08-13 1

JLO_LAM_0813_MoPLC_TA_1268-0029.1

1 General information

Mobile Phone label part no	<ul style="list-style-type: none"> 1264-2170
Bar code	<ul style="list-style-type: none"> Standard: according to Ericsson corporate standard 102 01–109 Uen Print quality: C, according to ANSI X3.182-1990 as stated in Ericsson corporate standard 102 01–1003 Uen Quiet zone: No bar codes are allowed to be closer to a label edge than 2 mm!
Text	If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.
Coordinates	“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

2 Printing information

	Content	Format
Line 1a (7,0/25,5)	SIM card logo	Graphics height 5,0 mm, rotated 180 degree clock-wise. According to 1210-0475.
Line 1b (7,0/39,0)	Micro SD card logo	Graphics height 5,2 mm. According to 1247-1508.
Line 2a (10,0/4,0)	SONY stylized name.	Graphics, height 2,0 mm. According to 1263-9535.
Line 2b (10,0/28,0)	Model name, “ST26a”	Text, height 1,5 mm.
Line 3a (13,0/4,0)	Type number of the phone, “TYPE: PM-0170-BV”.	Text, height 1,5 mm.
Line 3b (13,0/28,0)	HW & SW identification field, if applicable; “EFF”	Text, height 1,5 mm. <i>According to Type-testing report under Product Model Specifying Document</i>
Line 4a (16,0/4,0)	“FCC ID: PY7PM-0170”	Text, height 1,5 mm.
Line 4b (16,0/28,0)	Location code of where the phone is flashed, if applicable, “XXX”	Text, height 1,5 mm.
Line 5 (19,0/4,0)	“IC: 4170B-PM0170”	Text, height 1,2 mm.
Line 6a (22,0/4,0)	Product number without revision of the Sales Item in which the phone is packed, if applicable. “SI XXXX-XXXX”	Text, height 1,5 mm.
Line 6b (22,0/28,0)	Production week (flash), “yy’W’ww” (yy = year, ww = week)	Text, height 1,5 mm.
Line 7 (25,0/4,0)	Supplier’s identification for trace-ability of the telephone, as desired by supplier (e.g. “S/N: nnn....” for serial number).	Text, height 1,5 mm. Defined by supplier.
Line 8 (28,0/4,0)	Line 7 in bar code. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).

Prepared (also subject responsible if other)

SEM/CGVIOA MARK 2 WANG

Approved

SoMC/CGOVIOA/Mark Wang

Checked

Company Internal
MARKING DRAWINGTECHNICAL
No.

27/0363-1/FCP 119 1293

Date

Rev

Reference

2012-08-143

PA1

6

Line 9 (31,0/4,0)	Actual electronic serial number (IMEI) of the mobile phone, "00000000-000000-0"	Text, height 1,5 mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 10 (34,0/4,0)	Line 9 in bar code (only actual number, without data identifier).	Bar code, height 2,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.
Line 11a (42,0/4,0)	CE approval symbol	Graphics, height 5 mm. According to 1210-0131.
Line 11b (42,0/11,5)	The notified body number "0682"	Text, height 5,0 mm.
Line 11c (42,0/28,0)	WEE trashcan without bar symbol	Graphics, height 5,0 mm, According to 1202-5537.
Line 12 (48,0/4,0)	Marking of origin. "Made in Xxx"; "Xxx" = actual country of production of the included telephone, in English	Text, height 1,5 mm.

3 Layout

The conceptual picture (for Zebra 90Xill printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

3.1 Conceptual picture



double underlined = major changes since last revision.