

Sony Mobile Communications  
Prepared by  
SEM/CGQBAD RAZVAN BUJILA  
Contents responsible if other than preparer

Approved by  
SEM/CGQBAD (RAZVAN BUJILA)

Confidential  
LETTER  
Document number  
46/0061-LXE 110 0790 Uen  
Date  
2013-04-17  
Remarks  
This document is managed in metaDoc.

1(1)  
Revision  
A

**Receiver**  
Federal Communications Commission &  
Certification and Engineering Bureau

## Dual Cell HSDPA Declaration Letter - PY7PM-0520

### Applies to:

Product	Type number	FCC ID	IC ID
C6606/C6616	PM-0520-BV	PY7PM-0520	4170B-PM0520

There is no difference between uplink with DC-HSDPA configured and the normal HSDPA case. For the reporting format used on HS-DPCCH for CQI and ACK/NACK reporting please see 3GPP 25.212 4.7.3A.

The RF chain remains unchanged. This implementation described above does not affect uplink modulation, spurious emission, bandwidths and temperature behavior. Output power in DC-HSDPA mode is equal or lower than output power in RMC 12.2kbps mode, as demonstrated in this filing.

Secondary carrier share uplink HS-DPCCH according to document 3GPP TS 25.212 s4.7 with the first carrier. Uplink will be power controlled as normal by one stream of TPC commands received on DL DPCH i.e. E-DPDCH, E-DPCCH, DPDCH, DPCCH and HS-DPCCH will all be power controlled jointly.

Based on this the DC-HSDPA mode has been excluded from the testing performed in the EMC test reports.

Yours sincerely



**Mats Hansson**  
Head of Regulatory Compliance

Sony Mobile Communications  
Tel: +46 70 24 71084  
Mobilvägen 10, SE-221 88 Lund, Sweden  
[mats.hansson@sonymobile.com](mailto:mats.hansson@sonymobile.com)