

Sony Mobile Communications
Prepared by
SEM/CGQTAOA TOSHIKO KITAHARA
Contents responsible if other than preparer

Approved by
SEM/CGQTAOA (MIGUEL DELORME)

Document number
152/1483-LXE 108 828 Uen
Date
2014-07-10

Remarks
This document is managed in metaDoc.

Revision
A

Federal Communication Commission
Equipment Authorization Division,
Application Processing Branch
7435 Oakland Mills Road
Columbia, MD 21046

Declaration about MIF values Modulation Index Factor values

TO WHOM IT MAY CONCERN

Sony Mobile Communications Inc. declares that the reported MIF (Modulation Index Factor) values for our equipment with

FCC ID: PY7PM-0742

are based on worst case operating modes for all air interfaces for which the HAC rating is provided based on the current methodology for determining MIF values.

The following related UID files for GSM, WCDMA and CDMA are filed together with the HAC test report under exhibition type 'Test Report'.

10011 UMTS-FDD (WCDMA), probe calibration certificate appendix UID 10011-CAA, 2013-02-28

10021 GSM-FDD (TDMA, GMSK), probe calibration certificate appendix UID 10021-DAA, 2013-05-13

We confirm that the listed UID files used represent the air interfaces supported by our above identified equipment.

Yours sincerely



Mika Kaneko
Senior Architect – Global Type Approval
Sony Mobile Communications Inc.
Tel: +81 3 5782 5706
Konan, Minato-ku, 108-0075, Tokyo, Japan
mika.kaneko@sonymobile.com