



TEST REPORT

Test Report No. : UL-RPT-RP10295117JD01A V2.0

Manufacturer : Sony Mobile Communications Inc.

FCC ID : PY7PM-0807

Test Standard(s) : FCC Parts 15.107 & 15.109

1. This test report shall not be reproduced in full or partial, without the written approval of UL VS LTD.
2. The results in this report apply only to the sample(s) tested.
3. The sample tested is in compliance with the above standard(s).
4. The test results in this report are traceable to the national or international standards.
5. Version 2.0 supersedes all previous versions.

Date of Issue: 02 August 2014

Checked by:

Steven White
Project Lead, Radio Laboratory

Issued by :

pp

John Newell
Group Quality Manager
Basingstoke,
UL VS LTD



This laboratory is accredited by UKAS.
The tests reported herein have been
performed in accordance with its' terms
of accreditation.

UL VS LTD

Pavilion A, Ashwood Park, Ashwood Way, Basingstoke, Hampshire, RG23 8BG, UK
Telephone: +44 (0)1256 312000
Facsimile: +44 (0)1256 312001

This page has been left intentionally blank.

Table of Contents

1. Customer Information	4
2. Summary of Testing	5
2.1. General Information	5
2.2. Summary of Test Results	5
2.3. Methods and Procedures	5
2.4. Deviations from the Test Specification	5
3. Equipment Under Test (EUT)	6
3.1. Identification of Equipment Under Test (EUT)	6
3.2. Description of EUT	7
3.3. Modifications Incorporated in the EUT	7
3.4. Additional Information Related to Testing	7
3.5. Support Equipment	7
4. Operation and Monitoring of the EUT during Testing	8
4.1. Operating Modes	8
4.2. Configuration and Peripherals	8
5. Measurements, Examinations and Derived Results	9
5.1. General Comments	9
5.2. Test Results	10
5.2.1. Receiver/Idle Mode AC Conducted Spurious Emissions	10
5.2.2. Receiver/Idle Mode Radiated Spurious Emissions	13
6. Measurement Uncertainty	19
7. Report Revision History	20

1.Customer Information

Company Name:	Sony Mobile Communications Inc.
Address:	Nya Vattentornet Mobilvägen 10 Lund 22188 Sweden

2. Summary of Testing

2.1. General Information

Specification Reference:	47CFR15.107 and 47CFR15.109
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart B (Unintentional Radiators) – Sections 15.107 and 15.109
Site Registration:	209735
Location of Testing:	UL VS LTD, Unit 3 Horizon, Wade Road, Kingsland Business Park, Basingstoke, Hampshire, RG24 8AH, United Kingdom
Test Dates:	07 July 2014 to 15 July 2014

2.2. Summary of Test Results

FCC (47CFR)	Measurement	Result
Part 15.107(a)	Receiver/Idle Mode AC Conducted Spurious Emissions	
Part 15.109	Receiver/Idle Mode Radiated Spurious Emissions	
Key to Results  = Complied  = Did not comply		

2.3. Methods and Procedures

Reference:	ANSI C63.4 (2009)
Title:	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

3. Equipment Under Test (EUT)

3.1. Identification of Equipment Under Test (EUT)

Brand Name:	Sony
IMEI:	004402452692654 (<i>Radiated sample #1</i>)
Test Sample Serial Number:	CB5A1ZG8UF
Hardware Version Number:	A
Software Version Number:	23.0.H.0.61
FCC ID:	PY7PM-0807

Brand Name:	Sony
IMEI:	004402452693934 (<i>Radiated sample #2</i>)
Test Sample Serial Number:	CB5A1ZG8UW
Hardware Version Number:	A
Software Version Number:	23.0.H.0.61
FCC ID:	PY7PM-0807

Brand Name:	Sony
Description:	AC Charger
Model Name or Number:	EP880

Brand Name:	Generic
Description:	MHL Cable
Model Name or Number:	Not marked

Brand Name:	Sony
Description:	MHL Adaptor
Model Name or Number:	IM750

Brand Name:	Sony
Description:	USB Cable
Model Name or Number:	EC803

Brand Name:	Sony
Description:	Deskstand
Model Name or Number:	DK43

Identification of Equipment Under Test (EUT) (continued)

Brand Name:	Sony
Description:	PHF
Model Name or Number:	MH410c

3.2. Description of EUT

The equipment under test (EUT) was a GSM/WCDMA/LTE Phone + Bluetooth, DTS/UNII a/b/g/n/ac + NFC & ANT+

3.3. Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

3.4. Additional Information Related to Testing

Type of Radio Device:	Transceiver	
Power Supply Requirement(s):	Nominal	3.8 VDC

3.5. Support Equipment

The following support equipment was used to exercise the EUT during testing:

Description:	2 GB Micro SD Card
Brand Name:	Generic
Model Name or Number:	Not marked

Description:	22" High Definition Television
Brand Name:	Logik
Model Name or Number:	L22FE12A
Serial Number:	1309020661

4.Operation and Monitoring of the EUT during Testing

4.1.Operating Modes

The EUT was tested in the following operating mode(s):

- Receiver/Idle mode.

4.2.Configuration and Peripherals

The EUT was tested in the following configuration(s):

- Idle radiated spurious emission tests were performed with the following configurations, employing all available accessories:
 - o Configuration 1 – Handset with the AC charger, USB Cable, MHL cable (terminated in to a television), MHL adaptor and PHF.
 - o Configuration 2 – Handset with the AC charger, USB Cable, Deskstand and PHF.

Pre-scans below 1 GHz were performed in both configurations 1 and 2, with final measurements limited to the configuration which provided worst case results. Pre-scans above 1 GHz were performed in the configuration that employed the most accessories (Configuration 1), with any final measurements being performed in both configurations.

- The radiated sample with IMEI 004402452693934 was used for radiated emissions measurements.
- The radiated sample with IMEI 004402452692654 was used for AC conducted emissions measurements.

5. Measurements, Examinations and Derived Results

5.1. General Comments

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to *Section 6. Measurement Uncertainty* for details.

In accordance with UKAS requirements all the measurement equipment is on a calibration schedule. All equipment was within the calibration period on the date of testing.

5.2. Test Results**5.2.1. Receiver/Idle Mode AC Conducted Spurious Emissions****Test Summary:**

Test Engineer:	Mark Percival	Test Date:	08 July 2014
Test Sample IMEI:	004402452692654		

FCC Reference:	Part 15.107
Test Method Used:	ANSI C63.4-2009

Environmental Conditions:

Temperature (°C):	22
Relative Humidity (%):	55

Results: Live / Quasi Peak

Frequency (MHz)	Line	Level (dB (V))	Limit (dB (V))	Margin (dB)	Result
0.164	Live	48.8	65.3	16.5	Complied
0.173	Live	48.3	64.8	16.5	Complied
0.182	Live	47.1	64.4	17.3	Complied
0.213	Live	43.4	63.1	19.7	Complied
0.227	Live	43.1	62.6	19.5	Complied
0.483	Live	39.5	56.3	16.8	Complied

Results: Live / Average



Frequency (MHz)	Line	Level (dB (V))	Limit (dB (V))	Margin (dB)	Result
0.245	Live	27.8	51.9	24.1	Complied
0.483	Live	31.7	46.3	14.6	Complied
0.569	Live	27.8	46.0	18.2	Complied
0.888	Live	24.7	46.0	21.3	Complied
0.942	Live	23.3	46.0	22.7	Complied
14.604	Live	27.5	50.0	22.5	Complied

Receiver/Idle Mode AC Conducted Spurious Emissions (continued)**Results: Neutral / Quasi Peak**

Frequency (MHz)	Line	Level (dB (V))	Limit (dB (V))	Margin (dB)	Result
0.154	Neutral	50.0	65.8	15.8	Complied
0.186	Neutral	47.0	64.2	17.2	Complied
0.312	Neutral	35.0	59.9	24.9	Complied
0.483	Neutral	40.6	56.3	15.7	Complied
1.424	Neutral	33.0	56.0	23.0	Complied
14.249	Neutral	38.3	60.0	21.7	Complied

Results: Neutral / Average

Frequency (MHz)	Line	Level (dB (V))	Limit (dB (V))	Margin (dB)	Result
0.488	Neutral	30.9	46.2	15.3	Complied
0.510	Neutral	28.2	46.0	17.8	Complied
0.812	Neutral	24.3	46.0	21.7	Complied
0.861	Neutral	25.4	46.0	20.6	Complied
15.099	Neutral	28.5	50.0	21.5	Complied
15.504	Neutral	28.0	50.0	22.0	Complied

Receiver/Idle Mode AC Conducted Spurious Emissions (continued)**Live****Neutral**

Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1625	Thermohygrometer	JM Handelspunkt	30.5015.06	None stated	31 Dec 2014	12
A004	LISN	Rohde & Schwarz	ESH3-Z5	890604/027	18 Nov 2014	12
A1830	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100668	27 Feb 2015	12
M1263	Test Receiver	Rohde & Schwarz	ESIB7	100265	14 Oct 2014	12

5.2.2. Receiver/Idle Mode Radiated Spurious Emissions**Test Summary:**

Test Engineer:	Georgios Vrezas	Test Date:	07 July 2014
Test Sample IMEI:	004402452693934		

FCC Reference:	Part 15.109
Test Method Used:	ANSI C63.4-2009
Frequency Range:	30 MHz to 1000 MHz

Environmental Conditions:


Temperature (°C):	25
Relative Humidity (%):	31

Note(s):

1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
2. All other emissions shown on the pre-scan plot were investigated and found to be ambient or >20 dB below the applicable limit or below the measurement system noise floor.
3. Measurements below 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.

Results: Quasi Peak

Frequency (MHz)	Antenna Polarity	Level (dB V/m)	Limit (dB V/m)	Margin (dB)	Result
30.096	Vertical	28.2	40.0	11.8	Complied
86.812	Vertical	23.4	40.0	16.6	Complied
92.378	Vertical	23.9	43.5	19.6	Complied
959.623	Vertical	26.8	46.0	19.2	Complied

Receiver/Idle Mode Radiated Spurious Emissions (continued)

Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1622	Thermohygrometer	JM Handelspunkt	30.5015.06	None stated	31 Dec 2014	12
K0001	5m RSE Chamber	Rainford EMC	N/A	N/A	26 Nov 2014	12
M1273	Test Receiver	Rohde & Schwarz	ESIB 26	100275	15 Feb 2015	12
G0543	Amplifier	Sonoma	310N	230801	19 Aug 2014	3
A490	Antenna	Chase	CBL6111A	1590	29 Apr 2015	12
A1834	Attenuator	Hewlett Packard	8491B	10444	15 Nov 2014	12

Receiver/Idle Mode Radiated Spurious Emissions (continued)**Test Summary:**

Test Engineers:	David Doyle & Andrew Edwards	Test Dates:	14 July 2014 & 15 July 2014
Test Sample IMEI:	004402452693934		

FCC Reference:	Part 15.109
Test Method Used:	As detailed in ANSI C63.4 Section 8
Frequency Range:	1 GHz to 29.5 GHz

Environmental Conditions:





Temperature (C):	24 to 26
Relative Humidity (%):	42 to 46




Note(s):

1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
2. No spurious emissions were detected above the noise floor of the measuring receiver therefore the highest peak noise floor reading of the measuring receiver was recorded as shown in the table below. The peak level was compared to the average limit as opposed to being compared to the peak limit because this is the more onerous limit.
3. Measurements were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.
4. Pre-scans above 1 GHz were performed in a fully anechoic chamber (Asset Number K0002) at a distance of 3 metres. The EUT was placed at a height of 1.5 metres above the test chamber floor in the centre of the chamber turntable. All measurement antennas were placed at a fixed height of 1.5 metres above the test chamber floor, in line with the EUT. Final measurements above 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.

Results:

Frequency (MHz)	Antenna Polarity	Peak Level (dB [V/m])	Average Limit (dB [V/m])	Margin (dB)	Result
25669.071	Vertical	50.2	54.0	3.8	Complied

Receiver/Idle Mode Radiated Spurious Emissions (continued)

Receiver/Idle Mode Radiated Spurious Emissions (continued)

Receiver/Idle Mode Radiated Spurious Emissions (continued)**Test Equipment Used:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1656	Thermohygrometer	JM Handelspunkt	30.5015.13	None stated	14 Mar 2015	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	14 Nov 2014	12
M1874	Test Receiver	Rohde & Schwarz	ESU 26	100553	13 May 2015	12
A1534	Pre Amplifier	Hewlett Packard	8449B	3008A00405	18 May 2015	12
A1818	Antenna	EMCO	3115	00075692	14 Nov 2014	12
A253	Antenna	Flann Microwave	12240-20	128	14 Nov 2014	12
A254	Antenna	Flann Microwave	14240-20	139	14 Nov 2014	12
A255	Antenna	Flann Microwave	16240-20	519	14 Nov 2014	12
A256	Antenna	Flann Microwave	18240-20	400	14 Nov 2014	12
A436	Antenna	Flann Microwave	20240-20	330	14 Nov 2014	12
A203	Antenna	Flann Microwave	22240-20	343	19 May 2016	36
A1785	Pre Amplifier	Farran Technology	FLNA-28-30	FTL 6483	13 Jan 2015	12
M1630	Test Receiver	Rohde & Schwarz	ESU40	100233	13 Mar 2015	12
M1229	Digital Multimeter	Fluke	179	87640015	24 Apr 2015	12
S0557	DC Power Supply	TTI	EL303R	395819	Calibrated before use	-

6.Measurement Uncertainty

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	±4.69 dB
Radiated Spurious Emissions	30 MHz to 1 GHz	95%	±5.65 dB
Radiated Spurious Emissions	1 GHz to 29.5 GHz	95%	±2.94 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

7. Report Revision History

Version Number	Revision Details		
	Page No(s)	Clause	Details
1.0	-	-	Initial Version
2.0	-	-	EUT Description update

--- END OF REPORT ---