

## TEST REPORT

Test report no.: 1-5831/13-10-12-A



Deutsche  
Akkreditierungsstelle  
D-PL-12076-01-01

### Testing laboratory

**CETECOM ICT Services GmbH**  
Untertuerkheimer Strasse 6 – 10  
66117 Saarbruecken / Germany  
Phone: + 49 681 5 98 - 0  
Fax: + 49 681 5 98 - 9075  
Internet: <http://www.cetecom.com>  
e-mail: [ict@cetecom.com](mailto:ict@cetecom.com)

#### Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2005) by the Deutsche Akkreditierungsstelle GmbH (DAkkS). The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12076-01-01  
Area of Testing: Radio/Satellite Communications

### Applicant

**Sony Mobile Communications AB**  
Nya Vattentornet  
22188 Lund / SWEDEN  
Phone: +46 46 19 30 00  
Fax: -/  
Contact: Fredrik Björk  
e-mail: [Fredrik.Bjork@sonymobile.com](mailto:Fredrik.Bjork@sonymobile.com)  
Phone: +46 1 08 01 46 75  
Mobile: +46 70 32 40 14 0

### Manufacturer

**Sony Mobile Communications AB**  
Nya Vattentornet  
22188 Lund / SWEDEN

### Test standard/s

47 CFR Part 15	Title 47 of the Code of Federal Regulations; Chapter I Part 15 - Radio frequency devices
RSS - 210 Issue 8	Spectrum Management and Telecommunications - Radio Standards Specification Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

For further applied test standards please refer to section 3 of this test report.

### Test Item

Kind of test item:	Tablet PC GPRS/EGPRS 850/900/1800/1900; UMTS HSPA FDDI/V/VIII; LTE FDD1/3/5/7/8/20; WLAN a/b/g/n; BT 3.1; RFID; FM Rx; A-GPS
Model name:	SGP321
FCC ID:	PY7TM-0030
IC:	4170B-TM0030
Frequency:	ISM band 5725 MHz to 5850 MHz (lowest channel 149 – 5745 MHz, highest channel 165 – 5825 MHz)
Technology tested:	WLAN (OFDM / a – & n HT20 – mode; OFDM / n HT40 – mode)
Antenna:	Integrated antenna
Power Supply:	3.7 V DC by Li - Ion battery
Temperature Range:	-20°C to +55°C

This test report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### Test report authorised:

cn=Stefan Boes, o=CETECOM ICT Services GmbH, ou=BOE-111011, email=Stefan.Boes@cetecom.com, c=DE  
2013.04.17 09:34:06 +02'00'

Stefan BöS  
Senior Testing Manager

### Test performed:

cn=Marco Bertolino, o=CETECOM ICT Services GmbH, ou=BTL-100826, email=marco.bertolino@cetecom.com, c=DE  
2013.04.17 09:53:25 +02'00'

Marco Bertolino  
Testing Manager

<b>1 Table of contents</b>	
1	Table of contents .....2
2	General information .....3
2.1	Notes and disclaimer .....3
2.2	Application details.....3
3	Test standard/s .....3
3.1	Measurement guidance.....3
4	Test environment.....4
5	Test item .....4
5.1	Additional information .....4
6	Test laboratories sub-contracted .....4
7	Summary of measurement results .....5
8	RF measurements .....6
8.1	Description of test setup .....6
8.1.1	Radiated measurements.....6
8.1.2	Conducted measurements.....7
8.2	Additional comments .....7
8.3	RSP100 test report cover sheet / performance test data .....8
9	Measurement results.....9
9.1	Output power verification (conducted) .....9
9.2	Antenna gain .....10
9.3	Maximum output power .....13
9.4	Power spectral density .....20
9.5	Spectrum bandwidth – 6 dB .....27
9.6	Spectrum bandwidth – 20 dB .....33
9.7	Band edge compliance conducted .....39
9.8	Band edge compliance radiated .....39
9.9	TX spurious emissions conducted .....40
9.10	TX spurious emissions radiated .....48
9.11	RX spurious emissions radiated .....65
9.12	Spurious emissions radiated < 30 MHz .....69
9.13	Spurious emissions conducted < 30 MHz .....71
10	Test equipment and ancillaries used for tests .....74
11	Observations .....75
Annex A	Document history .....76
Annex B	Further information.....76
Annex C	Accreditation Certificate .....77

## 2 General information

### 2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM ICT Services GmbH.

The testing service provided by CETECOM ICT Services GmbH has been rendered under the current "General Terms and Conditions for CETECOM ICT Services GmbH".

CETECOM ICT Services GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CETECOM ICT Services GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CETECOM ICT Services GmbH test report include or imply any product or service warranties from CETECOM ICT Services GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CETECOM ICT Services GmbH.

All rights and remedies regarding vendor's products and services for which CETECOM ICT Services GmbH has prepared this test report shall be provided by the party offering such products or services and not by CETECOM ICT Services GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### 2.2 Application details

Date of receipt of order:	2013-01-30
Date of receipt of test item:	2013-04-01
Start of test:	2013-04-01
End of test:	2013-04-10
Person(s) present during the test:	-/-

## 3 Test standard/s

Test standard	Date	Test standard description
47 CFR Part 15	2012-10	Title 47 of the Code of Federal Regulations; Chapter I Part 15 - Radio frequency devices
RSS - 210 Issue 8	2010-12	Spectrum Management and Telecommunications - Radio Standards Specification Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

### 3.1 Measurement guidance

DTS : KDB 558074	2012-04	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
------------------	---------	---

#### 4 Test environment

Temperature:	$T_{nom}$	+22 °C during room temperature tests
	$T_{max}$	+55 °C during high temperature tests
	$T_{min}$	-20 °C during low temperature tests
Relative humidity content:		41 %
Barometric pressure:		not relevant for this kind of testing
Power supply:	$V_{nom}$	3.7 V DC by Li - Ion battery
	$V_{max}$	4.1 V
	$V_{min}$	3.3 V

#### 5 Test item

Kind of test item	:	Tablet PC GPRS/EGPRS 850/900/1800/1900; UMTS HSPA FDDI/V/VIII; LTE FDD1/3/5/7/8/20; WLAN a/b/g/n; BT 3.1; RFID; FM Rx; A-GPS
Type identification	:	SGP321
S/N serial number	:	Radiated units: CB5A1NY06R; CB5A1NY07J Conducted units: CB5A1NY07G; CB5A1NY070
HW hardware status	:	AP1
SW software status	:	10.1.1.A.1.11
Frequency band [MHz]	:	ISM band 5725 MHz to 5850 MHz (lowest channel 149 – 5745 MHz; highest channel 165 – 5825 MHz)
Type of radio transmission	:	OFDM
Use of frequency spectrum	:	
Type of modulation	:	QPSK, 16 – QAM, 64 – QAM
Number of channels	:	5 – 20 MHz channels 2 – 40 MHz channels
Antenna	:	Integrated antenna
Power supply	:	3.7 V DC by Li - Ion battery
Temperature range	:	-20°C to +55 °C

#### 5.1 Additional information

Test setup - and EUT - photos are included in the following test reports:

External EUT photos: 1-5831/13-10-01\_AnnexA  
 Internal EUT photos: 1-5831/13-10-01\_AnnexB  
 Test setup: 1-5831/13-10-01\_AnnexD

#### 6 Test laboratories sub-contracted

None

## 7 Summary of measurement results

- No deviations from the technical specifications were ascertained  
 There were deviations from the technical specifications ascertained

TC Identifier	Description	Verdict	Date	Remark
RF-Testing	CFR Part 15 RSS 210, Issue 8	Passed	2013-04-17	-/-

Test specification clause	Test case	Temperature conditions	Power source voltages	Mode	Pass	Fail	NA	NP	Remark
§15.247(b)(4) RSS 210 / A8.4(2)	Antenna gain	Nominal	Nominal	OFDM	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(e) RSS 210 / A8.2(b)	Power spectral density	Nominal	Nominal	OFDM	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(a)(2) RSS 210 / A8.2(a)	Spectrum bandwidth - 6dB bandwidth	Nominal	Nominal	OFDM	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(a)(2) RSS 210 / A8.2(a)	Spectrum bandwidth - 20dB bandwidth	Nominal	Nominal	OFDM	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(b)(3) RSS-210 / A8.4(4)	Maximum output power	Nominal	Nominal	OFDM	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(d) RSS-210 / A8.5	Band edge compliance conducted	Nominal	Nominal	OFDM	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	No restricted band!
§15.205 RSS-210 / A8.5	Band edge compliance radiated	Nominal	Nominal	OFDM	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	No restricted band!
§15.247(d) RSS-210 / A8.5	TX spurious emissions conducted	Nominal	Nominal	OFDM	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(d) RSS-210 / A8.5	TX spurious emissions radiated	Nominal	Nominal	OFDM	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.109 RSS-Gen	RX spurious emissions radiated	Nominal	Nominal	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.209(a) RSS-Gen	TX spurious emissions radiated < 30 MHz	Nominal	Nominal	OFDM	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.107(a)	Conducted emissions < 30 MHz	Nominal	Nominal	OFDM	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies

**Note:** NA = Not Applicable; NP = Not Performed


## 8 RF measurements

### 8.1 Description of test setup

#### 8.1.1 Radiated measurements

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 25 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63. Antennas are confirmed with ANSI C63.

Semi anechoic chamber




Picture 1: Diagram radiated measurements

9 kHz - 30 MHz:	active loop antenna
30 MHz – 1 GHz:	tri-log antenna
> 1 GHz:	horn antenna

The EUT is powered by an external power supply with nominal voltage. The signalling is performed from outside the chamber with a signalling unit (CMU200 or other) by air link using signalling antenna.

### 8.1.2 Conducted measurements

The EUT's RF signal is coupled out by the antenna connector which is supplied by the manufacturer. The signal is first 10dB attenuated before it is power divided (~6dB loss per branch). One of the signal paths is connected to the communication base Station (CMU200 or other), the other one is connected to the spectrum analyzer. The specific losses for both signal paths are first checked within a calibration. The measurement readings on the signalling unit/spectrum analyzer are corrected by the specific test set-up loss. The attenuator, power divider, signalling unit and the spectrum analyzer are impedance matched on 50 Ohm.



Picture 2: Diagram conducted measurements

### 8.2 Additional comments

Reference documents: None

Special test descriptions: None

Configuration descriptions: None

Test mode:

- No test mode available.  
lperf was used to ping another device with the largest support packet size
- Special software is used.  
EUT is transmitting pseudo random data by itself

### 8.3 RSP100 test report cover sheet / performance test data

Test report number	:	1-5831/13-10-12-A			
Equipment model number:		SGP321			
Certification number	:	4170B-TM0030			
Manufacturer (complete address)	:	Sony Mobile Communications AB Nya Vattentorget 22188 Lund / SWEDEN			
Tested to radio standards specification no.	:	RSS 210, Issue 8			
Open area test site IC No. :		IC 3462C-1			
Frequency range	:	ISM band 5725 MHz to 5850 MHz			
RF-power [W] (max.)	:	Conducted values:			
		Band	a – mode	n HT20 – mode	n HT40 – mode
		5745 – 5825 MHz	117.76 mW	114.02 mW	
		5755 – 5835 MHz			174.98 mW
		Radiated values:			
		Band	a – mode	n HT20 – mode	n HT40 – mode
Occupied bandwidth (99%-BW) [kHz]	:	Band	a – mode	n HT20 – mode	n HT40 – mode
		5745 – 5825 MHz	16.49 MHz	17.67 MHz	
		5755 – 5835 MHz			36.07 MHz
Necessary bandwidth (calculated) [kHz]	:	Band	a – mode	n HT20 – mode	n HT40 – mode
		5745 – 5825 MHz	16.88 MHz	16.88 MHz	
		5755 – 5835 MHz			33.75 MHz
Emission classification	:	(according TRC-43)	G7D		
Type of modulation	:	QPSK, 16 – QAM, 64 – QAM			
Antenna information	:	Integrated antenna			
Transmitter spurious [dBμV/m @ 3m]	:	45 @ 12 GHz (noise floor, peak)			

#### ATTESTATION:

#### DECLARATION OF COMPLIANCE:

I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned Industry Canada standard(s); and that the equipment identified in this application has been subjected to all the applicable test conditions specified in the Industry Canada standards and all of the requirements of the standard have been met.

#### Laboratory manager:

2013-04-17

Date

Marco Bertolino

Name



Signature

cn=Marco Bertolino, o=CETECOM ICT  
Services GmbH, ou=BTL-100826,  
email=marco.bertolino@cetecom.com,  
c=DE  
2013.04.17 09:54:04 +02'00'



## 9 Measurement results

### 9.1 Output power verification (conducted)

#### Description:

Measurement of the maximum output power conducted. This measurement is performed only at the middle channel in both modes and all data rates to determine the data rate per mode which results in the highest output power. This mode will be selected for all further measurements.

#### Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	5 s
Resolution bandwidth:	40 MHz
Video bandwidth:	40 MHz
Span:	Zero-Span
Trace-Mode:	Max Hold

#### Results:

OFDM / a – mode Data Rate [MBit/s]	Maximum Output Power Conducted [dBm]							
	6	9	12	18	24	36	48	54
Ch 157 - 5785 MHz	20.57	20.39	20.18	20.33	20.50	20.62	20.31	<b>20.70</b>
Measurement uncertainty	± 0.5 dB							

OFDM / n – mode HT20 Data Rate [MBit/s]	Maximum Output Power Conducted [dBm]							
	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Ch 157 - 5785 MHz	20.44	20.33	20.13	20.58	<b>20.65</b>	20.38	20.40	20.59
Measurement uncertainty	± 0.5 dB							

OFDM / n – mode HT40 Data Rate [MBit/s]	Maximum Output Power Conducted [dBm]							
	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Ch 149 - 5755 MHz	21.05	<b>22.25</b>	21.51	21.44	21.38	20.78	22.23	20.35
Measurement uncertainty	± 0.5 dB							

Result: Selected data rate for all measurements:

OFDM / a – mode: 54 MBit/s  
 OFDM / n – mode HT20: MCS4  
 OFDM / n – mode HT40: MCS1

## 9.2 Antenna gain

### Measurement:

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

### Measurement parameters:

Measurement parameter	
Detector:	Peak
Sweep time:	5 s
Resolution bandwidth:	3 MHz
Video bandwidth:	3 MHz
Trace-Mode:	Max hold

### Limits:

FCC	IC
Antenna Gain	
6 dBi	


### Results:

T <sub>nom</sub>	V <sub>nom</sub>	lowest channel 5745 MHz	middle channel 5785 MHz	highest channel 5825 MHz
Conducted power [dBm]		14.93	14.43	15.37
Radiated power [dBm]		11.50	12.00	9.80
Gain [dBi] Calculated		-3.43	-2.43	-5.57
Measurement uncertainty			± 1.5 dB (cond.) / ± 3 dB (rad.)	


**Result: Passed**

**Plots:** conducted power for gain calculation

**Plot 1:** low channel11



**Plot 2:** middle channel



Plot 3: high channel



Date: 5. APR. 2013 16:09:06

### 9.3 Maximum output power

**Description:**

Measurement of the maximum output power conducted and radiated. The measurements are performed using the data rate producing the highest conducted output power. The determination of these data rates was performed at the beginning of the tests.

**Measurement:**

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	3 MHz / 10 MHz (at least 1 MHz)
Video bandwidth:	≥ 3 x RBW (or maximum of available setting)
Span:	> DTS bandwidth
Integration bandwidth:	99% power - bandwidth
Trace-Mode:	Max hold (allow trace to fully stabilize)

**Limits:**

FCC	IC
Maximum Output Power	
Conducted: 1.0 W – Antenna Gain max. 6 dBi	

**Results: OFDM / a – mode**

OFDM / a – mode Frequency	Maximum Output Power [dBm]		
	5745 MHz	5785 MHz	5825 MHz
Peak Output Power Conducted	20.00	18.99	20.71
Output Power Radiated – EIRP <sup>*</sup> )	16.57	16.56	15.14
Measurement uncertainty	± 1.5 dB (cond.) / ± 3 dB (rad.)		

<sup>\*</sup>) calculated with Antenna gain

**Result: Passed**

**Results: OFDM / n – mode HT20**

OFDM / n – mode HT20 Frequency	Maximum Output Power [dBm]		
	5745 MHz	5785 MHz	5825 MHz
Peak Output Power Conducted	20.57	20.20	19.54
Output Power Radiated – EIRP*)	17.14	17.77	13.97
Measurement uncertainty	± 1.5 dB (cond.) / ± 3 dB (rad.)		

\*) calculated with Antenna gain

**Result: Passed****Results: OFDM / n – mode HT40**


OFDM / n – mode HT40 Frequency	Maximum Output Power [dBm]		
	5755 MHz	5795 MHz	-/-
Peak Output Power Conducted	22.43	18.70	-/-
Output Power Radiated – EIRP*)	19.00	16.27	-/-
Measurement uncertainty	± 1.5 dB (cond.) / ± 3 dB (rad.)		

\*) calculated with Antenna gain


**Result: Passed**

**Plots: OFDM / a – mode**


**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, middle channel**




Plot 3: TX mode, highest channel






**Plots: OFDM / n – mode HT20**


**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, middle channel**




Plot 3: TX mode, highest channel




Date: 6.APR.2013 09:29:32

**Plots: OFDM / n – mode HT40**

**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, highest channel**



## 9.4 Power spectral density

### Description:

Measurement of the power spectral density of a digital modulated system. The measurement is repeated for both modulations at the lowest, middle and highest channel.

### Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	$\geq 3$ kHz
Video bandwidth:	$\geq 3 \times$ RBW
Span:	1.5 times of the DTS BW
Trace-Mode:	Max hold (allow trace to fully stabilize)
Bandwidth correction:	Peak

### Limits:

FCC	IC
Power Spectral Density	
8 dBm (conducted)	


**Results:**

Modulation Frequency	Power Spectral density [dBm]		
	5725 MHz	5785 MHz	5825 MHz
OFDM / a – mode	-14.94	-15.58	-13.73
OFDM / n – mode HT20	-14.10	-14.37	-13.87
Frequency	5755 MHz	5795 MHz	-/-
OFDM / n – mode HT40	-14.13	-17.88	-/-
Measurement uncertainty	± 1.5 dB		


**Result:** Passed

**Plots: OFDM / a – mode**


**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, middle channel**




Plot 3: TX mode, highest channel




**Plots: OFDM / n – mode HT20**

**Plot 1: TX mode, lowest channel**




**Plot 2: TX mode, middle channel**






Plot 3: TX mode, highest channel




**Plots: OFDM / n – mode HT40**

**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, highest channel**



## 9.5 Spectrum bandwidth – 6 dB

**Description:**

Measurement of the 6 dB bandwidth of the modulated signal.

...

**Measurement:**

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	1 - 5% of the DTS BW but not exceed 100 kHz
Video bandwidth:	≥ 3 x RBW
Span:	Complete signal
Measurement procedure:	Measurement of the 75% bandwidth using the integration function of the analyzer
Trace-Mode:	Max hold (allow trace to stabilize)

**Limits:**

FCC	IC
Spectrum Bandwidth – 6 dB	
Systems using digital modulation techniques may operate in the 2400–2483.5 MHz band. The minimum 6 dB bandwidth shall be at least 500 kHz.	


**Results:**

Modulation Frequency	6 dB bandwidth [MHz]		
	Lowest channel	Middle channel	Highest channel
OFDM / a – mode	12.50	12.48	12.50
OFDM / n – mode HT20	13.37	13.31	13.42
OFDM / n – mode HT40	26.49	-/-	26.27
Measurement uncertainty	± RBW		


**Result:** Passed

**Plots: OFDM / a – mode**


**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, middle channel**




Plot 3: TX mode, highest channel




**Plots: OFDM / n – mode HT20**


**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, middle channel**




Plot 3: TX mode, highest channel




**Plots: OFDM / n – mode HT40**

**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, highest channel**





## 9.6 Spectrum bandwidth – 20 dB

### Description:

Measurement of the 20 dB bandwidth of the modulated signal.

### Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	Auto
Resolution bandwidth:	1 - 5% of the DTS BW but not exceed 100 kHz
Video bandwidth:	≥ 3 x RBW
Span:	Complete signal
Measurement procedure:	Measurement of the 99% bandwidth using the integration function of the analyzer
Trace-Mode:	Max hold (allow trace to stabilize)

### Limits:

FCC	IC
Spectrum Bandwidth – 20 dB	
Systems using digital modulation techniques may operate in the 2400–2483.5 MHz band. The minimum 6 dB bandwidth shall be at least 500 kHz.	


### Results:

Modulation Frequency	20 dB bandwidth [MHz]		
	Lowest channel	Middle channel	Highest channel
OFDM / a – mode	16.47	16.47	16.49
OFDM / n – mode HT20	17.67	17.66	17.67
OFDM / n – mode HT40	36.07	-/-	35.96
Measurement uncertainty	± RBW		


**Result: Passed**

**Plots: OFDM / a – mode**


**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, middle channel**




Plot 3: TX mode, highest channel




Date: 5. APR. 2013 16:30:20

**Plots: OFDM / n – mode HT20**


**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, middle channel**




Plot 3: TX mode, highest channel




**Plots: OFDM / n – mode HT40**

**Plot 1: TX mode, lowest channel**



**Plot 2: TX mode, highest channel**



## 9.7 Band edge compliance conducted

Not applicable! No restricted band close to used band!

## 9.8 Band edge compliance radiated

Not applicable! No restricted band close to used band!

## 9.9 TX spurious emissions conducted

### Description:

Measurement of the conducted spurious emissions in transmit mode. The measurement is performed at the lowest, middle and highest channel. The measurement is repeated for all modulations.

### Measurement:

Measurement parameter	
Detector:	Peak
Sweep time:	1s / 100 MHz
Resolution bandwidth:	F < 1 GHz: 100 kHz F > 1 GHz: 100 kHz
Video bandwidth:	F < 1 GHz: 500 kHz F > 1 GHz: 500 kHz
Span:	9 kHz to 25 GHz
Trace-Mode:	Max Hold

### Limits:

FCC	IC
TX Spurious Emissions Conducted	
<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required</p>	



**Results: OFDM / a – mode**

TX Spurious Emissions Conducted					
OFDM / a – mode					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
5745		0.42	30 dBm		Operating frequency
No peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		complies
5785		-0.33	30 dBm		Operating frequency
No peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		complies
5825		1.53	30 dBm		Operating frequency
No peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		complies
Measurement uncertainty		± 3 dB			

**Result: Passed**

**Results: OFDM / n – mode HT20**

TX Spurious Emissions Conducted					
OFDM / n – mode HT20					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
5745		1.13	30 dBm		Operating frequency
No peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		complies
5785		1.01	30 dBm		Operating frequency
No peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		complies
5825		0.29	30 dBm		Operating frequency
No peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc (peak) -30 dBc (average)		complies
Measurement uncertainty		± 3 dB			

**Result: Passed**


**Results: OFDM / n – mode HT40**

TX Spurious Emissions Conducted					
OFDM / n – mode HT40					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
5755		-0.14	30 dBm		Operating frequency
No peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc (peak)		complies
			-30 dBc (average)		
5785		-3.81	30 dBm		Operating frequency
No peaks detected. All detected emissions are below the -20 dBc criteria.			-20 dBc (peak)		complies
			-30 dBc (average)		
			30 dBm		Operating frequency
-/-			-20 dBc (peak)		-/-
			-30 dBc (average)		
Measurement uncertainty		± 3 dB			

**Result: Passed**


**Plots: OFDM / a – mode**

**Plot 1: TX mode, lowest channel, up to 40 GHz**




The peak at the beginning of the plot is the LO from the SA.

**Plot 2: TX mode, middle channel, up to 40 GHz**



The peak at the beginning of the plot is the LO from the SA.


Plot 3: TX mode, highest channel, up to 40 GHz



The peak at the beginning of the plot is the LO from the SA.


**Plots: OFDM / n – mode HT20**

**Plot 1: TX mode, lowest channel, up to 40 GHz**




The peak at the beginning of the plot is the LO from the SA.

**Plot 2: TX mode, middle channel, up to 40 GHz**



The peak at the beginning of the plot is the LO from the SA.


Plot 3: TX mode, highest channel, up to 40 GHz



The peak at the beginning of the plot is the LO from the SA.


**Plots: OFDM / n – mode HT40**

**Plot 1: TX mode, lowest channel, up to 40 GHz**



The peak at the beginning of the plot is the LO from the SA.

**Plot 2: TX mode, highest channel, up to 40 GHz**



The peak at the beginning of the plot is the LO from the SA.

## 9.10 TX spurious emissions radiated

### Description:

Measurement of the radiated spurious emissions in transmit mode. The measurement is performed at the lowest, middle and highest channel. The measurement is repeated for all modulations.

### Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak / RMS
Sweep time:	Auto
Resolution bandwidth:	F > 1 GHz: 1 MHz F < 1 GHz: 100 kHz
Video bandwidth:	Sweep: 100 kHz Remeasurement: 10 Hz / 3 MHz
Span:	30 MHz to 25 GHz
Trace-Mode:	Max Hold
Measured Modulation	<input checked="" type="checkbox"/> OFDM a – mode <input checked="" type="checkbox"/> OFDM n – mode HT20 <input checked="" type="checkbox"/> OFDM n – mode HT40

The modulation with the highest output power was used to perform the transmitter spurious emissions. If spurious were detected a re-measurement was performed on the detected frequency with each modulation.

### Limits:

FCC	IC	
TX Spurious Emissions Radiated		
<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).</p>		
Frequency (MHz)	Field Strength (dBµV/m)	Measurement distance
30 - 88	30.0	10
88 – 216	33.5	10
216 – 960	36.0	10
Above 960	54.0	3



**Results: OFDM / a – mode**

TX Spurious Emissions Radiated [dBµV/m]								
OFDM / a – mode								
5745 MHz			5785 MHz			5825 MHz		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
No emissions detected between 1 GHz and 12.75 GHz.			No emissions detected between 1 GHz and 12.75 GHz.			No emissions detected between 1 GHz and 12.75 GHz.		
For emissions above 12.75 GHz, please take a look at the plots.			For emissions above 12.75 GHz, please take a look at the plots.			For emissions above 12.75 GHz, please take a look at the plots.		
Measurement uncertainty			± 3 dB					

**Result: Passed**

**Results: OFDM / n – mode HT20**

TX Spurious Emissions Radiated [dBµV/m]								
OFDM / n – mode HT20								
5745 MHz			5785 MHz			5825 MHz		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
No emissions detected between 1 GHz and 12.75 GHz.			No emissions detected between 1 GHz and 12.75 GHz.			No emissions detected between 1 GHz and 12.75 GHz.		
For emissions above 12.75 GHz, please take a look at the plots.			For emissions above 12.75 GHz, please take a look at the plots.			For emissions above 12.75 GHz, please take a look at the plots.		
Measurement uncertainty			± 3 dB					

**Result: Passed**

**Results: OFDM / n – mode HT40**

TX Spurious Emissions Radiated [dBµV/m]								
OFDM / n – mode HT40								
5755 MHz			5795 MHz			-/-		
F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]	F [MHz]	Detector	Level [dBµV/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			-/-		
No emissions detected between 1 GHz and 12.75 GHz.			No emissions detected between 1 GHz and 12.75 GHz.					
For emissions above 12.75 GHz, please take a look at the plots.			For emissions above 12.75 GHz, please take a look at the plots.					
Measurement uncertainty			± 3 dB					

**Result: Passed**

**Note:** Results of OFDM a – mode are added to show the compliance with the standard.

**Plots: OFDM / a – mode**

**Plot 1:** Lowest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


**Common Information**

EUT: TM-0030-BV  
 Serial Number: CB5A1NY07J  
 Test Description: FCC part 15 C class B @ 10 m  
 Operating Conditions: wlan a-mode ch 149 + charging  
 Operator Name: Wolsdorfer  
 Comment: USB powered

**Scan Setup: STAN\_Fin [EMI radiated]**

Hardware Setup: Electric Field (NOS)  
 Receiver: [ESCI 3]  
 Level Unit: dBµV/m


Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
96.000000	13.0	1000.0	120.000	170.0	V	327.0	11.4	20.5	33.5	
144.000000	21.9	1000.0	120.000	98.0	V	0.0	8.8	11.6	33.5	
240.000000	22.7	1000.0	120.000	120.0	V	112.0	13.0	13.3	36.0	
336.000000	23.9	1000.0	120.000	111.0	V	250.0	15.6	12.1	36.0	
506.040000	22.7	1000.0	120.000	270.0	V	166.0	18.8	13.3	36.0	
600.000000	29.6	1000.0	120.000	98.0	V	327.0	20.8	6.4	36.0	


Plot 2: Lowest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization




Plot 3: Lowest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Plot 4: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Plot 5: Lowest channel, 26 GHz to 40 GHz, vertical & horizontal polarization



**Plot 6:** Middle channel, 30 MHz to 1 GHz, vertical & horizontal polarization


### Common Information

EUT: TM-0030-BV  
 Serial Number: CB5A1NY07J  
 Test Description: FCC part 15 C class B @ 10 m  
 Operating Conditions: wlan a-mode ch 157 + charging  
 Operator Name: Wolsdorfer  
 Comment: USB powered

### Scan Setup: STAN\_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)  
 Receiver: [ESCI 3]  
 Level Unit: dBµV/m


Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB




### Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
144.000000	22.7	1000.0	120.000	270.0	V	0.0	8.8	10.8	33.5	
168.000000	18.3	1000.0	120.000	120.0	V	81.0	9.7	15.2	33.5	
240.000000	21.3	1000.0	120.000	104.0	V	0.0	13.0	14.7	36.0	
336.000000	24.7	1000.0	120.000	270.0	V	242.0	15.6	11.3	36.0	
507.000000	25.3	1000.0	120.000	119.0	V	154.0	18.8	10.7	36.0	
600.000000	28.7	1000.0	120.000	98.0	V	334.0	20.8	7.3	36.0	


Plot 7: Middle channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization




Plot 8: Middle channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Plot 9: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Plot 10: Middle channel, 26 GHz to 40 GHz, vertical & horizontal polarization



Plot 11: Highest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


### Common Information

EUT: TM-0030-BV  
 Serial Number: CB5A1NY07J  
 Test Description: FCC part 15 C class B @ 10 m  
 Operating Conditions: wlan a-mode ch 165 + charging  
 Operator Name: Wolsdorfer  
 Comment: USB powered

### Scan Setup: STAN\_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)  
 Receiver: [ESCI 3]  
 Level Unit: dBµV/m

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB




### Final Result 1


Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
44.400000	10.7	1000.0	120.000	270.0	V	150.0	13.3	19.3	30.0	
144.000000	19.5	1000.0	120.000	111.0	V	40.0	8.8	14.0	33.5	
168.000000	18.0	1000.0	120.000	132.0	V	81.0	9.7	15.5	33.5	
240.000000	24.0	1000.0	120.000	98.0	V	117.0	13.0	12.0	36.0	
336.000000	24.6	1000.0	120.000	121.0	V	319.0	15.6	11.4	36.0	
600.000000	26.9	1000.0	120.000	98.0	V	319.0	20.8	9.1	36.0	




Plot 12: Highest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization




Plot 13: Highest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Plot 14: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Plot 15: Highest channel, 26 GHz to 40 GHz, vertical & horizontal polarization



**Plots: OFDM / n – mode HT40**

**Plot 1:** Lowest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


**Common Information**

EUT: TM-0030-BV  
 Serial Number: CB5A1NY07J  
 Test Description: FCC part 15 C class B @ 10 m  
 Operating Conditions: wlan n-mode HT40 ch 151 + charging  
 Operator Name: Wolsdorfer  
 Comment: USB powered

**Scan Setup: STAN\_Fin [EMI radiated]**

Hardware Setup: Electric Field (NOS)  
 Receiver: [ESCI 3]  
 Level Unit: dBµV/m


Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
47.254200	10.1	1000.0	120.000	98.0	V	-2.0	13.3	19.9	30.0	
67.871550	14.1	1000.0	120.000	170.0	V	170.0	9.8	15.9	30.0	
144.009600	14.2	1000.0	120.000	170.0	V	273.0	8.8	19.3	33.5	
432.022200	18.8	1000.0	120.000	170.0	V	92.0	17.4	17.2	36.0	
728.609400	20.1	1000.0	120.000	170.0	H	100.0	23.2	15.9	36.0	
957.103650	22.2	1000.0	120.000	170.0	V	273.0	25.4	13.8	36.0	


Plot 2: Lowest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization




Plot 3: Lowest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Plot 4: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Plot 5: Lowest channel, 26 GHz to 40 GHz, vertical & horizontal polarization



**Plot 6:** Highest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


### Common Information

EUT: TM-0030-BV  
 Serial Number: CB5A1NY07J  
 Test Description: FCC part 15 C class B @ 10 m  
 Operating Conditions: wlan n-mode HT40 ch 159 + charging  
 Operator Name: Wolsdorfer  
 Comment: USB powered

### Scan Setup: STAN\_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)  
 Receiver: [ESCI 3]  
 Level Unit: dBµV/m


Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB




### Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
65.336400	10.5	1000.0	120.000	143.0	V	10.0	10.3	19.5	30.0	
67.664850	12.6	1000.0	120.000	170.0	V	-9.0	9.8	17.4	30.0	
71.783850	14.4	1000.0	120.000	170.0	V	-4.0	9.2	15.6	30.0	
144.019350	14.5	1000.0	120.000	135.0	V	280.0	8.8	19.0	33.5	
691.691850	19.2	1000.0	120.000	170.0	V	10.0	22.3	16.8	36.0	
893.380200	21.9	1000.0	120.000	170.0	V	80.0	25.1	14.1	36.0	


**Plot 7:** Highest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization




**Plot 8:** Highest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization



Plot 9: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization



Plot 10: Highest channel, 26 GHz to 40 GHz, vertical & horizontal polarization





## 9.11 RX spurious emissions radiated

### Description:

Measurement of the radiated spurious emissions in idle/receive mode. The results are valid for both modes.

### Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak / RMS
Sweep time:	Auto
Resolution bandwidth:	F > 1 GHz: 1 MHz F < 1 GHz: 100 kHz
Video bandwidth:	Sweep: 100 kHz Remeasurement: 10 Hz / 3 MHz
Span:	30 MHz to 25 GHz
Trace-Mode:	Max Hold

### Limits:

FCC		IC
RX Spurious Emissions Radiated		
Frequency (MHz)	Field Strength (dB $\mu$ V/m)	Measurement distance
30 - 88	30.0	10
88 - 216	33.5	10
216 - 960	36.0	10
Above 960	54.0	3

### Results:

RX Spurious Emissions Radiated [dB $\mu$ V/m]		
F [MHz]	Detector	Level [dB $\mu$ V/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
No emissions detected between 1 GHz and 12.75 GHz.		
For emissions above 12.75 GHz, please take a look at the plots.		
Measurement uncertainty	$\pm$ 3 dB	

**Result: Passed.**

**Plots: RX / Idle – mode**

**Plot 1:** 30 MHz to 1 GHz, vertical & horizontal polarization


**Common Information**

EUT: TM-0030-BV  
 Serial Number: CB5A1NY07J  
 Test Description: FCC part 15 B class B @ 5 m  
 Operating Conditions: wlan idle+ charging  
 Operator Name: Wolsdorfer  
 Comment: USB powered

**Scan Setup: STAN\_Fin [EMI radiated]**

Hardware Setup: Electric Field (NOS)  
 Receiver: [ESCI 3]  
 Level Unit: dBµV/m


Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB




**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
46.979550	15.7	1000.0	120.000	98.0	V	261.0	13.3	14.3	30.0	
99.907950	13.3	1000.0	120.000	143.0	V	100.0	11.9	20.2	33.5	
166.572600	24.9	1000.0	120.000	98.0	V	100.0	9.6	8.6	33.5	
209.894250	18.9	1000.0	120.000	123.0	V	170.0	12.0	14.6	33.5	
232.934550	14.7	1000.0	120.000	120.0	V	10.0	12.8	21.3	36.0	
941.230500	22.1	1000.0	120.000	98.0	V	260.0	25.3	13.9	36.0	


Plot 2: 1 GHz to 12.75 GHz, vertical & horizontal polarization




Plot 3: 12.75 GHz to 18 GHz, vertical & horizontal polarization



Plot 4: 18 GHz to 26 GHz, vertical & horizontal polarization



Plot 5: 26 GHz to 40 GHz, vertical & horizontal polarization



## 9.12 Spurious emissions radiated < 30 MHz

### Description:

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The EUT is set to mid channel. This measurement is representative for all channels and modes. If peaks are found the lowest channel and the highest channel will be measured too. The measurement is performed with the data rate producing the highest output power. The limits are recalculated to a measurement distance of 3 m with 40 dB/decade according CFR Part 2.

### Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Video bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Resolution bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace-Mode:	Max Hold

### Limits:

FCC		IC
TX Spurious Emissions Radiated < 30 MHz		
Frequency (MHz)	Field Strength (dBµV/m)	Measurement distance
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30


### Results:

TX Spurious Emissions Radiated < 30 MHz [dBµV/m]		
F [MHz]	Detector	Level [dBµV/m]
No peaks found.		
Measurement uncertainty	± 3 dB	

**Result: Passed**


**Plots: TX mode**

**Plot 1: 9 kHz to 30 MHz**



**Plots: RX / Idle – mode**

**Plot 1: 9 kHz to 30 MHz**



### 9.13 Spurious emissions conducted < 30 MHz

**Description:**

Measurement of the conducted spurious emissions in transmit mode below 30 MHz. The EUT is set to mid channel. If peaks are found the lowest channel and the highest channel will be measured too. The measurement is performed with the data rate producing the highest output power. Both power lines, phase and neutral line, are measured. Found peaks are re-measured with average and quasi peak detection to show compliance to the limits.

**Measurement:**

Measurement parameter	
Detector:	Peak - Quasi Peak / Average
Sweep time:	Auto
Video bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Resolution bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace-Mode:	Max Hold

**Limits:**

FCC		IC	
TX Spurious Emissions Conducted < 30 MHz			
Frequency (MHz)	Quasi-Peak (dBµV/m)	Average (dBµV/m)	
0.15 – 0.5	66 to 56*	56 to 46*	
0.5 – 5	56	46	
5 – 30.0	60	50	

\*Decreases with the logarithm of the frequency


**Results:**

TX Spurious Emissions Conducted < 30 MHz [dBµV/m]		
F [MHz]	Detector	Level [dBµV/m]
No peaks detected. All detected peak values are below the average limits.		
Measurement uncertainty	± 3 dB	


**Result: Passed**

**Plots:**

**Plot 1:** TX mode, 150 kHz to 30 MHz, phase line




**Plot 2:** TX mode, 150 kHz to 30 MHz, neutral line






Plot 3: RX / Idle – mode, 150 kHz to 30 MHz, phase line



Plot 4: RX / Idle – mode, 150 kHz to 30 MHz, neutral line



## 10 Test equipment and ancillaries used for tests

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, rf-generating and signalling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Labor/Item).

No.	Lab / Item	Equipment	Type	Manufact.	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	45	Switch-Unit	3488A	HP Meßtechnik	2719A14505	300000368	g		
2	50	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP Meßtechnik	2920A04466	300000580	ne		
3	n. a.	software	SPS_PHE 1.4f	Spitzberger & Spieß	B5981; 5D1081;B597 9	300000210	ne		
4	n. a.	EMI Test Receiver	ESCI 3	R&S	100083	300003312	k	09.01.2013	09.01.2014
5	n. a.	Analyzer- Reference- System (Harmonics and Flicker)	ARS 16/1	SPS	A3509 07/0 0205	300003314	k	14.07.2011	14.07.2013
6	n. a.	Amplifier	JS42- 00502650- 28-5A	MITEQ	1084532	300003379	ev		
7	n. a.	Antenna Tower	Model 2175	ETS- LINDGREN	64762	300003745	izw		
8	n. a.	Positioning Controller	Model 2090	ETS- LINDGREN	64672	300003746	izw		
9	n. a.	Turntable Interface-Box	Model 105637	ETS- LINDGREN	44583	300003747	izw		
10	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbe ck	295	300003787	k	12.04.2012	12.04.2014
11	n. a.	Spectrum- Analyzer	FSU26	R&S	200809	300003874	k	16.01.2013	16.01.2014
12	n. a.	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP Meßtechnik	2818A03450	300001040	Ve	12.01.2012	12.01.2015
13	n. a.	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	8812-3088	300001032	viKI!	11.05.2011	11.05.2013
14	n. a.	Active Loop Antenna	6502	EMCO	2210	300001015	ne		
15	n. a.	Anechoic chamber	FAC 3/5m	MWB / TDK	87400/02	300000996	ev		
16	n. a.	Switch / Control Unit	3488A	HP Meßtechnik	*	300000199	ne		
17	n. a.	Switch / Control Unit	3488A	HP Meßtechnik	2719A15013	300001156	ne		
18	9	Isolating Transformer	MPL IEC625 Bus Regeltrennt ravo	Erfi	91350	300001155	ne		
19	n. a.	Three-Way Power Splitter, 50 Ohm	11850C	HP Meßtechnik		300000997	ne		
20	n. a.	Amplifier	js42- 00502650- 28-5a	Parzich GMBH	928979	300003143	ne		
21	n. a.	Highpass Filter	WHKX7.0/1 8G-8SS	Wainwright	18	300003789	ne		
22	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbe ck	371	300003854	viKI!	14.10.2011	14.10.2014
23	n. a.	MXE EMI	N9038A	Agilent	MY51210197	300004405	k	21.02.2013	21.02.2014

		Receiver 20 Hz bis 26,5 GHz		Technologies					
24	CR 79	Std. Gain Horn Antenna 26.5-40.0 GHz	V637	Narda	7911	300001751	ne		
25	11b	Microwave System Amplifier, 0.5-26.5 GHz	83017A	HP Meßtechnik	00419	300002268	ev		
26	A025	Std. Gain Horn Antenna 12.4 to 18.0 GHz	639	Narda		300000786	ne		
27	A027	Std. Gain Horn Antenna 18.0 to 26.5 GHz	638	Narda		300000486	ne		
28	n. a.	Spectrum Analyzer 20 Hz - 50 GHz	FSU50	R&S	200012	300003443	Ve	09.10.2012	09.10.2014
29	n. a.	Broadband Low Noise Amplifier 18-50 GHz	CBL18503 070-XX	CERNEX	19338	300004273	ne		
30	n. a.	Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517	k	22.10.2012	22.10.2013
31	n. a.	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP Meßtechnik	2920A04590	300001041	Ve	12.01.2012	12.01.2015
32	n. a.	DC Power Supply 0 – 32V	1108-32	Heiden	001802	300001383	Ve	23.06.2010	23.06.2013

**Agenda:** Kind of Calibration

k calibration / calibrated  
 ne not required (k, ev, izw, zw not required)  
 ev periodic self verification  
 Ve long-term stability recognized  
 vlk! Attention: extended calibration interval  
 NK! Attention: not calibrated

EK limited calibration  
 zw cyclical maintenance (external cyclical maintenance)  
 izw internal cyclical maintenance  
 g blocked for accredited testing  
 \*) next calibration ordered / currently in progress

## 11 Observations

No observations exceeding those reported with the single test cases have been made.

## Annex A Document history

Version	Applied changes	Date of release
1.0	Initial release	2013-04-10
A	Changed RSP100	2013-04-17

## Annex B Further information

### Glossary

AVG	-	Average
DUT	-	Device under test
EMC	-	Electromagnetic Compatibility
EN	-	European Standard
EUT	-	Equipment under test
ETSI	-	European Telecommunications Standard Institute
FCC	-	Federal Communication Commission
FCC ID	-	Company Identifier at FCC
HW	-	Hardware
IC	-	Industry Canada
Inv. No.	-	Inventory number
N/A	-	Not applicable
PP	-	Positive peak
QP	-	Quasi peak
S/N	-	Serial number
SW	-	Software

**Annex C Accreditation Certificate**

Front side of certificate



Back side of certificate



**Note:**

The current certificate including annex is published on our website (see link below) or may be received from CETECOM ICT Services on request.

<http://www.cetecom.com/eu/de/cetecom-group/europa/deutschland-saarbruecken/akkreditierungen.html>