

RF EXPOSURE REPORT

REPORT NO.: SA990202A02

MODEL NO.: CK-200

VERSION: Proto: B4.0D, HW: 1.0, BT SW: 0.69C,
RCU SW: 0.5B, MV: 1.0

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT : Nokia Corporation

ADDRESS : Joensuunkatu 7E P.O. Box 86 Salo, FIN-24100,
Finland

ISSUED BY : Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS : No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien, 244 Taiwan

Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	4.5	2.8
EIRP Power	8.2	6.6

***Note:** The antenna is F Type antenna with 3.71dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 6.6mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

---END---