



# RF EXPOSURE REPORT

**REPORT NO.:** SA960709A04

**MODEL NO.:** LD-4W

**VERSION:** PROTO: B4.2, HW: 3.0, BT SW: 2.4,  
GPS SW :3.2.5N01.6, MV: 3.0

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT :** NOKIA CORPORATION

**ADDRESS :** Keilalahdentie 2-4, 02150 Espoo, Finland

**ISSUED BY :** Advance Data Technology Corporation

**LAB ADDRESS :** No. 47, 14<sup>th</sup> Ling, Chia Pau Tsuen, Linko Hsiang  
244, Taipei Hsien, Taiwan, R.O.C.



## Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

	Pout (dBm)	Pout (mW)
Conducted Power	-2.91	0.512
EIRP Power	-2.56	0.555

**\*Note:** The antenna is Dipole antenna with 0.35dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 0.555mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold