

FCC Part 22/24/27 Compliance Test Report

Test Report no.:	FCC_Cellular_RM-1063_07_Ant2	Date of Report:	12-Jan-2015
Number of pages:	13	Customer's Contact person:	Jari Rontu
Testing laboratory:	TCC Microsoft Salo Laboratory P.O.Box(86) Joensuunkatu 7E FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 71 80 44122	Customer:	Microsoft P.O.Box(86) Joensuunkatu 7E FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 71 80 44122
FCC listing no.:	533467		
IC recognition no.:	661V-1		
Tested devices/ accessories:	Phone RM-1063 / Battery BV-T4V		
FCC ID:	PYARM-1063	IC:	-
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Parts 22/24/27, TIA-603-C-2004 and IC standards, RSS-GEN (Issue 4, November 2014), RSS-133 (Issue 6, January 2013), RSS-132 (Issue 3, January 2013), RSS-199 (Issue 2, October 2014), RSS-130 (Issue 1, October 2013), RSS-139 (Issue 2, February 2009). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Microsoft.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Sami Lehtonen, Specialist, EMC

1. Summary for FCC Part 22/24/27 Compliance Test Report

Date of receipt	18-Dec-2014
Testing completed	05-Jan-2015
The customer's contact person	Jari Rontu
Test Plan referred to	T:\Projects\RM-1063\TestPlan\RS_testplan_RM-1063.xlsm
Notes	-
Document name	T:\Projects\RM-1063\EMC\FCC_Cellular_RM-1063_07_Ant2.docx

1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:

GSM/WCDMA/WLAN/Bluetooth

The EUT is tested with maximum rated TX power.

Devices under tests

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-1063	356493060017073	6204	-	02154.00000.14501.24000	18955
Battery	BV-T4V	4181574345C1010324260670764	CCE	-	-	18707

1.2. Summary of Test Results

GSM 850:

Section in CFR 47	Section in RSS-GEN or RSS-132	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	NP
§22.913(a)	4.4	Radiated RF output power	PASSED
N/A	5.4	Peak to average power ratio	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§22.917(a)	4.5	Band edge compliance	NP
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	NP
§22.917(a), §2.1053	4.5	Spurious radiated emissions	NP
§2.1055(a)	4.3	Frequency stability, temperature variation	NP
§2.1055(d)	4.3	Frequency stability, voltage variation	NP

GSM 1900:

Section in CFR 47	Section in RSS-GEN or RSS-133	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§24.232(b)	6.4	Radiated RF output power	PASSED
N/A	6.4	Peak to average power ratio	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§24.238(a)	6.5	Band edge compliance	NP
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	NP
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

WCDMA2:

Section in CFR 47	Section in RSS-GEN or RSS-133	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§24.232(b)	6.4	Radiated RF output power	PASSED
N/A	6.4	Peak to average power ratio	NP

§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§24.238(a)	6.5	Band edge compliance	NP
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	NP
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

WCDMA5:

Section in CFR 47	Section in RSS-GEN or RSS-132	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	NP
§22.913(a)	4.4	Radiated RF output power	PASSED
N/A	5.4	Peak to average power ratio	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§22.917(a)	4.5	Band edge compliance	NP
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	NP
§22.917(a), §2.1053	4.5	Spurious radiated emissions	NP
§2.1055(a)	4.3	Frequency stability, temperature variation	NP
§2.1055(d)	4.3	Frequency stability, voltage variation	NP

LTE2:

Section in CFR 47	Section in RSS-GEN or RSS-133	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§24.232(b)	6.4	Radiated RF output power	PASSED
N/A	6.4	Peak to average power ratio	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§24.238(a)	6.5	Band edge compliance	NP
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§24.238(a), §2.1053	6.5	Spurious radiated emissions	NP
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

LTE5:

Section in CFR 47	Section in RSS-GEN or RSS-132	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	NP
§22.913(a)	4.4	Radiated RF output power	PASSED
N/A	5.4	Peak to average power ratio	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§22.917(a)	4.5	Band edge compliance	NP
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	NP
§22.917(a), §2.1053	4.5	Spurious radiated emissions	NP
§2.1055(a)	4.3	Frequency stability, temperature variation	NP
§2.1055(d)	4.3	Frequency stability, voltage variation	NP

LTE7:

Section in CFR 47	Section in RSS-GEN or RSS-199	Name of the test	Result
§2.1046(a)	4.4	Conducted RF output power	NP
§27.50(h)(2)	4.4	Radiated RF output power	PASSED
N/A	N/A	Peak to average power ratio	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§27.53(l)	4.5(b)	Band edge compliance	NP

§2.1051	4.5(b)	Spurious emissions at antenna terminals	NP
§27.53(l), §2.1053	4.5(b)	Spurious radiated emissions	NP
§27.54	4.3	Frequency stability, temperature variation	NP
§27.54	4.3	Frequency stability, voltage variation	NP

LTE12:

Section in CFR 47	Section in RSS-GEN or RSS-130	Name of the test	Result
§2.1046(a)	4.4	Conducted RF output power	NP
§27.50(c)10	4.4	Radiated RF output power	PASSED
N/A	N/A	Peak to average power ratio	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§27.53(f)	4.6	Band edge compliance	NP
§27.53(f)	4.6	Spurious emissions at antenna terminals	NP
§27.53(f)	4.6	Spurious radiated emissions	NP
§27.54	4.3	Frequency stability, temperature variation	NP
§27.54	4.3	Frequency stability, voltage variation	NP

LTE17:

Section in CFR 47	Section in RSS-GEN or RSS-130	Name of the test	Result
§2.1046(a)	4.4	Conducted RF output power	NP
§27.50(c)(10)	4.4	Radiated RF output power	PASSED
N/A	N/A	Peak to average power ratio	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§27.53(g)	4.6	Band edge compliance	NP
§27.53(g), §2.1051	4.6	Spurious emissions at antenna terminals	NP
§27.53(g), §2.1051	4.6	Spurious radiated emissions	NP
§2.1055(a)	4.3 (a)	Frequency stability, temperature variation	NP
§2.1055(d)	4.3 (a)	Frequency stability, voltage variation	NP

LTE4:

Section in CFR 47	Section in RSS-GEN or RSS-139	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	NP
§27.50(d)(4)	6.4	Radiated RF output power	PASSED
N/A	6.4	Peak to average power ratio	NP
§2.1049(h)	4.6.1	99 % occupied bandwidth	NP
§27.53(h)	6.5	Band edge compliance	NP
§27.53(h), §2.1051	6.5	Spurious emissions at antenna terminals	NP
§27.53(h), §2.1053	6.5	Spurious radiated emissions	NP
§2.1055(a)	6.3	Frequency stability, temperature variation	NP
§2.1055(d)	6.3	Frequency stability, voltage variation	NP

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Microsoft Laboratory.

CONTENTS


1. Summary for FCC Part 22/24/27 Compliance Test Report	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Radiated RF output power (FCC §24.232(b), §27.50(d)(4), §27.50(c)(10), §27.50(c)10, §27.50(h)(2), §22.913(a), RSS-133 6.4, RSS-132 4.4, RSS-199 4.4, RSS-130 4.4, RSS-139 6.4).....	6
2.2. Test method and limit	6
2.3. GSM 850 test results	7
2.4. GSM 850 E-GPRS (MSC9) test results.....	7
2.5. GSM 1900 test results	7
2.6. GSM 1900 E-GPRS (MSC9) test results.....	7
2.7. WCDMA2 test results	8
2.8. WCDMA5 test results	8
2.9. LTE2 test results.....	8
2.10. LTE4 test results.....	9
2.11. LTE5 test results.....	9
2.12. LTE7 test results.....	10
2.13. LTE12 test results.....	10
2.14. LTE17 test results.....	11
3. Test Equipment.....	12
3.1. Conducted measurements	12
3.2. Radiated measurements	12

2. Radiated RF output power

(FCC §24.232(b), §27.50(d)(4), §27.50(c)(10), §27.50(c)10, §27.50(h)(2), §22.913(a), RSS-133 6.4, RSS-132 4.4, RSS-199 4.4, RSS-130 4.4, RSS-139 6.4)

EUT with DUT number	RM-1063, DUT 18955
Accessories with DUT numbers	BV-T4V, DUT 18707
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	Measured from antenna 2.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 41 / 101.8
Date of measurements	05-Jan-2015
Measured by	Sami Lehtonen

2.1.1 Test setup



2.2. Test method and limit

The measurement is made according to TIA-603-C-2004 as follows:

The measurement is performed in the Anechoic Chamber with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system. The turntable is rotated 360 degrees and this is repeated for both horizontal and vertical receive antenna polarizations.

The EUT is placed on a nonconductive plate at 170 cm height.

The substitution method is used. The measurement results are obtained as described below:

$$P[dBm] = P_{SUBST\ TX} + P_{MEAS} - P_{SUBST\ RX} - L_{SUBST\ CABLES} + G_{SUBST\ TX\ ANT}$$

Where $P_{SUBST\ TX}$ is signal generator level. P_{MEAS} is measured power level from the EUT. $P_{SUBST\ RX}$ is measured power level in substitute measurement. $L_{SUBST\ CABLE}$ is the loss of the cable between the signal generator and the substitution antenna and $G_{SUBST\ TX\ ANT}$ is substitution antenna gain.

Limits for radiated RF output power measurements

Frequency range [MHz]	Limit [W]	Limit [dBm]
1850 - 1910	2 EIRP	33
824 - 849	7 ERP	38.5
2502.5 - 2567.5	2 EIRP	33
699 - 712	2 ERP	33
704 - 716	3 ERP	34.8

2.3. GSM 850 test results

RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
128 / 824.2	29.05	0.803	-7.1	36.15	VERTICAL	PASSED
190 / 836.6	28.47	0.703	-6.53	35	VERTICAL	PASSED
251 / 848.8	27.52	0.565	-6.51	34.03	VERTICAL	PASSED

2.4. GSM 850 E-GPRS (MSC9) test results

RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
128 / 824.2	25.91	0.39	-10.24	36.15	VERTICAL	PASSED
190 / 836.6	24.88	0.308	-10.35	35.23	HORIZONTAL	PASSED
251 / 848.8	23.9	0.246	-10.13	34.03	VERTICAL	PASSED

2.5. GSM 1900 test results

RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
512 / 1850.2	30.93	1.239	-14.07	45	HORIZONTAL	PASSED
661 / 1880	32.55	1.798	-12.63	45.18	HORIZONTAL	PASSED
810 / 1909.8	32.62	1.83	-12.66	45.28	HORIZONTAL	PASSED

2.6. GSM 1900 E-GPRS (MSC9) test results

RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
512 / 1850.2	28.47	0.703	-16.53	45	HORIZONTAL	PASSED
661 / 1880	30.3	1.071	-14.88	45.18	HORIZONTAL	PASSED
810 / 1909.8	29.69	0.931	-15.59	45.28	HORIZONTAL	PASSED

2.7. WCDMA2 test results

RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
9262 / 1852.4	23.8	0.24	-21.16	44.96	HORIZONTAL	PASSED
9400 / 1880	24.63	0.29	-20.55	45.18	HORIZONTAL	PASSED
9538 / 1907.6	24.61	0.289	-20.7	45.31	HORIZONTAL	PASSED

2.8. WCDMA5 test results

RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
4132 / 826.4	19.35	0.086	-16.72	36.07	VERTICAL	PASSED
4175 / 835	18.24	0.067	-16.87	35.11	VERTICAL	PASSED
4233 / 846.6	17.97	0.063	-16.2	34.17	VERTICAL	PASSED

2.9. LTE2 test results

FDD, CBW 5MHz, QPSK, 1RB mid, RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
26065 / 1852.5	23.3	0.214	-21.66	44.96	HORIZONTAL	PASSED
18900 / 1880	26.08	0.405	-19.1	45.18	HORIZONTAL	PASSED
19175 / 1907.5	26	0.398	-19.31	45.31	HORIZONTAL	PASSED

FDD, CBW 5MHz, 16QAM, 1RB mid, RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
26065 / 1852.5	23.08	0.203	-21.88	44.96	HORIZONTAL	PASSED
18900 / 1880	26.25	0.422	-18.93	45.18	HORIZONTAL	PASSED
19175 / 1907.5	25.92	0.391	-19.39	45.31	HORIZONTAL	PASSED

2.10. LTE4 test results

FDD, CBW 5MHz, QPSK, 1RB mid, RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
19975 / 1712.5	25.88	0.388	-18.38	44.26	HORIZONTAL	PASSED
20175 / 1732.5	25.48	0.353	-18.81	44.29	HORIZONTAL	PASSED
20375 / 1752.5	24.33	0.271	-20.35	44.68	HORIZONTAL	PASSED

FDD, CBW 5MHz, 16QAM, 1RB mid, RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
19975 / 1712.5	25.59	0.362	-18.67	44.26	HORIZONTAL	PASSED
20175 / 1732.5	25.71	0.372	-18.58	44.29	HORIZONTAL	PASSED
20375 / 1752.5	24.61	0.289	-20.07	44.68	HORIZONTAL	PASSED

2.11. LTE5 test results

FDD, CBW 5MHz, QPSK, 1RB mid, RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
20425 / 826.5	19.85	0.097	-16.21	36.06	VERTICAL	PASSED
20525 / 836.5	19.35	0.086	-15.65	35	VERTICAL	PASSED
20625 / 846.5	18.2	0.066	-15.97	34.17	VERTICAL	PASSED

FDD, CBW 5MHz, 16QAM, 1RB mid, RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
20425 / 826.5	19.75	0.094	-16.31	36.06	VERTICAL	PASSED
20525 / 836.5	19.31	0.085	-15.69	35	VERTICAL	PASSED
20625 / 846.5	17.99	0.063	-16.18	34.17	VERTICAL	PASSED

2.12. LTE7 test results

FDD, CBW 5MHz, QPSK, 1RB mid, RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
20775 / 2502.5	22.79	0.19	-26.28	49.07	HORIZONTAL	PASSED
21100 / 2535	22.53	0.179	-26.64	49.17	HORIZONTAL	PASSED
21425 / 2567.5	23.03	0.201	-26.32	49.35	HORIZONTAL	PASSED

FDD, CBW 5MHz, 16QAM, 1RB mid, RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
20775 / 2502.5	22.7	0.186	-26.37	49.07	HORIZONTAL	PASSED
21100 / 2535	22.69	0.186	-26.48	49.17	HORIZONTAL	PASSED
21425 / 2567.5	23.13	0.205	-26.22	49.35	HORIZONTAL	PASSED

2.13. LTE12 test results

FDD, CBW 5MHz, QPSK, 1RB mid, RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
23035 / 701.5	19.11	0.082	-13.96	33.07	HORIZONTAL	PASSED
23095 / 707.5	19.41	0.087	-15	34.41	VERTICAL	PASSED
23155 / 713.5	19.74	0.094	-15.11	34.85	VERTICAL	PASSED

FDD, CBW 5MHz, 16QAM, 1RB mid, RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
23035 / 701.5	19.14	0.082	-14.71	33.85	VERTICAL	PASSED
23095 / 707.5	19.76	0.095	-14.65	34.41	VERTICAL	PASSED
23155 / 713.5	19.96	0.099	-14.89	34.85	VERTICAL	PASSED

2.14. LTE17 test results

FDD, CBW 5MHz, QPSK, 1RB mid, RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
23755 / 706.5	19.36	0.086	-13.61	32.97	HORIZONTAL	PASSED
23790 / 710	19.78	0.095	-14.89	34.67	VERTICAL	PASSED
23825 / 713.5	19.87	0.097	-14.98	34.85	VERTICAL	PASSED

FDD, CBW 5MHz, 16QAM, 1RB mid, RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
23755 / 706.5	19.56	0.09	-14.77	34.33	VERTICAL	PASSED
23790 / 710	19.77	0.095	-14.9	34.67	VERTICAL	PASSED
23825 / 713.5	20	0.1	-14.85	34.85	VERTICAL	PASSED

3. Test Equipment

3.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
6039	USB Interface	5541765	Testo	22/24/27, 15C, 15B
6044	V-network	ESH3-Z6	R&S	-
2059	V-network	ESH3-Z6	R&S	-
1759	LISN 50 µH	ESH3-Z5	R&S	22/24/27, 15C, 15B
2097	Pulse Limiter	ESH3-Z2	R&S	22/24/27, 15C, 15B
1999	Receiver	ESIB26	R&S	22/24/27, 15C, 15B
2180	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2390	Directional Coupler	DC2600	AR	-
-	RF immunity / Emission Software	EMC32	R&S	22/24/27, 15C, 15B
2060	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
1759	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
2039	Power Supply	PL330QMD	Thurlby	15C, 15B
6036	Data Logger	175-H2	Testo	22/24/27, 15C, 15B
2359	Temperature Test Chamber	VT4002	Vötsch	22/24/27
2352	Spectrum Analyzer	FSP-30	R&S	22/24/27, 15C
6109	Communication Tester	CMU200	R&S	22/24/27, 15C
6246	Power Supply	66332A	HP	22/24/27, 15C
1992	Signal Generator	83630B	Agilent	15C, 15B
6098	Signal Generator	8648C	Agilent	-
6046	Attenuator 10dB	8493C	Agilent	22/24/27, 15C
6047	Attenuator 20dB	8493C	Agilent	22/24/27, 15C
6045	Power splitter	11667B	Agilent	22/24/27, 15C
6247	Communication Tester	CBT	R&S	22/24/27, 15C 15B
6052	Communication Tester	CMU200	R&S	22/24/27, 15C 15B
6248	Power Supply	6632B	-	22/24/27, 15C 15B
6106	Spectrum Analyzer	FSP-30	R&S	22/24/27, 15C 15B
6113	Signal Generator	SMF100A	R&S	22/24/27, 15C 15B
6202	Temperature Test Chamber	VT4002	Vötsch	22/24/27, 15C 15B
6122	Power Splitter	11667B	Agilent	22/24/27, 15C 15B
6134	Attenuator 10dB	BW-S10-2W263+	Mini-Circuits	22/24/27, 15C
6136	Attenuator 20dB	BW-S20-2W263+	Mini-Circuits	22/24/27, 15C
6103	Bluetooth tester	CBT	R&S	22/24/27, 15C 15B
6250	Power Supply	6651A	Agilent	22/24/27, 15C 15B
6108	Communication Tester	CMU200	R&S	22/24/27, 15C 15B
6105	Spectrum Analyzer	FSV-30	R&S	22/24/27, 15C 15B
6251	Temperature Test Chamber	VT4002	Vötsch	22/24/27, 15C 15B
6243	Power Splitter	1167B	Agilent	22/24/27, 15C 15B
6245	Attenuator 10dB	BW-S10-2W263+	Mini-Circuits	22/24/27, 15C 15B
6244	Attenuator 20dB	BW-S20-2W263+	Mini-Circuits	22/24/27, 15C 15B

3.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
2388	Bluetooth Tester	CBT	R&S	15B
10479	Communication Tester	CMW500	R&S	22/24/27, 15C, 15B
2347	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
2009	Signal Generator	SMP 22	R&S	22/24/27, 15C, 15B
2348	Controller	G-1000DXC	Yaesu	22/24/27, 15C, 15B
2349	Computer Controller	g-1000DXC	Yaesu	22/24/27, 15C, 15B
2116	Controller	EMCO 2090	ETS	22/24/27, 15C, 15B
2109	Power Supply	PL330QMD	Thurlby	22/24/27, 15C, 15B
2353	Receiver	ESIB26	R&S	22/24/27, 15C, 15B
6115	Open switch and control unit	OSP 130	R&S	22/24/27, 15C 15B
6116	Open switch and control unit	OSP 150	R&S	22/24/27, 15C 15B

Eq. No	Equipment	Type	Manufacturer	Used in
6117	Open switch and control unit	OSP 150	R&S	22/24/27, 15C, 15B
6131	Notch Filter	WRCT902.4-0.4/40-8SS	Wainwright	22/24/27, 15C, 15B
6130	Notch Filter	WRCD1880-1.1.25/50-10SS	Wainwright	22/24/27
6159	Band Reject Filter	WRCD1747.8-0.4/40-5SS	Wainwright	22/24/27, 15C, 15B
6158	Band Reject Filter	WRCT836.6-0.4/40-8SS	Wainwright	22/24/27, 15C, 15B
6197	Band Reject Filter	WRCJV2531/2539-2523/2547-60/12SS	Wainwright	22/24/27, 15C, 15B
2231	Band Reject Filter	WRCG1947/1953-1940/1960-40/6SS	Wainwright	22/24/27, 15C, 15B
2391	Band Reject Filter	WRCG1729.4/1735.4-1722.4/1742.4-40/6SS	Wainwright	27
2386	Band Reject Filter	WRCG1764.4/1770.4-1760.4/1774.4-40/6SS	Wainwright	22/24/27, 15C, 15B
2385	Band Reject Filter	WRCG1744.4/1750.4-1740.4/1754.4-40/6SS	Wainwright	22/24/27, 15C, 15B
2357	Band Reject Filter	WRCG2400/2483-2390/2493-35/10SS	Wainwright	15C
2188	Preamplifier	AFS4-00100300-20-23P-6	Miteq	22/24/27, 15C, 15B
6195	High Pass Filter	-	Wainwright	22/24/27, 15C, 15B
2364	Band Reject Filter	WRCG1877/1883 - 1870/1890-40/6SS	Wainwright	24
2361	Anechoic Chamber	3 m Semi / Full Anechoic Chamber	Euroshield	22/24/27, 15C, 15B
6212	Antenna Array system	-	TCC	22/24/27, 15C, 15B
-	RF immunity / Emission Software	EMC32	R&S	22/24/27, 15C, 15B
6089	Antenna	HFH2-Z2	R&S	15C, 15B
2027	CDN	M2 (modified) DC1	MEB	22/24/27, 15C, 15B
2028	CDN	M3 (modified) DC2	MEB	22/24/27, 15C, 15B
2176	CDN	CDN 801-M3	Lüthi	22/24/27, 15C, 15B
2135	CDN	CDN 801-M3	Lüthi	22/24/27, 15C, 15B
2029	Power Supply	PL330	Thurlby	22/24/27, 15C
6038	Data Logger	Testo 580	Testo	22/24/27, 15C, 15B
6037	Data Logger	175-H2	Testo	22/24/27, 15C, 15B
6039	USB Interface	5541765	Testo	22/24/27, 15C, 15B