

FCC RF EXPOSURE REPORT

FCC ID: Q3N-1564A

Project No. : 1411078
Equipment : BT Barcode Scanner
Model : 1564A
Applicant : CIPHERLAB CO., LTD.
Address : 12F, 333, Dunhua S. Rd., Sec. 2, Taipei, Taiwan

**According: : FCC Guidelines for Human Exposure IEEE
C95.1**

BTL Inc.

B1, No. 37, Lane 365, YangGuang St., NeiHu District 114, Taipei, Taiwan

TEL : (0769) 8318-3000 FAX : (0769) 8319-6000

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	Cipherlab	1564 BT Antenna	PIFA	N/A	-0.074

GENERAL CONCLUSION:

Maximum measured transmitter power:

Output Power (dBm)	Output Power (mW)	Limit (mW)
7.61	5.8	10
4.03	2.5	10

According to FCC KDB447498 V05, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 5.8mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold