



TEST REPORT

Report No. : AF004602-001 Date : 2005 March 17

Application No.: LF202625(6)

Applicant : Early Light Industrial Co., Ltd.
Early Light International Centre,
No. 9, Ka Fu Close, Sheung Shui,
N. T., Hong Kong.

Sample Description : One(1) submitted sample stated to be 1/24 Bobble Head RC Car
of Model No. WC165
Rating : 4 x 1.5V "AA" size battery
No. of sample(s) : Three (3) set(s) ***

Date Received : 2005 February 17

Test Period : 2005 February 17 – 2005 March 02

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – April 2004
ANSI C63.4 – 2001

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC
Part 15 Subpart B.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature : _____

Danny Chui
EMC Engineer - EL. Division

Page 1 of 11

FCC ID : Q4RWC165R



TEST REPORT

Report No. : AF004602-001

Date : 2005 March 17

Table of Contents

1	General Information	3
1.1	General Description	3
1.2	Related Submittal Grants	3
1.3	Location of the test site	4
1.4	List of measuring equipment	5
2	Description of the radiated emission test	6
2.1	Test Procedure	6
2.2	Test Result	6
2.3	Radiated Emission Measurement Data	7
3	Description of the Line-conducted Test	8
3.1	Test Procedure	8
3.2	Test Result	8
3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Photograph	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9
4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supplementary document	10
5.1	Bandwidth	10
5.2	Duty cycle	10
6	Appendices	11



TEST REPORT

Report No. : AF004602-001

Date : 2005 March 17

Test Result :

1 General Information

1.1 General Description

The equipment under test (EUT) is a superregenerative receiver for 1/24 Bobble Head RC Car. Operating at 49.860 MHz which is controlled by a LRC circuit. The EUT is powered by 4 x 1.5V "AA" size battery. When it power on, it can receive forward, backward, turn left and turn right radio signal and go difference direction.

The brief circuit description is listed as follows:

- Q1 and associated circuit act as super-regenerative circuit
- IC2 and associated circuit act as decoder
- Q14 and associated circuit act as voltage regulator
- Q8 ~ Q13 and associated circuit act as forward of backward motor control
- Q2 ~ Q7 and associated circuit act as turn left & turn right motor control

1.2 Related Submittal Grants

This is a single application for certification of a receiver. The transmitter for this receiver is authorized by Certification procedure.



TEST REPORT

Report No. : AF004602-001

Date : 2005 March 17

Test Result :

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2001. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2001. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AF004602-001

Date : 2005 March 17

Test Result :

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S21141
Broadband Antenna	Schaffner	CBL6113B	2718	AC1753
Signal Generator	IFR	2023B	202302/938	Nil
LISN	R&S	ESH3-Z5	100038	S21142
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02



TEST REPORT

Report No. : AF004602-001

Date : 2005 March 17

Test Result :

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2001.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to “cohere” the characteristic broadband emissions from the receiver.

2.2 Test Result

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasipeak detector.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AF004602-001

Date : 2005 March 17

Test Result :

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
48.535	V	20.9	10.3	31.2	40.0	-8.8
48.977	V	20.0	10.3	30.3	40.0	-9.7
52.220	V	25.3	8.1	33.4	40.0	-6.6
52.514	V	24.9	8.1	33.0	40.0	-7.0
54.350	V	22.7	8.1	30.8	40.0	-9.2
94.940	V	12.3	9.2	21.5	43.5	-22.0
95.280	V	13.4	9.2	22.6	43.5	-20.9
143.620	V	11.6	11.9	23.5	43.5	-20.0
144.792	V	12.3	11.9	24.2	43.5	-19.3
146.420	V	12.7	11.9	24.6	43.5	-18.9



TEST REPORT

Report No. : AF004602-001

Date : 2005 March 17

Test Result :

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2001. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AF004602-001

Date : 2005 March 17

Test Result :

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



TEST REPORT

Report No. : AF004602-001

Date : 2005 March 17

Test Result :

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

a. Bandwidth

N/A

b. The duty cycle is simply the on-time divided by the period:

N/A



TEST REPORT

Report No. : AF004602-001

Date : 2005 March 17

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1 page
A2.	Photos of External Configurations	1 page
A3.	Photos of Internal Configurations	1 page
A4.	ID Label/Location	1 page
A5.	Block Diagram	1 page
A6.	Schematics	1 page
A7.	User Manual	4 pages
A8.	Operation Description	1 page

***** End of Report *****