



FCC CFR47 PART 15 SUBPART C  
FCC CFR47 PART 15 SUBPART B  
INDUSTRY CANADA RSS-210 ISSUE 8  
INDUSTRY CANADA RSS-GEN ISSUE 3

**CERTIFICATION TEST REPORT**

**FOR**

**Wireless Card Reader**

**MODEL NUMBER: ViVOpay 4800**

**FCC ID: Q55VIVOPAY4800  
IC: 5141A-VP4800**

**REPORT NUMBER: 11U13961-1, Revision B**

**ISSUE DATE: AUGUST 15, 2011**

*Prepared for*  
**ViVotech, Inc.**  
**451 EL CAMINO REAL**  
**SANTA CLARA, CA 95050, U.S.A.**

*Prepared by*  
**COMPLIANCE CERTIFICATION SERVICES**  
**47173 BENICIA STREET**  
**FREMONT, CA 94538, U.S.A.**  
**TEL: (510) 771-1000**  
**FAX: (510) 661-0888**

**NVLAP**<sup>®</sup>

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	08/08/11	Initial Issue	F. Ibrahim
A	08/12/11	Corrected corrupt Maximum Output Table	A. Zaffar
B	08/15/11	Revised model number	A. Zaffar

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>4</b>
<b>2. TEST METHODOLOGY .....</b>	<b>5</b>
<b>3. FACILITIES AND ACCREDITATION.....</b>	<b>5</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>5</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION .....</i>	5
4.2. <i>SAMPLE CALCULATION.....</i>	5
4.3. <i>MEASUREMENT UNCERTAINTY.....</i>	5
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>6</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	6
5.2. <i>MAXIMUM OUTPUT POWER.....</i>	6
5.3. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	7
5.4. <i>SOFTWARE AND FIRMWARE .....</i>	7
5.5. <i>WORST-CASE CONFIGURATION AND MODE.....</i>	7
5.6. <i>DESCRIPTION OF TEST SETUP.....</i>	8
<b>6. TEST AND MEASUREMENT EQUIPMENT .....</b>	<b>10</b>
<b>7. RADIATED EMISSION TEST RESULTS.....</b>	<b>11</b>
7.1. <i>LIMITS AND PROCEDURE .....</i>	11
7.1.1. <i>FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz): .....</i>	13
7.1.2. <i>TX/RX SPURIOUS EMISSION 30 TO 1000 MHz .....</i>	14
<b>8. AC MAINS LINE CONDUCTED EMISSIONS.....</b>	<b>17</b>
<b>9. FREQUENCY STABILITY.....</b>	<b>21</b>
<b>10. 99% BANDWIDTH.....</b>	<b>23</b>
<b>11. MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>25</b>
<b>12. SETUP PHOTOS .....</b>	<b>28</b>

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** ViVOtech, Inc.  
451 EL CAMINO REAL  
SANTA CLARA, CA 95050, U.S.A.

**EUT DESCRIPTION:** Wireless Card Reader

**MODEL:** ViVOpay 4800

**SERIAL NUMBER:** 402

**DATE TESTED:** August 1 – 3, 2011

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	Pass
FCC PART 15 SUBPART B	Pass
INDUSTRY CANADA RSS-210 Issue 8	Pass
INDUSTRY CANADA RSS-GEN Issue 3	Pass

Compliance Certification Services, Inc. (CCS) tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by CCS based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For CCS By:



---

FRANK IBRAHIM  
EMC SUPERVISOR  
COMPLIANCE CERTIFICATION SERVICES

Tested By:



---

WILLIAM ZHUANG  
EMC ENGINEER  
COMPLIANCE CERTIFICATION SERVICES

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4-2009, FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 3, and RSS-210 Issue 8.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

### 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 1000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

ViVOpay 4800 is a Wireless Card Reader. It operates at 13.56 MHz.



### 5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum E field as follows:

Frequency (MHz)	Mode	Fundamental E field @ 10m distance (dBuV/m)
13.56	Normal TX mode	53.65

The transmitter has a maximum E-field at 10m distance as follows:

EIRP = E field at 3m distance – 95.2

E field at 3m distance = E field at 10m distance + 20 = 53.65 + 20 = 73.65 dBuV/m

EIRP = 73.65 -95.2 = **-21.55 dBm**

### **5.3. DESCRIPTION OF AVAILABLE ANTENNAS**

The 13.56MHz antenna is integrated inside the product, around the LCD area invisible to the user.

### **5.4. SOFTWARE AND FIRMWARE**

The firmware installed in the EUT during testing was HG3-AR 2.1.0.

### **5.5. WORST-CASE CONFIGURATION AND MODE**

EUT powered by AC/DC adapter and connected to laptop PC.

## 5.6. DESCRIPTION OF TEST SETUP


### SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number / Part Number	FCC ID
AC/DC adapter	Global Power	3A-161WP09	GPWAC-15-09-VT	N/A
Laptop PC	DELL	Latitude D610	CN-0U8082-48643-5CE-5546	DoC
AC/DC adapter	DELL	HA65NS1-00	CN-0HN662-47890-79I-C03L	N/A

### I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	DC	1	DC	Unshielded	2m	Ferrite at one end
2	AC	1	AC	Unshielded	1m	N/A
2	DC	1	DC	Unshielded	2m	N/A
2	Serial	1	RS232	Unshielded	0.8m	N/A

**SETUP DIAGRAM FOR TESTS**



## 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	S/N	Cal Due
LISN, 10 kHz ~ 30 MHz	Solar	8012-50-R-24-BNC	N02481	11/05/11
LISN, 30 MHz	FCC	LISN-50/250-25-2	N02625	11/06/11
EMI Test Receiver, 30 MHz	R & S	ESHS 20	N02396	05/06/12
Temperature / Humidity Chamber	Thermotron	SE 600-10-10	C00930	04/11/12
Antenna, Loop, 30 MHz	EMCO	6502	C00593	01/12/12
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C00996	10/29/11
Bilog Antenna	Sunol Science	JB1	A121003	07/14/12
Pre-amplifier	Agilent / HP	8447D	1937A02062	07/06/12

## 7. RADIATED EMISSION TEST RESULTS

### 7.1. LIMITS AND PROCEDURE

#### LIMIT

§15.225

IC RSS-210, Section 2.6 (Transmitter)  
IC RSS-GEN, Section 6 (Receiver)

(a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/ meter at 30 meters.

(b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

(c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

(d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz and shall not exceed the general radiated emission limits in § 15.209 as follows:

§15.209 (a) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Limits for radiated disturbance of an intentional radiator		
Frequency range (MHz)	Limits ( $\mu$ V/m)	Measurement Distance (m)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 – 88	100**	3
88 - 216	150**	3
216 – 960	200**	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g. §§ 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

Formula for converting the field strength from uV/m to dBuV/m is:

Limit (dBuV/m) = 20 log limit (uV/m)

In addition:

§15.209 (d) The emission limits shown the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

§15.209 (d) The provisions in §§ 15.225, measuring emissions at distances other than the distances specified in the above table, determining the frequency range over which radiated emissions are to be measured, and limiting peak emissions apply to all devices operated under this part.

### **TEST PROCEDURE**

ANSI C63.4

The EUT is an intentional radiator that incorporates a digital device, the highest fundamental frequency generated or used in the device is 90 MHz; therefore, the frequency range was investigated from 30 MHz to 1000 MHz.

The EUT uses the following frequencies:  
32 kHz, 13.56 MHz, 24 MHz and 27.12 MHz

## RESULTS

### 7.1.1. FUNDAMENTAL AND SPURIOUS EMISSIONS (0.15 – 30 MHz):


FCC Part 15, Subpart B & C 10 Meter Distance Measurement At Open Field											
Frequency (MHz)	PK (dBu/V)	QP (dBu/V)	AV (dBuV)	AF dB/m	Distance Correction (dB)	PK Corrected Reading (dBuV/m)	AV Corrected Reading (dBuV/m)	QP Limit (dBuV/m)	AV Limit (dBuV/m)	PK Margin (dB)	Notes
<b>Loop Antenna Face On:</b>											
13.56	62.17		N/A	10.56	-19.08	53.65	N/A	84.00	N/A	-30.4	Fundamental @10m Dist
13.553	48.57		N/A	10.56	-19.08	40.05	N/A	50.47	N/A	-10.4	Spurious @10m Dist
13.567	48.88		N/A	10.56	-19.08	40.36	N/A	50.47	N/A	-10.1	Spurious @10m Dist
13.42	38.52		N/A	10.54	-19.08	29.98	N/A	50.47	N/A	-20.5	Spurious @10m Dist
13.71	35.8		N/A	10.57	-19.08	27.29	N/A	50.47	N/A	-23.2	Spurious @10m Dist
13.41	23.19		N/A	10.54	-19.08	14.65	N/A	40.51	N/A	-25.9	Spurious @10m Dist
13.72	34.36		N/A	10.57	-19.08	25.85	N/A	40.51	N/A	-14.7	Spurious @10m Dist
13.4	23.42		N/A	10.54	-19.08	14.88	N/A	40.51	N/A	-25.6	Spurious @10m Dist
13.73	28.64		N/A	10.57	-19.08	20.13	N/A	40.51	N/A	-20.4	Spurious @10m Dist
13.112	17.18		N/A	10.51	-19.08	8.61	N/A	40.51	N/A	-31.9	Spurious @10m Dist
14.283	25.36		N/A	10.63	-19.08	16.91	N/A	29.54	N/A	-12.6	Spurious @10m Dist
27.12	35.49		N/A	9.046	-19.08	25.46	N/A	29.54	N/A	-4.1	Spurious @10m Dist
<b>Loop Antenna Face Off:</b>											
13.56	59.5		N/A	10.56	-19.08	50.98	N/A	84.00	N/A	-33.0	Fundamental @10m Dist
13.41	35.85		N/A	10.54	-19.08	27.31	N/A	40.51	N/A	-13.2	Spurious @10m Dist
13.553	45.9		N/A	10.56	-19.08	37.38	N/A	50.47	N/A	-13.1	Spurious @10m Dist
13.567	46.21		N/A	10.56	-19.08	37.69	N/A	50.47	N/A	-12.8	Spurious @10m Dist
13.66	33.13		N/A	10.57	-19.08	24.62	N/A	50.47	N/A	-25.9	Spurious @10m Dist
13.186	31.69		N/A	10.52	-19.08	23.13	N/A	40.51	N/A	-17.4	Spurious @10m Dist
13.85	31.69		N/A	10.59	-19.08	23.20	N/A	40.51	N/A	-17.3	Spurious @10m Dist
27.12	30.26		N/A	9.046	-19.08	20.23	N/A	29.54	N/A	-9.3	Spurious @10m Dist


\* No more emissions were found up to 30MHz

Note: The emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 10000Mhz. Radiated emission limits in these three bands are based on measurements employing an average detector.

P.K. = Peak  
Q.P. = Quasi Peak Readings  
A.F. = Antenna factor

### 7.1.2. TX/RX SPURIOUS EMISSION 30 TO 1000 MHz





HORIZONTAL AND VERTICAL DATA

Range 1 30 - 1000MHz														
Test Frequency	Meter Reading	Detector	5m A			10m to 3m			CFR 47 Part 15 Class B		CFR 47 Part 15 Class A		Height [cm]	Polarity
			Cable below 1GHz.TXT [dB]	5m A T64 PreAmp below 1GHz.TXT [dB]	5m A T122 BiLog below 1GHz.TXT [dB]	Conversion [dB]	dBuV/m	Margin	Margin	Margin	Margin			
129.6363	55.8	PK	1.2	-28.2	13.5	-10.5	31.8	33.1	-1.3	43.5	-11.7	200	Horz	
359.9241	54.36	PK	2.1	-27.9	14.3	-10.5	32.36	35.6	-3.24	46.4	-14.04	100	Horz	
720.0879	51.56	PK	3	-27.1	19.9	-10.5	36.86	35.6	1.26	46.4	-9.54	100	Horz	
766.4169	47.37	PK	3.1	-27.1	20.5	-10.5	33.37	35.6	-2.23	46.4	-13.03	100	Horz	
810.2258	52.62	PK	3.2	-27.2	21.1	-10.5	39.22	35.6	3.62	46.4	-7.18	100	Horz	
e 2 30 - 1000MHz														
Test Frequency	Meter Reading	Detector	5m A			10m to 3m			CFR 47 Part 15 Class B		CFR 47 Part 15 Class A		Height [cm]	Polarity
			Cable below 1GHz.TXT [dB]	5m A T64 PreAmp below 1GHz.TXT [dB]	5m A T122 BiLog below 1GHz.TXT [dB]	Conversion [dB]	dBuV/m	Margin	Margin	Margin	Margin			
40.6615	52.4	PK	0.7	-28.3	13.5	-10.5	27.8	29.6	-1.8	39.1	-11.3	100	Vert	
60.2398	54.7	PK	0.8	-28.3	7.9	-10.5	24.6	29.6	-5	39.1	-14.5	100	Vert	
129.6363	54.32	PK	1.2	-28.2	13.5	-10.5	30.32	33.1	-2.78	43.5	-13.18	100	Vert	
810.2258	42.53	PK	3.2	-27.2	21.1	-10.5	29.13	35.6	-6.47	46.4	-17.27	100	Vert	

## 8. AC MAINS LINE CONDUCTED EMISSIONS

### LIMITS

§15.207  
IC RSS-GEN, Section 7.2.2

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Notes:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### TEST PROCEDURE

ANSI C63.4


## RESULTS

### **FIRST CONFIGURATION:**


#### **6 WORST EMISSIONS**

Project:11U13961									
Line-L1 .15 - 30MHz									
Test Frequency	Meter Reading	Detector	LISN [dB]	Conducted Emission		Class B QP Limit	Margin	Class B	
				Cable [dB]	dB[uVolt s]			Avg Limit	Margin
0.3165	53.51	PK	0	0	53.51	59.8	-6.29	49.8	3.71
0.6045	54.24	PK	0	0	54.24	56	-1.76	46	8.24
11.3685	51.83	PK	0	0	51.83	60	-8.17	50	1.83
0.3165	39.7	Av	0	0	39.7	59.8	-20.1	49.8	-10.1
0.6045	40.37	Av	0	0	40.37	56	-15.63	46	-5.63
11.3685	38.99	Av	0	0	38.99	60	-21.01	50	-11.01
e-L2 .15 - 30MHz									
Test Frequency	Meter Reading	Detector	LISN [dB]	Conducted Emission		Class B QP Limit	Margin	Class B	
				Cable [dB]	dB[uVolt s]			Avg Limit	Margin
0.3165	50.04	PK	0	0	50.04	59.8	-9.76	49.8	0.24
0.5685	53.62	PK	0	0	53.62	56	-2.38	46	7.62
11.3685	51.69	PK	0	0	51.69	60	-8.31	50	1.69
0.3165	37.54	Av	0	0	37.54	59.8	-22.26	49.8	-12.26
0.5685	39.61	Av	0	0	39.61	56	-16.39	46	-6.39
11.4585	36.55	Av	0	0	36.55	60	-23.45	50	-13.45

## LINE 1 RESULTS



**LINE 2 RESULTS**



## 9. FREQUENCY STABILITY

### LIMIT

§15.225 (e) The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency, over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### TEST PROCEDURE

ANSI C63.4:2009

**RESULTS**

Reference Frequency: EUT Channel 13.56 MHz @ 20°C Limit: $\pm 100$ ppm = 135.600 kHz				
Power Supply (Vac)	Environment Temperature (°C)	Frequency Deviation Measured with Time Elapse		
		(MHz)	Delta (ppm)	Limit (ppm)
115.00	50	13.5601012	-0.066	$\pm 100$
115.00	40	13.5600414	-0.022	$\pm 100$
115.00	30	13.5600223	-0.007	$\pm 100$
<b>115.00</b>	<b>20</b>	<b>13.5600122</b>	<b>0.000</b>	<b><math>\pm 100</math></b>
115.00	10	13.5600236	-0.008	$\pm 100$
115.00	0	13.5600323	-0.015	$\pm 100$
115.00	-10	13.5600376	-0.019	$\pm 100$
115.00	-20	13.5600386	-0.019	$\pm 100$
97.15	20	13.5600132	-0.001	$\pm 100$
132.25	20	13.5600098	0.002	$\pm 100$

## 10. 99% BANDWIDTH

### LIMITS

None; for reporting purposes only.


### TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

### RESULTS

Frequency (MHz)	99% Bandwidth kHz
13.56	1.0232

**99% BANDWIDTH**



## 11. MAXIMUM PERMISSIBLE EXPOSURE

### FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842f	4.89f	*(900f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824f	2.19f	*(180f <sup>2</sup> )	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

## IC RULES

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

**Table 5**  
**Exposure Limits for Persons Not Classed As RF and Microwave Exposed Workers (Including the General Public)**

1 Frequency (MHz)	2 Electric Field Strength; rms (V/m)	3 Magnetic Field Strength; rms (A/m)	4 Power Density (W/m <sup>2</sup> )	5 Averaging Time (min)
0.003–1	280	2.19		6
1–10	280/f	2.19/f		6
10–30	28	2.19/f		6
30–300	28	0.073	2*	6
300–1 500	$1.585f^{0.5}$	$0.0042f^{0.5}$	$f/150$	6
1 500–15 000	61.4	0.163	10	6
15 000–150 000	61.4	0.163	10	$616\,000/f^{1.2}$
150 000–300 000	$0.158f^{0.5}$	$4.21 \times 10^{-4}f^{0.5}$	$6.67 \times 10^{-5}f$	$616\,000/f^{1.2}$

\* Power density limit is applicable at frequencies greater than 100 MHz.

**Notes:**

1. Frequency,  $f$ , is in MHz.
2. A power density of 10 W/m<sup>2</sup> is equivalent to 1 mW/cm<sup>2</sup>.
3. A magnetic field strength of 1 A/m corresponds to 1.257 microtesla ( $\mu$ T) or 12.57 milligauss (mG).

## EQUATIONS

Power density is given by:

$$S = \text{EIRP} / (4 * \pi * D^2)$$

where

S = Power density in W/m<sup>2</sup>

EIRP = Equivalent Isotropic Radiated Power in W

D = Separation distance in m

Power density in units of W/m<sup>2</sup> is converted to units of mWc/m<sup>2</sup> by dividing by 10.

Distance is given by:

$$D = \text{SQRT} (\text{EIRP} / (4 * \pi * S))$$

where

D = Separation distance in m

EIRP = Equivalent Isotropic Radiated Power in W

S = Power density in W/m<sup>2</sup>

For multiple colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the Power \* Gain product (in linear units) of each transmitter.

$$\text{Total EIRP} = (P1 * G1) + (P2 * G2) + \dots + (Pn * Gn)$$

where

Px = Power of transmitter x

Gx = Numeric gain of antenna x

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

## LIMITS

From FCC §1.1310 Table 1 (B), the maximum value of S = 1.0 mW/cm<sup>2</sup>

From IC Safety Code 6, Section 2.2 Table 5 Column 4, S = 10 W/m<sup>2</sup>

## RESULTS

The transmitter has a maximum E-field at 10m distance as follows:

EIRP = E field at 3m distance – 95.2

E field at 3m distance = E field at 10m distance + 20 = 53.65 + 20 = 73.65 dBuV/m

EIRP = 73.65 -95.2 = **-21.55 dBm = 0.00700 W**, this is less than 2.5 W based on section 2.2 of RSS210 therefore this test is N/A.