

Report No. : AG014932-001 Date : 2006 July 12

Application No. : LG207275(1)

Applicant : K&B International Limited

406 Empire Centre

68 Mody Road, TST East Kowloon, Hong Kong

Sample Description : One(1) submitted sample(s) stated to be R/C Thunder Spin Pick up Car

of Model No. KR-1263

Rating : 4 x 1.5V AA size batteries

No. of submitted sample: One (1) piece

Date Received : 2006 May 24

Test Period : 2006 May 30 – 2006 June 14

Test Requested : FCC Part 15 Certification.

Test Method : FCC Rules and Regulations Part 15 – July 2004

ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15

Subpart B.

For and on behalf of

CMA Industrial Development Foundation Limited

Authorized Signature :

Danny Chui Deputy Manager - EL. Division

Page 1 of 11



Report No. : AG014932-001 Date : 2006 July 12

Table of Contents

1	Gen	eral Information	3
	1.1	General Description	3
	1.2	Location of the test site	4
	1.3	List of measuring equipment	
2	Desc	cription of the radiated emission test.	
	2.1	Test Procedure	6
	2.2	Test Result	
	2.3	Radiated Emission Measurement Data	7
3	Desc	cription of the Line-conducted Test	
	3.1	Test Procedure	8
	3.2	Test Result	
	3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Phot	tograph	9
	4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	
	4.2	Photographs of the External and Internal Configurations of the EUT	
5	Sup	plementary document	
6		endices	

Page 2 of 11



Report No. : AG014932-001 Date : 2006 July 12

1 General Information

1.1 General Description

The equipment under test (EUT) is a super regenerative for RC Thunder Spin Pick Up Car. It is operating at 49.860MHz which is controlled by a LRC circuit. The EUT is powered by 4 x 1.5V AA size batteries. When it switched on, it can receive the radio control signal and running to corresponding direction.

The brief circuit description is listed as follows:

- Q1 and associated circuit act as receiver.
- U1 and associated circuit act as decoder.
- Q2~Q7 and associated circuit act as Forward and Backward motor control.
- Q8~Q13 and associated circuit act as Turn left and Turn right motor control.



Report No. : AG014932-001 Date : 2006 July 12

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Page 4 of 11



Report No. : AG014932-001 Date : 2006 July 12

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.
EMI Test Receiver	R&S	ESCI	100152
Broadband Antenna	Schaffner	CBL6112B	2692
Signal Generator	IFR	2023B	202302/938



Report No. : AG014932-001 Date : 2006 July 12

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to "cohere" the characteristic broadband emissions from the receiver.

2.2 Test Result

All other measurements are well below the limit. Thus, those highest emissions were presented in next page.

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector.

It was found that the EUT meet the FCC requirement.

Page 6 of 11



Report No. : AG014932-001 Date : 2006 July 12

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Frequency (MHz)	Polarity (H/V)	Reading at 3m	Antenna and Cable factor	Field Strength	Limit at 3m (dBµV/m)	Margin (dB)
		$(dB\mu V/m)$	(dB)	$(dB\mu V/m)$		
50.138	V	20.2	8.1	28.3	40.0	-11.7
50.402	V	20.9	8.1	29.0	40.0	-11.0
50.665	V	20.6	8.1	28.7	40.0	-11.3
52.755	V	14.4	8.1	22.5	40.0	-17.5
53.014	V	14.7	8.1	22.8	40.0	-17.2
96.890	V	8.1	9.2	17.3	43.5	-26.2
147.204	V	8.8	11.9	20.7	43.5	-22.8
147.476	V	8.9	11.9	20.8	43.5	-22.7
148.266	V	9.2	11.9	21.1	43.5	-22.4
196.800	V	13.5	9.2	22.7	43.5	-20.8

FCC ID: Q5K12639R



Report No. : AG014932-001 Date : 2006 July 12

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable

Page 8 of 11 FCC ID: Q5K12639R



Report No. : AG014932-001 Date : 2006 July 12

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.

Page 9 of 11 FCC ID: Q5K12639R



Report No. : AG014932-001 Date : 2006 July 12

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf



Report No. : AG014932-001 Date : 2006 July 12

6 Appendices

A 1	Photos of the set-up of Radiated Emissions	1	page
A2	Photos of External Configurations	1	page
A3	Photos of Internal Configurations	1	page
A4	ID Label/Location	1	page
A5	Block Diagram	1	page
A6	Schematics	1	page
A7	User Manual	1	page
A8	Operation Description	1	page

***** End of Report *****

FCC ID: Q5K12639R