

FCC RF Test Report

APPLICANT : ZTE CORPORATION
EQUIPMENT : WCDMA GSM (GPRS) Dual-Mode Digital Mobile Phone
BRAND NAME : ZTE
MODEL NAME : Movistar One
FCC ID : Q78-MOVISTARONE
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
Tx/Rx FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /
869.2 ~ 893.8 MHz
GSM1900 : 1850.2 ~ 1909.8 MHz /
1930.2 ~ 1989.8 MHz
WCDMA Band V : 826.4 ~ 846.6 MHz /
871.4 ~ 891.6 MHz
WCDMA Band II : 1852.4 ~ 1907.6 MHz /
1932.4 ~ 1987.6 MHz
MAX. ERP/EIRP POWER : GSM850 (GSM) : 0.78 W
GSM850 (EDGE 8) : 0.22 W
GSM1900 (GSM) : 0.43 W
GSM1900 (EDGE 8) : 0.16 W
WCDMA Band V (RMC 12.2Kbps) : 0.10 W
WCDMA Band II (RMC 12.2Kbps) : 0.11 W
EMISSION DESIGNATOR : GMSK : 246KGXW
8PSK : 252KG7W
QPSK : 4M18F9W

The product was received on Sep. 20, 2011 and completely tested on Sep. 25, 2011. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 6

 1.4 Testing Site 7

 1.5 Applied Standards 7

 1.6 Ancillary Equipment List..... 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1 Test Mode..... 8

 2.2 Connection Diagram of Test System 10

3 TEST RESULT..... 11

 3.1 Conducted Output Power Measurement..... 11

 3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement 13

 3.3 Occupied Bandwidth Measurement 19

 3.4 Band Edge Measurement..... 26

 3.5 Conducted Emission Measurement 33

 3.6 Field Strength of Spurious Radiation Measurement 49

 3.7 Frequency Stability Measurement..... 63

4 LIST OF MEASURING EQUIPMENTS 69

5 UNCERTAINTY OF EVALUATION..... 70

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.2	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§2.1049 §22.917(a) §24.238(a)	Occupied Bandwidth	N/A	PASS	-
3.4	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Conducted Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 22.56 dB at 7520 MHz
3.7	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-



1 General Description

1.1 Applicant

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.2 Manufacturer

ZTE CORPORATION

ZTE Plaza, Keji Road South, Hi-Tech, Industrial Park, Nanshan District, Shenzhen, Guangdong, 518057, P.R.China

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	WCDMA GSM (GPRS) Dual-Mode Digital Mobile Phone
Brand Name	ZTE
Model Name	Movistar One
FCC ID	Q78-MOVISTARONE
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz WCDMA Band V : 824 MHz ~ 849 MHz WCDMA Band II : 1850 MHz ~ 1910 MHz
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz WCDMA Band V : 869 MHz ~ 894 MHz WCDMA Band II : 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna	GSM850 : 32.37 dBm GSM1900 : 29.77 dBm WCDMA Band V : 22.80 dBm WCDMA Band II : 22.51 dBm
Maximum ERP/EIRP	GSM850 (GSM) : 0.78 W (28.94 dBm) GSM850 (EDGE 8) : 0.22 W (23.44 dBm) GSM1900 (GSM) : 0.43 W (26.37 dBm) GSM1900 (EDGE 8) : 0.16 W (22.05 dBm) WCDMA Band V (RMC 12.2Kbps) : 0.10 W (20.18 dBm) WCDMA Band II (RMC 12.2Kbps) : 0.11 W (20.36 dBm)
Antenna Type	WWAN : Fixed Internal Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna
HW Version	WMAB
SW Version	ZTE-CN-W850-W1900-P173A30V0.0.1B01T
Type of Modulation	GSM / GPRS : GMSK EDGE : 8PSK WCDMA : QPSK HSDPA : QPSK / 16QAM
Type of Emission	GMSK : 246KGXW 8PSK : 252KG7W QPSK : 4M18F9W
EUT Stage	Production Unit

Remark:

1. For other wireless features of this EUT, the test report will be issued separately.
2. This test report recorded only product characteristics and test results of PCS Licensed Transmitter Held to Ear (PCE).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.	
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
Test Site No.	Sporton Site No.	
	TH01-KS	03CH01-KS

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- ♦ 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (Certification), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW	GPS-30300	N/A	N/A	Unshielded, 1.8 m

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ GPRS 8 Link ■ EDGE 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ GPRS 8 Link ■ EDGE 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link ■ HSDPA Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link ■ HSDPA Link

Note:

1. The maximum power levels are GSM mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.
2. Because there are individual antennas for each WWAN, WLAN, and Bluetooth, the co-location test modes are not required.




The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880	1909.8
GSM (1 Uplink)	32.37	32.23	32.27	29.77	29.45	29.05
GPRS 8 (1 Uplink) – CS1	32.31	32.17	32.21	29.75	29.43	29.04
GPRS 10 (2 Uplink) – CS1	31.50	31.35	31.40	28.80	28.44	27.98
GPRS 11 (3 Uplink) – CS1	29.07	28.93	28.96	26.82	26.44	25.98
GPRS 12 (4 Uplink) – CS1	27.10	27.00	26.98	26.00	25.61	25.15
EDGE 8 (8PSK, 1 Uplink) – MCS9	26.36	26.64	26.80	25.57	25.34	24.94
EDGE 10 (8PSK, 2 Uplink) – MCS9	25.24	25.55	25.80	24.28	24.11	23.75
EDGE 11 (8PSK, 3 Uplink) – MCS9	21.94	22.27	22.44	22.16	22.00	21.42
EDGE 12 (8PSK, 4 Uplink) – MCS9	19.51	19.87	20.00	20.77	20.54	20.00

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Tx Channel	4132	4182	4233	9262	9400	9538
Rx Channel	4357	4408	4458	9662	9800	9938
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
AMR	22.79	22.78	22.60	22.50	22.34	22.35
RMC 12.2K	22.80	22.79	22.65	22.51	22.36	22.37
HSDPA Subtest-1	22.78	22.77	22.60	22.49	22.35	22.34
HSDPA Subtest-2	21.79	21.74	21.59	21.40	21.30	21.26
HSDPA Subtest-3	21.29	21.30	21.10	20.91	20.76	20.75
HSDPA Subtest-4	21.28	21.34	21.11	20.92	20.77	20.75

2.2 Connection Diagram of Test System



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM850 (GSM)	128 (Low)	824.2	32.37	1.73
	189 (Mid)	836.4	32.23	1.67
	251 (High)	848.8	32.27	1.69
GSM850 (EDGE 8)	128 (Low)	824.2	26.36	0.43
	189 (Mid)	836.4	26.64	0.46
	251 (High)	848.8	26.80	0.48
WCDMA Band V (RMC 12.2Kbps)	4132 (Low)	826.4	22.80	0.19
	4182 (Mid)	836.4	22.79	0.19
	4233 (High)	846.6	22.65	0.18

PCS Band				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM1900 (GSM)	512 (Low)	1850.2	29.77	0.95
	661 (Mid)	1880.0	29.45	0.88
	810 (High)	1909.8	29.05	0.80
GSM1900 (EDGE 8)	512 (Low)	1850.2	25.57	0.36
	661 (Mid)	1880.0	25.34	0.34
	810 (High)	1909.8	24.94	0.31
WCDMA Band II (RMC 12.2Kbps)	9262 (Low)	1852.4	22.51	0.18
	9400 (Mid)	1880.0	22.36	0.17
	9538 (High)	1907.6	22.37	0.17

3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

ERP/EIRP is measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The ERP of mobile transmitters must not exceed 7 Watts for 824 MHz ~ 849 MHz. The EIRP of mobile transmitters are limited to 2 Watts for 1850~1910 MHz.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$
Ps (dBm) : Input power to substitution antenna.
Gs (dBi or dBd) : Substitution antenna Gain.
Et = Rt + AF
Es = Rs + AF
AF (dB/m) : Receive antenna factor
Rt : The highest received signal in spectrum analyzer for EUT.
Rs : The highest received signal in spectrum analyzer for substitution antenna.

3.2.4 Test Setup



3.2.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-18.50	-48.12	0.00	-1.08	28.54	0.71
836.40	-18.47	-48.28	0.00	-0.93	28.88	0.77
848.80	-18.65	-48.35	0.00	-0.76	28.94	0.78
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-34.19	-47.97	0.00	-1.08	12.70	0.02
836.40	-33.94	-48.01	0.00	-0.93	13.14	0.02
848.80	-34.22	-48.05	0.00	-0.76	13.07	0.02

GSM850 (EDGE 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-23.93	-48.12	0.00	-1.08	23.11	0.20
836.40	-23.91	-48.28	0.00	-0.93	23.44	0.22
848.80	-24.55	-48.35	0.00	-0.76	23.04	0.20
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-38.81	-47.97	0.00	-1.08	8.08	0.01
836.40	-39.27	-48.01	0.00	-0.93	7.81	0.01
848.80	-39.23	-48.05	0.00	-0.76	8.06	0.01



WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-27.59	-48.12	0.00	-1.08	19.45	0.09
836.40	-27.23	-48.28	0.00	-0.93	20.12	0.10
846.60	-27.41	-48.35	0.00	-0.76	20.18	0.10
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-42.99	-47.97	0.00	-1.08	3.90	0.002
836.40	-42.74	-48.01	0.00	-0.93	4.34	0.003
846.60	-41.93	-48.05	0.00	-0.76	5.36	0.003



3.2.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-28.59	-51.88	0.00	1.96	25.25	0.33
1880.00	-29.13	-52.99	0.00	2.00	25.86	0.39
1909.80	-30.14	-54.28	0.00	1.98	26.12	0.41
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-29.06	-52.13	0.00	1.96	25.03	0.32
1880.00	-29.60	-53.17	0.00	2.00	25.57	0.36
1909.80	-29.74	-54.13	0.00	1.98	26.37	0.43

GSM1900 (EDGE 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-32.38	-51.88	0.00	1.96	21.46	0.14
1880.00	-33.34	-52.99	0.00	2.00	21.65	0.15
1909.80	-34.60	-54.28	0.00	1.98	21.66	0.15
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-32.78	-52.13	0.00	1.96	21.31	0.14
1880.00	-33.52	-53.17	0.00	2.00	21.65	0.15
1909.80	-34.06	-54.13	0.00	1.98	22.05	0.16



WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-34.69	-51.88	0.00	1.96	19.15	0.08
1880.00	-34.63	-52.99	0.00	2.00	20.36	0.11
1907.60	-36.42	-54.28	0.00	1.98	19.84	0.10
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-35.37	-52.13	0.00	1.96	18.72	0.07
1880.00	-35.01	-53.17	0.00	2.00	20.16	0.10
1907.60	-35.98	-54.13	0.00	1.98	20.13	0.10

3.3 Occupied Bandwidth Measurement

3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.

3.3.4 Test Setup






3.3.5 Test Result (Plots) of Occupied Bandwidth


Band :	GSM 850	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 189



Date: 22.SEP.2011 18:57:58

26dB Bandwidth Plot on Channel 189




Date: 22.SEP.2011 18:56:39




Band :	GSM 850	Power Stage :	High
Test Mode :	EDGE 8 Link		

99% Occupied Bandwidth Plot on Channel 189



Date: 24.SEP.2011 12:06:57

26dB Bandwidth Plot on Channel 189




Date: 24.SEP.2011 12:05:37




Band :	GSM 1900	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 661



Date: 22.SEP.2011 18:31:42

26dB Bandwidth Plot on Channel 661




Date: 22.SEP.2011 18:30:22




Band :	GSM 1900	Power Stage :	High
Test Mode :	EDGE 8 Link		

99% Occupied Bandwidth Plot on Channel 661



Date: 24.SEP.2011 12:18:37

26dB Bandwidth Plot on Channel 661




Date: 24.SEP.2011 12:17:17




Band :	WCDMA Band V	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

99% Occupied Bandwidth Plot on Channel 4182



Date: 24.SEP.2011 10:40:12

26dB Bandwidth Plot on Channel 4182




Date: 24.SEP.2011 10:31:55




Band :	WCDMA Band II	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

99% Occupied Bandwidth Plot on Channel 9400



Date: 24.SEP.2011 11:09:24

26dB Bandwidth Plot on Channel 9400



Date: 24.SEP.2011 11:14:50

3.4 Band Edge Measurement

3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW 3kHz for GSM / EDGE, Setting RBW 100kHz for WCDMA.


3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Band Edge


Band :	GSM850	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 128



Date: 22.SEP.2011 18:59:51

Higher Band Edge Plot on Channel 251




Date: 22.SEP.2011 19:00:17




Band :	GSM850	Power Stage :	High
Test Mode :	EDGE 8 Link		

Lower Band Edge Plot on Channel 128



Date: 24.SEP.2011 12:08:49

Higher Band Edge Plot on Channel 251




Date: 24.SEP.2011 12:09:16




Band :	GSM1900	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 512



Date: 22.SEP.2011 18:33:34

Higher Band Edge Plot on Channel 810




Date: 22.SEP.2011 18:34:00




Band :	GSM1900	Power Stage :	High
Test Mode :	EDGE 8 Link		

Lower Band Edge Plot on Channel 512



Date: 24.SEP.2011 13:03:56

Higher Band Edge Plot on Channel 810




Date: 24.SEP.2011 13:04:23




Band :	WCDMA Band V	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

Lower Band Edge Plot on Channel 4132



Date: 24.SEP.2011 10:47:25

Higher Band Edge Plot on Channel 4233




Date: 24.SEP.2011 10:50:31




Band :	WCDMA Band II	Power Stage :	High
Test Mode :	RMC 12.2Kbps Link		

Lower Band Edge Plot on Channel 9262



Date: 24.SEP.2011 10:57:01

Higher Band Edge Plot on Channel 9538



Date: 24.SEP.2011 11:03:34

3.5 Conducted Emission Measurement

3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

3. The EUT was connected to spectrum analyzer and base station via power divider.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.

3.5.4 Test Setup






3.5.5 Test Result (Plots) of Conducted Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 22.SEP.2011 19:15:00


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 22.SEP.2011 19:17:34




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 22.SEP.2011 19:19:31

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 22.SEP.2011 19:21:03




Band :	GSM850	Channel :	CH189
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2011 13:28:32


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2011 13:32:45




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2011 13:36:23

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 24.SEP.2011 13:41:32




Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 22.SEP.2011 19:25:07


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 22.SEP.2011 19:27:50




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 22.SEP.2011 19:31:05


Conducted Emission Plot between 7GHz ~ 13.6G



Date: 22.SEP.2011 19:33:08



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 22.SEP.2011 19:34:39




Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE 8 Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2011 13:10:43


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2011 13:13:24




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2011 13:17:39


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 24.SEP.2011 13:20:59



Conducted Emission Plot between 13.6GHz ~ 19.1GHz




Date: 24.SEP.2011 13:22:18




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2011 11:42:06


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2011 11:44:33




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2011 11:45:53

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 24.SEP.2011 11:47:07




Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 24.SEP.2011 11:24:17


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 24.SEP.2011 11:30:15




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 24.SEP.2011 11:32:48


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 24.SEP.2011 11:34:58



Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 24.SEP.2011 11:36:58

3.6 Field Strength of Spurious Radiation Measurement

3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$


3.6.4 Test Setup





3.6.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	23~24°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 192004

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-48.35	-13	-35.35	-47.42	-49.00	0.57	3.37	H	Pass
2509	-63.05	-13	-50.05	-65.30	-65.28	0.78	5.16	H	Pass
3345	-61.42	-13	-48.42	-63.36	-65.06	0.87	6.66	H	Pass
4182	-62.55	-13	-49.55	-65.29	-67.14	0.97	7.71	H	Pass
5018	-60.11	-13	-47.11	-66.31	-65.78	1.09	8.91	H	Pass
5854	-58.27	-13	-45.27	-66.98	-64.71	1.22	9.81	H	Pass



Band :	GSM850	Temperature :	23~24°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 192004

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-39.85	-13	-26.85	-44.66	-40.50	0.57	3.37	V	Pass
2509	-61.08	-13	-48.08	-64.19	-63.31	0.78	5.16	V	Pass
3345	-62.67	-13	-49.67	-64.65	-66.31	0.87	6.66	V	Pass
4182	-62.20	-13	-49.20	-66.04	-66.79	0.97	7.71	V	Pass
5018	-61.16	-13	-48.16	-66.10	-66.83	1.09	8.91	V	Pass
5854	-59.35	-13	-46.35	-67.34	-65.79	1.22	9.81	V	Pass



Band :	GSM850	Temperature :	23~24°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 192004

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-62.64	-13	-49.64	-58.42	-63.29	0.57	3.37	H	Pass
2509	-61.75	-13	-48.75	-64.00	-63.98	0.78	5.16	H	Pass
3345	-62.07	-13	-49.07	-64.01	-65.71	0.87	6.66	H	Pass
4182	-63.29	-13	-50.29	-66.03	-67.88	0.97	7.71	H	Pass
5018	-60.20	-13	-47.20	-66.40	-65.87	1.09	8.91	H	Pass
5854	-59.61	-13	-46.61	-68.32	-66.05	1.22	9.81	H	Pass



Band :	GSM850	Temperature :	23~24°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 192004

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-49.00	-13	-36.00	-51.57	-49.65	0.57	3.37	V	Pass
2509	-61.41	-13	-48.41	-64.52	-63.64	0.78	5.16	V	Pass
3345	-60.83	-13	-47.83	-62.81	-64.47	0.87	6.66	V	Pass
4182	-61.32	-13	-48.32	-65.16	-65.91	0.97	7.71	V	Pass
5018	-60.85	-13	-47.85	-65.79	-66.52	1.09	8.91	V	Pass
5854	-58.78	-13	-45.78	-66.77	-65.22	1.22	9.81	V	Pass



Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 192004

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-54.82	-13	-41.82	-55.79	-61.20	0.78	7.16	H	Pass
5640	-47.60	-13	-34.60	-55.72	-56.14	1.04	9.58	H	Pass
7520	-42.85	-13	-29.85	-55.23	-52.96	1.35	11.46	H	Pass
9400	-60.00	-13	-47.00	-63.26	-71.06	1.75	12.81	H	Pass
11280	-53.58	-13	-40.58	-65.07	-64.67	2	13.09	H	Pass
13160	-55.60	-13	-42.60	-66.90	-67.31	2.04	13.75	H	Pass



Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GSM Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 192004

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-47.23	-13	-34.23	-52.98	-53.61	0.78	7.16	V	Pass
5640	-39.80	-13	-26.80	-51.65	-48.34	1.04	9.58	V	Pass
7520	-35.56	-13	-22.56	-51.68	-45.67	1.35	11.46	V	Pass
9400	-58.76	-13	-45.76	-59.98	-69.82	1.75	12.81	V	Pass
11280	-54.51	-13	-41.51	-65.75	-65.60	2	13.09	V	Pass
13160	-54.52	-13	-41.52	-65.71	-66.23	2.04	13.75	V	Pass



Band :	GSM1900	Temperature :	23~24°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 192004

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-59.81	-13	-46.81	-60.78	-66.19	0.78	7.16	H	Pass
5640	-54.48	-13	-41.48	-58.66	-63.02	1.04	9.58	H	Pass
7520	-53.13	-13	-40.13	-58.81	-63.24	1.35	11.46	H	Pass
9400	-62.35	-13	-49.35	-65.61	-73.41	1.75	12.81	H	Pass
11280	-55.14	-13	-42.14	-66.63	-66.23	2	13.09	H	Pass
13160	-54.93	-13	-41.93	-66.23	-66.64	2.04	13.75	H	Pass



Band :	GSM1900	Temperature :	23~24°C
Test Mode :	EDGE 8 Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 192004

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-62.11	-13	-49.11	-63.48	-68.49	0.78	7.16	V	Pass
5640	-58.10	-13	-45.10	-61.32	-66.64	1.04	9.58	V	Pass
7520	-55.80	-13	-42.80	-60.29	-65.91	1.35	11.46	V	Pass
9400	-63.05	-13	-50.05	-64.27	-74.11	1.75	12.81	V	Pass
11280	-54.78	-13	-41.78	-66.02	-65.87	2	13.09	V	Pass
13160	-55.08	-13	-42.08	-66.27	-66.79	2.04	13.75	V	Pass



Band :	WCDMA Band V	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 192004

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-68.28	-13	-55.28	-64.06	-68.93	0.57	3.37	H	Pass
2509	-62.13	-13	-49.13	-64.38	-64.36	0.78	5.16	H	Pass
3345	-62.00	-13	-49.00	-63.94	-65.64	0.87	6.66	H	Pass
4182	-63.55	-13	-50.55	-66.29	-68.14	0.97	7.71	H	Pass
5018	-59.55	-13	-46.55	-65.75	-65.22	1.09	8.91	H	Pass
5854	-57.81	-13	-44.81	-66.52	-64.25	1.22	9.81	H	Pass



Band :	WCDMA Band V	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 192004

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-68.25	-13	-55.25	-63.90	-68.90	0.57	3.37	V	Pass
2509	-61.38	-13	-48.38	-64.49	-63.61	0.78	5.16	V	Pass
3345	-60.86	-13	-47.86	-62.84	-64.50	0.87	6.66	V	Pass
4182	-61.45	-13	-48.45	-65.29	-66.04	0.97	7.71	V	Pass
5018	-60.36	-13	-47.36	-65.30	-66.03	1.09	8.91	V	Pass
5854	-58.38	-13	-45.38	-66.37	-64.82	1.22	9.81	V	Pass



Band :	WCDMA Band II	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 HORIZONTAL
 Project : (FG) 192004

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3762	-55.22	-13	-42.22	-56.19	-61.60	0.78	7.16	H	Pass
5640	-62.04	-13	-49.04	-66.22	-70.58	1.04	9.58	H	Pass
7520	-60.57	-13	-47.57	-65.70	-70.68	1.35	11.46	H	Pass
9400	-61.62	-13	-48.62	-64.88	-72.68	1.75	12.81	H	Pass
11280	-54.89	-13	-41.89	-66.38	-65.98	2	13.09	H	Pass
13160	-54.73	-13	-41.73	-66.03	-66.44	2.04	13.75	H	Pass



Band :	WCDMA Band II	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link	Relative Humidity :	42~43%
Test Engineer :	Jack Li	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition: FCC PART22 24 27 HF EIRP FACTOR-09020 VERTICAL
 Project : (FG) 192004

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3762	-52.90	-13	-39.90	-55.2	-59.28	0.78	7.16	V	Pass
5640	-62.49	-13	-49.49	-65.71	-71.03	1.04	9.58	V	Pass
7520	-61.89	-13	-48.89	-66.38	-72.00	1.35	11.46	V	Pass
9400	-62.72	-13	-49.72	-63.94	-73.78	1.75	12.81	V	Pass
11280	-53.84	-13	-40.84	-65.08	-64.93	2	13.09	V	Pass
13160	-55.17	-13	-42.17	-66.36	-66.88	2.04	13.75	V	Pass

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.7.2 Measuring Instruments

See list of measuring instruments of this test report.


3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.7.5 Test Setup



3.7.6 Test Result of Temperature Variation

Band :	GSM 850		Channel :	189	
Limit (ppm) :	2.5				
Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	N/A	N/A	PASS
-20	N/A	N/A	N/A	N/A	
-10	10	0.01	11	0.01	
0	-10	-0.01	12	0.01	
10	6	0.01	9	0.01	
20	11	0.01	10	0.01	
30	7	0.01	17	0.02	
40	14	0.02	16	0.02	
50	11	0.01	19	0.02	
55	16	0.02	20	0.02	

Note:

1. The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.



Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5		

Temperature (°C)	GSM		EDGE 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	N/A	N/A	PASS
-20	N/A	N/A	N/A	N/A	
-10	20	0.01	29	0.02	
0	21	0.01	28	0.01	
10	16	0.01	33	0.02	
20	25	0.01	30	0.02	
30	28	0.01	45	0.02	
40	34	0.02	47	0.02	
50	32	0.02	46	0.02	
55	37	0.02	43	0.02	

Note:

1. The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.



Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5		

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	5	0.01	
0	6	0.01	
10	5	0.01	
20	4	0.00	
30	6	0.01	
40	5	0.01	
50	5	0.01	
55	6	0.01	

Note:

1. The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.



Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5		

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	N/A	N/A	
-10	8	0.00	
0	-5	0.00	
10	7	0.00	
20	-8	0.00	
30	5	0.00	
40	-6	0.00	
50	7	0.00	
55	6	0.00	

Note:

1. The manufacturer declared that the EUT could work properly between temperatures -10°C~55°C.

3.7.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.8	8	0.01	2.5	PASS
		BEP	10	0.01		
		4.2	11	0.01		
	EDGE 8	3.8	15	0.02		
		BEP	13	0.02		
		4.2	14	0.02		
GSM 1900 CH661	GSM	3.8	25	0.01		
		BEP	27	0.01		
		4.2	26	0.01		
	EDGE 8	3.8	34	0.02		
		BEP	30	0.02		
		4.2	32	0.02		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	-7	-0.01		
		BEP	-4	0.00		
		4.2	5	0.01		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	6	0.00		
		BEP	-7	0.00		
		4.2	7	0.00		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.6 V.



4 List of Measuring Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 07, 2011	Jan. 06, 2012	Conducted (TH01-KS)
System Simulator	R&S	CMU200	837587/066	Full-Band	Jan. 07, 2011	Jan. 06, 2012	Conducted (TH01-KS)
DC Power Supply	TOPWARD	GPS-3030D	E1884515	N/A	Aug. 23, 2011	Aug. 22, 2012	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Jan. 17, 2011	Jan. 16, 2012	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 16, 2010	Nov. 15, 2011	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2010	Dec. 06, 2011	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060004	30MHz~2GHz	Dec. 09, 2010	Dec. 08, 2011	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701023	1GHz-18GHz	Nov. 09, 2010	Nov. 08, 2011	Radiation (03CH01-KS)
SHE-EHF Horn	Schwarzbeck	BBHA9170	BBHA170249	15GHz-40GHz	Oct. 15,2010	Oct. 14,2011	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	837587/066	Full-Band	Jan. 07, 2011	Jan. 06, 2012	Radiation (03CH01-KS)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP192004 as below.