

RF Exposure Report

Report No.: SA190515E04A

FCC ID: Q87-03448

Test Model: MX5300

Received Date: May 15, 2019

Test Date: July 03, 2019

Issued Date: Apr. 15, 2020

Applicant: Linksys LLC

Address: 121 Theory Drive, Irvine, CA 92617, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	5
2.5 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA190515E04A	Original release.	Apr. 15, 2020

1 Certificate of Conformity

Product: Velop

Brand: Linksys

Test Model: MX5300

Sample Status: ENGINEERING SAMPLE

Applicant: Linksys LLC

Test Date: July 03, 2019


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :


Phoenix Huang / Specialist

Date:

Apr. 15, 2020

Approved by :



Clark Lin / Technical Manager

Date:

Apr. 15, 2020

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 28cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Frequency Range (GHz)	Directional Antenna Gain (dBi)	Antenna Type	Antenna Connector
2.4~2.4835 (Bluetooth+Zigbee)	1.97	Dipole	i-pex(MHF)
2.4~2.4835 (WLAN)	3.98		
5.15~5.25	5.18		
5.25~5.35	5.98		
5.47~5.725	4.72		
5.725~5.85	5.73		
Note: More detailed information, please refer to operating description.			

2.5 Calculation Result of Maximum Conducted Power

For 2.4GHz, 5GHz (U-NII-1, U-NII-3), Bluetooth and Zigbee data was copied from the original test report (Report No.: SA190515E04)

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN 2.4GHz	2437	986.923	3.98	28	0.25047	1
Zigbee	2475	198.153	1.97	28	0.03166	1
Bluetooth	2402	23.605	1.97	28	0.00377	1
WLAN 5GHz (U-NII-1)	5240	922.721	5.18	28	0.30870	1
WLAN 5GHz (U-NII-2A)	5310	249.702	5.98	28	0.10044	1
WLAN 5GHz (U-NII-2C)	5530	249.392	4.72	28	0.07505	1
WLAN 5GHz (U-NII-3)	5755	671.308	5.73	28	0.25491	1

Conclusion:

The formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + Zigbee + Bluetooth + WLAN 5GHz (low band) + WLAN 5GHz (high band) = $0.25047 / 1 + 0.03166 / 1 + 0.00377 / 1 + 0.30870 / 1 + 0.25491 / 1 = 0.84951$

Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---