



FCC RADIO TEST REPORT

Applicant's company	Linksys LLC
Applicant Address	121 Theory Drive, Irvine, CA 92617, USA
FCC ID	Q87-RE6500
Manufacturer's company	U-MEDIA Communications, Inc.
Manufacturer Address	9F, No. 1, Jin-Shan 7th St., Hsinchu 300, Taiwan

Product Name	Linksys AC1200 MAX Wi-Fi Range Extender
Brand Name	LINKSYS
Model No.	RE6500
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Feb. 19, 2016
Final Test Date	Mar. 28, 2016
Submission Type	Class II Change

Statement

Test result included in this report is for the IEEE 802.11n and IEEE 802.11b/g of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2013, 47 CFR FCC Part 15 Subpart C, KDB558074 D01 v03r05 and KDB 662911 D01 v02r01**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Testing Laboratory
1190

Table of Contents

1. VERIFICATION OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	4
3.4. Table for Carrier Frequencies	5
3.5. Table for Test Modes.....	5
3.6. Table for Testing Locations.....	6
3.7. Table for Class II Change	6
3.8. Table for Supporting Units	6
3.9. Test Configurations	7
4. TEST RESULT	9
4.1. AC Power Line Conducted Emissions Measurement.....	9
4.2. Radiated Emissions Measurement.....	13
4.3. Antenna Requirements	19
5. LIST OF MEASURING EQUIPMENTS	20
6. MEASUREMENT UNCERTAINTY.....	21
APPENDIX A. TEST PHOTOS	A1 ~ A3



History of This Test Report



1. VERIFICATION OF COMPLIANCE

Product Name : Linksys AC1200 MAX Wi-Fi Range Extender
Brand Name : LINKSYS
Model No. : RE6500
Applicant : Linksys LLC
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sportun International as requested by the applicant to evaluate the EMC performance of the product sample received on Feb. 19, 2016 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	12.58 dB
4.2	15.247(d)	Radiated Emissions	Complies	2.13 dB
4.3	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

Items	Description	
Product Type	WLAN (2TX, 2RX)	
Radio Type	Intentional Transceiver	
Power Type	From power adapter	
Modulation	IEEE 802.11b: DSSS IEEE 802.11g: OFDM IEEE 802.11n: see the below table	
Data Modulation	IEEE 802.11b: DSSS (BPSK / QPSK / CCK) IEEE 802.11g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM)	
Data Rate (Mbps)	IEEE 802.11b: DSSS (1 / 2 / 5.5/11) IEEE 802.11g: OFDM (6/9/12/18/24/36/48/54) IEEE 802.11n: see the below table	
Frequency Range	2400 ~ 2483.5MHz	
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth	
Carrier Frequencies	Please refer to section 3.4	
Antenna	Please refer to section 3.3	

Items	Description	
Beamforming Function	<input type="checkbox"/> With beamforming	<input checked="" type="checkbox"/> Without beamforming

Antenna and Band width

Antenna	Two (TX)	
Band width Mode	20 MHz	40 MHz
IEEE 802.11b	V	X
IEEE 802.11g	V	X
IEEE 802.11n	V	V

IEEE 11n Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	2	MCS 0-15
802.11n (HT40)	2	MCS 0-15

Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput).

Then EUT supports HT20 and HT40.

Note 2: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n

3.2. Accessories


Power	Brand	Model	Rating
Adapter	Ktec	KSAS0121200100VU	INPUT: 100-240Vac, 50/60Hz, 0.4A OUTPUT: 12Vdc, 1.0A

3.3. Table for Filed Antenna

Ant.	Brand	Model No.	Antenna Type	Connector	Gain (dBi)		Cable Loss (dB)		True Gain (dBi)	
					2.4GHz	5GHz	2.4GHz	5GHz	2.4GHz	5GHz
1	INVAX	AN2450	Dipole Antenna	RP SMA	3.5	3.5	1.0	2.8	2.5	0.7
2	INVAX	AN2450	Dipole Antenna	RP SMA	3.5	3.5	2.8	1.0	0.7	2.5

Note: The EUT has two antennas.

Ant. 1 and Ant. 2 could transmit/receive simultaneous



3.4. Table for Carrier Frequencies

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 1~Channel 11.

For 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Ant.
AC Power Line Conducted Emissions	Normal Link	-	-	-
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-

The following test modes were performed for all tests:

For Conducted Emission test:

Test Mode: Normal Link-EUT + adapter

For Radiated Emission Below 1GHz test:

The EUT was performed at Y axis and Z axis position, and the worst case was found at Z axis. So the measurement will follow this same test configuration.

Test Mode: Normal Link-EUT in Z axis + adapter

For Co-location MPE Test:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Co-location Maximum Permissible Exposure (Please refer to FA4N1172-37) test is added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

3.6. Table for Testing Locations

Test Site Location				
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.			
Test Site No.	Site Category	Location	FCC Designation No.	IC File No.
03CH01-CB	SAC	Hsin Chu	TW0006	IC 4086D
CO02-CB	Conduction	Hsin Chu	TW0006	IC 4086D

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

3.7. Table for Class II Change

This product is an extension of original one reported under Sporton project number: FR421849AA

Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
1. Updating adapter (Model name: KSAS0121200100VU) to Level VI energy efficiency.	1. AC Power Line Conducted Emissions 2. Radiated Emissions (below 1GHz)
2. Updating applicant's company to "121 Theory Drive, Irvine, CA 92617, USA" from "131 Theory Drive, Irvine, CA 92617, USA".	It's not necessary to re-test all test items.
3. Updating brand name to "LINKSYS" from "Linksys".	
4. Removing accessories: RJ-45 cable.	

3.8. Table for Supporting Units

For Test Site No: 03CH01-CB (below 1GHz test)


Support Unit	Brand	Model	FCC ID
NB	DELL	E4300	DoC
NB*2	APPLE	MACpro	QDS-BRCM1055
WLAN AP	NETGEAR	WNDR3300v2	PY309300116
Earphone	e-Power	S90W	N/A

For Test Site No: CO02-CB

Support Unit	Brand	Model	FCC ID
NB*3	DELL	E6430	DoC
AP Router	Planex	GW-AP54SGX	KA220030603014-1
Earphone	e-Power	S90W	N/A

3.9. Test Configurations


3.9.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	Audio cable	No	1.4m
3	RJ-45 cable	No	10m
4	RJ-45 cable*3	No	1.5m

3.9.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.5m
2	Audio cable	No	1.4m
3	RJ-45 cable*3	No	1.5m
4	RJ-45 cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	58%
Test Engineer	Edison Lin	Phase	Line
Configuration	Normal Link		



Freq	Level	Over	Limit	Read	LISN	Cable	
		Line	dBuV	Level	Factor	Remark	
	MHz	dBuV	dB	dBuV	dB	dB	dB
1	0.1590	42.94	-12.58	55.52	32.82	9.96	Average
2	0.1590	48.52	-17.00	65.52	38.40	9.96	QP
3	0.2007	40.35	-13.23	53.58	30.22	9.95	Average
4	0.2007	47.62	-15.96	63.58	37.49	9.95	QP
5	0.2404	35.75	-16.33	52.08	25.59	9.97	Average
6	0.2404	43.54	-18.54	62.08	33.38	9.97	QP
7	0.3558	33.42	-15.41	48.83	23.22	10.00	Average
8	0.3558	41.22	-17.61	58.83	31.02	10.00	QP
9	0.6683	29.03	-16.97	46.00	18.80	10.03	Average
10	0.6683	36.33	-19.67	56.00	26.10	10.03	QP
11	9.2043	24.03	-25.97	50.00	13.51	10.15	Average
12	9.2043	31.95	-28.05	60.00	21.43	10.15	QP

Temperature	25°C	Humidity	58%
Test Engineer	Edison Lin	Phase	Neutral
Configuration	Normal Link		



Freq	Level	Over	Limit	Read	LISN	Cable		
		Line	dBuV	Level	Factor	Remark	Loss	Pol/Phase
	MHz	dBuV	dB	dBuV	dB		dB	
1	0.1624	35.75	-19.59	55.34	25.63	9.96 Average	0.16	NEUTRAL
2	0.1624	45.09	-20.25	65.34	34.97	9.96 QP	0.16	NEUTRAL
3	0.1904	33.46	-20.56	54.02	23.32	9.96 Average	0.18	NEUTRAL
4	0.1904	43.10	-20.92	64.02	32.96	9.96 QP	0.18	NEUTRAL
5	0.2353	33.02	-19.24	52.26	22.87	9.96 Average	0.19	NEUTRAL
6	0.2353	41.05	-21.21	62.26	30.90	9.96 QP	0.19	NEUTRAL
7	0.2878	33.09	-17.50	50.59	22.93	9.97 Average	0.19	NEUTRAL
8	0.2878	40.36	-20.23	60.59	30.20	9.97 QP	0.19	NEUTRAL
9	0.6683	27.27	-18.73	46.00	17.10	9.97 Average	0.20	NEUTRAL
10	0.6683	34.13	-21.87	56.00	23.96	9.97 QP	0.20	NEUTRAL
11	8.2351	22.11	-27.89	50.00	11.62	10.12 Average	0.37	NEUTRAL
12	8.2351	29.06	-30.94	60.00	18.57	10.12 QP	0.37	NEUTRAL

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Radiated Emissions Measurement

4.2.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.2.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 1/T for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.2.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1m & 3m far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 1/T VBW for average reading in spectrum analyzer.
7. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
8. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
9. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.2.4. Test Setup Layout

For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	20.7°C	Humidity	52%
Test Engineer	John Tang	Configurations	Normal Link
Test Date	Mar. 25, 2016		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


4.2.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	20.7°C	Humidity	52%
Test Engineer	John Tang	Configurations	Normal Link

Horizontal



Freq	Level	Limit		Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phase
		Line	dB			dBuV	dB	dB/m	dB	cm	deg	
MHz	dBuV/m	dBuV/m	dB									
1	31.94	33.55	40.00	-6.45	40.79	0.50	24.66	32.40	150	151	Peak	HORIZONTAL
2	67.83	33.30	40.00	-6.70	51.93	0.71	13.06	32.40	200	92	Peak	HORIZONTAL
3	90.14	31.74	43.50	-11.76	47.74	0.82	15.57	32.39	200	99	Peak	HORIZONTAL
4	282.20	33.94	46.00	-12.06	45.08	1.43	19.72	32.29	150	56	Peak	HORIZONTAL
5	500.45	33.42	46.00	-12.58	39.80	1.94	24.03	32.35	200	15	Peak	HORIZONTAL
6	828.31	35.80	46.00	-10.20	38.28	2.49	27.13	32.10	125	192	Peak	HORIZONTAL

Vertical


Freq	Level	Limit	Over	Read	Cable			Antenna	Preamp	A/Pos	T/Pos	Remark	Pol/Phase
					Line	Limit	Level						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg				
1	44.55	33.42	40.00	-6.58	47.87	0.59	17.37	32.41	100	358	QP		VERTICAL
2	50.37	33.51	40.00	-6.49	50.46	0.61	14.85	32.41	100	328	QP		VERTICAL
3	56.19	34.15	40.00	-5.85	51.76	0.66	14.14	32.41	150	349	QP		VERTICAL
4	67.83	37.87	40.00	-2.13	56.50	0.71	13.06	32.40	200	5	QP		VERTICAL
5	78.50	33.95	40.00	-6.05	52.09	0.77	13.49	32.40	100	252	Peak		VERTICAL
6	90.14	31.36	43.50	-12.14	47.36	0.82	15.57	32.39	125	24	Peak		VERTICAL

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.3. Antenna Requirements

4.3.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.3.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
LISN	Schwarzbeck	NSLK 8127	8127650	9kHz ~ 30MHz	Nov. 16, 2015	Conduction (CO02-CB)
LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Nov. 13, 2015	Conduction (CO02-CB)
EMI Receiver	Agilent	N9038A	MY52260140	9kHz ~ 8.4GHz	Jan. 18, 2016	Conduction (CO02-CB)
COND Cable	Woken	Cable	01	0.15MHz ~ 30MHz	Dec. 01, 2015	Conduction (CO02-CB)
Software	Audix	E3	6.120210n	-	N.C.R.	Conduction (CO02-CB)
LISN	Schwarzbeck	NSLK 8127	8127650	9kHz ~ 30MHz	Nov. 16, 2015	Conduction (CO02-CB)
BILOG ANTENNA	Schaffner	CBL6112D	37880	20MHz ~ 2GHz	Sep. 03, 2015	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9kHz - 30 MHz	Mar. 16, 2016*	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Mar. 15, 2016	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	Oct. 27, 2015	Radiation (03CH01-CB)
EMI Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8.4GHz	Jan. 27, 2016	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz ~ 1 GHz	Nov. 02, 2015	Radiation (03CH01-CB)
Test Software	Audix	E3	6.2009-IO-7	N/A	N/A	Radiation (03CH01-CB)

Note: Calibration Interval of instruments listed above is one year.

*Calibration Interval of instruments listed above is two year.

N.C.R. means Non-Calibration required.

6. MEASUREMENT UNCERTAINTY

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.2 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	3.6 dB	Confidence levels of 95%