



# SAR TEST REPORT

**REPORT NO.:** SA951114L02

**MODEL NO.:** WPC600N

**RECEIVED:** Nov. 14, 2006

**TESTED:** Jul. 05 ~ Jul. 10, 2007

**ISSUED:** Jul. 17, 2007

**APPLICANT:** Cisco-Linksys LLC

**ADDRESS:** 121 Theory Drive Irvine, CA 92617 (USA)

**ISSUED BY:** Advance Data Technology Corporation

**LAB ADDRESS:** 47 14<sup>th</sup> Lin, Chiapau Tsun, Linko, Taipei, Taiwan,  
R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2<sup>nd</sup> Rd., Kueishan, Taoyuan,  
Taiwan, R.O.C.

This test report consists of 67 pages in total except Appendix. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF, A2LA or any government agencies. The test results in the report only apply to the tested sample.





## TABLE OF CONTENTS

1. CERTIFICATION .....	3
2. GENERAL INFORMATION .....	4
2.1 GENERAL DESCRIPTION OF EUT .....	4
2.2 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	6
2.3 GENERAL INOFRMATION OF THE SAR SYSTEM .....	7
2.4 GENERAL DESCRIPTION OF THE SPATIAL PEAK SAR EVALUATION .....	10
3. DESCRIPTION OF SUPPORT UNITS .....	14
4. DESCRIPTION OF TEST MODES AND CONFIGURATIONS .....	15
4.1. DESCRIPTION OF ANTENNA LOCATION .....	15
4.2. DESCRIPTION OF ASSESSMENT POSITION .....	16
4.3. DESCRIPTION OF TEST MODE .....	17
4.4. SUMMARY OF TEST RESULTS .....	18
5. TEST RESULTS .....	22
5.1 TEST PROCEDURES .....	22
5.2 MEASURED SAR RESULTS .....	24
5.3 SAR LIMITS .....	40
5.4 RECIPES FOR TISSUE SIMULATING LIQUIDS .....	41
5.5 TEST EQUIPMENT FOR TISSUE PROPERTY .....	53
6. SYSTEM VALIDATION .....	54
6.1 TEST EQUIPMENT .....	54
6.2 TEST PROCEDURE .....	55
6.3 VALIDATION RESULTS .....	57
6.4 SYSTEM VALIDATION UNCERTAINTIES .....	58
7. MEASUREMENT SAR PROCEDURE UNCERTAINTIES .....	59
7.1. PROBE CALIBRATION UNCERTAINTY .....	59
7.2. ISOTROPY UNCERTAINTY .....	60
7.3. BOUNDARY EFFECT UNCERTAINTY .....	60
7.4. PROBE LINEARITY UNCERTAINTY .....	61
7.5. READOUT ELECTRONICS UNCERTAINTY .....	61
7.6. RESPONSE TIME UNCERTAINTY .....	61
7.7. INTEGRATION TIME UNCERTAINTY .....	62
7.8. PROBE POSITIONER MECHANICAL TOLERANCE .....	63
7.9. PROBE POSITIONING .....	63
7.10. PHANTOM UNCERTAINTY .....	64
7.11. DASY4 UNCERTAINTY BUDGET (FOR 2.4GHz) .....	65
7.12. DASY4 UNCERTAINTY BUDGET (FOR 5 ~ 6GHz) .....	66
8. INFORMATION ON THE TESTING LABORATORIES .....	67
APPENDIX A: TEST CONFIGURATIONS AND TEST DATA	
APPENDIX B: ADT SAR MEASUREMENT SYSTEM	
APPENDIX C: PHOTOGRAPHS OF SYSTEM VALIDATION	
APPENDIX D: SYSTEM CERTIFICATE & CALIBRATION	



## 1. CERTIFICATION

**PRODUCT:** Dual Band Wireless-N Notebook Adapter

**MODEL:** WPC600N

**BRAND:** Linksys

**APPLICANT:** Cisco-Linksys LLC

**TESTED :** Jul. 05 ~ Jul. 10, 2007

**TEST SAMPLE:** ENGINEERING SAMPLE

**STANDARDS:** FCC Part 2 (Section 2.1093)

FCC OET Bulletin 65, Supplement C (01-01)

RSS-102

IEEE 1528-2003

The above equipment (model: WPC600N) have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Wendy Liao , DATE: Jul. 17, 2007  
Wendy Liao / Senior Specialist

**TECHNICAL  
ACCEPTANCE** : Stanely Hsu , DATE: Jul. 17, 2007  
Responsible for RF Stanely Hsu / Senior Engineer

**APPROVED BY** : Gary Chang , DATE: Jul. 17, 2007  
Gary Chang / Supervisor



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Dual Band Wireless-N Notebook Adapter
<b>MODEL NO.</b>	WPC600N
<b>FCC ID</b>	Q87-WPC600NV11
<b>POWER SUPPLY</b>	3.3Vdc from host equipment
<b>CLASSIFICATION</b>	Portable device, production unit
<b>MODULATION TYPE</b>	CCK, DQPSK, DBPSK for DSSS, 64QAM, 16QAM, QPSK, BPSK for OFDM
<b>RADIO TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	802.11b: 11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps Draft 802.11n (20MHz): 130.0/ 117.0/ 104.0/ 78.0/ 52.0/ 39.0/ 26.0/ 13.0/ 65.0/ 58.5/ 52.0/ 29.0/ 26.0/ 19.5/ 13.0/ 6.5Mbps Draft 802.11n (40MHz): 270.0/ 243.0/ 216.0/ 162.0/ 108.0/ 81.0/ 54.0/ 27.0/ 135.0/ 121.5/ 108.0/ 81.0/ 54.0/ 40.5/ 27.0/ 13.5Mbps
<b>FREQUENCY RANGE</b>	2.4GHz: 2400 ~ 2483.5MHz 5.0GHz: 5150 ~ 5350MHz, 5470 ~ 5725MHz, 5725 ~ 5850MHz
<b>NUMBER OF CHANNEL</b>	2.4GHz: 11 for 802.11b, 802.11g, draft 802.11n (20MHz) 7 for draft 802.11n (40MHz) 5.0GHz: 5150 ~ 5350MHz, 5470 ~ 5725MHz: 19 for 802.11a, draft 802.11n (20MHz) 9 for draft 802.11n (40MHz) 5725 ~ 5850MHz: 5 for 802.11a, draft 802.11n (20MHz) 2 for draft 802.11n (40MHz)
<b>CHANNEL FREQUENCIES UNDER TEST AND ITS CONDUCTED OUTPUT POWER FOR 2.4GHz</b>	<b>802.11b:</b> 63.241mW / Ch1: 2412MHz 64.121mW / Ch6: 2437MHz 63.533mW / Ch11: 2462MHz <b>802.11g:</b> 101.859mW / Ch1: 2412MHz 141.906mW / Ch6: 2437MHz 100.925mW / Ch11: 2462MHz

	<p><b>DRAFT 802.11n (20MHz):</b></p> <p>161.634mW / Ch1: 2412MHz      159.783mW / Ch6: 2437MHz      127.507mW / Ch11: 2462MHz</p> <p><b>DRAFT 802.11n (40MHz):</b></p> <p>101.165mW / Ch1: 2422MHz      162.192W / Ch4: 2437MHz      113.904mW / Ch7: 2452MHz</p>
<b>CHANNEL FREQUENCIES UNDER TEST AND ITS CONDUCTED OUTPUT POWER FOR 5GHz</b>	<p>44.875mW / Ch36: 5180MHz      40.365mW / Ch48: 5240MHz      45.290mW / Ch52: 5260MHz      45.499mW / Ch64: 5320MHz      45.186mW / Ch100: 5500MHz      45.093mW / Ch104: 5520MHz      45.086mW / Ch116: 5580MHz      45.082mW / Ch120: 5600MHz      45.061mW / Ch124: 5620MHz      44.795mW / Ch136: 5680MHz      44.771mW / Ch140: 5700MHz      63.973mW / Ch149: 5745MHz      63.680mW / Ch157: 5785MHz      63.241mW / Ch165: 5825MHz</p> <p><b>DRAFT 802.11n (20MHz):</b></p> <p>47.817mW / Ch36: 5180MHz      47.909mW / Ch48: 5240MHz      45.033mW / Ch52: 5260MHz      45.397mW / Ch64: 5320MHz      35.771mW / Ch100: 5500MHz      36.758mW / Ch104: 5520MHz      36.854mW / Ch116: 5580MHz      36.227mW / Ch120: 5600MHz      36.925mW / Ch124: 5620MHz      36.771mW / Ch136: 5680MHz      35.648mW / Ch140: 5700MHz      81.544mW / Ch149: 5745MHz      81.452mW / Ch157: 5785MHz      81.174mW / Ch165: 5825MHz</p> <p><b>DRAFT 802.11n (40MHz):</b></p> <p>41.647mW / Ch38: 5190MHz      41.228mW / Ch46: 5230MHz      35.895mW / Ch54: 5270MHz      35.937mW / Ch62: 5310MHz      35.772mW / Ch102: 5510MHz      36.060mW / Ch118: 5590MHz      35.854mW / Ch134: 5670MHz      81.731mW / Ch151: 5755MHz      81.452mW / Ch159: 5795MHz</p>
<b>AVERAGE SAR (1g)</b>	0.450W/kg for 2.4GHz 0.302W/kg for 5GHz



<b>ANTENNA TYPE</b>	2.4GHz: PIFA antenna with 2.7dBi gain 5.0GHz: PIFA antenna with 1.2dBi gain
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	NA
<b>ACCESSORY DEVICES</b>	NA

**NOTE:**

1. The EUT incorporates a MIMO function. Physically, the card provides two completed transmitters and three receivers.
2. The EUT is 2 \* 3 spatial MIMO (2Tx & 3Rx) without beam forming function that only operate dual chain configuration (both chain 0 and chain 1 transceivers are operational).
3. When the EUT operating in 802.11b, 802.11g, 802.11a, the software operation, which is defined by manufacturer, only set single Tx.
4. When the EUT operating in draft 802.11n, the software operation, which is defined by manufacturer, only set 0 ~ 15 of "MCS" (MCS: Modulation and Coding Schemes) for dual Tx.
5. The EUT complies with draft 802.11n standards and backwards compatible with 802.11b, 802.11g, 802.11a products.
6. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 270Mbps.
7. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

## **2.2 GENERAL DESCRIPTION OF APPLIED STANDARDS**

According to the specifications of the manufacturer, this product must comply with the requirements of the following standards:

**FCC Part 2 (2.1093)**

**FCC OET Bulletin 65, Supplement C (01- 01)**

**RSS-102**

**IEEE 1528-2003**

All test items have been performed and recorded as per the above standards.



## 2.3 GENERAL INFORMATION OF THE SAR SYSTEM

DASY4 (software 4.7 Build 53) consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY4 software defined. The DASY4 software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.

### ET3DV6 ISOTROPIC E-FIELD PROBE (FREQUENCY BAND < 3GHz)

<b>CONSTRUCTION</b>	Symmetrical design with triangular core. Built-in optical fiber for surface detection system. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., glycoether).
<b>FREQUENCY</b>	10 MHz to 3 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 3 GHz)
<b>DYNAMIC RANGE</b>	5 $\mu$ W/g to > 100 mW/g; Linearity: $\pm 0.2$ dB
<b>OPTICAL SURFACE DETECTION</b>	$\pm 0.2$ mm repeatability in air and clear liquids over diffuse reflecting surfaces
<b>DIMENSIONS</b>	Overall length: 330 mm (Tip Length: 16 mm) Tip diameter: 6.8 mm (Body diameter: 12 mm) Distance from probe tip to dipole centers: 2.7 mm
<b>APPLICATION</b>	General dosimetric measurements up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (ET3DV6)



## EX3DV3 ISOTROPIC E-FIELD PROBE (FREQUENCY BAND 5 ~ 6GHz)

<b>DIMENSIONS</b>	Overall length: 330 mm (Tip Length: 20 mm) Tip diameter: 2.5 mm (Body diameter: 12 mm) Distance from probe tip to dipole centers: 1.0 mm
<b>APPLICATION</b>	General dosimetric measurements range 5 ~ 6 GHz. Fast automatic scanning in arbitrary phantoms (EX3DV3)

### NOTE

1. The Probe parameters have been calibrated by the SPEAG. Please reference "APPENDIX D" for the Calibration Certification Report.
2. For frequencies above 800 MHz, calibration in a rectangular wave-guide is used, because wave-guide size is manageable.
3. For frequencies below 800 MHz, temperature transfer calibration is used because the wave-guide size becomes relatively large.

## TWIN SAM V4.0

<b>CONSTRUCTION</b>	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-2003, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.
<b>SHELL THICKNESS</b>	2 ± 0.2mm
<b>FILLING VOLUME</b>	Approx. 25liters
<b>DIMENSIONS</b>	Height: 810mm; Length: 1000mm; Width: 500mm

## SYSTEM VALIDATION KITS:

<b>CONSTRUCTION</b>	Symmetrical dipole with 1/4 balun enables measurement of feedpoint impedance with NWA matched for use near flat phantoms filled with brain simulating solutions. Includes distance holder and tripod adaptor
<b>CALIBRATION</b>	Calibrated SAR value for specified position and input power at the flat phantom in brain simulating solutions
<b>FREQUENCY</b>	2450 , 5200, 5800 MHz



<b>RETURN LOSS</b>	> 20dB at specified validation position
<b>POWER CAPABILITY</b>	> 100W (f < 1GHz); > 40W (f > 1GHz)
<b>OPTIONS</b>	Dipoles for other frequencies or solutions and other calibration conditions upon request

## DEVICE HOLDER FOR SAM TWIN PHANTOM

<b>CONSTRUCTION</b>	The device holder for the mobile phone device is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles. The holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered. The device holder for the portable device makes up of the polyethylene foam. The dielectric parameters of material close to the dielectric parameters of the air.
---------------------	--

## DATA ACQUISITION ELECTRONICS

<b>CONSTRUCTION</b>	The data acquisition electronics (DAE3) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplex, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe is mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE3 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.
---------------------	--

## 2.4 GENERAL DESCRIPTION OF THE SPATIAL PEAK SAR EVALUATION

The DASY4 post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the micro-volt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Norm <sub>i</sub> , a <sub>i0</sub> , a <sub>i1</sub> , a <sub>i2</sub>
	- Conversion factor	ConvF <sub>i</sub>
	- Diode compression point	dcp <sub>i</sub>
Device parameters:	- Frequency	F
	- Crest factor	Cf
Media parameters:	- Conductivity	$\sigma$
	- Density	$\rho$

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \bullet \frac{cf}{dcp_i}$$

V <sub>i</sub>	=compensated signal of channel i	(i = x, y, z)
U <sub>i</sub>	=input signal of channel i	(i = x, y, z)
Cf	=crest factor of exciting field	(DASY parameter)
dcp <sub>i</sub>	=diode compression point	(DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-fieldprobes: } E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$\text{H-fieldprobes: } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

$V_i$	=compensated signal of channel i	$(i = x, y, z)$
$Norm_i$	=sensor sensitivity of channel i $\mu\text{V}/(\text{V}/\text{m})^2$ for E-field Probes	$(i = x, y, z)$
$ConvF$	= sensitivity enhancement in solution	
$a_{ij}$	= sensor sensitivity factors for H-field probes	
$F$	= carrier frequency [GHz]	
$E_i$	= electric field strength of channel i in $\text{V}/\text{m}$	
$H_i$	= magnetic field strength of channel i in $\text{A}/\text{m}$	

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{S}{r \cdot 1'000}$$

$SAR$	= local specific absorption rate in $\text{mW}/\text{g}$
$E_{tot}$	= total field strength in $\text{V}/\text{m}$
$\sigma$	= conductivity in $[\text{mho}/\text{m}]$ or $[\text{Siemens}/\text{m}]$
$\rho$	= equivalent tissue density in $\text{g}/\text{cm}^3$



Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid. The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. The extraction of the measured data (grid and values) from the Zoom Scan
2. The calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
3. The generation of a high-resolution mesh within the measured volume
4. The interpolation of all measured values from the measurement grid to the high-resolution grid
5. The extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
6. The calculation of the averaged SAR within masses of 1g and 10g.

The probe is calibrated at the center of the dipole sensors that is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated. The angle between the probe axis and the surface normal line is less than 30 degree.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extreme of the SAR distribution. The uncertainty on the locations of the extreme is less than 1/20 of the grid size. Only local maximum within -2dB of the global maximum are searched and passed for the Cube Scan measurement. In the Cube Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1g and 10g cubes, the extrapolation distance should not be larger than 5mm.



The maximum search is automatically performed after each area scan measurement. It is based on splines in two or three dimensions. The procedure can find the maximum for most SAR distributions even with relatively large grid spacing. After the area scanning measurement, the probe is automatically moved to a position at the interpolated maximum. The following scan can directly use this position for reference, e.g., for a finer resolution grid or the cube evaluations. The 1g and 10g peak evaluations are only available for the predefined cube 7 x 7 x 7 scans. The routines are verified and optimized for the grid dimensions used in these cube measurements. The measured volume of 30 x 30 x 30mm contains about 30g of tissue. The first procedure is an extrapolation (incl. boundary correction) to get the points between the lowest measured plane and the surface. The next step uses 3D interpolation to get all points within the measured volume in a 1mm grid (42875 points). In the last step, a 1g cube is placed numerically into the volume and its averaged SAR is calculated. This cube is moved around until the highest averaged SAR is found. If the highest SAR is found at the edge of the measured volume, the system will issue a warning: higher SAR values might be found outside of the measured volume. In that case the cube measurement can be repeated, using the new interpolated maximum as the center.



### 3. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	Dell	PP01L	TW-09C748-12800-16M-5064	FCC DoC Approved
2	NOTEBOOK	Compaq	N800C	470048-515	FCC DoC Approved
3	NOTEBOOK	Dell	D600	CN-0G5152-48643-49C-8226	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA
3	NA

**NOTE:** All power cords of the above support units are non shielded (1.8m).

## 4. DESCRIPTION OF TEST MODES AND CONFIGURATIONS

### 4.1. DESCRIPTION OF ANTENNA LOCATION



## 4.2. DESCRIPTION OF ASSESSMENT POSITION

The following test configurations have been applied in this test report:

	
<b>A: NOTEBOOK MODEL: N800C</b> The bottom of the EUT face to the phantom with 11mm-separation distance.	<b>B: NOTEBOOK MODEL: PP01L</b> The bottom of the EUT face to the phantom with 12mm-separation distance.
 <b>C: NOTEBOOK MODEL: D600</b> The bottom of the EUT face to the phantom with 14mm-separation distance.	

**NOTE:** The bottom of the notebook contacts to the bottom of the flat phantom with 0mm-separation distance.

### 4.3. DESCRIPTION OF TEST MODE

ITEM	TEST MODE	MODULATION	ASSESSMENT POSITION	TESTED CHANNEL
<b>FOR 2.4GHz</b>				
1	802.11b	DBPSK	A	L, M, H
2	802.11g	BPSK	A	L, M, H
3	Draft 802.11n (20MHz)	BPSK	A	L, M, H
4	Draft 802.11n (40MHz)	BPSK	A	L, M, H
5	802.11b	DBPSK	B	H
6	802.11g	BPSK	B	M
7	Draft 802.11n (20MHz)	BPSK	B	M
8	Draft 802.11n (40MHz)	BPSK	B	M
9	802.11b	DBPSK	C	H
10	802.11g	BPSK	C	M
11	Draft 802.11n (20MHz)	BPSK	C	M
12	Draft 802.11n (40MHz)	BPSK	C	M
<b>FOR 5GHz</b>				
13	802.11a	BPSK	A	36, 48, 52, 64, 100, 104, 116, 120, 124, 136, 140, 149, 157, 165
14	Draft 802.11n (20MHz)	BPSK	A	36, 48, 52, 64, 100, 104, 116, 120, 124, 136, 140, 149, 157, 165
15	Draft 802.11n (40MHz)	BPSK	A	38, 46, 54, 62, 102, 118, 134, 151, 159
16	802.11a	BPSK	B	64, 140, 165
17	Draft 802.11n (20MHz)	BPSK	B	64, 140, 165
18	Draft 802.11n (40MHz)	BPSK	B	46, 102, 159
19	802.11a	BPSK	C	64, 140, 165
20	Draft 802.11n (20MHz)	BPSK	C	64, 140, 165
21	Draft 802.11n (40MHz)	BPSK	C	46, 102, 159



#### 4.4. SUMMARY OF TEST RESULTS

COMMUNICATION MODE	802.11b	802.11g	Draft 802.11n (20MHz)	Draft 802.11n (40MHz)
TEST MODE	1	2	3	4

MEASURED VALUE OF 1g SAR ( W/kg)

CHANNEL	ASSESSMENT POSITION (A)			
LOW	0.426	0.304	0.285	0.226
MIDDLE	0.446	0.326	0.296	0.268
HIGH	<b>0.450</b>	0.314	0.283	0.238

COMMUNICATION MODE	802.11b	802.11g	Draft 802.11n (20MHz)	Draft 802.11n (40MHz)
TEST MODE	5	6	7	8

MEASURED VALUE OF 1g SAR ( W/kg)

CHANNEL	ASSESSMENT POSITION (B)			
LOW	-	-	-	-
MIDDLE	-	0.316	0.225	0.205
HIGH	0.392	-	-	-

COMMUNICATION MODE	802.11b	802.11g	Draft 802.11n (20MHz)	Draft 802.11n (40MHz)
TEST MODE	9	10	11	12
MEASURED VALUE OF 1g SAR ( W/kg)				
CHANNEL	ASSESSMENT POSITION (C)			
LOW	-	-	-	-
MIDDLE	-	0.238	0.150	0.133
HIGH	0.311	-	-	-

NOTE: The worst value has been marked by boldface.



COMMUNICATION MODE	802.11a	Draft 802.11n (20MHz)
TEST MODE	13	14
<b>MEASURED VALUE OF 1g SAR ( W/kg)</b>		
CHANNEL	<b>ASSESSMENT POSITION (A)</b>	
36	0.285	0.203
48	0.251	0.225
52	0.238	0.215
64	<b>0.302</b>	0.226
100	0.206	0.166
104	0.201	0.171
116	0.210	0.183
120	0.221	0.187
124	0.229	0.204
136	0.247	0.219
140	0.254	0.228
149	0.193	0.225
157	0.195	0.254
165	0.211	0.259

COMMUNICATION MODE	Draft 802.11n (40MHz)
TEST MODE	15
<b>MEASURED VALUE OF 1g SAR ( W/kg)</b>	
CHANNEL	<b>ASSESSMENT POSITION (A)</b>
38	0.188
46	0.195
54	0.192
62	0.190
102	0.186
118	0.182
134	0.185
151	0.209
159	0.211



COMMUNICATION MODE	802.11a	Draft 802.11n (20MHz)
TEST MODE	16	17
<b>MEASURED VALUE OF 1g SAR ( W/kg)</b>		
CHANNEL	<b>ASSESSMENT POSITION (B)</b>	
64	0.265	0.195
140	0.201	0.226
165	0.228	0.184

COMMUNICATION MODE	Draft 802.11n (40MHz)
TEST MODE	18
<b>MEASURED VALUE OF 1g SAR ( W/kg)</b>	
CHANNEL	<b>ASSESSMENT POSITION (B)</b>
46	0.162
102	0.156
159	0.174



COMMUNICATION MODE	802.11a	Draft 802.11n (20MHz)
TEST MODE	19	20
<b>MEASURED VALUE OF 1g SAR ( W/kg)</b>		
CHANNEL	<b>ASSESSMENT POSITION (C)</b>	
64	0.202	0.146
140	0.151	0.175
165	0.173	0.150

COMMUNICATION MODE	Draft 802.11n (40MHz)
TEST MODE	21
<b>MEASURED VALUE OF 1g SAR ( W/kg)</b>	
CHANNEL	<b>ASSESSMENT POSITION (C)</b>
46	0.106
102	0.088
159	0.112

## 5. TEST RESULTS

### 5.1 TEST PROCEDURES

The EUT plugged into the notebook. Use the software to control the EUT channel and transmission power. Then record the conducted power before the testing. Place the EUT to the specific test location. After the testing, must writing down the conducted power of the EUT into the report. The SAR value was calculated via the 3D spline interpolation algorithm that has been implemented in the software of DASY4 SAR measurement system manufactured and calibrated by SPEAG. According to the IEEE 1528 standards, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Verification of the power reference measurement
- Area scan
- Zoom scan
- Power reference measurement

The area scan was performed for the highest spatial SAR location. The zoom scan with 30mm x 30mm x 30mm volume was performed for SAR value averaged over 1g and 10g spatial volumes.



In the zoom scan, the distance between the measurement point at the probe sensor location (geometric center behind the probe tip) and the phantom surface is 4.0mm and maintained at a constant distance of  $\pm 1.0$ mm during a zoom scan to determine peak SAR locations. The distance is 4mm between the first measurement point and the bottom surface of the phantom. The secondary measurement point to the bottom surface of the phantom is with 9mm separation distance. The cube size is 7 x 7 x 7 points consist of 343 points and the grid space is 5mm.

The measurement time is 0.5s at each point of the zoom scan. The probe boundary effect compensation shall be applied during the SAR test. Because of the tip of the probe to the Phantom surface separated distances are longer than half a tip probe diameter.

In the area scan, the separation distance is 4mm between the each measurement point and the phantom surface. The scan size shall be included the transmission portion of the EUT. The measurement time is the same as the zoom scan. At last the reference power drift shall be less than  $\pm 5\%$ .



## 5.2 MEASURED SAR RESULTS

### 2.4GHz

ENVIRONMENTAL CONDITION		Air Temperature : 23.8°C, Liquid Temperature : 22.6°C Humidity : 62%RH					
TESTED BY		Long Chen			DATE		Jul. 05, 2007
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
1	2412 (Low)	802.11b	63.241	61.841	-2.21	1	0.426
6	2437 (Mid.)	802.11b	64.121	62.875	-1.94	1	0.446
11	2462 (High)	802.11b	63.533	62.146	-2.18	1	0.450
1	2412 (Low)	802.11g	101.859	100.184	-1.64	2	0.304
6	2437 (Mid.)	802.11g	141.906	139.531	-1.67	2	0.326
11	2462 (High)	802.11g	100.925	99.144	-1.76	2	0.314

#### NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



ENVIRONMENTAL CONDITION		Air Temperature : 23.8°C, Liquid Temperature : 22.6°C Humidity : 62%RH					
TESTED BY		Long Chen			DATE	Jul. 05, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
1	2412 (Low)	DRAFT 802.11n (20MHz)	161.634	159.124	-1.55	3	0.285
6	2437 (Mid.)	DRAFT 802.11n (20MHz)	159.783	157.223	-1.60	3	0.296
11	2462 (High)	DRAFT 802.11n (20MHz)	127.507	125.027	-1.94	3	0.283
1	2422 (Low)	DRAFT 802.11n (40MHz)	101.165	99.845	-1.30	4	0.226
4	2437 (Mid.)	DRAFT 802.11n (40MHz)	162.192	160.021	-1.34	4	0.268
7	2452 (High)	DRAFT 802.11n (40MHz)	113.904	111.982	-1.69	4	0.238

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



ENVIRONMENTAL CONDITION		Air Temperature : 23.8°C, Liquid Temperature : 22.6°C Humidity : 62%RH						
TESTED BY		Long Chen				DATE	Jul. 05, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)	
			BEGIN TEST	AFTER TEST				
11	2462 (High)	802.11b	63.533	62.345	-1.87	5	0.392	
6	2437 (Mid.)	802.11g	141.906	140.128	-1.25	6	0.316	

**NOTE:**

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



ENVIRONMENTAL CONDITION		Air Temperature : 23.8°C, Liquid Temperature : 22.6°C Humidity : 62%RH					
TESTED BY		Long Chen			DATE	Jul. 05, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
6	2437 (Mid.)	DRAFT 802.11n (20MHz)	159.783	158.026	-1.10	7	0.225
4	2437 (Mid.)	DRAFT 802.11n (40MHz)	162.192	160.182	-1.24	8	0.205

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



ENVIRONMENTAL CONDITION		Air Temperature : 23.8°C, Liquid Temperature : 22.6°C Humidity : 62%RH					
TESTED BY		Long Chen			DATE	Jul. 05, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
11	2462 (High)	802.11b	63.533	62.547	-1.55	9	0.311
6	2437 (Mid.)	802.11g	141.906	140.239	-1.17	10	0.238

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



ENVIRONMENTAL CONDITION		Air Temperature : 23.8°C, Liquid Temperature : 22.6°C Humidity : 62%RH					
TESTED BY		Long Chen			DATE	Jul. 05, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
6	2437 (Mid.)	DRAFT 802.11n (20MHz)	159.783	157.518	-1.42	11	0.150
4	2437 (Mid.)	DRAFT 802.11n (40MHz)	162.192	160.024	-1.34	12	0.133

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



## 5GHz

ENVIRONMENTAL CONDITION		Air Temperature : 23.5°C, Liquid Temperature : 22.3°C Humidity : 61%RH					
TESTED BY		Long Chen			DATE		Jul. 09, 2007
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
36	5180.000	802.11a	44.875	43.968	-2.02	13	0.285
48	5240.000	802.11a	40.365	38.951	-3.50	13	0.251
52	5260.000	802.11a	45.290	44.132	-2.56	13	0.238
64	5320.000	802.11a	45.499	44.224	-2.80	13	0.302
100	5500.000	802.11a	45.186	44.297	-1.97	13	0.206
104	5520.000	802.11a	45.093	44.121	-2.16	13	0.201
116	5580.000	802.11a	45.086	44.114	-2.16	13	0.210
120	5600.000	802.11a	45.082	44.205	-1.95	13	0.221
124	5620.000	802.11a	45.061	44.362	-1.55	13	0.229
136	5680.000	802.11a	44.795	43.521	-2.84	13	0.247
140	5700.000	802.11a	44.771	43.599	-2.62	13	0.254
149	5745.000	802.11a	63.973	62.300	-2.62	13	0.193
157	5785.000	802.11a	63.680	61.840	-2.89	13	0.195
165	5825.000	802.11a	63.241	61.870	-2.17	13	0.211

### NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



ENVIRONMENTAL CONDITION			Air Temperature : 23.5°C, Liquid Temperature : 22.3°C Humidity : 61%RH				
TESTED BY		Long Chen			DATE	Jul. 10, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
36	5180.000	DRAFT 802.11n (20MHz)	47.817	46.553	-2.64	14	0.203
48	5240.000	DRAFT 802.11n (20MHz)	47.909	46.688	-2.55	14	0.225
52	5260.000	DRAFT 802.11n (20MHz)	45.033	43.982	-2.33	14	0.215
64	5320.000	DRAFT 802.11n (20MHz)	45.397	44.125	-2.80	14	0.226
100	5500.000	DRAFT 802.11n (20MHz)	35.771	34.589	-3.30	14	0.166
104	5520.000	DRAFT 802.11n (20MHz)	36.758	35.598	-3.16	14	0.171
116	5580.000	DRAFT 802.11n (20MHz)	36.854	35.824	-2.79	14	0.183

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



ENVIRONMENTAL CONDITION			Air Temperature : 23.6°C, Liquid Temperature : 22.3°C Humidity : 63%RH				
TESTED BY		Long Chen			DATE	Jul. 10, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
120	5600.000	DRAFT 802.11n (20MHz)	36.227	35.198	-2.84	14	0.187
124	5620.000	DRAFT 802.11n (20MHz)	36.925	35.768	-3.13	14	0.204
136	5680.000	DRAFT 802.11n (20MHz)	36.771	35.689	-2.94	14	0.219
140	5700.000	DRAFT 802.11n (20MHz)	35.648	34.589	-2.97	14	0.228
149	5745.000	DRAFT 802.11n (20MHz)	81.544	79.858	-2.07	14	0.225
157	5785.000	DRAFT 802.11n (20MHz)	81.452	79.685	-2.17	14	0.254
165	5825.000	DRAFT 802.11n (20MHz)	81.174	79.033	-2.64	14	0.259

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



ENVIRONMENTAL CONDITION			Air Temperature : 23.6°C, Liquid Temperature : 22.3°C Humidity : 63%RH				
TESTED BY			Long Chen		DATE		Jul. 10, 2007
CHAN.	FREQ. (MHz)	TEST MODE	CONDUCTED POWER (mW)		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
			BEGIN TEST	AFTER TEST			
38	5190.000	DRAFT 802.11n (40MHz)	41.647	40.654	-2.38	15	0.188
46	5230.000	DRAFT 802.11n (40MHz)	41.228	40.315	-2.21	15	0.195
54	5270.000	DRAFT 802.11n (40MHz)	35.895	34.855	-2.90	15	0.192
62	5310.000	DRAFT 802.11n (40MHz)	35.937	34.886	-2.92	15	0.190
102	5510.000	DRAFT 802.11n (40MHz)	35.772	34.842	-2.60	15	0.186
118	5590.000	DRAFT 802.11n (40MHz)	36.060	35.112	-2.63	15	0.182
134	5670.000	DRAFT 802.11n (40MHz)	35.854	34.844	-2.82	15	0.185
151	5755.000	DRAFT 802.11n (40MHz)	81.731	79.684	-2.50	15	0.209
159	5795.000	DRAFT 802.11n (40MHz)	81.452	79.621	-2.25	15	0.211

NOTE:

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



<b>ENVIRONMENTAL CONDITION</b>		Air Temperature : 23.6°C, Liquid Temperature : 22.3°C Humidity : 63%RH						
<b>TESTED BY</b>		Long Chen				<b>DATE</b>	Jul. 10, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	<b>CONDUCTED POWER (mW)</b>		POWER DRIFT (%)	DEVICE TEST POSITION MODE	<b>MEASURED 1g SAR (W/kg)</b>	
BEGIN TEST	AFTER TEST							
64	5320.000	802.11a	45.499	44.236	-2.78	16	0.265	
140	5700.000	802.11a	44.771	43.652	-2.50	16	0.201	
165	5825.000	802.11a	63.241	61.840	-2.22	16	0.228	

**NOTE:**

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



<b>ENVIRONMENTAL CONDITION</b>			Air Temperature : 23.6°C, Liquid Temperature : 22.3°C Humidity : 63%RH				
<b>TESTED BY</b>		Long Chen			<b>DATE</b>		Jul. 11, 2007
CHAN.	FREQ. (MHz)	TEST MODE	<b>CONDUCTED POWER (mW)</b>		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
64	5320.000	DRAFT 802.11n (20MHz)	BEGIN TEST	AFTER TEST	-2.60	17	0.195
140	5700.000	DRAFT 802.11n (20MHz)	35.648	34.602	-2.93	17	0.226
165	5825.000	DRAFT 802.11n (20MHz)	81.174	78.854	-2.86	17	0.184

**NOTE:**

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



<b>ENVIRONMENTAL CONDITION</b>			Air Temperature : 23.6°C, Liquid Temperature : 22.3°C Humidity : 63%RH				
<b>TESTED BY</b>		Long Chen			<b>DATE</b>	Jul. 11, 2007	
CHAN.	FREQ. (MHz)	TEST MODE	<b>CONDUCTED POWER (mW)</b>		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
BEGIN TEST	AFTER TEST						
46	5230.000	DRAFT 802.11n (40MHz)	41.228	40.025	-2.92	18	0.162
102	5510.000	DRAFT 802.11n (40MHz)	35.772	34.854	-2.57	18	0.156
159	5795.000	DRAFT 802.11n (40MHz)	81.452	79.245	-2.71	18	0.174

**NOTE:**

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



<b>ENVIRONMENTAL CONDITION</b>			Air Temperature : 23.4°C, Liquid Temperature : 22.1°C Humidity : 62%RH				
<b>TESTED BY</b>		Long Chen			<b>DATE</b>		Jul. 11, 2007
CHAN.	FREQ. (MHz)	TEST MODE	<b>CONDUCTED POWER (mW)</b>		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
64	5320.000	802.11a	BEGIN TEST	AFTER TEST	-2.49	19	0.202
140	5700.000	802.11a	44.771	43.687	-2.42	19	0.151
165	5825.000	802.11a	63.241	61.568	-2.65	19	0.173

**NOTE:**

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, 1.6 W/kg, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



<b>ENVIRONMENTAL CONDITION</b>			Air Temperature : 23.4°C, Liquid Temperature : 22.1°C Humidity : 62%RH				
<b>TESTED BY</b>		Long Chen			<b>DATE</b>		Jul. 11, 2007
CHAN.	FREQ. (MHz)	TEST MODE	<b>CONDUCTED POWER (mW)</b>		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
64	5320.000	DRAFT 802.11n (20MHz)	BEGIN TEST	AFTER TEST	-2.45	20	0.146
140	5700.000	DRAFT 802.11n (20MHz)	35.648	34.588	-2.97	20	0.175
165	5825.000	DRAFT 802.11n (20MHz)	81.174	79.263	-2.35	20	0.150

**NOTE:**

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



<b>ENVIRONMENTAL CONDITION</b>			Air Temperature : 23.4°C, Liquid Temperature : 22.1°C Humidity : 62%RH				
<b>TESTED BY</b>		Long Chen			<b>DATE</b>		Jul. 11, 2007
CHAN.	FREQ. (MHz)	TEST MODE	<b>CONDUCTED POWER (mW)</b>		POWER DRIFT (%)	DEVICE TEST POSITION MODE	MEASURED 1g SAR (W/kg)
46	5230.000	DRAFT 802.11n (40MHz)	BEGIN TEST	AFTER TEST	-2.47	21	0.106
102	5510.000	DRAFT 802.11n (40MHz)	35.772	34.685	-3.04	21	0.088
159	5795.000	DRAFT 802.11n (40MHz)	81.452	79.365	-2.56	21	0.112

**NOTE:**

1. Test configuration of each mode is described in section 3.
2. In this testing, the limit for General Population Spatial Peak averaged over 1g, **1.6 W/kg**, is applied.
3. Please see the Appendix A for the data.
4. The variation of the EUT conducted power measured before and after SAR testing should not over 5%.



### 5.3 SAR LIMITS

HUMAN EXPOSURE	SAR (W/kg)	
	(GENERAL POPULATION / UNCONTROLLED EXPOSURE ENVIRONMENT)	(OCCUPATIONAL / CONTROLLED EXPOSURE ENVIRONMENT)
Spatial Average (whole body)	0.08	0.4
Spatial Peak (averaged over 1 g)	<b>1.6</b>	8.0
Spatial Peak (hands / wrists / feet / ankles averaged over 10 g)	4.0	20.0

**NOTE:**

1. This limits accord to 47 CFR 2.1093 – Safety Limit.
2. The EUT property been complied with the partial body exposure limit under the general population environment.

## 5.4 RECIPES FOR TISSUE SIMULATING LIQUIDS

For the measurement of the field distribution inside the SAM phantom, the phantom must be filled with 25 litters of tissue simulation liquid.

The following ingredients are used :

- **WATER-** Deionized water (pure H<sub>2</sub>O), resistivity  $\geq 16$  M - as basis for the liquid
- **SUGAR-** Refined sugar in crystals, as available in food shops - to reduce relative permittivity
- **SALT-** Pure NaCl - to increase conductivity
- **CELLULOSE-** Hydroxyethyl-cellulose, medium viscosity (75-125mPa.s, 2% in water, 20°C),  
CAS # 54290 - to increase viscosity and to keep sugar in solution
- **PRESERVATIVE-** Preventol D-7 Bayer AG, D-51368 Leverkusen, CAS # 55965-84-9 - to prevent the spread of bacteria and molds
- **DGMBE-** Diethylenglycol-monobutyl ether (DGMBE), Fluka Chemie GmbH,  
CAS # 112-34-5 - to reduce relative permittivity

### THE RECIPES FOR 2450MHz SIMULATING LIQUID TABLE

INGREDIENT	HEAD SIMULATING LIQUID 2450MHz (HSL-2450)	MUSCLE SIMULATING LIQUID 2450MHz (MSL-2450)
Water	45%	69.83%
DGMBE	55%	30.17%
Salt	NA	NA
Dielectric Parameters at 22°C	$f = 2450\text{MHz}$ $\epsilon = 39.2 \pm 5\%$ $\sigma = 1.80 \pm 5\% \text{ S/m}$	$f = 2450\text{MHz}$ $\epsilon = 52.7 \pm 5\%$ $\sigma = 1.95 \pm 5\% \text{ S/m}$



## THE INFORMATION FOR 5GHz SIMULATING LIQUID

**The 5GHz liquids was purchased from SPEAG.**

**Body liquid model:** HSL 5800, P/N: SL AAH 5800 AA

**Head liquid model:** M 5800, P/N: SL AAM 580 AD

**5GHz liquids contain the following ingredients:**

Water 64 - 78%

Mineral Oil 11 - 18%

Emulsifiers 9 - 15%

Additives and Salt 2 - 3%

Testing the liquids using the Agilent Network Analyzer E8358A and Agilent Dielectric Probe Kit 85070D. The testing procedure is following as

1. Turn Network Analyzer on and allow at least 30min. warm up.
2. Mount dielectric probe kit so that interconnecting cable to Network Analyzer will not be moved during measurements or calibration.
3. Pour de-ionized water and measure water temperature ( $\pm 1^\circ$ ).
4. Set water temperature in Agilent-Software (Calibration Setup).
5. Perform calibration.
6. Validate calibration with dielectric material of known properties (e.g. polished ceramic slab with >8mm thickness  $\epsilon' = 10.0$ ,  $\epsilon'' = 0.0$ ). If measured parameters do not fit within tolerance, repeat calibration ( $\pm 0.2$  for  $\epsilon'$ :  $\pm 0.1$  for  $\epsilon''$ ).
7. Conductivity can be calculated from  $\epsilon''$  by  $\sigma = \omega \epsilon_0 \epsilon'' = \epsilon'' f [\text{GHz}] / 18$ .
8. Measure liquid shortly after calibration. Repeat calibration every hour.
9. Stir the liquid to be measured. Take a sample (~ 50ml) with a syringe from the center of the liquid container.
10. Pour the liquid into a small glass flask. Hold the syringe at the bottom of the flask to avoid air bubbles.
11. Put the dielectric probe in the glass flask. Check that there are no air bubbles in front of the opening in the dielectric probe kit.
12. Perform measurements.
13. Adjust medium parameters in DASY4 for the frequencies necessary for the measurements ('Setup Config', select medium (e.g. Brain 900MHz) and press 'Option'-button).
14. Select the current medium for the frequency of the validation (e.g. Setup Medium Brain 900MHz).



### FOR 2.4GHz BAND SIMULATING LIQUID

LIQUID TYPE		HSL-2450		MSL-2450	
SIMULATING LIQUID TEMP.		NA		22.6	
TEST DATE		NA		Jul. 05, 2007	
TESTED BY		NA		Long Chen	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
2412.0	Permitivity ( $\epsilon$ )	NA	NA	52.8	52.5
2422.0		NA	NA	52.7	52.4
2437.0		NA	NA	52.7	52.3
2450.0		NA	NA	52.7	52.2
2452.0		NA	NA	52.7	52.1
2462.0		NA	NA	52.7	52.0
2412.0	Conductivity ( $\sigma$ ) S/m	NA	NA	1.91	1.99
2422.0		NA	NA	1.92	2.00
2437.0		NA	NA	1.94	2.01
2450.0		NA	NA	1.95	2.02
2452.0		NA	NA	1.95	2.03
2462.0		NA	NA	1.97	2.04
Dielectric Parameters Required at 22°C		$f = 2450\text{MHz}$ $\epsilon = 39.2 \pm 5\%$ $\sigma = 1.80 \pm 5\% \text{ S/m}$		$f = 2450\text{MHz}$ $\epsilon = 52.7 \pm 5\%$ $\sigma = 1.95 \pm 5\% \text{ S/m}$	

**FOR 5.0GHz BAND SIMULATING LIQUID****BAND (5.150 ~ 5.350GHz)**

LIQUID TYPE		HSL-5200		MSL-5200	
SIMULATING LIQUID TEMP.		NA		22.3	
TEST DATE		NA		Jul. 09, 2007	
TESTED BY		NA		Long Chen	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5180	Permitivity ( $\epsilon$ )	NA	NA	49.00	51
5190		NA	NA	49.00	51
5200		NA	NA	49.00	51
5230		NA	NA	49.00	50.9
5240		NA	NA	49.00	50.9
5260		NA	NA	48.90	50.9
5270		NA	NA	48.90	50.9
5310		NA	NA	48.90	50.8
5320		NA	NA	48.90	50.8
5180	Conductivity ( $\sigma$ ) S/m	NA	NA	5.28	5.29
5190		NA	NA	5.29	5.30
5200		NA	NA	5.30	5.32
5230		NA	NA	5.33	5.36
5240		NA	NA	5.35	5.38
5260		NA	NA	5.37	5.41
5270		NA	NA	5.38	5.42
5310		NA	NA	5.43	5.48
5320		NA	NA	5.44	5.50
Dielectric Parameters Required at 21°C					

**BAND (5.470 ~ 5.850GHz)**

LIQUID TYPE		HSL-5800		MSL-5800	
SIMULATING LIQUID TEMP.		NA		22.3	
TEST DATE		NA		Jul. 09, 2007	
TESTED BY		NA		Long Chen	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5500	Permitivity ( $\epsilon$ )	NA	NA	48.60	50.40
5510		NA	NA	48.60	50.40
5520		NA	NA	48.60	50.40
5580		NA	NA	48.50	50.20
5590		NA	NA	48.50	50.50
5600		NA	NA	48.50	50.20
5620		NA	NA	48.40	50.10
5670		NA	NA	48.40	50.00
5680		NA	NA	48.40	50.00
5700		NA	NA	48.30	50.00
5745		NA	NA	48.30	49.90
5755		NA	NA	48.30	49.90
5785		NA	NA	48.20	49.80
5795		NA	NA	48.20	49.80
5800	Conductivity ( $\sigma$ ) S/m	NA	NA	48.20	49.80
5825		NA	NA	48.20	49.80
5500		NA	NA	5.65	5.76
5510		NA	NA	5.66	5.78
5520		NA	NA	5.67	5.79
5580		NA	NA	5.74	5.88
5590		NA	NA	5.75	5.83
5600		NA	NA	5.77	5.91
5620		NA	NA	5.79	5.94
5670		NA	NA	5.85	6.02
5680		NA	NA	5.86	6.03
5700		NA	NA	5.88	6.07



FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5745	Conductivity ( $\sigma$ ) S/m	NA	NA	5.94	6.14
5755		NA	NA	5.95	6.15
5785		NA	NA	5.98	6.20
5795		NA	NA	5.99	6.21
5800		NA	NA	6.00	6.22
5825		NA	NA	6.03	6.26
<b>Dielectric Parameters Required at 21°C</b>					

**BAND (5.150 ~ 5.350GHz)**

LIQUID TYPE		HSL-5200		MSL-5200	
SIMULATING LIQUID TEMP.		NA		22.3	
TEST DATE		NA		Jul. 10, 2007	
TESTED BY		NA		Long Chen	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5180	Permitivity ( $\epsilon$ )	NA	NA	49.00	51.2
5190		NA	NA	49.00	51.2
5200		NA	NA	49.00	51.2
5230		NA	NA	49.00	51.1
5240		NA	NA	49.00	51.1
5260		NA	NA	48.90	51.0
5270		NA	NA	48.90	50.9
5310		NA	NA	48.90	50.9
5320		NA	NA	48.90	50.9
5180	Conductivity ( $\sigma$ ) S/m	NA	NA	5.28	5.28
5190		NA	NA	5.29	5.30
5200		NA	NA	5.30	5.31
5230		NA	NA	5.33	5.36
5240		NA	NA	5.35	5.37
5260		NA	NA	5.37	5.40
5270		NA	NA	5.38	5.42
5310		NA	NA	5.43	5.47
5320		NA	NA	5.44	5.49
Dielectric Parameters Required at 21°C					

**BAND (5.470 ~ 5.850GHz)**

LIQUID TYPE		HSL-5800		MSL-5800	
SIMULATING LIQUID TEMP.		NA		22.3	
TEST DATE		NA		Jul. 10, 2007	
TESTED BY		NA		Long Chen	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5500	Permitivity ( $\epsilon$ )	NA	NA	48.60	50.60
5510		NA	NA	48.60	50.60
5520		NA	NA	48.60	50.50
5580		NA	NA	48.50	50.40
5590		NA	NA	48.50	50.40
5600		NA	NA	48.50	50.30
5620		NA	NA	48.40	50.30
5670		NA	NA	48.40	50.20
5680		NA	NA	48.40	50.20
5700		NA	NA	48.30	50.20
5745		NA	NA	48.30	50.10
5755		NA	NA	48.30	50.10
5785		NA	NA	48.20	50.00
5795		NA	NA	48.20	50.00
5800	Conductivity ( $\sigma$ ) S/m	NA	NA	48.20	50.00
5825		NA	NA	48.20	49.90
5500		NA	NA	5.65	5.75
5510		NA	NA	5.66	5.77
5520		NA	NA	5.67	5.78
5580		NA	NA	5.74	5.87
5590		NA	NA	5.75	5.89
5600		NA	NA	5.77	5.90
5620		NA	NA	5.79	5.93
5670		NA	NA	5.85	6.01
5680		NA	NA	5.86	6.02
5700		NA	NA	5.88	6.06



FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5745	Conductivity ( $\sigma$ ) S/m	NA	NA	5.94	6.13
5755		NA	NA	5.95	6.14
5785		NA	NA	5.98	6.19
5795		NA	NA	5.99	6.20
5800		NA	NA	6.00	6.21
5825		NA	NA	6.03	6.25
<b>Dielectric Parameters Required at 21°C</b>					

**BAND (5.150 ~ 5.350GHz)**

LIQUID TYPE		HSL-5200		MSL-5200	
SIMULATING LIQUID TEMP.		NA		22.1	
TEST DATE		NA		Jul. 11, 2007	
TESTED BY		NA		Long Chen	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5180	Permitivity ( $\epsilon$ )	NA	NA	49.00	50.80
5190		NA	NA	49.00	50.80
5200		NA	NA	49.00	50.80
5230		NA	NA	49.00	50.70
5240		NA	NA	49.00	50.70
5260		NA	NA	48.90	50.70
5270		NA	NA	48.90	50.70
5310		NA	NA	48.90	50.60
5320		NA	NA	48.90	50.60
5180	Conductivity ( $\sigma$ ) S/m	NA	NA	5.28	5.27
5190		NA	NA	5.29	5.28
5200		NA	NA	5.30	5.29
5230		NA	NA	5.33	5.34
5240		NA	NA	5.35	5.36
5260		NA	NA	5.37	5.38
5270		NA	NA	5.38	5.40
5310		NA	NA	5.43	5.46
5320		NA	NA	5.44	5.47
Dielectric Parameters Required at 21°C					

**BAND (5.470 ~ 5.850GHz)**

LIQUID TYPE		HSL-5800		MSL-5800	
SIMULATING LIQUID TEMP.		NA		22.1	
TEST DATE		NA		Jul. 11, 2007	
TESTED BY		NA		Long Chen	
FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5500	Permitivity ( $\epsilon$ )	NA	NA	48.60	50.20
5510		NA	NA	48.60	50.20
5520		NA	NA	48.60	50.20
5580		NA	NA	48.50	50.00
5590		NA	NA	48.50	50.00
5600		NA	NA	48.50	50.00
5620		NA	NA	48.40	49.90
5670		NA	NA	48.40	49.80
5680		NA	NA	48.40	49.80
5700		NA	NA	48.30	49.80
5745		NA	NA	48.30	49.70
5755		NA	NA	48.30	49.70
5785		NA	NA	48.20	49.60
5795		NA	NA	48.20	49.60
5800	Conductivity ( $\sigma$ ) S/m	NA	NA	48.20	49.60
5825		NA	NA	48.20	49.60
5500		NA	NA	5.65	5.74
5510		NA	NA	5.66	5.75
5520		NA	NA	5.67	5.76
5580		NA	NA	5.74	5.85
5590		NA	NA	5.75	5.87
5600		NA	NA	5.77	5.88
5620		NA	NA	5.79	5.91
5670		NA	NA	5.85	5.99
5680		NA	NA	5.86	6.01
5700		NA	NA	5.88	6.04



FREQ. (MHz)	LIQUID PARAMETER	STANDARD VALUE	MEASUREMENT VALUE	STANDARD VALUE	MEASUREMENT VALUE
5745	Conductivity ( $\sigma$ ) S/m	NA	NA	5.94	6.11
5755		NA	NA	5.95	6.12
5785		NA	NA	5.98	6.17
5795		NA	NA	5.99	6.19
5800		NA	NA	6.00	6.19
5825		NA	NA	6.03	6.23
<b>Dielectric Parameters Required at 21°C</b>					



## 5.5 TEST EQUIPMENT FOR TISSUE PROPERTY

ITEM	NAME	BAND	TYPE	SERIES NO.	CALIBRATED UNTIL
1	Network Analyzer	Agilent	E8358A	US41480538	Nov. 06, 2007
2	Dielectric Probe	Agilent	85070D	US01440176	NA

**NOTE:**

1. Before starting, all test equipment shall be warmed up for 30min.
2. The tolerance ( $k=1$ ) specified by Agilent for general dielectric measurements, deriving from inaccuracies in the calibration data, analyzer drift, and random errors, are usually  $\pm 2.5\%$  and  $\pm 5\%$  for measured permittivity and conductivity, respectively. However, the tolerances for the conductivity is smaller for material with large loss tangents, i.e., less than  $\pm 2.5\%$  ( $k=1$ ). It can be substantially smaller if more accurate methods are applied.



## 6. SYSTEM VALIDATION

The system validation was performed in the flat phantom with equipment listed in the following table. Since the SAR value is calculated from the measured electric field, dielectric constant and conductivity of the body tissue, and the SAR is proportional to the square of the electric field. So, the SAR value will be also proportional to the RF power input to the system validation dipole under the same test environment. In our system validation test, 250mW RF input power was used.

### 6.1 TEST EQUIPMENT

ITEM	NAME	BAND	TYPE	SERIES NO.	CALIBRATED UNTIL
1	SAM Phantom	S & P	QD000 P40 CA	PT-1150	NA
2	Signal Generator	Anritsu	68247B	984703	May 18, 2008
3	E-Field Probe	Speaq	EX3DV6	3504	Nov. 22, 2007
4	E-Field Probe	Speaq	ET3DV6	1790	Nov. 22, 2007
5	DAE	Speaq	DAE3 V1	510	Sep. 06, 2007
6	Robot Positioner	Staubli Unimation	NA	NA	NA
7	Validation Dipole	Speaq	D2450V2	716	Aug. 20, 2007
8	Validation Dipole	Speaq	D5GHzV2	1018	Apr. 18, 2008
9	Power Meter	Agilent	E4416A	GB41291763	May 27, 2008
10	Peak and Average Power Sensor	Agilent	E9327A	US40441181	May 27, 2008

**NOTE:** Before starting the measurement, all test equipment shall be warmed up for 30min.

## 6.2 TEST PROCEDURE

Before the system performance check, we need only to tell the system which components (probe, medium, and device) are used for the system performance check; the system will take care of all parameters. The dipole must be placed beneath the flat section of the SAM Twin Phantom with the correct distance holder in place. The distance holder should touch the phantom surface with a light pressure at the reference marking (little cross) and be oriented parallel to the long side of the phantom. Accurate positioning is not necessary, since the system will search for the peak SAR location, except that the dipole arms should be parallel to the surface. The device holder for mobile phones can be left in place but should be rotated away from the dipole.

The "Power Reference Measurement" and "Power Drift Measurement" jobs are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the amplifier output power. If it is too high (above  $\pm 0.1$  dB), the system performance check should be repeated; some amplifiers have very high drift during warm-up. A stable amplifier gives drift results in the DASY system below  $\pm 0.02$  dB.

The "Surface Check" job tests the optical surface detection system of the DASY system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above  $\pm 0.1$  mm). In that case it is better to abort the system performance check and stir the liquid. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within  $\pm 30^\circ$ .) However, varying breaking indices of different liquid compositions might also influence the distance. If the indicated difference varies from the actual setting, the probe parameter "optical surface



The "Area Scan" job measures the SAR above the dipole on a plane parallel to the surface. It is used to locate the approximate location of the peak SAR. The proposed scan uses large grid spacing for faster measurement; due to the symmetric field, the peak detection is reliable. If a finer graphic is desired, the grid spacing can be reduced. Grid spacing and orientation have no influence on the SAR result.

The "Zoom Scan" job measures the field in a volume around the peak SAR value assessed in the previous "Area Scan" job (for more information see the application note on SAR evaluation).

About the validation dipole positioning uncertainty, the constant and low loss dielectric spacer is used to establish the correct distance between the top surface of the dipole and the bottom surface of the phantom, the error component introduced by the uncertainty of the distance between the liquid (i.e., phantom shell) and the validation dipole in the DASY4 system is less than  $\pm 0.1\text{mm}$ .

$$SAR_{tolerance}[\%] = 100 \times \left( \frac{(a + d)^2}{a^2} - 1 \right)$$

As the closest distance is 10mm, the resulting tolerance  $SAR_{tolerance}[\%]$  is  $<2\%$ .



### 6.3 VALIDATION RESULTS

2450MHz SYSTEM VALIDATION TEST IN THE MUSCLE SIMULATING LIQUID					
TEST FREQUENCY (MHz)	REQUIRED SAR (mW/g)	MEASURED SAR (mW/g)	DEVIATION (%)	SEPARATION DISTANCE	TEST DATE
MSL2450	13.40 (1g)	12.70	-5.55	10mm	Jul. 05, 2007
MSL5200	19.50 (1g)	18.50	-5.13	10mm	Jul. 09, 2007
MSL5200	19.50 (1g)	18.30	-6.15	10mm	Jul. 10, 2007
MSL5200	19.50 (1g)	18.60	-4.62	10mm	Jul. 11, 2007
MSL5500	19.60 (1g)	19.00	-3.06	10mm	Jul. 09, 2007
MSL5500	19.60 (1g)	18.60	-5.10	10mm	Jul. 10, 2007
MSL5500	19.60 (1g)	18.80	-4.08	10mm	Jul. 11, 2007
MSL5800	17.60 (1g)	16.60	-5.68	10mm	Jul. 09, 2007
MSL5800	17.60 (1g)	16.70	-5.11	10mm	Jul. 10, 2007
MSL5800	17.60 (1g)	16.80	-4.55	10mm	Jul. 11, 2007
TESTED BY	Long Chen				

**NOTE:** Please see Appendix for the photo of system validation test.

## 6.4 SYSTEM VALIDATION UNCERTAINTIES

In the table below, the system validation uncertainty with respect to the analytically assessed SAR value of a dipole source as given in the IEEE 1528 standard is given. This uncertainty is smaller than the expected uncertainty for mobile phone measurements due to the simplified setup and the symmetric field distribution.

Error Description	Tolerance (±%)	Probability Distribution	Divisor	(C <sub>i</sub> )		Standard Uncertainty (±%)		(v <sub>i</sub> )
				(1g)	(10g)	(1g)	(10g)	
<b>Measurement System</b>								
Probe Calibration	4.8	Normal	1	1	1	4.8	4.8	∞
Axial Isotropy	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	∞
Hemispherical Isotropy	0	Rectangular	$\sqrt{3}$	1	1	0	0	∞
Boundary effect	1.0	Rectangular	$\sqrt{3}$	1	1	0.6	0.6	∞
Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	∞
System Detection Limit	1.0	Rectangular	$\sqrt{3}$	1	1	0.6	0.6	∞
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	∞
Response Time	0	Rectangular	$\sqrt{3}$	1	1	0	0	∞
Integration Time	0	Rectangular	$\sqrt{3}$	1	1	0	0	∞
RF Ambient Conditions	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
Probe Positioner	0.4	Rectangular	$\sqrt{3}$	1	1	0.2	0.2	∞
Probe positioning	2.9	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
Algorithms for Max. SAR Evaluation	1.0	Rectangular	$\sqrt{3}$	1	1	0.6	0.6	∞
<b>Dipole</b>								
Dipole Axis to Liquid Distance	2.0	Rectangular	$\sqrt{3}$	1	1	1.2	1.2	∞
Input power and SAR drift measurement	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	∞
<b>Phantom and Tissue Parameters</b>								
Phantom Uncertainty	4.0	Rectangular	$\sqrt{3}$	1	1	2.3	2.3	∞
Liquid Conductivity (target)	5.0	Rectangular	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	2.5	Normal	1	0.64	0.43	1.6	1.1	∞
Liquid Permittivity (target)	5.0	Rectangular	$\sqrt{3}$	0.6	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	2.5	Normal	1	0.6	0.49	1.5	1.2	∞
Combined Standard Uncertainty						8.4	8.1	∞
Coverage Factor for 95%						kp=2		
Expanded Uncertainty (K=2)						16.8	16.2	

**NOTE:** About the system validation uncertainty assessment, please reference the section 7.

## 7. MEASUREMENT SAR PROCEDURE UNCERTAINTIES

The assessment of spatial peak SAR of the hand handheld devices is according to IEEE 1528. All testing situation shall be met below these requirements.

- The system is used by an experienced engineer who follows the manual and the guidelines taught during the training provided by SPEAG.
- The probe has been calibrated within the requested period and the stated uncertainty for the relevant frequency bands does not exceed 4.8% (k=1).
- The validation dipole has been calibrated within the requested period and the system performance check has been successful.
- The DAE unit has been calibrated within the within the requested period.
- The minimum distance between the probe sensor and inner phantom shell is selected to be between 4 and 5mm.
- The operational mode of the DUT is CW, CDMA, FDMA or TDMA (GSM, DCS, PCS, IS136 and PDC) and the measurement/integration time per point is >500 ms.
- The dielectric parameters of the liquid have been assessed using Agilent 85070D dielectric probe kit or a more accurate method.
- The dielectric parameters are within 5% of the target values.
- The DUT has been positioned as described in section 3.

### 7.1. PROBE CALIBRATION UNCERTAINTY

SPEAG conducts the probe calibration in compliance with international and national standards (e.g. IEEE 1528, EN50361, IEC 62209, etc.) under ISO17025. The uncertainties are stated on the calibration certificate. For the most relevant frequency bands, these values do not exceed 4.8% (k=1). If evaluations of other bands are performed for which the uncertainty exceeds these values, the uncertainty tables given in the summary have to be revised accordingly.

## 7.2. ISOTROPY UNCERTAINTY

The axial isotropy tolerance accounts for probe rotation around its axis while the hemispherical isotropy error includes all probe orientations and field polarizations. These parameters are assessed by SPEAG during initial calibration. In 2001, SPEAG further tightened its quality controls and warrants that the maximal deviation from axial isotropy is  $\pm 0.20$ dB, while the maximum deviation of hemispherical isotropy is  $\pm 0.40$ dB, corresponding to  $\pm 4.7\%$  and  $\pm 9.6\%$ , respectively. A weighting factor of  $cp$  equal to 0.5 can be applied, since the axis of the probe deviates less than 30 degrees from the normal surface orientation.

## 7.3. BOUNDARY EFFECT UNCERTAINTY

The effect can be estimated according to the following error approximation formula

$$SAR_{tolerance}[\%] = SAR_{be}[\%] \times \frac{(d_{be} + d_{step})^2}{2d_{step}} \frac{e^{\frac{d_{be}}{d/2}}}{d/2}$$

$$d_{be} + d_{step} < 10\text{mm}$$

The parameter  $d_{be}$  is the distance in mm between the surface and the closest measurement point used in the averaging process;  $d_{step}$  is the separation distance in mm between the first and second measurement points;  $\delta$  is the minimum penetration depth in mm within the head tissue equivalent liquids (i.e.,  $\delta = 13.95$ mm at 3GHz);  $SAR_{be}$  is the deviation between the measured SAR value at the distance  $d_{be}$  from the boundary and the wave-guide analytical value  $SAR_{ref}$ . DASY4 applies a boundary effect compensation algorithm according to IEEE 1528, which is possible since the axis of the probe never deviates more than 30 degrees from the normal surface orientation.  $SAR_{be}[\%]$  is assessed during the calibration process and SPEAG warrants that the uncertainty at distances larger than 4mm is always less than 1%. In summary, the worst case boundary effect SAR tolerance[%] for scanning distances larger than 4mm is  $< \pm 0.8\%$ .

## 7.4. PROBE LINEARITY UNCERTAINTY

Field probe linearity uncertainty includes errors from the assessment and compensation of the diode compression effects for CW and pulsed signals with known duty cycles. This error is assessed using the procedure described in IEEE 1528. For SPEAG field probes, the measured difference between CW and pulsed signals, with pulse frequencies between 10Hz and 1kHz and duty cycles between 1 and 100, is  $< \pm 0.20\text{dB}$  ( $< \pm 4.7\%$ ).

## 7.5. READOUT ELECTRONICS UNCERTAINTY

All uncertainties related to the probe readout electronics (DAE unit), including the gain and linearity of the instrumentation amplifier, its loading effect on the probe, and accuracy of the signal conversion algorithm, have been assessed accordingly to IEEE 1528. The combination (root-sum-square RSS method) of these components results in an overall maximum error of  $\pm 1.0\%$ .

## 7.6. RESPONSE TIME UNCERTAINTY

The time response of the field probes is assessed by exposing the probe to a well-controlled electric field producing SAR larger than 2.0W/kg at the tissue medium surface. The signal response time is evaluated as the time required by the system to reach 90% of the expected final value after an on/of switch of the power source. Analytically, it can be expressed as:

$$\text{SAR}_{tolerance} [\%] = 100 \times \left( \frac{T_m}{T_m + t e^{-T_m/t} - t} - 1 \right)$$

where  $T_m$  is 500 ms, i.e., the time between measurement samples, and  $\tau$  the time constant. The response time  $\tau$  of SPEAG's probes is  $< 5\text{ms}$ . In the current implementation, DASY4 waits longer than 100 ms after having reached the grid point before starting a measurement, i.e., the response time uncertainty is negligible.

## 7.7. INTEGRATION TIME UNCERTAINTY

If the device under test does not emit a CW signal, the integration time applied to measure the electric field at a specific point may introduce additional uncertainties due to the discretization and can be assessed as follows

$$SAR_{tolerance} [\%] = 100 \times \sum_{all sub-frames} \frac{t_{frame}}{t_{integration}} \frac{slot_{idle}}{slot_{total}}$$

The tolerances for the different systems are given in Table 7.1, whereby the worst-case  $SAR_{tolerance}$  is 2.6%.

System	$SAR_{tolerance} \%$
CW	0
CDMA*	0
WCDMA*	0
FDMA	0
IS-136	2.6
PDC	2.6
GSM/DCS/PCS	1.7
DECT	1.9
Worst-Case	2.6

TABLE 7.1

## 7.8. PROBE POSITIONER MECHANICAL TOLERANCE

The mechanical tolerance of the field probe positioner can introduce probe positioning uncertainties. The resulting SAR uncertainty is assessed by comparing the SAR obtained according to the specifications of the probe positioner with respect to the actual position defined by the geometric center of the probe sensors. The tolerance is determined as:

$$SAR_{tolerance}[\%] = 100 \times \frac{d_{ph}}{d/2}$$

The specified repeatability of the RX robot family used in DASY4 systems is  $\pm 25\mu\text{m}$ . The absolute accuracy for short distance movements is better than  $\pm 0.1\text{mm}$ , i.e., the  $SAR_{tolerance}[\%]$  is better than 1.5% (rectangular).

## 7.9. PROBE POSITIONING

The probe positioning procedures affect the tolerance of the separation distance between the probe tip and the phantom surface as:

$$SAR_{tolerance}[\%] = 100 \times \frac{d_{ph}}{d/2}$$

where  $d_{ph}$  is the maximum deviation of the distance between the probe tip and the phantom surface. The optical surface detection has a precision of better than  $0.2\text{mm}$ , resulting in an  $SAR_{tolerance}[\%]$  of  $<2.9\%$  (rectangular distribution). Since the mechanical detection provides better accuracy, 2.9% is a worst-case figure for DASY4 system.

## 7.10. PHANTOM UNCERTAINTY

The SAR measurement uncertainty due to SPEAG phantom shell production tolerances has been evaluated using

$$SAR_{tolerance}[\%] \cong 100 \times \frac{2d}{a}, \quad d \ll a$$

For a maximum deviation  $d$  of the inner and outer shell of the phantom from that specified in the CAD file of  $\pm 0.2\text{mm}$ , and a  $10\text{mm}$  spacing  $a$  between source and tissue liquid, the calculated phantom uncertainty is  $\pm 4.0\%$ .

## 7.11. DASY4 UNCERTAINTY BUDGET (FOR 2.4GHz)

Error Description	Tolerance (±%)	Probability Distribution	Divisor	(C <sub>i</sub> )		Standard Uncertainty (±%)		(v <sub>i</sub> )
				(1g)	(10g)	(1g)	(10g)	
<b>Measurement Equipment</b>								
Probe Calibration	4.8	Normal	1	1	1	4.8	4.8	∞
Axial Isotropy	4.7	Rectangular	√3	1	1	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	√3	1	1	3.9	3.9	∞
Boundary effect	1.0	Rectangular	√3	1	1	0.6	0.6	∞
Linearity	4.7	Rectangular	√3	1	1	2.7	2.7	∞
System Detection Limit	1.0	Rectangular	√3	1	1	0.6	0.6	∞
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	∞
Response Time	0.8	Normal	1	1	1	0.8	0.8	∞
Integration Time	2.6	Normal	1	1	1	2.6	2.6	∞
Noise	0.0	Normal	1	0	0	0	0	∞
<b>Mechanical Constraints</b>								
Scanning System	0.4	Rectangular	√3	1	1	0.2	0.2	∞
Phantom Shell	4.0	Rectangular	√3	1	1	2.3	2.3	∞
Probe Positioning	2.9	Rectangular	√3	1	1	1.7	1.7	∞
Device Positioning	2.9	Normal	1	1	1	2.9	2.9	875
<b>Physical Parameters</b>								
Liquid Conductivity (target)	5.0	Rectangular	√3	0.7	0.5	2	1.4	∞
Liquid Conductivity (measurement)	4.3	Rectangular	√3	0.7	0.5	1.7	1.2	∞
Liquid Permittivity (target)	5.0	Rectangular	√3	0.6	0.5	1.7	1.4	∞
Liquid Permittivity (measurement)	4.3	Rectangular	√3	0.6	0.5	1.5	1.2	∞
Power Drift	5	Rectangular	√3	1	1	2.9	2.9	∞
RF Ambient Conditions	3.0	Rectangular	√3	1	1	1.7	1.7	∞
<b>Post-Processing</b>								
Extrapolation and Integration	1	Rectangular	√3	1	1	0.6	0.6	∞
<b>Combined Standard Uncertainty</b>						<b>9.9</b>	<b>9.7</b>	
<b>Coverage Factor for 95%</b>						<b>kp=2</b>		
<b>Expanded Uncertainty (K=2)</b>						<b>19.9</b>	<b>19.3</b>	

TABLE 7.2

The table 7.2: Worst-Case uncertainty budget for DASY4 assessed according to IEEE 1528. The budget is valid for the frequency range 300MHz ~ 3GHz and represents a worst-case analysis. For specific tests and configurations, the uncertainty could be considerably smaller.



## 7.12.DASY4 UNCERTAINTY BUDGET (FOR 5 ~ 6GHz)

Error Description	Tolerance (±%)	Probability Distribution	Divisor	(C <sub>i</sub> )		Standard Uncertainty (±%)		(v <sub>i</sub> )
				(1g)	(10g)	(1g)	(10g)	
<b>Measurement System</b>								
Probe Calibration	6.8	Normal	1	1	1	6.8	6.8	∞
Axial Isotropy	4.7	Rectangular	$\sqrt{3}$	0.7	0.7	1.9	1.9	∞
Hemispherical Isotropy	9.6	Rectangular	$\sqrt{3}$	0.7	0.7	3.9	3.9	∞
Boundary effect	2.0	Rectangular	$\sqrt{3}$	1	1	1.2	1.2	∞
Linearity	4.7	Rectangular	$\sqrt{3}$	1	1	2.7	2.7	∞
System Detection Limit	1.0	Rectangular	$\sqrt{3}$	1	1	0.6	0.6	∞
Readout Electronics	1.0	Normal	1	1	1	1.0	1.0	∞
Response Time	0.8	Rectangular	$\sqrt{3}$	1	1	0.5	0.5	∞
Integration Time	2.6	Rectangular	$\sqrt{3}$	1	1	1.5	1.5	∞
RF Ambient Conditions	3.0	Rectangular	$\sqrt{3}$	1	1	1.7	1.7	∞
Probe Positioner	0.8	Rectangular	$\sqrt{3}$	1	1	0.5	0.5	∞
Probe positioning	5.7	Normal	1	1	1	5.7	5.7	∞
Algorithms for Max. SAR Evaluation	4.0	Rectangular	$\sqrt{3}$	1	1	2.3	2.3	∞
<b>Test EUT Related</b>								
Device Positioning	2.9	Normal	1	1	1	2.9	2.9	145
Device Holder	3.6	Normal	1	1	1	3.6	3.6	5
Power Drift	5.0	Rectangular	$\sqrt{3}$	1	1	2.9	2.9	∞
<b>Phantom and Tissue Parameters</b>								
Phantom Uncertainty	4.0	Rectangular	$\sqrt{3}$	1	1	2.3	2.3	∞
Liquid Conductivity (target)	5.0	Rectangular	$\sqrt{3}$	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	2.5	Normal	1	0.64	0.43	1.6	1.1	∞
Liquid Permittivity (target)	5.0	Rectangular	$\sqrt{3}$	0.60	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	2.5	Normal	1	0.60	0.49	1.5	1.2	∞
<b>Combined Standard Uncertainty</b>						12.8	12.7	330
<b>Expanded STD Uncertainty</b>						25.7	25.3	

TABLE 7.3

The table 7.3: Worst-Case uncertainty budget for DASY4 valid for the frequency range 5 ~ 6 GHz. Probe calibration error reflects uncertainty of the narrow-bandwidth EX3DV3 probe conversion factor (±50 MHz).



## 8. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

<b>USA</b>	FCC, UL, A2LA
<b>GERMANY</b>	TUV Rheinland
<b>JAPAN</b>	VCCI
<b>NORWAY</b>	NEMKO
<b>CANADA</b>	INDUSTRY CANADA , CSA
<b>R.O.C.</b>	TAF, BSMI, NCC
<b>NETHERLANDS</b>	Telefication
<b>SINGAPORE</b>	PSB , GOST-ASIA (MOU)
<b>RUSSIA</b>	CERTIS (MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180  
Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab:**

Tel: 886-3-3183232  
Fax: 886-3-3185050

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.